

US007010887B2

(12) **United States Patent**
Walters

(10) **Patent No.:** **US 7,010,887 B2**
(45) **Date of Patent:** **Mar. 14, 2006**

(54) **MOUNTING STRUCTURE AND METHOD
FOR ARCUATE GUTTER TROUGHS**

(75) Inventor: **A. B. Walters**, Georgetown, TX (US)

(73) Assignee: **Senox Corporation**, Austin, TX (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/117,755**

(22) Filed: **Apr. 5, 2002**

(65) **Prior Publication Data**

US 2003/0188493 A1 Oct. 9, 2003

(51) **Int. Cl.**
E04D 13/00 (2006.01)

(52) **U.S. Cl.** **52/11; 248/48.2**

(58) **Field of Classification Search** 52/11,
52/12, 15; 248/48.2, 18.2
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

836,012	A *	11/1906	Cassen	
1,803,154	A *	4/1931	Vail	
2,271,081	A *	1/1942	Layton	
3,067,881	A *	12/1962	Goosmann	
3,333,803	A *	8/1967	Landis	
5,575,118	A *	11/1996	Vahldieck	52/11
5,706,608	A *	1/1998	Sweet	52/11
6,493,993	B1 *	12/2002	Serano	52/12

* cited by examiner

Primary Examiner—Carl D. Friedman

Assistant Examiner—Yvonne M. Horton

(74) *Attorney, Agent, or Firm*—Andrews Kurth LLP; J.
Scott Denko

(57) **ABSTRACT**

The present invention provides an apparatus and methods
for curved troughs used in gutter systems. An arcuate trough
is formed with a mounting structure that employs two folds,
with one fold disposed between the other fold and the outer
surface of the trough.

7 Claims, 6 Drawing Sheets






Fig. 1



PRIOR ART

Fig. 2



PRIOR ART




Fig. 4




Fig. 5





Fig. 6



1

**MOUNTING STRUCTURE AND METHOD
FOR ARCUATE GUTTER TROUGHS****TECHNICAL FIELD**

The present invention relates to rain and run-off collection and diversion systems and, in particular, to rain collection trough designs.

BACKGROUND OF THE INVENTION

Diversion of rain from buildings is a well-known and beneficial practice. For centuries, architects and builders have understood the benefits of diverting rain to forestall erosion, maintain structural stability, and preserve vegetation. In recent decades, a multitude of systems have been developed to divert rain from structures and homes. Typically, such systems have been placed beneath or adjacent to the roofline to allow collection and diversion of rain accumulated from across the surface area of the structure roof. Such systems are sometimes called "gutter" systems.

Typical gutter systems employ a trough structure that is either open along its length or covered by a deflector or hood to inhibit the collection of debris that would otherwise be swept into the system by the collected water. Gutter system troughs often exhibit a cross-sectional shape known as the "o-gee" (i.e., "OG"). Other gutter systems may employ troughs that are arcuate in shape with what is known as "half-round" being a common shape for such arcuate troughs.

When bearing the weight of accumulated water, arcuate troughs and, in particular, half-round troughs are less stable than the OG style trough. An OG trough has a flattened backside that supports the weight of accumulated water. In contrast, a trough with a curved back wall area contacts a small area of the fascia board or other mounting surface of the building from which runoff is collected. Consequently, the force of the accumulated water weight is concentrated in a smaller area. Typically, most of the weight of a curved trough is borne at the site of attachment or, specifically, around the location where the mounting fastener penetrates the back wall of the trough. This is particularly true where the back mounting area of the trough is curved and lacks the flat rear mounting surface of an OG. In a trough with a curved mounting area, over time, the trough will tend to sag and may even pull from the fascia board or other mounting surface to which it has been attached. These structural instabilities arise from the shape of arcuate troughs employed in gutter and rain collection systems.

What is needed therefore is an arcuate trough design that contemplates the loads imposed by the weight of water accumulated in the trough and provides added stability and load bearing capacity while retaining the aspect of curvature preferred by same.

SUMMARY OF THE INVENTION

The present invention provides an apparatus and methods for curved troughs used in gutter systems. An arcuate trough is formed with a mounting structure that employs two folds, with one fold disposed between the other fold and the outer surface of the trough.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 depicts a prior art arcuate trough typically employed in gutter systems.

2

FIG. 2 depicts a prior art mounting area for the prior art trough of FIG. 1.

FIG. 3 depicts a preferred embodiment of the present invention.

FIG. 4 depicts a preferred embodiment of the present invention.

FIG. 5 depicts a preferred embodiment of a mounting structure employed in a preferred embodiment of the present invention.

FIG. 6 illustrates, in a preferred embodiment, a first step in formation of a preferred mounting structure in accordance with the present invention.

**DESCRIPTION OF PREFERRED
EMBODIMENTS**

The term "arcuate" is to be understood to mean curved. For example, many gutter troughs are fashioned in what is called in the trade a "half-round" style. This is but one example of an arcuate trough. Other gutter troughs where the trough perimeter is curved in the mounting area of the trough should also be considered within the general category of arcuate troughs.

FIG. 1 depicts a prior art half-round trough **10** composed of trough material **11** shaped to have a rear lip **12** in a mounting area **14** and a front lip **16**. Mounting area **14** of trough **10** is depicted in enlargement in FIG. 2. As shown, rear lip **12** is devised by folding over trough material **11** to create a double thickness mount field **20**. A fastener then passes through mount field **20** to attach trough **10** to the building from which runoff is diverted. The fold is either inward toward the inside of the trough as shown or outward against the backside of the trough. In practice, although creation of a mount field **20** by folding trough material **11** over to double the material thickness at the point of attachment provides some added strength, it does not prevent sagging. Trough **10** will typically exhibit a tendency to sag or shift as, over time, the weight of borne water pulls the structure downward with more force than the mechanics of the trough mounting can reliably bear. As those of skill in the field recognize, the problem of weight-caused sag becomes more acute in larger troughs as the mechanical level arm through which the weight is applied increases downward forces.

FIGS. 3 and 4 depict a preferred embodiment of the present invention. In depicted trough **30** comprised from trough material **11**, a mounting structure **32** is depicted in accordance with the present invention. Mounting structure **32** exhibits at least two folds. A first (or outer) fold **34** in trough material **11** is imposed by bending trough material **11** at the upper extent of mounting structure **32** and a second (or inner) fold **36** is imposed at a lower extent of mounting structure **32** to create mounting field **20** on the backside of trough **30**. Those of skill will recognize that folds **34** and **36** may be creases, folds, or bends or similar impositions on material **11**. This creates a double metal layer (depicted by reference A) consisting of the thicknesses of the metal trough material of trough **30** and outer fold **34** and a triple metal layer (depicted by reference B) comprised of the thicknesses of the trough material, outer fold **34** and inner fold **36**. This also creates, in a preferred embodiment, gap **38** which is an optional feature of the present invention. The front containment wall border area of trough **30** of FIG. 3 is depicted with an inwardly projecting containment shelf **39** that is described in co-pending U.S. application Ser. No. 09/880,412 owned by the assignee of the present invention.

3

The entire extent of mounting field **20** need not rest against the building from which runoff is collected. The assignee of the present invention has used an aluminum alloy as well as copper-based metals for trough material **11** but as those in the field will understand, other materials may be employed to advantage with the present invention.

In a preferred embodiment, outer fold **34** extends from apex **33** to apex **35** of inner fold **36** while inner fold **36** extends from apex **35** to its end **37**. To preserve clarity in the figures, end **37** of inner fold **36** is shown in FIG. 6.

There are several sizes of half-round gutter trough available. For example, the assignee of the present invention offers 6" half-round troughs. These and other sizes of troughs may be fabricated in conformity with the present invention using standard sized materials (i.e., coil stock of approximately 11 and $\frac{7}{8}$ inches in width in the Western U.S. and 11 and $\frac{3}{4}$ inches in parts of the Eastern U.S.). The use of standard sized materials with the present invention is of significant advantage in fabrication and cost administration.

FIG. 5 depicts a preferred mounting structure **32** penetrated by fastener **40** which may be a screw, nail, spike or other similar fastening device. Fastener **40** passes below the apex **33** of outer fold **34** and above apex **35** of inner fold **36**.

FIG. 6 illustrates, in a preferred embodiment, a first step in formation of mounting structure **32** in accordance with the present invention. In the preferred embodiment of the method, inner fold **36** is created first by folding over trough material **11** to the outside surface **39** of the trough. It should be understood that the process of forming a trough in accordance with the present invention may be implemented in a forming machine devised to impose the appropriate folds or bends in the proper sequence. Such forming machinery will generally also simultaneously form the trough itself.

Inner fold **36**, in a preferred embodiment, doubles over approximately 0.200" of trough material **11** as measured from apex **35** of inner fold **36** to the end **37** of inner fold **36**. Inner fold **36** may double over between 0.050" and 0.250" of material with a fold over of 0.200" being found to be preferable in light of the constraints of using standard sized materials in fabrication of trough **30**. Then preferably, approximately 1.0 inches below apex **35** of inner fold **36**, trough material **11** is then bent over again to create outer fold **34**. This is a preferred process for creating the double layer A and triple layer B. The recited dimensions have been found to be preferable by the assignee of the present invention to allow standard sized materials to be employed in the configuration of embodiments of the present invention. Those of skill in the field will note however, that other relative dimensions for folds **34** and **36** will also provide

4

satisfactory results and mounting field **20** extending between apex **33** and apex **35** may, for example, be between $\frac{1}{2}$ and 4 inches in extent from apex **33** and apex **35** and still use standard materials. Some may prefer to use specialized materials for fabrication of trough **30** and in those cases, mounting field **20** may exceed the range of between $\frac{1}{2}$ and 4 inches from apex **33** of fold **34** to apex **35** of fold **36**.

Although the present invention has been described in detail, it will be apparent to those skilled in the art that the invention may be embodied in a variety of specific forms and that various changes, substitutions and alterations can be made without departing from the spirit and scope of the invention. The described embodiments are only illustrative and not restrictive and the scope of the invention is, therefore, indicated by the following claims.

I claim:

1. An arcuate trough employed in rain diversion systems, the trough comprising:

an inside surface and an outside surface;

metallic material; and

a mounting structure integral with the trough and formed of metallic material, the mounting structure comprising:

an inner fold of metallic material,

an outer fold of metallic material, the outer fold extending from an apex corresponding to the outer fold to an apex corresponding to the inner fold the inner fold being disposed between the outer fold and the outside surface of the trough, the inner fold of metallic material and the outer fold of metallic material forming a double metal layer.

2. The trough of claim 1 in which a fastener penetrates the mounting structure between the apex corresponding to the inner fold and the apex corresponding to the outer fold.

3. The trough of claim 1 in which the metallic material is aluminum alloy.

4. The trough of claim 1 in which the metallic material is copper.

5. The trough of claim 1 in which the trough is half-round.

6. The trough of claim 1 in which the inner fold extends a distance from the apex corresponding to the inner fold to the end of the inner fold, the distance being in the range of between 0.050 and 0.250 inches.

7. The trough of claim 1 in which the outer fold extends a distance from the apex corresponding to the outer fold to the apex corresponding to the inner fold, the distance being in the range of between $\frac{1}{2}$ and 4 inches.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,010,887 B2
APPLICATION NO. : 10/117755
DATED : March 14, 2006
INVENTOR(S) : A. B. Walters

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On the cover page, item (73), the Assignee "Senox Corpration" should read --Senox Corporation--.

Signed and Sealed this
Seventh Day of August, 2012

A handwritten signature in black ink, reading "David J. Kappos". The signature is written in a cursive, flowing style with a large initial 'D' and 'K'.

David J. Kappos
Director of the United States Patent and Trademark Office