

US007056376B2

(12) United States Patent

Popat et al.

(10) Patent No.: US 7,056,376 B2

(45) **Date of Patent:** Jun. 6, 2006

(54) PRINTING PROCESS USING SPECIFIED AZO COMPOUNDS

(75) Inventors: Ajay Haridas Popat, Manchester (GB);

Alan Dickinson, Grangemouth (GB); Maria Soteri Hadjisoteriou, Manchester (GB); Neil James Thompson, Manchester (GB); Paul Wight, Manchester (GB); Peter Gregory, Bolton (GB); Roy Bradbury, Manchester (GB); Philip John Double,

Manchester (GB); Thomas Paul,

Manchester (GB)

Wianchester (OD)

(73) Assignee: Avecia Limited, Manchester (GB)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 89 days.

(21) Appl. No.: 10/411,327

(22) Filed: **Apr. 11, 2003**

(65) Prior Publication Data

US 2004/0020404 A1 Feb. 5, 2004

(30) Foreign Application Priority Data

Jun. 13, 2002	(GB)		0213573
Jun. 13, 2002	(GB)		0213578
Aug. 7, 2002	(GB)		0218292
Oct. 2, 2002	(GB)	•••••	0222740

(51) **Int. Cl.**

C09D 11/00 (2006.01) **C09B** 35/378 (2006.01)

534/814, 716 See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

1,209,154	A	12/1916	Haugwitz 534/678
1,235,253	A *	9/1917	Stebbins, Jr 534/813
4,426,226	A	1/1984	Ohta et al 106/31.52
5,536,819	A *	7/1996	Tamura et al 106/31.52
6,075,131	A *	6/2000	Tallant et al 534/659
6,451,989	B1*	9/2002	Beach et al 534/728
6,503,308	B1*	1/2003	Stramel et al 106/31.27
6,749,674	B1*	6/2004	Geisenberger et al 106/31.52
6,858,069	B1*	2/2005	Aoyama et al 106/31.52
2004/0040466	A1*	3/2004	Aoyama et al 106/31.52
2005/0076806	A1*	4/2005	Hanmura et al 106/31.48
2005/0126435	A1*	6/2005	Hanmura et al 106/31.46

FOREIGN PATENT DOCUMENTS

EP	0 347 803 A2	12/1989
EP	0 539 178 A2	4/1993
EP	0 979 847 A1	2/2000
GB	774612	5/1957
JP	59-075965	4/1984

^{*} cited by examiner

Primary Examiner—Helene Klemanski (74) Attorney, Agent, or Firm—Morgan, Lewis & Bockius, LLP

(57) ABSTRACT

A process for printing an image on a substrate comprising applying thereto a composition comprising a liquid medium and a compound of Formula (1):

T-Q-N=N-L-T Formula (1)

wherein:

each T independently is an azo group;

Q is an optionally substituted, optionally metallised 1,8-dihydroxynaphthyl group; and

L is a divalent organic linker group.

Also claimed are compositions and dyes.

24 Claims, No Drawings

PRINTING PROCESS USING SPECIFIED AZO COMPOUNDS

This invention relates to a printing process, to compounds and processes for their manufacture, to compositions 5 derived therefrom, to cartridges, to printed substrates and to ink sets. Ink jet printing ("IJP"), is a non-impact printing technique in which droplets of ink are ejected through a fine nozzle onto a substrate without bringing the nozzle into contact with the substrate.

There are many demanding performance requirements for dyes and inks used in IJP. For example they desirably provide sharp, non-feathered images having good water-fastness, light-fastness and optical density. The inks are often required to dry quickly when applied to a substrate to 15 prevent smudging, but they should not form a crust over the tip of ink jet nozzles because this will stop the printer from working. The inks should also be stable to storage over time without decomposing or forming a precipitate which could block the fine nozzles.

Direct Black 38 and Direct Black 19 are known colorants for ink jet printing. These dyes comprise a 1-amino-8-hydroxynaphthalene unit.

GB 774,612 describes certain blue to bluish red dyes comprising a 1,8-dihydroxynaphthalene group carrying a 25 tris-azo group on one side only. These dyes are used for the conventional dyeing of leather.

U.S. Pat. No. 1,209,154 describes violet dyes for cotton containing a 1,8-dihydroxynaphthalene group carrying a tris-azo group on one side only.

Surprisingly it has been found that certain compounds comprising twice-coupled 1,8-dihydroxynaphthalene have outstanding properties as ink jet inks.

According to the present invention there is provided a process for printing an image on a substrate comprising 35 applying thereto a composition comprising a liquid medium and a compound of Formula (1):

T-Q-N=N-L-T Formula (1)

wherein:

each T independently is an azo group;

Q is an optionally substituted, optionally metallised 1,8-dihydroxynaphthyl group; and

L is a divalent organic linker group.

Preferably the composition is applied to the substrate by means of an ink jet printer. The ink let printer preferably applies the composition to the substrate in the form of droplets which are ejected through a small orifice onto the substrate. Preferred ink jet printers are piezoelectric ink jet printers and thermal ink jet printers. In thermal ink jet printers, programmed pulses of heat are applied to the composition in a reservoir by means of a resistor adjacent to the orifice, thereby causing the composition to be ejected in the form of small droplets directed towards the substrate 55 during relative movement between the substrate and the orifice. In piezoelectric ink jet printers the oscillation of a small crystal causes ejection of the composition from the orifice.

The substrate is preferably paper, plastic, a textile, metal or glass, more preferably a treated substrate such as a coated paper or coated plastic, especially coated paper.

Preferred plain or treated papers are papers which may have an acid, alkaline or neutral character. Examples of commercially available treated papers include HP Premium 65 Coated PaperTM, HP PhotopaperTM, HP Printing Paper, HP new and improved Premium Plus photopaper all available

2

from Hewlett Packard Inc.); Stylus Pro 720 dpi Coated PaperTM, Epson Photo Quality Glossy FilmTM, Epson Photo Quality Glossy PaperTM, Epson Premium Photo PaperTM (all available from Seiko Epson Corp.); Canon HR 101 High 5 Resolution PaperTM, Canon GP 201 Glossy PaperTM, Canon HG 101 and HG201 High Gloss FilmTM, Canon PR 101TM (all available from Canon); Kodak Premium PhotopaperTM, Kodak Premium InkJetpaperTM (available from Kodak); Konica Inkjet Paper QPTM Professional Photo Glossy, Konica Inkjet Paper QPTM Premium Photo Glossy, Konica Inkjet Paper QPTM Premium Photo Glossy, Konica Inkjet Paper QPTM Premium Photo SilkyTM (available from Konica); Ilford Instant Dry PaperTM (available from Ilford).

Preferably the compound of Formula (1) carries at least 2 water-solubilising groups, e.g. sulpho groups, more preferably 2 to 10 sulpho groups, especially 2 to 6 sulpho groups. In various embodiments the compound of Formula (1) carries 2, 3, 4, 5, 6, 7, 8, 9 or 10 sulpho groups.

Preferred azo groups represented by T comprise an azo link of formula —N=N— connected to a group comprising a double bond, preferably a carbon-carbon double bond. More preferred azo groups represented by T are of the formula A-N=N— wherein each A independently is an optionally substituted aryl, heteroaryl, non-aromatic heterocyclic or an alkenyl group.

Preferred optionally substituted aryl groups represented by A are optionally substituted phenyl and naphthyl. Preferred optionally substituted heteroaryl groups and nonaromatic heterocyclic groups represented by A are any heterocycle or substituted heterocycle comprising a 5 to 7 membered ring, preferably comprising at least one double bond.

Preferred optionally substituted alkenyl groups are of the Formula (2):

Formula (2)

$$Y$$
 Y^1
 X^1

wherein:

Y is an electron withdrawing group;

Y¹ is H, alkyl or aryl, OR or N(R)₂ in which each R independently is H, optionally substituted alkyl or optionally substituted aryl; or,

Y and Y¹ together with the double bond shown above form a 5- or 6-membered ring; and

X¹ comprises at least one heteroatom selected from N, O and S.

Y is preferably selected from CN, CO_2H , CO_2R , $CON(R)_2$, COR and $-SO_2N(R)_2$ in which each R is independently defined as above. When R is optionally substituted alkyl it is preferably C_{1-8} -alkyl, more preferably C_{1-4} -alkyl. When R is optionally substituted aryl it is preferably phenyl or naphthyl, more preferably phenyl. When R is optionally substituted alkyl or aryl optional substituents are preferably selected from water solubilising groups, particularly SO_3H , $SO_2N(R)_2$, CO_2H or PO_3H_2 .

When Y^1 is alkyl it is preferably C_{1-8} -alkyl, more preferably C_{1-4} -alkyl. When Y^1 is aryl it is preferably phenyl. When Y and Y^1 are joined together to form a 5- or 6-mem-

bered ring it is preferably an optionally substituted pyrazolone or triazole ring, more preferably pyrazolone or 1,3, 4-triazole.

X¹ is preferably O, CO₂R or NR in which R is defined above.

More preferably Y is CO_2R^1 , Y¹ is OR^1 and X¹ is OR^1 wherein each R^1 independently is H or C_{1-4} -alkyl.

Optional substituents which may be present on A and L (including L¹ and L²) are preferably selected from OH, ¹⁰ SO₃H, PO₃H₂, CO₂H, NO₂, NH₂, optionally substituted alkyl (especially C_{1-4} -alkyl optionally carrying a sulpho, carboxy, phosphato C_{1-4} -alkoxy, amino or hydroxy group), optionally substituted alkoxy (especially C_{1-4} -alkoxy ₁₅ complex thereof; optionally carrying a sulpho, carboxy, phosphate, C_{1-4} alkoxy, C_{1-4} -alkyl, amino or hydroxy group), optionally substituted amine (especially N carrying one or two C_{1-4} alkyl groups optionally carrying a sulpho, carboxy, phosphate, C_{1-4} -alkoxy, amino or hydroxy group), optionally 20 substituted acylamine (especially C_{1-4} -acylamino) and optionally substituted azo (especially phenylazo, naphthylazo and heteroarylazo where the phenyl, naphthyl and heteroaryl units are optionally further substituted with one or 25 more groups selected from OH, SO₃H, PO₃H₂, CO₂H, NO₂ and NH₂, and azo groups comprising Formula (2) as hereinbefore defined).

Preferably each A and L independently carries from 0 to 3 substituents, more preferably 1 or 2 substituents.

Preferably at least one group represented by A carries at least one sulpho group. In a further preferred embodiment, both groups represented by A carry at least one sulpho group. In another preferred embodiment, at least one group 35 represented by A carries at least one optionally substituted amino or acylamino group.

As examples of optionally substituted phenyl and naphthyl groups represented by A there may be mentioned 2-sulfo-4-aminophenyl, 2-sulfo-4-nitrophenyl, 2-hydroxy-4-aminophenyl and 1-hydroxy-3-sulpho-6-aminonaphthyl. Preferred optionally substituted heteroaryl groups represented by A are any heterocycle or substituted heterocycle comprising a 5 to 7 membered ring, more preferably option-45 ally substituted pyridyl, pyrazolyl or 1,2,4-triazole.

Q is preferably optionally substituted 1,8-dihydroxynaph-thylene, i.e. unmetallised.

Preferably Q is of Formula (3) or a metal complex thereof; 50

wherein a is 1 or 2 and SO₃H is in free acid or salt form. Preferably a is 2 and the SO₃H groups shown in Formula (3) are in the 3- and 6-positions or the 3- and 5-positions.

In a preferred aspect of the invention, Q is of Formula (4) or a metal complex thereof:

Formula (4)

OH

OH

OH

OH

SOLU

More preferably Q is of Formula (5) or (6) or a metal complex thereof;

Formula (5)

HO₃S

SO₃H

In this specification any groups shown in the free acid form are also include the salt form; for example in Formulae (3), (4), (5) and (6) the SO₃H groups include the free acid and salt forms. Furthermore the formulae shown in this specification cover all tautomers thereof.

Preferably L is or comprises one or more arylene groups, more preferably one or two optionally substituted phenylene or naphthylene groups. When L is or comprises more than one arylene group, the said arylene groups are optionally connected by means of a covalent bond or group containing from 1 to 10 atoms selected from O, S, N, C, H and combinations thereof, for example —O—, —NR²—, —N=N—, —NR²—CO—, —NR²CONR²—, —S—, —SO—, —SO₂—, —SO₂NR²— or —CR²=CR²—, wherein each R² independently is H or C₁₋₄-alkyl.

Particularly preferred groups represented by L are of Formula (7):

$$-L^{1}(-G-L^{2})_{x}$$
-Formula (7)

wherein:

- L¹ is a single covalent bond or optionally substituted phenyl or naphthyl;
- L² is optionally substituted phenyl or naphthyl;
- G is —O—, —NR²—, —N=N—, —NR²—CO—, —NR²CONR²—, —S—, —SO—, —SO₂—, —SO₂NR²— or —CR²=CR²—, wherein each R² independently is H or C_{1-4} -alkyl; and

5

X is 0, 1 or 2.

In one embodiment of the invention, L carries at least one substituent of the formula $-O-(CH_2)_{1-4}-OH$.

In a further one embodiment of the invention L is free $_{5}$ from substituents of the formula —O—(CH₂)₁₋₄—OH.

In a yet further one embodiment of the invention L carries at least one sulpho group.

In a yet further one embodiment of the invention L is free from sulpho groups.

As examples of optionally substituted phenylene and ¹⁵ naphthylene groups represented by L there may be mentioned 2-sulphophenylene and 2,5-di(2-hydroxyethyloxy) phenylene.

When Q is a metallised 1,8-dihydroxynaphthylene group (i.e. a metal complex) the metal is preferably B or a transition metal, more preferably Mn, Fe, Cr, Co, Ni, Cu or Zn, especially Co, Ni or Cu. The metal may be complexed with the compound of Formula (1) in a ratio of from 1:2 to 2:1, preferably in a ratio of metal to compound of Formula (1) of 1:2, 2:3, 1:1, 2:2 or 2:1, especially 2.1. However we have found that when Q is not metallised the compound of Formula (1) is still a valuable colorant for ink jet printing. Such unmetallised dyes are cheaper and easier to make than the corresponding metallised dyes and they are more environmentally friendly due to the absence of, for example, transition metals.

In view of the foregoing preferences the compound of Formula (1) is preferably as follows:

T is A-N=N—

each A independently is optionally substituted phenyl, naphthyl, pyridyl or pyrazolyl;

Q is of Formula (5) or (6) or a metal complex thereof:

6

Formula (5)

$$_{\mathrm{HO_{3}S}}^{\mathrm{OH}}$$
 $_{\mathrm{SO_{3}H}}^{\mathrm{OH}}$

L is of Formula (7):

HO₃S

$$-L^{1}(-G-L^{2})_{x}-$$
 Formula (7)

wherein:

40

L¹ is a single covalent bond or optionally substituted phenyl or naphthyl;

L² is optionally substituted phenyl or naphthyl;

 SO_3H

X is 0, 1 or 2;

with the proviso that at least one of the groups represented by T comprises a water solubilising group selected from sulpho, phosphato and carboxy.

In one preferred embodiment of the invention, the compound of Formula (1) is of Formula (8) or a salt thereof:

Formula (8)

In a further preferred embodiment of the invention, the compound of Formula (1) is of Formula (9) or a salt thereof:

8 leneglycols, preferably diethylene glycol, triethylene glycol, polyethylene glycol and polypropylene glycol; triols, pref-

Formula (9)

Preferably the compound of Formula (1) is black.

The composition used in the process preferably comprises:

- (a) from 0.01 to 30 parts of a compound of Formula (1) 25 or salt thereof; and
- (b) from 70 to 99.99 parts of a liquid medium or a low melting point solid medium;

wherein all parts are by weight and the number of parts of (a)+(b)=100.

The aforementioned composition, and indeed compositions in general comprising a liquid medium and a compound of Formula (1), form a second aspect of the invention.

The number of parts of component (a) is preferably from 0.1 to 20, more preferably from 0.5 to 15, further preferably from 1 to 10 and especially from 1 to 5 parts. The number of parts of component (b) is preferably from 99.9 to 80, more preferably from 99.5 to 85, further preferably from 99 to 90 and especially from 99 to 95 parts.

When the medium is a liquid, preferably component (a) is completely dissolved in component (b). Preferably component (a) has a solubility in component (b) at 20° C. of at least 10%. This allows the preparation of liquid dye concentrates which may be used to prepare inks and reduces the chance 45 of the dye precipitating if evaporation of the liquid medium occurs during storage.

Preferred liquid media include water or a mixture of water and an organic solvent.

When the liquid medium comprises a mixture of water 50 and an organic solvent, the weight ratio of water to organic solvent is preferably from 99:1 to 1:99, more preferably from 99:1 to 50:50 and especially from 95:5 to 80:20.

It is preferred that the organic solvent present in the mixture of water and organic solvent is a water-miscible 55 organic solvent or a mixture of such solvents. Preferred water-miscible organic solvents include C₁₋₆-alkanols, preferably methanol, ethanol, n-propanol, isoprapanol, n-butanol, sec-butanol, tert-butanol, n-pentanol, cyclopentanol and cyclohexanol; linear amides, preferably dimethylformamide or dimethylacetamide; ketones and ketone-alcohols, preferably acetone, methyl ether ketone, cyclohexanone and diacetone alcohol; water-miscible ethers, preferably tetrahydrofuran and dioxane; diols, preferably diols having from 2 to 12 carbon atoms, for example pentane-1,5-diol, ethylene 65 glycol, propylene glycol, butylene glycol, pentylene glycol, hexylene glycol and thiodiglycol and oligo- and poly-alky-

erably glycerol and 1,2,6-hexanetriol; mono-C₁₋₄-alkyl ethers of diols, preferably mono-C₁₋₄-alkyl ethers of diols having 2 to 12 carbon atoms, especially 2-methoxyethanol, 2-(2-methoxyethoxy)ethanol, 2-(2ethoxyethoxy)ethanol, 2-[2-(2-methoxyethoxy)ethoxy]ethanol, 2-[2-(2-ethoxyethoxy)-ethoxy]-ethanol and ethyleneglycol monoallylether; cyclic amides, preferably 2-pyrrolidone, N-methyl-2-pyrrolidone, N-ethyl-2-pyrrolidone, caprolactam and 1,3-dimethylimidazolidone; cyclic, esters, preferably caprolactone; sulphoxides, preferably dimethyl sulphoxide and sulpholane. Preferably the liquid medium comprises water and 2 or more, especially from 2 to 8, water-soluble organic solvents.

Especially preferred water-soluble organic solvents are cyclic amides, especially 2-pyrrolidone, N-methyl-pyrrolidone and N-ethyl-pyrrolidone; diols, especially 1,5-pentane diol, ethyleneglycol, thiodiglycol, diethyleneglycol and triethyleneglycol; and mono- C_{1-4} -alkyl and C_{1-4} -alkyl ethers of diols, more preferably mono C_{1-4} -alkyl ethers of diols having 2 to 12 carbon atoms, especially ((2-methoxy-2)-ethoxy)-2-ethoxyethanol.

In one embodiment, the liquid medium comprises an oxidant. This is particularly preferred for compositions wherein the group T in the compound of Formula (1) comprises a pyrazolyl group. We have found that the presence of an oxidant in the liquid medium further improves the stability of the composition. Preferred oxidants include KIO₃, KIO₄, K₂S₂O₈, 1,4-benzoquinone, tetrachloro benzoquinone and mixtures thereof.

Preferred low melting solid media have a melting point in the range from 60° C. to 125° C. Suitable low melting point solids include long chain fatty acids or alcohols, preferably those with C_{18-24} chains, and sulphonamides. The compound of Formula (1) may be dissolved in the low melting point solid or may be finely dispersed in it.

The pH of the composition is preferably from 4 to 11, more preferably from 7 to 10. The desired pH may be obtained by the addition of a pH-adjusting agent such as an acid, base or pH buffer. The amount of pH adjusting agent used will vary according to the desired pH of the ink and is preferably present in an amount of up to 10% by wt of the total composition, more preferably from 0.1 to 6% by wt of the total composition. Preferred pH adjusting agents are pH buffers, more preferably pH buffers which maintain a pH of 4 to 8. In one preferred embodiment, the composition

comprises a pH buffer and has a pH of 4 to 8. This is particularly preferred for compositions wherein the group T in the compound of Formula (1) comprises a pyrazolyl moiety. Especially preferred are pH buffers selected from the comprising TRIS (tris(hydroxymethyl)amigroup nomethane), cationic primary aliphatic amines, zwitterionic amino acids (these last two categories being known to those in the art as "Good's buffers" described by N. E. Good et. al. in Biochemistry, 1966, 5(2) 467–477, herein incorporated by reference), phosphate buffers, amino-hydroxyalkylsulfonic acid zwitterions (such as those described in U.S. Pat. No. 4,169,950 herein incorporated by reference) and trishydroxymethylaminomethane derivatives. Examples of suitable pH buffers include 1,3-bis[tris(hydroxymethyl)methy-N-tris(hydroxymethyl)methyl-2lamino propane, aminoethanesulfonic acid, 2-(N-morpholino)ethanesulfonic N-(2-hydroxyethyl)piperazine-N'-(2-ethanesulfonic acid), 4-(N-morpholino)butanesulfonic acid, 3-[N,N-bis(2hydroxyethyl)-amino]-2-hydroxypropanesulfonic acid, tris (hydroxymethyl)aminomethane, N-(2-acetamido)-2-iminodiacetic acid, N-tris(hydroxymethyl)methylglycine, N-(2hydroxy-ethyl)piperazine-N'-(2-hydroxypropanesulfonic acid, N,N-diethylanthranilic acid and NaH₂PO₄.

The viscosity of the composition at 25° C. is preferably less than 50 cP, more preferably less than 20 cP and especially less than 5 cP.

When the compositions according to the invention are used as ink jet printing compositions, the composition preferably has a concentration of less than 500 parts per million, more preferably less than 100 parts per million of halide ions. It is especially preferred that the composition has less than 100, more preferably less than 50 parts per million of divalent and trivalent metals, wherein parts refer to parts by weight relative to the total weight of the composition. We have found that purifying the compositions to reduce the concentration of these undesirable ions reduces nozzle blockage in ink jet printing heads, particularly in thermal ink jet printers. Similarly low levels as divalent and trivalent metals are also preferred.

The compounds of the invention may be used as the sole colorant in inks because of their attractive black shade. However, if desired, one may combine the present compounds with one or more further colorants if a slightly different shade is required for a particular end use. The 45 further colorants are preferably dyes. When further colorants are included in the ink these are preferably selected from black, magenta, cyan and yellow colorants and combinations thereof.

Suitable further black colorants include C.I.Food Black 2, ⁵⁰ C.I.Direct Black 19, C.I.Reactive Black 31, PRO-JETTM Fast Black 2, C.I.Direct Black 195; C.I.Direct Black 168; and black dyes described in patents by Lexmark (e.g. EP 0 539,178 A2, Example 1, 2, 3, 4 and 5), Orient Chemicals (e.g. EP 0 347 803 A2, pages 5–6 dyes 3, 4, 5, 6, 7, 8, 12, ⁵⁵ 13, 14. 15 and 16)and Seiko Epson Corporation.

Suitable further magenta colorants include PRO-JETTM Fast Magenta 2.

Suitable further yellow colorants include C.I.Direct Yellow 142; C.I.Direct Yellow 132; C.I.Direct Yellow 86: C.I.Direct Yellow 85; C.I.Direct Yellow 173; and C.I.Acid Yellow 23.

Suitable further cyan colorants include phthalocyanine colorants, Direct Blue 199 and Acid Blue 99.

The composition may also contain additional components conventionally used in ink jet printing inks, for example

10

viscosity and surface tension modifiers, corrosion inhibitors, biocides, kogation reducing additives and surfactants which may be ionic or non-ionic.

In a third aspect of the invention we have also devised a process for the preparation of a compound of Formula (1), as hereinbefore defined, which comprises diazotising an amine (preferably of formula A-NH₂) and coupling the resultant diazonium salt with a compound of formula T-Q-N=N-LH, wherein A, T, L and Q are each independently as 10 hereinbefore defined to give a compound of Formula (1). The compound of formula T-Q-N=N-LH is formed by diazotising an amine of formula L-NH₂ to give a diazonium salt, and coupling the resultant diazonium salt with a compound of formula T-QH to give a compound of formula 15 T-Q-N=N-LH. Preferably the diazotisations are carried out using a diazotising agent especially sodium nitrite. Further preferably the diazotisations are carried out at a temperature of 0 to 25° C., more preferably at 0 to 20° C., further preferably at 0 to 5° C.

Preferably the diazotisation is performed using a diazotising agent, especially sodium nitrite. Further preferably the diazotisation is performed at a temperature of 0 to 5° C. Surprisingly we have found that the coupling can be performed under conditions of moderate, i.e. relatively neutral, 25 pH facilitated by the use of substantial amounts of aprotic solvents. Aprotic solvents which may be used may be chosen from, for example, dimethylformamide, dimethylsulphoxide, N-methylpyrrolidone, 2-pyrrolidone, ethers, acetone, glymes such as polyglyme (MW 300) or polyethylene glycols and/or mixtures thereof. Particularly preferred aprotic solvents are tetrahydrofuran, N-methylpyrrolidone and polyglyme. The aprotic solvent is preferably present in the range 0 to 80 wt %, preferably 20 to 60 wt %, especially 25 to 45 wt % relative to the total solvent amount used. Use of substantial amounts of aprotic solvents has the advantage of permitting diazo coupling at much lower pH than customary (usually pH in the region of 14), thereby significantly improving the efficiency, from 30% to as much as 70%, of the process as a result of greatly reduced decomposition of 40 diazonium salts.

Preferably the process of the third aspect of the present invention is performed in the presence of an acid binding agent to maintain a moderate pH. Preferably the acid binding agent used is any which maintains the pH between 5 and 9, preferably between 6 and 7.5. Further, the acid binding agent is preferably selected from but is not limited to alkali metal hydroxides, carbonates, bicarbonates or phosphates or organic bases such as triethanolamine or triethylamine. Particularly preferred alkali metal hydroxide-acid-binding agents are NaOH, KOH and LiOH, especially NaOH and LiOH. Particularly preferred alkali metal carbonate acid-binding agents are Li₂CO₃ and Na₂CO₃, especially Na₂CO₃. This has the advantage of maintaining pH sufficiently low to reduce the decomposition of diazonium salts significantly.

A fourth feature of the present invention comprises a process for the preparation of a compound of Formula (1), as hereinbefore defined, which comprises the reaction of a compound of formula T-X—N=N-L-T (wherein each T independently and L are as hereinbefore defined and X is an optionally substituted 1-hydroxy-8-amino-naphthylene group) with a strong base thereby forming a compound of Formula (1) optionally followed by contacting the compound so formed with a metal salt. Preferably the strong base is a metal hydroxide, more preferably an alkali metal hydroxides especially sodium or potassium hydroxide. The reaction with strong base preferably comprises heating in solution at an elevated temperature until reaction is com-

plete. Preferred elevated temperatures are 60 to 90° C. more preferably 65 to 80° C., especially 65 to 75° C. The pH is preferably alkaline, more preferably 10 to 14, especially 12 to 14.

The compound of formula T-X—N=N-L-T may be 5 formed by diazotising an amino of formula T (preferably A-NH₂) and coupling the resultant diazonium salt with a compound of formula T-X—N=N-LH.

The process according to the fourth aspect of the present invention has the unexpected advantages of using common and cheaply available starting materials based on 1-amino-8-hydroxynaphthylene disulphonic acid. In a further optional step, the process optionally further comprises the complexation of a compound of Formula (1) with a metal, preferably a transition metal.

A fifth aspect of the invention provides a compound of Formula (1) and salts thereof, as hereinbefore defined, with the proviso that at least one of the groups represented by T comprises a water-solubilising group, preferably selected

12

The present compounds and compositions provide prints of attractive, neutral black shades that are particularly well suited for the ink jet printing of text and images. The compositions have good storage stability and low tendency to block the very fine nozzles used in ink jet printers. Furthermore, compounds of Formula (1) may be used to provide printer images having good optical density, good fastness properties (e.g. light-fastness and wet-fastness) and resistance to fading in the presence of oxidising air pollutants (e.g. ozone).

The invention is further illustrated by the following Examples in which all parts and percentages are by weight unless specified otherwise. The abbreviation "Ac" means CH₃CO— and N/A means "not applicable".

EXAMPLE 1

Preparation of:

from sulpho, phosphato and carboxy (for the avoidance of doubt sulpho does not include sulphato). Preferred compounds of Formula (1) are as defined above in relation to the process of the first aspect of the present invention and the composition according to the second aspect of the present 40 invention.

A further aspect of the present invention provides a paper, an overhead projector slide or a textile material printed with a composition, a compound or by means of a process according to the present invention.

A still further as aspect of the present invention provides an ink jet printer cartridge, optionally refillable, comprising one or more chambers and a composition, wherein the composition is present in at least one of the chambers and the composition is as defined in the second aspect of the 50 present invention.

In a yet further aspect of the present invention, an ink set is provided, which comprises a black ink, a magenta ink, a cyan ink and a yellow ink, wherein the black ink comprises a compound according to the fifth aspect of the present 55 invention and/or a composition according to the second aspect of the present invention.

Dyes typically comprised in a magenta ink in such an ink set include Pro-Jet® Fast Magenta 2 and/or Acid Red 52. Dyes typically comprised in a cyan ink in such an ink set 60 include C.I. Direct Blue 199, Direct Blue 68 and/or Direct Blue 87. Dyes typically comprised in a yellow ink in such an ink set include C.I. Direct Yellow 86, Direct Yellow 132 and/or Direct Yellow 173. Optionally the black ink further contains one or more black dyes, e.g. Pro-Jet® Fast Black 2 65 and/or any of the dyes described in EP 539,178 A2 or EP 347,803.

Stage (A)—First Diazotisation and Coupling

$$HO_3S$$
 HO_3S
 HO_3S

Sodium nitrite (5.8 g) was added to a suspension of 5-nitro-2-aminobenzenesulfonic acid (21.3 g) in water (350 ml). The suspension was cooled to <5° C. and added over 0.5 h to a cooled (<5° C.) mixture of ice/water (100 g) and concentrated hydrochloric acid (20 ml). The mixture was stirred at <5° C. for 0.5 h and the excess nitrous acid was destroyed by addition of sulfamic acid. A solution of 1-amino-8-hydroxy-3,6-disulpho naphthalene (40 g) in water (100 ml) at pH 6.0 was added to the above solution over 0.5 h whilst maintaining pH 1.8 and <5° C. and then stirred for a further 2 h. The solution was salted to 10% w/w sodium chloride and the resulting precipitate collected by filtration. The solid washed with saturated brine (200 ml)

and dried in the oven at 50° C. overnight to give the monoazo compound Formula (8) (92 g) shown above.

Stage (B)—Second Diazotisation and Coupling

$$H_3C$$
 N
 SO_3H
 NH_2

Sodium nitrite (18 g) was added portionwise to a cooled (<5° C.) stirred mixture of 5-acetylamino-2-aminobenzene sulfonic acid (74 g), water (500 ml) and concentrated 30 hydrochloric acid (75 ml). The mixture was stirred for 1 hour at <5° C. and sulfamic acid was added to destroy excess nitrous acid. This suspension was added portionwise over 0.5 hours to a stirred solution of 2,5-diacetoxyethoxy aniline (70 g) in water (350 ml) at <5° C. The mixture was stirred 35 for 3 hours and the resulting solid was collected by filtration, slurried in acetone and then filtered. The solid was washed with acetone, dried overnight at 60° C. to give the amine Formula (9) (65 g) shown above.

Stage (C)—Third Diazotisation and Coupling

14

Sodium nitrite (2.7 g) was added to a suspension of the amine Formula (9) (17 g) in water (200 ml) at pH 9 (saturated sodium hydroxide solution) and acetone (100 ml). The suspension was added portionwise over 10 min to a cooled (<5° C.), stirred mixture of ice/water (100 g) and concentrated hydrochloric acid (18 g). The reaction mixture was stirred at room temperature for 1 hour and 1-methyl-2-pyrrolidinone (50 ml) was added to aid solubility. The reaction mixture was stirred for a further 1 hour and excess nitrous acid was destroyed with sulfamic acid. The suspension was added in four portions to a cooled (<5° C.), stirred solution of the monoazo compound Formula (8) (45 g) in water (200 g) at pH 7 (saturated sodium hydroxide solution). The pH of the reaction mixture dropped to -3 after the addition of each aliquot of diazonium salt and was raised to 7 by the addition of 2N sodium hydroxide. The reaction mixture was stirred overnight, during which it warmed up to room temperature. The product was salted-out (10% w/v 20 sodium chloride), filtered off and washed with 10% brine. The solid was dissolved in water and the pH adjusted to 12 (saturated sodium hydroxide solution). The solution was stirred overnight and the pH was lowered to 7 (concentrated hydrochloric acid). The product was precipitated by the ²⁵ addition of acetone, filtered off and washed with acetone. The solid was dissolved in water and the resulting solution was dialysed (<50 μScm⁻¹), filtered (GF/A, GF/F and 0.45 µm nylon) and dried overnight at 60° C. to give the trisazo compound Formula (10) (12 g).

Stage (D) Conversion of Amino to Hydroxy Group

A solution of the trisazo compound Formula (10) (8 g) in water (80 ml) was heated at 60° C. and pH 12.5 (2N sodium hydroxide), for 8 h. The mixture was allowed to cool to room temperature and adjusted to pH 7 with concentrated hydrochloric acid. The product was precipitated by addition of acetone. The collected solid was washed with acetone, re-dissolved in water and precipitated with acetone. The solid was dissolved in the minimum amount of water and the resulting solution was dialysed (<50 µScm⁻¹), filtered (GF/

Formula (10)

A, GF/F and 0.45 μ m nylon) and dried over 3 d at 60° C. to give the title compound (1.3 g).

EXAMPLE 2

Preparation of:

The above dark red solid was dissolved in water (1000 ml) and heated to 80° C. Sodium hydroxide (10 g) was added and the temperature maintained at 80° C. for 8 hours. After this time the pH was adjusted to 7 to 8 with concentrated hydrochloric acid and the solution allowed to cool to ambient temperature. The solution was then dialysed using visking tubing (<50 µScm⁻¹) and then screened through a

Stage (A)—First Coupling

5-Acetylamino-2-aminobenzene sulphonic acid (23.0 g, 0.10 moles) was added to water (300 ml), containing concentrated hydrochloric acid (30 g). Sodium nitrite (6.9 g) 45 was added over 10 minutes at 0 to 5° C. After 60 minutes the excess nitrous acid was destroyed and the resultant solution of diazonium salt was added slowly at 5 to 10° C. and pH 8 to 9, to a solution of 1,8-dihydroxynaphthalene-3,6-disulphonic acid (32.0 g, 0.10 moles), which had been dissolved in water (500 g). The reaction was shown to have reacted quantitatively by HPLC.

Stage (B)—Second Coupling

5-Nitro-2-aminobenzene sulphonic acid (43.6 g, 0.20 moles) was added to water (500 g), containing concentrated hydrochloric acid (60 g). Sodium nitrite (13.8 g) was added over 15 minutes at 0 to 5° C. After 60 minutes the resultant solution of diazonium salt was added over 120 minutes at 5 to 10° C. and pH 6 to 7, to the above dye base to which previously had been added tetrahydrofuran (1000 g). After 5 hours the resultant precipitate was then collected and after oven drying gave a dark red solid (55.3 g).

cascade of filters (GF/A, GF/D, 0.45 μ m) and dried in the oven to give a 47.2 g of a black solid (λ_{max} 584 nm).

Stage (C)—Third Coupling

The above black solid was re-dissolved in water at pH 7 to 9, lithium hydroxide being used to adjust pH. Sodium nitrite (8.3 g) was then added and allowed to stir in for 10 minutes. The dye/nitrite solution was then transferred into iced water (100 ml) containing concentrated hydrochloric acid (30 g). The temperature was allowed to rise to 15 to 25° C. and held for three hours. The resultant solution of diazonium salt was added over 120 minutes at 15 to 20° C. and pH 6 to 7, to a solution of 1-(4-sulphophenyl)-3-carboxy-5-pyrazolone (17.9 g, 0.06 moles). The pH being maintained by addition of lithium hydroxide. The solution was then dialysed using ViskingTM tubing (<50 μScm⁻¹) and then screened through a cascade of filters (GF/A, GF/D, 0.45 μm) and dried in the oven to give the title product as a black solid (60.0 g).

EXAMPLES 3–22

The method of Example 2 was repeated except that where indicated in Table 1 the compound in column C was used in place of 1-(4-sulphophenyl)-3-carboxy-5-pyrazolone. The formula of the final dye is given in column D.

	Lamb- da Max (mm)	089	286
TABLE 1	D Formula of final dye	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	$\begin{array}{cccccccccccccccccccccccccccccccccccc$
	C	$\begin{array}{c c} & HO_3S \\ & & \\$	$_{ m N_2^2H}$
	Ex:	3	4

TABLE 1-continued

	Lamb- da Max (nm)	£	969	620
TABLE 1-continued	D Formula of final dye	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	O OH
	X:	$\frac{O}{\sqrt{NH_2}}$	$\begin{array}{c} 1 \\ \\ \\ \\ \end{array}$	2 O CH ₃
	H K	20	21	22

*made by reduction of the nitro compound using sodium sulphite

EXAMPLES 23–26

The method of Example 2 was repeated except that where indicated in Table 2 the compound in Column A was used in place of 1-(4-sulphophenyl)-3-carboxy-5-pyrazolone, the

38

compound in Column B was used in place of 5-acetylamino-2-benzoic acid and the compound in Column C was used in place of 5-nitro-2-aminobenzene sulphonic acid in Stage (B). The formula of the final dye is given in column D.

Preparation of:

The method of Example 2 was repeated except that 2,5-diacetoxyethoxyaniline was used in place of 5-acety-lamino-2-aminobenzene sulphonic acid in Stage (A).

EXAMPLE 28

Preparation of:

$$O = S - OH$$
 $O = S - OH$
 $O =$

OF OH OH N NH2 SO₃H
$$_{\rm HO_3S}$$
 $_{\rm SO_3H}$

This was prepared according to the procedure given above in Example 2, Stages (A) and (B).

Step 2—Final Dye Synthesis:

A solution of sodium sulphide (2.93 g) and sodium sulphite (0.19 g) in water (30 ml) was added to a stirred solution of the product from step 1 above (20 g) in water (300 ml) at pH 8 (2N LiOH). The mixture was stirred at room temperature for 48 hours, after 1 hour the pH had risen to 12.4. The solution was screened through GF/F paper and then the pH was adjusted to 7. The product was isolated by addition of LiCl (250 g) followed by filtration and then the past was dried in the oven to give the diamine as a black solid (10.8 g).

A solution of the diamine (9 g) and sodium nitrite (0.82 g) in water (200 ml) at pH 7 (2N LiOH) and 0-5° C. was added to a stirred mixture of concentrated hydrochloric acid (15 ml) in ice/water (100 ml) at 0–5° C. and maintained at that temperature with stirring for 1 hour. Sulphamic acid was added to destroy excess nitrous acid. A solution of 1-(4sulphophenyl)-3-methyl-5-pyrazalone (3.08 g) in water (100 ml) at pH 7 (2N LiOH) and 0–5° C. was added dropwise to the prepared diazo solution. After addition the resulting solution was adjusted to pH 7 at 0–5° C. and stirred under these conditions for 2.5 hours. The dye was isolated by addition of 10% w/v LiCl solution until precipitation was complete and then filtered and washed with 10% w/v LiCl solution. The resulting black paste was dissolved in water (300 ml) and dialysed using ViskingTM tubing(<50 μScm⁻¹) and screened through a cascade of filters (GF/A, GF/D, 0.45 μm) and dried in the oven to give the title dye as a black solid (6 g).

EXAMPLE 29

Preparation of:

A solution of monoazo compound of Formula (9) (108 g) (as prepared in Stage (B) of Example 1 above) and sodium nitrite (27.4 g) in water (1.2 l) and acetone (800 ml) at pH 10, adjusted with lithium hydroxide was added over 10 minutes to a mixture of water (200 ml) and concentrated hydrochloric acid (80 ml) at room temperature. The solution was stirred for 1 hour and then excess nitrous acid was destroyed by addition of sulfamic acid. This solution was added over 10 minutes to a solution of chromotropic acid (80 g, 0.2 mol) in water (800 ml) at pH 7-8 and 0-10° C. and the resulting solution was stirred overnight at room temperature. Lithium hydroxide (20 g) was added and the solution was stirred for 1 hour at room temperature. The solution was then adjusted to pH7 (concentrated hydrochloric acid) and then lithium chloride (250 g) was added whilst maintained at room temperature. The resulting mixture was filtered, washed with lithium chloride solution (1 1, 15%) and the collected paste was stirred in acetone (2.5 l). This 20 mixture was filtered, washed with acetone (1 l) and dried in the oven to give a dark blue solid (150 g).

Stage (B)

A solution of sodium nitrite (15 ml, 10% w/v) was added 25 dropwise to a solution of 5-nitro-2-aminobenzene sulfonic acid (5.8 g) in water (80 ml) and concentrated hydrochloric acid (15 ml) at 0–5° C. The solution was stirred for 30 minutes and then excess nitrous acid was destroyed by addition of sulfamic acid. This solution was added portionwise to a solution of the dark blue solid (10.1 g) from Stage (A) in water (100 ml) and THF (50 ml) at pH7 (4N LiOH solution) and 0–5° C. The resulting solution was maintained at this temperature and pH for 4 hours and then allowed to warm to room temperature overnight. Lithium chloride (15) g) was added at 30° C. and the resulting mixture was filtered and the collected paste was washed with lithium chloride solution (150 ml, 7.5%). This paste was then slurried in acetone (250 ml) with some water and the solid was collected, washed with acetone and then dried at 70° C. The resulting solid was dissolved in water (50 ml), dialysed using ViskingTM tubing (<50 µScm⁻¹) and the resulting solution was screened through a cascade of filters (GF/A, GF/D, 0.45 µm) and dried in the oven to give the title product as a black solid (5 g).

EXAMPLES 30–62

The method of Example 29 was repeated except that where indicated in Table 3 in place of the monoazo compound of Formula (9) in Stage (A) there was used the monoazo compound obtained from the azo-coupling of the

48

components shown in columns A and B of Table 3; and, in place of 5-nitro-2-aminobenzene sulfonic acid in Stage (B), there was used the amine shown in column C of Table 3, unless indicated "N/A". The formula of the final dye is given in Table 3, column D.

In Example 53, the Glucose Reductive Coupling was Carried Out as Follows:

Concentrated sodium hydroxide (7 ml) was added to a stirred solution of the disazo intermediate derived as indicated in the Table(16.8 g) in water (200 ml) at 75° C.

followed by a solution of D-glucose (2.2 g) in water (3 ml). The solution was stirred at 75° C. for 30 mins and then cooled to room temperature before adjusting to pH 1 with concentrated hydrochloric acid. Acetone (500 ml) was added to the stirred solution and the resulting precipitate was collected by filtration, washed with acetone (300 ml) and then redissolved in water (200 ml) at pH 8 (2N LiOH). The solution was dialysed (<100 μScm⁻¹) and screened through a cascade of filters (GF/A, GF/D, 0.45 μm) and dried in the oven to give the title dye as a black solid (12.5 g).

	Lamb- da Max (mm)	671		940	653	949
	D (Formula of final dye)	HÖ	H_2N SO_3H O	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	Achin So ₃ H \rightarrow OH \rightarrow HO ₃ S \rightarrow NH ₂ \rightarrow HO \rightarrow OH \rightarrow N \rightarrow HO ₃ S \rightarrow So ₃ H \rightarrow HO ₃ S \rightarrow So ₃ H
TABLE 3		N/A		H_{2N}	HO_3S H_2N SO_3H	N/A
	B	N/A		N/A	N/A	N/A
	A Y	N/A		N/N	N/A N/A N/A	N/A
	Ex.	30*h		31	32*h	33#

	Lamb- da Max (nm)	859		
	D (Formula of final dye)	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
TABLE 3-continued	C	N/A	N/A	N/N
	B	N/A	$\begin{array}{c} OH \\ O $	$\begin{array}{c} OH \\ O $
	A	N/A	AcHN NH ₂	AcHN NH2
	Ex.	34*h#	35	36*h

	Lamb- da Max (nm)	94	628	634	280
	D (Formula of final dye)	H $_{2}N$ $_{3}N$ $_{4}N$ $_{5}N$ $_{5}N$ $_{5}N$	Achn So ₃ H \rightarrow OH \rightarrow NO ₂ \rightarrow HO \rightarrow NO ₃ \rightarrow So ₃ H \rightarrow So ₃ H	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	$\begin{array}{cccccccccccccccccccccccccccccccccccc$
TABLE 3-continued	C	H_{2N} N N CO_{2}	H_{2N}	H_{2N}	H_{2N}
	B	N/A	N/A	N/A	NH ₂
	A	N/A	N/A	N/A	N/A
	Ex.	40*h	7	74	43

	Lamb- da Max (nm)	630	624	620
	D (Formula of final dye)	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	$\begin{array}{cccccccccccccccccccccccccccccccccccc$
TABLE 3-continued		N N N N N N N N N N	$\begin{array}{c} 0 \\ N \\ N \end{array}$	$^{\mathrm{O}}$ $^{\mathrm{OH}}$ $^{\mathrm{N}}$ $^{\mathrm{H}_{2}N}$
	B	N/A	N/A	H_3C O
	A	N/A	N/A	N/A
	Ex.	4	4	46

	Lamb- da Max (nm)		
	D (Formula of final dye)	$\begin{array}{c} O \\ O $	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
TABLE 3-continued	C	H_2^{O}	$\begin{array}{c} O \\ O \\ \\ \\ \\ \\ \\ \end{array}$
	B	ZHN O	H_3C O NH_2
	A	N/A	N/A
	Ex.	54(*h)	25(*h)

	Lamb- da Max (nm)	659
	D (Formula of final dye)	$\begin{array}{c} OH \\ O=S\\ OH \\ ON\\ ONH_2 \end{array}$ $\begin{array}{c} OH \\ OH \\ OO\\ OH\\ OO\\ OO$
TABLE 3-continued	C	$H_{0} = \frac{1}{8} - 0$ $H_{0} = \frac{1}{8} - 0$ 0
	B	N/A
	A	N/A
	Ex.	61(*3)

	Lamb- da Max (nm)	672
	D (Formula of final dye)	$\begin{array}{c} OH \\ O = \begin{array}{c} OH \\ OH \end{array} \end{array}$
TABLE 3-continued	C	$\begin{array}{c} O \\ O \\ HO \\ O \\ N^{\overline{c}H} \end{array}$
	B	N/A
	A	N/A
	Ex.	62(*3)

*acetyl groups removed by alkaline hydrolysis

(#)nitro reduced to amine by sodium sulphite

(*8)glucose reductive coupling of dis-azo intermediate as described above

(**h)amino-product derived from alkaline hydrolysis of the corresponding acetylamino-compound

(*1)from reductive coupling of two molecules of Example 9 via the terminal nitro groups

(*2)metallisation carried out after stage (A) by addition of 1 mole equivalent of metal (II) acetate

(*3)followed by:
removal of acetyl by hydrolysis

diazotisation

	D (Formula of final dye)		
TABLE 3-continued			
	B		
	Y	HO	
	E x.	coupling onto	

EXAMPLE 63—Ink Formulations

Inks may be prepared according to the following formulation wherein Dye is the dye from each of the Examples 1 to 15 above:

2-Pyrrolidone	5 parts	•
Thiodiglycol	5 parts	
Surfynol TM 465	1 part (from Air Products Inc., USA)	
Dye	3 parts	
Water	86 parts	

Further inks described in Tables 4 and 5 may be prepared wherein the Dye described in the first column is the Dye 15 made in the above example of the same number. Numbers quoted in the second column onwards refer to the number of

82

DEG=diethylene glycol

NMP=N-methyl pyrollidone

DMK=dimethylketone

IPA=isopropanol

MEOH=methanol

2P=2-pyrollidone

MIBK=methylisobutyl ketone

P12=propane-1,2-diol

BDL=butane-2,3-diol

CET=cetyl ammonium bromide

PHO=Na₂HPO₄ and

TBT=tertiary butanol

TDG=thiodiglycol

TABLE 4

Dye	Dye Content	Water	PG	DEG	NMP	DMK	NaOH	Na Stearate	IPA	МЕОН	2P	MIBK
1	2.0	80	5		6	4					5	
2	3.0	90		5	5		0.2					
3	10.0	85	3		3	3				5	1	
4	2.1	91		8								1
5	3.1	86	5					0.2	4			5
6	1.1	81			9		0.5	0.5			9	
7	2.5	60	4	15	3	3			6	10	5	4
8	5	65		20					10			
9	2.4	75	5	4		5				6		5
10	4.1	80	3	5	2	10		0.3				
11	3.2	65		5	4	6			5	4	6	5
12	5.1	96								4		
13	10.8	90	5						5			
14	10.0	80	2	6	2	5			1		4	
15	1.8	80		5							15	
1	2.6	84			11						5	
2	3.3	80	2			10				2		6
3	12.0	90				7	0.3		3			
4	5.4	69	2	20	2	1					3	3
5	6.0	91			4						5	

TABLE 5

Dye	Dye Content	Water	PG	DEG	NMP	CET	TBT	TDG	DBL	РНО	2P	PI2
6	3.0	80	15			0.2					5	
7	9.0	90		5						1.2		5
8	1.5	85	5	5		0.15	5.0	0.2				
9	2.5	90		6	4					0.12		
10	3.1	82	4	8		0.3						6
11	0.9	85		10					5	0.2		
12	8.0	90		5	5			0.3				
13	4.0	70		10	4				1		4	11
14	2.2	75	4	10	3				2		6	
15	10.0	91			6						3	
1	9.0	76		9	7		3.0			0.95	5	
2	5.0	78	5	11							6	
3	5.4	86			7						7	
4	2.1	70	5	5	5	0.1	0.2	0.1	5	0.1	5	
5	2.0	90		10								
6	2	88						10				
7	5	78			5			12			5	
8	8	70	2		8			15			5	
9	10	80						8			12	
10	10	80		10								

parts of the relevant ingredient and all parts are by weight. The inks may be applied to paper by thermal or piezo ink jet printing.

The following abbreviations are used in Table 3 and 4: PG=propylene glycol

EXAMPLE 64—Buffered Ink Formulations

Inks may be prepared according to the following formulation wherein Dye is the dye from each of the Examples:

25

2-Pyrrolidone	5 parts
Propylene glycol	5 parts
Surfynol TM 465	1 part (from Air Products Inc., USA)
Dye	3 parts
TRIS	2 parts
Water	84 parts

Further inks described in Tables 6 and 7 may be prepared wherein the Dye described in the first column is the Dye made in the above examples of the same number. Numbers quoted in the second column onwards refer to the number of parts of the relevant ingredient and all parts are by weight. 15 The inks may be applied to paper by thermal or piezo ink jet printing.

The following additional abbreviations are used in Table 6, all other abbreviations are as used in Tables 4 and 5:

BIS-TRIS PROPANE=1,3-bis[tris(hydroxymethyl)me-thylamino]propane

TES=N-tris(hydroxymethyl)methyl-2-aminoethanesulfonic acid

MES=2-(N-morpholino)ethanesulfonic acid

HEPES=N-(2-hydroxyethyl)piperazine-N'-(2-ethane-sulfonic acid)

MOBS=4-(N-morpholino)butanesulfonic acid

DIPSO=3-[N,N-bis(2-hydroxyethyl)amino]-2-hydrox-ypropanesulfonic acid

TRIS=tris(hydroxymethyl)aminomethane

ADA=N-(2-acetamido)-2-iminodiacetic acid

TRICINE=N-tris(hydroxymethyl)methylglycine

HEPPSO=N-(2-hydroxyethyl)piperazine-N'-(2-hydroxypropanesulfonic acid

DEAS=N,N-diethylanthranilic acid

PHO=NaH₂PO₄

Print Test Examples

The inks described in Example 63 were ink-jet printed onto a variety at papers using a Hewlett Packard DeskJet 560CTM. The CIE colour co-ordinates of each print (a, b, L, Chroma and hue H) were measured using a Gretag Spectrolino SpectrodensitometerTM with 0°/45° measuring geometry with a spectral range of 400–700 nm at 20 nm spectral intervals, using illuminant D50 with a 2° (CIE 1931) observer angle and a density operation of status A. No less than 2 measurements were taken diagonally across a solid colour block on the print with a size greater than 10 mm×10 mm. The properties of the resultant prints are shown in Table 8, where the example number of the dye used to prepare the ink is indicated in the left hand column.

The substrates used in Tables 8, 9 and 10 were as follows:

		Number	
30	HP Printing Paper ™	1	
	HP Premium Plus MkII™	2	
	Epson Premium Photo TM	3	
	Ilford Instant Dry TM	4	

TABLE 6

Dye	Dye Content	Water	PG	DEG	NMP	DMK	Na Stearate	IPA	МЕОН	2P	MIBK	Buffer	Buffer substance	adjusted pH
2	2.0	78	5		6	4				5		2	РНО	7.8
2	3.0	86.2		5	5							0.8	TRIS	7.2
2	10.0	75.5		2	3	3		5		1		0.5	BIS-TRIS	6.4
													PROPANE	
5	2.1	88.7		8							1	0.2	TES	7.1
5	3.1	77.7	5				0.2	4			5	5	HEPES	7.5
5	8.5	70.5			9					9		3	MOBS	8.0
7	2.5	45.5	4	15	3	3		6	10	5	4	2	DIPSO	7.6
7	6	72				10		10				2	ADA	6.5
7	12	622	5	4		5	0.3		6		5	0.5	TRICINE	8.0

TABLE 7

Dye	Dye Content	Water	PS	DEG	NMP	CET	TBT	TDG	BDL	2P	PI2	Buffer	Buffer substance	adjusted pH
2	3.0	76.5	15			0.2			1	4		0.3	TRICINE	7.9
2	9.0	80		5							5	1	HEPPSO	7.7
2	1.5	81.4	5	5		0.1	5.0	0.2				1.8	MES	5.9
5	0.9	88.8		6	4							0.3	BIS-TRIS	6.8
													PROPANE	
5	3.1	88	4	8		0.3					6	0.6	TRIS	7.8
5	9.5	74		10					5			1.5	DIPSO	7.5
7	8.0	80.6		5	5	0.1		0.3				0.8	DEAS	7.4
7	4.0	65		10	4					5	11	1	TRIG	8.0
7	2.2	68.8	4	10	3		1.0		2	6		3	ADA	6.5

TABLE 8

			IABLE	, 0					
Example No.	Dye	SUBSTRATE	DEPT H%	ROD	L	Α	В	С	Н
65	2	1	100	1.15	33	-2	-8	8	254
65	2	1	70	0.48	65	1	-9	9	274
65	2	2	10	0.93	11	0	-10	10	270
65	2	2	70	0.75	50	-1	-8	8	260
65	2	3	100	1.93	11	-1	-12	12	266
65	2	3	70	0.74	50	-2	-7	7	254
65 65	2	4	100	2.02	10	0	-13	13	270
65 66	2	4	70	0.00	40 27	-2 1	-11	11	259
66 66	3	1 1	100 70	1.04 0.44	37 67	-1 1	-12 -12	12 12	266 276
66	3	2	100	1.63	19	0	-17	17	270
66	3	2	70	0.66	55	-2	-11	11	262
66	3	3	100	1.73	17	-1	-22	22	268
66	3	3	70	0.66	55	-3	-13	13	258
66	3	4	100	1.72	17	-1	-20	20	267
66	3	4	70	0.72	52	-2	-14	14	261
67	8	1	100	1.20	31	0	-8	8	270
67	8	1	70	0.49	64	1	-10	10	278
67	8	2	100	1.61	18	1	-2	2	301
67	8	2	70	0.78	49	-4	-7 -	8	241
67 67	8	3	100	1.56	19	1	- 5	5	287
67 67	8	3 1	70	0.74	51	-4 2	-9 4	10	244
67 67	8 8	4 4	100 70	1.57 0.86	19 45	2 -4	-4 -10	4 11	294 249
68	25	1	100	1.11	34	- 4	-10 -8	9	249
68	25	1	70	0.48	65	0	_9	9	271
68	25	2	100	2.29	6	-2	-11	11	259
68	25	2	70	0.83	46	-4	- 9	10	245
68	25	3	100	2.23	7	-2	-15	15	263
68	25	3	70	0.85	46	-5	-12	13	248
68	25	4	100	2.07	9	-3	-12	12	254
68	26	4	70	0.91	43	-6	-11	13	243
69	29	1	100	1.02	38	-3	-4	5	237
69	29 20	1	70	0.47	65	1	-8	8	274
69	29	2	100	1.84	13	0	-8	8	265
69 69	29 29	2 3	70 100	0.74	50 17	-1 1	-6 °	6 5	259
69	29 29	3	70	1.65 0.68	17 53	-1 -1	-8 -5	<i>5</i>	266 261
69	29	4	100	1.74	16	-3	-10	11	253
69	29	4	70	0.80	48	-3	-8	9	261
70	34	1	100	1.08	35	-2	-5	6	253
70	34	1	70	0.47	66	1	-8	8	278
70	34	2	100	1.80	14	-5	-5	7	226
70	34	2	70	0.78	49	-4	-5	6	229
70	34	3	100	1.82	14	-3	-8	9	248
70 70	34	3	70	0.74	50	-3	-6	6	239
70 70	34	4	100	1.74	15	-2 2	-9 7	9	257
70 71	34 37	4 1	70 100	$0.82 \\ 0.98$	47 39	−3 −3	−7 −7	7 7	248 248
71	37	1	70	0.46	66	-3 0	-7 -9	9	272
71	37	2	100	1.48	22	0	-11	11	270
71	37	2	70	0.64	56	Ŏ	- 7	7	266
71	37	3	100	1.34	26	1	-12	12	273
71	37	3	70	0.59	58	0	-8	8	270
71	37	4	100	1.41	24	-1	-12	13	267
71	37	4	70	0.67	54	0	- 9	9	268
72	49	1	100	0.97	39	3	-3	5	317
72 72	49 40	1	70	0.44	67	4	-7 4	8	298
72 72	49 40	2	100	1.54	19 55	8	-4 3	9 5	337
72 72	49 49	2 3	70 100	0.64 1.38	55 23	4 10	-3 -4	5 10	321 335
72 72	49 49	3	70	0.59	23 57	6	-4 -3	7	333 329
72	49	4	100	1.43	22	9	-3 -4	10	336
72	49	4	70	0.67	53	6	-3	7	333
73	53	1	100	1.06	37	-8	-13	15	240
73	53	1	70	0.44	68	-2	-12	12	261
73	53	2	100	1.83	15	-11	-18	21	237
73	53	2	70	0.71	53	-8	-12	14	237
73	53	3	100	1.75	18	-1 0	-23	25	247
73	53	3	70	0.73	53	-9	-16	19	242
73	53	4	100	1.77	17	-11	-20	23	242
73	53	4	70	0.80	49	-10	-17	19	239
74 74	59 50	1	100	0.78	48	-1 1	-4 7	4	256
74 74	59 59) 1	70 100	0.42 1.43	68 24	1 -8	−7 −3	7 9	277 203
7 4 74	59 59	2	70	0.72	52	-8 -7	-3 -4	8	203
<i>1</i> T		~	70	0.72	52	,	₹	G	207

TABLE 8-continued

Example No.	Dye	SUBSTRATE	DEPT H%	ROD	L	A	В	С	Н
74 74 74 74 74	59 59 59 59	3 3 4 4	100 70 100 70	1.52 0.69 1.61 0.77	22 53 19 50	-11 -9 -11 -9	-5 -4 -5 -5	12 10 12 10	204 204 204 211

Light Fastness

To evaluate light fastness the prints were irradiated in an Atlas Ci5000 Weatherometer for 100 hours. The results are shown in Table 9 where the example number of the dye used to prepare the ink is indicated in the left hand column. The degree of fade is expressed as ΔE where a lower figure indicates higher light fastness, and ΔE is defined as the overall change in the CIE colour co-ordinates L, a, b of the print and is expressed by the equation $\Delta E = (\Delta L^2 + \Delta a^3 + \Delta b^2)_{0.5}$

TADIE

Example No. Dye SUBSTRATE ΔΕ				
Example No.	Бус	SUBSTRATE	ΔE	
65	2	1	17	
65	2	2	62	
64	2	3	14	
64	2	4	47	
66	3	1	16	
66	3	2	20	
66	3	3	23	
66	3	4	36	
67	8	1	16	
67	8	2	16	
67	8	3	7	
67	8	4	24	
68	25	1	14	
68	25	2	30	
68	25	3	33	
68	25	4	55	
69	29	1	13	
69	29	2	18	
69	29	3	15	
69	29	4	34	
70	34	1	8	
70	34	2	11	
70	34	3	9	
70	34	4	17	
71	37	1	16	
71	37	2	35	
71	37	3	33	
71	37	4	46	
72	49	1	12	
72	49	2	10	
72	49	3	9	
72	49	4	36	
73	53	1	17	
73	53	2	27	
73	53	3	21	
73	53	4	55	
74	59	1	4	
74	59	2	10	
74	59	3	12	
7.4	50	<i>.</i>	25	

Ozone Fastness

The inks from Examples and were printed onto the substrate shown using a HP560TM ink jet printer. The printed substrate was then assessed for ozone stability using an ozone test cabinet from Hampden Test Equipment. The test was carried out for 24 hours at 40° C. and 50% relative 65 humidity in the presence of 1 part per million of ozone. Fastness of the printed ink to ozone was judged by the

difference in the optical density before and after exposure to ozone using a Gretag Spectrolino Spectrodensitometer. Thus, the lower the % OD loss the greater the ozone fastness. The results are shown in Table 10 where the example number of the dye used to prepare the ink is indicated in the left hand column. These clearly demonstrate that inks based on compositions of this invention display good ozone fastness.

TABLE 10

	Example No.	Dye	SUBSTRATE	% OD loss
35	65	2	3	3
	65	2	4	5
	66	3	3	12
	66	3	4	13
	67	8	3	6
	67	8	4	8
	68	25	3	6
	68	25	4	12
	69	29	3	12
	69	29	4	21
	70	34	3	39
	70	34	4	41
	71	37	3	27
	71	37	4	35
	72	49	3	30
	72	49	4	32
	73	53	3	3
	73	53	4	5
	74	59	3	5
	74	59	4	7

The invention claimed is:

1. A process for printing an image on a substrate comprising applying thereto a composition comprising a liquid medium and a compound of Formula (1):

wherein:

55

each T independently is an azo group of the formula A-N=N— wherein each A independently is an optionally substituted aryl, heteroaryl, non-aromatic heterocyclic or an alkenyl group;

Q is an optionally substituted, optionally metallised 1,8-dihydroxynaphthyl group of Formula (4);

Formula (4)

$$_{\mathrm{HO_{3}S}}^{\mathrm{OH}}$$
 $_{\mathrm{SO_{3}H}}^{\mathrm{OH}}$

L is a divalent organic linker group; and wherein each A and L independently carries 1 or 2 substituents, and

with the proviso that at least one of the groups represented by T comprises a water-solubilising group.

2. A composition comprising a liquid medium and a compound of Formula (1):

T-Q-N=N-L-T Formula (1)

wherein:

each T independently is an azo group of the formula A-N=N— wherein each A independently is an optionally substituted aryl, heteroaryl, non-aromatic heterocy- 10 clic or an alkenyl group;

Q is an optionally substituted, optionally metallised 1,8-dihydroxynaphthyl group of Formula (4);

Formula (4)

OH OH

HO₃S

SO₃H

L is a divalent organic linker group; and wherein each A and L independently carries 1 or 2 substituents, and with the proviso that at least one of the groups represented by T comprises a water-solubilising group.

3. A composition according to claim 2 which further comprises a pH buffer and the composition has a H of 4 to 8.

4. A composition according to claim 3 wherein the buffer is selected from the group consisting of (tris(hydroxymethy-1)aminomethane), cationic aliphatic primary amines, zwitterionic amino acids, phosphate buffers, amino-hydroxyalkylsulfonic acid zwitterions and 35 trishydroxymethylaminomethane derivatives.

5. A composition according to claim 2 wherein the liquid medium further comprises an oxidant.

6. A process for the preparation of a compound of Formula (1):

T-Q-N=N-L-T Formula (1)

wherein:

each T independently is an azo group of the formula A-N=N— wherein each A independently is an option- 45 ally substituted aryl, heteroaryl, non-aromatic heterocyclic or an alkenyl group;

Q is an optionally substituted, optionally metallised 1,8-dihydroxynaphthyl group of Formula (4);

OH OH

$$_{\mathrm{HO_{3}S}}$$

L is a divalent organic linker group; and wherein each A ₆₀ and L independently carries 1 or 2 substituents;

which process comprises diazotising an amine and coupling the resultant diazonium salt with a compound of formula T-Q-N=N-LH, wherein T, L and Q are each independently as defined in Formula (1), and with the proviso that at least 65 one of the groups represented by T comprises a water-solubilising group.

90

7. A process for the preparation of Formula (1):

wherein:

each T independently is an azo group of the formula A-N=N— wherein each A independently is an optionally substituted aryl, heteroaryl, non-aromatic heterocyclic or an alkenyl group;

Q is an optionally substituted, optionally metallised 1,8-dihydroxynaphthyl group of Formula (4);

Formula (4)

$$_{
m HO_3S}$$
 OH OH $_{
m SO_3H}$

L is a divalent organic linker group; and wherein each A and L independently carries 1 or 2 substituents;

which comprises the reaction of a compound of formula 25 T-X—N=N-L-T with a strong base thereby forming a compound of Formula (1), wherein each T independently and L are as defined in Formula (1) and X is an optionally substituted 1-hydroxy-8-amino-naphthylene group, and with the proviso that at least one of the groups represented by T comprises a water-solubilising group.

8. A compound of Formula (1):

wherein:

40

50

55

each T independently is an azo group of the formula A-N=N— wherein each A independently is an optionally substituted aryl, heteroaryl, non-aromatic heterocyclic or an alkenyl group;

Q is an optionally substituted, optionally metallised 1,8-dihydroxynaphthyl group of Formula (4);

Formula (4)

$$_{\mathrm{HO_{3}S}}^{\mathrm{OH}}$$
 $_{\mathrm{SO_{3}H}}^{\mathrm{OH}}$

L is a divalent organic linker group; and wherein each A and L independently carries 1 or 2 substituents; and with the proviso that at least one of the groups represented by T comprises a water-solubilising group.

9. A compound according to claim 8 wherein at least one group represented by A carries at least one sulpho group.

10. A compound according to claim 8 wherein at both groups represented by A carry at least one sulpho group.

11. A compound according to any one of claim 8 or 9 wherein L is of Formula (7):

$$-L^{1}(-G-L^{2})_{x}$$
-Formula (7)

wherein:

L¹ is a single covalent bond or optionally substituted phenyl or naphthyl;

91

L² is optionally substituted phenyl or naphthyl;

G is -O, $-NR^2$, -N, $-NR^2$ —-CO, $-NR^2CONR^2$, -S, -SO, -SO, -SO, $-SO_2NR^2$ or $-CR^2$ $-CR^2$, wherein each R^2 independently is H or C_{1-4} -alkyl; and X is 0, 1 or 2.

12. A compound according to claim 8 wherein: each A independently is optionally substituted phenyl, naphthyl, pyridyl or pyrazolyl;

Q is of Formula (5) or (6) or a metal complex thereof:

 HO_3S SO_3H

L is of Formula (7):

$$-L^{1}(-G-L^{2})_{x}$$
-Formula (7)

wherein;

L¹ is a single covalent bond or optionally substituted phenyl or naphthyl;

L² is optionally substituted phenyl or naphthyl;

 $-SO_2NR_2$ — or $-CR^2$ = $-CR^2$ —, wherein each R^2 independently is H or C_{1-4} -alkyl; and

X is 0, 1 or 2.

13. A compound according to claim 8 or 12 wherein said 5 optional substituents which may be present on A and L are selected from the group consisting of OH, SO₃H, PO₃H₂, CO₂H, NO₂, NH₂, optionally substituted alkyl, optionally substituted alkoxy, optionally substituted amine, optionally substituted acylamine and optionally substituted azo.

14. A compound according to claim 8 or 12 wherein said optional substituents which may be present on A and L are selected from the group consisting of OH; SO₃H; PO₃H₂; CO₂H; NO₂; NH₂; C₁₋₄-alkyl optionally carrying a sulpho, carboxy, phosphato, C_{1-4} -alkoxy, amino or hydroxy group; 15 C_{1-4} -alkoxy optionally carrying a sulpho, carboxy, phosphato, C₁₋₄-alkoxy, C₁₋₄alkyl, amino or hydroxy group; N carrying one or two C_{1-4} -alkyl groups optionally carrying a sulpho, carboxy, phosphato, C_{1-4} -alkoxy, amino or hydroxy group; C_{1-4} -acylamino; and phenylazo, naphthylazo and 20 heteroarylazo where the phenyl, naphthyl and heteroaryl units are optionally further substituted with one or more groups selected from the group consisting of OH, SO₃H, PO₃H₂, CO₂H, NO₂ and NH₂, and azo groups containing a substituent of Formula (2):

Formula (6) 25

30

$$Y$$
 Y^1
 X^1

wherein

Y is an electron withdrawing group;

Y¹ is H, alkyl or aryl, OR or N(R)₂ in which each R independently is H, optionally substituted alkyl or optionally substituted aryl; or,

Formula (2)

Y and Y¹ together with the double bond shown above form a 5- or 6-membered ring; and

X¹ comprises at least one heteroatom selected from the group consisting of N, O and S.

15. A compound according to claim 8 of Formula (8) or a salt thereof:

Formula (8) SO_3H SO_3H . OHOH \cdot SO₃H

G is —O—, —NR²—, —N=N—, —NR²—CO—, 16. A compound according to claim 8 of Formula (9) or —NR²CONR²—, —S—, —SO—, —SO₂—, a salt thereof:

93

material printed by means of a process according to claim 1.

18. A paper, an overhead projector slide or a textile material printed with a compound according to claim 8.

19. An ink jet printer cartridge, optionally refillable, comprising one or more chambers and a composition, 25 mula (2): wherein the composition is present in at least one of the chambers and the composition is as defined in claim 2.

20. An ink set comprising a black ink, a magenta ink, a cyan ink an a yellow ink, wherein the black ink comprises a compound according to claim 8 or 15.

21. An ink set comprising a black ink, a magenta ink, a cyan ink and a yellow ink, wherein the black ink comprises a composition according to claim 2.

22. A compound according to claim 12 wherein said substituents which may be present on A and L¹ and L² are selected from the group consisting of OH, SO₃H, PO₃H₂, CO₂H, NO₂, NH₂, optionally substituted alkyl, optionally substituted alkoxy, optionally substituted amine, optionally substituted acylamine and optionally substituted azo.

23. A compound according to claim 12 wherein said optional substituents which may be present on A and L¹ and L² are selected from the group consisting of OH; SO₃H; PO₃H₂; CO₂H; NO₂; NH₂; C₁₋₄-alkyl optionally carrying a sulpho, carboxy, phosphato, C_{1-4} -alkoxy, amino or hydroxy group; C_{1-4} -alkoxy optionally carrying a sulpho, carboxy, $_{45}$ phosphato, C_{1-4} -alkoxy, C_{1-4} alkyl, amino or hydroxy group; N carrying one or two C_{1-4} -alkyl groups optionally carrying a sulpho, carboxy, phosphato, C_{1-4} -alkoxy, amino or

17. A paper, an overhead projector slide or a textile $_{20}$ hydroxy group; C_{1-4} -acylamino; and phenylazo, naphthylazo and heteroarylazo where the phenyl, naphthyl and heteroaryl units are optionally further substituted with one or more groups selected from OH, SO₃H, PO₃H₂, CO₂H, NO₂ and NH₂, and azo groups containing a substituent of For-

94

Formula (2)
$$\begin{array}{c} Y \\ Y^1 \\ X^1 \end{array}$$

Y is an electron withdrawing group;

Y¹ is H, alkyl or aryl, OR or N(R)₂ in which each R independently is H, optionally substituted alkyl or optionally substituted aryl; or,

Y and Y¹ together with the double bond shown above form a 5- or 6-membered ring; and

X¹ comprises at least one heteroatom selected from the group consisting of N, O and S.

24. A compound according to claim 8 wherein L carries at least one substituent of the formula $-O-(CH_2)_{1-4}OH$ or carries at least one sulpho group.