



US007057814B2

(12) **United States Patent**  
**Boyd et al.**

(10) **Patent No.:** **US 7,057,814 B2**  
(45) **Date of Patent:** **\*Jun. 6, 2006**

(54) **ILLUMINATION SYSTEM FOR REFLECTIVE DISPLAYS**

(75) Inventors: **Gary T. Boyd**, Woodbury, MN (US);  
**Richard A. Miller**, Stillwater, MN (US);  
**Leland R. Whitney**, St. Paul, MN (US)

(73) Assignee: **3M Innovative Properties Company**,  
St. Paul, MN (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **11/070,806**

(22) Filed: **Mar. 2, 2005**

(65) **Prior Publication Data**

US 2005/0185277 A1 Aug. 25, 2005

**Related U.S. Application Data**

(60) Continuation of application No. 10/854,943, filed on May 27, 2004, now Pat. No. 6,900,936, which is a division of application No. 09/498,801, filed on Jan. 31, 2000, now Pat. No. 6,785,049.

(51) **Int. Cl.**

**G02B 5/30** (2006.01)  
**G02B 27/14** (2006.01)  
**F21V 9/14** (2006.01)  
**H04N 5/225** (2006.01)  
**G03B 19/00** (2006.01)

(52) **U.S. Cl.** ..... **359/485**; 359/501; 359/631;  
359/633; 362/19; 362/555; 362/558; 362/560;  
362/612; 362/615; 362/800; 348/207.1; 348/333.01;  
348/333.08; 396/429

(58) **Field of Classification Search** ..... 359/485, 359/487, 501, 618, 629, 630, 631, 633; 362/19, 362/555, 558, 560, 227, 612, 615, 800; 345/7, 345/8; 353/20, 119; 348/207.1, 333.01, 348/333.08, 333.09, 335; 396/385, 429  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,642,487 A	6/1953	Schroeder
5,382,987 A	1/1995	Sperling
5,394,253 A	2/1995	Kelly
5,402,269 A	3/1995	Oono et al.
5,506,704 A	4/1996	Broer et al.
5,596,451 A	1/1997	Handschy et al.
5,605,390 A	2/1997	Brice et al.
5,612,820 A	3/1997	Schrenk et al.
5,676,442 A	10/1997	Fujimori
5,800,032 A	9/1998	Uchiyama et al.
5,808,800 A	9/1998	Handschy et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 492 636 7/1992

(Continued)


*Primary Examiner*—Ricky D. Shafer

(74) *Attorney, Agent, or Firm*—George W. Jonas

(57) **ABSTRACT**

An illumination system for a reflective display is particularly useful for microdisplays that use reflective displays. The light source and the reflective image display unit are mounted in a coplanar manner, thus permitting the light source and the display unit to be mounted on a single board, or even on a single substrate. The display unit may include a first light source directing light generally along a first axis and a reflective image display unit disposed with an optical axis substantially parallel to the first axis. A reflective polarizing film is disposed to direct light from the first light source to the reflective image light display unit.

**29 Claims, 15 Drawing Sheets**



# US 7,057,814 B2

Page 2

---

## U.S. PATENT DOCUMENTS


5,826,960 A 10/1998 Gotoh et al.  
5,853,240 A 12/1998 Tanaka et al.  
5,926,318 A \* 7/1999 Hebert ..... 359/618  
5,943,171 A 8/1999 Budd et al.  
6,072,635 A 6/2000 Hashizume et al.  
6,256,151 B1 7/2001 Ma et al.  
6,282,029 B1 8/2001 Ma et al.  
6,449,439 B1 \* 9/2002 Boyd et al. .... 396/374  
6,785,049 B1 \* 8/2004 Boyd et al. .... 359/485

6,900,936 B1 \* 5/2005 Boyd et al. .... 359/485  
2002/0003508 A1 1/2002 Schehrer et al.



## FOREIGN PATENT DOCUMENTS

EP 0 982 705 3/2000  
WO WO 94/11766 5/1994  
WO WO 99/34246 7/1999


\* cited by examiner



**Fig. 1**



**Fig. 2**



**Fig. 3**




Fig. 4







Fig. 5




**Fig. 6A**




**Fig. 6B**




**Fig. 6C**




**Fig. 6D**




**Fig. 7A**




**Fig. 7B**




**Fig. 8A**




**Fig. 8B**




**Fig. 8C**




**Fig. 9A**




**Fig. 9B**




**Fig. 9C**




**Fig. 9D**




**Fig. 9E**



**Fig. 9F**



**Fig. 9G**



**Fig. 10**




Fig. 11A




Fig. 11C







Fig. 11B




**Fig. 12**




**Fig. 13**




**Fig. 14A**



**Fig. 14B**



**Fig. 15A**



**Fig. 15B**

1

## ILLUMINATION SYSTEM FOR REFLECTIVE DISPLAYS

### CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 10,854,943, filed May 27, 2004, now U.S. Pat. No. 6,900,936, which is a divisional of U.S. application Ser. No. 09/498,801 filed Jan. 31, 2000, issued as U.S. Pat. No. 6,785,049 of which the entirety of these disclosures are incorporated by reference herein.

### FIELD OF THE INVENTION

The invention relates to reflective displays, and more particularly to a compact illumination system for a reflective display.

### BACKGROUND

Many optical devices, such as microdisplays in electronic cameras and other types of display system, require illumination by a beam of light having relatively uniform brightness. Generally, light sources, such as incandescent lights, arc lamps, and light emitting diodes, provide a nonuniform light output that is unsuitable for direct use, so the light is typically homogenized in a diffusing cavity before illuminating a display unit. The display unit is often a reflective display unit, for example a reflective liquid crystal display panel, an array of tunable mirrors or "electronic paper". A polarization sensitive mirror is often used to direct light from the light source to the display unit.

The light source and display unit are typically mounted separately from each other on the display system housing, and are electrically connected via flex circuitry. This approach results in high component and fabrication costs, and a fault in the flex circuitry or in the connectors is often a primary failure mechanism for the display system.

Therefore, there is a need for a display system that is less expensive to fabricate and is more reliable than current display systems.

### SUMMARY OF THE INVENTION

Generally, the present invention relates to an illumination system for a reflective display. The invention is believed to be particularly useful for microdisplays that use reflective displays. In the display system of the invention, the light source and display unit are mounted in a coplanar manner. This permits the light source and the display unit to be mounted on a single board, or even on a single substrate. Thus, the assembly costs may be reduced, and the reliability increased since the system is simpler, has fewer components, and omits the connectors and the flex circuit which tend to be unreliable.

One particular embodiment of the invention is an illuminated display device that includes a light source directing light generally along a first axis and a reflective image display unit disposed with an optical axis substantially parallel to the first axis. A reflective polarizing film is disposed to direct light from the first light source to the reflective image light display unit. The light source may include a reflector to direct light to the reflective polarizing film.

Another particular embodiment of the invention is an illuminated display device that includes light generating

2

means for emitting diffuse, polarized light along a first direction and reflective display means for modulating reflected light with an image, the reflective display means having an optical axis substantially parallel to the first axis. Reflective polarizing means are disposed to direct the diffuse, polarized light from the light generating means to the reflective display means.

In another embodiment of the invention, an optical system includes a display device that has a first light source directing light generally along a first axis and a reflective image display unit disposed with an optical axis substantially parallel to the first axis. A reflective polarizing film is disposed to direct light from the first light source to the reflective image light display unit. A controller is coupled to the reflective image display unit to control the image formed by the reflective image display unit. Viewing optics transport the image formed by the reflective display unit to a user.

The above summary of the present invention is not intended to describe each illustrated embodiment or every implementation of the present invention. The figures and the detailed description which follow more particularly exemplify these embodiments.

### BRIEF DESCRIPTION OF THE DRAWINGS

The invention may be more completely understood in consideration of the following detailed description of various embodiments of the invention in connection with the accompanying drawings, in which:

FIG. 1 schematically illustrates a reflective display system;

FIG. 2 illustrates a schematic of a camera having an electronic viewfinder;

FIG. 3 schematically illustrates a microdisplay connected to a controller and a computer;

FIG. 4 schematically illustrates an optically folded reflective display system;

FIG. 5 schematically illustrates an embodiment of a reflective display system of the present invention;

FIGS. 6A–6D schematically illustrate embodiments of light sources according to the present invention;

FIGS. 7A and 7B schematically illustrate reflective displays with different embodiments of reflector according to the present invention;

FIGS. 8A–8C schematically illustrate different embodiments of polarizing beamsplitter according to the present invention;

FIGS. 9A–9G schematically illustrate different embodiments of reflective display according to the present invention;

FIG. 10 schematically illustrates a method of vacuum-forming a doubly curved polarizing beamsplitter;

FIG. 11A schematically illustrates an embodiment of the present invention used in Example 1;

FIGS. 11B and 11C respectively illustrate schematic side and top views of the embodiment illustrated in FIG. 11A;

FIG. 12 schematically illustrates the embodiment of the invention used in Example 2;

FIG. 13 schematically illustrates the embodiment of the invention used in Example 3;

FIG. 14A schematically illustrates an embodiment of the present invention used in Example 4;

FIG. 14B illustrates a schematic side view of the embodiment illustrated in FIG. 14A;

FIG. 15A schematically illustrates an embodiment of the present invention used in Example 5; and

FIG. 15B illustrates a schematic side view of the embodiment illustrated in FIG. 15A.

While the invention is amenable to various modifications and alternative forms, specifics thereof have been shown by way of example in the drawings and will be described in detail. It should be understood, however, that the intention is not to limit the invention to the particular embodiments described. On the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the appended claims.

#### DETAILED DESCRIPTION

The present invention is applicable to reflective displays and is believed to be particularly useful for microdisplays that employ reflective display devices. Amongst the advantages provided by the invention are a reduction in manufacturing costs for a display system and an increased reliability.

Reflective displays are used in several types of information display system. FIG. 1 illustrates basic elements of a reflective display 100. A light source 102 transmits polarized light 104 to a reflective image display unit 106. The reflective image display unit 106 may be a liquid crystal display (LCD) unit, for example a LCD on silicon (LCOS) display. Light 108 reflected by the reflective image display unit 106 is directed to a polarizer 110. Light 112 transmitted through the polarizer 110 is then transmitted through viewing optics 114, which may include one or more lenses, that transmit the image to the viewer. In this arrangement, LCD unit modulates the incident light by rotating the polarization of some of the incident light by 90°. Reflected light 108 whose polarization has been rotated is transmitted by the polarizer 110 to the viewing optics 114. Reflected light whose polarization remains unrotated is not transmitted by the polarizer 110, and is typically absorbed or reflected. The polarizer 110, therefore, separates the image light from non-image light. The viewing optics 114 may be, for example, an eyepiece.

The reflective image display unit 106 may also be a different type of unit, for example an array of individually movable miniature mirrors, such as the Digital Micromirror Device™ produced by Texas Instruments, or may be based on the use of so-called “electronic paper”, such as an electrophoretic display manufactured by E-Tek Inc., or a gyricon-based display manufactured by Xerox Corp. The invention is particularly advantageous for a reflective image display unit that modulates the incident light based on polarization rotation, such as an LCD, but may also be used for other types of reflective image display units.

Examples of where a reflective display may be used include microdisplays, for instance, in a viewfinder of an electronic camera. Electronic cameras include video cameras and digital cameras, and any other device that converts an optical image to electronic form. For example, a video camera 200, as illustrated in FIG. 2, records an image of an object 202. The user views an image 204 of the object 202 through a viewfinder 206 by placing his or her eye close to the viewing aperture 208.

Microdisplays may also be used elsewhere, for example in head-mounted displays such as DVD viewers, virtual reality goggles, wearable computer displays and internet appliances. A general approach to using a microdisplay is illustrated in FIG. 3, which shows microdisplay 302, which typically includes a light source, reflective image display unit and viewing optics, coupled to a controller 304. The controller 304 may be, for example, a DVD player which is

coupled to direct the image from the DVD player to the microdisplay 302. The controller 304 may also be coupled to, or part of, a computer system 306 to display information from the computer system, for example in a heads-up display, virtual reality goggles or as a display for a wearable computer. The microdisplay 302 may also be used in a wearable display for a laptop or other type of computer.

It will be appreciated that reflective displays are not restricted to use in microdisplays, but may also be used in larger displays, for example projection displays and heads-up displays.

One particular arrangement for a reflective display that may be used in a microdisplay is illustrated in FIG. 4. The reflective display 400 includes a three-color light emitting diode (LED) 402 for generating light. Light from the LED 402 is directed to a diffuser 404 that mixes and homogenizes the color of the light that is subsequently incident on the reflective image display unit 406. A pre-polarizer 408 polarizes the light that has passed through the diffuser so that light of only one polarization is incident on the reflective image display unit 406.

A brightness enhancer 410 may be placed before the diffuser 404 to enhance the brightness of the light reaching the reflective image display unit 406. For example, the brightness enhancer 410 may be a film having a prismatic structure on an input surface to direct off-axis light from the LED 402 towards the axis 412, such as BEF brightness enhancing film manufactured by 3M Company of Minnesota. Light reflected by the BEF brightness enhancing film may be recirculated by a diffusely reflecting cavity 413 containing the LED 402.

The brightness enhancer 410 may also be a reflective polarizing film whose transmission polarization state is substantially aligned with the transmission polarization state of the pre-polarizer 408. If a reflective polarizing film is used as the brightness enhancer 410, the LED 402 is advantageously enclosed within a diffusely reflecting cavity 413 so that the polarization of the light reflected by the brightness enhancer 410 may be randomized as it recirculates within the diffusely reflecting cavity. Randomization of the polarization results in a greater fraction of the light generated by the LED 402 being transmitted by the reflective brightness enhancer 410, thus increasing the optical efficiency of the reflective display 400. One example of a reflective polarizing film that may be used as brightness enhancer 410 is DBEF multilayer optical film manufactured by 3M Company of Minnesota.

Light transmitted by the pre-polarizer 408 is polarized in the block polarization state of a polarizing beamsplitter 412, that is the polarization state orthogonal to the transmission polarization state of the polarizing beamsplitter 412. Therefore, the light is reflected by the polarizing beamsplitter 412 towards the reflective image display unit 406. The reflective image display unit 406 spatially modulates the incident light 414 by polarization rotation. The reflected light 416 contains light in both the block and the pass polarizations for the polarizing beamsplitter 412. Only that light in the pass polarization of the polarizing beamsplitter 412, the image light 418, is transmitted to the eyepiece 420. A clean-up polarizer 422 may be placed between the polarizing beamsplitter 412 and the eyepiece 420 to enhance the contrast of the image viewed by the user. The use of the polarizing beamsplitter 412 for reflecting the illumination light from the LED 402 and for separating the image light 418 enables the reflective display 400 to be more compact.

## 5

The reflective image display unit **406**, the polarizing beamsplitter **412** and the clean-up polarizer **422** are typically disposed within a housing **424**.

There are, however, certain disadvantages with the arrangement for the reflective display **400**. For example, the light source, including LED **402**, the diffuser **404** and the pre-polarizer **408** is typically mounted on a light source board **426** while the reflective image display unit **406** is mounted on a display board **428**, and the two boards **426** and **428** are separately attached to the housing **424**. Typically the two boards **426** and **426** are electrically coupled using connectors and flex circuits. This can add significant manufacturing and assembly cost to the display system. Furthermore, the system complexity is increased and the flex circuits lower manufacturing yields and long term reliability.

The present invention is directed to a reflective display where the light source and the reflective image display unit are mounted in a coplanar manner. In other words, the light source is mounted so that its light is generally directed along a first axis that is parallel to the optical axis of the reflective image display device. An advantage of this approach is that the light source and the reflective image display unit may be mounted on a shared board, thus reducing assembly costs. This permits the light source and the reflective image display unit to be soldered to a printed circuit board using standard and relatively inexpensive printed circuit fabrication techniques. The light source and reflective image display unit may even be formed on the same substrate, for example by evaporation or sputtering, or other fabrication method, of the appropriate materials to form an organic or inorganic LED, thus further reducing assembly costs. Furthermore, the flex circuits are eliminated, which not only reduces manufacturing costs, but also eliminates low reliability components.

A schematic view of one embodiment of the present invention is illustrated in FIG. 5. The reflective display **500** includes a light source **502** that generally generates light parallel to the first axis **504**. It will be appreciated that a light source such as an LED, tungsten bulb or the like, produces light into a large cone angle. However, the direction of maximum intensity, also known as the chief ray, is substantially parallel to the first axis **504**.

The reflective image display unit **506** is disposed with its optical axis **508** substantially parallel to the first axis, in other words is mounted coplanar with the light source **502**. Light **510** from the light source **502** reflects off at least one reflecting surface, and some light reflects off two reflecting surfaces, before being incident on the reflective image display unit **506**. The reflecting surfaces may be provided by a polarizing beamsplitter **512**, or a combination of a polarizing beamsplitter **512** and another reflector **514**, as is explained more fully below. The reflector **514** may be considered to be part of the light source. A clean-up polarizer **516** may be disposed to enhance the polarization of the light transmitted through the polarizing beamsplitter **512** to increase contrast in the image seen by the viewer. The clean-up polarizer **516** removes, through reflection or absorption, stray light of the polarization normally reflected by the polarizing beamsplitter **512** that may have leaked through the polarizing beamsplitter **512**.

Different embodiments of a light source are illustrated in FIGS. 6A–6D. The first embodiment of light source **600**, illustrated in FIG. 6A, includes a light emitter **602**, which may be a three color LED array, coupled to a diffuser cavity **604**. The diffuser cavity **604** may be hollow or filled with a diffusing material, and includes diffusely reflecting side walls. Light output from the cavity **604** may pass through a lens **606** before reaching a diffuser **608**. The combination of

## 6

the diffusing cavity **604** and the diffuser **608** mix and homogenize the light, thus ensuring that the light emerging through the diffuser is uniform in color and brightness. Light that passes through the diffuser **608** is then passed through a pre-polarizer **610**.

The second embodiment of light source **620**, illustrated in FIG. 6B, includes a light emitter **622**, such as a three color LED array, coupled to a diffuser cavity **624**. The diffuser cavity **624** may be hollow or filled with a diffusing material, and includes diffusely reflecting side walls.

A brightness enhancer **626**, for example a prismatic film or reflective polarizing film as described above, may be disposed to intercept light transmitted outwards from the cavity **624**. Where the brightness enhancer **626** is a prismatic film, light falling outside a specific angular range is reflected back to the diffuser cavity **624**, while light falling within a desired angular range is transmitted. Where the brightness enhancer **626** is a reflective polarizer, light in the block polarization state is reflected to the diffuser cavity **624**, while light in the pass polarization state is transmitted. The light returned to the diffusing cavity is recirculated and its direction and/or polarization randomized, so that it may be transmitted through the brightness enhancer on a succeeding pass to the brightness enhancer **626**.

A lens **628**, such as a curved lens or a Fresnel lens, may be disposed to redirect the light transmitted by the brightness enhancer **626** so as to fall within a narrower cone angle.

The light transmitted out of the cavity **624** illuminates a diffuser **630**. The combination of the diffuser **630** and the diffusing cavity **624** is used to make the light emitted from the light source **620** uniformly bright and have uniform color.

A third embodiment of light source **640**, illustrated in FIG. 6C, employs a light emitter **642**, which may be a three-color LED array, a diffuser **646** and a pre-polarizer **648**. Light from the light emitter **602** is coupled to the diffuser via a light guide **644**. The light guide **644** may be, for example, a solid, clear plastic pipe which traps and reflects the light, via total internal reflection at its side walls, or by reflection off side walls coated with a suitably reflective material, to an output window **645**. The window **645** may be capped with a diffuser or be roughened, the walls of the light guide **644** may be roughened, or the material within the light guide **644** may itself be diffusing, in order to homogenize the light.

A fourth embodiment of a light source **660**, illustrated in FIG. 6D employs a light guide incorporating side extraction for directing the light from a light emitter towards a reflective beamsplitter **512**. Light from a light emitter **662**, for example a three-color LED unit, enters the light guide **664**. The light is extracted through the output face **666** of the light guide **664** by facets or other light scattering features **668** on the disposed on the left hand face **670**. The direction and divergence of the light **672** output through the output face **666** may be conditioned by the extraction features **668**. For example, the extraction features **668** may be directed at a specific angle or partially collimated. The light **672** exiting the light guide **664** may be further conditioned, for example collimated or partially collimated, by an array **674** of lenslets the output face **666**.

Propagation of the light through the light guide **664** may result in mixing and homogenization of the light from the light emitter **662**. The light **672** output from the light guide may be further homogenized by a diffuser **676**. In addition, light diffusing particles may be embedded within a portion, or all, of the light guide **664** to further mix and homogenize the light.

The light **672** may be polarized by a pre-polarizer **678**. The pre-polarizer **678** may be a linear polarizer, for example a dichroic absorber or a reflective polarizer, or may be a circular polarizer, for example a cholesteric polarizer or a dichroic absorber combined with a quarter-wave retarder film.

The lenslet array **674**, diffuser **676** and pre-polarizer **678** may be positioned in a region of greatest extraction from the light guide **664** in order to facilitate mixing within the guide for homogenization or to place the outgoing light **672** at an appropriate height for illuminating the polarizing beamsplitter **512**.

One of the advantages afforded by this embodiment **660** is its compactness in the direction parallel to the input surface of the reflective image display unit **506**.

It will be appreciated that many different types of light source may be used, in addition to variations of the four embodiments illustrated in FIGS. **6A–6D**. For example, different types of light emitter may be used, such as incandescent light bulbs, halogen lamps, arc lamps, or any other suitable light emitter. The light emitter may also include a shaped reflector, for example a parabolic reflector, in order to redirect emitted light towards the output of the light source.

The pre-polarizer may be a linear polarizer, for example a polymeric multiple layer reflective polarizing film, as described in U.S. Pat. No. 5,612,820, or a wire grid polarizer, for example as described in WO 94/11766, "A Reflective Polarizer". The pre-polarizer may also be a circular polarizer, for example a cholesteric polarizer as described in U.S. Pat. No. 5,506,704. A cholesteric polarizer is particularly useful where the reflective image display unit is based on the modulation of circularly polarized light.

Likewise, a polarizing brightness enhancer may be formed from a multiple layer reflective polarizing film, a wire grid polarizer or a cholesteric polarizer.

Any number of light emitters may be combined in a single light source using this technique, for increased brightness and for covering larger area displays. Furthermore, a reflective display may use more than one light source.

Where light from the light source **502** is reflected off two reflecting surfaces to reach the reflecting image display unit, a reflector **514** may be used for the first reflection and a polarizing beamsplitter **512** used for the second reflection. The reflector **514** may be part of the light source **502**.

The reflector **514** may be made of a metal-coated substrate (plastic or metal), polished metal, a stamped metal sheet, thermoformed metal coated film, a thermoformed multi-layer optical film, or other suitable reflecting material. Furthermore, the reflector **514** may be flat, as illustrated in FIG. **5**, or may be curved in one or two directions to increase illumination uniformity and efficiency. For example, a reflector **714** that is curved in one direction is illustrated in FIG. **7A**. The figure illustrates a light source **702** and a reflective image display device **706**, mounted in a coplanar fashion. The optical axes **704** and **708** of the light source **702** and reflective image display device **706** are also illustrated. The optical axes **704** and **708** are parallel to the z-direction, and the reflective image display device **706** is translated laterally from the light source **702** in the x-direction. A radius of curvature,  $r$ , of the curved reflector **714** lies in the x-z plane.

The divergence of light in the x-z plane, emitted from the light source **702**, is reduced upon reflection from the curved reflector **714**. The light is directed to the polarizing beamsplitter **712** for transmission to the reflective image display device **706**.

A reflector **734** that is curved in two directions is illustrated in FIG. **7B**. In this case, the reflector **734** has a first radius of curvature lying in the x-z plane and a second radius of curvature lying in the y-z plane, where the y-direction is directed out of the plane of the figure, and is orthogonal to both the x and z directions. Light emitted from the light source **702** has its divergence reduced in both the x-z and y-z planes upon reflection from the reflector **734**.

It will be appreciated that the reflector may also be singly curved with a radius of curvature in the y-z plane.

The polarizing beamsplitter **512** typically reflects light having one polarization and transmits light having the orthogonal polarization. The polarization may be linear or circular. One particular example of linear polarizer that may be used as the polarizing beamsplitter is a polymeric multiple layer polarizing film, such as DBEF manufactured by 3M Company, Minnesota. This is useful as a polarizing beamsplitter since it maintains a high degree of extinction over a wide spectral and angular range. Furthermore, this type of film may readily be deformed in one or two directions to form curved mirrors to more efficiently collect light from the light source, and to lower the overall profile of the illumination system. Another type of linear polarizer also suitable for use as the polarizing beamsplitter **512** is a wire grid polarizer.

The polarizing beamsplitter **512** may also be a circular polarizer, and may be a cholesteric polarizer. It will be appreciated that use of a cholesteric polarizer may also necessitate the introduction of a quarter wave retarder in order to convert light between linear and circular polarization. For example, where the reflective image display unit **506** operates on linearly polarized light and the light from the light source is also linearly polarized, then the cholesteric polarizer may be provided with a quarter wave retarder layer on its front surface so as to circularize the polarization of the light prior to incidence on the surface of the cholesteric polarizer. Furthermore, the quarter wave retarder linearizes the polarization of the reflected light before propagating to the reflective image display unit **506**. Where the light from the light source is circularly polarized, the reflective image display unit **506** may be provided with a quarter wave retarder at its input so as to linearize the polarization of the light reflected from the cholesteric polarizer.

The polarizing beamsplitter **512** may be flat, or curved in one or two directions, as illustrated in FIGS. **8A–8C**, which show different types of polarizing beamsplitter positioned close to a reflective image display unit **806**. Each polarizing beamsplitter may be provided with a clean-up polarizer **816**. The polarizing beamsplitter **812** illustrated in FIG. **8A** is flat. The clean-up polarizer may be disposed immediately behind the polarizing beamsplitter **812**. The polarizing beamsplitter **822** illustrated in FIG. **8B** is curved in one direction. In other words, the polarizing beamsplitter **822** has a radius of curvature lying in the x-z plane, in a manner similar to that described above for the reflector in FIG. **7A**.

Advantages of the using polarizing beamsplitter that is flat or is curved in one dimension include the ability to directly laminate the clean-up polarizer **816** to the rear surface of the polarizing beamsplitter **822**. Furthermore, simple mechanical devices may be used to provide the shape to the polarizing beamsplitter. For example, the polarizing beamsplitter **822** may be formed from a sheet of material that is constrained at its two opposite ends where the separation between the constraints is less than the overall length of the film so that the film buckles to take on a curved shape. In another example, the polarizing beamsplitter **822** may be formed from a sheet of material that is federal into a curved

slot that conforms the sheet to the desired curvature. Both of these advantages reduce manufacturing costs.

A polarizing beamsplitter **832** that is curved in two directions is illustrated in FIG. **8C**. This polarizing beamsplitter **832** has a first radius of curvature lying in the x-z plane, and a second radius of curvature lying in the y-z plane. A flat clean-up polarizer **816** may be positioned above the polarizing beamsplitter **832**.

The doubly curved polarizing beamsplitter **832** may be shaped by vacu-forming. Furthermore, a laminate of polarizing beamsplitter and clean-up polarizer may be vacu-formed so that the clean-up polarizer does not need to be mounted separately within the display.

One particular method of vacu-forming a doubly curved polarizing beamsplitter **832** is illustrated with respect to FIG. **10**. A multilayer reflective polarizer optical film **1002** is stretched over a hole **1004** in a plate **1006**. A vacuum is applied to pull the film **1002** through the hole **1004**. Heat is applied using a heat gun to soften the film **1002** and to deepen the sag, forming a concave surface. When cooled, the film **1002** retains the concave shape. Using this technique for forming a doubly curved polarizing beamsplitter, the polarization extinction is maintained out to the edge of the concave shape. A curved polarizing beamsplitter **832** having an elliptical edge may also be made by vacu-forming through an elliptical hole **1004**. The transmission axis of the curved polarizing beamsplitter may be controlled by aligning the optical axes of the film **1002** to the major axis of the hole **1004**.

A singly curved polarizing beamsplitter **822** generally shows higher polarization extinction over a wider angular range than the doubly curved polarizing beamsplitter **832** PBS, owing to the higher range of angles of incidence on the doubly curved surface. Thus, it becomes increasingly more important to use a clean-up polarizer **816** with a doubly-curved polarizing beamsplitter **832**. A doubly curved beamsplitter assembly may be formed by first laminating the clean-up polarizer **816** to the polarizing beamsplitter **832** to form a lamination, and then vacu-forming the lamination using the vacu-forming technique illustrated in FIG. **10**.

It will be appreciated that the polarizing beamsplitter may be singly curved with a radius of curvature in the y-z plane.

Different embodiments of polarizing beamsplitter are presented in the display devices shown in FIGS. **9A–9G**. Each display device includes a light source **902** and a reflecting image display device **906**. In several of the illustrated embodiments, the reflector **914** and the polarizing beamsplitter **912** are formed from a single, unitary portion of reflective polarizer material, which reduces manufacturing costs.

In FIG. **9A**, the reflector **914** and polarizing beamsplitter **912** are formed from a single unitary portion of the reflective polarizer material **918**. The unitary portion of reflective polarizer material **918** is singly curved, and may have different curvatures for the reflector **914** and the polarizing beamsplitter **912**. A clean-up polarizer **916** may be laminated to the rear surface of the unitary portion of reflective polarizer material **918**, or may be disposed elsewhere to clean up the polarization of light transmitted through the polarizing beamsplitter **912**.

In FIG. **9B**, the polarizing beamsplitter **922** extends over both the light source **902** and the reflecting image display unit **906** to collect light directly from the light source **902** and direct it to the reflective image display unit **906**. The polarizing beamsplitter **922** may be doubly curved, as illustrated, or may be singly curved. A flat clean-up polarizer **926**

may be provided above the polarizing beamsplitter **922**, or may be formed onto the rear surface of the polarizing beamsplitter.

In FIG. **9C**, the reflector **934** and polarizing beamsplitter **932** are formed from a single unitary portion of the reflective polarizer material **938**. The reflector **934** may be doubly curved, as illustrated, may be singly curved, or may be flat.

The polarizing beamsplitter **932** may be flat, as illustrated, may be singly curved or may be doubly curved. A clean-up polarizer **936** may be disposed to clean-up the polarization of light transmitted through the polarizing beamsplitter **932** from the reflective image display unit **906**. The clean-up polarizer **936** may be laminated or otherwise attached to the polarizing beamsplitter **932**.

Different variations of the embodiment illustrated in FIG. **90** are shown in FIGS. **9D** and **9E**. In FIG. **9D**, the reflector **934** is doubly curved, and the polarizing beamsplitter **932** is singly curved. In FIG. **9E**, both the reflector **934** and the polarizing beamsplitter **932** are doubly curved. It will be appreciated that flat, singly curved and doubly curved reflectors **934** may be combined in different ways with flat, singly curved and doubly curved polarizing beamsplitters **932**. Furthermore, the clean-up polarizer **932** may extend over both the reflector **934** and the polarizing beamsplitter **936**, for example as illustrated in FIG. **9E**.

In the embodiment illustrated in FIG. **9F**, the light source is distributed. A light emitter directs light to the reflector **944**. A diffuser/polarizer **943**, including a diffuser and a pre-polarizer, is positioned between the reflector **944** and the polarizing beamsplitter **946** so that light is diffused and polarized by the diffuser/polarizer **943** after reflection by the reflector **944**. An advantage of this embodiment is that there may be greater overlap of light beams from multiple emitters prior to diffusion and polarization, resulting in an enhanced illumination uniformity.

The invention is not limited to single light sources. Multiple light sources may be placed in coplanar positions relative to the reflective image display unit **906** to increase brightness or to improve illumination uniformity of the reflective image display unit **906**. One particular embodiment using multiple light sources is illustrated in FIG. **9G**. In this particular embodiment, the polarization beamsplitter **952** extends over the two light sources **902** as well as the reflective image display unit **906**. Light from the light sources **902** is reflected to the reflective image display unit **906** which modulates and reflects the light back to the reflective polarizer **952**. The modulated light is transmitted through the polarizing beamsplitter **952** to the viewer. A clean-up polarizer **956** may be disposed to clean-up the light transmitted through the polarizing beamsplitter.

Different reflector and beamsplitter designs have been explored for effectiveness in illuminating a reflective image display unit. The major characteristics of interest in designing a reflector/beamsplitter combination include the efficiency with which light from the light source is directed onto the surface of the reflective image display unit within the display unit's acceptance cone, and the uniformity of illumination across the reflective image display unit. An additional parameter that was studied was the maximum height of the reflector/beamsplitter combination above the display unit. This last parameter is important in designing display units that are used in confined spaces, for example in a camcorder or other type of camera. In the examples described below, the illumination of a display unit was calculated for a particular configuration of reflector and beamsplitter.

## 11

## EXAMPLE 1

In the first example, illustrated in FIGS. 11A–11C, the light source **1102** was assumed to include a light emitting diode followed by a diffuser. The light source **1102** was centered at a point approximately 5 units from the center of an LCD display unit **1104**. Since the display illumination system scales linearly with size, dimensions are presented in arbitrary “units” rather than in any particular linear measure. The light source **1102** was assumed to have a Lambertian, uniformly emitting surface, having a size 1 unit×1.6 units. The short dimension was aligned parallel to direction of separation between the light source **1102** and the LCD display unit **1104**. The LCD display unit **1104** was assumed to be 2.88 units×3.84 units, oriented with its long dimension parallel to the separation direction between the LCD display unit **1104** and the LED **1102**. The emitting surface of the LED **1102** was assumed to be 0.98 units higher than the surface of the liquid crystal layer of the LCD display unit **1104**.

The polarizing beamsplitter **1112** was assumed to be formed as a flat sheet positioned above the LCD display unit **1104** at an angle of 40° relative to the upper surface **1104a** of the display unit **1104**.

The reflector **1114** was assumed to have a “tapered box” shape, being formed with an upper reflecting surface **1314a**, and side reflecting surfaces **1314b** (only one side reflecting surface shown in FIGS. 11A and 11B). The shape of the upper surface **1314a** was formed using an AUTOCAD spline function that connected the following points in the (x,z) plane: (5.5804, -0.2035), (5.9644, 0.9476), (5.6674, 1.6398), (5.1616, 2.2553), (4.1499, 3.2774), and (3.0478, 4.5078). The tangent at the first point was set by the point (5.7462, 0.1190) and the tangent to the last point was set by the point (3.5694, 3.9642). The cross-sectional shape formed by the “tapered box” was rectangular, and the aspect ratio of the rectangular cross-section was preserved throughout its length, from the light source **1102** to the output end.

The combination of flat beamsplitter **1112** and “tapered box” reflector **1114** produced the following results. The efficiency of illuminating the LCD display unit **1104** was 4.6%. The efficiency was defined as the ratio of light entering the LCD display unit **1104** within its acceptance cone angle over the total amount of light emitted by the light source **1102**. The uniformity of illumination was measured by the ratio of the brightness of the maximum of illumination intensity on the LCD display unit **1104** over the brightness of the minimum illumination intensity on the LCD display unit **1104**. In this particular case, the max/min ratio was 3.34. Lastly, the height, H, the maximum beamsplitter height above the LCD display unit **1104** required to enable this particular combination of reflector and beamsplitter to operate most effectively, was 5.57 units.

## EXAMPLE 2

In the second example, illustrated in FIG. 12, the light source **1102** and LCD display unit **1104** were assumed to have the same size and relative spacing as in Example 1. The only differences between the design of Example 1 and Example 2 were in the shapes of the reflector and the

## 12

beamsplitter. The beamsplitter **1212** was assumed to have a singly curved shape, forming a 41° arc having a radius of curvature of 11.903 units. The reflector **1214** was assumed to be flat and oriented at 47° to the emitting surface of the light source **1102**.

For this particular combination, the illumination efficiency was 3.4%, the max/min ratio was 2.8 and the height, H, was 4.53 units. The overall illumination efficiency was less than in Example 1 because the flat reflector is not as good at gathering the light from the light source **1102** and presenting it to the beamsplitter for reflection to the LCD display unit **1104**. On the other hand, the illumination uniformity is increased through the use of the curved beamsplitter. Also, use of the curved beamsplitter results in a reduction in the overall height, H.

## EXAMPLE 3

In the third example, illustrated in FIG. 13, the light source **1102** and LCD display unit **1104** were assumed to have the same size and relative spacing as in Example 1. The only differences between the design of Example 1 and Example 3 were in the shapes of the reflector and the beamsplitter. The beamsplitter **1312** was assumed to have the same shape as in Example 2. The reflector was assumed to be a singly-curved reflecting surface, having a curved profile matching the curved profile of the upper reflector **1114a** described for Example 1.

For this particular combination, the illumination efficiency was 4.6%, the max/min ratio was 1.93 and the height, H, was 4.53 units. The human eye is typically able to detect a max/min ration in excess of about 2, so this design approaches the region of acceptable uniformity where the eye does not detect any nonuniformity.

## EXAMPLE 4

In the fourth example, illustrated in FIGS. 14A and 14B, the light source **1102** and LCD display unit **1104** were assumed to have the same size and relative spacing as in Example 1. Furthermore, the reflector **1414** was assumed to have the same “tapered box” shape as described for the reflector **1114** in Example 1. The only difference between the design of Example 1 and Example 4 was in the shape of the beamsplitter **1412**. The beamsplitter **1412** was assumed to have the same arcuate shape as in Example 2.

For this particular combination, the illumination efficiency was 8.2%, the max/min ratio was 1.25 and the height, H, was 4.53 units.

## EXAMPLE 5

In the fifth example, illustrated in FIGS. 15A and 15B, the light source **1102** and LCD display unit **1104** were assumed to have the same size and relative spacing as in Example 1. Furthermore, the beamsplitter **1512** was assumed to be the same as in Example 4. The reflector **1514** was assumed to have the same general “tapered box” shape as in Example 4. However, rather than having the upper surface **1514a** meet the side surfaces **1514b** at right angles, the corners **1514c** between the upper surface **1514a** and sides **1514b** were curved. For this particular combination, the illumination efficiency was 6.7%, the max/min ratio was 1.52 and the height, H, was 4.53 units. The results for the five examples are summarized in Table I.

TABLE I

Summary of Illumination Characteristics for Different Reflector/Beamsplitter Combinations					
	Reflector	Beamsplitter	Max/Min	Eff.	H (arb. units)
Ex. 1	tapered box square corners	flat	3.34	4.6%	5.57
Ex. 2	flat	single curve arcuate	2.80	3.4%	4.53
Ex. 3	single curve spline	single curve arcuate	1.93	4.6%	4.53
Ex. 4	tapered box square corners	single curve arcuate	1.25	8.2%	4.53
Ex. 5	tapered box rounded corners	single curve arcuate	1.52	6.7%	4.53

While various examples were provided above, the present invention is not limited to the specifics of the illustrated embodiments. As noted above, the present invention is believed to be particularly applicable to illumination sources requiring a uniform, or substantially uniform, light output. Accordingly, the present invention should not be considered limited to the particular examples described above, but rather should be understood to cover all aspects of the invention as fairly set out in the attached claims. Various modifications, equivalent processes, as well as numerous structures to which the present invention may be applicable will be readily apparent to those of skill in the art to which the present invention is directed upon review of the present specification. The claims are intended to cover such modifications and devices.

We claim:

1. An optical system, comprising:
  - a first light source mounted to a first position on a substantially planar mount surface of a mount and directing light generally along a first axis;
  - an image display unit mounted to a second position on the mount surface different from the first position, with an optical axis substantially parallel to the first axis; and
  - a reflective polarizing film disposed to direct light from the first light source to the image light display unit.
2. A system as recited in claim 1, further comprising a viewing port for a user to view an image formed by the image display unit, and the reflective polarizing film is disposed between the image display unit and the viewing port.
3. A system as recited in claim 1, further comprising a clean up polarizer disposed to polarize light transmitted through the reflective polarizing film from the image display unit.
4. A system as recited in claim 1, wherein the reflective polarizing film is curved.
5. A system as recited in claim 1, further comprising a reflector disposed to direct light from the first light source to the reflective polarizing film.
6. A system as recited in claim 5, wherein at least one of the reflector and the reflective polarizing film is curved in at least one dimension to form a curved reflector.
7. A system as recited in claim 1, wherein the first light source includes a light emitter to emit light and a pre-polarizer to polarize light from the light emitter, the light polarized by the pre-polarizer being directed to the image display unit.
8. A system as recited in claim 7, wherein the first light source further includes a reflector disposed to direct light from the light emitter to the reflective polarizing film.

9. A system as recited in claim 7, further comprising a diffuser disposed on an optical path for light passing from the light emitter and the image display unit.

10. A system as recited in claim 7, wherein the light emitted by the light emitter is directed to the image display unit by at least two reflecting surfaces, the reflective polarizing film forming a final reflecting surface closest to the image display unit along an optical path between the light emitter and the image display unit.

11. A system as recited in claim 10, wherein the pre-polarizer is disposed along the optical path between the final reflecting surface and a previous reflecting surface.

12. A system as recited in claim 10, further comprising a diffuser disposed along the optical path between the pre-polarizer and a previous reflecting surface.

13. A system as recited in claim 10, further comprising a light guide disposed between the light emitter and the pre-polarizer, the light guide having an output end to transmit light out of the light guide to the pre-polarizer.

14. A system as recited in claim 13, wherein the light guide comprises a light diffuser.

15. A system as recited in claim 7, further comprising a light guide coupled to receive light from the light emitter, the light guide having a rear surface and an output surface, the rear surface being provided with light extraction features to direct light propagating within the light guide out through output surface towards the pre-polarizer.

16. A system as recited in claim 15, wherein the light guide comprises a diffuser.

17. A system as recited in claim 7, wherein the light emitter comprises one or more light emitting diodes (LEDs).

18. A system as recited in claim 17, wherein light propagating from the one or more LEDs to the image-display unit is white light.

19. A system as recited in claim 1, further comprising a second light source disposed to direct light to the image display unit by reflection off the reflective polarizing film.

20. A system as recited in claim 1, wherein the first light source and the image display are disposed on the mount surface in a coplanar manner.

21. A system as recited in claim 1, wherein the mount is a substrate common to the first light source and the image display.

22. A system as recited in claim 1, wherein the first light source and image display are mounted side by side on the mount surface.

23. A system as recited in claim 1, wherein the mount is a circuit board and the mount surface is a surface of the circuit board.

24. A system as recited in claim 1, wherein at least one of the first light source and the image display unit is mounted directly to the mount surface.

25. A system as recited in claim 1, further comprising a controller coupled to the image display unit to control the image formed by the image display unit and viewing optics disposed to transport the image formed by the image display unit to a user.

26. A system as recited in claim 25, further comprising a camera unit coupled to the controller, the controller being configured to control the image display unit to display an image corresponding to an object image received by the camera.

27. A system as recited in claim 26, wherein the camera unit is a video camera.

28. A system as recited in claim 26, wherein the camera unit is a digital camera.

29. A system as recited in claim 25, further comprising a computer coupled to the controller to display information generated by the computer.

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 7,057,814 B2  
APPLICATION NO. : 11/070806  
DATED : June 6, 2006  
INVENTOR(S) : Gary T. Boyd

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 1,

Line 8, delete "10,854,943" and insert in place thereof -- 10/854,943 --.

Line 10, after "09/498,801" insert -- , --.

Column 10,

Line 16, delete "90" and insert in place thereof -- 9C --.

Signed and Sealed this

Nineteenth Day of December, 2006

A handwritten signature in black ink on a dotted background. The signature reads "Jon W. Dudas" in a cursive style.

JON W. DUDAS

*Director of the United States Patent and Trademark Office*