

US007083012B2

(12) **United States Patent**  
**Vogel et al.**

(10) **Patent No.:** **US 7,083,012 B2**  
(45) **Date of Patent:** **Aug. 1, 2006**

(54) **MOTORIZED TRACTION DEVICE FOR A PATIENT SUPPORT**

(75) Inventors: **John David Vogel**, Columbus, IN (US); **Thomas W. Hanson**, Loveland, OH (US); **Craig Crandall**, Greensburg, IN (US); **Joseph A. Kummer**, Cincinnati, OH (US); **Michael M. Frondorf**, Lakeside Park, KY (US); **David P. Lubbers**, Cincinnati, OH (US); **Ronald P. Kappeler**, Batesville, IN (US); **Bradley T. Wilson**, Batesville, IN (US); **Darrell L. Metz**, Batesville, IN (US); **Doug K. Smith**, Batesville, IN (US); **Jeffrey A. Ruschke**, Lawrenceburg, IN (US); **John Vodzak**, Batesville, IN (US); **Terry J. Stratman**, Villa Hills, KY (US); **Eric W. Oberhaus**, West Chester, OH (US)

(73) Assignee: **Hill-Rom Service, Inc.**, Wilmington, DE (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/104,228**

(22) Filed: **Apr. 12, 2005**

(65) **Prior Publication Data**  
US 2005/0236193 A1 Oct. 27, 2005

**Related U.S. Application Data**

(63) Continuation of application No. 10/783,267, filed on Feb. 20, 2004, now Pat. No. 6,877,572, which is a continuation of application No. 10/336,576, filed on Jan. 3, 2003, which is a continuation-in-part of application No. 09/853,221, filed on May 11, 2001, now Pat. No. 6,749,034.

(60) Provisional application No. 60/345,058, filed on Jan. 4, 2002, provisional application No. 60/203,214, filed on May 11, 2000.

(51) **Int. Cl.**  
*A16G 7/08* (2006.01)  
*A16G 7/00* (2006.01)

(52) **U.S. Cl.** ..... **180/15**; 180/19.3; 180/9.21; 180/9.22; 180/9.64

(58) **Field of Classification Search** ..... 180/9, 180/9.1, 9.21, 9.22, 9.26, 9.28, 9.3, 9.34, 180/9.62, 9.64, 15, 19.1, 16, 19.3, 209, 65.1, 180/65.5; 5/600, 86.1

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

813,213 A 2/1906 Johnson  
1,110,838 A 9/1914 Taylor  
1,118,931 A 12/1914 Hasley

(Continued)

FOREIGN PATENT DOCUMENTS

CA 2010543 9/1990

(Continued)

OTHER PUBLICATIONS

Stryker Medical, 2040 Zoom™ Critical Care Bed Maintenance Manual, date unknown.

(Continued)


*Primary Examiner*—Lesley D. Morris  
*Assistant Examiner*—Matthew Luby

(74) *Attorney, Agent, or Firm*—Bose McKinney & Evans LLP

(57) **ABSTRACT**

A patient support including a propulsion device for moving the patient support. The patient support includes a propulsion system having a propulsion device operably coupled to an input system.

**2 Claims, 61 Drawing Sheets**



U.S. PATENT DOCUMENTS					
			5,251,429 A	10/1993	Minato et al.
			5,255,403 A	10/1993	Ortiz
1,598,124 A	8/1926	Evans	5,279,010 A	1/1994	Ferrand et al.
1,639,801 A	8/1927	Heise	5,284,218 A	2/1994	Rusher, Jr.
1,778,698 A	10/1930	Walter	5,287,938 A *	2/1994	Welling ..... 180/9.3
2,224,087 A	12/1940	Reichert	5,293,950 A	3/1994	Marliac
2,599,717 A	6/1952	Menzies	5,307,889 A	5/1994	Bohannan
2,635,899 A	4/1953	Osbon, Jr.	5,322,306 A	6/1994	Coleman
2,999,555 A	9/1961	Stroud et al.	5,337,845 A	8/1994	Foster et al.
3,004,768 A	10/1961	Klages	5,348,326 A	9/1994	Fullenkamp et al.
3,112,001 A	11/1963	Wise	5,358,265 A	10/1994	Yaple
3,304,116 A	2/1967	Stryker	5,366,036 A	11/1994	Perry
3,305,876 A	2/1967	Hutt	5,381,572 A	1/1995	Park
3,380,546 A	4/1968	Rabjohn	5,388,294 A	2/1995	Reeder
3,393,004 A	7/1968	Williams	5,406,778 A	4/1995	Lamb et al.
3,452,371 A	7/1969	Hirsch	5,439,069 A	8/1995	Beeler
3,544,127 A	12/1970	Dobson	5,445,233 A	8/1995	Fernie et al.
3,618,966 A	11/1971	Vendervest	5,447,317 A	9/1995	Gehlsen et al.
3,680,880 A	8/1972	Blaauw	5,477,935 A	12/1995	Chen
3,770,070 A	11/1973	Smith	5,495,904 A	3/1996	Zwaan et al.
3,814,199 A	6/1974	Jones	5,526,890 A	6/1996	Kadowaki
3,820,838 A	6/1974	Limpach	5,535,465 A	7/1996	Hannant
3,872,945 A	3/1975	Hickman et al.	5,562,091 A	10/1996	Foster et al.
3,876,024 A	4/1975	Shieman	5,570,483 A	11/1996	Williamson
4,136,888 A *	1/1979	Bowie et al. .... 280/5.22	5,580,207 A	12/1996	Kiebooms
4,137,984 A	2/1979	Jennings	5,613,252 A	3/1997	Yu et al.
4,164,355 A	8/1979	Eaton	5,669,086 A	9/1997	Garman
4,167,221 A	9/1979	Edmonson	5,687,437 A	11/1997	Goldsmith
4,175,632 A	11/1979	Lassanlke	5,690,185 A	11/1997	Sengel
4,175,783 A	11/1979	Pioth	5,697,623 A	12/1997	Bermes et al.
4,274,503 A	6/1981	Mackintosh	5,737,782 A	4/1998	Matsuura et al.
4,275,797 A	6/1981	Johnson	5,749,424 A	5/1998	Reimers
4,415,049 A	11/1983	Wereb	5,775,456 A	7/1998	Reppas
4,415,050 A	11/1983	Nishida	5,806,111 A	9/1998	Heimbrock et al.
4,439,879 A	4/1984	Werner	5,809,755 A	9/1998	Velke et al.
4,444,284 A	4/1984	Montemurro	5,839,528 A	11/1998	Lee
4,475,611 A	10/1984	Fisher	5,868,403 A *	2/1999	Culp et al. .... 280/5.22
4,475,613 A	10/1984	Walker	5,906,017 A	5/1999	Ferrand et al.
4,511,825 A	4/1985	Klimo	5,915,487 A	6/1999	Splittstoesser et al.
4,513,832 A	4/1985	Engman	5,921,338 A	7/1999	Edmondson
4,541,498 A *	9/1985	Pitchford ..... 180/9.26	5,934,694 A	8/1999	Schugt et al.
4,566,707 A	1/1986	Nitzberg	5,937,961 A	8/1999	Davidson
4,584,989 A	4/1986	Stith	5,944,131 A	8/1999	Schaffner et al.
4,598,783 A *	7/1986	Tippen ..... 180/9.32	5,964,313 A	10/1999	Guy
4,629,242 A	12/1986	Schrager	5,964,473 A	10/1999	Degonda et al.
4,671,369 A *	6/1987	Tiffin et al. .... 180/8.1	5,971,091 A	10/1999	Kamen et al.
4,723,808 A	2/1988	Hines	5,983,425 A	11/1999	DiMucci et al.
4,724,555 A	2/1988	Poehner	5,987,671 A	11/1999	Heimbrock et al.
4,759,418 A	7/1988	Goldenfeld et al.	5,988,304 A	11/1999	Behrendts
4,771,840 A	9/1988	Keller	5,996,149 A	12/1999	Heimbrock et al.
4,807,716 A	2/1989	Hawkins	6,016,580 A	1/2000	Heimbrock et al.
4,811,988 A	3/1989	Immel	6,035,561 A	3/2000	Paytas et al.
4,895,040 A	1/1990	Soederberg	6,050,356 A	4/2000	Takeda et al.
4,922,574 A	5/1990	Heiligenthal et al.	6,059,060 A	5/2000	Kanno et al.
4,938,493 A	7/1990	Okuda	6,059,301 A	5/2000	Skarnulis
4,949,408 A	8/1990	Trkla	6,062,328 A	5/2000	Campbell et al.
4,979,582 A	12/1990	Forster	6,065,555 A	5/2000	Yuki et al.
4,981,309 A	1/1991	Froeschle	6,070,679 A	6/2000	Berg et al.
5,060,327 A	10/1991	Celestina et al.	6,073,285 A	6/2000	Ambach et al.
5,060,959 A	10/1991	Davis et al.	6,076,208 A	6/2000	Heimbrock et al.
5,069,465 A	12/1991	Stryker et al.	6,076,209 A	6/2000	Paul
5,083,625 A	1/1992	Bleicher	6,105,348 A	8/2000	Turk et al.
5,084,922 A	2/1992	Louit	6,125,957 A	10/2000	Kauffmann
5,094,314 A	3/1992	Hayata	6,131,690 A	10/2000	Galando et al.
5,117,521 A	6/1992	Foster et al.	6,148,942 A	11/2000	Mackert, Sr.
5,121,806 A	6/1992	Johnson	6,173,799 B1	1/2001	Miyazaki et al.
5,156,226 A	10/1992	Boyer et al.	6,178,575 B1	1/2001	Harada
5,181,762 A	1/1993	Beumer	6,179,074 B1	1/2001	Scharf
5,187,824 A	2/1993	Stryker	6,256,812 B1	7/2001	Bartow et al.
5,201,819 A	4/1993	Shiraishi et al.	6,286,165 B1	9/2001	Heimbrock et al.
5,222,567 A	6/1993	Broadhead et al.	6,330,926 B1	12/2001	Heimbrock et al.
5,232,065 A	8/1993	Cotton	6,343,665 B1	2/2002	Eberlein et al.
5,244,225 A	9/1993	Frycek	6,422,576 B1 *	7/2002	Michaeli et al. .... 280/5.22



# US 7,083,012 B2

6,505,359	B1	1/2003	Heimbrock et al.	JP	59-186554	10/1984
6,626,255	B1 *	9/2003	Timm ..... 180/7.1	JP	60-12058	1/1985
6,725,956	B1	4/2004	Lemire	JP	60-12059	1/1985
6,752,224	B1	6/2004	Hopper et al.	JP	60-21751	2/1985
6,772,850	B1	8/2004	Waters et al.	JP	60-31749	2/1985
6,942,226	B1 *	9/2005	Walkingshaw ..... 280/5.22	JP	60-31750	2/1985

## FOREIGN PATENT DOCUMENTS

DE	1 041 210	10/1958		JP	60-31751	2/1985
DE	19921503	10/1988		JP	60-122561	7/1985
DE	9420429 U	12/1996		JP	60-188152	9/1985
DE	29518502 U	1/1997		JP	60-188153	9/1985
EP	093700	11/1983		JP	61-188727	11/1986
EP	0 204 637	10/1986		JP	62-60433	4/1987
EP	420263	4/1991		JP	64-17231	1/1989
EP	630637	12/1994		JP	2-84961	3/1990
EP	776637	6/1997		JP	3-31063	2/1991
EP	776648	6/1997		JP	4-108525	9/1992
FR	2714008	12/1996		JP	6-50631	7/1994
FR	2735019	12/1996		JP	6-237959	8/1994
FR	2 746 060	9/1997		JP	7-136215	5/1995
GB	415450	8/1934		JP	7-328074	12/1995
GB	672557	5/1952		JP	8-112244	5/1996
GB	1 601 930	11/1981		JP	8-317953	12/1996
GB	2 285 393	7/1995		JP	9-24071	1/1997
JP	46-31490	9/1971		JP	9-38154	2/1997
JP	47-814	8/1972		JP	9-38155	2/1997
JP	47-17495	10/1972		JP	10-146364	6/1998
JP	48-44792	6/1973		JP	2000-107230	4/2000
JP	48-44793	6/1973		JP	2000-175974	6/2000
JP	48-54494	7/1973		WO	WO 82/01313	4/1982
JP	48-54495	7/1973		WO	WO 94/16935	8/1994
JP	49-29855	3/1974		WO	WO 97/39715	10/1997
JP	51-20491	2/1976		WO	WO 00/37222	6/2000
JP	53-9091	7/1976		WO	WO 00/51830	9/2000
JP	53-96397	8/1978		WO	WO 01/19313	3/2001
JP	56-68523	6/1981		WO	WO 01/85084	11/2001
JP	56-68524	6/1981				
JP	56-73822	6/1981				
JP	57-157325	10/1982				
JP	57-187521	11/1982				
JP	58-63575	4/1983				
JP	59-37946	3/1984				
JP	59-38176	3/1984				
JP	59-183756	10/1984				

## OTHER PUBLICATIONS

Motorvator 3 Product Features Webpage, May 10, 2000.  
 Stryker Corporation, Zoom™ Drive brochure, Mar. 2000.  
 Midmark 530 Stretcher Information, Midmark Catalog, p. 14.  
 Curtis Model 1203A Motor Controller Manual, Aug. 1988.

\* cited by examiner




Fig. 1




FIG. 2




Fig. 3A




Fig. 3B






Fig. 3C




Fig. 4A






Fig. 4B




Fig. 6B

Fig. 6A

Fig. 5




Fig. 7






Fig. 8




Fig. 9




Fig. 10






Fig. 11




Fig. 12




Fig. 13






Fig. 14




Fig. 15




Fig. 16






FIG. 17





FIG. 18








FIG. 20




FIG. 21




FIG. 22






FIG. 23






FIG. 24




FIG. 25




FIG. 26






FIG. 27






FIG. 28




FIG. 29




FIG. 30




FIG. 31






FIG. 32




FIG. 33




FIG. 34






FIG. 35






FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40






FIG. 41




FIG. 42




FIG. 43




FIG. 44






FIG. 45




FIG. 46




FIG. 47






FIG. 48






FIG. 49




FIG. 50




FIG. 51





FIG. 52





**FIG. 53**




FIG. 54




FIG. 55




FIG. 56






FIG. 57




FIG. 58

FIG. 59




FIG. 60




FIG. 61




FIG. 62






FIG. 63

## MOTORIZED TRACTION DEVICE FOR A PATIENT SUPPORT

### CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 10/783,267, filed Feb. 20, 2004, now U.S. Pat. No. 6,877,572, which is a continuation of U.S. patent application Ser. No. 10/336,576, filed Jan. 3, 2003, which is a continuation-in-part of U.S. patent application Ser. No. 09/853,221, filed May 11, 2001, now U.S. Pat. No. 6,749,034, which claims the benefit of U.S. Provisional Application Ser. No. 60/203,214, filed May 11, 2000, and further claims the benefit of U.S. Provisional Application Ser. No. 60/345,058, filed Jan. 4, 2002, the disclosures of which are expressly incorporated by reference herein. The disclosure of U.S. patent application Ser. No. 09/853,802, filed May 11, 2001, is expressly incorporated by reference herein.

### BACKGROUND OF THE INVENTION

This invention relates to patient supports, such as beds. More particularly, the present invention relates to devices for moving a patient support to assist caregivers in moving the patient support from one location in a care facility to another location in the care facility.

Additional features of the disclosure will become apparent to those skilled in the art upon consideration of the following detailed description when taken in conjunction with the accompanying drawings.

### SUMMARY OF THE INVENTION

The present invention provides a patient support including a propulsion system for providing enhanced mobility. The patient support includes a bedframe supporting a mattress defining a patient rest surface. A plurality of swivel-mounted casters, including rotatably supported wheels, provide mobility to the bedframe. The casters are capable of operating in several modes, including: brake, neutral, and steer. The propulsion system includes a propulsion device operably connected to an input system. The input system controls the speed and direction of the propulsion device such that a caregiver can direct the patient support to a proper position within a care facility.

The propulsion device includes a traction device that is movable between a first, or storage, position spaced apart from the floor and a second, or use, position in contact with the floor so that the traction device may move the patient support. Movement of the traction device between its storage and use positions is controlled by a traction engagement controller.

The traction device includes a rolling support positioned to provide mobility to the bedframe and a rolling support lifter configured to move the rolling support between the storage position and the use position. The rolling support lifter includes a rolling support mount, an actuator, and a biasing device, illustratively a spring. The rolling support includes a rotatable member supported for rotation by the rolling support mount. A motor is operably connected to the rotatable member.

The actuator is configured to move between first and second actuator positions and thereby move the rolling support between first and second rolling support positions. The actuator is further configured to move to a third actuator position while the rolling support remains substantially in

the second position. The spring is coupled to the rolling support mount and is configured to bias the rolling support toward the second position when the spring is in an active mode. The active mode occurs during movement of the actuator between the second and third actuator positions.

The input system includes a user interface comprising a first handle member coupled to a first user input device and a second handle member coupled to a second user input device. The first and second handle members are configured to transmit first and second input forces to the first and second user input devices, respectively. A third user input, or enabling, device is configured to receive an enable/disable command from a user and in response thereto provide an enable/disable signal to a motor drive. A speed controller is coupled to the first and second user input devices to receive the first and second force signals therefrom. The speed controller is configured to receive the first and second force signals and to provide a speed control signal based on the combination of the first and second force signals. The speed controller instructs the motor drive to operate the motor at a suitable horsepower based upon the input from the first and second user input devices. However, the motor drive will not drive the motor absent an enable signal being received from the third user input device.

A caster mode detector and an external power detector are in communication with the traction engagement controller and provide respective caster mode and external power signals thereto. The caster mode detector provides a caster mode signal to the traction engagement controller indicative of the casters mode of operation. The external power detector provides an external power signal to the traction engagement controller indicative of connection of external power to the propulsion device. When the caster mode detector indicates that the casters are in a steer mode, and the external power detector indicates that external power has been disconnected from the propulsion device, then the traction engagement controller causes automatic deployment or lowering of the traction device from the storage position to the use position. Likewise, should the caster mode detector or the external power detector provide a signal to the traction engagement controller indicating either that the casters are no longer in the steer mode or that external power has been reconnected to the propulsion device, then the traction engagement controller will automatically raise or stow the traction device from the use position to the storage position.

In a further illustrative embodiment, an automatic braking system is provided to selectively brake the patient support based upon the power available to drive the traction device. More particularly, a power source is configured to provide power to the motor wherein the braking system includes a controller coupled intermediate the power source and the motor. The braking system causes the motor to operate as an electronic brake when the power detected by the controller is below a predetermined value. In one illustrative embodiment, the controller comprises a braking relay configured to selectively short a pair of power leads in electrical communication with the motor. An override switch is illustratively provided intermediate the controller and the motor, and is configured to disengage the braking system by opening the short between the power leads to the motor.

Additional features and advantages of the present invention will become apparent to those skilled in the art upon consideration of the following detailed description of the presently perceived best mode of carrying out the invention.



## BRIEF DESCRIPTION OF THE DRAWINGS

The detailed description particularly refers to the accompanying figures in which:

FIG. 1 is a perspective view of a hospital bed of the present invention, with portions broken away, showing the bed including a bedframe, an illustrative propulsion device coupled to the bottom of the bedframe, and a U-shaped handle coupled to the bedframe through a pair of load cells for controlling the propulsion device;

FIG. 2 is a schematic block diagram of a propulsion device, shown on the right, and a control system, shown on the left, for the propulsion device;

FIG. 3A is a schematic block diagram of an automatic braking system of the present invention shown in a driving mode of operation;

FIG. 3B is a schematic block diagram of the automatic braking system of FIG. 3A shown in a braking mode of operation;

FIG. 3C is a schematic block diagram of the automatic braking system of FIG. 3A shown in an override mode of operation;

FIG. 4A is a schematic diagram showing an illustrative input system of the control system of FIG. 2;

FIG. 4B is a schematic diagram showing a further illustrative input system of the control system of FIG. 2;

FIG. 5 is a side elevation view taken along line 5—5 of FIG. 1 showing an end of the U-shaped handle coupled to one of the load cells and a bail in a raised off position to prevent operation of the propulsion system;

FIG. 6A is a view similar to FIG. 5 showing the handle pushed forward and the bail moved to a lowered on position to permit operation of the propulsion system;

FIG. 6B is a view similar to FIG. 5 showing the handle pulled back and the bail bumped slightly forward to cause a spring to bias the bail to the raised off position;

FIG. 7 is a graph depicting the relationship between an input voltage to a gain stage (horizontal axis) and an output voltage to the motor (vertical axis);

FIG. 8 is a perspective view showing a propulsion device including a wheel coupled to a wheel mount, a linear actuator, a pair of links coupled to the linear actuator, a shuttle coupled to one of the links, and a pair of gas springs coupled to the shuttle and the wheel mount;

FIG. 9 is an exploded perspective view of various components of the propulsion device of FIG. 8;

FIG. 10 is a sectional view taken along lines 10—10 of FIG. 8 showing the propulsion device with the wheel spaced apart from the floor;

FIG. 11 is a view similar to FIG. 10 showing the linear actuator having a shorter length than in FIG. 10 with the shuttle pulled to the left through the action of the links, and movement of the shuttle moving the wheel into contact with the floor;

FIG. 12 is a view similar to FIG. 10 showing the linear actuator having a shorter length than in FIG. 11 with the shuttle pulled to the left through the action of the links, and additional movement of the shuttle compressing the gas springs;

FIG. 13 is a view similar to FIG. 12 showing the gas springs further compressed as the patient support rides over a “bump” in the floor;

FIG. 14 is a view similar to FIG. 12 showing the gas springs extended as the patient support rides over a “dip” in the floor to maintain contact of the wheel with the floor;

FIG. 15 is a perspective view of a relay switch and keyed lockout switch for controlling enablement of the propulsion

device showing a pin coupled to the bail spaced apart from the relay switch to enable the propulsion device;

FIG. 16 is a view similar to FIG. 15 showing the pin in contact with the relay switch to disable the propulsion device from operating;

FIG. 17 is a perspective view of a second embodiment hospital bed showing the bed including a bedframe, a second embodiment propulsion device coupled to the bottom of the bedframe, and a pair of spaced-apart handles coupled to the bedframe through a pair of load cells for controlling the propulsion device;

FIG. 18 is a perspective view showing the second embodiment propulsion device including a traction belt supported by a belt mount, an actuator, an arm coupled to the actuator, and a biasing device coupled to the arm and the belt mount;

FIG. 19 is a top plan view of the of the propulsion device of FIG. 18;

FIG. 20 is a detail view of FIG. 19;

FIG. 21 is an exploded perspective view of the propulsion device of FIG. 18;

FIG. 22 is a sectional view taken along lines 22—22 of FIG. 19 showing the second embodiment propulsion device of FIG. 18 with the track drive spaced apart from the floor;

FIG. 23 is a view similar to FIG. 22 showing the biasing device moved to the left through action of the arm, thereby moving the traction belt into contact with the floor;

FIG. 24 is a view similar to FIG. 22 showing the biasing device moved further to the left than in FIG. 23 through action of the arm, and additional movement of the biasing device compressing a spring received within a tubular member;

FIG. 25 is a view similar to FIG. 24 showing the spring further compressed as the patient support rides over a “bump” in the floor;

FIG. 26 is a view showing the spring extended from its position in FIG. 24 as the patient support rides over a “dip” in the floor to maintain contact of the traction belt with the floor;

FIG. 27 is a sectional view taken along lines 27—27 of FIG. 19 showing the second embodiment propulsion device of FIG. 18 with the track drive spaced apart from the floor;

FIG. 28 is a view similar to FIG. 27 showing the traction belt in contact with the floor as illustrated in FIG. 24;

FIG. 29 is a sectional view taken along lines 29—29 of FIG. 19;

FIG. 30 is a detail view of FIG. 29;

FIG. 31 is a side elevational view of the second embodiment hospital bed of FIG. 17 showing a caster and braking system operably connected to the second embodiment propulsion device;

FIG. 32 is view similar to FIG. 31 showing the caster and braking system in a steer mode of operation whereby the traction belt is lowered to contact the floor;

FIG. 33 is a partial perspective view of the second embodiment hospital bed of FIG. 17, with portions broken away, showing the second embodiment propulsion device;

FIG. 34 is a perspective view of the second embodiment propulsion device of FIG. 17 showing the track drive spaced apart from the floor as in FIG. 22;

FIG. 35 is a view similar to FIG. 34 showing the traction belt in contact with the floor as in FIG. 24;

FIG. 36 is a partial perspective view of the second embodiment hospital bed of FIG. 17 as seen from the front and right side, showing a second embodiment input system;

FIG. 37 is a perspective view similar to FIG. 36 as seen from the front and left side;



## 5

FIG. 38 is an enlarged partial perspective view of the second embodiment input system of FIG. 36 showing an end of a first handle coupled to a load cell;

FIG. 39 is a sectional view taken along line 39—39 of FIG. 38;

FIG. 40 is an exploded perspective view of the first handle of the second embodiment input system of FIG. 38;

FIG. 41 is a perspective view of a third embodiment hospital bed showing the bed including a bedframe, a third embodiment propulsion device coupled to the bottom of the bedframe, and a pair of spaced-apart handles coupled to the bedframe and controlling the propulsion device;

FIG. 42 is a perspective view showing the third embodiment propulsion device including a traction belt supported by a belt mount, an actuator, an arm coupled to the actuator, and a spring coupled to the arm and the belt mount;

FIG. 43 is a top plan view of the of the propulsion device of FIG. 42;

FIG. 44 is a detail view of FIG. 43;

FIG. 45 is an exploded perspective view of the propulsion device of FIG. 42;

FIG. 46 is a sectional view taken along lines 46—46 of FIG. 43 showing the alternative embodiment propulsion device of FIG. 42 with the track drive spaced apart from the floor;

FIG. 47 is a view similar to FIG. 46 showing the spring moved to the left through action of the arm, thereby moving the traction belt into contact with the floor;

FIG. 48 is a view similar to FIG. 46 showing the spring moved further to the left than in FIG. 47 through action of the arm, and additional movement of the spring placing the spring in tension;

FIG. 49 is a sectional view taken along lines 49—49 of FIG. 43;

FIG. 50 is a detail view of FIG. 49;

FIG. 51 is a side elevational view of the alternative embodiment hospital bed of FIG. 41 showing a caster and braking system operably connected to the third embodiment propulsion device;

FIG. 52 is view similar to FIG. 51 showing the caster and braking system in a steer mode of operation whereby the traction belt is lowered to contact the floor;

FIG. 53 is a detail view of FIG. 52, illustrating the override switch of the automatic braking system;

FIG. 54 is a partial perspective view of the third embodiment hospital bed of FIG. 41, with portions broken away, showing the third embodiment propulsion device;

FIG. 55 is a perspective view of the third embodiment propulsion device of FIG. 42 showing the track drive spaced apart from the floor as in FIG. 46;

FIG. 56 is a view similar to FIG. 55 showing the traction belt in contact with the floor as in FIG. 48;

FIG. 57 is a partial perspective view of the third embodiment hospital bed of FIG. 42 as seen from the front and right side, showing a third embodiment input system;

FIG. 58 is a perspective view similar to FIG. 57 as seen from the front and left side;

FIG. 59 is a detail view of the charge indicator of FIG. 58;

FIG. 60 is an enlarged partial perspective view of the third embodiment input system of FIG. 57 showing a lower end of a first handle supported by the bedframe;

FIG. 61 is a sectional view taken along line 61—61 of FIG. 60;

FIG. 62 is an exploded perspective view of the first handle of the third embodiment input system of FIG. 60; and

## 6

FIG. 63 is a partial end elevational view of the third embodiment input system of FIG. 57 showing selective pivotal movement of the first handle.

## 5 DETAILED DESCRIPTION OF THE DRAWINGS

A patient support or bed 10 in accordance with an illustrative embodiment of the present disclosure is shown in FIG. 1. Patient support 10 includes a bedframe 12 extending between opposing ends 9 and 11, a mattress 14 positioned on bedframe 12 to define a patient rest surface 15, and an illustrative propulsion system 16 coupled to bedframe 12. Propulsion system 16 is provided to assist a caregiver in moving bed 10 between various rooms in a care facility. According to the illustrative embodiment, propulsion system 16 includes a propulsion device 18 and an input system 20 coupled to propulsion device 18. Input system 20 is provided to control the speed and direction of propulsion device 18 so that a caregiver can direct patient support 10 to the proper position in the care facility.

Patient support 10 includes a plurality of casters 22 that are normally in contact with floor 24. A caregiver may move patient support 10 by pushing on bedframe 12 so that casters 22 move along floor 24. The casters 22 may be of the type disclosed in U.S. Pat. No. 6,321,878 to Mobley et al., and in PCT Published Application No. WO 00/51830 to Mobley et al., both of which are assigned to the assignee of the present invention, and the disclosures of which are expressly incorporated by reference herein. When it is desirable to move patient support 10 a substantial distance, propulsion device 18 is activated by input system 20 to power patient support 10 so that the caregiver does not need to provide all the force and energy necessary to move patient support 10 between locations in a care facility.

As shown schematically in FIG. 2, a suitable propulsion system 16 includes a propulsion device 18 and an input system 20. Propulsion device 18 includes a traction device 26 that is normally in a storage position spaced apart from floor 24. Propulsion device 18 further includes a traction engagement controller 28. Traction engagement controller 28 is configured to move traction device 26 from the storage position spaced apart from the floor 24 to a use position in contact with floor 24 so that traction device 26 can move patient support 10.

According to alternative embodiments, the various components of the propulsion system are implemented in any number of suitable configurations, such as hydraulics, pneumatics, optics, or electrical/electronics technology, or any combination thereof such as hydro-mechanical, electro-mechanical, or opto-electric embodiments. In the preferred embodiment, propulsion system 16 includes mechanical, electrical and electro-mechanical components as discussed below.

Input system 20 includes a user interface or handle 30, a first user input device 32, a second user input device 34, a third user input device 35, and a speed controller 36. Handle 30 has a first handle member 38 that is coupled to first user input device 32 and second handle member 40 that is coupled to second user input device 34. Handle 30 is configured in any suitable manner to transmit a first input force 39 from first handle member 38 to first user input device 32 and to transmit a second input force 41 from second handle member 40 to second user input device 34. Further details regarding the mechanics of a first embodiment of handle 30 are discussed below in connection with



FIGS. 1, 5, 6A and 6B. Details of additional embodiments of handle 30 are discussed below in connection with FIGS. 36–40, 58 and 60–63.

Generally, first and second user input devices 32, 34 are configured in any suitable manner to receive the first and second input forces 39 and 41, respectively, from first and second handle members 38 and 40, respectively, and to provide a first force signal 43 based on the first input force 39 and a second force signal 45 based on the second input force 41.

As shown in FIG. 2, speed controller 36 is coupled to first user input device 32 to receive the first force signal 43 therefrom and is coupled to second user input device 34 to receive the second force signal 45 therefrom. In general, speed controller 36 is configured in any suitable manner to receive the first and second force signals 43 and 45, and to provide a speed control signal 46 based on the combination of the first and second force signals 43 and 45. Further details regarding illustrative embodiments of speed controller 36 are discussed below in connection with FIGS. 4A and 4B.

As previously mentioned, propulsion system 16 includes propulsion device 18 having traction device 26 configured to contact floor 24 to move bedframe 12 from one location to another. Propulsion device 18 further includes a motor 42 coupled to traction device 26 to provide power to traction device 26. Propulsion device 18 also includes a motor drive 44, a power reservoir 48, a charger 49, and an external power input 50. Motor drive 44 is coupled to speed controller 36 of input system 20 to receive speed control signal 46 therefrom.

Third user input, or enabling, device 35 is also coupled to motor drive 44 as shown in FIG. 2. In general, third user input device 35 is configured to receive an enable/disable command 51 from a user and to provide an enable/disable signal 52 to motor drive 44. When the traction device 26 is in its use position and a user provides an enable command 51a to third user input device 35, motor drive 44 reacts by responding to any speed control signal 46 received from the speed controller 36. Similarly, when a user fails to provide an enable command 51a, or provides a disable command 51b, to third user input 35, motor drive 44 reacts by not responding to any speed control signal 46 received from the speed controller 36.

In the illustrative embodiment of FIG. 2, limit switches 33 detect whether the traction device 26 is in its storage or use positions and provide signals indicative thereof to the traction engagement controller 28 and the motor drive 44. After the motor drive 44 receives a signal indicating that the traction device 26 is in its use position, it permits operation of the motor 42 in response to a speed control signal 46 provided that an enable/disable signal 52 has been received from the third user input device 35 as described above. After the motor drive 44 receives a signal indicating that the traction device 26 is in its storage position, it inhibits operation of the motor 42 in response to a speed control signal 46.

In alternative embodiments, third user input device 35 may be configured to receive an enable/disable command 51 from a user and to provide an enable/disable signal 52 to traction engagement controller 28. In one illustrative embodiment, when a user provides an enable command 51a to third user input device 35, the traction engagement controller 28 responds by placing traction device 26 in its use position in contact with floor 24. Similarly, when a user fails to provide an enable command 51a, or provides a disable command 51b, to third user input 35, traction

engagement controller 28 responds by placing traction device 26 in its storage position raised above floor 24.

In a further illustrative embodiment, when a user provides an enable command 51a to third user input device 35, the traction engagement controller 28 responds by preventing the lowering of traction device 26 from its storage position raised above floor 24. Similarly, when a user fails to provide an enable command 51a, or provides a disable command 51b, to third user input 35, traction engagement controller 28 responds by permitting the lowering of traction device 26 to its use position in contact with floor 24, provided that other required inputs are supplied to traction engagement controller 28 as identified herein. As may be appreciated, in this embodiment of the invention, the enable signal 52a from third user input device 35 allows for operation of motor drive 44 and motor 42, while preventing the lowering of traction device 26 from its storage position to its use position. As noted above, however, the limit switches 33 will detect the storage position of the traction device 26 and prevent operation of the motor 42 in response thereto. As such, should a switch failure occur causing a constant enable signal 52a to be produced by third user input device 35, then the traction device 26 will not lower, and the motor 42 will not propel the patient support 10. A fault condition of the third user input device 35 is therefore identified by the traction device 26 not lowering to its use position in response to unintentional receipt of enable signal 52a by traction engagement controller 28.

Illustratively, a temperature sensor 37 may be coupled to the motor drive 44 and the motor 42 as shown in FIG. 2. The temperature sensor 37 is in thermal communication with the motor 42 for detecting a temperature thereof. If the detected temperature exceeds a predetermined value, then the motor drive 44 responds by slowing the motor 42 to a stop. Once the detected temperature falls below the predetermined value, the motor drive 44 operates in a normal manner as detailed herein.

Generally, motor drive 44 is configured in any suitable manner to receive the speed control signal 46 and to provide drive power 53 based on the speed control signal 46. The drive power 53 is a power suitable to cause motor 42 to operate at a suitable horsepower 47 (“motor horsepower”). In an illustrative embodiment, motor drive 44 is a commercially available Curtis PMC Model No. 1208, which responds to a voltage input range from roughly 0.3 VDC (for full reverse motor drive) to roughly 4.7 VDC (for full forward motor drive) with roughly a 2.3–2.7 VDC input null reference/deadband (corresponding to zero motor speed).

Motor 42 is coupled to motor drive 44 to receive the drive power 53 therefrom. Motor 42 is suitably configured to receive the drive power 53 and to provide the motor horsepower 47 in response thereto. In an illustrative embodiment, the motor 42 is a commercially available Teco Team-1, 24 VDC, 350 Watt, permanent magnet motor.

Traction engagement controller 28 is configured to provide actuation force to move traction device 26 into contact with floor 24 or away from floor 24 into its storage position. Additionally, traction engagement controller 28 is coupled to power reservoir 48 to receive a suitable operating power therefrom. Traction engagement controller 28 is also coupled to a caster mode detector 54 and to an external power detector 55 for receiving caster mode and external power signals 56 and 57, respectively. In general, traction engagement controller 28 is configured to automatically cause traction device 26 to lower into its use position in contact with floor 24 upon receipt of both signals 56 and 57 indicating that the casters 22 are in a steer mode of operation



and that no external power **50** is applied to the propulsion system **16**. Likewise, traction engagement controller **28** is configured to raise traction device **26** away from contact with floor **24** and into its storage position when the externally generated power is being received through the external power input **50**, or when casters **22** are not in a steer mode of operation.

As detailed above, in a further illustrative embodiment, an enable command **51a** to the third user input device **35** is also required in order for the traction engagement controller **28** to cause lowering of the traction device **26** to its use position in contact with the floor **24**. Likewise, when the third user input device **35** fails to receive the enable command **51a**, or receives a disable command **51b**, then the traction engagement controller **28** responds by raising the traction device **26** to its storage position raised above the floor **24**. In another illustrative embodiment, the lack of an enable command **51a** to the third user input device **35** is required in order for the traction engagement controller **28** to cause lowering of the traction device **26** to its use position in contact with the floor **24**.

The caster mode detector **54** is configured to cooperate with a caster and braking system **58** including the plurality of casters **22** supported by bed frame **12**. More particularly, each caster **22** includes a wheel **59** rotatably supported by caster forks **60**. The caster forks **60**, in turn, are supported for swiveling movement relative to bedframe **12**. Each caster **22** includes a brake mechanism (not shown) to inhibit the rotation of wheel **59**, thereby placing caster **22** in a brake mode of operation. Further, each caster **22** includes an anti-swivel or directional lock mechanism (not shown) to prevent swiveling of caster forks **60**, thereby placing caster **22** in a steer mode of operation. A neutral mode of operation is defined when neither the brake mechanism nor the directional lock mechanism are actuated such that wheel **59** may rotate and caster forks **60** may swivel. The caster and braking system **58** also includes an actuator including a plurality of pedals **61**, each pedal **61** adjacent to a different one of the plurality of casters **22** for selectively placing caster and braking system **58** in one of the three different modes of operation: brake, steer, or neutral. A linkage **63** couples all of the actuators of casters **22** so that movement of any one of the plurality of pedals **61** causes movement of all the actuators, thereby simultaneously placing all of the casters **22** in the same mode of operation. Additional details regarding the caster and braking system **58** are provided in U.S. Pat. No. 6,321,878 to Mobley et al. and in PCT Published Application No. WO 00/51830 to Mobley et al., both of which are assigned to the assignee of the present invention and the disclosures of which are expressly incorporated by reference herein.

With reference now to FIGS. **31** and **32**, caster mode detector **54** includes a tab or protrusion **65** supported by, and extending downwardly from, linkage **63** of caster and braking system **58**. A limit switch **67** is supported by bedframe **12** wherein tab **65** is engagable with switch **67**. A neutral mode of casters **22** is illustrated in FIG. **31** when pedal **61** is positioned substantially horizontal. By rotating the pedal **61** counterclockwise in the direction of arrow **166** and into the position as illustrated in phantom in FIG. **31**, pedal **61** is placed into a brake mode where rotation of wheels **59** is prevented. In either the neutral or brake modes, the tab **65** is positioned in spaced relation to the switch **67** such that the traction engagement controller **28** does not lower traction device **26** from its storage position into its use position.

FIG. **32** illustrates casters **22** in a steer mode of operation where pedal **61** is positioned clockwise, in the direction of arrows **160**, from the horizontal neutral position of FIG. **31**. In this steer mode, wheels **59** may rotate, but forks **60** are prevented from swiveling. By rotating pedal **61** clockwise, linkage **63** is moved to the right in the direction of arrow **234** in FIG. **32**. As such, tab **65** moves into engagement with switch **67** whereby caster mode signal **56** supplied to traction engagement controller **28** indicates that casters **22** are in the steer mode. In response, assuming no external power is supplied to the propulsion system **16** from power input **50**, traction engagement controller **28** automatically lowers the traction device **26** from its storage position into its use position in contact with the floor **24**.

In a further illustrative embodiment, the tab **65** and switch **67** may be replaced by a conventional reed switch. The reed switch may be coupled to the linkage **63**. More particularly, the reed switch may be coupled to a transversely extending rod (not shown) rotatably supported and interconnecting pedals **61** positioned on opposite sides of the patient support **10**. Regardless of the particular embodiment, the caster mode detector **54** is configured to provide the caster mode signal **56** indicating that the casters **22** are in the steer mode.

The external power detector **55** is configured to detect alternating current (AC) since this is the standard current supplied from conventional external power sources. The power reservoir **48** supplies direct current (DC) to traction engagement controller **28**, speed controller **36**, and motor drive **44**. As such, external power detector **55**, by sensing the presence of AC current, provides an indication of the connection of an external power source through power input **50** to the propulsion system **16**. It should be appreciated that in alternative embodiments, other devices for detecting the connection of an external AC power source to the bed **10** may be utilized. For example, a detector may be used to detect DC current supplied by the charger **49** to the power reservoir **48**, indicating the connection of the bed **10** to an external AC power source.

The traction engagement controller **28** is configured to (i) activate an actuator to raise traction device **26** when casters **22** are not in a steer mode of operation as detected by caster mode detector **54**; and (ii) activate an actuator to raise traction device **26** when externally generated power is received through external power input **50** as detected by external power detector **55**. Limit switches **33** detect the raised storage position and the lowered use position of the traction device **26** and provide a signal indicative thereof to the traction engagement controller **28**. In response, the traction engagement controller **28** stops the raising or lowering of the traction device **26** once it reaches its desired storage or use position, respectively.

As discussed in greater detail below, the linear actuator in the embodiment of FIGS. **8–14** is normally extended (i.e., the linear actuator includes a spring (not shown) which causes it to be in the extended state when it receives no power). Retraction of the linear actuator provides actuation force which moves traction device **26** into contact with floor **24**, while extension of the linear actuator removes the actuation force and moves traction device **26** away from floor **24**. In the illustrative embodiment, traction engagement controller **28** inhibits contact of traction device **26** with floor **24** not only when the user places casters **22** of bed **10** in brake or neutral positions, but also when charger **48** is plugged into an external power line through input **50**. In further illustrative embodiments, traction engagement controller **28** prevents lowering of traction device **26** from its



storage position to its use position in contact with floor 24 when third user input 35 produces an enable signal 52.

Power reservoir 48 is coupled to speed controller 36 of input system 20 and motor drive 44 and traction engagement controller 28 of propulsion system 16 to provide the necessary operating power thereto. In the preferred embodiment, power reservoir 48 includes two rechargeable 12 AmpHour 12 Volt type 12120 batteries connected in series which provide operating power to motor drive 44, motor 42, and the linear actuator in traction engagement controller 28, and further includes an 8.5 V voltage regulator which converts unregulated power from the batteries into regulated power for electronic devices in propulsion system 16 (such as operational amplifiers). However, it should be appreciated that power reservoir 48 may be suitably coupled to other components of propulsion system 16 in other embodiments, and may be accordingly configured as required to provide the necessary operating power.

Charger 49 is coupled to external power input 50 to receive an externally generated power therefrom, and is coupled to power reservoir 48 to provide charging thereto. Accordingly, charger 49 is configured to use the externally generated power to charge, or replenish, power reservoir 48. In the preferred embodiment, charger 49 is an IBEX model number L24-1.0/115 AC.

External power input 50 is coupled to charger 49 and traction engagement controller 28 to provide externally generated power thereto. In the preferred embodiment, the external power input 50 is a standard 115V AC power plug.

Referring further to FIG. 2, a charge detector or battery gas gauge 69 is provided in communication with power reservoir 48 for sensing the amount of power or charge contained therein. The charge detector 69 is based on the TI/Benchmark 2013H gas gauge chip. A 0.005 ohm resistor is positioned intermediate the battery minus and ground. The charge detector 69 monitors the voltage across the resistor as a function of time, interpreting positive voltages as current into the power reservoir 48 (charging) and negative voltages as current out of the power reservoir 48 (discharging). The amount of detected charge is provided to a charge indicator 70 through a charge indication signal 71. The charge indicator 70 may comprise any conventional display visible to the caregiver. One embodiment, as illustrated in FIG. 59, comprises a plurality of lights 72, preferably light emitting diodes (LEDs), which provide a visible indication of remaining charge in the power reservoir 48. Each illuminated LED 72 is representative of a percentage of full charge remaining, such that the fewer LEDs illuminated, the less charge remains within power reservoir 48. It should be appreciated that the charge indicator 70 may comprise other similar displays, including, but not limited to liquid crystal displays.

With further reference to FIGS. 2 and 59, the charge indicator 70 illustratively comprises a total of five LEDs 72. Each LED 72 represents approximately 20% of the nominal power reservoir capacity, i.e., 5 LEDs 72 illuminated represents an 80% to 100% capacity in the power reservoir 48, 4 LEDs 72 illuminated represents an 60 to 79% capacity in the power reservoir 48, etc. A single illuminated LED 72 indicates that the remaining capacity is less than 20%.

A shut down relay 77 is provided in communication with the charge detector 69. When the charge detector 69 senses a remaining charge within the power reservoir 48 below a predetermined amount, it sends a low charge signal 74 to the shut down relay 77. In an illustrative embodiment, the predetermined amount is defined as seventy percent of a full charge. The shut down relay 77, in response to the low

charge signal 74, disconnects the power reservoir 48 from the motor drive 44 and the traction engagement controller 28. As such, further depletion of the power reservoir 48 (i.e., deep discharging) is prevented. Preventing the unnecessary depletion of the power reservoir 48 typically extends the useful life of the batteries within the power reservoir 48.

The shut down relay 77 is in further communication with a manual shut down switch 100. The shut down switch 100 may comprise a conventional toggle switch supported by the bedframe 12 and physically accessible to the user. As illustrated in FIGS. 42 and 45, the switch 100 may be positioned behind a wall 101 formed by traction device 26 such that access is available only through an elongated slot 102, thereby preventing inadvertent movement of the switch 100. The switch 100 causes shut down relay 77 to disconnect power from motor drive 44 and traction engagement controller 28 which is desirable during shipping and maintenance of patient support 10.

The propulsion device 18 is configured to be manually pushed should the traction device 26 be in the lowered use position and power is no longer available to drive the motor 42 and traction engagement controller 28. In the preferred embodiment, the motor 42 is geared to permit it to be backdriven. Furthermore, it is preferred that the no more than 200% of manual free force is required to push the bed 10 when the traction device 76 is lowered to the use position in contact with floor 24 but not driven in motion by the motor 42, compared to when the traction device 26 is raised to the storage position.

When the batteries of power reservoir 48 become drained, the user recharges them by connecting external power input 50 to an AC power line. However, as discussed above, traction engagement controller 28 does not provide the actuation force to lower traction device 26 into contact with floor 24 unless the user disconnects external power input 50 from the power line and places casters 22 in a steer mode of operation through pedal 61.

In an illustrative embodiment of the patient support 10, an automatic braking system 103 is coupled intermediate the power reservoir 48 and the motor 42. The braking system 103 is configured to provide braking to the patient support 10 should insufficient power be available to drive the motor 42 and, in turn, the traction device 26 is not capable of moving the bedframe 12. More particularly, the braking system 103 is configured to detect power available to drive the motor 42 and to provide braking of the motor 42 selectively based upon the power detected.

As illustrated schematically in FIGS. 3A-3C, the braking system includes a braking controller 105 configured to cause the traction device 26 to operate in a driving mode when it detects power supplied to the motor 42 at least as great as a predetermined value. The braking controller 105 is further configured to cause the traction device 26 to operate in a dynamic braking mode when it detects power supplied to the motor 42 below the predetermined value. In the illustrative embodiment of FIGS. 3A-3C, the controller 105 comprises a conventional relay 106 including a movable contact 107 which provides electrical communication between a pair of pins P1 and P2 when a sufficient current passes through a coil 108 (FIG. 3A). More particularly, the contact 107 is pulled toward pin P1 by the energized coil 108 against a spring bias tending to cause the contact 107 to be drawn toward pin P3. The contact 107 of the relay 106 disconnects pins P1 and P2 and instead provides electrical communication between pins P2 and P3 when the current through the coil 108 drops below the predetermined value (FIGS. 3B and 3C). In other words, the spring bias causes the contact 107



to move toward the pin P3. The relay 106 may comprise commercially available Tyco Model VF4-15H13-C01 having approximately a 40 amp capacity. Illustratively, the relay 106 is configured to open, and thereby connect pins P2 and P3, when voltage applied to the motor 42 is less than approximately 21 volts and the current supplied to the motor 42 is less than approximately 5 amps.

The braking relay 106 functions to switch the motor 42 between a driving mode, as illustrated in FIG. 3A, and a dynamic braking mode, as illustrated in FIG. 3B. In the driving mode, the braking relay 106 connects the power leads 109a and 109b of the motor 42 with the power reservoir 48, thereby supplying power for driving the motor 42. This, in turn, causes the traction device 26 to drive the bed frame 12 in motion. In the braking mode, the braking relay 106 disconnects one of the power leads 109b from the motor 42 and instead shorts the power leads 109a and 109b through contact 107. Since the motor 42 includes a permanent magnet, shorting the power leads 109a and 109b causes the motor 42 to act as an electronic brake, in a manner known in the art. Moreover, shorting the power leads 109a and 109b causes the motor 42 to function as a brake resulting in the traction device 26 resisting movement of the patient support 10. The override switch 111 is provided in order to remove the short from the motor leads 109a and 109b and thereby prevent the motor 42 from functioning as an electronic brake.

In operation, when power to the motor 42 drops below a certain predetermined value, as measured by current and/or voltage supplied to the motor 42, then the relay 106 shorts the leads to the motor 42. As described above, in an illustrative embodiment, the predetermined value of the voltage is approximately 21 volts and the predetermined value of the current is approximately 5 amps. When the motor leads 109a and 109b are shorted, the motor 42 will act as a generator should the traction device 26 be moved in an attempt to transport the patient support 10. By attempting to generate into a short circuit of the power leads 109a and 109b, the motor 42 acts as an electronic brake thereby slowing or preventing movement of the patient support 10. Such braking is often desirable, particularly if the patient support 10 is located on a ramp or incline with insufficient power supplied to the motor 42 to cause the traction device 26 to assist in moving the patient support 10 against gravity. More particularly, the electronic braking mode of the motor 42 will act against gravity induced movement of the patient support 10 down the incline. Should the operator need to physically or manually push the patient support 10, he or she may disengage the electronic braking mode by activating the override switch 111 which, as detailed above, removes the short circuit of the power leads 109a and 109b to the motor 42.

As detailed above, the shut down relay 77 disconnects the power reservoir 48 from the motor drive 44 in response to the low charge signal 74 from the charge detector 69 or in response to manipulation of the shut down switch 100 by a user. As may be appreciated, disconnecting power from the motor drive 44 and motor 42 will cause the braking relay 106 to short the leads to the motor 42, thereby causing the motor 42 to operate in the braking mode as detailed above. In other illustrative embodiments, the shut down relay 77 may disconnect the power reservoir 48 from the motor drive 44 in response to additional inputs. For example, the shut down relay 77 may respond to the enable/disable signal 52 from the third user input device 35, thereby causing the braking relay 106 to short the leads to the motor 42 resulting in the motor 42 operating in the braking mode. This condi-

tion may be desirable in certain circumstances where braking is desired in response to either (i) the failure of the user to provide an enable command 51a to the third user input device 35 or (ii) the user providing a disable command 51b to the third user input device 35.

In further illustrative embodiments, the third user input device 35 may directly control a motor relay similar to the braking relay 106 and configured such that when the relay is off, its normally-closed contact shorts the motor 42, and when energized, its normally-open contact connects the motor 42 to the motor drive 44 to permit operation of the motor 42. As detailed above, the override switch 111 may be utilized to open the short circuit of the motor leads and eliminate the braking function of the motor 42.

The mounting of the override switch 111 is illustrated in greater detail in FIGS. 52 and 53. More particularly, the override switch 111 may comprise a conventional toggle switch including a lever 115 operably connected to the contact 113 (FIGS. 3A-3C) and which may be moved between closed (FIGS. 3A and 3B) and opened (FIG. 3C) positions. The lever 115 is preferably received within a recess 117 formed in a side wall 119 supported by the bed frame 12 in order to provide access to the operator while preventing inadvertent activation thereof. The switch 111 may be secured to the side wall 119 using conventional fasteners, such as screws 121.

Propulsion system 16 of FIG. 2 operates generally in the following manner. When a user wants to move bed 10 using propulsion system 16, the user first disconnects external power 50 from the patient support 10 and then places casters 22 in a steer mode through pivoting movement of pedal 61 in a clockwise direction as illustrated in FIG. 41. In response, traction engagement controller 28 lowers traction device 26 to floor 24. The user then activates the third user, or enabling, device 35 by providing an enabling command 51 thereto. Next, the user applies force to handle 30 so that propulsion system 16 receives the first input force 39 and the second input force 41 from first and second handle members 38, 40, respectively. The motor 42 provides motor horsepower 47 to traction device 26 based on first input force 39 and second input force 41. Accordingly, a user selectively applies a desired amount of motor horsepower 47 to traction device 26 by imparting a selected amount of force on handle 30. It should be readily appreciated that in this manner, the user causes patient support 10 of FIG. 1 to "self-propel" to the extent that the user applies force to handle 30.

The user may push forward on handle 30 to move bed 10 in a forward direction 23 or pull back on handle 30 to move bed 10 in a reverse direction 25. In the preferred embodiment, first input force 39, second input force 41, motor horsepower 47, and actuation force 104 generally are each signed quantities; that is, each may take on a positive or a negative value with respect to a suitable neutral reference. For example, pushing on first handle member 38 of propulsion system 16 in forward direction 23, as shown in FIG. 6A for handle 30, generates a positive first input force 39 with respect to a neutral reference position, as shown in FIG. 5 for handle 30, while pulling on first end 38 in direction 25, as shown in FIG. 6B for preferred handle 30, generates a negative first input force with respect to the neutral position. The deflection shown in FIGS. 6A and 6B is exaggerated for illustration purposes only. In actual use, the deflection of the handle 30 is very slight.

Consequently, first force signal 43 from first user input device 32 and second force signal 45 from second user input device 34 are each correspondingly positive or negative with respect to a suitable neutral reference, which allows speed



controller 36 to provide a correspondingly positive or negative speed control signal to motor drive 44. Motor drive 44 then in turn provides a correspondingly positive or negative drive power to motor 42. A positive drive power causes motor 42 to move traction device 26 in a forward direction, while the negative drive power causes motor 42 to move traction device 26 in an opposite reverse direction. Thus, it should be appreciated that a user causes patient support (FIG. 1) to move forward by pushing on handle 30, and causes the patient support to move in reverse by pulling on handle 30.

The speed controller 36 is configured to instruct motor drive 44 to power motor 42 at a reduced speed in a reverse direction as compared to a forward direction. In the illustrative embodiment, the negative drive power 53a is approximately one-half the positive drive power 53b. More particularly, the maximum forward speed of patient support 10 is between approximately 2.5 and 3.5 miles per hour, while the maximum reverse speed of patient support 10 is between approximately 1.5 and 2.5 miles per hour.

Additionally, speed controller 36 limits both the maximum forward and reverse acceleration of the patient support 10 in order to promote safety of the user and reduce damage to floor 24 as a result of sudden engagement and acceleration by traction device 26. The speed controller 36 limits the maximum acceleration of motor 42 for a predetermined time period upon initial receipt of force signals 43 and 45 by speed controller 36. In the illustrative embodiment, forward direction acceleration shall not exceed 1 mile per hour per second for the first three seconds and reverse direction acceleration shall not exceed 0.5 miles per hour per second for the first three seconds.

The illustrative embodiment provides motor horsepower 47 to traction device 26 proportional to the sum of the first and second input forces from first and second ends 38, 40, respectively, of handle 30. Thus, the illustrative embodiment generally increases the motor horsepower 47 when a user increases the sum of the first input force 39 and the second input force 41, and generally decreases the motor horsepower 47 when a user decreases the sum of the first and second input forces 39 and 41.

Motor horsepower 47 is roughly a constant function of torque and angular velocity. Forces which oppose the advancement of a platform over a plane are generally proportional to the mass of the platform and the incline of the plane. The illustrative embodiment also provides a variable speed control for a load bearing platform having a handle 30 for a user and a motor-driven traction device 26. For example, in relation to the patient support, when the user moves a patient of a particular weight, such as 300 lbs, the user pushes handle 30 of propulsion system 16 (see FIG. 2), and thus imparts a particular first input force 39 to first user input device 32 and a particular second input force 41 to second user input device 34.

The torque component of the motor horsepower 47 provided to traction device 26 assists the user in overcoming the forces which oppose advancement of patient support 10, while the speed component of the motor horsepower 47 ultimately causes patient support 10 to travel at a particular speed. Thus, the user causes patient support 10 to travel at a higher speed by imparting greater first and second input forces 39 and 41 through handle 30 (i.e., by pushing harder) and vice-versa.

The operation of handle 30 and the remainder of input system 20 and the resulting propulsion of patient support 10 propelled by traction device 26 provide inherent feedback (not shown) to propulsion system 16 which allows the user

to easily cause patient support 10 to move at the pace of the user so that propulsion system 16 tends not to "outrun" the user. For example, when a user pushes on handle 30 and causes traction device 26 to move patient support 10 forward, patient support 10 moves faster than the user which, in turn, tends to reduce the pushing force applied on handle 30 by the user. Thus, as the user walks (or runs) behind patient support 10 and pushes against handle 30, patient support 10 tends to automatically match the pace of the user. For example, if the user moves faster than the patient support, more force will be applied to handle 30 and causes traction device 26 to move patient support 10 faster until patient support 10 is moving at the same speed as the user. Similarly, if patient support 10 is moving faster than the user, the force applied to handle 30 will reduce and the overall speed of patient support 10 will reduce to match the pace of the user.

The illustrative embodiment also provides coordination between the user and patient support 10 propelled by traction device 26 by varying the motor horsepower 47 with differential forces applied to handle 30, such as are applied by a user when pushing or pulling patient support 10 around a corner. The typical manner of negotiating a turn involves pushing on one end of handle 30 with greater force than on the other end, and for sharp turns, typically involves pulling on one end while pushing on the other. For example, when the user pushes patient support 10 straight ahead, the forces applied to first end 38 and second end 40 of handle 30 are roughly equal in magnitude and both are positive; but when the user negotiates a turn, the sum of the first force signal 43 and the second force signal 45 is reduced, which causes reduced motor horsepower 47 to be provided to traction device 26. This reduces the motor horsepower 47 provided to traction device 26, which in turn reduces the velocity of patient support 10, which in turn facilitates the negotiation of the turn.

It is further envisioned that a second traction device (not shown) may be provided and driven independently from the first traction device 26. The second traction device would be laterally offset from the first traction device 26. The horsepower provided to the second traction device would be weighted in favor of the second force signal 45 to further facilitate negotiating of turns.

Next, FIG. 4A is an electrical schematic diagram showing selected aspects of one embodiment of input system 20 of propulsion system 17 of FIG. 2. In particular, FIG. 4A depicts a first load cell 62, a second load cell 64, and a summing control circuit 66. Regulated 8.5 V power ("Vcc") to these components is supplied by the illustrative embodiment of power reservoir 48 as discussed above in connection with FIG. 2. First load cell 62 includes four strain gauges illustrated as resistors: gauge 68a, gauge 68b, gauge 68c, and gauge 68d. As shown in FIG. 4A, these four gauges 68a, 68b, 68c, 68d are electrically connected within load cells 62, 64 to form a Wheatstone bridge.

In one embodiment, each of the load cells 62, 64 is a commercially available HBM Co. Model No. MED-400 06101. These load cells 62, 64 of FIG. 4A are an embodiment of first and second user input devices 32, 34 of FIG. 2. According to alternative embodiments, the user inputs are other elastic or sensing elements configured to detect the force on the handle, deflection of the handle, or other position or force related characteristics.

In a manner which is well known, Vcc is electrically connected to node A of the bridge, ground (or common) is applied to node B, a signal S1 is obtained from node C, and a signal S2 is obtained from node D. The power to second



load cell **64** is electrically connected in like fashion to first load cell **62**. Thus, nodes E and F of second load cell **64** correspond to nodes A and B of first load cell **62**, and nodes G and H of second load cell **64** correspond to nodes C and D of first load cell **62**. However, as shown, signal S3 (at node G) and signal S4 (at node H) are electrically connected to summing control circuit **66** in reverse polarity as compared to the corresponding respective signals S1 and S2.

Summing control circuit **66** of FIG. 4A is one embodiment of the speed controller **36** of FIG. 2. Accordingly, it should be readily appreciated that a first differential signal (S1–S2) from first load cell **62** is one embodiment of the first force signal **43** discussed above in connection with FIG. 2, and, likewise, a second differential signal (S3–S4) from second load cell **64** is one embodiment of the second force signal **45** discussed above in connection with FIG. 2. The summing control circuit **66** includes a first buffer stage **76**, a second buffer stage **78**, a first pre-summer stage **80**, a second pre-summer stage **82**, a summer stage **84**, and a directional gain stage **86**.

First buffer stage **76** includes an operational amplifier **88**, a resistor **90**, a resistor **92**, and a potentiometer **94** which are electrically connected to form a high input impedance, noninverting amplifier with offset adjustability as shown. The noninverting input of operational amplifier **88** is electrically connected to node C of first load cell **62**. Resistor **90** is very small relative to resistor **92** so as to yield practically unity gain through buffer stage **76**. Accordingly, resistor **90** is 1 k ohm, and resistor **92** is 100 k ohm. Potentiometer **94** allows for calibration of summing control circuit **66** as discussed below. Accordingly, potentiometer **94** is a 20 k ohm linear potentiometer. It should be readily understood that second buffer stage **78** is configured in identical fashion to first buffer stage **76**; however, the noninverting input of the operational amplifier in the second buffer stage **78** is electrically connected to node H of second load cell **64** as shown.

First pre-summer stage **80** includes an operational amplifier **96**, a resistor **98**, a capacitor **110**, and a resistor **112** which are electrically connected to form an inverting amplifier with low pass filtering as shown. The noninverting input of operational amplifier **96** is electrically connected to the node D of first load cell **62**. Resistor **98**, resistor **112**, and capacitor **110** are selected to provide a suitable gain through first pre-summer stage **80**, while providing sufficient noise filtering. Accordingly, resistor **98** is 110 k ohm, resistor **112** is 1 k ohm, and capacitor **110** is 0.1  $\mu$ F. It should be readily appreciated that second pre-summer stage **82** is configured in identical fashion to first pre-summer stage **80**; however, the noninverting input of the operational amplifier in second pre-summer stage **82** is electrically connected to node G of second load cell **64** as shown.

Summer stage **84** includes an operational amplifier **114**, a resistor **116**, a resistor **118**, a resistor **120**, and a resistor **122** which are electrically connected to form a differential amplifier as shown. Summer stage **84** has an inverting input **124** and a noninverting input **126**. Inverting input **124** is electrically connected to the output of operational amplifier **96** of first pre-summer stage **80** and noninverting input **126** is electrically connected to the output of the operational amplifier of second pre-summer stage **82**. Resistor **116**, resistor **118**, resistor **120**, and resistor **122** are selected to provide a roughly balanced differential gain of about 10. Accordingly, resistor **116** is 100 k ohm, resistor **118** is 100 k ohm, resistor **120** is 10 k ohm, and resistor **122** is 12 k ohm. If an ideal operational amplifier is used in the summer stage, resistors **120**, **122** would have the same value (for example, 12 K

ohms) so that both the noninverting and inverting inputs of the summer stage are balanced; however, to compensate for the slight imbalance in the actual noninverting and inverting inputs, resistors **120**, **122** are slightly different in the illustrative embodiment.

Directional gain stage **86** includes an operational amplifier **128**, a diode **130**, a potentiometer **132**, a potentiometer **134**, a resistor **136**, and a resistor **138** which are electrically connected to form a variable gain amplifier as shown. The noninverting input of operational amplifier **128** is electrically connected to the output of operational amplifier **114** of summer stage **84**. Potentiometer **132**, potentiometer **134**, resistor **136**, and resistor **138** are selected to provide a gain through directional gain stage **86** which varies with the voltage into the noninverting input of operational amplifier **128** generally according to the relationship between the voltage out of operational amplifier **128** and the voltage into the noninverting input of operational amplifier **128** as depicted in FIG. 4A. Accordingly, potentiometer **132** is trimmed to 30 k ohm, potentiometer **134** is trimmed to 30 k ohm, resistor **136** is 22 k ohm, and resistor **138** is 10 k ohm. All operational amplifiers are preferably National Semiconductor type LM258 operational amplifiers.

In operation, the components shown in FIG. 4A provide the speed control signal **46** to motor drive **44** generally in the following manner. First, the user calibrates speed controller **36** (FIG. 2) to provide the speed control signal **46** within limits that are consistent with the configuration of motor drive **44**. As discussed above in the illustrative embodiment, motor drive **44** responds to a voltage input range from roughly 0.3 VDC (for full reverse motor drive) to roughly 4.7 VDC (for full forward motor drive) with roughly 2.3–2.7 VDC input null reference/deadband (corresponding to zero motor speed). Thus, with no load on first load cell **62**, the user adjusts potentiometer **94** of first buffer stage **76** to generate 2.5 V at inverting input **124** of summer stage **84**, and with no load on second load cell **64**, the user adjusts the corresponding potentiometer in second buffer stage **78** to generate 2.5 V at noninverting input **126** of summer stage **84**.

The no load condition occurs when the user is neither pushing nor pulling handle **30** as shown in FIGS. 1 and 5. A voltage of 2.5 V at inverting input **124** of summer stage **84** and 2.5 V at noninverting input **126** of summer stage **84** (simultaneously) causes summer stage **84** to generate very close to 0 V at the output of operational amplifier **114** (the input of operational amplifier **128** of the directional gain stage **86**), which in turn causes directional gain stage **86** to generate a roughly 2.5 V speed control signal on the output of operational amplifier **128**. Thus, by properly adjusting the potentiometers of first and second buffer stages **76**, **78**, the user ensures that no motor horsepower is generated at no load conditions.

Calibration also includes setting the desirable forward and reverse gains by adjusting potentiometer **132** and potentiometer **134** of directional gain stage **86**. To this end, it should be appreciated that diode **130** becomes forward biased when the voltage at the noninverting input of operational amplifier **128** begins to drop sufficiently below the voltage at the inverting input of operational amplifier **128**. Further, it should be appreciated that the voltage at the inverting input of operation amplifier **128** is roughly 2.5 V as a result of the voltage division of the 8.5 V Vcc between resistor **136** and resistor **138**.

As depicted in FIG. 4A, directional gain stage **86** may be calibrated to provide a relatively higher gain for voltages out of differential stage **84** which exceed the approximate 2.5 V



null reference/deadband of motor drive 44 than it provides for voltages out of differential stage 84 which are less than roughly 2.5 V. Thus, the user calibrates directional gain stage 86 by adjusting potentiometer 132 and potentiometer 134 as desired to generate more motor horsepower per unit force on handle 30 in the forward direction than in the reverse direction. Patient supports are often constructed such that they are more easily moved by pulling them in reverse than by pushing them forward. The variable gain calibration features provided in directional gain stage 86 tend to compensate for the directional difference.

After calibration, the user ensures that external power input 50 (FIG. 2) is not connected to a power line, and then places casters 22 into a steer mode through operation of pedal 61 which causes caster mode detector 54 to generate a representative signal 56. In response, an illustrative embodiment of traction engagement controller 28 provides an actuation force 104 which causes an illustrative embodiment of traction device 26 to contact floor 24. Next, the user inputs an enable command through third user input device 35 (activates a switch). Then, the user pushes or pulls on first handle member 38 and/or second handle member 40, which imparts a first input force 39 to first load cell 62 and/or a second input force 41 to second load cell 64, causing a first differential signal (S1-S2) and/or a second differential signal (S3-S4) to be transmitted to first pre-summer stage 80 and/or second pre-summer stage 82, respectively. Although first load cell 62 and second load cell 64 are electrically connected in relatively reversed polarities, summer stage 84 effectively inverts the output of second pre-summer stage 82, which provides that the signs of the forces imparted to first member 38 and second member 40 of handle 30 are ultimately actually consistent relevant to the actions of pushing and/or pulling patient support 10 of FIG. 1.

First buffer stage 76 and second buffer stage 78 facilitate obtaining first differential signal (S1-S2) and second differential signal (S3-S4) from first load cell 62 and second load cell 64. The differential signals from the Wheatstone bridges of load cells 62, 64 reject signals which might otherwise be undesirably generated by torsional type pushing or pulling on members 38, 40 of handle 30. Thus, the user can increase the magnitude of the sum of the forces imparted to first and second handle members 38, 40, respectively, to increase the speed control signal 46 or decrease the magnitude of the sum to decrease the speed control signal 46. These changes in the speed control signal 46 cause traction device 26 to propel patient support 10 in either the forward or reverse direction as desired.

FIG. 4B shows an alternate embodiment of aspects of input system 20 of propulsion system 17 of FIG. 2. Like the circuit of FIG. 4A, the circuit of FIG. 4B includes first load cell 62 and second load cell 64, both of which are identical to those described above. The circuit of FIG. 4B further includes a summing control circuit 66' for generating the speed control signal described above. Summing control circuit 66' generally includes a noise filtering stage 68', an instrumentation amplifier 70', a voltage reference circuit 72', a first buffering stage 74', and a second buffering stage 76'.

Noise filtering stage 68' includes a first inductor 78', which is connected at one end to signal S1 from node C of first load cell 62 and signal S4 from node H of second load cell 64, and a second inductor 80', which is connected at one end to signal S2 from node D of first load cell 62 and signal S3 from node G of second load cell 64. The other end of first inductor 78' is connected to the negative input pin ( $V_{-IN}$ ) of instrumentation amplifier 70' and to one side of capacitor 82'. Similarly, the other end of second inductor 80' is

connected to the positive input pin ( $V_{+IN}$ ) of instrumentation amplifier 70' and to the other side of capacitor 82'.

Instrumentation amplifier 70' is a commonly available precision instrumentation amplifier for measuring low noise differential signals such as an INA122 amplifier manufactured by Texas Instruments and other integrated circuit manufacturers. Instrumentation amplifier 70' includes two internal operational amplifiers 84', 86' connected to one another and to internal resistors R1-R4 in the manner shown in FIG. 4B. External resistor  $R_G$  is connected between the inverting inputs of operational amplifiers 84', 86' and establishes the gain of instrumentation amplifier 70' according to the equation  $GAIN=5+(200K/R_G)$ . In one embodiment of the invention,  $R_G$  is 73.2 ohms. The output voltage ( $V_O$ ) of instrumentation amplifier 70' conforms to the equation  $V_O=(V_{+IN}(-) V_{-IN})(GAIN)$ .

As shown in FIG. 4B, the reference voltage input ( $V_{REF}$ ) of instrumentation amplifier 70' is connected to the output of voltage reference circuit 72'. Voltage reference circuit 72' includes operational amplifier 88', capacitor 90', and voltage divider circuit 92' connected to the noninverting input of amplifier 88' as shown. According to one embodiment of the invention, the resistors 94', 96' of voltage divider circuit 92' are selected to provide a +2.5 volt output from amplifier 88'. Accordingly, in such an embodiment,  $V_{REF}=+2.5$  volts, and  $V_O$  of instrumentation amplifier 70' varies above and below +2.5 volts depending upon the polarity of the difference between the positive and negative inputs,  $V_{+IN}$  and  $V_{-IN}$ , respectively.

First buffering stage 74' includes resistors 98' and 100', capacitor 102', diode 104' and amplifier 106' connected in the manner shown in FIG. 4B. Second buffering stage 76' includes resistors 108', 110', and 112', operational amplifier 113', and diode 114' connected in the manner shown in FIG. 4B. The output of second buffering stage 76' corresponds to speed control signal 46 of FIG. 2. The configuration and component values of first and second buffering stages 74', 76' provide isolation between the output of instrumentation amplifier 70' and the input to motor drive 44 (FIG. 2) according to well-known principles in the art.

In operation, when the user is neither pushing nor pulling handle 30 (i.e., under no load conditions as shown in FIGS. 1 and 5), the output of instrumentation amplifier 70' ( $V_O$ ) is +2.5 volts because  $V_{+IN}=V_{-IN}$ , and no horsepower is generated at motor drive 44. When the user places casters 22 into a steer mode through operation of pedal 61, causing traction device 26 to contact floor 24, and inputs an enable command through third user input device 35, the user may push or pull on first handle member 38 and/or second handle member 40 to move patient support 10. Specifically, the forces 39, 41 applied to first and second load cells 62, 64, respectively, cause voltages at nodes C, D, G, and H that combine to result in either a positive  $V_O$  from instrumentation amplifier 70' or a negative  $V_O$  from instrumentation amplifier 70'. As indicated above,  $V_O$  (once passed through buffering stages 74', 76') corresponds to speed control signal 46. The polarity and magnitude of speed control signal 46 determines the direction and speed of patient support 10 as described in detail above.

The input system of the present disclosure may be used on motorized support frames other than beds. For example, the input system may be used on carts, pallet movers, or other support frames used to transport items from one location to another.

As shown in FIGS. 1, 5, 6A, and 6B, each load cell 62, 64 is directly coupled to bedframe 12 by a bolt 140 extending through a plate 142 of bedframe 12 into each load cell 62,



64. First and second handle members **38**, **40** of handle **30** are coupled to respective load cells **62**, **64** by bolts **71** so that handle **30** is coupled to bedframe **12** through load cells **62**, **64**.

An embodiment of third user input device **35** is shown in FIGS. **1**, **5**, **6A**, **6B**, **15**, and **16**. Input device **35** includes a bail **75** pivotally coupled to a lower portion of handle **30**, a spring mount **73** coupled to first handle member **38** of handle **30**, a pair of loops **79**, **81** coupled to bail **75**, and a spring **83** coupled to spring mount **73** and loop **79**. Bail **75** and loops **79**, **81** are pivotable between an on/enable position, shown in FIGS. **6A** and **6B**, and an off/disable position as shown in FIG. **5**.

User input device **35** further includes a pair of pins **89** coupled to handle **30** to limit the range of motion of loops **79**, **81** and bail **75**. When bail **75** is in the on/enable position, the weight of bail **75** acts against the bias provided by spring **83**. However, if a slight force is applied against bail **75** in direction of arrow **91**, spring **83** with the assistance of said force will pull bail **75** to the off/disable position to shut down propulsion system **16**. Thus, if bail **75** is accidentally bumped, bail **75** will flip to the off/disable position to disable use of propulsion system **16**. According to alternative embodiments of the present disclosure, spring **83** is coupled to the upper arm of loop **79**.

User input device **35** further includes a relay switch **85** positioned adjacent a pin **97** coupled to first end **87** of bail **75** and a keyed lockout switch **93** coupled to plate **142** as shown in FIG. **15**. Relay switch **85** and keyed lockout switch **93** are coupled in series to provide the enable and disable commands. Keyed lockout switch **93** must be turned to an “on” position by a key **95** for an enable command and relay switch must be in a closed position for an enable command. It should be appreciated that the keyed lockout switch **93** is optional and may be eliminated if not desired.

When bail **75** moves to the disable position as shown in FIG. **16**, pin **97** moves switch **85** to an open position to generate a disable command. When bail **75** moves to the enable position as shown in FIG. **15**, pin **97** moves away from switch **85** to permit switch **85** to move to the closed position to generate an enable command when keyed lockout switch **93** is in the on position permitting lowering of the illustrative embodiment of traction device **26** into contact with floor **24**. Thus, if bail **75** is moved to the raised/disable position or key **95** is not in keyed lockout switch **93** or not turned to the “on” position, traction device **26** will not lower into contact with floor **24**.

User input device **35** further includes a pair of pins **89** coupled to handle **30** to limit the range of motion of loops **79**, **81** and bail **75**. When bail **75** is in the on/enable position, the weight of bail **75** acts against the bias provided by spring **83**. However, if a slight force is applied against bail **75** in direction **91**, spring **83** with the assistance of said force will pull bail **75** to the off/disable position to shut down propulsion system **16**. Thus, if bail **75** is accidentally bumped, bail **75** will flip to the off/disable position to disable use of propulsion system **16**. For example, if a caregiver leans over the headboard to attend to a patient, the caregiver would likely bump bail **75** causing it to flip to the off/disable position. Thus, even if the caregiver applies force to handle **30** while leaning over the headboard, propulsion device **18** will not operate.

An illustrative embodiment propulsion device **18** is shown in FIGS. **1** and **8–14**. Propulsion device **18** includes an illustrative embodiment traction device **26** comprising a wheel **150**, an illustrative embodiment traction engagement controller **28** comprising a traction device mover, illustratively

a wheel lifter **152**, and a chassis **151** coupling wheel lifter **152** to bedframe **12**. According to alternative embodiments as described in greater detail below, other traction devices or rolling supports such as multiple wheel devices, track drives, or other devices for imparting motion to a patient support are used as the traction device. Furthermore, according to alternative embodiments, other configurations of traction engagement controllers are provided, such as the wheel lifter described in U.S. Pat. No. 5,348,326 to Fullenkamp, et al., U.S. Pat. No. 5,806,111 to Heimbrock, et al., and U.S. Pat. No. 6,330,926 to Heimbrock, et al., the disclosures of which are expressly incorporated by reference herein.

Wheel lifter **152** includes a wheel mount **154** coupled to chassis **151** and a wheel mount mover **156** coupled to wheel mount **154** and chassis **151** at various locations. Motorized wheel **150** is coupled to wheel mount **154** as shown in FIG. **8**. Wheel mount mover **156** is configured to pivot wheel mount **154** and motorized wheel **150** about a pivot axis **158** to move motorized wheel **150** between storage and use positions as shown in FIGS. **10–12**. Wheel mount **154** is also configured to permit motorized wheel **150** to raise and lower during use of patient support **10** to compensate for changes in elevation of patient support **10**. For example, as shown in FIG. **13**, wheel mount **154** and wheel **150** may pivot in a clockwise direction **160** about pivot axis **158** when bedframe **12** moves over a bump in floor **24**. Similarly, wheel mount **154** and motorized wheel **150** are configured to pivot about pivot axis **158** in a counterclockwise **166** direction when bedframe **12** moves over a recess in floor **24** as shown in FIG. **14**. Thus, wheel mount **154** is configured to permit motorized wheel **150** to remain in contact with floor **24** during changes in elevation of floor **24** relative to patient support **10**.

Wheel mount **154** is also configured to provide the power to rotate motorized wheel **150** during operation of propulsion system **16**. Wheel mount **154** includes a motor mount **170** coupled to chassis **151** and an illustrative embodiment electric motor **172** coupled to motor mount **170** as shown in FIG. **8**. In the illustrative embodiment, motor **172** is a commercially available Groschopp Iowa Permanent Magnet DC Motor Model No. MM8018.

Motor **172** includes a housing **178** and an output shaft **176** and a planetary gear (not shown). Motor **172** rotates shaft **176** about an axis of rotation **180** and motorized wheel **150** is directly coupled to shaft **176** to rotate about an axis of rotation **182** that is coaxial with axis of rotation **180** of output shaft **176**. Axes of rotation **180**, **182** are transverse to pivot axis **158**.

As shown in FIG. **8**, wheel mount mover **156** further includes an illustrative embodiment linear actuator **184**, a linkage system **186** coupled to actuator **184**, a shuttle **188** configured to slide horizontally between a pair of rails **190** and a plate **191**, and a pair of gas springs **192** coupled to shuttle **188** and wheel mount **154**. Linear actuator **184** is illustratively a Linak model number LA12.1-100-24-01 linear actuator. Linear actuator **184** includes a cylinder body **194** pivotally coupled to chassis **151** and a shaft **196** telescopically received in cylinder body **194** to move between a plurality of positions.

Linkage system **186** includes a first link **198** and a second link **210** coupling shuttle **188** to actuator **184**. First link **198** is pivotally coupled to shaft **196** of actuator **184** and pivotally coupled to a portion **212** of chassis **151**. Second link **210** is pivotally coupled to first link **198** and pivotally coupled to shuttle **188**. Shuttle **188** is positioned between rails **190** and plate **191** of chassis **151** to move horizontally



between a plurality of positions as shown in FIGS. 10–12. As shown in FIG. 10, each of gas springs 192 include a cylinder 216 pivotably coupled to shuttle 188 and a shaft 218 coupled to a bracket 220 of wheel mount 154. According to the alternative embodiments, the linear actuator is directly coupled to the shuttle.

Actuator 184 is configured to move between an extended position as shown in FIG. 10 and a retracted position as shown in FIG. 12–14. Movement of actuator 184 from the extended to retracted position moves first link 198 in a clockwise direction 222. This movement of first link 198 pulls second link 210 and shuttle 188 to the left in direction 224 as shown in FIG. 11. Movement of shuttle 188 to the left in direction 224 pushes gas springs 192 downward and to the left in direction 228 and pushes a distal end 230 of wheel mount 154 downward in direction 232 as shown in FIG. 11.

After wheel 150 contacts floor 24, linear actuator 184 continues to retract so that shuttle 188 continues to move to the left in direction 224. This continued movement of shuttle 188 and the contact of motorized wheel 150 with floor 24 causes gas springs 192 to compress so that less of shaft 218 is exposed, as shown in FIG. 12, until linear actuator 184 reaches a fully retracted position. This additional movement creates compression in gas springs 192 so that gas springs 192 are compressed while wheel 150 is in the normal use position with bedframe 12 at a normal distance from floor 24. This additional compression creates a greater normal force between floor 24 and wheel 150 so that wheel 150 has increased traction with floor 24.

As previously mentioned, bedframe 12 will move to different elevations relative to floor 24 during transport of patient support 10 from one position in the care facility to another position in the care facility. For example, when patient support 10 is moved up or down a ramp, portions of bedframe 12 will be at different positions relative to floor 24 when opposite ends of patient support 10 are positioned on and off of the ramp. Another example is when patient support 10 is moved over a raised threshold or over a depression in floor 24, such as a utility access plate (not shown). The compression in gas springs 192 creates a downward bias on wheel mount 154 in direction 232 so that when bedframe 12 is positioned over a “recess” in floor 24, gas springs 192 move wheel mount 154 and wheel 150 in clockwise direction 160 so that wheel 150 remains in contact with floor 24. When bedframe 12 moves over a “bump” in floor 24, the weight of patient support 10 will compress gas springs 192 so that wheel mount 154 and motorized wheel 150 rotate in counterclockwise direction 166 relative to chassis 151 and bedframe 12, as shown for example, in FIG. 14.

To return wheel 150 to the raised position, actuator 184 moves to the extended position as shown in FIG. 10. Through linkage system 186, shuttle 188 is pushed to the right in direction 234. As shuttle 188 moves in direction 234, the compression in gas springs 192 is gradually relieved until shafts 196 of gas springs 192 are completely extended and gas springs 192 are in tension. The continued movement of shuttle 188 in direction 234 causes gas springs 192 to raise motor mount 154 and wheel 150 to the raised position shown in FIG. 10. The compression of gas springs 192 assists in raising wheel 150. Thus, actuator 184 requires less energy and force to raise wheel 150 than to lower wheel 150.

An exploded assembly view of chassis 151, wheel 150, and wheel lifter 152 is provided in FIG. 9. Chassis 151 includes a chassis body 250, a bracket 252 coupled to chassis body 250 and bedframe 12, an aluminum pivot plate 254 coupled to chassis body 250, a pan 256 coupled to a first

arm 258 of chassis body 250, a first rail member 260, a second rail member 262, a containment member 264, a first stiffening plate 266 coupled to second rail member 262, a second stiffening plate 268 coupled to first rail member 260, and an end plate 270 coupled to bedframe 12 and first and second rail members 260, 262. Wheel mount 154 further includes a first bracket 272 pivotably coupled to chassis body 250 and pivot plate 254, an extension body 274 coupled to bracket 272 and motor 172, and a second bracket 276 coupled to motor 172.

Wheel 150 includes a wheel member 278 having a central hub 280 and a pair of locking members 282, 284 positioned on each side of central hub 280. To couple wheel 150 to shaft 176 of motor 172, first locking member 282 is positioned over shaft 176, then wheel member 278 is positioned over shaft 176, then second locking member 284 is positioned over shaft 176. Bolts (not shown) are used to draw first and second locking members 282, 284 together. Central hub 280 has a slight taper and inner surfaces of first and second locking members 282, 284 have complimentary tapers. Thus, as first and second locking members 282, 284 are drawn together, central hub 280 is compressed to grip shaft 176 of motor 172 to securely fasten wheel 150 to shaft 176.

First rail member 260 includes first and second vertical walls 286, 288 and a horizontal wall 290. Vertical wall 286 is welded to first arm 258 of chassis body 250 so that an upper edge 292 of first vertical wall 286 is adjacent to an upper edge 294 of first arm 258. Similarly, second rail member 262 includes a first vertical wall 296, a second vertical wall 298, and a horizontal wall 310. Second vertical wall 298 is welded to a second arm 312 of chassis body 250 so that an upper edge 314 of second vertical wall 298 is adjacent to an upper edge 316 of second arm 312. End plate 270 is welded to ends 297, 299 of first and second rail members 260, 262.

Containment member 264 includes a first vertical wall 318, a second vertical wall 320, and a horizontal wall 322. Second wall 288 of first rail member 260 is coupled to an interior of first vertical wall 318 of containment member 264. Similarly, first vertical wall 296 of second rail member 262 is coupled to an interior of second vertical wall 320. As shown in FIG. 10, shuttle 188 is trapped between horizontal wall 322 and vertical walls 288, 296 so that vertical walls 288, 286 define rails 190 and horizontal wall 322 defines plate 191.

Wheel lifter 152 further includes a pair of bushings 324 having first link 198 sandwiched therebetween. A pin pivotally couples bushings 324 and first link 198 to containment member 264 so that containment member 264 defines portion 212 of chassis 151 as shown in FIG. 10.

When fully assembled, first and second rail members 260, 262 include a couple of compartments. Motor controller 326 containing the preferred motor driver circuitry is positioned within first rail member 260 and circuit board 328 containing the preferred input system circuitry and relay 330 are positioned in first rail member 260.

Shuttle 188 includes a first slot 340 for pivotally receiving an end of second link 210. Similarly, shuttle 188 includes second and third slots 342 for pivotally receiving ends of gas spring 292 as shown in FIG. 9. Bracket 220 is coupled to the second bracket 276 with a deflection guard 334 sandwiched therebetween. Gas springs 292 are coupled to bracket 220 as shown in FIG. 9.

A plate 336 is coupled to pan 256 to provide a stop that limits forward movement of wheel mount 154. Furthermore, second bracket 276 includes an extended portion 338 that



provides a second stop for wheel mount **154** that limits backward movement of wheel mount **154**.

Referring now to FIGS. **17–40**, a second embodiment patient support **10'** is illustrated as including a second embodiment propulsion system **16'** coupled to the bedframe **12** in a manner similar to that identified above with respect to the previous embodiment. The propulsion system **16'** operates substantially in the same manner as the first embodiment propulsion system **16** illustrated in FIG. **2** and described in detail above. According to the second embodiment, the propulsion system **16'** includes a propulsion device **18'** and an input system **20'** coupled to the propulsion device **18'**. In the manner described above with respect to the first embodiment, the input system **20'** is provided to control the speed and direction of the propulsion device **18'** so that a caregiver may direct the patient support **10'** to the proper position in the care facility.

The input system **20'** of the second embodiment patient support **10'** is substantially the same as the input system **20** of the above-described embodiment as illustrated in FIG. **2**. However, as illustrated in FIGS. **36–40** and as described in greater detail below, a user interface or handle **430** is provided as including first and second handle members **431** and **433** positioned in spaced relation to each other and supported for relative independent movement in response to the application of first and second input forces **39** and **41** (FIG. **2**). The first handle member **431** is coupled to a first user input device **32'** while the second handle member **433** is coupled to a second user input device **34'**. The handle members **431** and **433** are configured to transmit first input force **39** from the first handle member **431** to the first user input device **32'** and to transmit second input force **41** from the second handle member **433** to the second user input device **34'**.

Referring further to FIGS. **36–40**, the first and second handle members **431** and **433** comprise elongated tubular members **434** extending between opposing upper and lower ends **436** and **437**. The upper end **436** of each first and second handle member **431** and **433** includes a third user input, or enabling, device **435**, preferably a normally open push button switch requiring continuous depression in order for the motor drive **44** to supply power to the motor **42**. A conventional handgrip (not shown) formed from a resilient material may be coupled to the upper end **436** of the handle members **431** and **433** for improving caregiver comfort and frictional engagement. The lower end **437** of each first and second handle member **431** and **433** is concentrically received within a mounting tube **438** fixed to the bedframe **12**. More particularly, with reference to FIG. **40**, a pin **440** passes through each tubular member **434** and into the sidewalls of the mounting tube **438** in order to secure the first and second handle members **431** and **433** thereto. A collar **442** may be concentrically received around an upper end of the mounting tube **438** in order to shield the pin **440**.

A mounting block **443** is secured to a lower surface of the bedframe **12** and connects the casters **22** thereto. A load cell **62, 64** of the type described above is secured to the mounting block **443**, typically through a conventional bolt **444**, and is in proximity to the lower end **437** of each first and second handle members **431** and **433**. Each load cell **62, 64** is physically connected to a lower end of the tubular member **434** by a bolt **444** passing through a pair of slots **446** formed within lower end **437**. As may be readily appreciated, force applied proximate the upper end **436** of the first and second handle members **431** and **433** is transmitted downwardly to the lower end **437**, through the bolt **444** and into the load cell **62, 64** for operation in the manner described above with

respect to FIGS. **4A** and **4B**. It should be appreciated that the independent supports and the spaced relationship of the first and second handle members **431** and **433** prevent the transmission of forces directly from one handle member **431** to the other handle member **433**. As such, the speed controller **36** is configured to operate upon receipt of a single force signal **43** or **45** due to application of only a single force **39** or **41** to a single user input device **32** or **34**.

A keyed lockout switch **93** configured to receive a lockout key **95**, of the type described above, is illustratively supported on the bedframe **12** proximate the first and second handle members **38** and **40** and may be used to prevent unauthorized operation of the patient support **10**. Again, the keyed lockout switch **93** is optional and may be eliminated if not desired.

The alternative embodiment propulsion device **18'** is shown in greater detail in FIGS. **18–30**. The propulsion device **18'** includes a rolling support in the form of a drive track **449** having rotatably supported first and second rollers **450** and **452** supporting a track or belt **453** for movement. The first roller **450** is driven by motor **42** while the second roller **452** is an idler. The second embodiment traction engagement controller **28'** includes a traction device mover, illustratively a rolling support lifter **454**, and a chassis **456** coupling the rolling support lifter **454** to bed frame **12**.

The rolling support lifter **454** includes a rolling support mount **458** coupled to the chassis **456** and a rolling support mount mover, or simply rolling support mover **460**, coupled to rolling support mount **458** and chassis **456** at various locations. The rollers **450** and **452** are rotatably supported intermediate side plates **462** and spacer plates **464** forming the rolling support mount **458**. The rollers **450** and **452** preferably include a plurality of circumferentially disposed teeth **466** for cooperating with a plurality of teeth **468** formed on an inner surface **470** of the belt **453** to provide positive engagement therewith and to prevent slipping of the belt **453** relative to the rollers **450** and **452**. Each roller **450** and **452** likewise preferably includes a pair of annular flanges **472** disposed near a periphery thereof to assist in tracking or guiding belt **453** in its movement.

A drive shaft **473** extends through the first roller **450** while a bushing **475** is received within the second roller **452** and receives a nondriven shaft **476**. A plurality of brackets **477** are provided to facilitate connection of the chassis **456** of bedframe **12**.

The rolling support mover **460** is configured to pivot the rolling support mount **458** and motorized track drive **449** about a pivot axis **474** to move the traction belt **453** between a storage position spaced apart from floor **24** and a use position in contact with floor **24** as illustrated in FIGS. **22–24**. Rolling support mount **458** is further configured to permit the track drive **449** to raise and lower during use of the patient support **10'** in order to compensate for changes in elevation of the patient support **10'**. For example, as illustrated in FIG. **25**, rolling support mount **458** and track drive **449** may pivot in a counterclockwise direction **166** about pivot axis **474** when bedframe **12** moves over a bump in floor **24**. Similarly, rolling support mount **458** and motorized track drive **449** are configured to pivot about pivot axis **474** in a clockwise direction **160** when bedframe **12** moves over a recess in floor **24** as illustrated in FIG. **26**. Thus, rolling support mount **458** is configured to permit traction belt **453** to remain in contact with floor **24** during changes in elevation of floor **24** relative to patient support **10**.

The rolling support mount **458** further includes a motor mount **479** supporting motor **42** and coupled to chassis **456** in order to provide power to rotate the first roller **450** and,



in turn, the traction belt 453. The motor 42 may be of the type described in greater detail above. Moreover, the motor 172 includes an output shaft 176 supported for rotation about an axis of rotation 180. The first roller 450 is directly coupled to the shaft 176 to rotate about an axis of rotation 478 that is coaxial with the axis of rotation 180 of the output shaft 176. The axes of rotation 180 and 478 are likewise coaxially disposed with the pivot axis 474.

The rolling support mount mover 460 further includes a linear actuator 480 connected to a motor 482 through a conventional gearbox 484. A linkage system 486 is coupled to the actuator 480 through a pivot arm 488. Moreover, a first end 490 of the pivot arm 488 is connected to the linkage system 486 while a second end 492 of the arm 488 is connected to a shuttle 494. The shuttle 494 is configured to move substantially horizontally in response to pivoting movement of the arm 488. The arm 488 is operably connected to the actuator 480 through a hexagonal connecting shaft 496 and link 497.

The linkage system 486 includes a first link 498 and a second link 500 coupling the actuator 480 to the rolling support mount 458. The first link 498 includes a first end which is pivotally coupled to the arm 488 and a second end which is pivotally coupled to a first end of the second link 500. The second link 500, in turn, includes a second end which is pivotally coupled to the side plate 462 of the rolling support mount 458.

The shuttle 494 comprises a tubular member 504 receiving a compression spring 506 therein. The body of the shuttle 494 includes an end wall 508 for engaging a first end 509 of the spring 506. A second end 510 of the spring 506 is adapted to be engaged by a piston 512. The piston 512 includes an elongated member or rod 514 passing coaxially through the spring 506. An end disk 516 is connected to a first end of member 514 for engaging the second end 510 of the spring 506.

A second end of the elongated member 514 is coupled to a flexible linkage, preferably a chain 518. The chain 518 is guided around a cooperating sprocket 520 supported for rotation by side plate 462. A first end of the chain 518 is connected to the elongated member 514 through a pin 521 while a second end of the chain 518 is coupled to an upwardly extending arm 522 of the side plate 462.

The actuator 480 is configured to move between a retracted position as shown in FIG. 22 and an extended position as shown in FIGS. 24–26 in order to move the connecting link 497 and connecting shaft 496 in a clockwise direction 160. This movement of the arm 522 moves the shuttle 494 to the left in the direction of arrow 224 as illustrated in FIG. 23. Movement of the shuttle 494 to the left results in similar movement of the spring 506 and piston 512 which, in turn, pulls the chain 518 around the sprocket 520. This movement of the chain 518 around the sprocket 520 in a clockwise direction 160 results in the rolling support mount 458 being moved in a downward direction as illustrated by arrow 232 in FIG. 23.

Extension of the actuator 480 is stopped when an engagement arm 524 supported by connecting link 497 contacts a limit switch 526 supported by the chassis 456. A retracted position of actuator 480 is illustrated in FIG. 34 while an extended position of actuator 480 engaging the limit switch 526 is illustrated in FIG. 35.

After the traction belt 453 contacts floor 24, the actuator 480 continues to extend so that the tubular shuttle 494 continues to move to the left in direction of arrow 224. This continued movement of the shuttle 494 and the contact of motorized belt 453 with floor 24 causes compression of

springs 506. Moreover, continued movement of the shuttle 494 occurs relative to the piston 512 which remains relatively stationary due to its attachment to the rolling support mount 458 through the chain 518. As such, continued movement of the shuttle 494 causes the end wall 508 to compress the spring 506 against the disk 516 of the piston 512. Such additional movement creates compression in the springs 506 such that the springs 506 are compressed while the belt 453 is in the normal use position with bedframe 12 at a normal distance from the floor 24. This additional compression creates a greater normal force between the floor 24 and belt 453 so that the belt 453 has increased traction with the floor. In order to further facilitate traction with the floor 24, the belt 453 may include a textured outer surface.

As mentioned earlier, the bedframe 12 will typically move to different elevations relative to floor 24 during transport of patient support 10' from one position in the care facility to another position in the care facility. For example, when patient support 10' is moved up or down a ramp, portions of bedframe 12 will be at different positions relative to the floor 24 when opposite ends of the patient support 10' are positioned on and off the ramp. Another example is when patient support 10 is moved over a raised threshold or over a depression in floor 24, such as an utility access plate (not shown). The compression in springs 506 create a downward bias on rolling support mount 458 in direction 232 so that when bedframe 12 is positioned over a "recess" in floor 24, spring 506 moves rolling support mount 458 and belt 453 in clockwise direction 160 about the pivot axis 474 so that the belt 453 remains in contact with the floor 24. Likewise, when bedframe 12 moves over a "bump" in floor 24, the weight of patient support 10 will compress springs 506 so that rolling support mount 458 and belt 453 rotate in counterclockwise direction 166 relative to chassis 456 and bedframe 12, as illustrated in FIG. 26.

To return the track drive 449 to the storage position, the actuator 480 moves to the retracted position as illustrated in FIG. 22 wherein the arm 488 is rotated counterclockwise by the connecting shaft 496. More particularly, as the actuator 480 retracts, the connecting link 497 causes the connecting shaft 496 to rotate in a counterclockwise direction, thereby imparting similar counterclockwise movement to the arm 488. The tubular shuttle 494 is thereby pushed to the right in direction 234. Simultaneously, the linkage 486 is pulled to the left thereby causing the rolling support mount 458 to pivot in a counterclockwise direction about the pivot axis 474 such that the track drive 449 are raised in a substantially vertical direction. As shuttle 494 moves in direction 234, the compression in springs 506 is gradually relieved until the springs 506 are again extended as illustrated in FIG. 22.

An exploded assembly view of chassis 456, track drive 449, and rolling support lifter 454 is provided in FIG. 21. Chassis 456 includes a chassis body 550 including a pair of spaced side arms 552 and 554 connected to a pair of spaced end arms 556 and 558 thereby forming a box-like structure. A pair of cross supports 560 and 562 extend between the end arms 556 and 558 and provide support for the motor 172 and actuator 480. The rolling support mount 458 is received between the cross supports 560 and 562. The hex connecting shaft 496 passes through a clearance 563 in the first cross support 560 and is rotatably supported by the second cross support 562. A pan 564 is secured to a lower surface of the chassis body 550 and includes an opening 566 for permitting the passage of the belt 453 therethrough. The sprockets 520 are rotatably supported by the cross supports 560 and 562.

A third embodiment patient support 10" is illustrated in FIGS. 41–63 as including an alternative embodiment pro-



pulsion system 16" coupled to the bedframe 12 in a manner similar to that identified above with respect to the previous embodiments. The alternative embodiment propulsion system 16" includes a propulsion device 18" and an input system 20" coupled to the propulsion device 18" in the manner described above with respect to the previous embodiments and as disclosed in FIG. 2.

The input system 20" of the third embodiment patient support 10" is substantially similar to the input system 20" of the second embodiment as described above in connection with FIGS. 36–40. As illustrated in FIGS. 57, 58, and 60–63, the user interface or handle 730 of the third embodiment includes first and second handle members 731 and 733 as in the second embodiment handle 430. However, these first and second handle members 731 and 733 are configured to be selectively positioned in an upright active position (in phantom in FIG. 63) or in a folded stowed position (in solid line in FIG. 63). Furthermore, the first and second user input devices 32 and 34 of input system 20" includes strain gauges 734 supported directly on outer surfaces of the handle members 731 and 733.

As in the second embodiment, the third user input device 735 of the third embodiment comprises a normally open push button switches of the type including a spring-biased button 736 in order to maintain the switch open when the button is not depressed. However, the switches 735 are positioned within a side wall of a tubular member 751 forming the handle members 731 and 733 such that the palms or fingers of the caregiver may easily depress the switches 735 when negotiating the bed 10". In the embodiment illustrated in FIGS. 57 and 58, the switch button 736 faces outwardly away from an end 9 of the patient support 10" such that an individual moving the bed 10" through the handle members 731 and 733 may have his or her palms contacting the button 736. Alternatively, the switch button 736 of each handle member 731 and 733 may be oriented approximately 180° relative to the position shown in FIGS. 57 and 58, thereby facing inwardly toward the mattress 14 such that an individual moving the bed 10" through the handle members 731 and 733 may have his or her fingers contacting the button 736.

With further reference to FIGS. 57, 58, and 60–63, lower ends 742 of the handle members 731 and 733 are supported for selective pivoting movement inwardly toward a center axis 744 of the bed 10". As such, when the bed 10" is not in use, the handle members 731 and 733 may be moved into a convenient and non-obtrusive position. A coupling 746 is provided between proximal and distal portions 748 and 750 of the handle members 731 and 733 in order to provide for the folding or pivoting of the handle members 731 and 733 into a stored position. More particularly, the distal portions 750 of the handle members 731 and 733 are received within the proximal portions 748 of the handle members 731 and 733. More particularly, both handle members 731 and 733 comprise elongated tubular members 751 including distal portions 750 which are slidably receivable within proximal portions 748.

A pair of opposing elongated slots 752 are formed within the sidewall 738 of distal portion 750 of the handle members 731 and 733 (FIGS. 61–63). A pin 754 is supported within the proximal portion 748 of the handle members 731 and 733 and is slidably receivable within the elongated slots 752. As illustrated in FIG. 62, in order to pivot the handle members 731 and 733 downwardly toward the center axis 744 of the bed 10", the distal portion 750 is first pulled upwardly away from the proximal portion 748 wherein the pin 754 slides within the elongated slots 752. The distal

portion 750 may then be folded downwardly into clearance notch 756 formed within the proximal portion 748 of the handle members 731 and 733. A conventional flexible bellows or sleeve (not shown) may be coupled to the handle members 731 and 733 to cover the coupling 746 while not interfering with pivotal movement between the proximal and distal portions 748 and 750 of the handle members 731 and 733.

The third embodiment propulsion device 18" is shown in greater detail in FIGS. 42–50. The propulsion device 18" includes a rolling support comprising a track drive 449 which is substantially identical to the track drive 449 disclosed above with respect to the second embodiment of propulsion device 18".

A third embodiment traction engagement controller 760 includes a traction device mover, illustratively a rolling support lifter 762, and a chassis 764 coupling the rolling support lifter 762 to the bed frame 12. The rolling support lifter 762 includes a rolling support mount 766 coupled to the chassis 764 and a rolling support mount mover, or simply rolling support mover 768, coupled to the rolling support mount 766 and chassis 764 at various locations. The rollers 450 and 452 of track drive 449 are rotatably supported by the rolling support mount intermediate side plates 770. The rolling support mover 768 is configured to pivot the rolling support mount 766 and track drive 449 about pivot axis 772 to move the traction belt 453 between a storage position spaced apart from floor 24 and a use position in contact with floor 24 as illustrated in FIGS. 46–48. Rolling support mount 766 is further configured to permit the track drive to raise and lower during use of the patient support 10" in order to compensate for changes in elevation of the patient support 10" in a manner similar to that described above with respect to the previous embodiments. Thus, rolling support mount 766 is configured to permit traction belt 453 to remain in contact with floor 24 during changes in elevation of floor 24 relative to patient support 10".

Rolling support mount 766 further includes a motor mount 479 supporting a motor 42 coupled to chassis 764 in order to provide power to rotate the first roller 450 and, in turn, the traction belt 453. Additional details of the motor 42 are provided above with respect to the previous embodiments of patient support 10 and 10'.

The rolling support mount mover 768 further includes a linear actuator 774, preferably a 24-volt linear motor including built-in limit travel switches. A linkage system 776 is coupled to the actuator 774 through a pivot bracket 778. Moreover, a first end 780 of pivot bracket 778 is connected to the linkage system 776 while a second end 782 of the pivot bracket 778 is connected to a shuttle 784, preferably an extension spring. The spring 784 is configured to move substantially horizontally in response to pivoting movement of the bracket 778. The bracket 778 is operably connected to the actuator 774 through a hexagonal connecting shaft 786 having a pivot axis 788.

The linkage system 776 includes an elongated link 790 having opposing first and second ends 792 and 794, the first end 792 secured to the pivot bracket 778 and the second end 794 mounted for sliding movement relative to one of the side plates 770. More particularly, a slot 795 is formed proximate the second end 794 of the link 790 for slidably receiving a pin 797 supported by the side plates 770.

The extension spring 784 includes opposing first and second ends 796 and 798, wherein the first end 796 is fixed to the pivot bracket 778 and the opposing second end 798 is fixed to a flexible linkage, preferably chain 518. The chain 518 is guided around a sprocket 520 and includes a first end



31

connected to the spring 784 and a second end fixed to an upwardly extending arm 800 of the side plate 770 of the rolling support mount 766.

The actuator 774 is configured to move between a retracted position as shown in FIG. 46 and an extended position as shown in FIGS. 47 and 48 in order to move the connecting link 497 and connecting hex shaft 786 in a clockwise direction 160. This movement of the hex shaft 786 results in similar movement of the pivot bracket 778 such that the spring 784 moves to the left in the direction of arrow 224 as illustrated in FIG. 47. Movement of the spring 784 to the left results in similar movement of chain 518 which is guided around sprocket 520. In turn, the rolling support mount 766 is moved in a downward direction as illustrated by arrow 232 in FIG. 47.

After the traction belt 453 contacts the floor 24, actuator 424 continues to extend so that the spring 784 is further extended and placed in tension. The tension in spring 784 therefore creates a greater normal force between the floor 24 and the belt 453 so the belt 453 has increased traction with the floor 24. As with the earlier embodiments, the spring 784 facilitates movement of the traction device 26 over a raised threshold or bump or over a depression in floor 24.

In order to return the track drive 449 to the storage position, actuator 774 moves to the retracted position as illustrated in FIG. 46 wherein the pivot bracket 778 is rotated counterclockwise by the hex shaft 786. More particularly, as the actuator 774 retracts, the connecting link 497 causes the hex shaft 786 to rotate in a counterclockwise direction, thereby imparting similar counterclockwise pivoting movement to the pivot bracket 778. The linkage 776 is thereby pulled to the left causing the rolling support mount 766 to pivot in a counterclockwise direction about the pivot axis 772 such that the track drive 449 is raised in a substantially vertical direction. It should be noted that initial movement of the link 790 will cause the pin 797 to slide within the elongated slot 795. However, as the pin 797 reaches its end of travel within the slot 795, the link 790 will pull the mount 766 upwardly.

Although the invention has been described in detail with reference to illustrative embodiments, variations and modifications exist within the scope and spirit of the invention as described and defined in the following claims.

32

The invention claimed is:

1. A patient support comprising:

- a bed frame;
- a plurality of casters to support the bed frame on a floor;
- a power source;
- a motor operably coupled to the power source;
- a drive track operably coupled to the motor to move the bed frame across the floor, the drive track including a first roller driven by the motor, a second roller, and a belt supported by the first and second roller, the belt including a plurality of belt teeth, the first roller and second roller each include a plurality of roller teeth located on their outer surface, wherein at least a portion of the plurality of roller teeth are sized to engage at least a portion of the plurality of belt teeth, wherein the rollers are spaced apart from the floor;
- a pair of side plates to rotatably support the first roller and the second roller;
- a drive shaft extending through the first roller and including an axis of rotation, the drive shaft coupled to the motor to drive the first roller; and
- a lifter to pivot the second roller about the axis of rotation between a first position with at least a portion of the belt contacting the floor and a second position with the belt out of contact with the floor.

2. A patient support comprising:

- a bed frame;
- a plurality of casters to support the bed frame on a floor;
- a power source;
- a motor operably coupled to the power source;
- a drive track operably coupled to the motor to move the bed frame across the floor, the drive track including a first roller driven by the motor about an axis of rotation, a second roller, and a belt supported by the first and second roller, the belt including a plurality of belt teeth, the first roller and second roller each include a plurality of roller teeth located on their outer surface, wherein at least a portion of the plurality of roller teeth are sized to engage at least a portion of the plurality of belt teeth, wherein the rollers are spaced apart from the floor;
- lifter to pivot the second roller about the axis of rotation between a first position with at least a portion of the belt contacting the floor and a second position with the belt out of contact with the floor; and
- a handle configured to receive a user input for controlling movement of the bed frame in at least one of a forward direction and a reverse direction.

\* \* \* \* \*