

US007128720B2

(12) **United States Patent**  
**Podany**

(10) **Patent No.:** **US 7,128,720 B2**  
(45) **Date of Patent:** **Oct. 31, 2006**

(54) **ULTRASONIC FINGER PROBE**  
(75) Inventor: **Vaclav O. Podany**, New Fairfield, CT (US)  
(73) Assignee: **Ethicon, Inc.**, Somerville, NJ (US)  
(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 175 days.

4,744,368 A *	5/1988	Young et al. ....	600/454
5,088,500 A *	2/1992	Wedel et al. ....	600/452
5,242,440 A *	9/1993	Shippert .....	606/30
5,891,026 A *	4/1999	Wang et al. ....	600/344
5,986,446 A *	11/1999	Williamson .....	324/157
6,193,709 B1 *	2/2001	Miyawaki et al. ....	606/1
6,527,767 B1 *	3/2003	Wang et al. ....	606/32
6,849,075 B1 *	2/2005	Bertolero et al. ....	606/41
2003/0120268 A1	6/2003	Bertolero et al.	
2004/0116921 A1	6/2004	Sherman et al.	
2004/0225217 A1 *	11/2004	Voegele et al. ....	600/439

(21) Appl. No.: **10/609,695**

(22) Filed: **Jun. 30, 2003**

(65) **Prior Publication Data**  
US 2004/0267133 A1 Dec. 30, 2004

\* cited by examiner

*Primary Examiner*—Francis J. Jaworski


(51) **Int. Cl.**  
*A61H 1/00* (2006.01)  
(52) **U.S. Cl.** ..... 601/3  
(58) **Field of Classification Search** ..... 601/2-4;  
600/439, 459-471  
See application file for complete search history.


(57) **ABSTRACT**

An ultrasonic finger probe including: a body having an ultrasonic transducer disposed therein, the ultrasonic transducer being operatively connected to an ultrasonic generator; and a securing device for securing the body to one or more fingers of an operator.


(56) **References Cited**  
U.S. PATENT DOCUMENTS  
4,545,386 A \* 10/1985 Hetz et al. .... 600/462

**15 Claims, 3 Drawing Sheets**







**FIG. 2**




**FIG. 3a**




**FIG. 3b**



**FIG. 4a**



**FIG. 4b**



**1****ULTRASONIC FINGER PROBE**

## BACKGROUND OF THE INVENTION

## 1. Field of the Invention

The present invention relates generally to ultrasonic medical instrumentation, and more particularly, to an ultrasonic probe for attachment to one or more fingers of a person.

## 2. Prior Art

Ultrasonic instruments are well known in the medical arts. Such instrumentation may be used to make lesions in tissue, but are also used to cut and coagulate tissue and blood, respectively. Typically, ultrasonic instrumentation have an ultrasonic transducer at a working end of the instrument, which is typically separated from a handle or other manipulation means by an elongated shaft.

In certain medical procedures, such as a MAZE procedure, lesions are made on the heart in a specific pattern. Often, the lesions are to be made on tissue that is hard to reach with conventional instrumentation or where visibility is poor. Thus, there is a need in the medical arts for a device and methods for easily manipulating the ultrasonic transducer, for accessing hard to reach areas, and which increase the visibility of surgical sites.

## SUMMARY OF THE INVENTION

Therefore it is an object of the present invention to provide ultrasonic devices and methods that overcome the disadvantages of conventional ultrasonic instrumentation and methods known in the art.

Accordingly, an ultrasonic finger probe is provided. The ultrasonic finger probe comprises: a body having an ultrasonic transducer disposed therein, the ultrasonic transducer being operatively connected to an ultrasonic generator; and securing means for securing the body to one or more fingers of an operator.

The ultrasonic generator can be remote from the ultrasonic transducer and operatively connected thereto by wiring. The body can have a surface configured for creating lesions in tissue. Furthermore, the body of the ultrasonic transducer can be an elongated bar and can have a length sufficient to span the joints of the one or more fingers to which it is secured.

The securing means can comprise one or more elastic loops fastened to the body and configured for securing one of the one or more fingers to the body, the one or more elastic loops being fabricated from an elastic material. The elastic material can be selected from a group consisting of an elastomer, a fabric, and a composite elastic/fabric. The one or more elastic loops can comprise two elastic loops and the one or more fingers can comprise one finger.

The securing means can also comprise one or more loops, each of the loops having two free ends, one of the free ends having a hook material and the other of the free ends having a loop material, the free ends being wrapped around the one or more fingers and the hook material being secured to the loop material. The one or more loops can comprise two loops and the one or more fingers can comprise one finger.

Also provided is a method for applying ultrasound energy to tissue. The method comprising: providing an ultrasonic finger probe having a body with an ultrasonic transducer disposed therein, the body having a surface for applying ultrasonic energy to tissue; securing the ultrasonic finger probe to one or more fingers of an operator; applying the

**2**

surface of the ultrasonic finger probe to the tissue; and generating ultrasonic energy and supplying the same to the ultrasonic transducer.

The applying can comprise applying the ultrasonic finger probe on a surface of the heart. The generating can comprise generating ultrasonic energy and supplying the same to the ultrasonic transducer in an amount sufficient to create lesions at least on the surface of the heart.

The method can further comprise repeating the applying and generating steps to create a plurality of lesions by manipulating the ultrasonic finger probe with the at least one finger secured thereto. The manipulating can comprise joining the plurality of lesions to form a single long lesion.

The method can further comprise stabilizing the heart with fingers of a same hand other than the one or more fingers secured to the ultrasonic finger probe.

Still yet provided is an ultrasonic finger probe. The ultrasonic finger probe comprising: an ultrasonic transducer operatively connected to an ultrasonic generator; and securing means for securing the ultrasonic transducer to one or more fingers of an operator.

## BRIEF DESCRIPTION OF THE DRAWINGS

These and other features, aspects, and advantages of the apparatus and methods of the present invention will become better understood with regard to the following description, appended claims, and accompanying drawings where:

FIG. 1 illustrates an isometric view of an ultrasonic finger probe according to an embodiment of the present invention.

FIG. 2 illustrates the ultrasonic finger probe of FIG. 1 being applied to a surface of the heart and having fingers other than the one(s) secured to the body of the ultrasonic finger probe used to support the heart.

FIG. 3a illustrates a sectional view of a first variation of a securing means as taken along line 3—3 of FIG. 1.

FIG. 3b illustrates a sectional view of a second variation of a securing means as taken along line 3—3 of FIG. 1.

FIGS. 4a and 4b are schematic diagrams of the atria portion of the heart illustrating a pattern of transmural lesions to create a predetermined conduction path in the atrium formed thereon by the ultrasonic finger probe of the present invention.

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Although this invention is applicable to numerous and various types of ultrasonic transducers and instrumentation, it has been found particularly useful in the environment of creating lesions, particularly for a MAZE procedure. Therefore, without limiting the applicability of the invention to ultrasonic devices configured for making lesions or the use thereof in MAZE procedures, the invention will be described in such environment. Those skilled in the art will appreciate that the ultrasonic devices of the present invention are also useful in other ways known in the art, such as cutting and coagulation of tissue and blood, respectively, and even imaging of tissue and other anatomy.

Referring now to FIGS. 1, 3a, and 3b, an ultrasonic finger probe is provided, the finger probe being referred to generally by reference numeral 100. The ultrasonic finger probe 100 has a body 102 which has an ultrasonic transducer 104 disposed therein or thereon (collectively referred to as disposed therein). The ultrasonic transducer 104 is operatively connected to an ultrasonic generator 106. The ultrasonic generator 106 can be integral with the finger probe 100

such as being housed in the body **102** or remotely connected to the ultrasonic transducer **104** by means of wiring **106a** or the like. Where the finger probe **100** is used for imaging, the wiring **106a** may also return signals to a processor and/or display for display or processing of the ultrasonic imaging corresponding to the signal. The finger probe **100** further has securing means for securing the body **102** to one or more fingers **108** of an operator. Although the finger probe **100** is preferably secured to a single finger **108**, those skilled in the art will appreciate that the finger probe **100** can be secured to more than one finger.

The body **102** can have a surface **102a** particularly configured for the intended purpose of the finger probe **100**, such as for creating lesions in tissue. Thus, the body **102** can be an elongated bar as shown in FIG. 1 with a length sufficient to span the joints **110** of the one or more fingers **108** to which it is secured. The elongated bar **102** and/or the surface **102a** can be linear, curved or have linear and curved portions along the length of the body **102**. Those skilled in the art will appreciate that different procedures will call for different shaped surfaces **102a** to improve the efficacy of the procedure. The body **102** can be fabricated from any materials known in the art for use with ultrasonic transducers, such as thermoplastics or metals.

The securing means can comprise one or more elastic loops **112** as shown in FIG. 3a. Preferably, two such loops **112** are utilized. Each of the elastic loops **112** are fastened to the body **102** and configured for securing the one or more fingers **108** to the body **102**. However, the one or more elastic loops **112** do not have to be fastened to the body **102** and could merely be disposed around both the one or more fingers **108** and the body **102**. If the finger probe **100** is secured to more than one finger **108**, one or more elastic loops **112** can secure each finger **108** to the body **102** or all of the fingers **108** that are secured to the body **102** can share common elastic loops **112**. The elastic loops **112** can be fabricated from any resilient material, such as an elastic material. The elastic material can be an elastomer, a fabric, or a composite elastic/fabric. The elastic loops **112** are preferably sized smaller than a typically sized finger and stretch to accommodate the one or more fingers **108** therein. The finger probe **100** can be alternatively connected to one or more fingers of a surgical glove. In yet another alternative, the finger probe **100** can be secured to the one or more fingers **108** by attachment to a glove which itself is secured around the wrist, arm, or hand.

The securing means can alternatively comprise one or more loops **114**, as shown in FIG. 3b. Each of the loops **114** has two free ends **116**, **118**. One of the free ends (**118** in FIG. 3b) has a hook material **120** and the other of the free ends (**116** in FIG. 3b) has a loop material **122**. The hook and loop materials **120**, **122** are typically referred to by the trade name Velcro®. At least one of the free ends **116**, **118** are wrapped around the one or more fingers **108** and the hook material **120** is secured to the loop material **122**.

The body **102** and/or ultrasonic transducer **104** can be configured in any way known in the art for creating lesions, cutting tissue, and/or imaging of tissue, such as that disclosed in co-pending U.S. application Ser. No. 10/609,692, entitled System For Creating Linear Lesions for the Treatment of Atrial Fibrillation, the entire contents of which is incorporated herein by its reference. For example, the ultrasonic transducer can have an ultrasonic crystal **123** housed in a cavity **124** in the body **102** and convexly curved as shown in FIGS. 3a and 3b such that the resulting ultrasonic energy is focused along a straight or curved line along the length of the ultrasonic crystal **123** to create a lesion. The

cavity **124** can be covered with an acoustic window **126** fabricated from a suitable material. The ultrasonic crystal **123** may also have an impedance matching coating (not shown) on the side of the ultrasonic crystal **123** that faces the acoustic window **126**. The ultrasonic transducer **104** can further provide for circulation of a cooling medium, such as a fluid, through the cavity **124** and/or through one or more conduits **128** provided in the body **102**. A cooling medium, for example, water or saline, may be re-circulated through the conduits **128** or through other openings (not shown) in the body **102**. The ultrasonic crystal **123** can also be positioned in the cavity **124** such that an air gap exists between a back surface **123a** of the ultrasonic crystal and a front surface **124a** of the cavity **124**. The configuration of the ultrasonic transducer **104** is given by way of example only and not to limit the spirit or scope of the present invention. Those skilled in the art will appreciate that the ultrasonic transducer **104** can be configured in any manner known in the art for producing ultrasonic energy for its intended purpose, whether it be creating lesions in tissue, cutting tissue, or imaging of anatomy proximate the finger probe **100**.

A method for applying ultrasound energy to tissue using the finger probe **100** will now be described with reference to FIGS. 2, 4a and 4b. The method is particularly useful for applying ultrasonic energy to tissue, and more particularly in creating lesions on a surface of the tissue, such as on a surface of the heart. Ideally, the lesions are transmural and created in the heart wall. Firstly, the ultrasonic finger probe **100** is secured to one or more fingers **108** of an operator. As discussed above, the finger probe **100** is preferably secured to a single finger **108**, such as the index (pointer) finger **108** and has a length sufficient to span the joints **110** of the finger(s) to which it is secured. Those skilled in the art will appreciate that the finger probe can also be shorter than a length sufficient to span the joints **110** of the finger(s) to which it is attached. In fact, the finger probe can be very small and attached only to a tip of one or more fingers and used to “write” lesions on the heart (i.e., create a continuous lesion line) instead of making linear lesion segments.

The surface **102a** of the ultrasonic finger probe **100** is then applied to the tissue and while applied, ultrasonic energy is generated and supplied to the ultrasonic transducer to create lesions. The application of the surface **102a** on the tissue can comprise applying the ultrasonic finger probe **100** on a surface of the heart **130**. The generation of ultrasonic energy can comprise generating ultrasonic energy and supplying the same to the ultrasonic transducer **104** in an amount sufficient to create lesions at least on the surface of the heart **130** and ideally transmurally in the heart wall. As will be discussed below in an Example, the method can further comprise repeating the applying and generating steps to create a plurality of lesions by manipulating the ultrasonic finger probe **100** with the at least one finger **108** secured thereto. The manipulating can also comprise joining the plurality of lesions to form a single long lesion. As shown in FIG. 2, the heart, or other tissue structure being worked on can be stabilized with fingers **109** of a same hand other than the one or more fingers **108** secured to the ultrasonic finger probe **100**. For example, where the finger probe **100** is secured to only the index (pointer) finger **108**, the thumb, pinky, ring, and middle fingers **109** can be used to stabilize, hold, and otherwise manipulate the heart **130** (collectively referred to herein as stabilizing).

## 5

## EXAMPLE

Cardiac arrhythmias, particularly atrial fibrillation, are a pervasive problem in modern society. Although many individuals lead relatively normal lives despite persistent atrial fibrillation, the condition is associated with an increased risk of myocardial ischemia, especially during strenuous activity. Furthermore, persistent atrial fibrillation has been linked to congestive heart failure, stroke, and other thromboembolic events. Thus, atrial fibrillation is a major public health problem.

Normal cardiac rhythm is maintained by a cluster of pacemaker cells, known as the sinoatrial (“SA”) node, located within the wall of the right atrium. The SA node undergoes repetitive cycles of membrane depolarization and repolarization, thereby generating a continuous stream of electrical impulses, called “action potentials.” These action potentials orchestrate the regular contraction and relaxation of the cardiac muscle cells throughout the heart. Action potentials spread rapidly from cell to cell through both the right and left atria via gap junctions between the cardiac muscle cells. Atrial arrhythmias result when electrical impulses originating from sites other than the SA node are conducted through the atrial cardiac tissue.

In most cases, atrial fibrillation results from perpetually wandering reentrant wavelets, which exhibit no consistent localized region(s) of aberrant conduction. Alternatively, atrial fibrillation may be focal in nature, resulting from rapid and repetitive changes in membrane potential originating from isolated centers, or foci, within the atrial cardiac muscle tissue. These foci exhibit centrifugal patterns of electrical activation, and may act as either a trigger of paroxysmal atrial fibrillation or may even sustain the fibrillation. Recent studies have suggested that focal arrhythmias often originate from a tissue region along the pulmonary veins of the left atrium, and even more particularly in the superior pulmonary veins.

Several surgical approaches have been developed for the treatment of atrial fibrillation. One particular example, known as the “MAZE” procedure, is disclosed by Cox, J. L. et al., *The surgical treatment of atrial fibrillation. I. Summary*, Thoracic and Cardiovascular Surgery 101(3): 402–405(1991) and also by Cox, J. L., *The surgical treatment of atrial fibrillation. IV. Surgical Technique*, Thoracic and Cardiovascular Surgery 101(4): 584–592 (1991). In general, the MAZE procedure is designed to relieve atrial arrhythmia by restoring effective SA node control through a prescribed pattern of lesions about the cardiac tissue wall. Although early clinical studies on the MAZE procedure included surgical incisions in both the right and left atrial chambers, more recent reports suggest that the MAZE procedure may be effective when lesions are created and performed only in the left atrium (see for example Sueda et al., “Simple Left Atrial Procedure for Chronic Atrial Fibrillation Associated With Mitral Valve Disease” (1996)).

The MAZE procedure involves forming lesions in the atrial tissue of the heart **108**. In this process, the lesions on the atrial tissue eliminates the atrial arrhythmia by blocking conduction of the aberrant action potentials. FIGS. **4a** and **4b** show a human heart **108** incorporating a series of strategically positioned transmural lesions **202** throughout the right atrium RA and the left atrium LA formed with the finger probe of the present invention. As shown in FIGS. **4a** and **4b**, these individual lesions **202** collectively form a pattern of transmurally ablated heart tissue to surgically treat medically refractory atrial fibrillation. The finger probe enables the surgical formation of the series of lesions

## 6

illustrated in FIGS. **4a** and **4b**. The process for forming the lesions is more fully described in U.S. Pat. No. 6,161,543, the entire contents of which is incorporated herein by its reference. The lesion shape and pattern is shown by way of example only and not to limit the scope or spirit of the present invention.

While there has been shown and described what is considered to be preferred embodiments of the invention, it will, of course, be understood that various modifications and changes in form or detail could readily be made without departing from the spirit of the invention. It is therefore intended that the invention be not limited to the exact forms described and illustrated, but should be constructed to cover all modifications that may fall within the scope of the appended claims.

What is claimed is:

1. An ultrasonic finger probe comprising:

an elongated body having an ultrasonic transducer disposed therein, the ultrasonic transducer being a crystal operatively connected directly to an ultrasonic generator and having a lesion creating surface, the elongated body having an acoustic window spaced from the crystal and spanning joints of one or more fingers of an operator to which the body is secured; and securing means for securing the body directly to the one or more fingers of the operator.

2. The ultrasonic finger probe of claim 1, wherein the ultrasonic generator is remote from the ultrasonic transducer and operatively connected thereto by wiring.

3. The ultrasonic finger probe of claim 1, wherein the body has a surface configured for creating lesions in tissue.

4. The ultrasonic finger probe of claim 1, wherein the securing means comprises one or more elastic loops fastened to the body and configured for securing the one or more fingers to the body, the one or more elastic loops being fabricated from an elastic material.

5. The ultrasonic finger probe of claim 4, wherein the elastic material is selected from a group consisting of an elastomer, a fabric, and a composite elastic/fabric.

6. The ultrasonic finger probe of claim 4, wherein the one or more elastic loops comprises two elastic loops and the one or more fingers comprises one finger.

7. The ultrasonic finger probe of claim 1, wherein the securing means comprises one or more loops, each of the loops having two free ends, one of the free ends having a hook material and the other of the free ends having a loop material, the free ends being wrapped around the one or more fingers and the hook material being secured to the loop material.

8. The ultrasonic finger probe of claim 7, wherein the one or more loops comprises two loops and the one or more fingers comprises one finger.

9. A method for applying ultrasound energy to tissue, the method comprising:

providing an ultrasonic finger probe having an elongated body with an ultrasonic transducer disposed therein, the ultrasonic transducer being a crystal operatively connected to an ultrasonic generator and the body having a surface for applying ultrasonic energy to tissue including an acoustic window spaced from the crystal and having a length that spans joints of one or more fingers of an operator to which the body is secured; securing the ultrasonic finger probe directly to the one or more fingers of the operator; applying the surface of the ultrasonic finger probe to the tissue; and

7

generating ultrasonic energy and supplying the same to  
diagnose and treat the tissue through the ultrasonic  
transducer.

**10.** The method of claim **9**, wherein the applying com-  
prises applying the ultrasonic finger probe on a surface of the 5  
heart.

**11.** The method of claim **10**, wherein the generating  
comprises generating ultrasonic energy and supplying the  
same to the ultrasonic transducer in an amount sufficient to  
create lesions on at least the surface of the heart. 10

**12.** The method of claim **11**, further comprising repeating  
the applying and generating steps to create a plurality of  
lesions by manipulating the ultrasonic finger probe with the  
at least one finger secured thereto.

**13.** The method of claim **12**, wherein the manipulating 15  
comprises joining the plurality of lesions to form a single  
long lesion.

8

**14.** The method of claim **10**, further comprising stabiliz-  
ing the heart with fingers of a same hand other than the one  
or more fingers secured to the ultrasonic finger probe.

**15.** An ultrasonic finger probe comprising:

an ultrasonic transducer housed in an elongated body  
spanning joints of one or more fingers of an operator to  
which the finger probed is secured, the transducer being  
a crystal operatively connected to an ultrasonic gen-  
erator and having a lesion creating surface, and the  
elongated body having an acoustic window spaced  
from the crystal; and

securing means for securing the ultrasonic transducer  
directly to the one or more fingers of the operator.

\* \* \* \* \*