



US007134773B2

(12) **United States Patent**  
**Tufte**

(10) **Patent No.:** **US 7,134,773 B2**  
(45) **Date of Patent:** **Nov. 14, 2006**

- (54) **LIGHTING APPARATUS**
- (75) Inventor: **Brian N. Tufte**, Eden Prairie, MN (US)
- (73) Assignee: **I3 Ventures, LLC**, Eden Prairie, MN (US)

- 3,359,030 A 12/1967 Newman
- 3,473,836 A 10/1969 Halter
- 3,551,723 A 12/1970 Van Groningen
- 3,612,848 A 10/1971 Koch et al.
- 3,639,748 A 2/1972 Pearson et al.

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 242 days.

(Continued)

**FOREIGN PATENT DOCUMENTS**

(21) Appl. No.: **10/811,602**

FR 2727498 11/1994

(22) Filed: **Mar. 29, 2004**

(Continued)

(65) **Prior Publication Data**

US 2005/0213342 A1 Sep. 29, 2005

**OTHER PUBLICATIONS**

“2004 Marine Product Catalog,” Taco Metals, 128 pages, 2004.

(51) **Int. Cl.**  
**B60Q 1/00** (2006.01)

(Continued)

(52) **U.S. Cl.** ..... **362/505; 362/551**

(58) **Field of Classification Search** ..... **362/505, 362/509, 511, 555, 540, 190–191**

*Primary Examiner*—Ali Alavi  
(74) *Attorney, Agent, or Firm*—Brian N. Tufte

See application file for complete search history.

(57) **ABSTRACT**


(56) **References Cited**

**U.S. PATENT DOCUMENTS**

- 1,647,014 A 10/1927 Pattison
- 1,729,274 A 9/1929 Miller
- 1,729,284 A 9/1929 Millar
- 1,779,180 A 10/1930 Macrae et al.
- 1,972,283 A 9/1934 Zimmers
- 2,277,433 A 3/1942 Guth
- 2,300,067 A 10/1942 Schwab
- 2,339,085 A 1/1944 Luckiesh
- 2,525,001 A 10/1950 Sherwood
- 2,561,756 A 7/1951 Shock
- 2,587,807 A 3/1952 Arenberg et al.
- 2,930,885 A 3/1960 Ehrenfreund
- 2,959,146 A 11/1960 Erkert
- 3,028,208 A 4/1962 Sharpe
- 3,140,111 A 7/1964 Dabroski
- 3,196,265 A 7/1965 Schneider
- 3,197,189 A 7/1965 Pemper et al.
- 3,317,722 A 5/1967 Whitney

A lighting apparatus is disclosed for providing illumination to an object or surface. In one illustrative embodiment, the light apparatus is used to help improve the visibility of a vehicle by providing illumination to at least part of the vehicle. In other illustrative embodiments, the light apparatus may be used to provide illumination for other objects or equipment including, for example, docks, retail and/or store shelving and/or equipment, bars, desks, counters, walls, railings, steps, and/or any other object or surface, as desired. In some embodiments, the lighting apparatus includes a bumper. When so provided, the lighting apparatus may help provide a level of protection to objects and/or surfaces that are subject to bumping, sliding or other abuse. In other illustrative embodiments, the lighting apparatus may be used to increase the visual appeal of an object or surface, such as a wall, a toy, an appliance or any other object, as desired.

**51 Claims, 51 Drawing Sheets**



## U.S. PATENT DOCUMENTS

3,675,527 A	7/1972	Reeder, Jr.	6,129,442 A	10/2000	Hoefling et al.
3,722,876 A	3/1973	Schwenk	6,152,586 A	11/2000	Dealey et al.
3,865,358 A	2/1975	Butters	6,179,431 B1	1/2001	Chien
3,885,144 A	5/1975	Lewis et al.	6,186,649 B1	2/2001	Zou et al.
4,107,767 A	8/1978	Anquetin	RE37,113 E	3/2001	Shimada
4,213,644 A	7/1980	Scrivo et al.	6,231,217 B1	5/2001	Krippelz, Sr.
4,245,281 A	1/1981	Ziaylek, Jr.	6,270,229 B1	8/2001	Chien
4,270,787 A	6/1981	Savell	6,278,827 B1	8/2001	Sugiyama et al.
4,360,859 A	11/1982	Ziaylek, Jr.	6,364,293 B1	4/2002	Beckett
4,376,966 A	3/1983	Tieszen	6,371,634 B1	4/2002	Tufte
4,418,378 A	11/1983	Johnson	6,450,678 B1	9/2002	Bayersdorfer
4,445,163 A	4/1984	Ziaylek, Jr.	6,461,028 B1	10/2002	Huang
4,625,266 A	11/1986	Winter	6,474,851 B1	11/2002	Baley
4,740,870 A	4/1988	Moore et al.	6,511,204 B1	1/2003	Emmel et al.
4,947,293 A	8/1990	Johnson et al.	6,523,986 B1	2/2003	Hoffmann
4,954,932 A	9/1990	Isenga	6,526,200 B1	2/2003	Davie
4,955,044 A	9/1990	Amstutz et al.	6,592,245 B1	7/2003	Tribelsky et al.
4,964,760 A	10/1990	Hartman	6,655,824 B1	12/2003	Tufte
4,979,081 A	12/1990	Leach et al.	6,733,161 B1	5/2004	Tufte
4,996,634 A	2/1991	Haneda et al.	6,742,916 B1	6/2004	Dunn
5,021,931 A	6/1991	Matsui et al.	2003/0209183 A1	11/2003	Tufte
5,023,762 A	6/1991	Tieszen	2004/0179358 A1	9/2004	Tufte
5,096,753 A	3/1992	McCue et al.	2005/0213342 A1	9/2005	Tufte
5,122,933 A	6/1992	Johnson			
5,180,223 A	1/1993	McNamee			
5,268,824 A	12/1993	Czipri			
5,304,993 A	4/1994	Handsaker			
5,337,225 A	8/1994	Brookman			
5,383,100 A	1/1995	Kikos			
5,410,458 A	4/1995	Bell			
5,430,627 A	7/1995	Nagano			
5,434,013 A	7/1995	Fernandez			
5,469,342 A	11/1995	Chien			
5,475,574 A	12/1995	Chien			
5,485,355 A	1/1996	Voskoboinik et al.			
5,495,401 A	2/1996	Evans			
5,499,170 A	3/1996	Gagne			
5,523,923 A	6/1996	Stowe, Jr.			
5,566,384 A	10/1996	Chien			
5,570,945 A	11/1996	Chien et al.			
5,579,429 A	11/1996	Naum			
5,611,621 A	3/1997	Chien			
5,613,750 A	3/1997	Roe			
5,636,916 A	6/1997	Sokolowski			
5,678,914 A	10/1997	Dealey et al.			
5,680,496 A	10/1997	Burkitt et al.			
5,711,592 A	1/1998	Hotta			
5,730,079 A	3/1998	Totty et al.			
5,737,472 A	4/1998	Bernasson et al.			
5,746,501 A	5/1998	Chien			
5,753,381 A	5/1998	Feldman et al.			
5,775,016 A	7/1998	Chien			
5,869,930 A	2/1999	Baumberg et al.			
5,871,269 A	2/1999	Chien			
5,873,646 A	2/1999	Fjaestad et al.			
5,902,034 A	5/1999	Santosuosso et al.			
5,903,695 A	5/1999	Zarian et al.			
5,915,830 A	6/1999	Dickson et al.			
5,917,288 A	6/1999	Feldman et al.			
6,019,476 A	2/2000	Kirschner			
6,033,085 A	3/2000	Bowker			
6,050,211 A	4/2000	Yamaguchi			
6,065,852 A	5/2000	Crumley			
6,074,071 A	6/2000	Baumberg et al.			
6,082,867 A	7/2000	Chien			
6,113,246 A	9/2000	Rub			
6,120,160 A	9/2000	Nakagawa			

## FOREIGN PATENT DOCUMENTS

WO	WO 96/13687	5/1996
WO	WO 00/42456	7/2000

## OTHER PUBLICATIONS

“2006 Marine Products Catalog,” Taco Metals, 122 pages, 2006.

Light Tech LLC., “Decorative Cable Lights,” brochure, copyright 1998.

Flex Glo Wire, Inc., “Flex Glo Wire Specifications,” Oct. 15, 1998.

*Selected pages from* <http://www.aqualuce.com/montkaj.html>, 2 pages, downloaded Jun. 3, 2000.

“Eagle Mouldings Specialty Trim & Extrusions,” brochure, 6 pages, prior to Aug. 11, 1999.

Lumenyte International Corporation, “Cove Lighting Applications,” 1 page, copyright, Mar. 19, 1998.

Lumenyte International Corporation, “Sta-Flex LEF™ 510M Linear Emitting Fiber,” 2 pages, copyright Mar. 6, 2001.

Lumenyte International Corporation, “Sta-Flex LEF™ 310 Linear Emitting Fiber,” 2 pages, copyright Mar. 19, 1998.

Lumenyte International Corporation, “Sta-Flex LEF™ 510 Linear Fiber,” 2 pages, copyright Mar. 19, 1998.

Lumenyte International Corporation, “Sta-Flex LEF™ 410M Linear Emitting Fiber,” 2 pages, copyright Mar. 6, 2001.

3M Marine Products, [http://www.3m.com/US/auto\\_marine\\_aero/marine/catalog/index.jhtml](http://www.3m.com/US/auto_marine_aero/marine/catalog/index.jhtml), 1 page, downloaded Feb. 11, 2002.

3M Automotive, Marine and Aerospace, [http://products.3m.com/usenglish/auto\\_marine\\_aero/marine.jhtml](http://products.3m.com/usenglish/auto_marine_aero/marine.jhtml), 1 page, downloaded Feb. 11, 2002.

3M United States, <http://www.3m.com/about3M/technologies/lightfiber>, 30 pages, downloaded Feb. 11, 2002.

<http://www.elam.co.il>, 24 pages, downloaded Feb. 11, 2002.

U.S. Appl. No. 10/074,162, filed Feb. 12, 2002, entitled, “Lighting Apparatus.”

U.S. Appl. No. 10/074,364, filed Feb. 12, 2002, entitled, “Lighting Apparatus.”

U.S. Appl. No. 10/074,356, filed Feb. 12, 2002, entitled, “Lighting Apparatus.”

U.S. Appl. No. 10/075,488, filed Feb. 12, 2002, entitled, “Lighting Apparatus.”

U.S. Appl. No. 10/075,489, filed Feb. 12, 2002, entitled, “Lighting Apparatus.”

U.S. Appl. No. 10/147,097, filed May 13, 2002, entitled, “Lighting Apparatus.”




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6






FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11





FIG. 12



**FIG. 13**




FIG. 14




FIG. 15






FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20







FIG. 21



**FIG. 22**



**FIG. 23**



**FIG. 24**




FIG. 25




FIG. 26




FIG. 27







FIG. 28




**FIG. 29**




**FIG. 30**



**FIG. 31**



**FIG. 32**



**FIG. 33**






FIG. 34







**FIG. 35**




**FIG. 36A**




**FIG. 36B**




**FIG. 36C**



**FIG. 37**



**FIG. 38**



**FIG. 39**




FIG. 40




FIG. 41




FIG. 42







FIG. 43




**FIG. 44**



**FIG. 45**



**FIG. 46**



**FIG. 47**




FIG. 48









FIG. 49




**FIG. 50**




**FIG. 51**




**FIG. 52**




**FIG. 53**




**FIG. 54**




**FIG. 55**




**FIG. 56**



**FIG. 57**




**FIG. 58**




**FIG. 59**







**FIG. 60**




**FIG. 61**




**FIG. 62**




**FIG. 63**




**FIG. 64**




**FIG. 65**




**FIG. 66**




**FIG. 67**




**FIG. 68**




**FIG. 69**




**FIG. 70**




**FIG. 71**




**FIG. 72**




**FIG. 73**




**FIG. 74**




**FIG. 75**




**FIG. 76**




**FIG. 77**




**FIG. 78**




**FIG. 79**




**FIG. 80**




**FIG. 81**



**FIG. 82**




**FIG. 83**




**FIG. 84**







**FIG. 85**




**FIG. 86**




**FIG. 87**




**FIG. 88**




**FIG. 89**



**FIG. 90**



**FIG. 91**



**FIG. 92**

## 1

## LIGHTING APPARATUS

## BACKGROUND OF THE INVENTION

This invention relates to lights, and more particularly, to lights for illuminating, protecting and/or increasing the visual appeal of an object or surface.

## SUMMARY OF THE INVENTION

The present invention provides a lighting apparatus that may be used to provide illumination for an object or surface. In one illustrative embodiment, the light apparatus is used to help improve the visibility of a vehicle by providing illumination to at least part of the vehicle. In other illustrative embodiments, the light apparatus may be used to provide illumination for other objects or equipment including, for example, docks, retail and/or store shelving and/or equipment, bars, desks, counters, walls, railings, steps, and/or any other object or surface, as desired. In some embodiments, the lighting apparatus includes a bumper. When so provided, the lighting apparatus may help provide a level of protection to objects and/or surfaces that are subject to bumping, sliding or other abuse. In other illustrative embodiments, the lighting apparatus may be used to increase the visual appeal of an object or surface, such as a wall, a toy, an appliance or any other object, as desired.

## BRIEF DESCRIPTION OF THE DRAWINGS

Other objects of the present invention and many of the attendant advantages of the present invention will be readily appreciated as the same becomes better understood by reference to the following detailed description when considered in connection with the accompanying drawings, in which like reference numerals designate like parts throughout the figures thereof and wherein:

FIG. 1 is a perspective view of a boat having a first illustrative boat lighting apparatus;

FIG. 2 is a perspective view of a boat having another illustrative boat lighting apparatus;

FIG. 3 is a schematic view of a boat hull having a number of boat lights, each directing light rays in a downward direction;

FIG. 4 is a schematic view of a boat hull having a number of boat lights, each directing light rays in an upward direction;

FIG. 5 is a schematic view of a boat hull having a number of boat lights, each directing light rays in forward and backward direction;

FIG. 6 is a partial cross-sectional perspective view of a boat hull having an illustrative elongated light apparatus;

FIG. 7 is a partial cross-sectional side view of a boat hull having another illustrative boat lighting apparatus;

FIG. 8 is a perspective view of another illustrative boat lighting apparatus in accordance with the present invention;

FIG. 9 is a partial cross-sectional side view of a boat hull having a boat lighting apparatus incorporated into a side bumper assembly;

FIG. 10 is a partial cross-sectional side view of a boat hull having a boat lighting apparatus incorporated into an outward extending hull portion;

FIG. 11 is a partial cross-sectional side view of a boat hull having a telescoping boat lighting apparatus;

FIG. 12 is a partial cross-sectional side view of a boat hull having a threaded boat lighting apparatus;

## 2

FIG. 13 is a schematic view of an illustrative circuit for powering the one or more light sources of the present invention;

FIG. 14 is a schematic view of another illustrative circuit for powering the one or more light sources of the present invention;

FIG. 15 is a timing diagram showing one illustrative energizing scheme provided by the control block of FIG. 14;

FIG. 16 is a timing diagram showing another illustrative energizing scheme provided by the control block of FIG. 14;

FIG. 17 is a perspective view of a personal watercraft having a boat lighting apparatus mounted thereto;

FIG. 18 is a cross-sectional side view of an illustrative lighting apparatus that includes a bumper member;

FIG. 19 is a cross-sectional side view of an illustrative lighting apparatus that includes a bumper member, wherein at least a portion of the bumper member is adapted to transmit light;

FIG. 20 is a cross-sectional side view of another illustrative lighting apparatus that includes a bumper member, wherein the bumper member is adapted to receive a light source and transmit light;

FIG. 21 is a cross-sectional side view of an illustrative lighting apparatus that includes a carrier and a bumper member, wherein the carrier is adapted to receive a light source;

FIG. 22 is a cross-sectional side view of another illustrative lighting apparatus that includes a carrier that is adapted to receive a light source;

FIG. 23 is a cross-sectional side view of yet another illustrative lighting apparatus that includes a carrier that is adapted to receive a light source;

FIG. 24 is a cross-sectional side view of an illustrative Fresnel lens that may be used in accordance various embodiments of the present invention;

FIG. 25 is a cross-sectional side view of another illustrative lighting apparatus that includes a carrier that is adapted to receive a light source;

FIG. 26 is a cross-sectional side view of another illustrative lighting apparatus that includes a carrier that is adapted to receive a light source;

FIG. 27 is a cross-sectional side view of another illustrative lighting apparatus that includes a carrier, wherein the carrier includes a parabolic shaped recess for receiving a light source;

FIG. 28 is a cross-sectional side view of another illustrative lighting apparatus that includes a carrier and a bumper member, wherein the carrier includes a recess for receiving a light source;

FIG. 29 is a cross-sectional side view of another illustrative lighting apparatus that includes a two piece carrier, wherein the first piece includes a recess for receiving a light source and the second piece provides a cover for the recess;

FIG. 30 is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention;

FIG. 31 is a cross-sectional side view of yet another illustrative lighting apparatus in accordance with the present invention;

FIG. 32 is a schematic view of a truck with an illustrative lighting apparatus mounted to the side thereof;

FIG. 33 is a schematic view of an object that has an illustrative lighting apparatus mounted to the side thereof;

FIG. 34 is a schematic view of a tow line that includes an illustrative lighting apparatus in accordance with the present invention;

FIG. 35 is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention;

FIG. 36A is a cross-sectional side view of the elongated bumper member (or insert) 700 of FIG. 35, with the slit 706 in the closed position;

FIG. 36B is a cross-sectional side view of the elongated bumper member (or insert) of FIG. 35, with the slit in an open position;

FIG. 36C is a cross-sectional side view of the insert of FIG. 35, with the slit in an open position and with a slit latching mechanism;

FIG. 37 is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention;

FIG. 38 is a cross-sectional side view of an illustrative rub-rail with nubs in accordance with the present invention;

FIG. 39 is a cross-sectional side view of an illustrative lighting apparatus with nubs in accordance the present invention;

FIG. 40 is a cross-sectional side view of an illustrative lighting apparatus for receiving an elongated light source;

FIG. 41 is a cross-sectional side view of another illustrative lighting apparatus for receiving an elongated light source;

FIG. 42 is a cross-sectional side view of yet another illustrative lighting apparatus for receiving an elongated light source;

FIG. 43 is a cross-sectional side view of another illustrative lighting apparatus for receiving an elongated light source;

FIG. 44 is a cross-sectional side view of an illustrative lighting apparatus with one or more legs for securing the lighting apparatus to a substrate;

FIG. 45 is a cross-sectional side view of another illustrative lighting apparatus with one or more legs for securing the lighting apparatus to a substrate;

FIG. 46 is a cross-sectional side view of the illustrative lighting apparatus of FIG. 45 with the one or more legs inserted through a substrate;

FIG. 47 is a cross-sectional side view of yet another illustrative lighting apparatus attached to a substrate;

FIG. 48 is a cross-sectional side view of an illustrative lighting apparatus for securing an elongated light source to a substrate;

FIG. 49 is a cross-sectional side view of an illustrative lighting apparatus for use with a stair or other ledge;

FIG. 50 is a schematic diagram of an illustrative appliance having an elongated light source positioned along the body of the appliance;

FIG. 51 is a schematic diagram of an illustrative toy having an elongated light source positioned along the body of the toy;

FIG. 52 is a schematic diagram of a solar powered lighting apparatus;

FIG. 53 is a schematic diagram of an illustrative toaster having an elongated light source positioned along the body of the toaster;

FIG. 54 is an overlapping cross-sectional side view of a carrier and in insert of another illustrative lighting apparatus;

FIG. 55 is a cross-sectional side view of the illustrative lighting apparatus of FIG. 54 with the insert installed within the carrier;

FIG. 56 is a front view of the illustrative lighting apparatus of FIG. 55, with the insert shorter than the carrier for illustrative purposes;

FIG. 57 is a perspective view of the illustrative lighting apparatus of FIG. 56, again the insert shorter than the carrier for illustrative purposes;

FIG. 58 is an overlapping cross-sectional side view of another illustrative lighting apparatus that includes a carrier and in insert, wherein the insert is adapted to receive a light source;

FIG. 59 is a cross-sectional side view of the illustrative lighting apparatus of FIG. 58 with the insert installed within the carrier;

FIG. 60 is a front view of the illustrative lighting apparatus of FIG. 59, with the insert shorter than the carrier for illustrative purposes;

FIG. 61 is a perspective view of the illustrative lighting apparatus of FIG. 60, again the insert shorter than the carrier for illustrative purposes;

FIG. 62 is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention;

FIG. 63 is a perspective side view of an illustrative insert that may be used in conjunction with the illustrative light apparatus of FIG. 62;

FIG. 64 is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention, wherein the carrier includes an opening for receiving a light source;

FIG. 65 is a cross-sectional side view of the illustrative lighting apparatus of FIG. 64 with a plug inserted into the opening of the carrier;

FIG. 66 is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention;

FIG. 67 is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention;

FIG. 68 is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention;

FIG. 69 is a cross-sectional side view of yet another illustrative lighting apparatus in accordance with the present invention, with an opening for receiving a light source;

FIG. 70 is a cross-sectional side view of the illustrative lighting apparatus of FIG. 69 with a plug inserted into the opening;

FIG. 71 is a cross-sectional side view of yet another illustrative lighting apparatus in accordance with the present invention, with an opening for receiving a light source;

FIG. 72 is a cross-sectional side view of the illustrative lighting apparatus of FIG. 71 with a plug inserted into the opening;

FIG. 73 is a cross-sectional side view of yet another illustrative lighting apparatus in accordance with the present invention;

FIG. 74 is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention;

FIG. 75 is a cross-sectional side view of yet another illustrative lighting apparatus in accordance with the present invention;

FIG. 76 is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention;

FIG. 77 is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention;

5

FIG. 78 is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention;

FIG. 79 is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention, including a carrier and an insert;

FIG. 80 is a cross-sectional side view of another illustrative insert for use with the carrier of FIG. 79;

FIG. 81 is a cross-sectional side view of yet another illustrative insert for use with the carrier of FIG. 79;

FIG. 82 is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention;

FIG. 83 is a partial perspective view of another illustrative lighting apparatus in accordance with the present invention, with a lumen for receiving a light source, and a plug for plugging the lumen;

FIG. 84 is a partial perspective view of a tube and cap for use in joining two of the illustrative lighting apparatuses of FIG. 83;

FIG. 85 is a partial perspective view of a tube and cap for use in joining two of the illustrative lighting apparatuses of FIG. 83 at a corner;

FIG. 86 is a partial perspective view of another illustrative lighting apparatus in accordance with the present invention, with an lumen for receiving a light source, and a plug for plugging the lumen;

FIG. 87 is a partial perspective view of a tube and cap for use in joining two of the illustrative lighting apparatuses of FIG. 86;

FIG. 88 is a partial perspective view of a tube and cap for use in joining two of the illustrative lighting apparatuses of FIG. 86 at a corner;

FIG. 89 is a cross-sectional side view of another illustrative lighting apparatus the present invention;

FIG. 90 is a cross-sectional side view of another illustrative lighting apparatus the present invention;

FIG. 91 is a cross-sectional side view of yet another illustrative lighting apparatus the present invention; and

FIG. 92 is a cross-sectional side view of another illustrative lighting apparatus the present invention.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIG. 1 is a perspective view of a boat 10 having a first illustrative boat lighting apparatus in accordance with the present invention. The boat is generally shown at 10, and includes an upper deck 11 extending over a hull 16. The hull 16 extends generally down from the upper deck 11 toward an expected water line 13. The hull 16 may also extend generally inward, as shown.

Prior art navigation lights typically include forward running lights 12 and a rear masthead light 14. The forward running lights 12 typically include a red port light and a green starboard light. In many cases, the forward running lights 12 are provided in a relatively small housing mounted to the front of the boat. The rear masthead light 14 is shown mounted higher than the forward running lights 12, and is visible from the front of the boat.

This lighting configuration may be adequate for experienced boaters traveling in relatively low traffic waterways under good weather conditions. However, under other conditions, they are less desirable. Many of today's waterways are extremely crowded, often occupied with high powered boats driven by inexperienced and inattentive boaters. Safely operating a boat at night under these conditions can

6

be a challenge. Depth perception is limited, and lights along the shoreline can cast misleading reflections on the water. In many instances, simply identifying boats via the forward running lights 12 and the masthead light 14 can be difficult, let alone determining the size, direction, speed, and other factors needed to safely travel the waterways.

To augment the basic running lights 12 and 14 shown in FIG. 1, the present invention contemplates providing a boat lighting apparatus that improves the visibility of a boat by illuminating one or more side surfaces of the hull 16 of the boat 10. The hull 16 of the boat provides a relatively large area that, when illuminated, can significantly increase the visibility of a boat 10. In addition, the size, direction, and speed of a boat 10 can more readily be determined, even by novice or inattentive boaters. It is believed that by providing such visibility, boat safety can be significantly improved.

In the illustrative embodiment shown in FIG. 1, a boat lighting apparatus 18 is provided along the length of the hull 16 of the boat 10. The boat lighting apparatus 18 includes one or more light sources for producing light rays 20. The boat lighting apparatus 18 may be mounted to the boat and configured such that at least a portion of the light rays 20 illuminate a portion of the hull 16. In the embodiment shown, the boat lighting apparatus 18 provides light rays 20 that illuminate a substantial portion of the outer surface of the hull 16. Although not shown, the boat lighting apparatus 18 may continue around the perimeter of the boat hull 16, and illuminate both side surfaces of the hull and the back surface of the hull. The boat lighting apparatus 18 may provide a different color light for each side of the boat, such as a red light on the port side, a green light on the starboard side and a white light on the back side.

It is contemplated that the boat lighting apparatus 18 may or may not include a redirector (see below) for redirecting at least a portion of the light rays 20 to the side surface of the hull 16. The redirector may also prevent at least a portion of the light rays from traveling horizontally away and/or upward from the hull 16 of the boat 10.

A method of the present invention includes the steps of providing one or more light sources, and mounting the one or more light sources to the boat such that when energized, the one or more light sources illuminate a side surface of the hull 16.

FIG. 2 is a perspective view of a boat having another illustrative boat lighting apparatus. The boat is generally shown at 30, and includes an upper deck 31 extending over a hull 32. The hull 32 extends generally down from the upper deck 31 toward an expected water line 34. The hull 32 may also extend generally inward, as shown. In this embodiment, a number of boat lights 36a, 36b, 36c and 36d are mounted to the hull 32 of the boat 30. Boat lights 36a and 36b are mounted to the starboard side of the hull 32, and boat lights 36c and 36d are mounted to the back of the hull 32.

In the illustrative embodiment, each of the boat lights 36a, 36b, 36c and 36d includes at least one light source for producing a number of light rays and an elongated carrier for carrying the at least one light sources. The elongated carrier is preferably adapted for directing the light rays down to the boat hull 32 along a longitudinally extending axis, wherein the longitudinally extending axis has a length that is substantially longer than the width of the carrier, as shown. FIGS. 3-5 below show a number of illustrative placements for the lights of, for example, FIGS. 2, 6-12, 18-31, and 35-48.

It is also contemplated that when the upper deck 31 includes one or more relatively vertically extending surfaces, additional boat lights 38 may be provided to illumi-



nate these side surfaces as well. This may even further increase the visibility of the boat 30.

FIG. 3 is a schematic view of a boat hull having a number of boat lights, each directing light rays in a downward direction. While rectangular shaped boat lights are shown, it is contemplated that the boat lights may assume any desired shape. A hull is illustrated at 40 with a number of boat lights 40a, 40b, 40c and 40d mounted thereto. Boat lights 40a and 40b are shown mounted near the top of hull 40 and provide light rays in a generally downward direction. Boat lights 40c and 40d are shown mounted in an intermediate location on hull 40, and also provide light rays in a generally downward direction.

It is recognized that only the upper row of boat lights 40a and 40b may be necessary to illuminate the boat hull 40 down to the expected water line. Some hull designs may curve significantly inward toward the expected water line. For these boat hulls, it has been found that water at the water line of the boat may reflect some of the light provided by the upper row of boat lights 40a and 40b toward the hull of the boat. In some embodiments, one or more lower rows of boat lights, such as boat lights 40c and 40d, may be provided to help illuminate the lower portion of the boat hull 40, if desired.

FIG. 4 is a schematic view of a boat hull having a number of boat lights, each directing light rays in an upward direction. A hull is illustrated at 46 with a number of boat lights 48a and 48b mounted thereto. Boat lights 48a and 48b are shown mounted on a lower portion of hull 46, and provide light rays in a generally upward direction.

FIG. 5 is a schematic view of a boat hull having a number of boat lights, each directing light rays in forward and backward direction. A hull is illustrated at 50 with a number of boat lights 52a and 52b mounted thereto. Boat lights 52a and 52b are shown mounted on the hull 50, and may provide light rays in either a forward direction, a backward direction, or both. For example, boat light 52a may provide light rays 54a in a generally backward direction, light rays 54b in a generally forward direction, or both.

FIG. 6 is a partial cross-sectional perspective view of a boat hull 60 having an illustrative elongated boat lighting apparatus 66. The boat hull 60 includes a generally downward extending portion 62 that extends to an expected water line 64. The boat hull 60 may also include a bumper assembly 70 for protecting the boat hull 60 from docks or the like. The bumper assembly 70 is shown mounted on a top portion of the downward extending portion 62 of the boat hull 60 via mounting bolt 72.

The elongated boat lighting apparatus 66 is shown mounted to the downward extending portion 62 just below the bumper assembly 70. The elongated boat lighting apparatus 66 includes at least one light source for producing a number of light rays as shown, and an elongated carrier for carrying the at least one light source. The elongated carrier is preferably at least partially transparent to allow the light rays produced by the one or more light source to exit the carrier. In the embodiment shown, the light rays exit the carrier in various directions including down to the downward extending portion 62 of the boat hull 60, horizontally away from the boat hull 60, and upward toward the bumper assembly 70. However, in some embodiments, a redirector (not shown) may be positioned adjacent the top and outer side of the carrier to redirect substantially all of the light rays to the downward extending portion 62 of the boat hull 60. The redirector may include, for example, a separate shield placed around the top and outer side of the carrier, a reflective coating positioned on the top and outer side

surface of the carrier, or portions of the carrier may be made non-transparent. Alternatively, or in addition, the elongated boat lighting apparatus 66 may be incorporated into the bumper assembly 70, similar to that shown in FIG. 9.

It is contemplated that the one or more light sources 88 (as well as the other light sources referenced throughout the drawings) may be any type of light source including, but not limited to, an incandescent light source, a fluorescent light source, a light emitting diode (LED), any type of laser including one or more vertical cavity surface emitting lasers (VCSEL), electroluminescent light sources including electroluminescent wire and electroluminescent strips, a phosphor material, a glow in the dark material, or any other type of light source, either active or passive, that is capable of producing visible light.

In some embodiments, the one or more light sources may include an elongated light source, such as an electro-luminescent wire. One such electro-luminescent wire is commercially available from Solution Industries, located in Cypress, Tex., under the Trademark Flex Wire®. Another such electro-luminescent wire is commercially available from ELAM Electro-luminescent Industries Ltd., located in Jerusalem, Israel, under the Trademark LyTec™. Another suitable electro-luminescent light source is an electroluminescent strip, such as that commercially available from E-Light Technologies Inc. of Stafford, Conn. The electroluminescent light strips are long flat narrow substrates that include an electro-luminescent material along the flat side. Yet another suitable light source may include a string of light sources, such as a string of incandescent or LED light sources. One such string of light sources is available from Light Tech, Inc., located in Grand Rapids, Mich.

It is also contemplated the one or more light sources may include a light guide, such as a solid or multi-strand fiber optic cable or any other type of light transmitting medium that can transmit light rays. When so provided, the actual source of light may be located remotely, if desired, and coupled to the fiber optic cable or other type of light transmitting medium that can deliver the light rays to the desired location. One particularly suitable fiber optic cable is a linear emitting fiber, which emits light out of the side of the fiber. One such linear emitting fiber is available from Lumenyte International Corporation, Irvine, Calif., under the Trademark STA-FLEX® LEFT™ Linear Emitting Fiber. More information on Linear Emitting Fibers can be found in, for example, U.S. Pat. Nos. 6,289,150, 6,282,355, 6,251,311, 5,987,199, 5,937,127, 5,903,695, RE36,157, all of which are incorporated herein by reference. Traditional fiber optical cable may also be used, if desired.

It is contemplated that in some embodiments, the light source may include a UV stabilizer, UV absorber and/or UV filter. For example, some commercially available electroluminescent wires include a polymer coating or sleeve over the electro-luminescent material. It is contemplated that the polymer coating or sleeve may include a UV stabilizer, UV absorber and/or UV filter to help limit the deterioration of the polymer coating and/or electro-luminescent material. A preferred UV absorber is Sanduvor PR-25, available from Clariant Corp., Charlotte, N.C., which operates using photoreactive chemistry. However, other UV stabilizers, UV absorbers, and UV filters may be used, as desired.

FIG. 7 is a partial cross-sectional side view of a boat hull having another illustrative boat lighting apparatus. The boat hull 80 includes a generally downward extending portion 82 that extends to an expected water line. The boat hull 80 may also include a bumper assembly 100 for protecting the boat hull 80 from docks or the like. The bumper assembly 100 is

shown mounted on a top portion of the downward extending portion **82** of the boat hull **80** via mounting bolt **106**.

In the illustrative embodiment, boat lighting apparatus **84** is mounted to the downward extending portion **82**, just below the bumper assembly **100**. The boat lighting apparatus **84** includes one or more light sources **88** for providing light rays, a housing **86** for carrying the light source **88**, and a mount **91** for mounting the housing **86** to the boat. The mount **91** is shown bolted to the side of the downward extending portion **82** of the hull via a bolt or screw **92**. It is contemplated, however, that any number of means may be used to attach the mount to the boat including an adhesive or the like.

The housing **86** preferably has at least one opening **90** for directing the light rays **94** to at least a portion of the hull of the boat. In the illustrative embodiment shown, the housing **86** includes a wall that extends around three sides of the light source **88**, leaving the one opening **90** on the fourth downward side. Such a configuration not only helps direct the light rays **94** toward the hull of the boat, but also helps prevent at least a portion of the light rays from traveling laterally away from the hull of the boat. The inside surface of the housing **86** may be reflective, and may be shaped to help redirect the light rays **94** in a downward direction toward the hull of the boat. The housing **86** may also include a bracket (not shown) for carrying the one or more light sources **88**.

A transparent or semi-transparent plate may be positioned across the opening **90**. The transparent or semi-transparent plate may be constructed as a lens or the like to help redirect and/or focus the light on the hull of the boat. It is also contemplated that the transparent or semi-transparent plate may include a pattern provided thereon or therein to cause an image to be projected onto the hull of the boat. Finally, the transparent or semi-transparent plate may help protect the one or more light sources **88** from water or other undesirable environmental conditions.

In some embodiments, the transparent or semi-transparent plate may include a UV stabilizer, UV absorber and/or UV filter. The remainder of the housing **86** may also include a UV stabilizer, UV absorber and/or UV filter. This may help prevent deterioration of the transparent or semi-transparent plate and/or housing **86**, and may limit the amount of UV radiation that engages the one or more light sources. This may help extend the life of the light assembly, especially when exposed to sun light. It is contemplated that UV stabilizers, UV absorbers and/or UV filters may be applied to the carriers, housings, light sources, and other parts of the various embodiments disclosed herein, as desired.

To enhance the illumination of the hull of the boat, it is contemplated that a reflective medium **96** may be provided in or on the outer surface of the boat as shown. The reflective medium preferably helps reflect the light rays **94** laterally outward and away from the hull of the boat to enhance the visibility of the boat. It is contemplated that the reflective medium may be patterned to form an image. The image may be, for example, the name of the boat, advertising logos or any other desired image.

FIG. **8** is a perspective view of another illustrative boat lighting apparatus in accordance with the present invention. This illustrative boat lighting apparatus includes a round housing **120** that has an outer plate **122** and an inner plate **124**. The inner plate **124** is preferably positioned adjacent the boat hull when installed, and includes a hole **128** for receiving wires or the like to power a local light source. While a round housing is shown, it is contemplated that the housing **120** may be any shape.

A side plate **126** extends around part of the perimeter of the outer plate **122** and the inner plate **124**. In the embodiment shown, the side plate **126** extends around the perimeter of about the upper half of the outer plate **122** and inner plate **124**, leaving the perimeter around the lower half open. A light source (not shown) is preferably provided in the space between the outer plate **122** and the inner plate **124**. In this configuration, the outer plate **122**, inner plate **124** and side plate **126** help redirect the light rays provided by the light source downward through the opening toward the hull of the boat.

A transparent or semi-transparent plate **130** may extend around the lower perimeter of the outer plate **122** and the inner plate **124**. The transparent or semi-transparent plate **130** helps protect the light source from water and other undesirable environmental conditions. It is contemplated that the transparent or semi-transparent plate may be configured as a lens or the like to help focus or redirect the light rays to the hull of the boat. One such transparent or semi-transparent plate is illustrated at **132**, and has an outer surface **134** that tapers inward toward the boat. Because the lens is thicker away from the boat, the light rays traveling parallel to the hull of the boat are refracted more than those light rays that are already traveling toward the hull of the boat. This may help increase the illumination of the hull of the boat.

FIG. **9** is a partial cross-sectional side view of a boat hull with yet another boat lighting apparatus. This embodiment is similar to that shown in FIG. **7**, but has the boat lighting apparatus integrated or incorporated into the bumper assembly **144**. The bumper assembly **144** includes a flexible bumper guard **146** attached to an elongated housing **148**. The elongated housing **148** is attached to the hull of the boat via a bolt or screw **150**. The elongated housing **148** preferably has a cavity therein for receiving one or more light sources **152**. The cavity is preferably open along the lower surface thereof to allow the light rays **158** to illuminate the hull of the boat.

FIG. **10** is a partial cross-sectional side view of a boat hull having a boat lighting apparatus incorporated into an outward extending hull portion. In this embodiment, the boat hull **180** includes an outward extending hull portion **184**. The boat lighting apparatus **190** may then be provided in a cavity **192** provided in the lower surface of the outward extending hull portion **184**. Alternatively, a boat lighting apparatus similar to that shown in FIG. **7**, for example, may be mounted to a lower surface **193** of the outward extending hull portion **184** to illuminate the hull of the boat.

FIG. **11** is a partial cross-sectional side view of a boat hull having a telescoping boat lighting apparatus. In this embodiment, the boat lighting apparatus **210** has a housing that includes a telescoping lever for allowing the light source to be selectively pulled laterally away from the boat. When extended, the light source is further away from the boat hull, thereby increasing the angle of incidence of the light rays **218** at the hull of the boat. By increasing the angle of incidence, the amount of light that is reflected laterally away from the boat may be increased, thereby increasing the visibility of the hull. When contracted, the boat lighting apparatus **210** is preferably safely out of the way to reduce the chance that the boat lighting apparatus **210** will become damaged by other boats, docks or the like.

FIG. **12** is a partial cross-sectional side view of a boat hull having a threaded boat lighting apparatus. In this embodiment, the boat lighting apparatus **258** includes a threaded end **262**. The threaded end **262** preferably is adapted to engage a threaded hole in the hull of the boat. This allows

the boat lighting apparatus **258** to be easily removed from the hull of the boat during, for example, daylight hours. In the illustrative embodiment, the boat lighting apparatus **258** is mounted near the top of the hull **250** so that boater inside the boat can easily remove the lights. In this configuration, a laterally extending portion **256** may be provided to extend the light source a sufficient distance away from the boat hull to adequately illuminate the hull of the boat. While the boat lighting apparatus **258** is shown mounted near the top of the hull **250**, it is contemplated that the boat lighting apparatus **258** may be mounted anywhere on the boat, including further down on the downward extending portion **252**.

FIG. **13** is a schematic view of an illustrative circuit for powering the one or more light sources of the present invention. In the embodiment shown, a power source **300** is coupled to one or more light sources **304a** and **304b** via switch **302**. The one or more light sources **304a** and **304b** are preferably coupled in a parallel configuration with power source **300**, as shown. This allows each light source **304a** and **304b** to continue to operate even when one or more of the remaining light sources burns out or otherwise becomes damaged. The power source **300** may be any type of power source, but preferably is the boat battery, the boat alternator, or any other type of power source that is capable of properly driving the one or more light sources **304a** and **304b**.

FIG. **14** is a schematic view of another illustrative circuit for powering the one or more light sources of the present invention. In this embodiment, an electronic control circuit **320** provides power to each of a number of light sources **324a**, **324b** and **324c**. The electronic control circuit receives power from a power source **322**, and may be any type of control circuit that provides the desired functionality. Preferably, the control circuit is a simple state machine, a microprocessor, or any other type of control circuit.

FIG. **15** is a timing diagram showing one illustrative energizing scheme that can be provided by the control circuit **320** of FIG. **14**. In this illustrative embodiment, the control circuit **320** simultaneously provides energizing pulses **330**, **332** and **334** to light sources **324a**, **324b** and **324c**, respectively, for example at time **336**. Each of the energizing pulses **330**, **332** and **334** has the same duration. Accordingly, this causes each of the light sources **324a**, **324b** and **324c** to blink “on” during the corresponding energizing pulse, and “off” after the energizing pulse terminates. After a time period, all of the light sources **324a**, **324b** and **324c** are again energized. This causes each of the light sources **324a**, **324b** and **324c** to simultaneously blink “on” and “off”. It is believed that a blinking light may increase the visibility of the hull, especially for inattentive boaters.

FIG. **16** is a timing diagram showing another illustrative energizing scheme that can be provided by the control circuit **320** of FIG. **14**. In this illustrative embodiment, each of the light sources is energized in a sequential manner. For example, light source **324a** is energized by energizing pulse **340** at time **342**. Later, light source **324b** is energized by energizing pulse **344** at time **346**. Finally, light source **324c** is energized. This sequence may be repeated. In a preferred embodiment, the light sources **324a**, **324b** and **324c** are spaced longitudinally along the length of the boat. By illuminating the light sources in sequence, a moving or sweeping pattern may be generated across the hull of the boat. This may further increase the visibility of the hull of the boat. It is recognized that the embodiments shown in FIGS. **14–16** are only illustrative, and that numerous other lighting sequences can be used.

FIG. **17** is a perspective view of a personal watercraft having one or more boat lights **402** and **404** mounted thereto.

Boat lights **402** and **404** are preferably similar to that described herein and preferably illuminate at least a portion of the side surfaces of the personal watercraft. While a personal watercraft is shown in FIG. **17**, it is contemplated that the boat lighting apparatus of the present invention may be used to light the side surfaces of airplanes, snowmobiles, automobiles, all terrain vehicles, or any other type of “vehicle” as that term is used in the most general sense, to increase their visibility to outside observers.

FIG. **18** is a cross-sectional side view of another illustrative lighting apparatus of the present invention. The illustrative lighting apparatus is generally shown at **410**, and includes a carrier **412**, a bumper member **414**, and a light source **416**. The carrier **412** includes a back support **420**, a top support **422** and a bottom support **424**, as shown. The terms “back”, “bottom” and “top” are only used herein as relative terms to help describe the Figures. They are not intended to imply that the bottom support **420** must be below the top support **422** when the carrier **412** is actually mounted to an object. The top support **422** and bottom support **424** are shown extending from the top **426** and bottom **428** ends, respectively, of the back support **420** in a leftward direction. The top support **422** and bottom support **424** terminate to define a gap or slot **430** therebetween.

The bumper member **414** is shown positioned in the gap or slot **430**. The bumper member **414** preferably has an outer facing portion **432** that is sized to fit into the slot **430**, and one or more inner facing legs **434a** and **434b** that extend into the cavity formed by the top support **422** and bottom support **424** of the carrier **412**. The one or more legs **434a** and **434b** preferably have a dimension that exceeds the lateral dimension of the slot **430**, which helps secure the bumper member **414** to the carrier **412**. In some embodiments, the bumper member **414** and/or carrier **412** are at least somewhat deformable, so that the bumper member **414** and/or the elongated carrier **412** can or must be elastically deformed (e.g. bent or otherwise deformed) to allow the one or more legs **434a** and **434b** of the bumper member **414** to slip through the slot **430**. The bumper member **414** may also have one or more holes or lumens **440a** and **440b**. These holes or lumens **440a** and **440b** may decrease the rigidity of the bumper member **414**, as desired.

In one illustrative embodiment, the back support **420**, top support **422** and bottom support **424** of the carrier **412** are integrally formed by extrusion, although this is not required. In some embodiments, the back support **420**, top support **422** and bottom support **424** of the carrier **412** are made from a relatively rigid material, such as Vinyl, PVC, aluminum, or any other suitable material.

The bumper member **414** may also be formed by extruding a material such as Vinyl, PVC, rubber, or any other suitable material. However, like above, this is not required. Preferably, the bumper member **414** is formed from a softer material than the carrier **412**, but this is also not required.

In the illustrative embodiment shown in FIG. **18**, the carrier **412** has an inner support member **436** that is curved to form a light receiving opening or cavity **438**. In the illustrative embodiment, the inner support member **436** is adapted to receive and secure an elongated light source **416**. In a preferred embodiment, the elongated light source **416** is an electro-luminescent wire or a Linear emitting fiber, as detailed above. However, it is contemplated that the elongated light source **416** may be any type of light source, including those discussed above.

The inner support member **436** may be at least partially transparent or non-transparent. When the inner support member **436** is non-transparent, the light emitted by the light

source is directed in a downward direction toward the bottom support 424 of the carrier 412. When so provided, at least a portion of the bottom support 424 is preferably at least partially transparent. This may be accomplished by, for example, forming the bottom support 424 or a portion thereof from a material that is at least semi-transparent. Alternatively, holes or slots may be provided in the bottom support 424 to allow the light to pass through the bottom support 424. In some embodiments, the holes or slots may be spaced holes or slots that are spaced along the length of the bottom support 424. Such spaced holes or slots may be formed by, for example, periodically interrupting the extrusion material along the bottom support 424. Other methods may also be used, such as cutting, drilling or otherwise forming spaced holes or slots. Spaced holes or slots may be used in other embodiments described herein, if desired.

In some embodiments, the back support 420, top support 422 and bottom support 424 may be formed from a transparent or semi-transparent material. In other embodiments, only selected portions may be formed from a transparent or semi-transparent material. For example, the bottom support 424, or portion thereof, may be formed from a transparent or semi-transparent material. In this latter case, the back support 420, top support 422 and bottom support 424 may be co-extruded using a non-transparent and transparent or semi-transparent material, with the transparent or semi-transparent material corresponding to the portion that is to transmit light. Alternatively, the bottom support 424, or the portion thereof that is to pass light, may be separately formed and subsequently attached, if desired.

In another illustrative embodiment, the inner support member 436 or a portion thereof may be made from a transparent or semi-transparent material to pass light toward the bumper member 414. In this illustrative embodiment, the bumper member 414, or a portion thereof, may also be formed from a transparent or semi-transparent material. When so provided, the light from the light source 416 may pass through the inner support member 436, through the bumper member 414, and away from the carrier 412. In use, the back support 420 is preferably positioned adjacent a mounting surface and mounted thereto.

It is contemplated that the bumper member 414 and/or carrier 412, or parts thereof, may be made using materials of different colors, as desired. Also, it is contemplated that the light source may be selected to produce a desired color of light.

FIG. 19 is a cross-sectional side view of another illustrative lighting apparatus of the present invention. The illustrative lighting apparatus includes a carrier 450, a bumper member 452, and a light source 454. The carrier 450 includes a back support 456, a top support 458 and a bottom support 460, as shown. The top support 458 and bottom support 460 are shown extending from the top and bottom ends, respectively, of the back support 456 in a leftward direction. The top support 458 and bottom support 460 terminate to define a gap or slot 462 therebetween.

The bumper member 452 is shown positioned in the gap or slot 462, as described above. In the illustrative embodiment, the back surface 464 of the bumper member 452 and the front surface 466 of the back support 456 are shaped to form a light receiving channel, opening or cavity. In the illustrative embodiment, the light receiving channel, opening or cavity is adapted to receive and secure an elongated light source 454. It is contemplated that the elongated light source 454 may be any type of light source, including those identified herein.

The bumper member 452, or a portion thereof, is preferably formed from a transparent or semi-transparent material. When so provided, the light from the light source 454 may pass through the bumper member 452, and away from the carrier 450 as shown by lines 468.

FIG. 20 is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention. In this illustrative embodiment, the bumper member 470 includes one or more holes, slots or lumens 472. A light source 474 is then positioned in one or more of the holes, slots or lumens 472. Only one light source 474 is shown in FIG. 20. The bumper member 470, or a portion thereof, is preferably formed from a transparent or semi-transparent material. When so provided, the light from the light source 474 may pass through the transparent or semi-transparent portion of the bumper member 470 and away from the carrier 478, as shown by lines 476.

When more than one light source 474 is provided, each light source 474 may be situated in a different one of the holes or lumens 472, but this is not required. Selected light sources may be selected to produce different colors. Alternatively, or in addition, the portion of the bumper member 470 adjacent selected light sources may be formed from materials of different colors. In some embodiments, this may provide the appearance of one or more stripes of colors along the bumper member 470.

FIG. 21 is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention. In this illustrative embodiment, the lighting apparatus includes a carrier 490, a bumper member 492, and a light source 494. The carrier 490 includes a back support 496, a top support 498 and a bottom support 500, as shown. Like above, the top support 498 and bottom support 500 terminate to define a gap or slot for receiving the bumper member 492.

In some embodiments, the back support 496, top support 498 and bottom support 500 of the carrier are made from a relatively rigid material, such as Vinyl, PVC, aluminum, or any other suitable material. The bumper member 492 may also be formed by, for example, extruding a material such as Vinyl, PVC, rubber, aluminum or any other suitable material. However, like above, this is not required. Preferably, the bumper member 492 is formed from a softer material than the carrier, but this is also not required.

In the illustrative embodiment, the back support 496 and the bottom support 500 are joined together through a light carrying member 502. Although not shown in FIG. 21, it is contemplated that the back support 496 and the top support 498 may also be joined together through another light carrying member, if desired, to provide light in an upward direction. The light carrying member 502 preferably defines a channel, cavity or recess for receiving the light source 494. Preferably, the cavity or recess is sized to receive the light source and secure the light source 494 to the carrier 490. In the illustrative embodiment, the cavity or recess has a receiving slot 504 for receiving the light source 494. In a preferred embodiment, the light source 494 is an elongated light source such as an electro-luminescent wire or a Linear Emitting Fiber, as detailed above. However, it is contemplated that the light source 494 may be any type of light source, including those identified herein.

FIG. 22 is a cross-sectional side view of yet another illustrative lighting apparatus in accordance with the present invention. In this illustrative embodiment, the lighting apparatus includes a carrier 510. For simplicity, the bumper member and light source are not shown. The carrier 510 includes a back support 512, a top support 514 and a bottom

15

support **516**, as shown. Like above, the top support **514** and bottom support **516** terminate to define a gap or slot **518** for receiving a bumper member.

In the illustrative embodiment, the bottom support **516** is shaped to provide a light carrying channel, cavity or recess **518**. The light carrying channel, cavity or recess **518** preferably is sized to receive a light source. In the illustrative embodiment, the channel, cavity or recess **518** preferably has a transparent or semi-transparent portion **520** for passing light in a downward direction. The transparent or semi-transparent portion **520** may be co-extruded with the rest of the carrier **510**, which may be made from a non-transparent material, if desired. Alternatively, the transparent or semi-transparent portion **520** may be formed separately, and subsequently secured to the bottom support **516**.

In either case, and in some embodiments, the transparent or semi-transparent portion **520** may be shaped to form a Fresnel lens, as shown in FIG. **24**. A Fresnel lens may help collect and focus the light that is emitted by the light source. A Fresnel lens may also help minimize the amount of absorption in the lens by reducing the thickness of the lens. Other lens shapes may also be used.

FIG. **23** is a cross-sectional side view of yet another illustrative lighting apparatus in accordance with the present invention. This illustrative embodiment is similar to the embodiment shown in FIG. **22**. However, the bottom support **530** is shaped to provide a larger cavity **532** for receiving a bumper member. Further, the wall thickness of the bottom support **530** is maintained along its length. In the illustrative embodiment, this is accomplished by moving the central axis **536** of the light carrying cavity or recess **534** further down and/or away from the carrier.

FIG. **25** is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention. This illustrative embodiment is similar to the embodiment shown in FIG. **21**. However, the cavity or recess **540** does not have a receiving slot for receiving the light source **494**. Instead, a wall encircles the cavity or recess **540**. In one embodiment, a lower portion **542** of the wall encircling the cavity or recess **540** is formed from a transparent or semi-transparent material. The remainder of the wall encircling the cavity or recess **540** may be at least partially reflective, but this is not required.

FIG. **26** is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention. This illustrative embodiment is similar to that shown in FIG. **25**. However, the cavity or recess **550** has a receiving slot **552** for receiving a light source **554**. The receiving slot **552** is shown opening into the inner cavity **556** of the carrier **558**. To install the light source **554** into the cavity or recess **550**, the bottom support **560** may be pulled away from the back support **562**. Preferably, the bottom support **560** and/or back support **562** temporarily elastically deform to open the receiving slot **552** and receive the light source **554**. Once the light source **554** is in the cavity or recess **550**, the bottom support **560** may be returned or nearly returned to its original position relative to the back support **562**. The bumper member **564** is then installed, also preferably by elastic deformation of the bumper member **564** and/or carrier **558**. Like the embodiment shown in FIG. **25**, it is contemplated that a lower portion **566** of the wall encircling the cavity or recess **550** may be formed from a transparent or semi-transparent material. The remainder of the wall encircling the cavity or recess **550** may be at least partially reflective, but this is not required.

FIG. **27** is a cross-sectional side view of yet another illustrative lighting apparatus in accordance with the present

16

invention. In this illustrative embodiment, a parabolic shaped recess or cavity **580** is formed in the bottom support **582**. A parabolic shape may help collect and direct the light emitted by the light source **584** in a particular direction, particular if the walls of the parabolic shaped recess or cavity **580** are at least partially reflective. In some embodiments, the axis **586** of the parabolic shaped recess or cavity **580** may be offset relative to a vertical axis **588** to help direct the light rays toward an object, such as an object that the carrier **590** is mounted.

A lens or cover **594** may be provided to cover the parabolic shaped recess or cavity **580**, if desired. In some illustrative embodiments, one or more receiving slots **596** and **598** may be provided for receiving the edges of the lens or cover **594**. In other illustrative embodiments, the lens or cover may be co-extruded or otherwise integrally formed or securely attached to the carrier **590**.

FIG. **28** is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention. This illustrative embodiment includes a “D” shaped carrier **600** having a bumper receiving slot **602**. A bumper member **604** may be provided in the bumper receiving slot **602**. The bumper member **604** may be an elongated tube that is sized to fit within the bumper receiving slot **602**, as shown. Like the illustrative embodiment of FIG. **27**, a parabolic shaped recess or cavity **606** is provided in a bottom portion of the “D” shaped carrier **600**. A lens or cover **608** may be provided to cover the parabolic shaped recess or cavity **606**, if desired. In the illustrative embodiment, the lens or cover is co-extruded or otherwise integrally formed or securely attached to the “D” shaped carrier **600**, but this is not required.

A light source **610** is shown positioned in the parabolic shaped recess or cavity **606**. One or more light source support members **612** may be provided to help secure the light source **610** in the parabolic shaped recess or cavity **606**. In some embodiments, the one or more light source support members **612** may help secure the light source **610** at or near the focal point of the parabolic shaped recess or cavity **606**.

FIG. **29** is a cross-sectional side view of yet another illustrative lighting apparatus in accordance with the present invention. In this illustrative embodiment, a carrier **620** is provided with a light receiving channel, cavity or recess **622** formed in the bottom support **624**. A light source **626** is positioned within the light receiving channel, cavity or recess **622**. The illustrative carrier **620** has a back support **626** that is adapted to be adjacent a mounting surface.

A mating member **628** is also provided. The mating member **628** may include a back support **630** and a lens or cover portion **632**. The mating member **628** preferably mates with the back support **626** of the carrier **620**. The lens or cover portion **632**, or a portion thereof, preferably is shaped to cover the light receiving cavity or recess **622** formed in the bottom support **624**. A slot may be provided in the bottom support **624** of the carrier **620** to receive a lip **634** of the lens or cover portion **632**, if desired.

In one illustrative embodiment, the carrier **620** may be made from a material that is non-transparent and at least partially reflective. The mating member **628** may be made from a material that is at least semi-transparent. Alternatively, only the lens or cover portion **632** of the mating member **628** may be made from a material that is at least semi-transparent. In other embodiments, the carrier **620** may be made from a material that is at least partially transparent, and the mating member may be made from a material that is non-transparent and at least partially reflective. In any

case, it is contemplated that the mating member **628** may be made separate from the carrier **620**.

FIG. **30** is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention. In this illustrative embodiment, no separate bumper member is provided. Instead, an elongated tube **640** is provided with a mounting support **642** extending therefrom. A spacer support **644** may also be provided to help space the tube **640** from the mounting surface. A light source (not shown) can be positioned within the inner lumen **648** of the tube **640**, as desired. At least a portion of the tube **640** is preferably at least semi-transparent to allow at least some of the light rays from the light source to exit from the tube **640**. In one embodiment, portion **645**, portion **646**, or both, are at least semi-transparent. In some embodiments, the tube **640** is adapted to prevent light rays from traveling in a first direction away from the tube **640** while allowing light rays to travel in a second different direction away from the tube **640**.

FIG. **31** is a cross-sectional side view of yet another illustrative lighting apparatus in accordance with the present invention. Like the embodiment shown in FIG. **30**, this illustrative embodiment also does not have a separate bumper member. Instead, an elongated member **650** is provided with a mounting region **652** and a light source receiving region **654**. The light source receiving region **654** includes a light source receiving cavity or recess **656**, which receives a light source **658**. The elongated member **650** may be made from a non-transparent or at least semi-transparent material, as desired.

As indicated above, it is contemplated that some embodiments of the present invention may be used to illuminate vehicles, such as boats (including barges), cars, trucks, etc., preferably by illuminating one or more side surfaces of the vehicle. The side surfaces of many vehicles provide a relatively large area that, when illuminated, can significantly increase the visibility of the vehicle, especially at night. It is believed that by providing such visibility, vehicle safety can be significantly improved. FIG. **32** is a schematic view of a truck **660** with an illustrative lighting apparatus **662** mounted to the side thereof. The illustrative truck **660** includes a cab **664** and a trailer **666**, with an illustrative lighting apparatus **662** mounted along a lower edge **668** of the trailer **666**. The illustrative lighting apparatus **662** may be similar to those described herein, and may distribute light in an upward direction to illuminate at least a portion of the side surface **670** of the trailer **666**. The lighting apparatus **662** may extend around the perimeter of the trailer **666**, if desired.

In some embodiments, the illustrative lighting apparatus **662** may include a bumper, to help provide a level of protection to the lower edge **668** of the trailer **666**. Such protection may be desirable when, for example, the truck **660** is maneuvering into a loading dock or the like. While the illustrative lighting apparatus is shown mounted to a truck trailer **666**, it may also be mounted to the box of a straight truck, or even to the cab **664**, as desired. In addition, it is contemplated that the illustrative lighting apparatus **662** may be mounted to an upper edge **672** of the cab **664** or trailer **666**, and/or at an intermediate location, as desired.

FIG. **33** is a schematic view of an object, generally shown at **680**, with an illustrative lighting apparatus **682** mounted to the side thereof. The object **680** may be any type of object. For example, the object **680** may include retail and/or store shelving and/or equipment (including grocery store shelving and/or equipment such as refrigerated shelving), bars, desks, counters, walls such as in hallways or rooms, ceilings,

railings, steps, and/or any other object or surface, as desired. The illustrative lighting apparatus **682** is shown providing illumination in both an upward and downward direction, although in some embodiments, illumination may be only provided in one direction, including in an outward direction. In some embodiments, the lighting apparatus **682** may include a bumper, such as described above. When so provided, the lighting apparatus **682** may help provide a level of protection to the object **680**.

FIG. **34** is a schematic view of a tow line **690** that includes an illustrative lighting apparatus in accordance with the present invention. A tug or other boat **692** is shown pulling one or more barges **694** via tow line **690**. It is contemplated that the tug boat **692**, tow line **690** and/or one or more barges **694** may be illuminated using a lighting apparatus in accordance with the present invention. The tow line **690** may be illuminated by securing one or more light sources to the tow line **690**. For example, an electro-luminescent wire or Linear Emitting Fiber may be secured along the length of the tow line. Other types of light sources may also be used. This may allow other boaters to more easily see the tug boat **692**, the tow line **690** and/or the barges **694** at night.

It is also contemplated that one or more light sources may be provided on parked barges **694** to illuminate one or more sides surfaces of the barges **694**. The one or more light sources may be incorporated into a lighting apparatus, as described herein. Barges are often fairly dark in color, and can be difficult to see at night. By illuminating one or more side surfaces of the barges **694**, boaters may more easily see the parked barges at night.

FIG. **35** is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention. In this illustrative embodiment, an elongated carrier **696** is provided. Like some of the embodiments above, the elongated carrier **696** includes two legs **698a** and **698b** that form a slot or opening for receiving an elongated bumper member or insert **700**. In some embodiments, the elongated carrier **696** and/or the elongated bumper member **700** must be elastically deformed (e.g. bent or otherwise deformed) for the elongated bumper member **700** to slip into the slot. To help aid the insertion of the elongated bumper member **700** into the slot of the elongated carrier **696**, the elongated bumper member **700** may include one or more relief lumens **704a** and **704b**, if desired.

The elongated bumper member **700** may include a cavity **702**. The illustrative cavity **702** is adapted to receive an elongated light source (not shown), such as an electro-luminescent wire, a linear emitting fiber, or any other suitable elongated light source. The elongated bumper member **700**, or a portion thereof, may be formed from a transparent or semi-transparent material. The transparent or semi-transparent material preferably defines at least part of the cavity **702**, and extends to an outer surface of the elongated bumper member **700**. In the embodiment shown, portion **710** may be formed from a transparent or semi-transparent material. When so provided, the light from the elongated light source may pass through the transparent or semi-transparent portion of the elongated bumper member **700** and away from the lighting apparatus.

To help aid with the insertion of the elongated light source into the cavity **702**, a slit **706** may be provided. The slit may extend from the cavity **702** to an outer surface **708** of the elongated bumper member **700**. In the embodiment shown, the slit extends from the cavity **702** to the outer surface **708** adjacent the back of the carrier **698**, but this is not required.

FIG. **36A** is a cross-sectional side view of the elongated bumper member (or insert) **700** of FIG. **35**, with the slit **706**

in the closed position. In one embodiment, the slot of the elongated carrier **698** as well as the shape and size of the elongated bumper member **700** are adapted so that when the elongated bumper member **700** is inserted into the slot of the elongated carrier **698**, the elongated carrier **698** provides a closing force to keep the slit **706** in, or nearly in, the closed position.

FIG. **36B** is a cross-sectional side view of the elongated bumper member (or insert) of FIG. **35**, with the slit in an open position. In the illustrative embodiment, the elongated bumper member **700** is normally in the closed position, as shown in FIG. **36A**. To place the elongated bumper member **700** in the open position, the elongated bumper member **700** is at least partially elastically deformed (e.g. bent or otherwise deformed) by applying an outward force. Alternatively, the elongated bumper member **700** may normally be in the open position, as shown in FIG. **36B**. To place the elongated bumper member **700** in the closed position, the elongated bumper member **700** is at least partially elastically deformed (e.g. bent or otherwise deformed) by applying an inward force. In either case, the elongated bumper member **700** may more easily receive an elongated light source (not shown) through the slit **706** when in the open position.

FIG. **36C** is a cross-sectional side view of the insert of FIG. **35**, with the slit in an open position and with a slit latching mechanism. In the illustrative embodiment, the slit latching mechanism includes a leg with a tooth **712**, along with a matching receiving opening **714**. As the elongated bumper member **700** is moved into the closed position, the leg **712** slides into the matching receiving opening **714**, and the tooth **712** snaps into a corresponding opening in the receiving opening. The latching mechanism may help the elongated bumper member **700** remain in the closed position.

FIG. **37** is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention. This illustrative embodiment is similar to that shown in FIG. **26**. However, the receiving slot **720** for receiving the light source **722** may be wider, and may be used to direct light from the light source **722** to the elongated bumper member **724**. The elongated bumper member **724** may then include a transparent or semi-transparent portion **726** that directs the light received through the receiving slot **720** to an outer surface **728** of the elongated bumper member **724**. In some embodiments, the entire elongated bumper member **724** may be made from a transparent or semi-transparent material. In other embodiments, only a portion of the elongated bumper member **724** is transparent or semi-transparent portion, as shown. In either case, the embodiment shown in FIG. **37** may allow light from the light source **722** to be directed to multiple locations, such as down through a transparent or semi-transparent window **730** as well as to the outer surface **728** of the elongated bumper member **724**.

FIG. **38** is a cross-sectional side view of an illustrative rub-rail with nubs in accordance with the present invention. The illustrative rub-rail is generally shown at **740**, and includes a carrier **742** and an elongated bumper member **744**. The carrier **740** includes a back support **746**, a top support leg **748** and a bottom support leg **750**. The top support leg **748** and bottom support leg **750** are shown extending from the top **752** and bottom **754** ends, respectively, of the back support **746** in a leftward direction. The top support leg **748** and bottom support leg **750** terminate to define a gap or slot **758** therebetween.

The bumper member **744** is shown positioned in the gap or slot **758**. The bumper member **744** preferably has an outer

portion **756** that is sized to fit into the slot **758**, and one or more inner facing legs **760a** and **760b** that extend into the cavity formed by the top support leg **748** and bottom support leg **750** of the carrier **742**. The one or more legs **760a** and **760b** preferably have a dimension that exceeds the lateral dimension of the slot **758**, which helps secure the bumper member **744** to the carrier **742**. In some embodiments, the bumper member **744** and/or carrier **742** are at least somewhat elastically deformable, so that the bumper member **744** and/or the elongated carrier **742** can or must be elastically deformed (e.g. bent or otherwise deformed) to allow the one or more legs **760a** and **760b** of the bumper member **744** to slip through the slot **758**. The bumper member **744** may also have one or more relief holes or lumens, such as relieve hole or lumen **762**. Such relief holes or lumens may decrease the rigidity of the bumper member **744**, as desired.

One or both of the top support leg **748** and bottom support leg **750** of the carrier **742** may have a nub, such as nub **764a** and/or **764b**. These nubs preferably extend inward into the cavity formed by the carrier **742**. For example, nub **764a** of the top support leg **748** is shown extending down into the cavity of the carrier **742** toward the bottom support leg **750**. Likewise, nub **764b** of the bottom support leg **750** is shown extending up into the cavity of the carrier **742** toward the top support leg **748**.

In the illustrative embodiment, the top support leg **748** has an increased thickness at nub **764a**, and the bottom support leg **750** has an increased thickness at nub **764b**. In other embodiments, however, the thickness may remain relatively constant along the length of the top and/or bottom support legs, with both the inner surface and outer surface of the support legs extending inwardly to form the corresponding nub. Although the nubs **764a** and **764b** are shown near the distal end of the corresponding support leg away from the back member **746**, it is contemplated that the nubs may be placed anywhere along the top and/or bottom support legs **748** and **750**, and/or along the back member **746** as desired. In addition, multiple nubs may be placed along one or more of the top support leg, bottom support leg and/or back support **746**, as desired. The elongated bumper member **744** preferably is shaped to accept the one or more nubs provided on the top support leg, bottom support leg and/or back support, as shown.

FIG. **39** is a cross-sectional side view of an illustrative lighting apparatus with nubs in accordance the present invention. This embodiment is similar to that shown in FIG. **38**, but the elongated bumper member **768** includes a cavity **770** for receiving a light source **772**, as shown. The elongated bumper member **768** is shaped to accept the nubs **764a** and **764b** provided on the top support leg **748** and bottom support leg **750**, respectively. That is, the elongated support member **768** includes an outer surface that is shaped to correspond to the inner surface of the carrier **742**, including nubs **764a** and **764b**. As indicated above, nubs **764a** and **764b** do not need to be positioned at or near the distal end of the top support leg **748** and/or bottom support leg **750**, but rather may be positioned anywhere along the top support leg **748**, bottom support leg **750** and/or back support **746**, depending on the application.

In the illustrative embodiment, the elongated support member **768** may be made from a transparent or semitransparent material, or alternatively only a portion **774** (indicated by a dashed line) of the elongated support member **768** may be made from a transparent or semitransparent material, with the remainder made from a substantially non-transparent material. In addition, the illustrative elongated support member **768** includes a slit that extends from the cavity **770**

21

to the back outer surface **776** of the elongated support member **768** to aid in the insertion of the elongated light source **772** into the cavity **770**.

FIG. **40** is a cross-sectional side view of an illustrative lighting apparatus for receiving an elongated light source. The illustrative lighting apparatus is shown generally at **800**, and includes a body **802**. The body **802** includes a cover portion **804**, which together form a cavity **806** for receiving an elongated light source **808**. The body **802** may be transparent or semi-transparent, or substantially non-transparent, depending on the application. In one illustrative embodiment, the cover **804** is transparent or semi-transparent, and the remainder of the body **802** is substantially non-transparent. The cover **804** may be shaped to form a lens, but this is not required. In another illustrative embodiment, the cover **804** is substantially non-transparent and the remainder of the body **802** is transparent or semi-transparent.

It is contemplated that the cover **804** may be formed integrally with the remainder of the body **802** (such as by, for example, extrusion, co-extrusion, molding, or any other suitable method). Alternatively, the cover **804** may be formed separately from the remainder of the body **802**. When formed separately from the remainder of the body **802**, the cover **804** may be later secured to the remainder of the body **802** by, for example, a snapping mechanism, an adhesive, screws, or any other suitable securing method. In some embodiments, the cover **804** is secured to the remainder of the body **802** after the elongated light source is inserted into the cavity **806**.

In some embodiments, the body **802** may include a slit **810** that extends from the cavity **806** to an outer surface of the body **802**, such as outer surface **812**. The slit **810** may be moved to an open position, by for example applying an external outward force, which may help aid in the insertion of the elongated light source **808** into the cavity **806** through the slit **810**. Like other embodiments, it is contemplated that the illustrative lighting apparatus **800** may be mounted to, for example, any object including a boat, retail and/or store shelving and/or equipment (including grocery store shelving and/or equipment such as refrigerated shelving), bars, desks, counters, walls such as in hallways or rooms, ceilings, railings, steps, and/or any other object or surface, as desired. The body **802** may help provide a level of protection to the object and/or a level of protection to the elongated light source.

FIG. **41** is a cross-sectional side view of another illustrative lighting apparatus for receiving an elongated light source. The illustrative lighting apparatus is shown generally at **820**, and includes a body **822**. The body **820** includes a cover portion **824**, which together form a cavity **826** for receiving an elongated light source **828**. In the illustrative embodiment, the cavity **826** is parabolic in shape, which in some embodiments, may help focus (by reflection) the light provided by the elongated light source **828** toward the cover portion **824**. The body **822** may be transparent or semi-transparent, or substantially non-transparent, depending on the application. In one illustrative embodiment, the cover **824** is transparent or semi-transparent, and the remainder of the body **822** is substantially non-transparent. The cover **824** may be flat or shaped to form a lens, as desired. In another illustrative embodiment, the cover **824** is substantially non-transparent and the remainder of the body **822** is transparent or semi-transparent.

It is contemplated that the cover **824** may be formed integrally with the remainder of the body **822** (such as by, for example, extrusion, co-extrusion, molding, or any other

22

suitable method). Alternatively, the cover **824** may be formed separately from the remainder of the body **822**. When formed separately from the remainder of the body **822**, the cover **824** may be later secured to the remainder of the body **822** by, for example, a snapping mechanism, an adhesive, screws, or any other suitable securing method. In some embodiments, the cover **824** is secured to the remainder of the body **822** after the elongated light source is inserted into the cavity **826**.

In some embodiments, the body **822** may include a slit **830** that extends from the cavity **826** to an outer surface of the body **822**, such as outer surface **832**. The slit **830** may be moved to an open position, by for example applying an external outward force, which may help aid in the insertion of the elongated light source **828** into the cavity **826** through the slit **830**. It is contemplated that the illustrative lighting apparatus **820** may be mounted to, for example, any object including boats, retail and/or store shelving and/or equipment (including grocery store shelving and/or equipment such as refrigerated shelving), bars, desks, counters, walls such as in hallways or rooms, ceilings, railings, steps, and/or any other object or surface, as desired. The body **822** may help provide a level of protection to the object and/or a level of protection to the elongated light source.

FIG. **42** is a cross-sectional side view of yet another illustrative lighting apparatus for receiving an elongated light source. This illustrative embodiment is similar to the embodiment shown in FIG. **41**, but the body **840** has a height **842** that is substantially greater than the thickness **844**. In addition, the body **840** extends a substantial distance beyond the cavity **846**. In one example, the cavity may have a diameter on the order of 0.050 inches, and the height **842** of the body **840** may be on the order of 0.25 to 24 inches or more. In some embodiments, this may provide a relatively large protection area (represented by the height **842** of the body **840**) to an object.

FIG. **43** is a cross-sectional side view of another illustrative lighting apparatus for receiving an elongated light source. This illustrative embodiment is similar to the embodiment of FIG. **42**. However, the body **850** includes both a first material **852** that is at least semi-transparent and a second material **854** that is substantially non-transparent. The at least semi-transparent material **852** is shown extending from the cavity **856** that houses the elongated light source **858** to one or more outer surfaces **860a** and **860b** of the body **850**. The at least semi-transparent material **852** thus at least partially defines the cavity **856** and accepts light therefrom. The light is then delivered down the at least semi-transparent material **852** to the illuminate the one or more outer surfaces **860a** and **860b**. In the illustrative embodiment, the outer surface **862** between the one or more outer surfaces **860a** and **860b** is substantially non-transparent, with the possible exception of cover portion **864**, but this is not required.

It is contemplated that the one or more outer surfaces **860a** and **860b** may be flat or may be shaped to form a lens, depending on the application. In addition, it is contemplated that the at least semi-transparent material **852** may have a higher index of refraction than the substantially non-transparent material **854**, but this is not required. This may promote greater total internal reflection of the light as it travels down the at least semi-transparent material **852**, much like an optical fiber.

In one illustrative embodiment, the at least semi-transparent material **852** may be integrally formed with the substantially non-transparent material **854**. For example, the at least semi-transparent material **852** may be co-extruded



with the substantially non-transparent material **854**. Alternatively, the at least semi-transparent material **852** may be separately formed from the substantially non-transparent material **854**, and subsequently mechanically secured together, as desired.

FIG. **44** is a cross-sectional side view of an illustrative lighting apparatus with one or more legs for securing the lighting apparatus to a substrate. The illustrative lighting apparatus is generally shown at **880** and includes a body **882**. The body **882** includes a main body portion **883**, a first leg **884** with a first tooth **886**, and a second leg **888** with a second tooth **890**. In this illustrative embodiment, the first leg **884** and second leg **888** extend continuously along the length of the main body portion **883**. The first leg **884** and the second leg **888** are shown extending away from the main body portion **883** at an angle **892** that is greater than zero. However, in some embodiments, the angle **892** may be zero or even negative, depending on the application. The main body portion **883** is similar that shown in FIG. **40**.

FIG. **45** is a cross-sectional side view of another illustrative lighting apparatus with one or more legs for securing the lighting apparatus to a substrate. This illustrative embodiment is similar to the embodiment shown in FIG. **44**, except the first leg **896** and the second leg **898** do not extend continuously along the length of the main body portion **900**. Rather, and in one embodiment, one or more first and second leg pairs **896**, **898** are provided periodically along the length of the main body portion. Only one first and second leg pair is shown.

FIG. **46** is a cross-sectional side view of the illustrative lighting apparatus of FIG. **45** with the first leg **896** and the second leg **898** inserted through a substrate **902**. As the first leg **896** and the second leg **898** are pushed through a hole in the substrate **902**, the first leg **896** and the second leg **898** are forced closer together, which may temporarily elastically deforming the first leg **896** and the second leg **898**. Once the teeth reach the backside **904** of the substrate **902**, the first leg **896** and the second leg **898** separate and the teeth engage the backside **904** of the substrate **902** as shown. This may help secure the illustrative lighting apparatus to the substrate **902**. The substrate may be any type of substrate including, for example, wall board, plywood, cement, fiberglass, metal, or any other type of substrate, as desired.

FIG. **47** is a cross-sectional side view of yet another illustrative lighting apparatus attached to a substrate. The illustrative lighting apparatus is shown generally at **908**, and includes an elongated body **910**. The elongated body **910** includes a cover portion **912**, which together form an elongated cavity **914** for receiving an elongated light source **916**. The elongated body **910** may be transparent or semi-transparent, or substantially non-transparent, depending on the application. In one illustrative embodiment, the cover **912** is transparent or semi-transparent, and the remainder of the body **910** is substantially non-transparent. The cover **912** may be shaped to form a lens, but this is not required. In another illustrative embodiment, the cover **912** is substantially non-transparent and the remainder of the body **910** is transparent or semi-transparent.

The elongated body **910** shown in FIG. **47** includes an upper extending leg **918** that extends upward from the remainder of the body **910**, and a lower extending leg **920** that extends downward from the remainder of the body **910**. The upper extending leg **918** and lower extending leg **920** may be relatively thin, and may extend outward from the remainder of the body **910** along a plane formed by the front face **926** of the remainder of the body **910**, but this is not required.

In one embodiment, the main body **910** is inserted into an appropriately sized recess or hole **922** in a substrate **924**. The upper extending leg **918** and lower extending leg **920** preferably extend out past the upper and lower edges **930a** and **930b** of the elongated recess or hole **922**, and engage the front face **932** of the substrate **924** as shown. In some embodiments, the upper extending leg **918** and lower extending leg **920** are secured to the substrate by, for example, an adhesive, screws, or any other suitable securing method, as desired.

In some embodiments, the body does not extend to the backside **934** of the substrate **924**. When so provided, the illustrative lighting apparatus may not disturb objects behind the substrate, such as studs **940** or any other members or objects behind the substrate **924**. In other embodiments, the body **910** may extend to or beyond the backside **934** of the substrate **924**, as desired.

FIG. **48** is a cross-sectional side view of an illustrative lighting apparatus for securing an elongated light source to a substrate. This embodiment may be particularly suitable for securing an elongated light source to a substrate that can be initially provided in a liquid or semi-liquid state, and then cured or hardened to a more solid state. The illustrative lighting apparatus is shown generally at **950**, and includes an elongated member or body **952**. The elongated member **952** includes a cover **954**, which together form a cavity **956** for receiving an elongated light source **958**.

The elongated member or body **952** may be transparent or semi-transparent, or substantially non-transparent, depending on the application. In one illustrative embodiment, the cover **954** is transparent or semi-transparent, and the remainder of the elongated member or body **952** is substantially non-transparent. The cover **954** may be flat, or shaped to form a lens such as a convex lens shown by dotted line **960**. In another illustrative embodiment, the cover **954** is substantially non-transparent and the remainder of the elongated member or body **952** is transparent or semi-transparent.

It is contemplated that the cover **954** may be formed integrally with the remainder of the elongated member or body **952** (such as by, for example, extrusion, co-extrusion, molding, or any other suitable method). Alternatively, the cover **954** may be formed separately from the remainder of the elongated member or body **952**. When formed separately from the remainder of the elongated member or body **952**, the cover **954** may be later secured to the remainder of the elongated member or body **952** by, for example, a snapping mechanism, an adhesive, screws, or any other suitable securing method. In some embodiments, the cover **954** is secured to the remainder of the elongated member or body **952** after the elongated light source **958** is inserted into the cavity **956**. In the illustrative embodiment, the cavity **956** is parabolic in shape to help direct (by reflection) the light produced by the elongated light source **958** toward the cover **954**, but this is not required.

In some embodiments, the elongated member or body **952** may include a removable portion **962**, which may include the cavity **956**, the elongated light source **958** and the cover **954**. The removable portion **962** may then be selectively removed from the remainder of the elongated member or body **952**, as desired. This may be particularly useful when the remainder of the elongated member or body **952** is permanently secured to a substrate, as further described below.

The elongated member or body **952** may have one or more legs, such as legs **964a**, **964b**, **964c** and **964d**, which extend away from the remainder of the elongated member or body

**952**. In the embodiment shown, legs **964a**, **964b**, **964c** and **964d** may help secure the elongated member or body **952** to the substrate **966**.

As noted above, this illustrative embodiment may be particularly suitable for securing an elongated light source to a substrate **966**, and in particular, a substrate **966** that can initially be provided in a liquid or semi-liquid state, and then cured or hardened to a more solid state. For example, the substrate **966** may be poured in a liquid or semi-liquid state, and then the elongated member or body **952** may be inserted into the substrate **966** as shown. The liquid or semi-liquid substrate may flow around the legs **964a**, **964b**, **964c** and **964d** of the elongated member or body **952**. When the substrate is cured or hardened to a more solid state, the elongated member or body **952** becomes secured to the substrate **966**, and in some cases, permanently secured to the substrate **966**.

In some embodiments, the substrate **966** may be, for example, concrete, asphalt, plastic, fiberglass, foam, or any other material that can be initially provided in a liquid or semi-liquid state, and then cured or hardened to a more solid state. The substrate may be part of, for example, a roadway, an airport runway, a wall, a floor, a stair, a ceiling, a running track, a boat, a car, a truck, a retaining wall, a swimming pool, a guard rail, or any other suitable surface or object, as desired.

In some embodiments, the elongated member or body **952** may be formed from a relatively rigid material, such as Vinyl, PVC, rubber, plastic, aluminum, or any other suitable material. When so provided, the removable portion **962** may be formed from the same or a different material than the elongated member or body **952**.

For some applications, the elongated member or body **952** may be formed from a relatively flexible or elastic material. This may be useful when, for example, there is a difference in the coefficient of thermal expansion between the substrate **966** and the elongated member or body **952**. Again, the removable portion **962** may be formed from the same or a different material such as a more rigid material, depending on the application.

FIG. **49** is a cross-sectional side view of an illustrative lighting apparatus for use with a stair or other ledge. The illustrative lighting apparatus is generally shown at **1000**, and includes an elongated member or body that has a horizontally extending portion **1002** and a vertically extending portion **1004**. In some embodiments, either the horizontally extending portion **1002** or the vertically extending portion **1004** may be omitted. The illustrative elongated member includes a cover portion **1006**, which together form a cavity **1008** for receiving an elongated light source **1010**.

In the illustrative embodiment, the horizontally extending portion **1002** of the elongated member includes both a first material **1012** that is at least semi-transparent and a second material **1014** that is substantially non-transparent. The at least semi-transparent material **1012** is shown extending from the cavity **1008** that houses the elongated light source **1010** horizontally to one or more outer surfaces **1016a** and **1016b** of the body. The at least semi-transparent material **1012** thus at least partially defines the cavity **1008** and accepts light therefrom. The light is delivered down the at least semi-transparent material **1012** to illuminate the one or more outer surfaces **1016a** and **1016b**. In the illustrative embodiment, the outer surface **1018** between the one or more outer surfaces **1016a** and **1016b** is substantially non-transparent, but this is not required. It is contemplated that the one or more outer surfaces **1016a** and **1016b** may be flat or shaped to form a lens, depending on the application.

In addition, it is contemplated that the at least semi-transparent material **1012** may have a higher index of refraction than the substantially non-transparent material **1014** to promote greater total internal reflection of the light as it travels down the at least semi-transparent material **1012**, much like an optical fiber.

The vertically extending portion **1004** of the elongated member may also include both a first material **1012** that is at least semi-transparent and a second material **1014** that is substantially non-transparent. The at least semi-transparent material **1012** is shown extending from the cavity **1008** that houses the elongated light source **1010** vertically down to an outer surface **1020** of the body. The at least semi-transparent material **1012** thus receives light from the cavity **1008**, and delivers at least some of the light down to the outer surface **1020**.

In some embodiments, the elongated member may include a slit **1024** that extends from the cavity **1008** to an outer surface of the body. The slit **1024** may be moved to an open position, by for example applying an external outward force, which may help aid in the insertion of the elongated light source **1010** into the cavity **1008** through the slit **1024**.

In one illustrative embodiment, the at least semi-transparent material **1012** may be integrally formed with the substantially non-transparent material **1014**. For example, the at least semi-transparent material **1012** may be co-extruded with the substantially non-transparent material **1014**. Alternatively, the at least semi-transparent material **1012** may be separately formed from the substantially non-transparent material **1014**, and subsequently mechanically secured together, as desired.

The illustrative lighting apparatus **1000** may be mounted to a stair or other ledge as shown. The cavity **1008** is shown positioned adjacent the ledge **1022** of the stair or ledge. However, it is contemplated that the cavity **1008** may be positioned anywhere along the elongated member, as desired, including adjacent the downward extending surface **1030** of the stair and/or adjacent the substantially horizontally extending surface **1032** of the stair.

FIG. **50** is a schematic diagram of an illustrative appliance having an elongated light source positioned along the body of the appliance. In some applications, it may be desirable to include an elongated light source along the body of an appliance to increase the visual appeal of the appliance, and in some cases, provide low level lighting. Almost any appliance may benefit, including household or office devices operated by gas or electric current. Some illustrative appliances include radios, CD players, DVD players, televisions, refrigerators, stoves, toasters (see FIG. **53**), phones, etc.

In one illustrative embodiment of the present invention, the outer housing of an appliance is provided with an elongated cavity. The term cavity, as used throughout, may include an open cavity or a closed cavity. An open cavity is one that is open on one or more sides, and a closed cavity is one that is closed on all sides. The elongated cavity extends along at least a portion of the outer housing, and is adapted to receive an elongated light source, such as an electro-luminescent wire. The cavity is preferably at least partially defined by a material that is at least partially transparent, and which extends to an outer surface of the housing. In some embodiments, the housing may also include a substantially non-transparent material, which in some cases, may be at least partially reflective. The substantially non-transparent material may include a surface that is shaped to reflect light toward the outer surface of the housing.

FIG. 50 shows one such appliance fitted with an elongated light source. The appliance shown in FIG. 50 is a portable music producing device. The portable music producing device includes an outer housing 1050 that has an elongated cavity formed therein. An elongated light source, such as an electro-luminescent wire, is provided in the elongated cavity as shown at 1052a, 1052b and 1052c. Each elongated cavity is preferably at least partially defined by a material that is at least partially transparent, and which extends to an outer surface of the housing 1050 so that the light produced by the elongated light source is visible to the user of the appliance. The elongated light source may receive power from the power source of the appliance. An inverter may be required in some applications to produce the desired power signal to drive the elongated light source.

It is contemplated that the elongated light source may be switched on or off by one or more signals of the appliance. For example, a switch may be provided on the appliance for turning the elongated light source on and off. In another example, the elongated light source may be pulsed on and off by the changes in sound intensity produced by the radio, or may just blink at a predetermined rate. In yet another example, the elongated light source may be turned on when, for example, a toaster is toasting, and turned off when toasting is complete. These are just a few examples of controlling the elongated light source with one or more signals of an appliance.

FIG. 51 is a schematic diagram of an illustrative toy having an elongated light source positioned along the body of the toy. In some embodiments, it may be desirable to include an elongated light source along the body of a toy to increase the visual appeal of the toy, and in some cases, provide low level lighting. Almost any toy may benefit, including toy swords, toy vehicle, board games, stuffed animals, etc.

In one illustrative embodiment, the outer shell or housing of a toy is provided with an elongated cavity. The elongated cavity extends along at least a portion of the outer shell or housing, and is adapted to receive an elongated light source, such as an electro-luminescent wire. The cavity is preferably at least partially defined by a material that is at least partially transparent, and which extends to an outer surface of the outer shell or housing. In some embodiments, the shell or housing may also include a substantially non-transparent material, which in some cases, may be at least partially reflective. The substantially non-transparent material may include a surface that is shaped to reflect light toward the outer surface of the housing.

FIG. 51 is a schematic diagram of an illustrative toy sword having an elongated light source positioned along the body of the toy. The toy sword is generally shown at 1060 and includes an outer shell or housing 1062 that has an elongated cavity formed therein. An elongated light source, such as an electro-luminescent wire, is provided in the elongated cavity as shown at 1064. The elongated cavity is preferably at least partially defined by a material that is at least partially transparent, and which extends to an outer surface of the housing 1062 so that the light produced by the elongated light source is visible to the user of the toy. The elongated light source may receive power from the toy. An inverter may be required in some applications to produce the desired power signal to drive the elongated light source.

It is contemplated that the elongated light source may be switched on or off by one or more signals of the toy. For example, a switch may be provided on the toy for turning the elongated light source on and off. In another example, the elongated light source may be pulsed on and off by move-

ment of the toy, or may just blink at a predetermined rate. In yet another example, the elongated light source may be turned on when, for example, the toy is brought close to another similarly equipped toy. These are just a few examples of controlling the elongated light source with one or more signals of a toy.

In another illustrative embodiment, the toy may include an outer shell, and may have a power source within the outer shell. The outer shell may be a sturdy outer shell, or a more flexible outer shell such as is common for stuffed animals. In some embodiments, an inverter may be provided within the outer shell and connected to an elongated light source, such as an electro-luminescent wire. At least part of the elongated light source preferably extends outside of the outer shell. For example, and in the case of a stuffed toy dog, the elongated light source may extend out of the outer shell and around the neck of the dog to produce an illuminated collar. In this embodiment, a separate cavity need not be provided in the outer shell of the toy to accommodate the elongated light source.

FIG. 52 is a schematic diagram of a solar powered lighting apparatus. In this embodiment, an elongated light source such as an electro-luminescent wire may be powered by one or more solar cells. In the illustrative embodiment shown, one or more solar cells 1070 receive light from an external source such as the sun. The electrical power generated by the one or more solar cells 1070 is provided to a power storage block 1072, which may include one or more batteries or other power storage device(s). A controller and/or inverter 1074 block may then be coupled to the power storage block 1072. The controller and/or inverter block 1074 may include an inverter to convert the power received from the power storage block 1072 to an appropriate power signal for the elongated light source 1076, such as an electro-luminescent wire.

The controller and/or inverter block 1074 may also include a controller for selectively enabling when power is delivered from the power storage block 1072 to the elongated light source 1076. For example, the controller may include a timer to prevent power from being delivered to the elongated light source during certain parts of a day, such as during day time, while allowing power to be delivered to the elongated light source at other times of the day, such as during night time. In another example, the controller may be connected to a light detector 1078. The light detector 1078 may detect the ambient lighting conditions to determine when it is day time and night time. The controller may use the output of the detector 1078 to disable power from being delivered to the elongated light source during the day time, while enabling power to be delivered to the elongated light source during the night time.

FIG. 54 is an overlapping cross-sectional side view of a carrier and in insert of another illustrative lighting apparatus. The carrier is shown at 1200 and includes a back support 1204, an upper leg 1206 extending from the back support 1204 and a lower leg 1208 also extending from the back support 1204. In the illustrative embodiment, the upper leg 1206 and the lower leg 1208 extend in the leftward direction and turn in toward one another to form a slot 1210. The upper leg 1206, back support 1204 and the lower leg 1208 also define a cavity 1212.

In the illustrative embodiment, the back support includes a first insert stop 1214a and a second insert stop 1214b, both extending into the cavity 1212. In the illustrative embodiment, the first insert stop 1214a includes an angled or curved surface 1216a, and the second insert stop 1214b includes an

angled or curved surface **1216b**. The angled or curved surfaces **1216a** and **1216b** are further discussed below.

The carrier **1200** may be formed in any number of ways, including injection molding, extrusion or any other suitable process. In one illustrative embodiment, the carrier **1200** is extruded using a rigid, semi-rigid and/or flexible PVC, and then cut to length. When more than one material is used, a co-extrusion or other suitable process may be used. More than one material may be useful to, for example, provide additional control over the flexibility of the various regions of the carrier **1200**, provide different optical characteristics, provide different colors, and/or provide any other characteristics or properties to the carrier **1200**, as desired.

The insert **1202** is shown overlapping the carrier **1200** in FIG. **54** to help show the shape of the insert **1202** relative to the carrier **1200** prior to inserting the insert **1202** into the cavity **1212** of the carrier **1200** via the slot **1210**. The illustrative insert **1202** includes a main body **1220**, an upper support leg **1222a** and a lower support leg **1222b**. In the illustrative embodiment, the upper support leg **1222a** and the lower support leg **1222b** are shaped to conform to the inner surface **1224a** of the upper leg **1206** and the lower leg **1208** of the carrier **1200** when the insert **1202** is inserted into the cavity **1212**, as better shown in FIG. **55**. However, prior to insertion of the insert **1202**, the upper support leg **1222a** and the lower support leg **1222b** of the insert **1202** are shown to overlap and/or interfere with the upper leg **1206** and the lower leg **1208** of the carrier **1200**. As such, when the insert **1202** is inserted into the cavity **1212** via the slot **1210**, the upper support leg **1222a** and the lower support leg **1222b** deform and provide an interference fit between the insert **1202** and the carrier **1200**.

In the illustrative embodiment, the main body **1220** of the insert **1202** is made slightly wider than the slot **1210** of the carrier **1200**. This may cause the main body **1220** to at least slightly deform when the insert is inserted into the cavity **1212** of the carrier **1200**. This may provide a further interference fit between the insert **1202** and the carrier **1200**, and may help the insert **1202** remain in place during use.

In the illustrative embodiment, the end **1226a** of the upper leg **1206** of the carrier **1200**, and the end **1226b** of the lower leg **1208** of the carrier **1200** are not parallel to one another. Rather, they are angled away from each other. The main body **1220** of the insert **1202** may have an outer shape that follows the shape of the end **1226a** of the upper leg **1206** and the end **1226b** of the lower leg **1208** of the carrier **1200**, as shown. This may help transfer any force that is applied to the insert to the upper leg **1206** and the lower leg **1208** of the carrier **1200**, and ultimately to a mounting surface (not shown). It should be recognized that this is only an illustrative embodiment, and that other configurations may be used. For example, in one alternative embodiment, the end **1226a** of the upper leg **1206** and the end **1226b** of the lower leg **1208** of the carrier **1200** may be rounded or assume some other shape, and the main body **1220** of the insert **1202** may follow or match the rounded or other shape, as desired.

In the illustrative embodiment, the main body **1220** includes a lumen **1230** that extends along the length of the main body **1220**. The lumen **1230** may assume any shape or size, as desired. In one illustrative embodiment, the lumen **1230** is appropriately sized to accept an elongated light source (see FIG. **55**). In some embodiments, the lumen may have a maximum width of less than 30 mm, less than 20 mm, less than 10 mm, or less than 5 mm across. However, other dimensions may be used.

In some cases, it may be desirable to oversize the lumen **1230** relative to the dimensions of the light source so that

there is sufficient room to accommodate changes in the dimensions of the lumen **1230** that occur when the carrier **1200** and insert **1202** are bent around curves or corners along a mounting surface. In some cases, the lumen **1230** may be oversized more in one dimension than another, particularly when the carrier **1200** and insert **1202** are expected to be bent more in one direction than another. For example, in the illustrative embodiment, the lumen **1230** is oversized more in the horizontal direction than in the vertical direction because it is expected that the carrier **1200** and insert **1202** will be bent more in the left and/or right direction than in the up and/or down direction.

In some embodiments, the lumen **1230** may be oversized in at least one dimension by 5%, 10%, 20%, 30%, 40%, 50%, 100%, 200%, 300%, 500%, 1000% or more relative to the corresponding dimension of the light source, or between any of these ranges. In other embodiments, the lumen **1230** may be oversized in at least one dimension by 5%, 10%, 20%, 30%, 40%, 50%, 100%, 200%, 300%, 500%, 1000% or more relative to another dimension of the lumen **1230**, or between any of these ranges.

In one illustrative embodiment, the lumen **1230** may be defined on one or more sides by a transparent or semi-transparent material, such as transparent or semi-transparent material **1232**, and on the other sides by a non-transparent, or a transparent or semi-transparent material, as desired. In one illustrative embodiment, the transparent or semi-transparent material shown at **1232** allows at least some of the light that is produced by a light source situated in the lumen **1230** to escape from the lumen **1230**. In some embodiments, one or more of the other sides of the lumen **1230** may be at least partially reflective, while in others, more than one of the sides are transparent or semi-transparent, as desired.

In some embodiments, one or more of the sides of the lumen **1230** may include a glow-in-the-dark material, if desired. In some cases, all of the sides of the lumen **1230** may include a glow-in-the-dark material, and/or the entire insert **1202** may include a glow-in-the-dark material. In either case, a light source that is situated in the lumen **1230** may charge the glow-in-the-dark material, which may then emit light during and even after the light source goes inactive.

In an illustrative embodiment, the lumen **1230** may be at least partially defined by two walls **1234a** and **1234b** that extend toward the back support **1204** of the carrier **1200**. In some embodiments, a slit **1236** extends through the back wall of the lumen to separate the two walls **1234a** and **1234b**, but this is not required in all embodiments. In some embodiments, the insert **1202** is made from a material that is sufficiently flexible so that the slit **1236** may be opened sufficiently to insert a light source (not shown) into the lumen **1230** before the insert **1202** is inserted into the cavity **1212** of the carrier **1200**. Once the insert **1202** is inserted into the cavity **1212** of the carrier **1200**, the interference fit between the upper support leg **1222a** and the lower support leg **1222b** of the insert **1202**, and the upper leg **1206** and the lower leg **1208** of the carrier **1200**, may help provide a closing force to the slit **1236**.

In the illustrative embodiment, the surface of the slit **1236** assumes a "V" shape, which may help keep the ends of the two walls **1234a** and **1234b** aligned. However, it is contemplated that the surface of the slit **1236** may have any desired shape including a flat shape, a grooved shape, a rounded shape, or any other shape, as desired.

In some embodiments, back terminal ends **1240a** and **1240b** of the two walls **1234a** and **1234b**, respectively, may be aligned with the angled or curved surfaces **1216a** and

**1216b** of the first and second insert stops **1214a** and **1214b**, respectively, of the carrier **1200**. In the illustrative embodiment, the first and second insert stops **1214a** and **1214b** may help limit the backward movement of the insert **1202** toward the back support **1204** of the carrier **1200**. This may be useful when, for example, a significant force is applied to the insert **1202**, such as when a boat bumps against a dock with sufficient force. The angled or curved surfaces **1216a** and **1216b** of the first and second insert stops **1214a** and **1214b** may also help keep the insert **1202** vertically aligned with the carrier **1200**, and/or help provide a closing force to the slit **1236**, when the back terminal ends **1240a** and **1240b** of the two walls **1234a** and **1234b**, respectively, engage the angled or curved surfaces **1216a** and **1216b**.

The insert **1202** may be made in any number of ways, including injection molding, extrusion or any other suitable process. In one illustrative embodiment, the insert **1202** is extruded using a rigid, a semi-rigid and/or a flexible PVC, and then cut to length. However, other materials may also be used. When the insert **1202** is made from more than one material, the various materials may be co-extruded, or any other suitable process may be used. For example, it is contemplated that more than one material may be used, for example, to help provide additional control over the flexibility of the various regions of the insert **1202**. Alternatively, or in addition, it is contemplated that more than one material may be used to make part of the insert transparent or semi-transparent and another part non-transparent, or different colors, as desired. For example, in one embodiment, the lumen **1230** is defined on one side by a transparent or semi-transparent material **1232**, and on the other sides by a non-transparent material. The transparent or semi-transparent material **1232** may be co-extruded with the non-transparent material, if desired.

Using more flexible material(s) for the insert **1230**, such as semi-rigid or flexible PVC, may allow the insert **1202** to be more easily coiled during shipment. However, a more rigid material may be more durable. It is contemplated that the insert **1202** may be made from any suitable material or material combination, using any suitable manufacturing process, as desired.

FIG. **55** is a cross-sectional side view of the illustrative lighting apparatus of FIG. **54** with the insert installed in the cavity **1212** of the carrier **1200**. As can be seen, and in the illustrative embodiment, the upper support leg **1222a** and the lower support leg **1222b** of the insert **1202** are shaped to conform to the inner surface **1224a** of the upper leg **1206** and the lower leg **1208** of the carrier **1200** when the insert **1202** is inserted to the cavity **1212**. As detailed above with respect to FIG. **54**, prior to insertion of the insert **1202**, the upper support leg **1222a** and the lower support leg **1222b** of the insert **1202** may be made to overlap and/or interfere with the upper leg **1206** and the lower leg **1208** of the carrier **1200**. As such, when the insert **1202** is inserted into the cavity **1212** via the slot **1210**, the upper support leg **1222a** and the lower support leg **1222b** of the insert **1202** deform to provide an interference fit between the insert **1202** and the carrier **1200**.

FIG. **55** also shows a light source **1250** extending through the lumen **1230** of the insert **1202**. In one embodiment, region **1232** may be formed from a transparent or semi-transparent material, and the other sides of the lumen **1230** may be formed from a non-transparent material. This non-transparent material may be at least partially reflective, in at least some embodiments. The transparent or semi-transparent

material shown at **1232** may allow at least some of the light emitted by the light source to escape from the lumen **1230**.

FIG. **56** is a front view of the illustrative lighting apparatus of FIG. **55**, wherein the insert is shorter than the carrier for illustrative purposes. Typically, the insert **1202** and carrier **1200** are made approximately the same length, but to reveal the hole **1254** in the carrier **1200**, the insert **1202** is shown having a shorter length. It is contemplated that the carrier **1200** may include a series of holes **1254** at spaced locations along the length of the carrier. In some embodiments, screws may be inserted through the holes **1254** to secure the carrier to a mounting surface (not shown) such as the side of a boat or dock. In some cases, the holes **1254** are spaced between 4 and 16 inches apart, but other spacings may be used depending on the application. FIG. **57** is a perspective view of the illustrative lighting apparatus of FIG. **56**.

FIG. **58** is an overlapping cross-sectional side view of another illustrative carrier and insert in accordance with the present invention. The carrier is shown at **1300**, and is similar to the carrier **1200** of FIG. **54**. The carrier **1300** of FIG. **58** includes a back support **1304**, an upper leg **1306** extending from the back support **1304** and a lower leg **1308** also extending from the back support **1304**. The upper leg **1306**, back support **1304** and the lower leg **1308** define a cavity **1312**.

In the illustrative embodiment, and like the illustrative embodiment shown in FIG. **54**, the back support **1304** includes a first insert stop **1314a** and a second insert stop **1314b**, both extending into the cavity **1312**. However, in the illustrative embodiment of FIG. **58**, the first insert stop **1314a** and the second insert stop **1314b** do not protrude as far into the cavity **1312** as that shown in FIG. **54**. This provides more space between the back terminal ends **1240a** and **1240b** of the insert **1202** and the angled or curved surfaces **1316a** and **1316b** of the first and second insert stops **1314a** and **1314b** of the carrier **1300**. This increased space may allow the carrier **1300** and insert **1202** to be bent around sharper corners along their length in the rightward direction without having the back terminal ends **1240a** and **1240b** of the insert **1202** coming into contact with the angled or curved surfaces **1316a** and **1316b** of the first and second insert stops **1314a** and **1314b** of the carrier **1300**.

In some cases, if the carrier **1300** is bent in the rightward direction in FIG. **58**, the upper leg **1306** and lower leg **1308** of the carrier **1300** may pull back toward the back support **1304**, at least to some degree. This may then move the insert **1202** back toward the back support **1304**. If the carrier **1300** is bent sufficiently far, the back terminal ends **1240a** and **1240b** of the insert **1202** may engage the angled or curved surfaces **1316a** and **1316b** of the first and second insert stops **1314a** and **1314b** of the carrier **1300**, and in some cases, prevent the insert **1202** from seating correctly in the carrier **1300**. As such, it is contemplated that the space between the back terminal ends **1240a** and **1240b** of the insert **1202** and the angled or curved surfaces **1316a** and **1316b** of the first and second insert stops **1314a** and **1314b** of the carrier **1300** may be tailored to accommodate the expected bend radius of the carrier **1300**.

FIG. **59** is a cross-sectional side view of the illustrative lighting apparatus of FIG. **58** with the insert **1202** installed within the carrier **1300**. As can be seen, the space between the back terminal ends **1240a** and **1240b** of the insert **1202** and the angled or curved surfaces **1316a** and **1316b** of the first and second insert stops **1314a** and **1314b** of the carrier **1300** is larger than that shown in FIG. **55**.

FIG. 60 is a front view of the illustrative lighting apparatus of FIG. 59, wherein the insert 1202 is shown shorter than the carrier 1300 for illustrative purposes. Typically, the insert 1202 and the carrier 1300 are made approximately the same length, but to reveal the hole 1354 in the carrier 1300, the insert 1202 is shown having a shorter length. It is contemplated that the carrier 1300 may include a series of holes 1354 at spaced locations along the length of the carrier 1300. In some embodiments, screws may be inserted through the holes 1354 to secure the carrier 1300 to a mounting surface (not shown) such as the side of a boat or dock. In some cases, the holes 1354 are spaced between 4 and 16 inches apart, but other spacings may be used, depending on the application. FIG. 61 is a perspective view of the illustrative lighting apparatus of FIG. 60.

FIG. 62 is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention. This illustrative embodiment includes a carrier 1370 and an insert 1372. The carrier 1370 includes a cavity 1382 for receiving the insert 1372. An upper leg 1384 and a lower leg 1386 of the carrier define a slot 1388 into the cavity 1382. The width of the slot 1388 is shown less than the width of the cavity 1382. An illustrative insert 1372 is shown in FIG. 63. The illustrative insert 1372 may be tubular in shape, or some other shape, and may have a lumen extending therethrough.

In the illustrative embodiment, a light source 1376 is provided in the lumen 1374 of the insert 1372, and the insert 1372 is provided in the cavity 1382 of the carrier 1370 via the slot 1388, as best shown in FIG. 62. It is contemplated that the light source may be provided in the lumen 1374 of the insert 1372 either before or after the insert 1372 is provided in the cavity 1382 of the carrier 1370 via the slot 1388. As can be seen, and in some embodiments, the insert 1372 may have to be deformed to fit through the slot 1388 of the carrier 1370. Some of the insert 1372, however, may extend out of the cavity 1382 and through the slot 1388 as shown. This may allow the insert 1372, which may be made from a softer or more flexible material than the carrier 1370, to provide a softer bumper function.

At least part of the insert 1372 may be made from a transparent or semi-transparent material so that at least some of the light 1390 emitted by the light source 1376 may escape as shown. In some embodiments, the entire insert 1372 may be made from a transparent or semi-transparent material. In other cases, only part(s) of the insert 1372 may be made from a transparent or semi-transparent material. When only part(s) of the insert 1372 is/are made from a transparent or semi-transparent material, that part(s) may be in registration with the slot 1388 so that at least some of the light 1390 emitted by the light source 1376 may escape. In some cases, at least part of the carrier 1370 and/or insert 1372 may include a glow-in-the-dark material, if desired.

FIG. 64 is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention. This illustrative embodiment includes a carrier 1400 and an insert 1402. The carrier 1400 includes a main cavity 1404 for receiving the insert 1402, where an upper leg 1406 and a lower leg 1408 of the carrier 1400 define a slot 1410 into the main cavity 1404. The width of the slot 1410 is shown less than the width of the main cavity 1404. An illustrative insert 1402 is shown in FIG. 63.

In some embodiments, the insert 1402 may have to be deformed to fit through the slot 1410 of the carrier 1400. Some of the insert 1402, however, may extend out of the main cavity 1404 and through the slot 1410 as shown. This

may allow the insert 1402, which may be made from a softer or more flexible material than the carrier 1402, to provide a softer bumper function.

In the illustrative embodiment, the carrier 1400 may also include a light source cavity 1412, which may extend from the main cavity 1404. In the illustrative embodiment, the carrier 1400 includes inward extending teeth or legs that narrow the channel between the light source cavity 1412 and the main cavity 1404. In one illustrative embodiment, the light source 1414 is an elongated light source and is inserted through the slot 1410 and into the light source cavity 1412. Then, an elongated plug 1422 is inserted between the light source cavity 1412 and the main cavity 1404, as best shown in FIG. 65. The teeth or legs of the carrier 1400 that narrow the channel between the light source cavity 1412 and the main cavity 1404 may help retain the plug in the inserted position. While teeth or legs are shown in the illustrative embodiment, they are not required in all embodiments.

In some embodiments, the light source cavity 1412 may be oversized at least in one dimension by 5%, 10%, 20%, 30%, 40%, 50%, 100%, 200%, 300%, 500%, 1000% or more relative to the corresponding dimensions of the light source 1414, or between any of these ranges. In other embodiments, the light source cavity 1412 may be oversized in at least one dimension by 5%, 10%, 20%, 30%, 40%, 50%, 100%, 200%, 300%, 500%, 1000% or more relative to another dimension of the light source cavity 1412, or between any of these ranges. In some cases, this may help accommodate changes in the dimensions of the light source cavity 1412 when the carrier 1400 is bent when it is installed on a mounting surface (not shown).

The carrier 1400 may also include a transparent or semi-transparent region 1416 that extends from the light source cavity 1412 to an outer surface 1418 of the carrier 1400 to allow at least some of the light 1420 emitted by the light source 1414 to escape. In some cases, the entire carrier 1400 may be formed from a transparent or semi-transparent material, if desired.

In some cases, the plug 1422 may be made from a non-transparent material. However, in other cases, the plug 1422 may include a transparent or semi-transparent material, which may allow at least some of the light emitted by the light source 1414 to enter the main cavity 1404. In these cases, at least part of the insert 1402 may also include a transparent or semi-transparent material to allow at least some of the light that enters the main cavity 1404 to escape through the slot 1410.

FIG. 66 is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention. This illustrative embodiment includes a carrier 1450 and an insert 1452. The carrier 1450 includes a main cavity 1454 for receiving the insert 1452, where an upper leg 1456 and a lower leg 1458 of the carrier 1450 define a slot 1460 into the main cavity 1454. The width of the slot 1460 is shown less than the width of the main cavity 1454.

In the illustrative embodiment, the insert 1452 includes an arched center region 1462, with an upper leg 1464 extending in an upward direction from the arched center region 1462 and a lower leg 1466 extending in a downward direction from the arched center region 1462. The upper leg 1464 includes a tooth 1468 for engaging a tooth 1472 on the upper leg 1456 of the carrier 1450. Likewise, the lower leg 1466 includes a tooth 1470 for engaging a tooth 1474 on the lower leg 1458 of the carrier 1450. The insert 1452 also includes an upper back side tooth 1480 and a lower back side tooth 1482 to engage the sides of a thickened portion 1484 of the back support of the carrier 1450, as shown.

In the illustrative embodiment, the arched center region **1462** includes a lumen **1486** for receiving a light source **1488**. In some embodiments, a slit **1490** may provide access to the lumen **1486**. The arched center region **1462** may include a transparent or semi-transparent region **1494**, indicated by dashed lines in FIG. **66**, to allow at least some of the light **1496** emitted by the light source **1488** to escape from the lumen **1486**, as shown. In some embodiments, the entire insert **1452** may be formed from a transparent or semi-transparent material, if desired.

In some embodiments, the lumen **1486** may be oversized at least in one dimension by 5%, 10%, 20%, 30%, 40%, 50%, 100%, 200%, 300%, 500%, 1000% or more relative to the corresponding dimensions of the light source **1488**, or between any of these ranges. In other embodiments, the lumen **1486** may be oversized in at least one dimension by 5%, 10%, 20%, 30%, 40%, 50%, 100%, 200%, 300%, 500%, 1000% or more relative to another dimension of the lumen **1486**, or between any of these ranges. In some cases, this may help accommodate changes in the dimensions of the lumen **1486** when the carrier **1450** and insert **1452** are bent when installed on a mounting surface (not shown).

In some embodiments, the carrier **1450** may also include one or more insert stops, such as insert stops **1500a** and **1500b**. Insert stops **1500a** and **1500b** may limit the amount that the arched center region **1462** may move toward the carrier **1450** when a sufficiently large force is applied to the insert **1452**. The illustrative insert stops **1500a** and **1500b** extend from the back support of the carrier **1450**, and are spaced on either side of the light source **1488**. The height of the insert stops **1500a** and **1500b** may be such that the light source **1488** may move between the insert stops **1500a** and **1500b** when a sufficient force is applied to the insert **1452**, but the arched center region **1462** of the insert **1452** is prevented from moving too close to the back support of the carrier **1450** to cause damage the light source **1488**.

FIG. **67** is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention. This illustrative embodiment includes a carrier **1510** and an insert **1502**. The carrier **1510** includes a main cavity **1514** for receiving the insert **1512**. An upper leg **1516** and a lower leg **1518** of the carrier **1510** define a slot **1520** into the main cavity **1514**. The width of the slot **1520** is shown less than the width of the main cavity **1514**. The carrier **1510** further includes a back support **1522** with a thickened region **1524**. The thickened region **1524** extends into the main cavity **1514**.

In this embodiment, the insert **1512** includes a main body region **1526**, and an upper leg **1528** that extends in an upward direction from the main body region **1526** and a lower leg **1530** that extends in a downward direction from the main body region **1526**. The upper leg **1528** extends into an upper portion of the main cavity **1514**, and the lower leg **1530** extends into a lower portion of the main cavity **1514**. In the illustrative embodiment, the upper leg **1528** and the lower leg **1530** also engage the sides of the thickened portion **1524** of the back support **1522** of the carrier **1510**, as shown.

In the illustrative embodiment, the main body region **1526** includes a lumen **1534** for receiving a light source **1536**. In some embodiments, a slit **1538** may provide access to the lumen **1534**. The main body region **1526** may include a transparent or semi-transparent region **1540**, indicated by dashed lines in FIG. **67**, to allow at least some of the light **1542** emitted by light source **1536** to escape from the lumen **1534**, as shown. In some embodiments, the entire insert **1512** may be formed from a transparent or semi-transparent material, if desired.

In some embodiments, the lumen **1534** may be oversized at least in one dimension by 5%, 10%, 20%, 30%, 40%, 50%, 100%, 200%, 300%, 500%, 1000% or more relative to the corresponding dimensions of the light source **1536**, or between any of these ranges. In other embodiments, the lumen **1534** may be oversized in at least one dimension by 5%, 10%, 20%, 30%, 40%, 50%, 100%, 200%, 300%, 500%, 1000% or more relative to another dimension of the lumen **1534**, or between any of these ranges. In some cases, this may help accommodate changes in the dimensions of the lumen **1534** when the carrier **1510** and insert **1512** are bent when installed on a mounting surface (not shown).

FIG. **68** is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention. The illustrative embodiment of FIG. **68** is similar to that shown in FIG. **67**, but the carrier **1600** includes a cavity **1602** for receiving a light source **1604**. To allow at least some of the light to escape, the insert **1610** may include a transparent or semi-transparent region **1612**, indicated by dashed lines in FIG. **68**. In some embodiments, the entire insert **1610** may be formed from a transparent or semi-transparent material, if desired. In some embodiments, a transparent or semi-transparent plug (not shown) may be installed between the main cavity **1618** of the carrier **1600** and the light source receiving cavity **1602** in a manner similar to that shown in FIG. **65**.

In some cases, the cavity **1602** may be oversized at least in one dimension by 5%, 10%, 20%, 30%, 40%, 50%, 100%, 200%, 300%, 500%, 1000% or more relative to the corresponding dimensions of the light source **1604**, or between any of these ranges. In other embodiments, the cavity **1602** may be oversized in at least one dimension by 5%, 10%, 20%, 30%, 40%, 50%, 100%, 200%, 300%, 500%, 1000% or more relative to another dimension of the cavity **1602**, or between any of these ranges. In some cases, this may help accommodate changes in the dimensions of the cavity **1602** when the carrier **1600** is bent when installed on a mounting surface (not shown).

FIG. **69** is a cross-sectional side view of yet another illustrative lighting apparatus in accordance with the present invention. This illustrative embodiment includes a bumper **1650** that includes a back side **1652** that faces a mounting surface (not shown). A light source cavity **1654** extends through the back side **1652** of the bumper **1650**, and in the illustrative embodiment, includes inward extending teeth or legs that narrow the channel between the exterior of the bumper **1650** and the light source cavity **1412**. While inward extending teeth or legs are shown in FIG. **69**, they are not required.

In one illustrative embodiment, a light source **1660** is inserted from the back side **1652** of the bumper **1650** and into the light source cavity **1654**. Then, an elongated plug **1658** may be inserted between the light source cavity **1654** and the exterior of the bumper, as best shown in FIG. **70**. In some cases, the light source **1660** is an elongated light source and the plug is an elongated plug. The teeth or legs of the bumper **1650** that narrow the channel between the light source cavity **1654** and the exterior of the bumper **1650** may help retain the plug in the installed position. In some embodiments, the plug **1658** forms a water tight seal to help prevent water or other moisture from entering the light source cavity **1654**.

In some embodiments, the light source cavity **1654** may be oversized at least in one dimension by 5%, 10%, 20%, 30%, 40%, 50%, 100%, 200%, 300%, 500%, 1000% or more relative to the corresponding dimensions of the light source **1660**, or between any of these ranges. In other

embodiments, the light source cavity **1654** may be oversized in at least one dimension by 5%, 10%, 20%, 30%, 40%, 50%, 100%, 200%, 300%, 500%, 1000% or more relative to another dimension of the light source cavity **1654**, or between any of these ranges. In some cases, this may help accommodate changes in the dimensions of the light source cavity **1654** when the bumper **1650** is bent when installed on a mounting surface (not shown).

The bumper **1650** may include a transparent or semi-transparent region **1664**, indicated by dashed lines, that extends from the light source cavity **1654** to an outer surface **1662** of the bumper **1650**. The transparent or semi-transparent region **1664** may allow at least some of the light emitted by the light source **1664** to escape. In some embodiments, the entire bumper **1650** may be made from a transparent or semi-transparent material, if desired. Alternatively, or in addition, it is contemplated that at least part of the bumper **1650** may include a glow-in-the-dark material.

FIG. **71** is a cross-sectional side view of yet another illustrative lighting apparatus in accordance with the present invention. This illustrative embodiment includes a bumper **1680** that includes a front surface **1682** that faces away from a mounting surface (not shown). A light source cavity **1684** extends through the front side **1682** of the bumper **1680**, and in the illustrative embodiment, includes inward extending teeth or legs that narrow the channel between the exterior of the bumper **1680** and the light source cavity **1684**. While inward extending teeth or legs are shown in FIG. **71**, they are not required.

In one illustrative embodiment, a light source **1686** is inserted from the front side **1682** of the bumper **1680** and into the light source cavity **1684**. Then, an elongated plug **1688** may be inserted between the light source cavity **1684** and the exterior of the bumper **1680**, as best shown in FIG. **72**. In some cases, the light source **1686** is an elongated light source and the plug **1688** is an elongated plug. The teeth or legs of the bumper **1680** that narrow the channel between the light source cavity **1684** and the exterior of the bumper **1680** may help retain the plug in the installed position. In some embodiments, the plug **1688** forms a water tight seal to help prevent water or other moisture from entering the light source cavity **1684**.

In some embodiments, the light source cavity **1684** may be oversized at least in one dimension by 5%, 10%, 20%, 30%, 40%, 50%, 100%, 200%, 300%, 500%, 1000% or more relative to the corresponding dimensions of the light source **1686**, or between any of these ranges. In other embodiments, the light source cavity **1684** may be oversized in at least one dimension by 5%, 10%, 20%, 30%, 40%, 50%, 100%, 200%, 300%, 500%, 1000% or more relative to another dimension of the light source cavity **1684**, or between any of these ranges. In some cases, this may help accommodate changes in the dimensions of the light source cavity **1684** when the bumper **1680** is bent when installed on a mounting surface (not shown).

In some cases, the plug **1688** may be transparent or semi-transparent to allow at least some of the light emitted by the light source **1686** to escape. Alternatively, or in addition, the bumper **1680** may include a transparent or semi-transparent region **1664** that extends from the light source cavity **1684** to an outer surface **1682** of the bumper **1680**. When so provided, the plug **1688** may or may not be transparent or semi-transparent, as desired. The transparent or semi-transparent region in the bumper **1680** may allow at least some of the light emitted by the light source **1686** to escape. In some embodiments, the entire bumper **1680** may be made from a transparent or semi-transparent material, if

desired. Alternatively, or in addition, it is contemplated that at least part of the bumper **1680** may include a glow-in-the-dark material. FIG. **72** is a cross-sectional side view of the illustrative lighting apparatus of FIG. **71** with the plug **1688** inserted into the opening.

FIG. **73** is a cross-sectional side view of yet another illustrative lighting apparatus in accordance with the present invention. This illustrative embodiment includes a bumper **1700** that has a front surface **1702** that faces away from a mounting surface (not shown). A light source **1704** is embedded in the bumper **1700**, as shown. As noted above, the "light source" may be any type of light source including an active light source, or a passive light source such as a glow-in-the-dark light source. The illustrative embodiment of FIG. **73** may be fabricated by extruding the bumper material over the light source.

The bumper **1700** may include a transparent or semi-transparent region **1706**, indicated by dashed lines, that extends from the light source **1704** to the front surface **1702** of the bumper **1700**. The transparent or semi-transparent region **1706** may allow at least some of the light emitted by the light source **1704** to escape. In some embodiments, the entire bumper **1700** may be made from a transparent or semi-transparent material, if desired. Alternatively, or in addition, it is contemplated that at least part of the bumper **1700** may include a glow-in-the-dark material.

FIG. **74** is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention. While not limited to such uses, the illustrative embodiments shown in FIGS. **74-78** may be particularly suitable for use on sides of docks, walls or other similar mounting surfaces. The illustrative embodiment shown in FIG. **74** includes a back support **1710** and an arched bumper member **1712**. The arched bumper member **1712** joins the back support **1710** as shown, and the back support member **1712** has an upper tab **1714** and a lower tab **1716** that extend above and below the arched bumper member **1712**, respectively. The upper tab **1714** and the lower tab **1716** may be used to secure the illustrative lighting apparatus to the mounting substrate, such as by providing screws or nails through the tabs, or by providing an adhesive along the back surface **1718** of the back support **1710**.

The back support **1710** may also have a thickened region **1720**. The thickened region **1720** may have a lumen **1722** extending therethrough for receiving a light source **1724** as shown. The lumen **1722** may be oversized relative to the light source **1724** so that the light source **1724** may be inserted into the lumen **1722** from one end, if desired. In some embodiments, a slit (not shown) may be provided from, for example, the back surface **1718** of the back support **1710** into the lumen **1722**. The slit may help facilitate the insertion and/or removal of the light source **1724** into/from the lumen **1722**.

In the illustrative embodiment, at least a portion of the thickened region **1720** may include a transparent or semi-transparent region **1730**, indicated by dashed lines, that extends from the lumen **1722** to a front surface of the thickened region **1720**. The transparent or semi-transparent region **1730** may allow at least some of the light emitted by the light source **1724** to escape. In some embodiments, the entire thickened region **1720**, as well as other regions, may be made from a transparent or semi-transparent material, if desired.

In some embodiments, the arched bumper member **1712** is made from a transparent or semi-transparent material, which transmits at least some of the light emitted by the light source **1724** to escape. In other embodiments, parts of the



arched bumper member **1712** are made from a non-transparent material, and other parts such as region **1732** indicated by dashed lines is made from a transparent or semi-transparent material. Alternatively, or in addition, it is contemplated that at least part of the arched bumper member **1712**, back support **1710** and/or thickened region **1720** may include a glow-in-the-dark material.

It is contemplated that the illumination apparatus of FIG. **74** may be made in any number of ways, including injection molding, extrusion or any other suitable process. In one illustrative embodiment, the arched bumper member **1712**, back support **1710** and/or thickened region **1720** are extruded using a rigid, a semi-rigid and/or a flexible PVC, and then cut to length. However, other materials and processes may also be used. When more than one material is used, the various materials may be co-extruded, or may be fabricated using any other suitable process, as desired.

FIG. **75** is a cross-sectional side view of yet another illustrative lighting apparatus in accordance with the present invention. This embodiment is similar to the embodiment shown in FIG. **74**, but the light receiving lumen **1748** is provided in or along the arched bumper member **1750**—rather than in a thickened region of the back support **1752** as shown in FIG. **74**. In the illustrative embodiment, at least a portion of the arched bumper member **1750** may include a transparent or semi-transparent region **1754**, indicated by dashed lines, that extends from the light receiving lumen **1748** to a front surface of the arched bumper member **1750**. The transparent or semi-transparent region **1754** may allow at least some of the light emitted by the light source **1756** to escape. In some embodiments, the entire arched bumper member **1750**, as well as other parts of the lighting apparatus, may be made from a transparent or semi-transparent material, if desired.

FIG. **76** is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention. This illustrative embodiment is similar to that shown in FIG. **75**, but the back support does not extend between an upper tab **1760** and a lower tab **1762**.

FIG. **77** is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention. This illustrative embodiment is similar to that shown in FIG. **75**, but the upper tab **1780** extends at an angle (e.g. perpendicular) relative to the back support **1782**. This embodiment may allow the upper tab **1780** to be mounted to a horizontal surface and the lower tab **1784** to a vertical surface. This embodiment may help provide additional protection to the top or bottom corner of a mounting surface such as a dock, if desired.

FIG. **78** is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention. This illustrative embodiment includes a back support **1800**, a front bumper member **1802**, a rounded top member **1804** and a bottom support **1806**. Two intermediate supports **1810a** and **1810b** are also provided in the illustrative embodiment between the back support **1800** and the front bumper member **1802**, as shown.

A lower tab **1812** is shown extending from the back support **1800** down past the bottom support **1806**. An upper tab **1814** is shown extending from the back support **1800** in a leftward direction. The upper tab **1814** joins the back support **1800** below the rounded top member **1804**. This embodiment may allow the upper tab **1814** to be mounted to a horizontal surface while the lower tab **1812** may be secured to a vertical surface. Thus, like the illustrative embodiment shown in FIG. **77**, this embodiment may help

provide additional protection to the top or bottom corner of a mounting surface such as a dock, if desired.

In the illustrative embodiment, the rounded top member **1804** and the upper intermediate support **1810a** form a light receiving lumen **1818** for receiving a light source **1820**. At least part of the rounded top member **1804** may be formed from a transparent or semi-transparent material, as indicated by dashed lines. This may allow at least some of the light emitted by the light source **1820** to escape. Alternatively, or in addition, a light source may be provided between the two intermediate supports **1810a** and **1810b**, or between the lower intermediate support **1810b** and the bottom support **1806**, if desired. In some cases, light sources may be provided at more than one of these locations, if desired.

It is contemplated that the illumination apparatus of FIG. **78** may be made in any number of ways, including injection molding, extrusion or any other suitable process. In one illustrative embodiment, the back support **1800**, front bumper member **1802**, rounded top member **1804**, bottom support **1806**, intermediate supports **1810a** and **1810b**, lower tab **1812** and upper tab **1814** are extruded as a single piece using a rigid, a semi-rigid and/or a flexible PVC, and then cut to length. However, other materials and processes may also be used. When more than one material is used, the various materials may be co-extruded, or formed using any other suitable process, as desired.

The light sources shown in the above embodiments may be active light sources that require electrical power to operate (e.g. electroluminescent, incandescent, LED or other active light sources) and/or passive light sources that do not require electric power (e.g. glow-in-the-dark light sources).

FIG. **79** is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention. The illustrative embodiments of FIGS. **79–82** explicitly show lighting apparatus assemblies that have a passive light source, such as a glow-in-the-dark material. The illustrative embodiment of FIG. **79** includes a carrier **1820** and an insert **1822**. The carrier **1820** includes a back support **1824**, an upper leg **1826** extending from the back support **1824** and a lower leg **1828** also extending from the back support **1824**. In the illustrative embodiment, the upper leg **1826** and the lower leg **1828** extend in the leftward direction and turn in toward one another to form a slot **1830**. The upper leg **1826**, back support **1824** and the lower leg **1828** also define a cavity **1832**.

The illustrative insert **1822** includes a main body **1834**, an upper support leg **1836** and a lower support leg **1838**. The upper support leg **1836** and the lower support leg **1838** are shaped to conform to the inner surface of the upper leg **1826** and the lower leg **1828** of the carrier **1820** when the insert **1822** is inserted into the cavity **1832**. Instead of providing an active light source, or in addition to providing an active light source, the illustrative embodiment of FIG. **79** includes an insert **1822** that is entirely formed from a glow-in-the-dark material. Alternatively, or in addition, the carrier may be formed from a glow-in-the-dark material, if desired. The glow-in-the-dark material may be charged by daylight, and glow at night.

FIG. **80** is a cross-sectional side view of another illustrative insert for use with the carrier of FIG. **79**. In this illustrative embodiment, a central region **1840** of the insert is formed from a glow-in-the-dark material, and the remainder of the insert is not. FIG. **81** is a cross-sectional side view of yet another illustrative insert for use with the carrier of FIG. **79**. In this illustrative embodiment, the three distinct regions **1844a**, **1844b** and **1844c** of the insert are formed from a glow-in-the-dark material, and the remainder of the

insert is not. The three distinct regions **1844a**, **1844b** and **1844c** shown in FIG. **81** are arranged to appear as lines of light when viewed at night. It is contemplated that the glow-in-the-dark regions and the non-glow-in-the-dark regions may be formed as an integral part by co-extruding the glow-in-the-dark material and the non-glow-in-the-dark material, if desired.

FIG. **82** is a cross-sectional side view of another illustrative lighting apparatus in accordance with the present invention. This illustrative embodiment includes a carrier **1850** that includes a front side **1852** that faces away from a mounting surface (not shown). In this illustrative embodiment, a central region **1854** of the carrier **1850** is formed from a glow-in-the-dark material, and the remainder of the carrier is not. Again, it is contemplated that the glow-in-the-dark regions and the non-glow-in-the-dark regions may be formed as an integral part by co-extruding the glow-in-the-dark material and the non-glow-in-the-dark material, if desired.

FIG. **83** is a partial perspective view of the illustrative lighting apparatus of FIG. **74**, with a plug for plugging the light receiving lumen **1722**. The plug **1870** may be sized to fit within the lumen **1722** and, in some cases, provide a water tight seal. In some embodiments, the plug **1870** may be pliable so it can be forced into the lumen **1722** to provide an interference fit and remain in place. In other embodiments, the plug may be more rigid, and in some cases, may be tapered so it too can be forced into the lumen **1722** to provide an interference fit and remain in place. In yet another embodiment, an adhesive or the like may be used to secure the plug in the lumen **1722**. In any case, the plug **1870** may provide a water tight seal to keep water, humidity, dust and/or other elements from entering the lumen **1722**.

In some embodiments, the plug **1870** may include a hole **1871** that extends partially through the plug **1870** as shown. The hole **1871** may be adapted to receive an end of a light source. In some cases, it may be desirable to secure the end of the light source to the plug **1870**, and when the plug is inserted into the lumen **1722**, the plug **1870** may hold the end of the light source relative to the end of the lumen **1722**. An interference fit, an adhesive or any other suitable method may be used to secure the end of the light source to the plug **1870**, if desired. In some cases, the end of the light source may also include one or more wires. In these embodiments, the plug may also serve to insulate the ends of the one or more wires.

FIG. **84** is a partial perspective view of a tube and cap for use in joining two of the illustrative lighting apparatuses of FIG. **74** end to end. A first lighting apparatus is shown generally at **1890** and a second lighting apparatus is shown at **1892**. To help seal the lumen **1722** across the joint, a tube **1894** may be provided. The tube **1894** may extend into the lumen **1722** of the first lighting apparatus **1890**, with the light source **1724** extending into and/or through the lumen **1896** of the tube **1894**. The tube **1894** may be sized to provide an interference fit with the lumen **1722** of the first light apparatus **1890**, and or an adhesive or the like may be used to secure the tube **1894** to the inner wall of the lumen **1722**, as desired. A similar connection may be made with the lumen (not shown) of the second lighting apparatus **1892**. The light source **1724** may extend out of the lumen **1722** of the first lighting apparatus **1890**, through the tube **1894** and into the corresponding lumen of the second lighting apparatus **1892**.

In some embodiments, the tube **1894** may provide a water tight connection between the lumen **1722** of the first lighting apparatus **1890** and corresponding lumen (not shown) of the

second lighting apparatus **1892**. The may help keep the light source **1724** from being exposed to the outside environmental conditions. It is contemplated that the tube **1894** may be formed from a transparent, semi-transparent or non-transparent material, as desired.

In the illustrative embodiment, a cap **1900** may be provided. An inner surface of the cap **1900** may be shaped similar to the outer surface of the first lighting apparatus **1890** and the second lighting apparatus **1892**. The cap **1900** may be provided over the joint between the first lighting apparatus **1890** and the second lighting apparatus **1892**, as shown. In some embodiments, the cap **1900** may include a flexible gasket **1902** in an initial liquid or solid state (shown as a dark line) to help provide a seal between the cap **1900**, the first lighting apparatus **1890**, and the second lighting apparatus **1892**. The flexible gasket **1902** may extend over the entire inside surface of the cap **1900**, around the perimeter of the inside surface of the cap **1900**, or only at selected locations. In some cases, the cap **1900** may help keep the joint between the first lighting apparatus **1890** and the second lighting apparatus **1892** from being exposed to the outside environmental conditions.

FIG. **85** is a partial perspective view of a tube and cap for use in joining two of the illustrative lighting apparatuses of FIG. **74** at a corner. This illustrative embodiment is similar to that shown in FIG. **84**, but the first lighting apparatus **1890** and the second lighting apparatus **1892** are joined at an angle, such as at a corner of a boat, dock or other mounting surface. In FIG. **85**, the tube **1894** extends into and is secured to the inner wall of the lumen **1722a** of the first light apparatus **1890**. The tube **1894** then extends around the corner, and is secured to the inner wall of the lumen **1722b** of the second light apparatus **1892**, as shown. The light source **1724** (see FIG. **74**) may extend out of the lumen **1722a** of the first lighting apparatus **1890**, through the tube **1894** and into the corresponding lumen **1722b** of the second lighting apparatus **1892**. In some embodiments, the tube **1894** may provide a water tight connection between the lumen **1722a** of the first lighting apparatus **1890** and lumen **1722b** of the second lighting apparatus **1892**. The may help keep the light source **1724** from being exposed to outside environmental conditions.

In the illustrative embodiment, a corner cap **1910** may be provided. An inner surface (not shown) of the cap **1910** may be shaped similar to the outer surface of the first lighting apparatus **1890** and the second lighting apparatus **1892**. The cap **1910** may be provided over the joint between the first lighting apparatus **1890** and the second lighting apparatus **1892**, as shown. In some embodiments, the cap **1910** may include a flexible gasket (not shown) in an initial liquid or solid state to help provide a seal between the cap **1910**, the first lighting apparatus **1890**, and the second lighting apparatus **1892**. The flexible gasket may extend over the entire inside surface of the cap **1910**, around the perimeter of the inside surface of the cap **1910**, or only at selected locations. In some cases, the cap **1910** may help keep the joint between the first lighting apparatus **1890** and the second lighting apparatus **1892** from being exposed to outside environmental conditions.

FIG. **86** is a partial perspective view of the illustrative lighting apparatus of FIG. **55** accordance with the present invention, with a lumen **1230** for receiving a light source, and a plug **1920** for plugging the lumen **1230**. The plug **1920** may be sized to fit within the lumen **1230** and, in some cases, provide a water tight seal. In some embodiments, the plug **1920** may be pliable so it can be forced into the lumen **1230** to provide an interference fit and remain in place. In other

embodiments, the plug **1920** may be more rigid, and in some cases, tapered so it too can be forced into the lumen **1230** to provide an interference fit and to remain in place. In yet another embodiment, an adhesive or the like may be used to secure the plug **1920** in the lumen **1230**. In any case, the plug **1920** may provide a water tight seal to keep water, humidity, dust and/or other elements from entering the lumen **1230**.

In some embodiments, the plug **1920** may include a hole **1921** that extends partially through the plug **1920** as shown. The hole **1921** may be adapted to receive an end of a light source. In some cases, it may be desirable to secure the end of the light source to the plug **1920**, and when the plug is inserted into the lumen **1230**, the plug **1920** may hold the end of the light source relative to the end of the lumen **1230**. An interference fit, an adhesive or any other suitable method may be used to secure the end of the light source to the plug **1920**, if desired. In some cases, the end of the light source may also include one or more wires. In these embodiments, the plug may also serve to insulate the ends of the one or more wires.

FIG. **87** is a partial perspective view of a tube and cap for use in joining two of the illustrative lighting apparatuses of FIG. **55** end to end. A first lighting apparatus is shown generally at **1930** and a second lighting apparatus is shown at **1932**. To help seal the lumen **1230** across the joint, a tube **1936** may be provided. The tube **1936** may extend into the lumen **1230** of the first lighting apparatus **1930**, with the light source **1250** extending into and/or through the lumen **1938** of the tube **1936**. The tube **1936** may be sized to provide an interference fit with the lumen **1230** of the first light apparatus **1930**, and or an adhesive or the like may be used to secure the tube **1936** to the inner wall of the lumen **1230**, as desired. A similar connection may be made with the lumen (not shown) of the second lighting apparatus **1932**. The light source **1250** may extend out of the lumen **1230** of the first lighting apparatus **1930**, through the tube **1936** and into the corresponding lumen (not shown) of the second lighting apparatus **1932**. In some embodiments, the tube **1936** may provide a water tight connection between the lumen **1230** of the first lighting apparatus **1930** and corresponding lumen (not shown) of the second lighting apparatus **1932**. The may help keep the light source **1250** from being exposed to the outside environmental conditions. It is contemplated that the tube **1936** may be formed from a transparent, semi-transparent or non-transparent material, as desired.

In the illustrative embodiment, a cap **1950** may be provided. An inner surface of the cap **1950** may be shaped similar to the outer surface of the first lighting apparatus **1930** and the second lighting apparatus **1932**. The cap **1950** may be provided over the joint between the first lighting apparatus **1930** and the second lighting apparatus **1932**, as shown. In some embodiments, the cap **1950** may include a flexible gasket **1952** in an initial liquid or sold state (shown as a dark line) to help provide a seal between the cap **1950**, the first lighting apparatus **1930**, and the second lighting apparatus **1932**. The flexible gasket **1952** may extend over the entire inside surface of the cap **1950**, around the perimeter of the inside surface of the cap **1950**, or only at selected locations. In some cases, the cap **1950** may help keep the joint between the first lighting apparatus **1930** and the second lighting apparatus **1932** from being exposed to outside environmental conditions.

FIG. **88** is a partial perspective view of a tube and cap for use in joining two of the illustrative lighting apparatuses of FIG. **55** at a corner. This illustrative embodiment is similar to that shown in FIG. **87**, but the first lighting apparatus **1930**

and the second lighting apparatus **1932** are joined at an angle, such as at a corner of a boat, dock or other mounting surface. In FIG. **88**, the tube **1936** extends into and is secured to the inner wall of the lumen **1230a** of the first light apparatus **1930**. The tube **1936** then extends around the corner, and is secured to the inner wall of the lumen **1230b** of the second light apparatus **1932**, as shown. The light source **1250** (see FIG. **87**) may extend out of the lumen **1230a** of the first lighting apparatus **1930**, through the tube **1936** and into the corresponding lumen **1230b** of the second lighting apparatus **1932**. In some embodiments, the tube **1936** may provide a water tight connection between the lumen **1230a** of the first lighting apparatus **1930** and lumen **1230b** of the second lighting apparatus **1932**. The may help keep the light source **1250** from being exposed to outside environmental conditions.

In the illustrative embodiment, a corner cap **1960** may be provided. An inner surface (not shown) of the cap **1960** may be shaped similar to the outer surface of the first lighting apparatus **1930** and the second lighting apparatus **1932**. The cap **1960** may be provided over the joint between the first lighting apparatus **1930** and the second lighting apparatus **1932**, as shown. In some embodiments, the cap **1960** may include a flexible gasket (not shown) in an initial liquid or sold state to help provide a seal between the cap **1960**, the first lighting apparatus **1930**, and the second lighting apparatus **1932**. The flexible gasket **1952** may extend over the entire inside surface of the cap **1960**, around the perimeter of the inside surface of the cap **1960**, or only at selected locations. In some cases, the cap **1960** may help keep the joint between the first lighting apparatus **1930** and the second lighting apparatus **1932** from being exposed to outside environmental conditions.

FIG. **89** is a cross-sectional side view of another illustrative lighting apparatus the present invention. This illustrative embodiment is similar that shown in FIG. **59**, but explicitly shows the use of a light strip as a light source. The illustrative lighting apparatus includes a carrier **2000** and an insert **2002**. The carrier **1370** includes a cavity **2004** for receiving the insert **2002**, as further described above with respect to FIG. **59**.

In the illustrative embodiment, the insert **2002** includes a lumen **2006** for receiving a light strip **2008**. In one illustrative embodiment, the light strip **2008** is an electro-luminescent light strip, such as that which is commercially available from E-Light Technologies Inc. of Stafford, Conn. It should be recognized, however, that any suitable light strip may be used, as desired. In some embodiments, the light strip **2008** may include a transparent coating or layer to help protect the light strip from outside environmental conditions.

The lumen **2006** may be sized to accommodate the light strip, and may include notches **2010a** and **2010b** for accepting the edges of the light strip. In some embodiments, the lumen **2006** may be oversized in at least one dimension by 5%, 10%, 20%, 30%, 40%, 50%, 100%, 200%, 300%, 500%, 1000% or more relative to the dimensions of the light strip, or between any of these ranges. For example, the notches **2010a** and **2010b** may be oversized relative to the width of the light strip by 5%, 10%, 20%, 30%, 40%, 50%, 100%, 200%, 300%, 500%, 1000% or more, or between any of these ranges.

In some embodiments, a slit **2012** may be provided through the back side (or other side) of the insert **2002** to facilitate insertion and extraction of the light strip to/from the lumen **2006**. A transparent or semi-transparent material, shown at **2014**, may allow at least some of the light emitted by the light strip **2008** to escape from the lumen **2006**.

FIG. 90 is a cross-sectional side view of another illustrative lighting apparatus the present invention. This illustrative embodiment is similar that shown in FIG. 68, but explicitly shows the use of a light strip as a light source. The illustrative lighting apparatus includes a carrier 2020 and an insert 2022. The carrier 2020 includes a cavity for receiving the light strip 2024. In the illustrative embodiment, the cavity is defined by a back wall that is positioned adjacent to the back of the light strip. An upper and a lower inward extending leg of the carrier 2020 then wrap around and engage the front of the light strip, as shown. The upper and lower legs may help secure the light strip to the carrier 2020 during use. The light strip is protected by insert 2022, which is inserted into the cavity of the carrier 2020 as further described above with respect to FIGS. 67–68. To allow at least some of the light to escape, the insert may have a transparent or semi-transparent region 2030.

The carrier 2020 may be secured to a mounting surface via screws or the like at locations 2028a and 2028b, if desired. As can be seen, FIG. 89 shows an illustrative light apparatus that houses a light strip in an insert that is carried by a carrier, and FIG. 90 shows an illustrative light apparatus that houses the light strip in a carrier that accepts an insert.

FIG. 91 is a cross-sectional side view of another illustrative lighting apparatus the present invention. This illustrative embodiment is similar to that shown in FIG. 90, except the carrier 2040 includes a different cavity position for receiving a light strip 2042. In some embodiments, the cavity may include one or more inward extending teeth 2044a and 2044b. In the illustrative embodiment, before the insert 2046 is installed on the carrier 2040, a light strip 2042 is inserted into the cavity from the front side of the carrier 2040. Then, the insert 2046 is installed in the carrier 2040. In the illustrative embodiment, the insert 2046 may include a plug 2050 that fits into the cavity, and engages the inward extending teeth 2044a and 2044b. The plug 2050 may help seal the cavity to help protect the light strip 2042 from undesirable environment conditions, such as water.

A region 2052 of the carrier 2040 that extends from the cavity to a lower outside surface 2054 of the carrier 2040 may be transparent or semi-transparent. The transparent or semi-transparent region 2052 may allow at least some of the light emitted by the light strip 2042 to escape. In the illustrative embodiment, the light escapes in a downward direction, but it is contemplated that the cavity and light strip 2042 may be configured to emit light in any direction, as desired.

FIG. 92 is a cross-sectional side view of another illustrative lighting apparatus the present invention. In this embodiment, the illumination apparatus 2070 may be separately provided. In the illustrative embodiment, the illumination apparatus 2070 is secured to a bumper assembly. In the illustrative embodiment, the bumper assembly includes a carrier 2060 and an insert 2062. However, this is only illustrative.

The illustrative lighting apparatus 2070 is adapted to be secured to the bumper assembly. For example, and in one illustrative embodiment, the lighting apparatus 2070 may be secured to the lower surface of the bumper assembly using, for example, an adhesive, screws, clips or any other suitable method for securing the lighting apparatus 2070 to the bumper assembly. In some embodiments, the lighting apparatus 2070 may include an integral clip that extends around a back leg 2072 of a bumper assembly. This may help secure the lighting apparatus 2070 to the bumper assembly (and a mounting surface). In the illustrative embodiment, the lighting apparatus 2070 may include a light strip 2074, but it is

contemplated that any suitable light source may be used. At least part of the lighting apparatus 2070 may include a transparent or semi-transparent material for allowing at least some of the light that is emitted from the light source to escape, as desired.

Having thus described illustrative embodiments of the present invention, those of skill in the art will readily appreciate that the teachings found herein may be applied to yet other embodiments within the scope of the claims hereto attached.

What is claimed is:

1. An elongated bumper, comprising:

an elongated bumper member having a lumen, cavity or opening extending lengthwise along the elongated bumper member for receiving an elongated light source; and

the elongated bumper member further including at least two tabs for securing the elongated bumper member to a mounting surface, wherein one of the tabs has a major surface that extends substantially perpendicular to a major surface of another one of the tabs.

2. The elongated bumper of claim 1 wherein at least one tab has a major surface that extends substantially parallel to an expected mounting surface.

3. The elongated bumper of claim 1 further comprising an elongated light source received by the lumen, cavity or opening of the elongated bumper.

4. The elongated bumper of claim 3 wherein the elongated light source includes an active light source.

5. The elongated bumper of claim 4 wherein the active light source is an electroluminescent light source powered by electrical current.

6. The elongated bumper of claim 5 wherein the electric current is provided by a battery.

7. The elongated bumper of claim 6 wherein the battery is recharged, at least in part, by solar power.

8. The elongated bumper of claim 3 wherein the elongated light source includes a passive light source.

9. The elongated bumper of claim 8 wherein the passive light source is a glow-in-the-dark light source.

10. The elongated bumper of claim 8 wherein the passive light source is a linear emitting fiber.

11. The elongated bumper of 1 wherein the elongated bumper is mounted to a dock or a pier.

12. The elongated bumper of 1 wherein the elongated bumper is mounted to a vehicle.

13. The elongated bumper of claim 1 wherein the elongated bumper member includes an arched bumper member extending from a back support, wherein the at least two tabs are extensions of the back support.

14. The elongated bumper of claim 13 wherein the arched bumper member includes the lumen, cavity or opening.

15. The elongated bumper of claim 13 wherein the back support includes the lumen, cavity or opening.

16. The elongated bumper of claim 1 wherein the elongated bumper member includes an arched bumper member, wherein the at least two tabs extend from the arched bumper member, and wherein the arched bumper member includes the lumen, cavity or opening.

17. The elongated bumper of claim 1 wherein the elongated bumper member includes a back support, a front bumper member, an arched top member and a bottom support.

18. The elongated bumper of claim 17 wherein the arched top member defines at least part of the lumen, cavity or opening, and includes a transparent or semi-transparent material.

47

19. An elongated bumper, comprising:  
 an elongated bumper member having a light source  
 extending along at least part of the length of the  
 elongated bumper member; and  
 the elongated bumper member further including at least  
 two tabs for securing the elongated bumper member to  
 a mounting surface.
20. The elongated bumper of claim 19 wherein the light  
 source includes an active light source.
21. The elongated bumper of claim 19 wherein the light  
 source includes a passive light source.
22. The elongated bumper of claim 21 wherein the passive  
 light source is a glow-in-the-dark light source.
23. The elongated bumper member of claim 19 wherein  
 the elongated bumper member includes two or more visually  
 distinguishable light sources.
24. A bumper member, comprising:  
 an elongated bumper having an elongated cavity extend-  
 ing lengthwise along the elongated bumper with an  
 elongated opening extending along at least part of the  
 length of the elongated cavity and from the elongated  
 cavity to an outer surface of the elongated bumper  
 member for receiving an elongated light source; and  
 an elongated plug for plugging at least part of the elon-  
 gated opening once an elongated light source is  
 installed in the cavity, the elongated plug and elongated  
 bumper forming an interference fit to help retain the  
 elongated plug in the installed position.
25. The bumper member of claim 24 wherein the elon-  
 gated bumper member includes a transparent or semi-trans-  
 parent material that extends from at least part of the cavity  
 to an outer surface of the elongated bumper member.
26. The bumper member of claim 25 wherein the elon-  
 gated plug is non-transparent.
27. The bumper member of claim 25 wherein the elon-  
 gated plug is transparent or semi-transparent.
28. The bumper member of claim 24 wherein the elon-  
 gated plug is transparent or semi-transparent.
29. The bumper member of claim 24 wherein the elon-  
 gated bumper member is adapted to receive an elongated  
 insert, and wherein part of the elongated insert forms at least  
 part of the elongated plug.
30. A kit for joining a first bumper member to a second  
 bumper member, wherein the first bumper member and the  
 second bumper member each include a lumen for receiving  
 an elongated light source, the kit comprising:  
 a tube having a lumen, the tube adapted to be inserted into  
 the lumen of the first bumper member and into the  
 lumen of the second bumper member, and further  
 adapted to allow the elongated light source to pass  
 through the lumen of the tube from the first bumper  
 member to the second bumper member.
31. The kit of claim 30 further comprising:  
 an adhesive suitable for providing a water tight seal  
 between the tube and the lumen of the first bumper  
 member, and the between the tube and the lumen of the  
 second bumper member.
32. The kit of claim 30 further comprising:  
 a cap adapted to fit over the joint between the first bumper  
 member and the second bumper member.
33. The kit of claim 32 wherein the cap includes a gasket  
 for providing a seal between the cap and the first bumper  
 member and the cap and the second bumper member.

48

34. The kit of claim 30 further comprising one or more  
 plugs for plugging the lumen of the first bumper member, the  
 lumen of the second bumper member, or both.
35. An elongated bumper, comprising:  
 an elongated bumper member having a length and two  
 ends, the elongated bumper member further having a  
 lumen extending lengthwise therethrough and out at  
 least one of the two ends of the elongated bumper, the  
 lumen for receiving an elongated light source; and  
 a plug, wherein the plug is adapted to fit into an end of the  
 lumen.
36. The elongated bumper of claim 35 wherein the plug  
 includes a hole extending at least partially therethrough,  
 wherein the hole is adapted to receive an elongated light  
 source and hold the elongated light source at a position in the  
 lumen relative to the elongated bumper.
37. An elongated bumper, comprising:  
 an elongated bumper member having a lumen, cavity or  
 opening extending lengthwise along the elongated  
 bumper member for receiving an elongated light  
 source; and  
 the elongated bumper member further including at least  
 two tabs for securing the elongated bumper member to  
 a mounting surface, wherein one of the tabs has a major  
 surface that extends substantially parallel to a major  
 surface of another one of the tabs.
38. The elongated bumper of claim 37 further comprising  
 an elongated light source received by the lumen, cavity or  
 opening of the elongated bumper.
39. The elongated bumper of claim 38 wherein the  
 elongated light source includes an active light source.
40. The elongated bumper of claim 39 wherein the active  
 light source is an electroluminescent light source powered  
 by electrical current.
41. The elongated bumper of claim 40 wherein the electric  
 current is provided by a battery.
42. The elongated bumper of claim 41 wherein the battery  
 is recharged, at least in part, by solar power.
43. The elongated bumper of claim 38 wherein the  
 elongated light source includes a passive light source.
44. The elongated bumper of claim 43 wherein the passive  
 light source is a glow-in-the-dark light source.
45. The elongated bumper of claim 43 wherein the passive  
 light source is a linear emitting fiber.
46. The elongated bumper of 37 wherein the elongated  
 bumper is mounted to a dock or a pier.
47. The elongated bumper of 37 wherein the elongated  
 bumper is mounted to a vehicle.
48. The elongated bumper of claim 37 wherein the  
 elongated bumper member includes an arched bumper mem-  
 ber extending from a back support, wherein the at least two  
 tabs are extensions of the back support.
49. The elongated bumper of claim 48 wherein the arched  
 bumper member includes the lumen, cavity or opening.
50. The elongated bumper of claim 48 wherein the back  
 support includes the lumen, cavity or opening.
51. The elongated bumper of claim 37 wherein the  
 elongated bumper member includes an arched bumper mem-  
 ber, wherein the at least two tabs extend from the arched  
 bumper member, and wherein the arched bumper member  
 includes the lumen, cavity or opening.

\* \* \* \* \*