

US007161628B2

(12) **United States Patent**
Tamamura

(10) **Patent No.:** **US 7,161,628 B2**
(45) **Date of Patent:** **Jan. 9, 2007**

(54) **IMAGE-PICKUP APPARATUS OUTPUTTING SIGNALS FOR FINDER DISPLAY AND SIGNALS FOR FOCAL-POINT DETECTION, CONTROL METHOD APPLIED TO THE APPARATUS, AND COMPUTER READABLE MEDIUM HAVING ENCODED THEREON A PROGRAM IMPLEMENTING A METHOD USING THE APPARATUS**

5,664,243	A	9/1997	Okada et al.	396/246
5,953,546	A	9/1999	Okada et al.	396/272
6,477,327	B1	11/2002	Imai	396/89
7,009,641	B1*	3/2006	Takahashi	348/223.1
2002/0008765	A1*	1/2002	Ejima et al.	348/239
2004/0207747	A1*	10/2004	Ikeda	348/335

(75) Inventor: **Hideo Tamamura**, Kanagawa (JP)
(73) Assignee: **Canon Kabushiki Kaisha**, Tokyo (JP)
(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 863 days.

FOREIGN PATENT DOCUMENTS

JP	7-143388	6/1995
JP	9-43506	2/1997
JP	2000-305010	11/2000
JP	2000-321488	11/2000
JP	2001-264624	9/2001

(21) Appl. No.: **10/320,477**
(22) Filed: **Dec. 17, 2002**

* cited by examiner

Primary Examiner—Vivek Srivastava
Assistant Examiner—Gevell Selby
(74) *Attorney, Agent, or Firm*—Fitzpatrick, Cella, Harper & Scinto

(65) **Prior Publication Data**
US 2003/0117508 A1 Jun. 26, 2003

(57) **ABSTRACT**

(30) **Foreign Application Priority Data**
Dec. 25, 2001 (JP) 2001-392639

An image-pickup apparatus, a control method applied to the image-pickup apparatus, and a control program for operating a computer used for the image-pickup apparatus are provided. The image-pickup apparatus comprises an image-pickup element for picking up the images of a subject. The image-pickup element can output image signals for performing finder display and focal-point detection. The image-pickup apparatus further comprises a control device for performing first-image pickup a predetermined number of times for performing the finder display and for performing second-image pickup for performing the focal-point detection every time the first-image pickup is performed the predetermined number of times.

(51) **Int. Cl.**
G03B 13/00 (2006.01)
H04N 5/232 (2006.01)
(52) **U.S. Cl.** **348/345; 348/333.11**
(58) **Field of Classification Search** 348/333.01, 348/345, 333.11, 346-352
See application file for complete search history.

(56) **References Cited**
U.S. PATENT DOCUMENTS
5,604,561 A * 2/1997 Ozawa et al. 396/96

9 Claims, 6 Drawing Sheets





FIG. 1






FIG. 3




FIG. 4




FIG. 5





FIG. 6



1

IMAGE-PICKUP APPARATUS OUTPUTTING SIGNALS FOR FINDER DISPLAY AND SIGNALS FOR FOCAL-POINT DETECTION, CONTROL METHOD APPLIED TO THE APPARATUS, AND COMPUTER READABLE MEDIUM HAVING ENCODED THEREON A PROGRAM IMPLEMENTING A METHOD USING THE APPARATUS

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to an image-pickup apparatus that performs focal-point detection by using an image-pickup element that performs image pickup for performing finder display. Further, the present invention relates to a control method applied to the image-pickup apparatus and to a control program for operating a computer used for the image-pickup apparatus.

2. Description of the Related Art

The art of using images picked up by a CCD video camera as AF images for performing mountain-climbing AF and as EVF images to be displayed on an electronic viewfinder (an EVF) is disclosed in Japanese Patent Laid-Open No. 7-143388.

The art of splitting part of an image-pickup element of a digital camera in two for performing phase-difference AF (autofocus) is disclosed in Japanese Patent Laid-Open No. 2000-305010. In such a case, it becomes possible to calculate the direction of a subject (the driving direction of a lens) and the moving amount of the lens more appropriately than in the case where the mountain-climbing AF is performed.

However, the above-described arts have the following problems.

In the case where the mountain-climbing AF as in Japanese Patent Laid-Open No. 7-143388 is performed, the contrast peak of subject images is searched by moving the lens. Therefore, it becomes necessary to perform AF calculation for each field by using image data. Subsequently, the AF speed is decreased.

Further, according to the art disclosed in Japanese Patent Laid-Open No. 2000-305010, the phase-difference AF is performed. Therefore, it becomes possible to calculate the subject direction and the defocusing amount by using an output image data obtained by using only one image pickup. However, the output image data is obtained by using only part of pixels of the image pickup element. Therefore, the obtained image cannot be used as an EVF image. In such a case, an optical finder, which requires expensive parts, such as a mirror, a prism, and so forth, and ample space, is used.

Accordingly, the object of the present invention is to provide an image-pickup apparatus that can perform high-speed autofocus (AF) by using an electronic viewfinder (EVF), an image-pickup method, a control program, and a recording medium.

SUMMARY OF THE INVENTION

It is an object of the present invention to perform focal-point detection without deteriorating finder display performed by using images captured by image pickup by using an image-pickup apparatus that performs the focal-point detection by using an image-pickup element that performs the image pickup for performing the finder display, a control method applied to the image-pickup apparatus, and a control program for operating a computer used for the image-pickup apparatus.

2

For achieving the above-described object, according to one aspect of the present invention, an image-pickup apparatus, a control method applied to the image-pickup apparatus, and a control program for operating a computer used for the image-pickup apparatus are provided. The image-pickup apparatus performs second-image pickup for performing focal-point detection every time it performs first-image pickup a predetermined number of times by using an image-pickup element for picking up the images of a subject and for outputting image signals for performing finder display and focal-point detection.

Other aspects of the present invention will be described in preferred embodiments shown below.

Further objects, features and advantages of the present invention will become apparent from the following description of the preferred embodiments (with reference to the attached drawings).

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a sectional view of a digital according to an embodiment of the present invention.

FIG. 2 is a block diagram illustrating circuits of the digital camera shown in FIG. 1.

FIG. 3 is a flowchart illustrating operation performed according to the embodiment of the present invention.

FIG. 4 is a timing chart illustrating operation timing according to the embodiment of the present invention.

FIG. 5 is another timing chart illustrating operation timing according to the embodiment of the present invention.

FIG. 6 is another flowchart illustrating operation performed according to the embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferred embodiments of the present invention will now be described with reference to attached drawings. An AF system according to a first embodiment of the present invention comprises an image-pickup element. On part of the image-pickup element, micro lenses for pupil-splitting the luminous flux that passes through a photographic lens and light receiving elements for receiving the pupil-split luminous flux are formed so that the micro lenses and the light receiving elements are paired with each other. Subsequently, a focus-detection area is formed on part of the image-pickup element for performing focus detection in a phase-difference detection mode. As described above, the light receiving elements, which are paired with the micro lenses, are not provided on the entire surface of the image-pickup element, but are provided only on part thereof. Such a configuration of the image-pickup element according to the first embodiment is the same as that of an image-pickup element disclosed in Japanese Patent Laid-Open No. 2000-305010. Therefore, the configuration and operating principles of the image-pickup element according to the first embodiment will not be described.

According to this embodiment, an image output from the image-pickup element can be viewed through an electronic view finder (an EVF), not through an optical finder. Further, since the AF speed is decreased by using a mountain-climbing AF system, a phase-difference AF system is used. That is to say, when a plurality of images is captured, only one image is captured as an AF image. All the other images are used as EVF images.

Since the AF image cannot be displayed as an EVF image, the EVF image just before the AF image must be displayed a longer period of time up until the point where the AF image would have been displayed if it had been captured as an EVF image. Accordingly, the EVF images are displayed without interruption.

Further, according to the first embodiment, the frequency of capturing AF images is changed according to the picture-taking mode. For example, when shooting a subject image that hardly moves, as in the case of portrait mode, there is no need to frequently capture images for AF. However, when shooting a subject image that moves quite often, as in the case of sports mode, it is necessary to capture images for AF as often as possible for following the subject.

FIGS. 1 to 4 illustrate a digital camera formed as an image-pickup unit according to the first embodiment of the present invention. In FIG. 1, reference numeral 1 indicates the main body of the digital camera, reference numeral 2 indicates a lens barrel, reference numeral 3 indicates a photographic optical system, reference numeral 4 indicates an infrared-cutting filter, reference numeral 5 indicates a low-pass filter, reference numeral 6 indicates an image-pickup unit, reference numeral 11 indicates a liquid-crystal display, reference numeral 12 indicates an eyepiece optical system, and reference numeral 21 indicates an eye of the user.

The configuration of the electronic view finder (the EVF) is described below. The infrared-cutting filter 4 eliminates infrared light from the luminous flux of the subject image passing through the photographic optical system 3. The low-pass filter 5 eliminates moiré fringes in the luminous flux. Then, the image-pickup unit 6 picks up the subject image. The image picked up by the image-pickup unit 6 is displayed by the liquid-crystal display 11 and is seen by the user (the eye 21) via the eyepiece optical system 12.

FIG. 2 is a block diagram illustrating the circuits of the digital camera shown in FIG. 1. This drawing illustrates a lens unit 101 for capturing the subject image, a CCD 102 serving as the image-pickup unit, a digital-signal processing circuit 103 for processing captured image signals, and an image-signal processing unit 104. Further, the drawing illustrates a microcomputer 105 for controlling operation timing, an operating unit 112 for performing shutter releasing and photographing-mode switching. Signals transmitted from the operating unit 112 are read by the microcomputer 105. Further, the drawing illustrates a compression circuit 106, a work memory 107 used when the compression circuit 106 compresses data, a memory 108 formed of a nonvolatile flash memory or the like, a driving circuit 109 for the liquid-crystal display (LCD) 11, and a backlight 110. The driving circuit 109 drives the backlight 110 and a liquid-crystal panel of the liquid-crystal display 11. The driving circuit 109 also serves as a finder for displaying an image. Further, the drawing illustrates a power circuit 111 serving as a power source for supplying power to the units and elements of the digital camera. Further, the drawing illustrates a driving circuit 115 for moving the lens unit 101, a video out-terminal 116, and a release button 120. When image data is captured in synchronization with the release button 120, the compression circuit 106 compresses the image data and stores the compressed image data in the memory 108.

A brief description of image pickup performed by an image-pickup unit and the details of image pickup for AF will be given below.

In the above-described case, a focus-detection area is formed by providing microlenses for pupil-splitting the luminous flux passing through a photographing lens and light receiving elements for receiving the pupil-split luminous flux on part of an image-pickup element. The microlenses and the light receiving elements are paired with each other. Focus detection in a phase-difference detection mode is performed in the focus-detection area. Since an image corresponding to the focus-detection area cannot be used, the following configuration is necessary. First light-receiving elements are provided by aligning a first plurality of light-receiving elements for receiving the light of a subject image passing through a photographing lens. Microlenses are provided for pupil-splitting luminous flux of the subject image. Second light-receiving elements are provided by aligning a second plurality of light-receiving elements for receiving the pupil-split luminous flux. The second light-receiving elements are paired with the microlenses. Focus-detection means is provided for performing focus detection based on the output from the second light-receiving elements. Correction means is provided for correcting the subject image corresponding to the focus-detection area on which the second light-receiving elements exist based on the output from the first light-receiving elements. Image-pickup means is provided for picking up the subject image based on the output from the first light-receiving elements and the output from the correction means.

FIG. 3 is a flowchart illustrating the operation performed for capturing EVF images and AF images.

At step S201, a main switch is turned on. At step S202, each block of the digital camera is initialized for displaying the subject image on the EVF serving as the finder.

At step S203, the subject image is captured by the image-pickup unit 6. At step S204, the captured subject image is processed. At step S205, the processed subject image is displayed on the EVF. Subsequently, the user can view the image displayed on the EVF serving as the finder.

At step S206, it is determined whether or not the switch SW1 is turned on. Then, the procedure goes back to step S203. By repeating such an operation, the subject image is continuously displayed on the EVF. The release button 120 has switches SW1 and SW2. The switch SW1 is turned on by half-pressing the release button 120. The switch SW2 is turned on by fully-pressing the release button 120. If the switch SW1 is turned on at step S206, the procedure advances to step S207. At step S207, the AF images are captured. The AF images are captured in the same way as in the case of Japanese Patent Laid-Open No. 2000-305010. As disclosed in Japanese Patent Laid-Open No. 2000-305010, AF images to be captured are images picked up by an AF-pixel unit (not shown).

At step S208, the EVF images are captured. Then, the captured EVF images are processed at step S209. At step S210, the processed EVF images are displayed on the EVF. The AF images captured at step S207 cannot be displayed on the EVF since they are partial images and can be used only for AF.

At step S211, it is determined whether or not the switch SW2 is turned on. At step S212, the number of captured EVF images is determined. If the switch SW2 is turned off, and the number of captured EVF images is less than a predetermined number, the procedure goes back to capture the EVF images and the subject image is continuously displayed on the EVF while the switch SW1 is in the ON state. During such a state, phase-difference AF calculation is performed

5

based on data of the captured AF images. The lens unit **101** is driven toward the focal point based on the calculation result.

If the number of captured EVF images reaches the pre-determined value at step **S212**, the procedure goes back to step **S207** for capturing the AF images again for confirming the AF images while the lens unit **101** is being driven. However, in contrast to a case where the mountain-climbing AF system is used, there is no need to frequently repeat the phase-difference AF calculation because the widely known phase-difference AF system is used in this embodiment.

If the switch **SW2** is turned on at step **S211**, the procedure advances to step **S213**. At step **S213**, the subject images are captured by the image-pickup unit **6**. That is to say, photographing is performed. Then, at step **S214**, the images are processed. At step **S215**, the captured images are displayed on the EVF. The images processed at step **S214** are stored in the memory **108** shown in FIG. **2**.

The flow of operation from the step of capturing the EVF images (step **S203**), via the step of processing the captured EVF images (step **S204**), to the step of displaying the EVF images (step **S205**) will be described. Further, the operation performed at step **S207** for capturing the AF images and the operation performed at step **S208** for capturing the EVF images will be described.

FIG. **4** illustrates the case where images are picked up to be displayed on the EVF. In this case, no image is used as an AF image.

A first image pickup performed by the image-pickup element **6** is indicated by **A1**. A second image pickup is indicated by **A2**. A third image pickup is indicated by **A3**. The following image pick up is also indicated in a like manner as shown in the drawing. A first processing of the picked up image is indicated by **B1** and a second processing of the picked up image is indicated by **B2**. The following processing is also indicated in a like manner as shown in the drawing. A first display of the image on the EVF is indicated by **C1**, and a second display is indicated by **C2**. The following display is also indicated in a like manner as shown in the drawing. The horizontal axis indicates the time. An image exposed to light as long as a time indicated by the **A1** width is processed at **B1**. When the processing is done, the image is transmitted to the EVF and is displayed on a display such as the liquid-crystal display **11** as long as a time indicated by the **C1** width. Then, the image is viewed by the user's eye, for example, the eye **21**. For avoiding black out, the EVF images are continuously displayed as shown by **C1**, **C2**, **C3**, and **C4** in FIG. **4**.

The steps flow in the order of **A1**, **B1**, and **C1**, **A2**, **B2**, and **C2**, **A3**, **B3**, and **C3**, and so forth.

FIG. **5** illustrates the case where the AF images are picked up while the EVF images are picked up. The image picked up at **A11** is processed at **B11** and is displayed on the EVF at **C11**. The image picked up at **A12** is processed at **B12** and is displayed on the EVF at **C12**. The image picked up at **A13** is used as the AF image. The AF image is processed at **B13** and is transmitted to an AF calculation unit (not shown). The AF image is not displayed on the EVF. Subsequently, at **C13**, there is no image to be displayed on the EVF. That is to say, a blackout period is formed, which is a cause of user discomfort. For staying out of such a trouble, according to this embodiment, the same EVF image as that displayed at **C12** is displayed at **C13** for eliminating the blackout period. The image being displayed on the EVF is renewed at **A14**. An image picked up to be used as the EVF image is processed at **B14** and is displayed on the EVF at **C14**.

6

FIG. **6** illustrates the operation performed when the switch **SW1** and the switch **SW2** are turned on.

For performing photographing by the digital camera, the power circuit **111** is turned on at step **S301**. The photographing mode is set at step **S302**. Subsequently, the AF photographing frequency is determined for detecting the focal point.

When the switch **SW1** is turned on at step **S303**, the release button **120** is half-pressed. If the switch **SW1** is turned off at step **S303**, the procedure advances to step **S304** for clearing and initializing control flags and control variables set in a RAM of the microcomputer **105**. The operations performed at step **S303** and **S304** are repeated until the switch **SW1** is turned on or the power circuit **111** is turned off. When the switch **SW1** is turned on, the procedure advances from step **S303** to step **S305**.

At step **S305**, a "photometric" subroutine is performed for controlling exposure. The microcomputer **105** obtains the most appropriate exposure control value and the most appropriate diaphragm control value based on an output from a photometric sensor (not shown) or the like. At the release operation time, the microcomputer **105** performs shutter control and diaphragm control. Then, at step **S306**, a "focusing" subroutine is performed. The microcomputer **105** performs calculation based on the image signal transmitted from the image-pickup element **6** and drives the photographic optical system **3** or the lens unit **101**.

The AF photographing frequency used by the image-pickup element **102** is changed according to the photographic mode. For example, the lens unit **101** may be driven to a predetermined position and may be stopped there after only one AF photographing is performed. In another case, AF photographing may be performed several times before determining the lens position.

For example, in the case where the portrait mode is used, the lens position can be determined based on the calculation result obtained by a first-captured image. This is because the subject scarcely moves in such a case. However, if the subject moves a lot, for example, as in the case of a sports event, it is preferable to perform photographing in sports mode where the AF photographing is performed several times during the EVF photographing. By performing the AF photographing, it becomes possible to determine whether or not the subject moves for appropriately performing correction. Subsequently, the position where the lens unit **101** should be stopped is correctly determined according to the position of the subject.

Thus, it is preferable to change the AF photographing frequency according to the photographing mode.

After driving the lens unit **101**, the procedure goes back to step **S303**. Then, the operations performed at step **S305**, step **S306**, and step **S307** are repeatedly performed until the switch **SW1** is turned off, or until the switch **SW2** is turned on by fully pressing the release button **120**. In this manner, the focal point of the subject is adjusted. When the release button **120** is fully pressed and the switch **SW2** is turned on, the cut-in function is performed. Subsequently, the procedure moves to step **S308** where the release operation is performed. At step **S309**, it is determined whether or not the lens unit **101** is being driven. If the lens unit **101** is being driven, the procedure advances to step **S310** and a lens-driving stop command is generated. Subsequently, the lens unit **101** is stopped and the procedure advances to step **S311**. If the lens unit **101** is not driven at step **S309**, the procedure directly advances from step **S309** to step **S311**. At step **S311**, photographing is performed for a predetermined time.

Thus, according to the embodiment, the images picked up by the image-pickup element 6 is viewed on the EVF. Then, while capturing the EVF images, the AF images are also captured for performing the phase-difference AF. Subsequently, it becomes possible to perform AF as fast as in the case where AF is performed by using an optical finder. Further, according to the embodiment, it becomes possible to perform AF faster than in the case where the widely known mountain-climbing AF is performed.

Further, by displaying the EVF image that was captured just before the AF image was captured a longer period of time up until the point where the AF image would have been displayed, the EVF display can be performed without interruption.

Further, by changing the frequency of picking up the AF images, it becomes possible to perform the most appropriate AF for the subject according to the photographic mode and to perform the EVF display without interruption.

The object of the embodiment can be achieved by providing a recording medium storing the program code of software that achieves the above-described functions to the system or the device. Then, a computer (or a CPU or an MPU) included in the system or the device may read the program code and may execute it for achieving the object of the present invention. In such a case, the program code that is read from the recording medium achieves the new functions of the present invention. Therefore, in such a case, the recording medium storing the program code serves as the component of the present invention. As has been described, the above-described functions can be achieved by executing the program code read by the computer. However, an OS operated on the computer based on the instructions of the program code may perform part of the procedures or all the procedures for achieving the functions of the present invention.

Further, when the program code read from the recording medium is stored in an expansion board provided in the computer or in a memory provided in an expansion unit connected to the computer, a CPU in the expansion board or the expansion unit may perform part of the procedures or all the procedures for achieving the functions of the present invention.

When the present invention is applied to the above-described recording medium, the recording medium stores the program code corresponding to the flowcharts shown in FIGS. 3 and 6.

Further, part of the components or the entire components, which are described in Claims or the embodiments of the present invention, may form one device. Otherwise, part of the components or the entire components may be connected to other apparatus or may be components of the other apparatus.

While the present invention has been described with reference to what are presently considered to be the preferred embodiments, it is to be understood that the invention is not limited to the disclosed embodiments. On the contrary, the invention is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

What is claimed is:

1. An image-pickup apparatus comprising:
an image-pickup element configured to pick up images of a subject and to output first-image signals usable for

performing finder display and second-image signals usable for performing focal-point detection; and
a control device configured to perform a first-image pickup operation a predetermined number of times, configured to perform the finder display, and configured to perform a second-image pickup operation for performing the focal-point detection every time the first-image pickup operation is performed the predetermined number of times,

wherein said control device does not perform the finder display using the second-image signal generated by the second-image pickup operation.

2. An image-pickup apparatus comprising:
an image-pickup element configured to pick up images of a subject and to output first-image signals usable for performing finder display and second-image signals usable for performing focal-point detection; and
a control device configured to perform a first-image pickup operation a predetermined number of times, configured to perform the finder display, and configured to perform a second-image pickup operation for performing the focal-point detection every time the first-image pickup operation is performed the predetermined number of times,

wherein said control device changes the number of times the first-image pickup operation is performed according to a photographic mode of operation of said image pick-up apparatus.

3. An image-pickup apparatus comprising,
an image-pickup element configured to pick up images of a subject and to output first-image signals usable for performing finder display and second-image signals usable for performing focal-point detection; and
a control device configured to perform a first-image pickup operation a predetermined number of times, configured to perform the finder display, and configured to perform a second-image pickup operation for performing the focal-point detection every time the first-image pickup operation is performed the predetermined number of times,

wherein said control device changes the number of times the first-image pickup operation is performed according to a photographic mode of operation of said image pick-up apparatus corresponding to movement of the subject.

4. A control method applied to an image-pickup apparatus including an image-pickup element configured to pick up images of a subject and to output first-image signals usable for performing finder display and second-image signals usable for performing focal-point detection, the control method comprising the steps of:

- performing a first-image pickup operation a predetermined number of times for performing the finder display; and

- performing a second-image pickup operation for performing the focal-point detection every time the first-image pickup operation is performed the predetermined number of times,

wherein the finder display is not performed by using the second-image signal generated by the second-image pickup operation.

5. A control method applied to an image-pickup apparatus including an image-pickup element configured to pick up images of a subject and to output first-image signals usable for performing finder display and second-image signals usable for performing focal-point detection, the control method comprising the steps of:

9

performing a first-image pickup operation a predetermined number of times for performing the finder display; and

performing a second-image pickup operation for performing the focal-point detection every time the first-image pickup operation is performed the predetermined number of times,

wherein the number of times the first-image pickup operation is performed is changed according to a photographic mode of operation of the image pick-up apparatus.

6. A control method applied to an image-pickup apparatus including an image-pickup element configured to pick up images of a subject and to output first-image signals usable for performing finder display and second-image signals usable for performing focal-point detection, the control method comprising the steps of:

performing a first-image pickup operation a predetermined number of times for performing the finder display; and

performing a second-image pickup operation for performing the focal-point detection every time the first-image pickup operation is performed the predetermined number of times,

wherein the number of times the first-image pickup operation is performed is changed according to a photographic mode of operation of the image pick-up apparatus corresponding to movement of the subject.

7. A computer readable medium having encoded thereon an image focal-point detection program comprising a set of instructions when executed by a computer to implement a method for picking up images of a subject with an image pick-up element and outputting first-image signals usable for performing finder display and second-image signals usable for performing focal-point detection, the method comprising the steps of:

performing a first-image pickup operation a predetermined number of times for performing the finder display; and

performing a second-image pickup operation for performing the focal-point detection every time the first-image pickup operation is performed the predetermined number of times,

10

wherein the finder display is not performed by using the second-image signal generated by the second-image pickup operation.

8. A computer readable medium having encoded thereon an image focal-point detection program comprising a set of instructions when executed by a computer to implement a method for picking up images of a subject with an image pick-up element and outputting first-image signals usable for performing finder display and second-image signals usable for performing focal-point detection, the method comprising the steps of:

performing a first-image pickup operation a predetermined number of times for performing the finder display; and

performing a second-image pickup operation for performing the focal-point detection every time the first-image pickup operation is performed the predetermined number of times,

wherein the number of times the first-image pickup operation is performed is changed according to a photographic mode of the operation of the method.

9. A computer readable medium having encoded thereon an image focal-point detection program comprising a set of instructions when executed by a computer to implement a method for picking up images of a subject with an image pick-up element and outputting first-image signals usable for performing finder display and second-image signals usable for performing focal-point detection, the method comprising the steps of:

performing a first-image pickup operation a predetermined number of times for performing the finder display; and

performing a second-image pickup operation for performing the focal-point detection every time the first-image pickup is performed the predetermined number of times,

wherein the number of times the first-image pickup is performed is changed according to a photographic mode of operation of the method corresponding to movement of the subject.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,161,628 B2
APPLICATION NO. : 10/320477
DATED : January 9, 2007
INVENTOR(S) : Hideo Tamamura

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

IN THE DRAWINGS
SHEET 3

FIG. 3, "PREDERMINED" should read --PREDETERMINED--.

COLUMN 2

Line 21, "view" should read --schematic view--; and "digital" should read --digital camera--.

COLUMN 7

Line 2, "is" should read --are--.

Signed and Sealed this

Fifth Day of June, 2007

A handwritten signature in black ink on a light gray dotted background. The signature reads "Jon W. Dudas" in a cursive style.

JON W. DUDAS

Director of the United States Patent and Trademark Office