



US007185174B2

(12) **United States Patent**  
**Stewart et al.**

(10) **Patent No.:** **US 7,185,174 B2**  
(45) **Date of Patent:** **Feb. 27, 2007**

(54) **SWITCH COMPLEX SELECTIVELY COUPLING INPUT AND OUTPUT OF A NODE IN TWO-DIMENSIONAL ARRAY TO FOUR PORTS AND USING FOUR SWITCHES COUPLING AMONG PORTS**

(75) Inventors: **Malcolm Stewart**, Nepean (CA); **Eric Giernalczyk**, Ottawa (CA); **Richard Beriault**, Hull (CA)

(73) Assignee: **Mtekvision Co., Ltd.**, Seoul (KR)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 228 days.

(21) Appl. No.: **10/469,525**

(22) PCT Filed: **Mar. 4, 2002**

(86) PCT No.: **PCT/CA02/00299**

§ 371 (c)(1),  
(2), (4) Date: **Feb. 23, 2004**

(87) PCT Pub. No.: **WO02/071246**

PCT Pub. Date: **Sep. 12, 2002**

(65) **Prior Publication Data**

US 2004/0133750 A1 Jul. 8, 2004

**Related U.S. Application Data**

(60) Provisional application No. 60/272,301, filed on Mar. 2, 2001.

(51) **Int. Cl.**  
**G06F 15/173** (2006.01)

(52) **U.S. Cl.** ..... 712/11; 710/316

(58) **Field of Classification Search** ..... None  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

5,048,108	A *	9/1991	Basille et al. ....	382/304
5,056,000	A	10/1991	Chang .....	710/110
5,235,575	A *	8/1993	Han .....	369/30.27
5,546,343	A	8/1996	Elliott et al. ....	365/189.04
5,590,356	A	12/1996	Gilbert .....	712/31
5,878,241	A	3/1999	Wilkinson et al. ....	712/203
5,937,202	A	8/1999	Crosetto .....	395/800.19
5,956,274	A	9/1999	Elliott et al. ....	365/189.04
6,266,760	B1	7/2001	DeHon et al. ....	712/15
6,681,316	B1 *	1/2004	Clermidy et al. ....	712/11
2005/0076187	A1 *	4/2005	Claydon .....	712/11

**FOREIGN PATENT DOCUMENTS**

WO WO 00/62182 10/2000

\* cited by examiner


*Primary Examiner*—Kenneth S. Kim

(74) *Attorney, Agent, or Firm*—Blackwell Sanders Peper Martin LLP; Changhoon Lee

(57) **ABSTRACT**

A switching element for switchably coupling a two-dimensional array of circuit elements comprises an input, an output, means for switchably coupling the input to the output; a first input/output port, a second input/output port, a third input/output port, and a fourth input/output port, each input/output port being switchably coupled to the input, the output, and each other, wherein the first and third input/output ports are spaced apart along a first axis, and the second and fourth input/output ports are spaced apart along a second axis, wherein the second axis traverses the first axis between the first and third input/output ports.

**7 Claims, 18 Drawing Sheets**






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6






FIG. 7




FIG. 8




FIG. 9






FIG. 10




FIG. 11




FIG. 12




FIG. 13






FIG. 14

TABLE 2

W-N		N		N-E	
S2	1	S2	1	S2	1
S1	0	S1	0	S1	0
S0	1	S0	0	S0	0
UEN	0	UEN	0	UEN	0
REN	1	REN	0	REN	0
DEN	0	DEN	0	DEN	1
W		BYPASS		E	
S2	1	S2	0	S2	1
S1	1	S1	X	S1	0
S0	1	S0	X	S0	1
UEN	1	UEN	X	UEN	0
REN	1	REN	X	REN	0
DEN	1	DEN	X	DEN	1
S-W		S		E-S	
S2	1	S2	1	S2	1
S1	1	S1	1	S1	1
S0	0	S0	0	S0	1
UEN	1	UEN	1	UEN	1
REN	1	REN	0	REN	0
DEN	1	DEN	0	DEN	0

FIG. 15






FIG. 18






FIG. 19





FIG. 20






FIG. 22




FIG. 23




FIG. 24



1

# SWITCH COMPLEX SELECTIVELY COUPLING INPUT AND OUTPUT OF A NODE IN TWO-DIMENSIONAL ARRAY TO FOUR PORTS AND USING FOUR SWITCHES COUPLING AMONG PORTS

## CROSS REFERENCE TO RELATED APPLICATIONS

This application is a National Phase application of PCT/CA02/00299 filed Mar. 4, 2002 claiming priority from U.S. Provisional Application 60/272,301 filed Mar. 2, 2001.

## FIELD OF THE INVENTION

The present invention relates to access control in a data processor, and in particular but not limited to access control in a single instruction multiple data (SIMD) processor.

## BACKGROUND OF THE INVENTION

A typical single-instruction-multiple-data (SIMD) processor has multiple processor units each having its own associated memory space. The processor units are simple processors unable to fetch or interpret instructions, and are controlled by a single control unit whereby the processor units act as slaves, performing at its request, arithmetic-logic operations. One advantage of this architecture is that more memory and processor units can be easily added to the computer.

An example of a SIMD processor is described in U.S. Pat. No. 5,956,274 ('274 patent) issued on 21<sup>st</sup> Sep., 1999 to Duncan G. Elliott, et al. In this architecture the processing units are placed within the memory, there being one processor unit per column of storage elements, each processor unit being directly coupled to the sense amplifier of each column, and whose output is coupled to the memory column decoder. Each processor element is a single bit processor element and is capable of processing serial data output from the memory column to which it is coupled and associated. The disclosed structure allows for higher bandwidth communications between the memory and processing elements, allowing for a much high processing throughout as processing is not limited by the ability to provide data to the individual processing elements.

There are however aspects to the disclosed architecture that hamper its ability to be widely implemented. First, the structure disclosed in the '274 patent implements a single row i.e. 1-D layout of processing elements. Second, processing elements are coupled to and associated with a single column of memory such that the processing elements in the '274 patent are only able to communicate with the column or columns of memory with which they are coupled and associated.

In applications such as the processing of image, including video, it is desirable to have a high bandwidth of data from the memory. It is further desirable to have access to numerous portions of memory, including those with which a given processing element is not associated. It is also advantageous to implement an array of processing elements i.e. a 2-D structure.

The tight integration of processing elements and memory as outlined in the '274 patent generally makes it difficult to provide for communications between a two dimensional array of processing elements. It is further difficult to provide for communications between a given processing element and the portions of memory with which it is not associated.

2

A communication network that implements 1 to 1 communications links between a given processing element and all other processing elements and all portions of memory is not practical, even with multi-layer metallization technology as is found in current semiconductor processing. Therefore there is a need for a communications between processing elements and memory without requiring 1 to 1 links between elements and is implementable within a structure where processing elements are integrated in memory.

U.S. Pat. No. 5,056,000 (Chang) discloses a Multi-Instruction/Multi-Data Stream (MIMD) computer comprising a number of processors each having a local memory and connected to a global bus. One processor acts as a master processor and the others as slaves. Each of the slave processors is connected to a shared Multi-Access Memory (MAM) through an interconnection switch. The interconnection switch has a grid configuration and can be controlled so that any one processor can access any number of memory modules simultaneously, but each memory module can only be connected to one processor at a time. This configuration allows a single processor to simultaneously write data to multiple memory modules of the multiple access memory.

## SUMMARY OF THE INVENTION

According to one aspect of the present invention, there is provided a data processor apparatus, comprising: a plurality of processor elements; a memory having a plurality of parts each associated with a respective processor element; a switching element associated with a processor element for switchably coupling said processor element to its associated memory part for at least one of read and write access; said switching element having an input port for access to at least one of said memory part and said processor element; an output port for access to at least one of said memory part and said processor element; a first port and a second port; a first switch for selectively coupling said first port to one of said input port and said output port; and a second switch for selectively coupling said second port to one of said input port and said output port.

Advantageously, this arrangement enables a processor element to access a memory segment associated with another processor element without the need to involve the processor element associated with the other memory segment in the data transfer, which therefore allows the associated processor element to perform other functions, rather than spend time/cycles transferring data to another processor element from its memory segment. This arrangement not only provides flexibility of enabling data transfers between different memory segments and a given processor element, but also significantly reduces the time required for the transfer, and in embodiments of the present invention, data transfers from non-local memory segments may be achieved in a single cycle.

According to another aspect of the present invention there is provided a switching element for switchably coupling an array of circuit elements each having an input and an output, the switching element comprising: an input for coupling to the output of a circuit element, an output for coupling to an input of a circuit element, a first port and a second port, and first and second switch means, said first switch means having a first state in which said first port is coupled to said input port, and a second state in which said first port is coupled to said output port, and said second switch means having a first state in which said second port is coupled to said input port and a second state in which said second port is coupled to said output port.



## 3

According to another aspect of the present invention there is provided a data processor apparatus comprising a plurality of processor elements and a memory having a plurality of segments, each containing at least one column of storage elements, and each segment having a memory port, and wherein at least one memory port is coupled to at least two processor elements.

According to another aspect of the present inventions there is provided a data processor having a first memory block, a first array of processor elements, each processor element being capable of accessing said first memory block, a first array of switching elements each associated with a respective processor element of said first array, a second memory block and a second array of processor elements, each being capable of accessing said second memory block, a second array of switching elements each associated with a respective processor element of said second array, wherein a corresponding switching element of said first array is coupled to a corresponding switching element of said second array.

According to another aspect of the present invention, there is provided a data processor comprising an array of circuit elements and a switching element associated with each of said circuit elements said switching elements being interconnected to enable data to be transferred between said circuit elements.

## BRIEF DESCRIPTION OF THE DRAWINGS

Examples of embodiments of the present invention will now be described with reference to the drawings, in which:

FIG. 1 shows a block diagram of a data processor according to an embodiment of the present invention;

FIG. 2 shows a diagram of an access switching arrangement according to an embodiment of the present invention;

FIG. 3 shows a schematic diagram of a data processor apparatus according to an embodiment of the present invention;

FIG. 4 shows a schematic diagram of a computational unit according to an embodiment of the present invention;

FIG. 5 shows a schematic diagram of a switching element interconnect scheme according to an embodiment of the present invention;

FIG. 6 shows a diagram of an array of computational units according to an embodiment of the present invention;

FIG. 7 shows a diagram of a two-dimensional array of switching elements and an interconnect scheme according to an embodiment of the present invention;

FIG. 8 shows an embodiment of a switching element, which may be used in the interconnect scheme of FIG. 7;

FIG. 9 shows a diagram of a switching element, according to another embodiment of the present invention;

FIG. 10 shows an array of interconnected switching elements of the embodiment shown in FIG. 8;

FIG. 11 shows a diagram of a switching element according to another embodiment of the present invention;

FIG. 12 shows a diagram of an array of switching elements of the embodiment of FIG. 10;

FIG. 13 shows a diagram of a switching element according to another embodiment of the present invention;

FIG. 14 shows Table 1, which contains the possible states of a tri-stateable inverter;

FIG. 15 shows Table 2, which contains examples of various sets of control signals for controlling the embodiment of the switching element shown in FIG. 13;

FIG. 16 shows a diagram of a switching element according to another embodiment of the present invention;

## 4

FIG. 17 shows a diagram of a switching element according to another embodiment of the present invention;

FIG. 18 shows a diagram of a switching element according to another embodiment of the present invention;

FIG. 19 shows a diagram of a switching element according to another element of the present invention;

FIG. 20 shows a block diagram of a data processor according to an embodiment of the present invention;

FIG. 21 shows a diagram of a data processor according to another embodiment of the present invention;

FIG. 22 shows a diagram of a switching element according to an embodiment of the present invention;

FIG. 23 shows a block diagram of a data processor according to another embodiment of the present invention, and

FIG. 24 shows a data processor according to another embodiment of the present invention.

## DESCRIPTION OF EMBODIMENTS

Embodiments of the current invention present aspects of a communications network that allows for communications between a given processing element and other processing elements, as may be found in a processor that implements a plurality of SIMD processing elements, and between a given processor and various regions of memory.

Referring to FIG. 1, a data processor 1, according to an embodiment of the present invention, comprises a plurality of processor elements (PE) 3, 5, 7 and a memory 9, which may for example comprise a random access memory (RAM). The memory includes a plurality of segments 11, 13, 15 and each segment has an associated input/output port 17, 19, 21 to permit read/write access to a respective memory segment. Each memory segment may comprise a one dimensional array (e.g. a column) or a two-dimensional array (e.g. containing a plurality of rows and columns) of one bit memory or storage elements. The memory may include a row selector to select a particular row of memory elements and each segment may include a column selector to select a particular column of memory elements and to connect that column to the I/O port, if each segment contains more than one column of memory elements.

The data processor 1 further includes a plurality of switching elements (SE) 23, 25, 27. The first switching element 23 is coupled to the I/O ports 17, 19 of the first and second memory segments 11, 13 and is switchable to selectively couple one of the first and second memory segments 11, 13 to the first processor element 3. Similarly, the second switching element 25 is coupled to the I/O ports 19, 21 of the second and third memory segments 13, 15 and is arranged to selectively couple either the second or third memory segment 13, 15 to the second processor element 5. The third switching element 27 is coupled to the third memory segment 15 and possibly to a fourth memory segment (not shown) and may be arranged to selectively couple the third memory segment 15 or the fourth memory segment to the third processor element 7. The first switching element 23 may be arranged to provide at least one of read access by the first (i.e. its local) processor element to at least one of the first (i.e. its local) memory segment 11 and to the second (i.e. its remote, e.g. neighbouring or more remote than neighbouring) memory segment 13, and write access from the first processor element 3 to at least one of the first and second memory segments 11, 13. Similarly, the second and/or third switching elements 25, 27 may be arranged to provide at least one of read access to at least one of its local and remote memory, and write access from the processor element to at



## 5

least one of its respective local and remote memories. The switching of each switching element **23**, **25**, **27** may be controlled by applying a control signal to a respective control signal input port **29**, **31**, **33**.

Advantageously, the switching arrangement shown in FIG. **1**, allows each processor element direct access not only to its local memory segment but also to the local memory segment of another processor element. This enables each processor element to perform calculations based on data contained in its local and associated remote memory segments. For example, in one embodiment, each processing element includes first and second local registers for storing data from its local memory and data from its associated remote memory, respectively, and an arithmetic logic unit (ALU) for performing a calculation based on the contents of these registers. This arrangement is particularly beneficial for image processing, where a comparison is made between the value of one pixel and that of another pixel, for example a neighbouring pixel for motion estimation and/or data compression.

In one embodiment, each of the switching elements may be controlled to provide the same memory segment to processor element coupling at the same time. For example, each switching element may first be controlled to couple each processor element to its local memory segment for read access. Secondly, each switching element may be controlled to couple each processor element to its respective remote or neighbouring memory segment for read access. Thirdly, each processor element may be controlled to perform an operation based on the data from its local and associated remote memory segment and subsequently to output the result of the operation. Each switching element may then be controlled to write the result of the operation into either its local or remote memory segment. Advantageously, controlling all of the switching elements to perform the same switching operation avoids memory segment and processor element access conflicts and enables all of the switching elements to be controlled simultaneously by the same control signal or instruction. This form of processing is particularly applicable to digital image processing and allows image pixels to be processed in parallel.

The embodiment shown in FIG. **1**, illustrates an example of a switching arrangement in which each processor element has access either to its local memory segment or to the memory segment to its right (i.e. East). In another embodiment, each switching element may be arranged to provide each processor element access to its local memory segment or to a remote memory segment to its left (i.e. West). In a further embodiment, each switching element may be arranged to permit each processor element selective access to either its local memory segment, a remote (e.g. neighbouring) memory segment to its right (East), or to a remote (e.g. neighbouring) memory segment to its left (West). An example of such a switching arrangement is shown in FIG. **2**.

Referring to FIG. **2**, the switching arrangement **101** according to an embodiment of the present invention, comprises a plurality of switching elements **103**, **105**, **107**. Each switching element includes an input port **109**, **111**, **113**, which is coupled to the output of a selector switch (SL1), which selectively couples the input port either to the local memory (segment) associated with each switching element or the local processor element associated with each switching element, the switching being controlled by a control signal applied to a control signal input port **115**, **117**, **119**. Each switching element further comprises a first port **121**, **123**, **125** (located to the left, or west, of each switching

## 6

element in this embodiment), and a second port **127**, **129**, **131** (situated to the right or east of each switching element, in this embodiment). The east port **127** of the first switching element **103** is coupled to the west port **123** of the second switching element **105**, and the east port **129** of the second switching element **105** is coupled to the west port **125** of the third switching element **107**. Each switching element **103**, **105**, **107** further includes first and second switches SW1, SW2, the first switch SW1 being arranged to couple/de-couple the input port **109**, **111**, **113** of each switching element to the west port **121**, **123**, **125**, and the second switch SW2 being arranged to couple/de-couple the input port **109** to the east port **127**, **129**, **131** of each switching element.

Each switching element **103**, **105**, **107** further includes a second selector switch SL2 connected to each of the input, first and second ports of each switching element, and which is arranged to selectively couple one of the input, first and second ports to an output port **133**, **135**, **137**, under the control of a control signal applied to its control signal input port **139**, **141**, **143**. Each of the output ports **133**, **135**, **137** are coupled to a third selector switch SL3 for selectively switching the output from the second selector switch either to the local memory associated with the switching element or to the local processor element associated with the switching element. Switching of each selector switch SL3 is controlled by a control signal applied to its control signal input port **145**, **147**, **149**.

The switching arrangement **101** shown in FIG. **2** is configurable to permit data transfer between local memory and local processor element, or between the local memory or local processor element associated with one switching element and the local memory or local processor element associated with a neighbouring switching element to which it is coupled. Examples of various modes of operation of the switching element **101** will now be described.

According to a first mode of operation each switching element is configured to permit its local processor element to read from its local memory. In this mode, selector switch SL1 is controlled to couple each of the input ports **109**, **111**, **113** to a respective local memory, switches SW1 and SW2 are both open (as shown), the second selector switch SL2 is controlled to couple the input port **109**, **111**, **113** to the output port **133**, **135**, **137**, and the third selector switch SL3 is controlled to couple the output port **133**, **135**, **137** to the local processor element.

In a second mode of operation, each switching element is configured to write from its local processor element to its local memory, in which case the first selector switch SL1 is controlled to couple the output of its local processor element to the input port **109**, **111**, **113**, the first and second switches SW1, SW2 are both open, the second selector switch SL2 is controlled to couple the input port **109**, **111**, **113** to output port **133**, **135**, **137**, and the third selector switch SL3 is controlled to couple the output port **133**, **135**, **137** to the local memory.

In a third mode of operation, each switching element is configured to transfer data from its local memory to the local processor element of the switching element to its right (east). In this mode, the first switching element SL1 is controlled to couple the input port **109**, **111**, **113** to the local memory, the first switch SW1 of each switching element is open, the second switch SW2 of each switching element is closed to connect the input port **109**, **111**, **113** to a respective east port **127**, **129**, **131**, the second selector switch SL2 is controlled to couple a respective west port **121**, **123**, **125** to the output port **133**, **135**, **137**. In this configuration, the input port **109**,



111, 113 of each switching element is connected to the output port 135, 137 of the neighbouring switching element to its right. Finally, the third selector switch SL3 is controlled to couple the output port 133, 135, 137 to its local processor element.

In another mode of operation, each switching element is configured to write from its local processor element into the local memory associated with a switching element to its right (east). In this case, each switching element is configured in a similar way to that described immediately above in connection with a memory read access, except that the first selector switch SL1 is controlled to couple the local PE to the input port 109, 111, 113, and the third selector switch SL3 is controlled to couple the output port 133, 135, 137 to the local memory.

In another mode of operation, each switching element is configured to transfer data from its local memory to a processor element associated with a switching element to its left (west). In this mode, each first selector switch SL1 is controlled to couple the input port 109, 111, 113 to the local memory, the first switch SW1 is closed to couple the input port 109, 111, 113 to the left port 121, 123, 125, and the second switch SW2 is open. The second selector switch SL2 is controlled to couple the right port 127, 129, 131 of each switching element to the output port 133, 135, 137, so that the input port of each switching element is effectively coupled to the output port of the switching element to its left. Finally, the third selector switch SL3 is controlled to couple the output port 133 to the local processor element.

In another mode of operation, each switching element may be configured to write the output of its local processor element to the local memory associated with the switching element to its left (west). This mode is similar to that described immediately above in connection with a west read access, except that the first selector switch SL1 is controlled to couple the input port 109, 111, 113 to the output of its local processor element, and the third selector switch SL3 is controlled to couple the output port 133, 135, 137 to its local memory.

In each of the switching modes described above, each switching element has the same configuration, and therefore conveniently, the same set of control signals can be applied to the switches SW1, SW2 and the selector switches SL1, SL2, SL3 of each switching element. Therefore, the control lines for corresponding switches and selector switches can be connected together, substantially simplifying and reducing the number of control wires which would otherwise be required if each element was controlled independently of the others.

Any number of switching elements may be used to transfer data between any number of processor elements or their respective memory segments. Generally, one switching element is required for each processor element.

#### Byte-Wise Processing and Data Transfer

In one embodiment, each processor element is capable of processing a single bit, and a plurality of processor elements may be functionally grouped together to process a multiple bit word, for example, a byte (8 bits). A group of processor elements which function to operate on a multiple bit word will be referred to as a computational unit (CU).

FIG. 3 shows an example of a data processor having a plurality of computational units, and a switching arrangement which allows the transfer of multiple bit words between computational units and/or between computational units and the local memories associated with other computational units (and optionally between memory segments).

Referring to FIG. 3, the data processor 201 comprises a plurality of computational units (CU) 203, a memory block 205 and a plurality of groups of switching elements (SEs) 207. In this embodiment, the computational units are arranged in a two-dimensional array having two rows, row 1 and row 2 and n columns. Each computational unit has 8 processor elements allowing the computational unit to perform byte processing, and an associated group of switching elements 207, each containing 8 switching elements, one switching element for each processor element. This configuration is shown in FIG. 4, in which a computational unit 203 includes 8 processing units 211, each connected to a switching element 213. Returning to FIG. 3, each computational unit 203 has 8 memory I/O ports associated therewith, one for each processor element of the computational unit, and in which a respective I/O port is coupleable to a respective processor element through a respective switching element. Thus, in this embodiment, each 8 bit computational unit is pitch-matched to the I/O ports of the memory. In the arrangement shown in FIG. 3, the first set of 8 I/O ports 210 and each alternate set of 8 I/O ports is associated with a successive computational unit 203 in the first row, and the second set of 8 I/O ports 212 and each alternate set of 8 I/O ports is associated with each successive computational unit in the second row.

Each group of 8 switching elements 207 is connected to an adjacent group of switching elements to allow byte transfer of data from one group to an adjacent group, as shown in FIG. 5.

Referring to FIG. 5, four groups of switching elements 215, 217, 219, 221 are shown, in which the first two groups 215, 217 occupy a first row 223 and the third and fourth groups 219, 221 occupy a second row 225. Each group contains eight switching elements labelled 0 to 7. Each group has an associated computational unit and an associated local memory (not shown), wherein each local memory is capable of storing at least one byte of data (containing 8 bits), and each computational unit is capable of byte-wise processing.

In order to perform byte-wise transfer between a computational unit or local memory associated with one group of switching elements and a computational unit or local memory associated with an adjacent group of switching elements, each switching element of one group is connected to a switching element of the adjacent group which has a corresponding bit significance. Thus, as shown in FIG. 5, switching element 0 of the first group 215 is directly connected to switching element 0 of the second, adjacent group 217 (when position 0 may correspond to the least significant bit (LSB)). Similarly, each of the other switching elements 1 to 7 of the first group 215 is connected to a corresponding switching element 1 to 7 of the second group 217 (where position 7 may correspond to the most significant bit (MSB)). These connections allow east-west or west-east byte-wise transfer between the local memory or computational unit associated with the first group of switching elements 215 and the second group of switching elements 217. The switching elements of the third and fourth groups 219, 221 are connected in like manner to permit east to west or west to east byte-wise transfer between the computational unit or local memory associated with the third group of switching elements 219 and the computational unit or local memory associated with the fourth group of switching elements 221.

In the embodiment shown in FIG. 5, the first and third group of switching elements 215, 219 are also connected to permit north-south or south-north byte-wise transfer



between the computational unit or local memory associated with the first group of switching elements **215** and the computational unit or local memory associated with the third computational unit **219**. To permit this byte-wise transfer, each switching element associated with the first group **215** is connected to a switching element of the third group **219** which has corresponding bit significance. Thus, the switching element **0** of the first group **215** is directly connected to the switching element **0** of the third group **219**, and each of the other switching elements **1** to **7** of the first group **215** is directly connected to a corresponding switching element **1** to **7** of the third group, as shown by the arrows **224**. The second and fourth groups of switching elements **217**, **221** are also coupled to permit north to south and south to north byte-wise transfer between the computational unit or local memory associated with the second group of switching elements **217** and the computational unit or local memory associated with the fourth group of switching elements **221**. Again, to enable this byte-wise transfer, each of the switching elements of the second group **217** is connected to a switching element of the fourth group **221** having the same bit significance. Thus, the switching element **0** of the second group **217** is directly coupled to the switching element **0** of the fourth group **221** and each of the other switching elements **1** to **7** of the second group **217** is directly coupled to a corresponding switching element **1** to **7** of the fourth group **221**, as shown by the arrows **226**.

It can be seen from the embodiment shown in FIG. **5**, that the switching arrangement allows byte-wise transfer between the computational unit or local memory associated with one group of switching elements and the computational unit or local memory associated with an adjacent group of switching elements displaced in the east/west direction and a group of switching elements displaced in the north/south direction. The array of groups of switching elements can be extended limitlessly to any size of array so that byte-wise data transfer can be permitted between a computational unit and/or local memory associated with any group of switching elements and the computational unit and/or local memory associated with any other adjacent switching element in the same row or the same column. This arrangement is particularly advantageous in video image processing as it allows a pixel, which is typically described by an 8 bit word to be compared with each of its north, south, east and west neighbours, and each comparison can be performed for all pixels in parallel. Thus, for example, one parallel operation may involve the transfer of a byte of data from the memory associated with each group of switching elements to the computational unit associated with its adjacent southern neighbour, for comparison with a byte stored in the memory of its southern neighbour. Another parallel operation may involve the transfer of a byte from a local memory associated with each group of switching elements into the computational unit associated with its immediate northern neighbour for comparison with a byte stored in the memory associated with its northern neighbour. Other parallel operations including for example east and west byte-wise transfers may also be performed. In addition to performing north to south (or south to north) and east to west (or west to east) byte-wise transfers, it may also be desirable to perform byte-wise transfers between neighbouring groups of switching elements on the diagonal. An example of a two dimensional array of computational units in which byte-wise transfers between a computational unit and its nearest eight neighbours is shown in FIG. **6**.

FIG. **6** shows a two-dimensional, three-by-three array **251** of nine computational units, in which the central computa-

tional unit **253** has 8 nearest neighbours, which include its adjacent computational units **255** to the north and **257** to the south in the same column, its adjacent computational units **259**, to the west, and **261** to the east in the same row, and its immediately adjacent computational units **263** to the north-west and **265** to the south-east on one diagonal, and its immediately adjacent computational units **267** to the north-east and **269** to the south-west, on the other diagonal. In order to permit data transfer between the central computational unit **253** or its local memory and the computational unit or local memory of each of its 8 nearest neighbours, each computational unit and local memory has an associated switching element. In one embodiment, the switching element associated with the central computational unit **253** may be connected to each of the switching elements associated with each of its nearest neighbours and each switching element may have 8 input-output ports or buses extending therefrom to connect to each of its neighbours, as shown schematically by the arrows **271** in FIG. **6**. An example of an interconnect scheme in which each switching element is connected to each of its nearest neighbours by one of eight buses, is shown in FIG. **7**. FIG. **7** shows a two-dimensional, three-by-three array **273** of switching elements **275**, in which each switching element has 8 ports or buses **277** extending therefrom for connecting to each of its nearest neighbour switching elements (for example to a bus or port of each element).

FIG. **8** shows an embodiment of a switching element which may be implemented in the interconnect scheme of the embodiment shown in FIG. **7**. The switching element comprises a first multiplexer **240** having nine inputs **242** and an output **244**. Eight of the inputs are for coupling to neighbouring switching elements and the remaining input is for coupling to the local unit, for example a memory or processor element output. The switching element further includes a second multiplexer **246** having a first input **248** coupled to an output port of the local PE, and a second input port **250** for receiving data from the local unit, e.g. the local memory. The output of the second multiplexer is broadcast to other switching elements. The switching element further includes a third multiplexer having a first input connected to the output of the first multiplexer, and a second input coupled to an output of the local processor element. The output of the third multiplexer is coupled to the local memory input.

An embodiment of a switching arrangement which advantageously allows the number of buses to be reduced, while still retaining the connectivity of a local memory and/or processor element to its nearest 8 neighbours will now be described below. Referring to FIG. **9**, a switching element **301** has four input/output ports **303**, **305**, **307**, **309**. In this embodiment, the third and fourth input/output ports **307**, **309** lie on a first north to south axis and the first and second input/output ports **303**, **305** lie on a transverse axis, which in this embodiment is a substantially orthogonal, east to west axis which enables other similar switching elements to be connected to each of the input/output ports in a two-dimensional grid pattern (which will be described below), although other arrangements are also possible.

The switching element **301** further includes four switches **311**, **313**, **315**, **317**, the first switch **311** being connected to the first input/port **303**, the second switch **313** being connected to the second input/output port **305**, the third switch **315** being connected to the third input/output port **307** and the fourth switch **317** being connected to the fourth input/output port **309**. Each switch is switchable between three terminals **319**, **321**, **323**, and further includes at least one



## 11

neutral position in which the switch is not connected to any of the three terminals. The switching element **301** further includes an input port **325** which is connected to each middle terminal **321** of the four switches. Each one of the other two terminals of each switch is connected to the terminal of an orthogonal switch on the same side. Thus, the first terminal **319** associated with the first switch **311** is connected to the third terminal **323** of the fourth switch **317**. The third terminal **323** associated with the first switch **311** is connected to the first terminal **319** of the third switch **315**. Similarly, the first terminal **319** of the second switch **313** is connected to the third terminal **323** of the third switch **315**, and the third terminal **323** of the second switch **313** is connected to the first terminal **319** of the third switch **317**.

The switching element further includes an output selector switch **327** having four inputs A, B, C and D and an output **329**. A respective one of the four inputs A, B, C and D is connected to a respective one of the interconnected switch terminal couples **319**, **323** also labelled A, B, C and D (although these interconnections are not shown for clarity). This embodiment further includes a second selector switch **341** having two inputs **343**, **345** and an output **347**. The first input **343** is connected to the output **329** of the first selector switch **327** and the second input **345** is connected to the input port **325** of the switching element (although this connection is also not shown for clarity).

The switching element **301** is capable of directing data received at the input **325** either to local elements (e.g. local memory or local processor element) associated with the switching element, or to one of the four input/output ports **303**, **305**, **307**, **309**. The input port **325** may be coupled to receive data from its associated local memory, or the output of its associated local processor element, and a switch may be provided to selectively couple the input port **325** to one of the associated local memory and an output of the associated processor element.

The switching element **301** is also capable of directing data received at any one of its four input/output ports **303**, **305**, **307**, **309** to the output port **329** of the first selector switch **327** and to the second output port **347** of the second selector switch **341**, depending on its state. The switching element is also capable of transferring data received at the input port **325** to the output port of the second selector switch **347** again depending on its state. In one embodiment, the output **347** of the second selector switch **341** is connected to the input of the local processor element associated with the switching element **301**. Thus, in one mode of operation, the switching element is capable of transferring data received at its input **325** to its output **347**, for example to enable the transfer of data from its local memory to its local processor element. In another mode of operation, the switching element is capable of transferring data received at any one of the four input/output ports to its associated local processor element. Examples of the various possible operating modes of the switching element **301** will now be described below.

To perform a data transfer to the south, the fourth switch **317** is controlled to couple the input port **325** to the fourth (south) input/output port **309** so that data from the local unit (e.g. local memory or local processor) is transferred to the south port **309**. At the same time, the third switch **315** is controlled to couple the third (north) input/output port **307** either to its first terminal **319** or to its third terminal **323**, thereby coupling the north port **307** either to the first input A or the second input B of the first selector switch **327**. The first selector switch **327** is controlled to couple the input port to which the third switch **315** is connected, to the output port

## 12

**329**. The second selector switch **341** is controlled to connect its first input port **343** to the output port **347**, which is connected to an input of the local unit (e.g. memory or local processor) associated with the switching element **301**. Thus, in this mode of operation, the switching element is configured to transfer data from the local unit to the south port **309** and to transfer data into the local unit via the north port **307**.

In another mode of operation, the switching element **301** may be controlled to transfer locally derived data to its north neighbour and simultaneously to receive data derived from its southern neighbour. In this mode, the third switch **315** is controlled to connect the north input/output **307** to the input port **325** of the switching element **301**, and the fourth switch **317** is controlled to connect the south port **309** to one of the first and third terminals **319**, **323** associated with the fourth switch **317** to connect the south port **309** to one of the third or fourth inputs C, D of the first selector switch **327**, and the second selector switch is controlled to output the data to the local unit.

In another mode of operation, the switching element may be configured to transfer locally derived data to its east neighbour and to receive data from its west neighbour. In this mode of operation, the second switch **313** is controlled to couple the input **325** of the switching element **301** to the east port **305**, and the first switch **311** is controlled to connect the west port **303** to one of the first or third terminals **319**, **323** associated with the first switch **311** to couple the west port **303** to one of the first and third input ports A, C of the first selector switch **327**. The first selector switch **327** is controlled to connect the appropriate input port A, C to its output port **329** and the second selector switch **341** is appropriately controlled to output the data received at the west port **303** to the local unit.

In a fourth mode of operation, the selector switch **301** is configured to transfer data to its west neighbour and to receive data from its east neighbour. In this mode, the first switch **311** is controlled to couple the input port **325** of the switching element **301** to the west port **303**, and the second switch **313** is controlled to couple the east port **305** to one of the first and third terminals **319**, **323** associated with the second switch **313**, so that the east port **305** is coupled to one of the second and fourth inputs B, D of the first selector switch **327**. The first and second selector switches **327**, **341** are appropriately controlled so that data received at the east port **305** is transferred to an input of the local unit (e.g. local memory or local processor element).

In each of the modes described above for a north to south, south to north, east to west and west to east transfer, the switching element **301** assumes both an output mode for transferring data out from one of its north, south, east or west ports and an input mode for receiving data at the respective opposite port. The switching element **301** can also be configured to operate in any one of four further modes to allow the transfer of data received at any one of its input/output ports **303**, **305**, **307**, **309** to an adjacent orthogonal input/output port **303**, **305**, **307**, **309** for transferring data between diagonally disposed nearest neighbours. To perform a diagonal data transfer, each switching element **301** is configured to operate in an input mode, for receiving data at one of its input/output ports **303**, **305**, **307**, **309** and transferring the received data to the local unit, an orthogonal output mode, in which locally derived data is output at a port which is orthogonal to the input/output port established for the input mode, and a by-pass or pass-through mode, in which the other two adjacent orthogonal input/output ports are interconnected to allow the transfer of data received at one of these ports to the other remaining port. The switching



## 13

element **301** is capable of adopting all three modes simultaneously to enable diagonal (e.g. NE, NW, SE, SW) nearest neighbour or more remote diagonal data transfers.

An example of how switching elements may be configured to enable a diagonal data transfer will now be described with reference to FIG. 10.

FIG. 10 shows an array of three switching elements **351**, **353**, **355**, each of which is similar to the switching element **301** shown in FIG. 9, and like parts are designated by the same reference numerals. The switching elements are interconnected such that the east input/output port **305** of the first switching element **351** is connected to the west input/output port **303** of the second switching element **353**, and the north input/output **307** of the second switching element **353** is connected to the south input/output port **309** of the third switching element **355**. Thus, the second switching element **353** constitutes the east neighbour (which may or may not be the nearest east neighbour) to the first switching element **351**, and the third switching element **355** constitutes the Northeast neighbour (which may or may not be the nearest Northeast neighbour) to the first switching element **351**. It is to be noted that the array of three switching elements shown in FIG. 10 may be part of a larger array of switching elements and that FIG. 10 simply serves to illustrate an arrangement of switching elements which enable a transfer between one switching element and another switching element on its Northeast diagonal.

To perform a transfer of data locally derived at the third switching element **355** to the first switching element **351**, the third switching element **355** assumes an output mode, in which the third switch **315** is controlled to connect the input port **325** of the third switching element **355** to its fourth (south) input/output port **309**, so that locally derived data is transferred onto the output port **309**. The second switching element **353** assumes a pass-through mode, in which the third switch **315** is connected to its associated first terminal **319**, and the first switch **311** of the second switching element **353** is connected to its associated first terminal **303**, thereby connecting the third (north) input/output port **307** of the second switching element to its first (west) input/output port **303**. The first switching element **351** assumes an input mode, in which the second switch **313** of the first switching element **351** is controlled to connect the second (east) input/output port **305** to the third terminal **323** associated with its second switch **313** so that the east input/output port **305** is connected to the fourth input port D of the selector switch **327**. The selector switch **327** is controlled to connect the fourth input D to its output port **329** (not labelled on FIG. 10). Thus, it can be seen that the first, second and third switching elements are configured to provide a continuous path from the input port **325** of the third switching element **355** to the output port **329** of the first switching element **351**.

It is to be noted in this operating mode that each of the switching elements **351**, **353**, **355** may all assume the same three operating modes: output mode, pass-through mode and input mode, so that each switching element assumes an output mode in which a respective input port **325** is connected to a respective south port **309** a pass-through mode, in which the third and first switches are controlled to couple a respective north port **307** to a respective west port **303**, and an input mode, in which a respective east port **305** is connected to a respective output port **329**. This symmetrical configuration of all of the switching elements allows same direction, parallel, diagonal transfers between diagonally disposed switching elements in the array. Since each switching element is configured in the same way to perform a given diagonal transfer, all of the switching elements may be

## 14

configured by the same set of control signals, which enables the control of data transfers between the switching elements to be considerably simplified.

Advantageously, as each switching element is designed to enable data to be transferred from any of its input/output ports to either of its adjacent, orthogonal input/output ports, an effective diagonal data transfer can be performed using the same buses which are used for north-south and east-west data transfers, thereby obviating the need for additional diagonal buses between diagonally disposed switching elements. Thus, the switching elements allow data transfer between a given switching element and its nearest eight neighbours using only four buses rather than eight, thereby considerably simplifying and reducing the cost and complexity of the additional interconnects, which would otherwise be required. This arrangement also alleviates the problem of superimposing or combining a diagonal interconnect system to a "Manhattan geometry", in which the interconnect wires are drawn orthogonally, i.e. in the north, south, east and west directions.

In the embodiments of the switching elements shown in FIGS. 9 and 10, each input mode from any of the input/output ports **303**, **305**, **309**, **311** has two possible configurations. The first configuration is illustrated in FIG. 10, in which for the input mode associated with the transfer of data into the switching element from the east input/output port **305**, the second switch **313** is connected to the third terminal **323** associated with the second switch, so that the east input/output port is connected to the fourth port D of the selector switch **327**. In the alternative configuration of this input mode, the second switch **313** may be controlled to couple to the first terminal **319** associated with the second switch **313** so that the east input/output **305** is connected to the second input port B of the selector switch **327**, in which case the selector switch is controlled to connect the second input port B to its output port **329**.

The embodiments of the switching elements shown in FIGS. 9 and 10 allow any diagonal transfer to be performed via all possible routes. In the case of a transfer to a switching element from a Northeast neighbour, one route is to pass the data via its east neighbour, as shown in FIG. 10, and the second route is to pass the data via its north neighbour, for example north neighbour **357** shown schematically in FIG. 10.

In another embodiment, each of the switching elements may be simplified to permit a diagonal transfer using only one of these two possible routes. An example of another embodiment of a switching element is shown in FIG. 11, and an example of an array of such switching elements is shown in FIG. 12. The switching element shown in FIG. 11 is similar to that shown in FIG. 9, and like parts are designated by the same reference numerals. The switching element **301** comprises four input/output ports **303**, **305**, **307**, **309** having associated switches **311**, **313**, **315**, **317**. Each switch has first and second terminals **319**, **321**, the first terminal **319** (also labelled N, E, S and W) being connected to a respective one of four input terminals, also labelled N, E, S, W of a first selector switch **327**. The first terminal **319** associated with each switch is also connected to the input/output port connected to its adjacent switch displaced in the clockwise sense. Thus, the first terminal **319** associated with the first switch (connected to the first (west) input/output port **303**) is connected to the third (north) input/output port **307**, the first terminal **319** associated with the third switch **315** is connected to the second (east) input/output port **305**, the first terminal **319** associated with the second switch **313** is connected to the fourth (south) input/output port **309**, and



## 15

the first terminal **319** of the fourth switch **317** is connected to the first (west) input/output port **303**. The second terminal **321** of each switch is connected to the input port **325** of the switching element.

Each switch is switchable between its associated first and second terminals **319**, **321**, and a third, neutral or floating state (e.g. between the two terminals), as shown in FIG. **11**.

FIG. **12** shows an array of four switching elements of the kind shown in FIG. **11** and will be used to illustrate a diagonal transfer from a Northeast neighbour. The switching elements are arranged such that the north port **307** of the first switching element **371** is connected to the south port **309** of the second switching element (north neighbour) **373**, and the east port **305** of the second switching element **373** is connected to the west port **303** of the third switching element **375**, and which constitutes the Northeast neighbour of the first switching element **371**.

To transfer data from the third switching element **375** to the first switching element **371**, the third switching element adopts an output mode in which the first switch **311** couples the input port **325** to the first (west) input/output **303**, the second switching element **373** adopts a pass-through mode, in which the second switch **313** connects the second (east) port **305** to the fourth (south) input/output port **309** and the first switching element **371** adopts an input mode, in which the third switch **315** connected to the third (north) input/output port **307** is in its neutral (or floating) position and the selector switch **327** is controlled to couple the first input port **N** to its output port. In this way, data can be transferred from the local unit (e.g. local memory or processor element) associated with the third (Northeast) switching element **375** to the local unit (e.g. local memory or processor element) associated with the first switching element **371**.

It is to be noted that the output mode adopted by the third switching element **375**, the pass-through mode adopted by the second switching element **373** and the input mode adopted by the first switching element **371** may all be adopted by all switching elements, as shown in FIG. **12**. This enables data to be transferred to each of the second and third switching elements from their respective Northeast neighbours, in an extended array.

It is to be noted that the array shown in FIG. **12** can be extended to any size, and that the switching elements enable data to be transferred in parallel in any of **N**, **S**, **E**, **W**, **NE**, **NW**, **SE**, **SW** directions.

Embodiments of the switching element may be implemented using any suitable components, and fabricated using any suitable technology (e.g. CMOS and/or passgate). For example, the switching element may comprise any suitable logic circuitry which can be controlled to perform the required function. An example of one implementation of the switching element of FIG. **11** is shown in FIG. **13**, where corresponding parts are designated by the same reference numerals.

Referring to FIG. **13**, a switching element **301** has first, second, third and fourth input/output ports **303**, **305**, **307**, **309**, each of which has an associated switch **311**, **313**, **315**, **317**, as for the embodiment of FIG. **11**. Each switch comprises a 2 to 1 multiplexer **350** having a first input port **352** connected to the input port **325** of the switching element, and a second input port **354** connected to the first terminal **319** of each switch. Each switch further comprises a tri-stateable inverter **356** whose input **358** is coupled to the output port **360** of the 2 to 1 multiplexer **350**. The output port **361** of the tri-stateable inverter is connected to a respective input/output port **303**, **305**, **307**, **309**, with which the switch is associated.

## 16

The switching element **301** further includes first, second, third and fourth inverters **362**, **364**, **366**, **368**, each having an input port **370** connected to a respective input/output port **303**, **305**, **307**, **309**, and an output port **372** connected to a respective first terminal **319** of the adjacent switch to its left, so that, for example, the output port **372** of the inverter connected to the north port **307** is connected to the first terminal of the first switch **311**.

The switching element **301** also comprises a first selector switch **327**, which may comprise a multiplexer, having four inputs labelled **N**, **E**, **S** and **W** which are connected to a respective terminal **N**, **E**, **S** and **W** coupled to a respective input/output port **307**, **305**, **309**, **303** via an inverter **302**. The first selector switch **327** has two control signal input ports **328**, **330** for receiving a control signal for selectively switching one of the inputs **N**, **E**, **S**, **W** to the output **329**. In one embodiment, the output of the first selector switch **327** could be connected to the local processor element associated with the switching element. In another embodiment, the output of the first selector switch **329** could be coupled to the local memory associated with the switching element. In another embodiment, a further selector switch (not shown) may be provided to selectively couple the output of the first selector switch **327** to one of an input to the local memory and an input to the local processor element. In the embodiment shown in FIG. **13**, a second selector switch **341** is optionally provided, which may also comprise a multiplexer, and has first and second input ports **343**, **345**, the first input port **343** being connected to the output port **329** of the first selector switch **327**, and the second input port **345** being connected to the input port **325** of the switching element **301**. The output port of the selector switch **341** may be coupled to an input of the processor element associated with the switching element **301**. The second selector switch **341** has a control signal input port **342** for selectively connecting the output port to one of the first and second input ports **343**, **345**, in response to a control signal. The second selector switch enables data to be transferred either locally between the local memory and the local processor element or from one of the input/output ports of the switching element into the local processor element.

The 2 to 1 multiplexer **350** of each switch has a control signal input port **374** for receiving a control signal which selectively couples its output port **360** to one of the input port **325** of the switching element **301** and the input/output port which is adjacent and displaced in a clockwise direction relative to the input/output port to which the output of the 2 to 1 multiplexer is connected through its respective tri-stateable inverter **356**.

The tri-stateable inverter **356** of each switch **311**, **313**, **315**, **317** has a control signal input port **376** for receiving a control signal which, with the signal at the input port controls the signal output from the inverter, according to the table shown in FIG. **14**. As can be seen from the table, the tri-stateable inverter can assume a neutral floating position, which implements the neutral or floating position of each switch of the switching element shown in FIG. **11**. In this embodiment, the tri-stateable inverter is controlled to adopt this state when the control signal is low (e.g. zero) as shown in the table. When the control signal is in the other state (i.e. high or one) the tri-stateable inverter functions as a simple inverter, by inverting the input signal.

The inverters are arranged such that on transferring data between one switching element and any one its eight neighbours (i.e. **N**, **E**, **S**, **W**, **NE**, **SE**, **SW** and **NW**), the data always passes through a minimum of two inverters and, always passes through an equal number of inverters to maintain



signal polarity. Advantageously, passing binary data through an inverter pair enhances the signal strength and signal definition, and also enhances the definition of the high to low or low to high transition edge, and thus functions as a repeater.

In an array of switching elements of the kind shown in FIG. 13, data which is transferred between one switching element and any one of its north, south, east or west neighbours, passes through two inverters, one being provided by a tri-stateable inverter 356 on passing the data from the input port 325 to one of the input/output ports 303, 305, 307, 309, and the other being provided by a simple inverter 364 on passing the data to the opposite input/output port to the output port 329 of the neighbouring switching element.

In transferring data between one switching element and a neighbouring switching element on a diagonal (e.g. NE, SE, SW, or NW), the data passes through four inverters, the first being provided by a tri-stateable inverter 356 between the input port 325 of one switching element and the selected input/output port 303, 305, 307, 309, the second and third being provided by a simple inverter 362 and a tri-stateable inverter 356, respectively, between adjacent orthogonal ports of the intermediate switching element, which effectively turns the data through 90°, and the fourth being provided by the simple inverter 364 between the input/output port 303, 305, 307, 309 and the output port 329 of the destination switching element.

In the embodiment of the switching element 301 shown in FIG. 13, a total of 11 (SOSO (bar), REN, REN(bar), UEN, UEN(bar), S1, S2, Den) control signals are required to control all of the switching components. However, the switching element may be implemented such that the control signals required for certain switching components can always be the inverse of that required for other switching components. The number of externally applied control signals can be reduced by providing local inversion. The switching element shown in FIG. 13 can be controlled to assume any configuration required for transferring data between its eight neighbours using just six control signals.

In the implementation shown in FIG. 13, the control signals applied to the 2 to 1 multiplexer 350 of the switches associated with the first and second input/output ports 303, 305 can always be the same. Similarly, the control signals applied to the 2 to 1 multiplexers 350 associated with the third and fourth input/output ports 307, 309 may also always be the same and can always be the inversion of the control signal applied to the other two 2 to 1 multiplexers associated with the first and second input/output ports. Thus, only a single external control signal SO is required to control all 2 to 1 multiplexers 350, this single control signal being split locally for the 2 to 1 multiplexers 350 associated with the first and second input/output ports 303, 305, and locally inverted and split to control the other two 2 to 1 multiplexers 350 associated with the third and fourth input/output ports 307, 309 (or vice versa). Therefore, this implementation reduces the number of externally applied control signals by three.

The embodiment of the switching element 301 shown in FIG. 13 is arranged such that the control signal, REN, applied to one of the tri-stateable inverters 356 of the first and second switches 311, 313 is always the inversion of the signal applied to the other tri-stateable inverter. Likewise, the switching element 301 may be implemented such that the control signal, UEN, applied to one of the tri-stateable inverters of the third and fourth switches 315, 317 is always the inversion of that applied to the other tri-stateable inverter. In this way, the control signal for controlling the

tri-stateable inverters associated with the first and second input/output ports may be inverted locally, and the non-inverted signal applied to one tri-stateable inverter, and the inverted signal applied to the other. This enables the number of required control signals to be reduced by one. Similarly, a single control signal for controlling the tri-stateable inverters 350 associated with the third and fourth input/output ports may also be inverted locally, and the non-inverted signal applied to one of the these two tri-stateable inverters, and the inverted signal applied to the other. This enables the number of required externally applied control signals to be reduced by a further one, so that the total number of external control signals is reduced by a total of five from eleven to six. The control signals required to configure the switching element 301 to transfer data between one switching element and another in any of the eight possible directions is given in Table 2, of FIG. 15. This table includes a by-pass mode, in which data is transferred locally, for example from the local memory to the local processor element.

#### Data Transfer Functions

Embodiments of the switching element may be arranged for different data transfer capabilities, examples of which will now be described with reference to FIGS. 16 and 17.

In one implementation, each switching element may be capable of transferring data from its local memory space to the input of a processing element associated with a neighbouring switching element. Referring to FIG. 16, this implementation is provided by coupling the output of the local memory space to the input port 325, and by coupling the output port 329 to an input of the local processor element. In a second implementation, each switching element may be arranged to permit the transfer of data from a register (or arithmetic logic unit (ALU) output) to the input of a processor element (e.g. register or ALU) associated with a neighbouring switching element. Again, referring to FIG. 16, this functionality may be implemented by coupling the input 325 of each switching element to an output of its local processor element (e.g. register or ALU output), and coupling the output port 329 of the switching element to an input (e.g. register input or ALU input) of its local processor element.

In a third implementation, each switching element may be arranged to enable the transfer of data from a processor element associated with a neighbouring switching element to its local memory. Referring again to FIG. 16, this functionality may be implemented by coupling the input 325 of the switching element to an output (e.g. register or ALU) of its local processor element, and coupling the output 329 of each switching to an input of its local memory.

In a fourth implementation, each switching element may be adapted for transferring data either from its local memory space or from an output from its local processor element (e.g. register or ALU output) to a processor element associated with a neighbouring switching element (i.e. a combination of the first and second implementations described above). Referring again to FIG. 16, this functionality may be implemented by providing a 2 to 1 selector switch (multiplexer) 302 which is switchable between two inputs 304, 306 and coupling the local memory to one of the inputs 304 and an output of the local processor element to the other input 306. The output 308 of the selector switch 302 is coupled to the input 325 of the switching element, and the output 329 of the switching element is connected to an input of its local processor element.

In a fifth implementation, each switching element may be arranged to transfer data from its local memory space to a PE



associated with a neighbouring switching element or to transfer data from a PE associated with a neighbouring switching element to its local memory space (which is a combination of the first and third implementations described above). Referring to FIG. 17, this functionality may be implemented by providing a 2 to 1 selector switch **302** having switchable inputs **304**, **306**, one connected to the local memory and the other connected to an output of the local processor element, as for the embodiment shown in FIG. 16 and connecting the output **308** of the selector switch **302** to the input **325** of the switching element. This arrangement enables data derived locally either from the local memory or local processor element to be transferred out of the switching element to a neighbouring switching element. The output port **329** of the switching element is arranged to be coupleable to an input of its local PE or an input of its local memory. Referring to FIG. 17, the output **329** of the switching element is connected to one of the two input ports of a second 2 to 1 output selector switch **341**, the output of which is connected to an input of the local processor element. The other input is connected to the local memory, for example via the input port **325** of the switching element to enable transfer from local memory to local processor element. The output port **329** is also coupled to one of the two inputs of a third 2 to 1 output selector switch **342** whose output is connected to the local memory, to enable incoming data from a neighbouring switching element to be written to the local memory. The second input of the third selector switch **342** is connected to an output of the local processor element to enable data output from the local PE to be transferred directly to the local memory.

It is to be noted that, in addition to providing a read function from a local memory to a processor element of a neighbouring switching element, and a write function from the local memory of a neighbouring switching element to its local memory, the circuit of FIG. 17 also enables the transfer of data between a local processor element and a neighbouring processor element. This functionality may be regarded as a combination of the first, second and third implementations.

In a seventh implementation, each switching element may be arranged for selectively, either transferring data from its local processor element to the processor element of a neighbouring switching element or to transfer data from its local processor element to the memory associated with a neighbouring switching element. Referring again to FIG. 17, this functionality may be implemented by coupling an output of a local processor element (e.g. register or ALU) to the input **325** of the switching element, and selectively coupling the output of the switching element to one of the local processor element and the local memory, which may for example be achieved by the same output circuit arrangement shown in FIG. 17.

FIG. 18 shows another embodiment of a switching element which is capable of transferring data between its nearest eight neighbours, in the row, column and diagonal directions of a two dimensional array. The switching element **401** has first, second, third and fourth input/output ports **403** (N), **405** (E), **407** (S) and **409** (W), each of which may be connected to one port of a similar switching element of its nearest four neighbours. These input/output ports have a similar function to the input/output ports of the embodiments of the switching elements described above. The switching element **401** also includes an input **425**, which may for example be coupled to either one or both of a local memory and local processor associated with the switching element, and an output **429**, which may be coupled to one or

both of a local memory and local processor element associated with the switching element.

The switching element **401** has a first group **431** of four switches L, J, K and I which enable data to be transferred from one input/output port to an adjacent input/output port when the switching element is placed in by-pass mode. The switching element **401** further includes a second group **433** of switches P, O, C and M, a respective one of which is switchable to a respective pair of switches of a third group **435** of switches containing four switch pairs XA, VU, TB and RQ. The first two pairs of switches in the third group, XA and VU determine which of the first and second input/output ports couples to the input **425** and the output **429**. Similarly, the third and fourth switch pair of the third group TB, RQ determine which of the third and fourth input/output ports **407**, **409** couple to the input port **425** and output port **429**. A fourth group **437** of four switches Z, Y,  $\bar{Z}$  and  $\bar{Y}$  are connected such that the first switch Z is connected to the terminal of the first switch in each of the first and second switch pairs of the third group of switches X, V, and the second switch Y of the fourth group is connected to the switch terminals of the second switch of the first and second switch pairs A, U. Thus, the first and second switches Z,  $\bar{Y}$  of the fourth group **437** together with the first two switch pairs of the third group **435** selectively couple either the first and second input/output ports **403**, **405** to either the input port **425** or the output port **429**. Similarly, the third switch Z of the fourth group **437** of switches is connected to the terminals of the first switches T, R in each of the third and fourth switch pairs of the third group of switches, and the fourth switch Y of the fourth group is connected to each of the terminals of the second switches B, Q of the third and fourth switch pairs. The third and fourth switches Z, Y of the fourth group, in conjunction with the third and fourth switch pairs of the third group **435** selectively couple the third or fourth input/output port **407**, **409** to one of the input and output ports **425**, **429**. An input access switch **439** is provided between the input **425** and the terminals of the first and third switches Z,  $\bar{Z}$  of the fourth group to switchably couple the input **425** for an inter-switching element transfer, and an output access switch **441** coupled to the terminals of the second and fourth switches Y,  $\bar{Y}$  of the fourth group of switches for coupling the output of the switching element for inter-switching element transfer. A local access switch **443** is also provided for direct local access between the input **425** and the output **429**, for example to enable direct local transfer between a local memory and a local processor element. It is to be noted that in operation, when the local access switch **443** is closed, both input and output access switches **431**, **433** are open, and vice versa.

One of the main differences between this embodiment and the embodiments described previously, is that the input and output **425**, **429** are switchably connected through a local access switch **443**, which may comprise a toggle switch, instead of a 2 to 1 by-pass multiplexer. A second difference between the switching element structure of FIG. 18 and that of the previously described embodiments, is that the input **425** is coupleable to each of the first, second, third and fourth input/output ports through a branched communication network rather than directly through a switch.

FIG. 19 shows a switching element according to another embodiment of the present invention. The switching element **402** is similar to that shown in FIG. 18, and like parts are designated by the same reference numerals. The main differences between this switching element **402** and that shown in FIG. 18 are that the second group **433** of switches P, O, C and M have been replaced by tri-state toggle switches P,



## 21

Q, R and T, each of which has a first position which connects each of the first, second, fourth input/output ports **403**, **405**, **409** directly to the input **425** of the switching element via an input access switch **439**. Each of the switches is switchable to a second position to place the switching element in one of four modes, in which a selected one of the four input/output ports **403**, **405**, **407**, **409** is coupled to the output port **429**. The switching element **402** further includes a third group **435** of switches **404**, **406**, **408**, **410**, the first two of which select between the first and second input/output ports **403**, **405** and the third and fourth of which select between the third and fourth input/output ports **407**, **409**. In this embodiment, the second switch is controlled by the inverse control signal applied to the first switch, and the third and fourth switches **408**, **410** are controlled by the same control signals as the first and second switches **404**, **406**, so that the third group of switches has two outputs, one of which is coupled to one of the first and second input/output ports **403**, **405** and the other of which is connected to one of the third and fourth input/output ports **407**, **409**.

The switching element **402** further includes a fourth group **437** of two switches **412**, **414**, which selectively couple one of the two outputs of the third group of switches to the output port **329** of the switching element via the output access switch **441**. In this embodiment, the fourth group **437** of two switches may conveniently be controlled by applying a desired control signal to one of the switches and the inverse of the control signal to the other switch.

Returning to FIG. 3, a data processor apparatus according to an embodiment of the present invention, which may comprise a SIMD processor comprises an array of computational units, each having access to an associated local memory segment contained within a memory block. The data processor further includes an array of switching elements, which may comprise any switching elements described above, as well as others, which enables data to be transferred between one computational unit and/or its local memory and another computational unit and its local memory. The array of computational units and the memory block may have any size. However, the size of the memory block may be limited depending on the application of the processor, since the access time for a read or write operation from or to a memory generally increases with memory size. The power drawn by the memory for read and write operations also increases with memory size. Memory access time may also depend on other factors such as the number of I/O ports. Therefore, a memory of a given size will have a minimum access or latency period. Advantageously, embodiments of the present invention provide a data processor apparatus in which the effective memory size may be increased to that required by the particular application, while retaining the desired memory access speeds and reducing power requirements. In one embodiment, this is achieved by selecting a memory block which provides the required memory access speeds and incorporating into the data processor as many memory blocks as necessary to provide the required memory size. An embodiment of a data processor having a plurality of memory blocks is shown in FIG. 20.

Referring to FIG. 20, the data processor apparatus **501**, which may comprise a SIMD processor comprises a first, second, third and fourth memory block **503**, **505**, **507**, **509**, each having a respective associated group **511**, **513**, **515**, **517** of computational units **519**. Each computational unit comprises one or more processor elements, and may comprise for example 8, 16 or 32 processor elements for performing 8, 16 or 32 bit word processing. Each computational unit has

## 22

an associated group of switching elements **521** which is arranged to provide data transfer between the computational unit (or its associated memory) and at least one other computational unit (or associated memory). In the present embodiment, the computational units **519** of each group **511**, **513**, **515**, **517** are arranged in a two-dimensional array having two rows **523** (Row 1) and **525** (Row 2) and n columns **527**. The groups of switching elements associated with each row of computational units are also arranged in rows **527** (Row 1), **529** (Row 2), and each group of switching elements in each row is connected to its adjacent group(s) of switching elements to provide lateral or east to west, (or west to east) data transfer between their associated computational units contained in each row **523**, **525**. The two groups of switching elements in each column are also interconnected to provide north to south and south north data transfer between the two computational units in each column, as indicated by the arrows **531**.

In this embodiment, the first two-dimensional array of computational units associated with memory block A **503** is effectively expanded from an array containing two rows and n columns into an array containing four rows and 2n columns by adding a second memory block B **505** and second array of associated computational units **513** below the first memory block **503**, and adjacent third and fourth memory blocks **507**, **509** and associated arrays of computational units **515**, **517** to the side. Groups of memory elements in corresponding columns and contained in the second row associated with memory block A and the adjacent first row associated with memory block B are interconnected, as shown by the arrows **533**, across memory block B to enable data to be transferred between the second row of computational units or their local memory, associated with memory block A and the first row of computational units or their local memory associated with memory block B.

The groups of switching elements contained in the nth column associated with memory blocks A and B are connected to the groups of switching elements of corresponding rows contained in the first column of the two groups of switching elements associated with memory blocks C and D, as indicated by the arrows **535**, to enable data to be transferred between computational units (and/or their associated memory), contained in the nth column associated with memory blocks A and B, and the adjacent first column associated with memory blocks C and D. Thus, a module containing a memory block of the required size and an associated array of computational units may be expanded into an enlarged integrated array, by adding any number of further modules simply by interconnecting the groups of switching elements at the edges of adjacent modules, as shown in FIG. 20.

In designing a module, the size of memory segment per I/O port, and the number of computational units required is generally determined by the application that is to be run on the processor. For example, for MPEG4 decoding, the inventors have determined that four kilobits of memory per I/O port and an array of four by twenty-four eight bit computational units are required. The number of required rows in each memory depends on the column decoder selected. For example, using an eight to one column decoder (or multiplexer), a memory having 512 rows is required to obtain 4 kb per I/O port ( $8 \times 512 = 4,096$  bits, 4 kb). Having determined the number of rows and the required array size, the number of I/Os in a memory can then be determined.

For example, if the processor runs at 100 MHz, a memory read must be completed in 10 ns. The inventors have found that, after simulation, a memory with 192 I/Os and 512 rows



deep has a latency period of 4 ns. Each switching element may have a latency of for example of 1.5 ns, and therefore the latency period of a north to south or east to west transfer, which requires two switching elements, is about 3.0 ns, and the latency period of a diagonal (i.e. NE, SE, SW, NW) read, which requires three switching elements, is about 4.5 ns. Adding the memory latency period of 4 ns to the worst case switching element latency (i.e. a diagonal read), data can be transferred to a neighbouring computational unit with at least 1.5 ns to spare.

Thus, by adopting a processor architecture in which the required size of memory is provided by a plurality of memory blocks, the performance of the processor can be optimized for the application, and at the same time scaled to any size.

A data processor according to another embodiment of the present invention comprises a plurality of processor elements associated with a memory segment. In one embodiment, each processor element is coupled to the same memory port (for at least one of read and write memory access). An input port of each processor element may be coupled to a common read line, which is coupled to a memory output port and/or an output port of each processor element may be coupled to a common write line, which is coupled to a memory input port, which may be associated with the same or different memory segment as the input port. The common read access line and/or the common write line to which the processor elements are connected, may be coupled to a respective memory input and output port through a switching element, which enables other processor elements associated with one or more different memory segments access to one or more of the processor elements and their associated memory segments.

The data processor may include at least one register for each processor element, each coupled to a common read access line, each of which may be selectively enabled to receive data from the common access line in order to control which processor element has access to the memory segment at any one time. The input registers may be controlled in conjunction with the memory decoders such that either the same or different data from the memory is read into different processor elements. An embodiment of a data processor having multiple processor elements associated with a memory segment is shown in FIG. 21.

Referring to FIG. 21, a data processor 601 comprises a memory 603 (for example a RAM) having a plurality of columns 607 of storage elements. The memory may have a plurality of segments 609 (only one of which is shown in FIG. 21), each segment having a plurality of columns of storage elements connected to a column decoder 611, which has a memory port 613 (e.g. an I/O port, which may include separate terminals for read and write access or a common read/access terminal). The memory 603 also includes a row decoder 615 for selecting a row of storage elements for read and/or write access. The data processor 601 comprises a plurality of processor elements 617, 619, 621 each having an input port 623, 625, 627 coupled to a common read access line 629, which is coupled to the memory port 613 via an optional switching element 631 which may be switchable to couple either the local read access line 629 to the local memory port 613, or to connect one or more other processor elements and/or their associated memory segments to the local memory segment 609 or to the local processor elements 617, 619, 621.

Each processor element 617, 619, 621 has at least one and in the present embodiment two input registers 633, 635 coupled to a respective processor input port 623, 625, 627

for temporarily storing data output from the memory before being processed by the respective processor element. Data write access to each register to enable or disable each register from receiving data on the common read access line 629 is controlled by a control signal applied to a control input port 637. Each register is individually controllable by a control signal. The control signals may be applied by any suitable device, for example a memory access controller (MAC, not shown). Although in another embodiment, simple switches may be used to selectively couple the input port of each processor element to the common read line, the provision of one or more registers enables a processor element to operate on the data contained in its register(s), while another processor element performs a memory access and data is downloaded into its register(s). The provision of two or more registers for one or more processor elements enables the or each processor elements to process data stored in one register and at the same time make a memory access so that data from the memory is downloaded into the second register (or one of its other registers, if the processor element has more than two registers) so that data to be processed is pre-fetched. In this way, each register of a PE may be alternately selected for (1) receiving data from the memory and (2) for outputting data to be processed by the PE, for example to its ALU.

In the present embodiment, the memory port 613 is switchably coupled to another line 639 via a switch 641, which may for example comprise a tri-stateable inverter, and may be controlled by any suitable device, e.g. the same or different device used to control the registers 633, 635. Advantageously, this arrangement enables the memory segment to be accessed by another device, such as a data processor. The provision of one or more registers 633, 635 coupled to the input port of each processor element enables the processor elements to process data from the memory, while the memory is being accessed by another device, via the other read access line 639.

The process or architecture of the embodiment of FIG. 21 offers a designer a wide range of possible operating modes. For example, the present configuration allows a page mode memory access. In page mode, a single row of memory (or segment of memory) is selected, and columns within the same memory segment are then successively selected by the column decoder (column access storage (CAS) signal), while the row access strobe (RAS) signal remains active. As each data bit appears on the common read line 629, the input registers of the processor elements may be successively activated so that for example a bit from each successive memory column is written to a register of successive processor elements. In one example, a byte of data may be stored in a row of storage elements, and the data processor may include eight or more processor elements. Different bits of the byte may be read into different processor elements, and the processor elements may be arranged to perform a parallel operation on the byte word. A second byte, for example from a second row of storage elements may also be read from the memory, for example using page mode, and different bits of the second byte also read into different processor elements, which may then perform an operation on both bytes, for example by making a comparison calculation, or any other operation.

In this embodiment, each memory segment includes one or more columns of storage elements, and may include any number of processor elements, for example 2, 4, 16, 32, or any other number.

Returning to FIG. 21, the data processor 601 also includes circuitry to enable each processor to output data to its local



## 25

memory, or optionally, another memory segment or another processor element, associated with that memory segment, through the switching element 631.

Each switching element 617, 619, 621 has an output port 645, 647, 649 each coupled to a respective output line 651, 653, 655. The output port of each processor element may be coupled to, for example, the output of an ALU, a register (e.g. internal register) or another element of the processor element, or may be coupleable to any one of these. The output circuit further includes a first output selector switch 657 coupled to each of the output lines 651, 653, 655, which switchably connects one of the output lines to the output port 659 of the selector switch 657. The output 659 of the selector switch 657 may be coupled to the switching element (SE) 631, which may be arranged to enable data from the processor elements to be written into their local memory 609, or into one or more other parts of the memory or into one or more other processor elements. Alternatively, the output of the first selector switch 657 may be coupled directly to the local memory input port (or to another memory input port). In the present embodiment, a second selector switch 661 is provided having two inputs 663, 665, one of which 663 is coupled to the output port 659 of the first selector switch 657, and the other being connected to another line 667 which may be used to receive data from another device. The second selector switch 661 is controlled by appropriate control signals applied (by any device, e.g. the array controller) to its control input port 669 for connecting one of its input ports to its output port 671. The output port of the second selector switch 661 may be connected to the switching element 631, or directly to the memory input port 613. (Alternatively, the output 671 port may be connected to any other component, for example, of the data processor, such as a memory segment of the same or different memory, or a different processor or other device.

An embodiment of a switching element which may be implemented as the switching element 631 in the embodiment of FIG. 21 is shown in FIG. 22. The switching element 631 has an input port 673, first and second input/output ports 675, 677 which is switchably coupled to the input port 673 by a respective first and second switch 679, 681, and an output port 683 which is switchably coupled to the input port 673, and the first and second input/output ports 675, 677 via a selector switch 685. The input port may be coupled to the local memory port (613 in FIG. 21), to one or more outputs of the processor elements (e.g. to one or more of the output lines 651, 653, 655 in FIG. 21, for example via the first or second selector switches 657, 661 in FIG. 21), or may be selectively coupled to either of the local memory or the output from one or more processor elements.

The output port 683 of the switching element may be coupled to the input port of one or more processor elements, and may, for example, be coupled to the common read access line 629 in FIG. 21 or may be coupled to the local memory input port (for example memory ports 613 in FIG. 21), or switchable coupled to either.

A series of switching elements, for example switching elements 631, 685, 687 may be coupled together to enable the lateral transfer of data from one unit, comprising, for example a memory segment and a plurality of local processor elements, associated with one switching element, and another unit associated with another switching element.

The combination of switching elements which allows east to west and west to east data transfer in the east to west and west to east directions, and the interconnected processor elements associated with each switching element enables data to be transferred between a processor element (or its

## 26

associated memory) and any one of its eight neighbours (processor elements or their local memory) (or more remotely) in the north to south, south to north direction, the east to west and west to east directions and both diagonal directions (i.e. Northeast to Southwest and vice versa and Northwest to Southeast directions and vice versa).

Another embodiment of a data processor having an architecture comprising a plurality of units, each having a memory segment and a plurality of processor elements associated with a memory segment, is shown in FIG. 23. The data processor 701 comprises a memory 703 having a plurality of column segments 705 which are divided into a plurality of row segments 707. Each column segment has an associated memory port 709 to enable data to be at least one of read from and written to the memory segment. The data processor further includes a plurality of processor elements 711, 713, 715, 717 associated with each column segment 705 of the memory, and which in this embodiment are arranged in column groups 719, 721, 723 etc., although processor elements associated with a particular memory segment may be arranged in any other configuration. Each group 719, 721, 723 of associated processor elements are interconnected to a common read line and/or to a common output line, for example as for the embodiment of FIG. 21. Each group of processor elements is coupled to the memory port of its respective memory segment by a switching element 725, which may for example be similar to the embodiment of the switching element shown in FIG. 22. In one embodiment, the switching elements may be interconnected to enable the transfer of data between neighbouring groups of processor elements and their associated memory segments, in applications where the data processor is required to operate on single bit data. However, in the present embodiment, adjacent switching elements are not interconnected, but are provided for another interconnection scheme which allows multiple bit words to be transferred between different elements of the data processor, as will be described below.

In the present embodiment, each row (0 to n) of processor elements has a corresponding row segment or slice (0 to n) of memory. In operation, each row of processor elements may be arranged to read data from its corresponding memory slice one at a time and in any order. For example, the processing elements in row 0 may first be enabled to read from their row 0 memory slice, then the processor elements in row 1 may be enabled to access their corresponding row 1 memory slice, (for example in the next cycle), until all required rows of processor elements have accessed their corresponding row memory slice. Successive memory accesses by successive rows of processor elements may be referred to as pipelined accesses. In processing the data, a row of processing elements may begin processing the data once the data is received, or wait until one or more other rows of processing elements have also received data to be processed. In either case, data may be processed by each row of processing elements at different times (i.e. in different cycles) or simultaneously in the same cycle or cycles.

The embodiments of the data processor shown in FIGS. 21 and 23 allow multiple processing elements to access the memory via a single switching element. This arrangement may improve the timing for transferring data from a given memory space to a number of processor elements since the latency period is that associated with a single switching element, rather than multiple switching elements. This arrangement also reduces the time required for inter-processor element data transfer between associated processor elements (for example in the same column), since the data



can be transferred from any processor element to any other associated processor element through a single switching element, in other words, by a left or right shift North/South except does not require a switching element. In one embodiment, the output port or line of one or more processor elements may be switchably connected to the input port of any other processor element by by-passing the switch as shown for example by the switch **691** between the output line **651** of the first processing element and the common read line **629** of the embodiment shown in FIG. **21**. The output or line of other processor elements may be similarly connected to the common read access line **629**.

In one embodiment, each row of processor elements may be arranged to perform parallel processing on multiple bit data, for example byte wide data or multiple byte wide data (e.g. containing 16, 32, 64 etc. bits). The processor elements may be arranged in groups of eight, thereby forming a computational unit capable of performing processing operations on byte length data. To enable data bytes to be transferred between one computational unit and another, each switching element **725** of the embodiment shown in FIG. **23** is connected to a corresponding switching element of a neighbouring computational unit (either to the right or to the left or both) to enable bits of the same significance to be transferred between computational units.

In other embodiments, the computational units may have any number of processor elements to enable the computational units to process data of any length, for example 16 bit data, 24 bit data, 32 bit data etc. In another embodiment, two or more computational units may be coupled together to enable variable length word processing. In this case, a switching element may be switchably connected to two or more other switching elements for transferring bits of the same significance in a data transfer, depending on the length of the word. For example, corresponding switching elements of neighbouring eight bit computational units may be interconnected to enable the transfer of data bytes between neighbouring computational units. Each switching element of a computational unit may also be switchably connected to an eight bit computational unit immediately adjacent its neighbouring computational unit to enable 16 bit data transfers between pairs of computational units acting together as a 16 bit parallel processor. This arrangement may be extended to enable data transfers between computational units of words of any desired length.

The processing capacity of the data processor described above and shown in FIG. **23** may be expanded to any desired size, by for example adding and interconnecting further blocks of memory and associated computational units. An example of a data processor containing four interconnected memory blocks and associated computational units is shown in FIG. **24**. Referring to FIG. **24**, the data processor **801** has four memory blocks **803**, **805**, **807**, **809** each having an associated array of computational units **811**, **813**, **815**, **817**. Each computational unit may comprise one or more processor elements, for example eight processor elements for byte length word processing. The computational units are arranged in two-dimensional arrays of rows and columns. Each column **819** of computational units has an associated switching element (if each computational unit has only one processor element) or group of switching elements (if each computational unit has more than one processor element) **821**. The switching element or group of switching elements **821** are arranged in rows, adjacent switching elements or groups of switching elements being coupled to the or each neighbouring switching element or group of switching elements to enable data to be transferred laterally between

computational units in different (e.g. neighbouring) columns. The switching element or groups of switching elements in corresponding columns of the first and second array of computational units **811**, **813** are also connected to allow data to be transferred between computational units and/or their associated memory space of the first and second units, as indicated by the arrow **821**, and the switching element or group of switching elements of corresponding columns of computational unit associated with the third and fourth array of computational units **815**, **817** are also interconnected as shown by the arrows **823**, to allow data to be transferred between the third and fourth units.

Although in the embodiment of FIG. **23**, a single memory block may be used to serve all of the arrays of computational units, it may be preferable to provide a number of smaller, separate memory blocks to give the required memory space in order to reduce memory access times and to provide other advantages as described in connection with the embodiments shown in FIG. **20**.

Embodiments of the data processor apparatus may be formed on a single die using any integrated circuit fabrication technique. Embodiments of the data processor apparatus are particularly applicable to SIMD processor operation and allows one or two-dimensional arrays of data of any size to be processed in parallel.

In other embodiments of the present invention, any one or more elements described above in connection with one embodiment may be incorporated in any other embodiment or combined with any other element or component.

Modifications to be the embodiments described above will be apparent skilled in the art.

The invention claimed is:

1. A switching element for switchably coupling a two-dimensional array of circuit elements each having an input and an output, the switching element comprising:

an input for coupling to at least one associated local circuit element;

an output for coupling to at least one associated local circuit element;

means for switchably coupling said input to said output; a first input/output port, a second input/output port, a third input/output port, and a fourth input/output port, each input/output port being switchably coupled to said input, said output, and each other;

a first switch means having a first state in which said first input/output port is coupled to said second input/output port, a second state in which said first input/output port is coupled to said third input/output port, and third state in which said first input/output port is coupled to said fourth input/output port;

a second switch means having a first state in which said second input/output port is coupled to said first input/output port, a second state in which said second input/output port is coupled to said fourth input/output port, and a third state in which said second input/output port is coupled to said third input/output port;

a third switch means having a first state in which said third input/output port is coupled to said second input/output port, a second state in which said third input/output port is coupled to said first input/output port, and a third state in which said third input/output port is coupled to said fourth input/output port; and

a fourth switch means having a first state in which said fourth input/output port is coupled to said third input/output port, a second state in which said fourth input/output port is coupled to said second input/output port,



29

and a third state in which said fourth input/output port is coupled to said first input/output port; and wherein said first and third input/output ports are spaced apart along a first axis, and said second and fourth input/output ports are spaced apart along a second axis, wherein said second axis traverses said first axis between said first and third input/output ports.

2. A switching element as claimed in claim 1, wherein each said switch means has a neutral state in which each said respective input/output ports associated therewith is isolated from any of said other input/output ports.

3. A switching element as claimed in claim 1, comprising selector means having a plurality of inputs for selectively coupling one of said selector inputs to said input port.

4. A switching element as claimed in claim 1, further comprising selector means having a plurality of output ports and arranged to couple said output port to one of said selector output ports.

5. A switching element as claimed in claim 1, wherein said first axis and said second axis have a substantially orthogonal relationship.

6. An array of a plurality of switching elements, comprising:

a plurality of switching elements, each switching element having structure recited in claim 1,

wherein said switching elements are interconnected such that a second input/output port of a first switching element is connected to a fourth input/output port of the second switching element,

and a first input/output port of said second switching element is connected to a third input/output port of a third switching element.

30

7. A switching element for switchably coupling a two-dimensional array of circuit elements each having an input and an output, the switching element comprising:

an input for coupling to at least one associated local circuit elements;

an output for coupling to at least one associated local circuit element;

means for switchably coupling said input to said output;

a first input/output port, a second input/output port, a third input/output port, and a fourth input/output port, each input/output port being switchably coupled to said input, said output, and each other;

a first switch means for coupling said first input/output port to one of said second, third, and fourth input/output port;

a second switch means for coupling said second input/output port to one of said first, third, and fourth input/output port;

a third switch means for coupling said third input/output port to one of said first, second, and fourth input/output port; and

a fourth switch means for coupling said fourth input/output port to one of said first, second, and third input/output port; and

wherein said first and third input/output ports are spaced apart along a first axis, and said second and fourth input/output ports are spaced apart along a second axis, wherein said second axis traverses said first axis between said first and third input/output ports.

\* \* \* \* \*