



US007188166B2

(12) **United States Patent**
Minematsu

(10) **Patent No.:** **US 7,188,166 B2**
(45) **Date of Patent:** **Mar. 6, 2007**

(54) **STORAGE SYSTEM, STORAGE CONTROL DEVICE, AND CONTROL METHOD FOR STORAGE SYSTEM**

2002/0103923 A1 *	8/2002	Cherian et al.	709/235
2002/0103969 A1	8/2002	Koizumi et al.	
2003/0093442 A1	5/2003	Mogi et al.	
2004/0083339 A1	4/2004	Yamamoto et al.	
2004/0111558 A1	6/2004	Kistler et al.	
2004/0122799 A1	6/2004	Goyal et al.	

(75) Inventor: **Tetsuya Minematsu**, Odawara (JP)

(73) Assignee: **Hitachi, Ltd.**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 237 days.

FOREIGN PATENT DOCUMENTS

JP	09-258907	10/1997
JP	2002-288105	10/2002

* cited by examiner

(21) Appl. No.: **10/785,972**

Primary Examiner—Ario Etienne

(22) Filed: **Feb. 26, 2004**

Assistant Examiner—Hussein Elchanti

(65) **Prior Publication Data**

US 2005/0125426 A1 Jun. 9, 2005

(74) *Attorney, Agent, or Firm*—Mattingly, Stanger, Malur & Brundidge, P.C.

(30) **Foreign Application Priority Data**

Dec. 4, 2003 (JP) 2003-406160

(57) **ABSTRACT**

(51) **Int. Cl.**

G06F 15/13 (2006.01)

G06F 15/16 (2006.01)

(52) **U.S. Cl.** **709/223; 709/224; 709/247**

(58) **Field of Classification Search** **709/203, 709/217–219, 223–226, 235, 245**

See application file for complete search history.

Provided is storage system comprising a plurality of first information-processing devices; a storage control device which is communicatively connected with the first information-processing devices via a first communication network, to receive a data input/output request transmitted from an information-processing device, and to read or write data from or to a storage device according to the data input/output request; and a second information-processing device communicatively connected with the first information-processing devices and the storage control device, wherein each of the first information-processing devices transmits processing status data relating to data input/output requests being processed to the second information-processing device; the second information-processing device receives the processing status data and transmits the storage control device a message which relates to performance adjustment of the storage control device for the first information-processing devices, and is determined according to the processing status data; and the storage control device executes processing related to performance adjustment of the first information-processing devices according to the message.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,606,679 A	2/1997	Cohn et al.	
5,720,028 A	2/1998	Matsumoto et al.	
6,088,814 A	7/2000	McKenzie et al.	
6,360,306 B1	3/2002	Bergsten	
6,526,478 B1 *	2/2003	Kirby	711/114
6,535,518 B1 *	3/2003	Hu et al.	370/401
6,542,964 B1 *	4/2003	Scharber	711/122
6,581,104 B1 *	6/2003	Bereiter	709/232
6,629,213 B1 *	9/2003	Sharma	711/144
6,735,631 B1 *	5/2004	Oehrke et al.	709/226

19 Claims, 7 Drawing Sheets




FIG. 1




FIG.2




FIG.3




FIG.4




FIG.5

DATA READ REQUEST




FIG.6

LU ADMINISTRATION TABLE

611 COMMUNICATION PORT (WWNc)	612 LUN	613 LOGICAL DEVICE NUMBER	614 STORAGE CAPACITY (GB)
⋮	⋮	⋮	⋮
100	0	1001	80
		1002	80
		1003	80
		1004	80
		1005	80
	1	1006	120
		1007	120
200	0	1010	40
		1011	40
		1012	40
		1013	40
		1014	40
⋮	⋮	⋮	⋮

FIG. 7




FIG. 8




FIG.11





FIG.12



STORAGE SYSTEM, STORAGE CONTROL DEVICE, AND CONTROL METHOD FOR STORAGE SYSTEM

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a storage system, storage control device, and control method for a storage system.

2. Description of the Related Art

In conjunction with developments in IT-related industries, storage control devices for disk array devices and the like are rapidly coming into broad use. Storage control devices have become established as the main infrastructure for performing data administration services, Web services, and various other information services provided in information service centers, data centers, and the like.

The amount of data handled by storage control devices is now increasing annually. Because of this, mechanisms for efficiently handling large amounts of data stored in memory resources and delivering a high-speed response to an information-processing device are being increasingly sought.

Among such mechanisms, mechanisms are disclosed in Japanese Patent Application Laid-open Nos. H9-258907 and 2002-288105, for example, for efficiently operating a storage control device. Both of these mechanisms are devised for performing performance adjustment (tuning) of a storage control device on the basis of the processing time required for processing a command received from a host computer, the amount of data transferred between servers, and other information acquired in the storage control device.

However, when control relating to the aforementioned performance improvement is performed in such a storage system solely on the basis of information acquired in the storage control device as described above, without taking the situation of the information-processing device into account, performance adjustment of the storage control device may not necessarily be performed optimally. For example, the processing load of the storage control device can sometimes be predicted based on the situation of the information-processing device, but because such information is not communicated to the storage control device, performance adjustment of the storage control device is sometimes not performed optimally.

SUMMARY OF THE INVENTION

The present invention was developed in view of the foregoing drawbacks, and an object thereof is to provide a storage system, a storage control device, and a control method for a storage system that are capable of optimally adjusting the performance of a storage control device while reflecting the situation of the information-processing device.

The main aspect of the present invention for achieving the aforementioned objects consists of a storage system that comprises a plurality of first information-processing devices; a storage control device communicatively connected with the first information-processing devices by a first communication network, to receive data input/output requests transmitted from the information-processing devices and to read or write data from or to the storage device according to the input/output request thus received; and a second information-processing device communicatively connected with the first information-processing devices and storage control device, wherein each of the first information-processing devices has a processing status data transmitter for transmitting to the second information-pro-

cessing device transmitting processing status data consisting of data that indicate the status of processing related to the aforementioned data input/output requests being processed; the second information-processing device has a message transmitter for receiving the aforementioned processing status data and transmitting to the aforementioned storage control device a message that relates to performance adjustment of the aforementioned storage device for the first information-processing devices and is determined according to the processing status data thus received; and the storage control device has an adjustment executer for receiving the aforementioned message and executing processing related to performance adjustment of the first information-processing devices according to the message thus received.

By means of the present invention, the performance of a storage control device can be optimally adjusted while reflecting the situation of an information-processing device.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a diagram depicting the basic structure of the storage system 1 described as an embodiment of the present invention;

FIG. 2 is a diagram depicting the hardware configuration of the channel controller 21 described as an embodiment of the present invention;

FIG. 3 is a diagram depicting the hardware configuration of the disk controller 22 described as an embodiment of the present invention;

FIG. 4 is a diagram depicting an example of the data format of the data write request described as an embodiment of the present invention;

FIG. 5 is a diagram depicting an example of the data format of the data read request described as an embodiment of the present invention;

FIG. 6 is a diagram depicting an example of the LU administration table 600 described as an embodiment of the present invention;

FIG. 7 is a diagram depicting the relationship between the WWNj, WWNc, LU, and LDEV in the storage system 1 described as an embodiment of the present invention;

FIG. 8 is a diagram depicting the software configuration of the storage system 1 described as an embodiment of the present invention;

FIG. 9 is a diagram depicting the data format of the processing status data described as an embodiment of the present invention;

FIG. 10 is a diagram depicting the relationship between items of configuration information described as an embodiment of the present invention;

FIG. 11 is a flowchart describing the mechanism for tuning the operation of the disk array device 20 according to the load state of the communication ports in an embodiment of the present invention; and

FIG. 12 is a diagram depicting the data format of the tuning instruction message described as an embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

An embodiment of the present invention will be described hereinafter with reference to the figures.

Configuration of Storage System

FIG. 1 shows the configuration of the storage system described as an embodiment of the present invention. The storage system 1 is made up of a plurality of information-

processing devices (first information-processing devices) **10** and a disk array device (storage control device) **20** connected so as to be capable of communication with the information-processing devices **10** by a SAN (Storage Area Network) (first communication network) **50** that is configured using a fiber channel protocol.

The storage system **1** is operated by a system center in a data center or company, for example. The information-processing devices **10** consist of computers for providing an automatic cash dispensing service at a bank or an Internet homepage browsing service, for example. The disk array device **20** functions as a depository for data used by application software and other programs executed in the information-processing devices **10**, for example. The disk array device **20** receives a data read request, data write request, or other request transmitted via SAN **50** from the information-processing devices **10** and reads or writes data in the hard disk drives (storage devices) **28** in response to the received data input/output request.

The information-processing devices **10** are connected by means of a LAN (Local Area Network) (second communication network) **60**. The TCP/IP protocol, for example, is employed as the transmission protocol of the LAN **60**. An administration server (second information-processing device) **30** is connected to the LAN **60**. The information-processing devices **10** are connected by the LAN **60** so as to be capable of communication with the administration server **30**. The administration server **30** is connected with the disk array device **20** via a LAN **70**. The TCP/IP protocol, for example, is employed as the transmission protocol of the LAN **70**. Also, the LAN **60** may be connected with the LAN **70**.

The disk array device **20** may be designed so as to function as a NAS (Network Attached Storage) that is configured to receive data input/output requests according to file name assignments from the information-processing devices **10** by means of a NFS (Network File System) or other protocol, for example. The disk array device **20** may also consist of other storage control devices, such as semiconductor disk devices or the like.

Communication between the information-processing devices **10** and the disk array device **20** may also be performed by means of a LAN (Local Area Network), SCSI (Small Computer System Interface), iSCSI (Internet Small Computer System Interface), ESCON (Enterprise System Connection) (registered trademark), FICON (Fiber connection) (registered trademark), ACONARC (Advanced Connection Architecture) (registered trademark), or FIBARC (Fiber connection Architecture) (registered trademark) in addition to SAN **50**. A peer-to-peer-type connection between the administration server **30** and disk array device **20** may be established using a SCSI specification communication line, for example.

<Information-Processing Devices 10>

The information-processing devices **10** consist, for example, of personal computers, workstations, mainframe computers, or other computers. The information-processing devices **10** are provided with a CPU (Central Processing Unit) **11**, memory (ROM, RAM) **12**, hard disk drive or other external storage device **13**, SAN adapter **14**, LAN adapter **15**, and the like. Various functions of the information-processing devices **10** are performed by means of various programs being executed by CPU **11**. SAN adapter **14** consists of a communication interface for connecting the information-processing devices **10** to SAN **50**. An HBA (Host Bus Adapter), for example, is used as the SAN adapter **14**. The LAN adapter **15** consists of an interface for con-

necting the information-processing devices **10** to the LAN **60**. A NIC (Network Interface Card), for example, is used as the LAN adapter **15**.

The information-processing devices **10** transmit a data input/output request in block units to the disk array device **20** according to the fiber channel protocol. The disk array device **20** performs processing related to reading/writing of data to a hard disk drive **28** when a data input/output request transmitted from the information-processing devices **10** is received. Also, when the information-processing devices **10** consist of NAS, a file name is set in the data input/output request.

<Disk Array Device 20>

The disk array device **20** is provided with a channel controller **21**, disk controller **22**, shared memory **23**, cache memory **24**, connector **25**, service processor (SVP) **26**, LAN adapter **27**, hard disk drive (storage device) **28**, and the like. The hard disk drive **28** may be built into the chassis of the disk array device **20**, or may be housed in a separate chassis.

The hardware configuration of the channel controller **21** is shown in FIG. 2. The channel controller **21** is provided with a CPU **211**, memory (RAM, ROM) **212**, external communication interface **213**, internal communication interface **214**, and the like. The CPU **211** administers control of the channel controller **21** as a whole. The CPU **211** (*1) performs various functions of the channel controller **21** by executing programs stored in the memory **212**. The external communication interface **213** is an interface for communicating with the information-processing devices **10** via SAN **50**. The internal communication interface **214** gives and receives data and commands between the disk controller **22**, shared memory **23**, cache memory **24**, and the like via the connector **25**. The internal communication interface **214** communicates with the service processor **26**. When a data input/output request is received from the information-processing devices **10**, the channel controller **21** writes a command to the shared memory **23** relating to reading/writing of corresponding data.

The hardware configuration of the disk controller **22** is shown in FIG. 3. The disk controller **22** performs reading/writing of data to the hard disk drive **28** in accordance with a data write request that the channel controller **21** receives from the information-processing devices **10**. The disk controller **22** is provided with a CPU **221**, memory **222**, internal communication interface **223**, disk interface **224**, and the like. The CPU **221** administers control of the disk controller **22** as a whole. The CPU **221** (*2) performs various functions of the disk controller **22** by executing programs stored in the memory **222**. The internal communication interface **223** gives and receives data and commands between the channel controller **21**, shared memory **23**, cache memory **24**, and the like via the connector **25**. The disk interface **224** reads and writes data from and to the hard disk drive **28**. The disk interface **224** gives and receives data from the hard disk drive **28**. Also, the disk controller **22** may be provided with functionality for controlling the hard disk drive **28** at a RAID level (0, 1, or 5, for example) specified by a so-called RAID (Redundant Array of Inexpensive Disks) system.

The disk controller **22** reads a command from the shared memory **23** relating to reading/writing of data written in the shared memory **23** by the channel controller **21**, and performs reading/writing of data to the hard disk drive **28** in accordance with the command. The disk controller **22** writes the data read from the hard disk drive **28** to the cache memory **24**. The disk controller **22** transmits an appropriate notification of data write completion, notification of data read completion, or the like to the channel controller **21**.

When the notification of completion is received, the channel controller **21** presents the information-processing devices **10** with a reply to the data input/output request.

The shared memory **23** and cache memory **24** are configured using RAM or other rewritable memory. Among such memory, the shared memory **23** mainly stores commands and data given and received between the channel controller **21** and disk controller **22**. The shared memory **23** (*2a) absorbs the time for accessing the hard disk drive **28** and enhances response to the information-processing devices **10**. Using the cache memory **24** makes it possible to enhance processing efficiency relating to reading/writing of data performed between the channel controller **21** and disk controller **22**; for example, the response speed (response) to the information-processing devices **10** can be enhanced.

The connector **25** connects together the channel controller **21**, disk controller **22**, shared memory **23**, and cache memory **24** to allow them to communicate with each other. The connector **25** is configured using an ultra high-speed crossover switch or other high-speed bus for transferring data by high-speed switching, for example.

The service processor (SVP) **26** is configured with a CPU and memory. The service processor **26**, as such, can be made to function as an independent computer. The service processor **26** receives operational input by an operator or the like and performs monitoring, setting, and the like of the operational status of the disk array device **20**. The service processor **26** communicates with the channel controller **21**. The service processor **26** communicates with the administration server **30** via the LAN adapter **27** shown in FIG. 1.

The administration server **30** is a computer provided with a CPU **31**; memory (RAM, ROM) **32**; hard disk drive or other external storage device **33**; CD-ROM device, DVD-ROM device, or other recording medium-reading device **34**; mouse, keyboard, or other input device **35**; display or other output device **36**; LAN adapter **37**; and the like. The CPU **31** administers overall control of the administration server **30**. The various functions of the administration server **30** are performed by means of the CPU **31** executing the programs stored in the memory **32**.

The recording medium-reading device **34** is a device for reading programs and data recorded in the recording medium **39**. A configuration may be adopted whereby the recording medium-reading device **34** reads the data and programs recorded in the recording medium **39** and stores these in the memory **32** and external storage device **33**. A configuration may be adopted whereby the recording medium **39** in which programs for executing various functions of the administration server **30** are recorded is set up in the recording medium-reading device **34**, and the programs are installed in the administration server **30**. A flexible disk, CD-ROM, DVD-ROM, DVD-RAM, semiconductor memory, or the like may be used as the recording medium **39**. The administration server **30** is connected so as to be capable of communication with the disk array device **20** via the LAN adapter **37**, and the administration server **30** can communicate with the information-processing devices **10** and service processor **26** of the disk array device **20**. Also, the functions of the administration server **30** described in the present embodiment may be performed by the service processor **26** of the disk array device **20**.

A WWN (World Wide Name) consisting of identifying information for identifying the instrument connected to the SAN **50** is created for the SAN adapter **14** of the information-processing devices **10**. The WWN is created for each of the communication ports to the SAN **50** possessed by the SAN adapter **14**. Consequently, two WWN are created for a

SAN adapter **14** having two communication ports, for example. On the other hand, a WWN consisting of a network address on the SAN **50** is also created for the communication port of the channel controller **21** for providing connectivity to the SAN **50** in the disk array device **20**. In the following description, the WWN created for the SAN adapter **14** of the information-processing devices **10** is abbreviated WWNj, and the WWN created for the communication port of the channel controller **21** is abbreviated WWNc.

The information-processing devices **10** recognize the storage area provided by the disk array device **20** as being made up of logical units (LU) that form a logical storage area. For example, when the operating system installed in the information-processing devices **10** is a UNIX (registered trademark) type operating system, the logical units are associated with a device file. As another example, when the operating system installed in the information-processing devices **10** is a Windows (registered trademark) type operating system, the logical units are associated with a drive letter (drive name). A specific logical unit number (LUN) is created for each logical unit in a set of logical units. The information-processing devices **10** specify a logical unit according to the LUN. The LUN is set by a data input/output request transmitted from the information-processing devices **10** to the disk array device **20**, for example.

FIG. 4 depicts an example of the data format of a data write request consisting of a data input/output request transmitted from the information-processing devices **10** when data are written to the hard disk drive **28** of the disk array device **20**. In the command column **411** of this data format, a command is set that indicates that the data input/output request is a data write request for the disk array device **20**. In the LUN column **412**, the LUN of the logical unit that will be written to is set. In the address column **413**, the address of the logical unit that will be written to is set. In the WWN column **414**, the WWNj created for the SAN adapter **14** from which the request was transmitted is set. In the write data column **415**, the write data that will be written to the hard disk drive **28** is set.

FIG. 5 depicts an example of the data format of a data read request consisting of a data input/output request transmitted from the information-processing devices **10** when data are to be read from the hard disk drive **28** of the disk array device **20**. In the command column **511**, a command is set that indicates that the data input/output request is a data read request from the disk array device **20**. In the LUN column **512**, the LUN of the logical unit that will be read from is set. In the address column **513**, the beginning address of the logical unit that will be read from is set. In the WWN column **514**, the WWNj created for the SAN adapter **14** from which the request was transmitted is set. In the data size column **515**, the data size of the data that will be read from is set.

The disk array device **20** recognizes the physical storage area (hereinafter referred to as a physical storage area) of the hard disk drive **28** as being made up of logical devices (LDEV) as a storage area that is logically set using this storage area. A specific logical device number is created as an identifier for each logical device in the logical devices. The disk array device **20** of the present embodiment administers a parity group in the RAID5 system as one logical device.

The disk array device **20** administers correlation of the aforementioned logical units, which are the administrative units of the storage area in the information-processing devices **10**, with a logical device. This administration is performed by the functioning of a logical unit manager **823**,

which will be described hereinafter. Regarding this administration, FIG. 6 depicts the LU administration table (hereinafter referred to as LU administration table) **600** that is stored and administered by the logical unit manager **823**. A logical unit is correlated with a communication port of the channel controller **21** in the disk array device **20**, and the correlation between the logical unit and the communication port is also administered by the LU administration table **600**. The logical unit manager **823** stores the LU administration table **600** in the channel controller **21** or service processor **26**, for example. In FIG. 6, a WWNc created for the communication port of the channel controller **21** is set in the communication port ID column **610**. In the LUN column **611**, a LUN is set, which is the number of the logical unit. In the logical device number column **612**, a logical device number is set. In the storage capacity column **613**, the storage capacity of the logical device is set. The relationship between the WWNj, WWNc, LU, and LDEV described above is shown schematically in FIG. 7.

Description of Functioning

The various functions performed in the storage system **1** of the present embodiment will next be described together with FIG. 8.

<Functioning of the Information-Processing Devices 10>

An operating system **811** operates in the information-processing devices **10**. A UNIX (registered trademark), Windows (registered trademark), or other operating system, for example, may be employed as the operating system **811**. A Web server or database, software for administrating a logical unit or logical device, software for setting and controlling a RAID system, or other application software **812** operates in the operating system **811**. Software for operating a file system or NFS (Network File System), software for receiving access in accordance with a CIFS (Common Interface File System), and the like are in operation when the disk array device **20** consists of NAS.

In the operating system **811**, an agent (processing status data transmitter) **813**, consisting of one of the aforementioned types of application software **812**, is in operation. The agent **813** provides functionality for transmitting processing status data that indicate the status of processing that relates to the data input/output requests transmitted from the information-processing devices **10** to the disk array device **20**, and also for transmitting the hereinafter-described configuration information data and the like to the administration server **30** via the LAN **60**. Also, the operating system **811**, application software **812**, and agent **813** are operated by means of the programs stored in the memory **12** and external storage device **13** being read and executed by CPU **11** in each of the information-processing devices **10**.

A specific example of the aforementioned processing status data is a queue length value, which is an average time for the number of data input/output requests registered in the transmission processing waiting queue **814** of a communication port in the SAN adapter **14** of the information-processing devices **10**. The queue length value is found by dividing the total number of data input/output requests registered in the transmission processing waiting queue **814** within a certain past period of time in the communication port by the length of the aforementioned period of time. The agent **813** acquires the queue length values of the communication port of the SAN adapter **14**. The agent **813** transmits the acquired queue length values of the SAN adapter **14** to the administration server **30** via the LAN **60**.

The agent **813** can acquire the aforementioned queue length values in real time using an operating system, API (Application Program Interface), or the like. For example, if

the operating system consists is a UNIX (registered trademark) system, the agent **813** can acquire the queue length values by delivering a "sar" command or "kstat" command.

FIG. 9 depicts an example of the data format of the processing status data. In FIG. 9, the WWNj of the communication port is set in the WWN column **911**. In the queue length value column **912**, a queue length value is set that corresponds to the aforementioned WWNj. Also, the queue length value is only an example of the processing status data, but if it consists of information that is effective for predicting the processing load of the disk array device **20** (*3), it may be employed as the processing status data.

Also, the agent **813** acquires a host name or IP address created as an identifier on the LAN **60** for the information-processing devices **10**; the type and version of the operating system operating in the information-processing devices **10**; the WWNj created for the SAN adapter **14** of the information-processing devices **10**; the port number, logical device number, or other information about the channel controller **21** of the disk array device **20** set so as to be accessed by the information-processing devices **10**; and other information relating to the configuration of the information-processing devices **10** (hereinafter referred to as configuration information), for example. Configuration information data, which consist of the data that set the aforementioned acquired configuration information, is then generated, and the configuration information data thus generated are transmitted to the administration server **30** (configuration information transmitter).

The agent **813** acquires the aforementioned configuration information using a command, API (Application Program Interface), or the like provided by the operating system **811**. When communication between the information-processing devices **10** and the disk array device **20** is performed according to an SCSI (Small Computer System Interface) specification, the agent **813** may sometimes acquire the WWNj created for the SAN adapter **14**, or a port number as an identifier of a communication port of the channel controller **21** of the disk array device **20** accessed by the information-processing devices **10**, by transmitting an "inquiry" command in the SCSI specification.

The agent **813** provides the configuration information data with a communication port or logical device number associated with an identifier for a storage area (a device file, drive letter, or the like, for example) recognized by the operating system **811** of the information-processing devices **10**, and transmits these data to the administration server **30**.

The configuration information is transmitted by the agent **813** periodically, arbitrarily, or with an appropriate timing at a time scheduled by a scheduler or the like. The agent transmitter **832** of the administration server **30** receives configuration information data transmitted by the administration server **30** and registers a description thereof in the database (configuration information storing unit) **834**. FIG. 10 shows the data format of the configuration information registered in the database **834**. The configuration information is associated as a WWNj or other prescribed item, for example, and is registered in the database **834**.

In FIG. 10, the host name of the information-processing device **10** is set in the host name column **1011**. The WWNj created for the SAN adapter **14** of the information-processing devices **10** is set in the WWNj column **1012**. A so-called device file name in UNIX (registered trademark) is set in the device file column **1013** when UNIX (registered trademark) is used as the operating system. An identifier for the disk array device **20** is set in the storage name column **1014**. The WWNc created for the channel adapter **21** is set in the

WWNc column **1015**. The logical device number is set in the logical device number column **1016**.

<Functioning of Administration Server **30**>

An operating system **831** operates in the administration server **30**. The operating system **831** is a UNIX (registered trademark), Windows (registered trademark), or other operating system. An agent transmitter **832**, a disk array transmitter **833**, a database **834**, a control information-setting unit **835**, and the like operate in the operating system **831**. Also, the agent transmitter **832**, disk array transmitter **833**, and database **834** each function by means of CPU **31** of the administration server **30** reading and executing the programs stored in the memory **32** or external storage device **33**.

The agent transmitter **832** communicates with the agent **813** operating in the information-processing devices **10** via the LAN **60**. The agent transmitter **832** receives processing status data or configuration information data transmitted from the agent **813** either autonomously or in response to a transmission request from the agent transmitter **832**, and registers this data in the database **834**.

The disk array transmitter **833** (message transmitter) communicates with the administration server transmitter **821** of the disk array device **20** via the LAN **60**.

The control information-setting unit **835** provides a user interface for performing setting relating to the operation of the tuning unit **822** of the disk array device **20**. A user operates a keyboard, mouse, or other input device **35** while referring to information that the control information-setting unit **835** displays on a display or other output device **36**, for example, and performs setting relating to the operation of the tuning unit **822**. The control information-setting unit **835** presents the tuning unit **822** with control information that corresponds to the set content.

<Functioning of Disk Array Device **20**>

A transmitter **821** to the administration server, a tuning unit **822**, and a logical unit manager **823** operate in the disk array device **20**. Also, these functions are performed by means of programs executed in the hardware of the service processor **26** or in the service processor **26**.

The transmitter **821** to the administration server communicates with the administration server **30** via the LAN **70**. The transmitter **821** to the administration server receives control information transmitted by the control information-setting unit **835** of the administration server **30** for performing operational setting of the tuning unit **822**, and notifies the tuning unit **822** of the setting information thus received.

The tuning unit (adjustment executing unit) **822** performs various functions relating to adjustment (tuning) of the access performance of the information-processing devices **10** with respect to the hard disk drive (storage device) **28** in order to elicit maximum performance of the disk array device **20**. A logical device configuration controller **8221** and priority controller **8222** are included in the tuning unit **822**. When, for example, a logical unit is configured with a logical device that has a high utilization rate, the logical device configuration controller **8221** of the tuning unit **822** functions to allocate a logical device with a low utilization rate to that logical unit. The utilization rate in this case is a value in which the number of processes per unit time for a data input/output request, or the amount of data processed in relation to a data input/output request, for example, is calculated as a parameter. The logical device configuration controller **8221** can also be provided as a software function for distributing loads concentrated in specific resources of the disk array device **20** in order to equalize load among the resources of the disk array device **20**.

A utilization rate measuring unit **82210**, a manual controller **82211**, and an automatic controller **82212** are contained in the logical device configuration controller **8221**. The utilization rate measuring unit **82210** measures the utilization rate of each logical device in real time and stores the measured utilization rates in time series.

The manual controller **82211** provides functionality whereby a user determines which logical device is allocated to which logical unit. This setting is performed, for example, using the functioning of the control information-setting unit **835** of the administration server **30**. The manual controller **82211** presents the logical device utilization rate stored by the utilization rate measuring unit **82210** to the user. The manual controller **82211** also presents the read speed of the logical devices to the user. The user refers to the utilization rate and read speed of the logical devices thus presented and determines which logical device is to be substituted. The logical device to be newly allocated to the logical unit is selected in place of the logical device targeted for substitution. During this selection, the user selects a logical device with a lower utilization rate or higher read/write speed than the logical device targeted for substitution as the logical device to be newly allocated to the logical unit. When the user selects a logical device to allocate to the logical unit, the manual controller **82211** duplicates the data stored in the logical device targeted for substitution onto the logical device thus selected. After this duplication, the manual controller **82211** then indicates to the logical unit manager **823** that the contents of the LU administration table **600** will be updated to show that the aforementioned logical device selected by the user was allocated to the aforementioned logical unit. The logical unit manager **823** updates the LU administration table **600** to reflect the aforementioned description. A logical unit consisting of a logical device with a high utilization rate is reconfigured with a logical device that has a low utilization rate or a logical device that has a high read speed as described above, and, as a result, reduction of the processing speed of logical devices with a high utilization rate is minimized.

On the other hand, the automatic controller **82212**, in contrast with the manual controller **82211**, automatically selects a logical device to be substituted and a logical device to be newly allocated to the logical unit on the basis of the utilization rate stored by the utilization rate measuring unit **82210**. For this selection, the automatic controller **82212** stores a maximum value for the utilization rate set for each logical device. This setting is performed, for example, using the functions of the control information-setting unit **835** of the administration server **30**. When the utilization rate of a logical device is detected to have exceeded the maximum value, the automatic controller **82212** assigns that logical device to be substituted and selects a logical device to be newly allocated to the logical unit in place of that logical device. In this selection, the automatic controller **82212** selects a logical device with a lower utilization rate or higher read/write speed than the logical device targeted for substitution as the logical device to be newly allocated to the logical unit. The automatic controller **82212** then duplicates the data stored in the logical device targeted for substitution onto the logical device thus selected. After this duplication, the automatic controller **82212** indicates to the logical unit manager **823** that the contents of the LU administration table **600** will be updated to show that the aforementioned logical device selected by the user was allocated to the aforementioned logical unit. The logical unit manager **823** updates the LU administration table **600** to reflect the aforementioned description. A logical unit consisting of a logical device with

a high utilization rate is reconfigured with a logical device that has a low utilization rate or a logical device that has a high read speed as described above, and, as a result, reduction of the processing speed of logical devices with a high utilization rate is minimized.

The priority controller **8222** provides functionality for controlling the disk array device **20** so as to give priority to executing processing that relates to a data input/output request transmitted from an information-processing device **10** in which high processing power is required. An information-processing device **10** in which high processing power is required may, for example, be an information-processing device **10** in which an institutional database or application program is operating. If the processing power of such an information-processing device **10** were to decline, the service of the related institution could be significantly reduced. The priority controller **8222** functions so that any processing related to input/output requests transmitted from information-processing devices **10** in which high processing power is required is performed with a higher priority than other data input/output requests. Also, a user or the like determines whether or not to give priority to an input/output request transmitted from any of the information-processing devices **10**, for example, by using the functions of the control information-setting unit **835** of the administration server **30**. The control information-setting unit **835** presents the tuning unit **922** with a WWNj created for an information-processing device **10** that is set such that priority is given to the control of its data input/output requests. The tuning unit **922** stores the WWNj (hereinafter referred to as priority WWNj) thus transmitted.

The priority controller **8222** sets a maximum value for the number of processes per unit time for data input/output requests transmitted from information-processing devices **10** that are not set to receive priority control, and for the amount of data processed per unit time in relation to data input/output requests, and control is performed so that processing related to data input/output requests transmitted from information-processing devices **10** that are not set to receive priority control is performed below the aforementioned maximum value. The tuning unit **922** determines whether or not the received data input/output request is set to receive priority control by ascertaining whether or not the WWN (the WWN set in WWN column **414** or WWN column **514**) set for that input/output request agrees with the stored priority WWNj. Specifically, when the WWN that is set for the data input/output request does not agree with the aforementioned priority WWNj, the tuning unit **922** performs control so that processing related to that data input/output request is performed below the aforementioned maximum value, and when the WWN that is set for the data input/output request agrees with the aforementioned priority WWNj, control according to the aforementioned maximum value is not performed for processing related to that data input/output request. By means of such an arrangement, the resources of the disk array device **20** are preferentially freed for data input/output requests transmitted from information-processing devices **10** with a high level of priority, with the result that processing related to data input/output requests from information-processing devices **10** with a high degree of priority is handled preferentially.

Also, in the aforementioned method whereby control is performed by setting a maximum value, during periods of time in which there are few data input/output requests transmitted from information-processing devices **10** with high priority, for example, allocation of more than the necessary amount of resources to information-processing

devices **10** with low priority can be limited. However, this inconvenience can be avoided by making it so that processing that cancels maximum value control is automatically executed when the number of data input/output requests from information-processing devices **10** with high priority decreases, for example. More specifically, a threshold value is set for the number of data input/output requests transmitted from information-processing devices **10** with high priority, for example, and when the number of data input/output requests transmitted from information-processing devices **10** with high priority falls below the threshold value, restriction of the aforementioned maximum value is automatically cancelled, and when the threshold value is exceeded, control by the maximum value is resumed.

Also, the aforementioned maximum value, threshold value, and other settings relating to the processing of the priority controller **8222** may be established, for example, by a user or the like using the functions of the control information-setting unit **835** of the administration server **30**.

The logical unit manager **823** shown in FIG. **8** manages the LU administration table **600**. The logical unit manager **823** receives instructions from the tuning unit **822** or the like and updates the contents of the LU administration table **600**.

Description of Processing

The storage system **1** in the present embodiment monitors the load state of the communication ports of the SAN adapter **14** of the information-processing devices **10**, and tunes the operation of the disk array device **20** according to the load state of the communication ports. This processing will be described hereinafter with reference to the flowchart shown in FIG. **11**.

The administration server **30** monitors the processing status data of the communication ports of the information-processing devices **10** registered in the database **834** in real time (S1111), and determines whether or not a communication port exists that will be targeted for performance improvement (S1112). The aforementioned processing status data in this case consist of the queue length value described previously. Also, the aforementioned monitoring in this case is performed by associating the queue length values of the communication ports in the SAN adapter **14** of the information-processing devices **10** with the communication ports, and comparing the result with a threshold value registered in advance in the database **834**.

In the presence of an information-processing device **10** whose performance is to be improved in this case (S1112: YES), the administration server **30** retrieves from the database **834** the WWNj created for the SAN adapter **14** of the information-processing device **10** targeted for performance improvement (S1113), and the system proceeds to processing step (S1114). Alternatively, when there is no information-processing device **10** whose performance is to be improved (S1112: NO), the system returns to processing step (S911).

In processing step (S1114), the administration server **30** transmits a message (hereinafter referred to as tuning instruction message) indicating performance improvement of the information-processing devices **10** to the tuning unit **822**. The data format of the tuning instruction message is depicted in FIG. **12**.

In this figure, information for describing the tuning method is set in the tuning method column **1211**. For example, information is set in the tuning method column **1211** that describes whether tuning will be performed by the functioning of the logical device configuration controller **8221** or the priority controller **8222**. The WWNj created for

the SAN adapter **14** of the information-processing device **10** to be tuned is set in the WWNj column **7223**.

When the aforementioned tuning instruction message is received, the tuning unit (adjustment executer) **822** executes tuning according to the contents of the message. When it is indicated in the tuning method column **1211** of the aforementioned tuning instruction message that tuning will be performed by the functioning of the logical device configuration controller **8221**, the logical device configuration controller **8221** changes the association in the LU administration table **600** so that the performance of the logical unit associated with the WWNj set in the WWNj column **1212** of the tuning instruction message is enhanced in the LU administration table **600** by means of the mechanism described above. For example, the performance of the logical unit can be enhanced by allocating a WWNj registered in the LU administration table **600** or allocating a logical device with a low utilization rate to the logical unit.

On the other hand, when it is indicated in the tuning method column **1011** of the tuning instruction message that tuning will be performed by the functioning of the priority controller **8222**, the priority controller **8222** performs control so that processing related to data input/output requests attached to the WWNj that is set in the WWNj column **1212** of the tuning instruction message is processed with priority by means of the mechanism described above.

As described above, in the storage system **1** of the present invention, processing status data are transmitted from the information-processing devices **10** to the administration server **30**. The administration server **30** monitors the processing status data and transmits a message relating to performance adjustment (tuning) to the disk array device **20**. The tuning unit **822** of the disk array device **20** executes processing for performance adjustment of the information-processing devices **10** according to the contents of the message. Thus, with the storage system **1** of the present embodiment, processing for performance adjustment in the disk array device **20** is performed appropriately according to the processing status of the information-processing devices **10**. In other words, with the storage system of the present embodiment, performance adjustment of the disk array device **20** can be performed appropriately while reflecting the situation of the information-processing devices **10**.

Tuning by Means of Configuration Information

The storage system **1** allows an operator or the like to input configuration information for the information-processing devices **10**, and provides functionality for adjusting the performance of the disk array device **20** based on the configuration information thus inputted.

The aforementioned configuration information is inputted, for example, with the aid of the user interface provided by the interface **613** of the information-processing devices **10**, or the user interface provided by the administration server **30** (configuration-designating information receiver). When the configuration information is inputted from the user interface of the information-processing devices **10**, the inputted configuration information is transmitted to the administration server **30**.

The administration server **30** generates a tuning instruction message based on the inputted configuration information. When the configuration information inputted by an operator or the like consists, for example, of a host name or IP address, the administration server **30** generates a tuning instruction message whose content directs that performance adjustment be performed for data input/output requests transmitted from the corresponding information-processing device **10**. Also, when the inputted configuration informa-

tion consists of the type or version of an operating system, for example, the administration server **30** generates a tuning instruction message with content that performance adjustment be performed for data input/output requests transmitted from information-processing devices **10** that are running the operating system **811** in accordance with the inputted type or version.

A WWNj for specifying the data input/output request targeted for performance adjustment is set in the tuning instruction message, and the administration server **30** acquires the WWNj (network address specifying unit) by searching the database **834** with the configuration information inputted by an operator or the like as a search key, and sets this WWNj in the tuning instruction message.

As described above, the storage system **1** of the present embodiment generates a tuning instruction message based on the configuration information inputted by an operator or the like. Specifically, an operator or the like can assign configuration information that is familiar to the operator or the like, for example, and can adjust the performance of the disk array device **20**. Convenience for the operator or the like is enhanced in this manner.

Other Embodiments

When a database is operating as one item of application software **812** in the information-processing devices **10**, the database may sometimes administer storage location information consisting of information indicating the logical unit in which the data administered by the database are stored. In this case, the administration server **30** allows an operator or the like to specify data registered in the database; for example, to ascertain the storage location of the specified data from the aforementioned storage location information and to specify a WWNj associated with that storage location from the database **834**. The administration server **30** then sets the aforementioned WWNj in the message that instructs performance adjustment to be performed. In other words, in this case, an operator or the like can carry out performance adjustment for data input/output requests relating to that data simply by specifying the data administered by the database.

An embodiment of the present invention was described above, but the description of the embodiment above was merely intended to aid in understanding the present invention, and does not limit the present invention. The present invention may, of course, include equivalents to the present invention obtainable by modification or improvement, insofar as they do not depart from the essence of the present invention.

What is claimed is:

1. A storage system comprising:

- a plurality of host computers;
- a storage control device which is communicatively connected with the host computers via a first communication network, to receive a data input/output request transmitted from the host computers, and to read or write data from or to a storage device according to the data input/output request received;
- a management server, for managing the storage system, communicatively connected with the host computers and the storage control device;
- wherein each of the host computers has a processing status data transmitter for transmitting to the management server processing status data including data that indicate the status of processing related to the data input/output request being processed;
- wherein the management server has a message receiver for receiving the processing status data and transmitting to the storage control device a message that relates to

15

performance adjustment of the storage control device for the host computers and is determined according to the processing status data received;

wherein the storage control device has an adjustment executor for receiving the message and executing processing related to performance adjustment of the host computers according to the message received;

wherein a first network address including a network address in the first communication network is provided to the host computers;

wherein the first network address is set in the message received by the storage control device;

wherein the storage control device stores the utilization rate of each logical device;

wherein the storage control device has a logical unit manager for storing an association between the first network address, a logical unit that is a logical storage area provided to the host computers, and a logical device that is a logical storage area that is set using a storage area provided by the storage device; and

wherein processing for changing the allocation of the storage devices for the host computers, executed by the adjustment executor, is performed by the logical unit manager changing the stored association in relation to the first network address contained in the message.

2. The storage system according to claim 1, wherein processing for changing the allocation of the storage devices for the host computers is included in the processing related to the performance adjustment executed by the adjustment executor.

3. The storage system according to claim 1, wherein processing for giving priority to processing of a specific data input/output request transmitted from the host computers is included in the processing related to the performance adjustment executed by the adjustment executor.

4. The storage system according to claim 2, wherein the processing status data transmitter of the host computers attaches a first network address, which is a network address in the first communication network provided to the host computers, to the processing status data and transmits the obtained data to the management server; the host computers attach the first network address to the data input/output request transmitted to the storage control device via the first communication network; the first network address is set in the message transmitted by the storage control device; and the processing for giving priority to processing of the specific data input/output request transmitted from the host computers, executed by the adjustment executor, including processing that causes the adjustment executor to perform processing so as to give priority to processing related to the data input/output request to which the first network address included in the message is attached.

5. The storage system according to claim 4, wherein the host computers have a configuration information transmitter for attaching a first network address provided to each of the host computers in the first communication network, to configuration information data including data in which information relating to the configuration of the host computers is set, and transmitting the obtained data;

the management server has a configuration information storing unit for receiving and storing the configuration information data;

16

the management server has a configuration-designating information receiver for receiving input of information relating to the configuration;

the management server has a network address specifying unit for specifying the first network address provided to the host computers targeted for adjustment by the adjustment executor based on information relating to the configuration received by the configuration-designating information receiver; and

the management server sets the first network address specified by the network address specifying unit in the message.

6. The storage system according to claim 5, wherein the management server is communicatively connected with the host computers via a second communication network; and the information relating to the configuration including a second network address in the second communication network provided to the host computers.

7. The storage system according to claim 5, wherein at least one item selected from information for specifying the operating system running in the host computers, information for specifying application software running in the host computers, and the names of the host computers is included in the information relating to the configuration.

8. The storage system according to claim 1, wherein the processing status data including the number of data input/output requests that are performed via the first communication network and are registered in the transmission processing waiting queue from the host computers to the storage control device.

9. The storage system according to claim 1, wherein the host computers comprise a first communication interface for communicatively connecting with the storage control device; and the processing status data including the number of data input/output requests that are registered in the transmission processing waiting queue from the host computers of the first communication interface to the storage control device.

10. The storage system according to claim 1, wherein the storage control device functions also as the management server.

11. The storage system according to claim 1, wherein the management server has a communication interface for connecting with the first communication network; and the first network address including a network address provided to the communication interface.

12. The storage system according to claim 1, wherein the storage control device comprises:

- a channel controller for performing communication with the host computers;
- a disk controller for reading and writing data from and to the storage device; and
- cache memory adapted to be accessed by the channel controller and disk controller.

13. The storage system according to claim 1, wherein the storage control device comprises:

- a channel controller for performing communication with the host computers;
- a disk controller for reading and writing data from and to the storage device;
- cache memory adapted to be accessed by the channel controller and disk controller; and
- a processor for functioning as the management server.

17

14. A storage control device in a storage system, the storage system including:

a plurality of host computers, and the storage control device, which is communicatively connected with the host computers via a first communication network to receive a data input/output request transmitted from the host computers and to read or write data from or to the storage device according to the data input/output request received,

a management server, for managing the storage system, communicatively connected with the host computers and the storage control device;

wherein each of the host computers has a processing status data transmitter for transmitting to the management server processing status data including data that indicate the status of processing related to the data input/output request being processed;

wherein the management server has a message receiver for receiving the processing status data and transmitting to the storage control device a message that relates to performance adjustment of the storage control device for the host computers and is determined according to the processing status data received; and

the storage control device comprising:

a channel controller for performing communication with the host computers;

a disk controller for reading and writing data from and to the storage device;

cache memory adapted to be accessed by the channel controller and disk controller;

a processor for receiving a message that relates to performance adjustment of the storage control device, receiving the processing status data transmitted from the host computers, and executing processing related to performance adjustment of the storage control device with respect to the host computers, determined according to the processing status data received;

wherein the storage control device stores the utilization rate of each logical device;

wherein the storage control device has a logical unit manager for storing an association between the first network address, a logical unit that is a logical storage area provided to the host computers, and a logical device that is a logical storage area that is set using a storage area provided by the storage device; and

wherein processing for changing the allocation of the storage devices for the host computers, executed by the adjustment executer, is performed by the logical unit manager changing the stored association in relation to the first network address contained in the message.

15. The storage control device according to claim 14, wherein processing for changing the allocation of the storage devices for the host computers is included in the processing related to the performance adjustment executed by the adjustment executer.

16. The storage control device according to claim 14, wherein processing for giving priority to processing of a specific data input/output request transmitted from the host computers is included in the processing related to the performance adjustment executed by the adjustment executer.

17. A control method for a storage system that comprises: a plurality of host computers;

a storage control device which is communicatively connected with the host computers via a first communication network, to receive a data input/output request transmitted from the information-processing devices,

18

and to read or write data from or to a storage device according to the data input/output request received; and a management server, for managing the storage system, communicatively connected with the host computers and storage control device,

wherein each of the host computers transmits processing status data, which includes data that indicate the status of processing related to the data input/output request being processed, to the management server;

wherein the management server receives the processing status data and transmits to the storage control device a message which relates to performance adjustment of the storage control device for the first information-processing devices and is determined according to the processing status data received;

wherein the storage control device receives the message and executes processing related to performance adjustment of the host computers according to the message received;

wherein a first network address including a network address in the first communication network is provided to the host computers;

wherein the first network address is set in the message received by the storage control device;

wherein the storage control device stores the utilization rate of each logical device;

wherein the storage control device stores an association between the first network address, a logical unit that is a logical storage area provided to the host computers, and a logical device that is a logical storage area that is set using a storage area provided by the storage device; and

wherein processing for changing the allocation of the logical device for the host computers is performed by changing the association stored for the first network address included in the message.

18. The control method for a storage system according to claim 17, wherein

the host computers attach a first network address, which is a network address in the first communication network provided to the host computers, to the processing status data and transmit the obtained to the management server;

the host computers attach the first network address to the data input/output request transmitted to the storage control device via the first communication network;

the first network address is set in the message transmitted by the storage control device; and

the processing for giving priority to processing of the specific data input/output request transmitted from the host computers including processing that causes priority to be given to processing related to the data input/output request to which the first network address included in the message is attached.

19. A control method for a storage system, the storage system including a plurality of host computers, a storage control device communicatively connected to the host computers via a first communication network, a management server, for managing the storage system, communicatively connected with the host computers and storage control device, the control method comprising:

receiving, by the storage control device, a data input/output request transmitted from the host computers;

reading or writing, by the storage control device, data from or to a storage device according to the data input/output request received;

19

transmitting, by a status data transmitter, processing status data, which consists of data that indicates the status of processing related to the data input/output request being processed, to the management server;

receiving, by a message receiver, the processing status data and transmitting to the storage control device a message which relates to performance adjustment of the storage control device for the host computers according to the processing status data received;

receiving, by an adjustment executor of the storage control device, the message and executing, by the adjustment executor, processing related to the performance adjustment of the host computers according to the message received;

providing to the host computers a first network address including a network address in the first communication network;

20

setting, in the message received by the storage control device, the first network address;

storing, by the storage control device, the utilization rate of each logical device;

wherein the storage control device has a logical unit manager for storing an association between the first network address, a logical unit that is a logical storage area provided to the host computers, and a logical device that is a logical storage area that is set using a storage area provided by the storage device; and

wherein processing for changing the allocation of the storage devices for the host computers, executed by the adjustment executor, is performed by the logical unit manager changing the stored association in relation to the first network address contained in the message.

* * * * *