

US007222413B2

(12) **United States Patent**
Hamasaki et al.

(10) **Patent No.:** **US 7,222,413 B2**
(45) **Date of Patent:** **May 29, 2007**

(54) **BOARD TRANSFERRING APPARATUS INCLUDING IDENTIFYING DEVICES, AND COMPONENT MOUNTING APPARATUS INCLUDING THE BOARD TRANSFERRING APPARATUS**

(75) Inventors: **Kurayasu Hamasaki**, Neyagawa (JP); **Makito Seno**, Hirakata (JP); **Kunio Sakurai**, Toyonaka (JP); **Hiroshi Ota**, Katano (JP); **Akiko Katsui**, Neyagawa (JP); **Yoshiyuki Nagai**, Toyonaka (JP)

(73) Assignee: **Matsushita Electric Industrial Co., Ltd**, Osaka (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/960,983**

(22) Filed: **Oct. 12, 2004**

(65) **Prior Publication Data**

US 2005/0077143 A1 Apr. 14, 2005

Related U.S. Application Data

(62) Division of application No. 09/853,681, filed on May 14, 2001, now Pat. No. 6,836,960.

(30) **Foreign Application Priority Data**

May 15, 2000 (JP) 2000-141611
May 22, 2000 (JP) 2000-149773

(51) **Int. Cl.**
B23P 19/00 (2006.01)

(52) **U.S. Cl.** 29/740; 29/739; 29/832

(58) **Field of Classification Search** 29/832,
29/739, 740

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,202,092 A *	5/1980	Shibasaki et al.	29/741
4,850,104 A *	7/1989	Matrone et al.	29/829
4,999,578 A *	3/1991	Ohashi et al.	324/754
5,778,524 A *	7/1998	Stridsberg	29/836
5,899,446 A	5/1999	Thompson	
6,453,548 B1	9/2002	Hidese	

FOREIGN PATENT DOCUMENTS

JP	04-176528	6/1992
JP	10-256785	9/1998
JP	2002-515655	5/2002

* cited by examiner

Primary Examiner—Richard Chang

(74) *Attorney, Agent, or Firm*—Wenderoth, Lind & Ponack L.L.P.

(57) **ABSTRACT**

The present invention has for its object to provide an apparatus and a method for transferring boards, and a component mounting apparatus whereby a production efficiency can be improved in accordance with types of boards to be produced. For accomplishing this object, there are arranged a shift device capable of moving a mounted board from a process-finished board transfer path to an unprocessed board transfer path, a controller for controlling this moving, and an identifying device. This arrangement enables switching of a method of transferring boards in accordance with types of boards to be produced, and controlling supply of boards to the component mounting apparatus, so that production efficiency is improved in accordance with types of boards.

20 Claims, 16 Drawing Sheets




Fig. 1




Fig. 2





Fig. 3






Fig. 4

Fig. 5





Fig. 6








Fig. 8









Fig. 11






Fig. 12

Fig. 13




Fig. 14





Fig. 15







Fig. 17



1

**BOARD TRANSFERRING APPARATUS
INCLUDING IDENTIFYING DEVICES, AND
COMPONENT MOUNTING APPARATUS
INCLUDING THE BOARD TRANSFERRING
APPARATUS**

This application is a Divisional of U.S. Ser. No. 09/853,681, filed May 14, 2001 now U.S. Pat. No. 6,836,960.

TECHNICAL FIELD

The present invention relates to a board transferring apparatus for transferring boards, e.g., printed boards or the like to a component mounting apparatus which mounts components, e.g., electronic components or the like to the boards, a board transfer method performed by the board transferring apparatus, and a component mounting apparatus used with the board transferring apparatus.

BACKGROUND ART

In accordance with widespread use of lead-wire less electronic components, namely, so-called chip components, components vary in shape and size. Since an electronic circuit is constituted by combining such electronic components, a much higher speed and a high reliability are demanded to be secured for electronic component mounting apparatuses which fix the electronic components to printed boards.

A plurality of the electronic component mounting apparatuses of the type referred to above are generally used in order to mount the electronic components to many printed boards. Since a loading operation of the printed board takes place for each component mounting apparatus when a plurality of the component mounting apparatuses are employed for one board transfer path, there is a problem that a degree of increase in production efficiency lowers as compared with a degree of increase in a number of apparatuses to be set. Suppose, for example, that a board loading time at each component mounting apparatus is 4 seconds and a mounting time of all electronic components is 10 seconds, then one component mounting apparatus requires 14 (10+4) seconds and two component mounting apparatuses require 9 (10/2)+4) seconds to produce one complete board.

The applicant of the present invention has disclosed an invention as a technique for solving the above problem in a publication of unexamined patent application of JP, 10-256785, A. A constitution and an operation of a printed board transferring apparatus disclosed in the published application of the above JP, 10-256785, A will be described below with reference to FIG. 9.

Roughly speaking, a component mounting apparatus 1 shown in FIG. 9 comprises two mounting parts 2A, 2B arranged in series, moving devices 3A, 3B for boards to be mounted, which are set respectively to the mounting parts 2A, 2B, a carry-in device 4 for supplying unmounted boards 7 to the mounting parts 2A, 2B, and a carry-out device 5 for transferring mounted boards 8 sent out from the mounting parts 2A, 2B. Although the carry-in device 4 and the carry-out device 5 are illustrated as if arranged in parallel in the same plane in FIG. 9 to facilitate a graphic representation and description, and moreover understanding, the carry-out device 5 and the carry-in device 4 are actually placed in an overlapping manner so as to be arranged on upper and lower sides to make the apparatus compact.

2

The moving devices 3A, 3B for boards to be mounted have loader conveyors 31A, 31B which reciprocate between the carry-in device 4 and the mounting parts 2A, 2B to supply unmounted boards 7 from the carry-in device 4 to the mounting parts 2A, 2B, and unloader conveyors 32A, 32B which reciprocate between the mounting parts 2A, 2B and the carry-out device 5 to send out mounted boards 8 from the mounting parts 2A, 2B to the carry-out device 5. Since the carry-in device 4 and the carry-out device 5 are set in an overlapping manner in an up-down direction as mentioned above, the loader conveyors 31A, 31B move slantwise along a first direction 10 orthogonal to a board transfer direction 9, while the unloader conveyors 32A, 32B, positioned at an equal height as that of the carry-out device 5, move at this height in a second direction 11.

The component mounting apparatus I constituted as above operates in a manner to be described below.

When the mounting part 2A is not operating, an unmounted board 7 transferred by the carry-in device 4 from upstream equipment (not shown) is carried by the loader conveyor 31A into the mounting part 2A, and then all electronic components are mounted onto the unmounted board 7 at the mounting part 2A. A mounted board 8 with the components mounted thereon is carried by the unloader conveyor 32A to the carry-out device 5 and then transferred by the carry-out device 5 to equipment of a next process.

If the mounting part 2A is operating, the unmounted board 7 is transferred by the carry-in device 4, to pass a section of the mounting part 2A, to the mounting part 2B. When the mounting part 2B is not operating at this time, the unmounted board 7 is carried into the mounting part 2B by the loader conveyor 31B, and then all electronic components are mounted onto the unmounted board 7 by the mounting part 2B. A mounted board 8 with the components mounted thereon is sent out by the unloader conveyor 32B to the carry-out device 5 and transferred by the carry-out device 5 to next process equipment.

In producing one mounted board 8 in the component mounting apparatus 1 as described above, a loading operation of boards to the mounting parts 2A, 2B is completed at a time irrespective of a number of mounting parts. In other words, boards 7 can be supplied independently to each of the mounting parts 2A, 2B because of presence of the carry-in device 4 and the carry-out device 5. Given, for instance, that a board loading time and a mounting time at each of the mounting parts 2A, 2B are 4 seconds and 10 seconds, respectively, and since boards 7 can be supplied and equipped with components at the same time at the mounting parts 2A, 2B, a line Tact necessary for producing one finished board becomes (10+4)/2, i.e. 7 seconds, and shortened by 2 seconds in comparison with the earlier-mentioned 9 seconds.

The invention disclosed by the published application of the above JP, 10-256785, A is aimed to provide a board transfer method whereby a production efficiency of an electronic component mounting apparatus can be improved by shortening a loading time per board sent out from component mounting apparatus 1 on an understanding that each mounting part 2A, 2B can mount all necessary electronic components for producing one mounted board 8. However, as in recent years, a production form, in which a volume of production is relatively low and there are a wide variety of products to be made, is frequently practiced. Therefore, a condition that all of electronic components are mounted by one mounting part without fail is difficult to maintain.

Concretely, in a case, for example, where a number of types of electronic components necessary for manufacturing one mounted board **8** is more than a number of types of components which one mounting part can provide, all electronic components cannot be mounted by the one mounting part. In such a case as this, there is a problem in that it is necessary to set another component mounting apparatus, having another constitution, in order to mount remaining components.

The present invention is devised to solve the above problems and has for its object to provide a board transferring apparatus and method, and a component mounting apparatus which can improve a production efficiency in accordance with types of boards to be produced.

SUMMARY OF THE INVENTION

In accomplishing the above and other objects, a board transferring apparatus provided according to a first aspect of the present invention transfers boards between the apparatus and a component-mounted board production apparatus, which comprises:

an unprocessed board transfer unit including an unprocessed board transfer path along which an unprocessed board, as a board not yet processed by the component-mounted board production apparatus, is transferred, and an unprocessed board carry-in device which moves between the unprocessed board transfer path and the component-mounted board production apparatus, thereby carrying the unprocessed board into the component-mounted board production apparatus;

a process-finished board send-out unit including a process-finished board transfer path along which a process-finished board, as a board processed by the component-mounted board production apparatus, is transferred, for carrying the process-finished board out from the component-mounted board production apparatus by moving between the process-finished board transfer path and the component-mounted board production apparatus; and

a shift device which moves between the unprocessed board transfer path and the process-finished board transfer path for shifting a board between the unprocessed board transfer path and the process-finished board transfer path.

At least one shift device can be equipped when a plurality of component-mounted board production apparatuses are arranged in series in a transfer direction of an unprocessed board and a process-finished board.

The board transferring apparatus may further comprise a controller for controlling operations of the unprocessed board transfer unit, the process-finished board transfer unit and the shift device.

In a case where a plurality of component-mounted board production apparatuses, for executing different processes, are arranged along the transfer direction of the unprocessed board and the process-finished board, the shift device may be disposed between a first component-mounted board production apparatus and a second component-mounted board production apparatus for executing mutually different processes, while the controller can control the shift device to shift process-finished boards carried out from the first component-mounted board production apparatus to the process-finished board transfer path, to the unprocessed board transfer path.

The controller can control operations of the unprocessed board transfer unit, the process-finished board transfer unit and the shift device on a basis of an arrangement of the

component-mounted board production apparatus along the transfer direction and a processing program to be executed for boards.

According to a second aspect of the present invention provided is a board transfer method which comprises:

carrying an unprocessed board, as a board not processed by a component-mounted board production apparatus, from an unprocessed board transfer path into the component-mounted board production apparatus;

sending out a process-finished board, as a processed board, to a process-finished board transfer path after being processed in the component-mounted board production apparatus; and

moving the process-finished board from the process-finished board transfer path to the unprocessed board transfer path.

A component mounting apparatus according to a third aspect of the present invention comprises the board transferring apparatus of the first aspect.

According to the board transferring apparatus of the first aspect, the board transfer method of the second aspect, and the component mounting apparatus of the third aspect of the present invention, since the shift device is provided, it is possible to supply an unprocessed board from the unprocessed board transfer path to the component-mounted board production apparatus, process the unprocessed board in the component-mounted board production apparatus and transport a process-finished board, sent out to the process-finished board transfer path, to the unprocessed board transfer path again, such that the process-finished board can be supplied from the unprocessed board transfer path to another component-mounted board production apparatus. A production efficiency can be improved in accordance with types of boards to be produced.

A plurality of component-mounted board production apparatuses are arranged in series in the transfer direction together with the controller which controls the shift device to transport a process-finished board, sent out from a first component-mounted board production apparatus to the process-finished board transfer path, to the unprocessed board transfer path. Therefore, various production forms for boards can be met without changing a layout in a factory including a layout of a board production line and incidental facilities, and the like. Production efficiency can hence be improved in accordance with types of boards to be produced.

Further, the controller is adapted to control operations of the unprocessed board transfer unit, the process-finished board transfer unit, and the shift device based on an arrangement of the component-mounted board production apparatus and a processing program to be executed for the boards, whereby production efficiency can be improved in accordance with kinds of boards to be produced.

According to a board transferring apparatus according to a fourth aspect of the present invention for transferring boards on a board transfer path and between the board transfer path and a component-mounted board production apparatus while the component-mounted board production apparatus is disposed along the board transfer path where boards are transferred in a transfer direction, the board transferring apparatus comprises:

a board carry-in unit which moves between the board transfer path and the component-mounted board production apparatus, thereby carrying a board into the component-mounted board production apparatus;

a board send-out unit which moves between the board transfer path and the component-mounted board production

5

apparatus, thereby sending the board from the component-mounted board production apparatus to the board transfer path;

an identifying device disposed on the board transfer path for identifying a carry-in propriety display part on the board indicative of whether or not the board can be carried into the component-mounted board production apparatus; and

a controller for determining whether or not the board is to be carried into the component-mounted board production apparatus on a basis of an identification result of the carry-in propriety display part identified by the identifying device, and controlling an operation of the board carry-in unit.

When the controller determines that the board is to be carried into the component-mounted board production apparatus on the basis of the identification result, the controller is adapted to have the board carry-in unit carry the board into the component-mounted board production apparatus, have the board processed by the component-mounted board production apparatus and have this processed board sent by the board send-out unit to the board transfer path.

When a plurality of component-mounted board production apparatuses are arranged in series along the board transfer path, with an identifying device being provided corresponding to each of the component-mounted board production apparatuses, the controller determines on a basis of an identification result whether or not an identified board is to be carried into one of the component-mounted board production apparatuses and can allow the identified board to be transferred along the board transfer path in the transfer direction when determining that the identified board is not to be carried into the component-mounted board production apparatus.

A recognizing device may further be included in the board transferring apparatus, which is disposed corresponding to a component-mounted board production apparatus arranged at a trail end in the transfer direction, from among a plurality of component-mounted board production apparatuses, for recognizing a propriety of processing by the component-mounted board production apparatuses for a board transferred along the board transfer path.

A carry-in propriety display part can be a mark preliminarily applied to the board.

According to a fifth aspect of the present invention provided is a board transfer method for transferring boards to a board transfer path, and between the board transfer path and a component-mounted board production apparatus disposed along the board transfer path, wherein the boards are transferred in a transfer direction, which comprises:

identifying a carry-in propriety display part of a board transferred along the board transfer path; and

determining, on a basis of an identification result, whether or not the board is to be carried into the component-mounted board production apparatus.

A component mounting apparatus according to a sixth aspect of the present invention is equipped with the board transferring apparatus of the fourth aspect.

According to the board transferring apparatus of the fourth aspect, the board transfer method of the fifth aspect, and the component mounting apparatus of the sixth aspect of the invention, since the identifying device and the controller are included, it is possible to determine whether or not a board can be moved to the component-mounted board production apparatus and, on a basis of this determination result, whether the board is to be supplied from the board transfer path to the component-mounted board production apparatus. Thus, a production efficiency is improved in accordance with types of boards to be produced.

6

When a plurality of component-mounted board production apparatuses are arranged in series in the transfer direction, with an identifying device being provided corresponding to each component-mounted board production apparatus, the controller determines a carry-in propriety for each component-mounted board production apparatus and controls supply of boards, on a basis of this determination result, from the board transfer path to each component-mounted board production apparatus. Various production forms for boards can be met without greatly changing a layout in a factory including a layout of a board production line and incidental facilities, and the like. Production efficiency can be improved in accordance with kinds of boards to be produced.

A recognizing device is installed corresponding to a component-mounted board production apparatus at a trail end when a plurality of component-mounted board production apparatuses are arranged, so that propriety of processing for each component-mounted board production apparatus is recognized by the recognizing device. Therefore, boards can be prevented from being sent out in a state without being processed at a next component-mounted board production apparatus.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other aspects and features of the present invention will become clear from the following description taken in conjunction with the preferred embodiments thereof with reference to the accompanying drawings, in which:

FIG. 1 is a diagram showing a constitution of a component mounting apparatus according to a first embodiment of the present invention;

FIG. 2 is a front view of the component mounting apparatus shown in FIG. 1;

FIG. 3 is a diagram showing structure of an unprocessed board carry-in device included in the component mounting apparatus shown in FIG. 1;

FIG. 4 is an oblique view showing structure of a component supply/mounting machine included in the component mounting apparatus shown in FIG. 1;

FIG. 5 is a diagram showing structure of a process-finished board send-out device included in the component mounting apparatus shown in FIG. 1;

FIG. 6 is an oblique view showing structure of a shift device included in the component mounting apparatus shown in FIG. 1;

FIG. 7 is a diagram of a component mounting apparatus comprising two component mounting apparatuses of FIG. 1 arranged in series;

FIG. 8 is a diagram of a component mounting apparatus comprising six component mounting apparatuses of FIG. 1 arranged in series;

FIG. 9 is a diagram showing structure of a conventional component mounting apparatus;

FIG. 10 is a diagram showing a constitution of a component mounting apparatus according to a second embodiment of the present invention;

FIG. 11 is a side view of the component mounting apparatus shown in FIG. 10;

FIG. 12 is an oblique view showing structure of a component supply/mounting machine included in the component mounting apparatus shown in FIG. 10;

FIG. 13 is a diagram showing structure of a board carry-in device included in the component mounting apparatus shown in FIG. 10;

7

FIG. 14 is a diagram showing structure of a board send-out device included in the component mounting apparatus shown in FIG. 10;

FIG. 15 is a diagram for explaining a component mounting operation performed by a component mounting apparatus constituted of four component mounting apparatuses of FIG. 10 arranged in series;

FIG. 16 is a diagram for explaining a component mounting operation performed by a component mounting apparatus constituted of four component mounting apparatuses of FIG. 10 arranged in series; and

FIG. 17 is a diagram for explaining a component mounting operation performed by a component mounting apparatus constituted of four component mounting apparatuses of FIG. 10 arranged in series.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

A board transferring apparatus, a board transfer method executed by the board transferring apparatus, and a component mounting apparatus equipped with the board transferring apparatus which are embodiments of the present invention will be described hereinbelow with reference to the drawings. It is to be noted that like parts are designated by like reference numerals throughout the drawings.

A printed board will be given as an example of a board, that is transfer object, in the board transferring apparatus in first and second embodiments below, and a component supply/mounting machine for supplying and mounting electronic components, as an example of components, onto the printed board will be exemplified as one of devices having functions exerted by a component-mounted board production apparatus attached to the board transferring apparatus in the first and second embodiments. However, the component-mounted board production apparatus and the board are not limited to the above and, the component-mounted board production apparatus can be, e.g., a printing apparatus for printing a solder paste to boards, a reflow apparatus for melting the solder paste to thereby solder components, or the like, and eventually the board can be, e.g., a board before having the solder paste printed, a board with the solder paste and components set, or the like. It is to be noted that, while the printing apparatus and the reflow apparatus are often normally constituted singly, the first and the second embodiments to be described below are directed to an electronic component mounting equipment which employs such plural apparatus.

First Embodiment

In FIGS. 1 and 2 is shown a component mounting apparatus 101 which is provided with a board transferring apparatus 120 according to the present first embodiment, and which also includes a component supply/mounting machine 110 for receiving a supply of unmounted boards 7 from the board transferring apparatus 120, mounting components onto these boards and then sending out a mounted board 8 with electronic components mounted thereon, after this mounting, to the board transferring apparatus 120, and a controller 180 for controlling operations of the board transferring apparatus 120 and the component supply/mounting machine 110. In the present first embodiment, an example of unprocessed boards corresponds to the above unmounted board 7, and an example of process-finished boards corresponds to the above mounted board 8. In unmounted boards 7 are included one having one circuit

8

exerting one function formed on one side, and one having a plurality of circuits each exerting the same function formed on one side.

Although the controller 180 is indicated to be separately arranged from the component mounting apparatus in FIG. 1, the controller may be arranged inside the component mounting apparatus or can be arranged for every part constituting the component mounting apparatus.

Moreover, although an unprocessed board transfer path 1211 and a process-finished board transfer path 1221 to be described below are illustrated in FIGS. 1, 7 and 8 as if arranged in parallel in the same plane to facilitate a graphic expression and understanding of the invention, actually, the unprocessed board transfer path 1211 and the process-finished board transfer path 1221 are disposed overlapping one another in a vertical direction as shown in FIG. 3 from a viewpoint of saving space in the board transferring apparatus 120 of the present first embodiment. Needless to say, the arrangement of the unprocessed board transfer path 1211 and the process-finished board transfer path 1221 is not limited to the above-described positional relationship and can be made parallel in the same plane as shown in FIG. 1, and the like. In addition, although the process-finished board transfer path 1221 is set to an upside and the unprocessed board transfer path 1211 is placed below the process-finished board transfer path in the present first embodiment as will be discussed later, this arrangement may be inverted.

The component supply/mounting machine 110 is a high-speed type machine of a so-called rotary form and comprises, as shown in FIG. 4, a component hold/mounting unit 111, a component supply unit 112 for supplying electronic components to the component hold/mounting unit 111, an XY-table 113 movable in XY-directions orthogonal to each other for loading an unmounted board 7 thereon, and a board supply/send unit 114 for supplying the unmounted board 7 to the XY-table 113 and sending the unmounted board 7 from the XY-table 113.

The component hold/mounting unit 111 has a rotating device 1111 and a rotary part 1112 intermittently rotatable by the rotating device 1111 by a predetermined angle. To a periphery of the rotary part 1112 are set, so as to move up and down, component hold/lift parts 1113 spaced from one another at equal intervals and each having a component hold member 1114 fitted to a leading end for holding an electronic component, for example, by suction. The thus-constituted component hold/mounting unit 111 will not move in the XY-directions.

The component supply unit 112 is comprised of component supply parts 1121 with reels 1123 installed for each kind of electronic component 115, which unwinds tapes, storing electronic components 115, from the reels 1123, thereby supplying respective electronic components 115, and a moving device 1122 having component supply parts 1121 set thereto for moving the component supply parts 1121 in the X direction to make the component hold/mounting unit 111 hold desired electronic components 115.

The board supply/send unit 114 has a board transfer passage 1141, and a driving device for transfer 1142 for transferring an unmounted board 7 and mounted board 8 along the board passage 1141. The board transfer passage 1141 is formed of a fixed side rail 125 and a movable side rail 126 extending in parallel along a transfer direction 124 of the unmounted board 7 and mounted board 8. The board transfer passage can be fitted to boards 7, 8 of any size by moving the movable side rail 126 in a breadth direction of the boards 7, 8. The fixed side rail 125 and the movable side rail 126 are provided with belt conveyors capable of sup-

porting opposite side edge portions of respective boards 7, 8. The boards 7, 8 are transferred in the transfer direction 124 by driving each belt conveyor via the driving device 1142 for transfer.

The above-described component hold/mounting unit 111, the component supply unit 112, the XY-table 113, and the board supply/send unit 114 are each connected to the controller 180 and controlled in operation by the controller 180.

The electronic components 115 are supplied and mounted by operations, to be described below, in the component supply/mounting machine 110 constituted as above. Specifically, unmounted board 7 is first placed on the XY-table 113 by the board supply/send unit 114. The unmounted board 7 is moved by the XY-table 113 to below the rotary part 1112 and is further positioned to make a mounting preparation position at the rotary part 1112 agree with a mounting position on the unmounted board 7. In the meantime, the component supply part 1121, which is to supply a desired electronic component 115, is positioned by the moving device 1122 to a component hold position where the component hold member 1114 is to hold the electronic component 115 received from the component supply part 1121. The component hold/lift part 1113 moves down and the component hold member 1114 holds the electronic component 115. After this holding, the component hold/lift part 1113 moves up and the rotary part 1112 is rotated by the rotating device 1111 to arrange the component hold/lift part 1113 to the mounting preparation position for mounting the held electronic component 115 to the board 7. Then, the component hold/lift part 1113 is moved down, thereby mounting the electronic component 115 to the mounting position of the board 7. The component hold/lift part 1113 moves up after this mounting and is disposed again to the component hold position by rotation of the rotary part 1112.

Electronic components 115 are sequentially mounted by each of the component hold members 1114 onto the unmounted board 7 through a repetition of the above operations.

While the component supply/mounting machine 110 in the present first embodiment is a high-speed type machine of the so-called rotary form, the machine is not limited to this and various known component supply/mounting machines, for example, a so-called multi-function type, in which a mounting head part with component hold members 1114 can freely move in XY-directions and can supply components also from trays, and the like, can be adopted.

The board transferring apparatus 120 will be described next.

The board transferring apparatus 120 is comprised of an unprocessed board transfer unit 121, a process-finished board send-out unit 122, and a shift device 123.

The unprocessed board transfer unit 121 is equipped with the unprocessed board transfer path 1211 for transferring unmounted boards 7 to be processed by the component supply/mounting machine 110, and also with an unprocessed board carry-in device 1212 which moves between the unprocessed board transfer path 1211 and the component supply/mounting machine 110 for carrying the unmounted boards 7 into the component supply/mounting machine 110. The unprocessed board transfer path 1211 is formed of a fixed side rail 125 and a movable side rail 126 extending in parallel along the transfer direction 124 of the unmounted boards 7 and mounted boards 8, functioning as a bypass line of the above board transfer passage 1141. The unprocessed board transfer path 1211 can be conformed to unmounted boards 7 of various sizes by moving the movable side rail 126 in a breadth direction of the unmounted boards 7. A belt

conveyor is set to each of the fixed side rail 125 and the movable side rail 126, which is capable of supporting opposite side edge portions of the unmounted board 7. Each unmounted board 7 is transferred in the above transfer direction 124 by driving each belt conveyor by a driving device 1213 for transferring unmounted boards.

The unprocessed board carry-in device 1212 has, as shown in FIG. 3, a skew board hold part 12121 and a drive part 12122. As is described before and as is clear from FIG. 3, in the first embodiment, since the unprocessed board transfer path 1211 and the process-finished board transfer path 1221 are arranged overlapping one another in the vertical direction, and moreover, the process-finished board transfer path 1221 and the board transfer passage 1141 are arranged to be the same height, the drive part 12122 reciprocates the skew board hold part 12121 slantwise between the unprocessed board transfer path 1211 and the board transfer passage 1141. A sensor 12123, e.g., a limit sensor, a proximity sensor or the like, for detecting that the skew board hold part 12121 is positioned at the unprocessed board transfer path 1211, is provided in the first embodiment. An arrangement position of the skew board hold part 12121 is determined by the controller 180 based on a signal supplied from the sensor 12123 to the controller 180.

The drive part 12122 is constructed from a structure including a ball screw in the present first embodiment, having a motor 121221 corresponding to a driving source being controlled in operation by the controller 180. The skew board hold part 12121 including the above fixed side rail 125 and the movable side rail 126 forms part of the unprocessed board transfer path 1211, when positioned at the unprocessed board transfer path 1211, and forms part of the board transfer passage 1141 when positioned at the board transfer passage 1141.

The unprocessed board carry-in device 1212 of the above constitution operates in a manner as will be described hereinbelow. The skew board hold part 12121 is normally arranged at the unprocessed board transfer path 1211. When it is necessary to carry a transferred unmounted board 7 to the component supply/mounting machine 110, the unmounted board 7 is held between the fixed side rail 125 and the movable side rail 126 of the skew board hold part 12121 and shifted to the board transfer passage 1141 by the drive part 12122. A mounting operation is performed for the unmounted board 7 carried to the board transfer passage 1141. Meanwhile, the skew board hold part 12121 returns to the unprocessed board transfer path 1211 after the unmounted board 7 is carried to the board transfer passage 1141. When it is not necessary to carry the unmounted board 7 to the component supply/mounting machine 110, the unmounted board 7 passes the skew board hold part 12121.

The process-finished board send-out unit 122 has the process-finished board transfer path 1221 for transferring mounted boards 8 processed by the component supply/mounting machine 110 and, a process-finished board send-out device 1222 which moves between the process-finished board transfer path 1221 and the component supply/mounting machine 110 to send a mounted board 8 from the component supply/mounting machine 110 to the process-finished board transfer path 1221. Similar to the above unprocessed board transfer path 1211, the process-finished board transfer path 1221 is constituted of a fixed side rail 125 and a movable side rail 126 extending in parallel along the transfer direction 124, thereby functioning as a bypass line of the board transfer passage 1141. The process-finished board transfer path can be suited to mounted boards 8 of various sizes by moving the movable side rail 126 in a

11

breadth direction of the boards **8**. The fixed side rail **125** and the movable side rail **126** are equipped with belt conveyors that can support opposite side edge portions of mounted board **8**, and therefore the board **8** is transferred in the transfer direction **124** by driving each of the belt conveyors via a driving device **1223** for transferring completely mounted boards.

The process-finished board send-out device **1222** has, as indicated in FIG. **5**, a board hold part **12221** and a drive part **12222**. The drive part **12222** reciprocates the board hold part **12221** between the process-finished board transfer path **1221** and the board transfer passage **1141**. In the present first embodiment, a sensor **12223**, for instance, a limit switch, a proximity sensor or the like is set for detecting that the board hold part **12221** is positioned at the process-finished board transfer path **1221**, so that an arrangement position of the board hold part **12221** is determined by the controller **180** on a basis of a signal supplied from the sensor **12223** to the controller **180**.

The drive part **12222** is formed from a structure including a ball screw in the first embodiment. A motor **12221** corresponding to a driving source is controlled in operation by the controller **180**. The board hold part **12221** with the fixed side rail **125** and the movable side rail **126** forms part of the process-finished board transfer path **1221** when positioned at the process-finished board transfer path **1221**, and forms part of the board transfer passage **1141** when positioned at the board transfer passage **1141**.

The process-finished board send-out device **1222** thus constituted operates as follows. The board hold part **12221** is normally arranged at the process-finished board transfer path **1221**, and is moved by the drive part **12222** from the process-finished board transfer path **1221** to the board transfer passage **1141** when a mounted board **8** is to be carried out from the component supply/mounting machine **110**. After disposed to the board transfer passage **1141**, the board hold part **12221** holds the mounted board **8** between the fixed side rail **125** and the movable side rail **126** of the board hold part **12221**, and is subsequently moved from the board transfer passage **1141** to the process-finished board transfer path **1221**. The mounted board **8** sent to the process-finished board transfer path **1221** is transferred along the process-finished transfer path **1221** in the transfer direction **124** by the driving device **1223** for transferring process-finished boards.

The shift device **123**, which is one of characteristic features constituting the board transferring apparatus **120** of the first embodiment, will be described now.

The shift device **123** has, as indicated in FIG. **6**, a path change part **1231** and a drive part **1232**. The drive part **1232** reciprocates the path change part **1231** up and down between the process-finished board transfer path **1221** and the unprocessed board transfer path **1211**. According to the present first embodiment, a sensor **1233**, e.g., a limit switch, a proximity sensor or the like is installed at each of the process-finished board transfer path **1221** and the unprocessed board transfer path **1211**, whereby an arrangement position of the path change part **1231** is determined by the controller **180** based on a signal supplied from a corresponding sensor **1233** to the controller **180**.

The drive part **1232** is of a structure having an air cylinder in this first embodiment. The air cylinder, corresponding to a driving source, is controlled in operation by the controller **180**. The path change part **1231** having the above fixed side rail **125** and movable side rail **126** forms part of the process-finished board transfer path **1221** when positioned at the process-finished board transfer path **1221**, and forms part

12

of the unprocessed board transfer path **1211** when positioned at the unprocessed board transfer path **1211**.

Since the process-finished board transfer path **1221** and the unprocessed board transfer path **1211** are arranged at an upper side and lower side respectively, the path change part **1231** is moved in an up-down direction by the drive part **1232**. Needless to say, however, a move direction of the path change part **1231** is not limited to this. That is, it is enough for the path change part **1231** to move between the process-finished board transfer path **1221** and the unprocessed board transfer path **1211**.

Although the shift device **123** normally transports a mounted board **8** from the process-finished board transfer path **1221** to the unprocessed board transfer path **1211**, the shift device can transfer an unmounted board **7** from the unprocessed board transfer path **1211** to the process-finished board transfer path **1221**.

Also, while the shift device **123** shifts one board **8**, **7** during one shift operation, the shift device is not restricted to this form of operation and can be adapted to shift a plurality of boards **8**, **7** during one shift operation, for example, by constituting the path change part **1231** so that the plurality of boards **8**, **7** can be aligned in a longitudinal direction along the transfer direction **124**. The path change part **1231** for moving the plurality of boards **8**, **7** is not limited to the above structure and can be configured to hold, e.g., the boards **8**, **7** in layers in a thickness direction of the boards.

Although the shift device **123** of the above constitution will be detailed as to its operation of mounting components, the shift device **123** itself operates roughly in a manner as will be described below. For example, when it is necessary to move a mounted board **8** to the unprocessed board transfer path **1211** while the path change part **1231** is positioned at the process-finished board transfer path **1221**, the path change part **1231** is moved by the drive part **1232** from the process-finished board transfer path **1221** to the unprocessed board transfer path **1211** after holding the mounted board **8** between the fixed side rail **125** and the movable side rail **126** of the path change part **1231**. The mounted board **8** sent into the unprocessed board transfer path **1211** is transferred by the driving device **1213** along the unprocessed board transfer path **1211** in the transfer direction **124**.

One component mounting apparatus **101** is provided in the above-discussed constitution. A further modification can be formed as will be described below.

Specifically, a plurality of component mounting apparatuses **101-1**, **101-2**, . . . may be arranged in the transfer direction **124** as in a component mounting apparatus **102** shown in FIG. **7**. In this case, shift devices **123** can be installed at respective component mounting apparatuses **101-1**, **101-2**, . . . or one shift device **123** can be installed for every plurality of component mounting apparatuses **101**. In other words, at least one shift device **123** is satisfactory.

In a case where a plurality of component-mounted board production apparatuses for carrying out different processes relative to each other are arranged in the transfer direction **124**, shift device **123** may be interposed between a first component-mounted board production apparatus and a second component-mounted board production apparatus, which perform different processes relative to each other. For example, when a plurality of, e.g., six component mounting apparatuses **101-1** to **101-6** are arranged in the transfer direction **124** as in a component mounting apparatus **103** of FIG. **8**, and types of components to be mounted by the component mounting apparatuses **101-1** to **101-3** and by the component mounting apparatuses **101-4** to **101-6** are differ-

ent; in other words, when part of all components are to be mounted by the component mounting apparatuses 101-1 to 101-3, and remaining components are to be mounted by the component mounting apparatuses 101-4 to 101-6, to one unmounted board 7, the shift device 123 can be arranged between the component mounting apparatus 101-3 and the component mounting apparatus 101-4.

A component mounting operation performed by the above-discussed component mounting apparatus will be described hereinbelow with use of the component mounting apparatus 102 in the constitution having two component mounting apparatuses 101-1, 101-2 arranged in series along the transfer direction 124 as shown in FIG. 7 as an example. A component mounting operation for unmounted boards 7 at the component supply/mounting machine (110-1, 110-2) in each component mounting apparatus (101-1, 101-2) is identical to the conventional one and will therefore be briefly described.

All performances of the component mounting operation are controlled by the controller 180. More specifically, the controller 180 has a program stored therein in relation to the component mounting operation such as a relationship between mounting positions on unmounted boards 7 and electronic components 115 to be mounted to the mounting positions, a mounting order, and the like. The controller 180 controls operation of the component supply/mounting machines (110-1, 110-2) and moreover controls operation of the unprocessed board transfer unit 121 including the unprocessed board carry-in device 1212, the process-finished board send-out unit 122 including the process-finished board send-out device 1222, and the shift device 123.

In the description below, unmounted boards 7 transferred from an upstream side of the component mounting apparatus 102 are all identical boards.

An unmounted board 7 transferred on the unprocessed board transfer path 1211 by the driving device 1213, for transferring unprocessed boards from the upstream side of the component mounting apparatus 102, is sent into the skew board hold part 12121 of the unprocessed board carry-in device (1212-1, 1212-2). Regarding a carry-in operation, the controller 180 confirms an arrangement position of the skew board hold part 12121 on a basis of a signal of the sensor 12123, and permits the unmounted board 7 to enter the skew board hold part 12121 as described above when the skew board hold part is positioned at the unprocessed board transfer path 1211. On the other hand, unless the skew board hold part 12121 is positioned at the unprocessed board transfer path 1211, the controller 180 controls operation of the driving device 1213 for transferring unprocessed boards, thereby temporarily stopping the unmounted board 7 at a stop region 1214 located immediately before the unprocessed board carry-in device (1212-1, 1212-2). The controller permits the unmounted board 7 to enter after the skew board hold part 12121 is disposed at the unprocessed board transfer path 1211.

When the unmounted board 7 advances to the skew board hold part 12121, moreover, the controller 180 determines whether or not the unmounted board 7 can be sent into the component supply/mounting machine 110-1 of the component mounting apparatus 101-1 based on factors such as presence of the unmounted board 7 on the XY-table 113, the fact that the component supply/mounting machine 110-1 remains at rest, and the like.

When sending is decided to be possible, the skew board hold part 12121 holding the unmounted board 7 moves to the board transfer passage 1141 from the unprocessed board transfer path 1211. The unmounted board 7 of the skew

board hold part 12121, after reaching the board transfer passage 1141 is transferred along the board transfer passage 1141, loaded on the XY-table 113 disposed at the board transfer passage 1141, positioned to a predetermined position and fixed.

Meanwhile, if sending of the unmounted board 7 into the component supply/mounting machine 110-1 of the component mounting apparatus 101-1 is determined to be impossible, the controller 180 controls the driving device 1213 for transferring unprocessed boards, thereby passing and transferring the unmounted board 7 along the unprocessed board transfer path 1211 through the skew board hold part 12121, located at the unprocessed board transfer path 1211, and through the path change part 1231, which is positioned at the unprocessed board transfer path 1211 of the shift device 123-1 of the component mounting apparatus 101-1. The unmounted board 7 is transferred to the stop region 1214 of the component mounting apparatus 101-2 of a next stage. However, when supplying of the unmounted board 7 to the component mounting apparatus 101-2 is forbidden, that is, when the component mounting apparatus 101-1 and the component mounting apparatus 101-2 are programmed to mount different electronic components, the unmounted board 7 is kept waiting at the skew board hold part 12121 until sending of the unmounted board 7 to the component supply/mounting machine 110-1 is allowed.

If sending of the unmounted board 7 to the component mounting apparatus 101-1 is impossible, whether the unmounted board 7 is to be transferred to the component mounting apparatus 101-2 of the next stage or is to be kept waiting, operation of the unprocessed board carry-in device 1212 is conformed to the mounting program stored in the controller 180 on the basis of the constitution of the component mounting apparatus, a number of electronic components to be mounted and an arrangement position of the shift device 123 as will be described in detail later.

A component mounting operation for the unmounted board 7 is performed when the unmounted board 7 can be carried to the component supply/mounting machine 110-1 and can be disposed to below rotary part 1112 of component hold/mounting unit 111 by XY-table 113 as described above. Concretely, the unmounted board 7 on the XY-table 113 is positioned as described earlier so that a mounting position on the unmounted board 7 agrees with a mounting preparation position of the rotary part 1112, and furthermore, component supply part 1121 is positioned by the moving device 1122 to the component hold position where the component hold member 1114 is to hold an electronic component 115 supplied from the component supply part 1121. After the component hold member 1114 holds the electronic component 115 at the component hold position, the rotary part 1112 rotates to the mounting preparation position, then the electronic component 115 is mounted to the mounting position of the unmounted board 7. After this mounting, the component hold member 1114 moves up and is positioned again to the component hold position by rotation of the rotary part 1112. Electronic components 115 are sequentially mounted to mounting positions on the unmounted board 7 by component hold members 1114 of the rotary part 1112, respectively, in this manner.

After all of predetermined electronic components 115 are mounted, mounted board 8 is removed from the XY-table 113 to the board supply/send unit 114, and is further moved to and held by the board hold part 12221 of the process-finished board send-out device 1222 located at the board transfer passage 1141.

The board hold part **12221** holding the mounted board **8** is moved by the drive part **12222** from the board transfer passage **1141** to the process-finished board transfer path **1221**. The mounted board **8** moved to the process-finished board transfer path **1221** is transferred along the process-finished board transfer path **1221** in the transfer direction **124** by the driving device **1223** and sent to the path change part **1231** of the shift device **123**.

When there are boards **7** or **8** transferred along the process-finished board transfer path **1221** from an upstream side of the component mounting apparatus **101-1**, the board hold part **12221** located at the process-finished board transfer path **1221** lets these boards **7**, **8** alike pass towards a downstream side of the component mounting apparatus **101-1**.

In a case where the program in the controller **180** is constructed so as to change the path change part **1231**, which is positioned at the process-finished board transfer path **1221** and to which a mounted board **8** is carried from the process-finished board transfer path **1221** to the unprocessed board transfer path **1211**, the controller **180** makes the path change part **1231** hold the mounted board **8** and then drives the drive part **1232** of the shift device **123** to move the path change part **1231** from the process-finished board transfer path **1221** to the unprocessed board transfer path **1211**. The mounted board **8** shifted to the unprocessed board transfer path **1211** is sent by the driving device **1213** to the stop region **1214** in the component mounting apparatus **101-2**. Regarding the mounted board **8** carried into the stop region **1214** of the component mounting apparatus **101-2**, control and operation similar to the control and operation which is performed when the unmounted board **7** is sent to the component mounting apparatus **101-1** described above, are performed.

On the other hand, when it is not necessary to move the path change part **1231** from the process-finished board transfer path **1221** to the unprocessed board transfer path **1211**, the path change part **1231** is left as it is positioned at the process-finished board transfer path **1221** to transfer a transferred mounted board **8** to the component mounting apparatus **101-2**.

As described hereinabove, in the component mounting apparatuses **101**, **102** of the present first embodiment, a path for sending out mounted boards **8** can be switched to the process-finished board transfer path **1221** or to the unprocessed board transfer path **1211**. Whether or not to move a mounted board **8** by the shift device **123** from the process-finished board transfer path **1221** to the unprocessed board transfer path **1211** is, as will be detailed below, pursuant to the mounting program stored in the controller **180** on the basis of the constitution of the component mounting apparatus, the number of electronic components to be mounted and the arrangement position of the shift device **123**.

Controlling operation of the unprocessed board carry-in device **1212** and the shift device **123** according to the aforementioned mounting program will be described in detail.

Following operation is performed in a case of completely mounting all of electronic components to be mounted to a printed board, to be produced, by one component mounting apparatus **101**. Specifically, a first unmounted board **7** transferred along the unprocessed board transfer path **1211** is supplied to the component supply/mounting machine **110-1** by the unprocessed board carry-in device **1212-1**, where a mounting operation is performed. A second unmounted board **7** transferred along the unprocessed board transfer path **1211** during the mounting operation passes the skew board hold part **12121** of the unprocessed board carry-in

device **1212-1** because the component mounting apparatus **101-1** is in the middle of the mounting operation, and then is transferred to the unprocessed board carry-in device **1212-2** of the component mounting apparatus **101-2** of the next stage. The second unmounted board is supplied to the component supply/mounting machine **110-2** by the unprocessed board carry-in device **1212-2** to be subjected to a mounting operation.

After all components are mounted to the first unmounted board **7** by the component supply/mounting machine **110-1**, mounted board **8** is sent out by the process-finished board send-out device **1222-1** to the process-finished board transfer path **1221**, and transferred along the process-finished board transfer path **1221** to a next process. A representative example of the next process is a soldering operation or the like. Since the component supply/mounting machine **110-1** becomes able to accept an unmounted board **7** after the mounted board **8** is sent out, a third unmounted board **7** is supplied by the unprocessed board carry-in device **1212-1** to the component supply/mounting machine **110-1**.

Similarly, after all components are mounted to the second unmounted board **7** by the component supply/mounting machine **110-2**, this mounted board **8** is sent out by the process-finished board send-out device **1222-2** to the process-finished board transfer path **1221**, and transferred along the process-finished board transfer path **1221** to the above-mentioned next process. The component supply/mounting machine **110-2** can consequently accept supply of a fourth unmounted board **7**.

In a case where all electronic components to be mounted to a printed board to be produced are mounted by a single component mounting apparatus **101** as described above, this mounted board **8** is not shifted by the shift device **123**, but is sent out from the process-finished board transfer path **1221** in the same manner as in the related art. Therefore, with a plurality of component mounting apparatuses **101-1**, **101-2** arranged as shown in FIG. 7, production efficiency can be improved by sending out mounted boards **8** from respective component mounting apparatuses **101-1**, **101-2**.

On the other hand, if all electronic components to be mounted to a printed board to be produced are not completely mounted by one component mounting apparatus, for example, when part of the electronic components are mounted by the component mounting apparatus **101-1** and the remaining electronic components are mounted by the component mounting apparatus **101-2**, thereby producing one printed board, following operation is performed. A first unmounted board **7** transferred along the unprocessed board transfer path **1211** is supplied by the unprocessed board carry-in device **1212-1** to the component supply/mounting machine **110-1**, and a mounting operation is conducted. After components are mounted to the first unmounted board **7**, a mounted board **8** is carried out by the process-finished board send-out device **1222-1** to the process-finished board transfer path **1221**, then moved by the shift device **123** from the process-finished board transfer path **1221** to the unprocessed board transfer path **1211** and supplied by the unprocessed board carry-in device **1212-2** of the component mounting apparatus **101-2** to the component supply/mounting machine **110-2**. After the remaining components are mounted to the mounted board **8** by the component supply/mounting machine **110-2**, the mounted board **8** is sent out by the process-finished board send-out device **1222-2** from the component supply/mounting machine **110-2** to the process-finished board transfer path **1221**, and transferred along the process-finished board transfer path **1221** to a next process.

Since use of the shift device **123** enables boards to be transported between the unprocessed board transfer path **1211** and the process-finished board transfer path **1221**, need of setting a new mounting line for mounting remaining components is eliminated. Further, even when a printed board to be produced is to be changed, the board transfer units **121**, **122** of the component mounting apparatus of the first embodiment can be used by changing types of components to be mounted by each component supply/mounting machine **110** and by controlling a board movement operation via the shift device **123**.

Accordingly, production efficiency can be improved in accordance with kinds of boards to be produced without greatly changing a layout in a factory, including a layout of a board production line, incidental facilities, and the like.

FIG. **8** shows a constitution in which, for a case where all electronic components to be mounted to a printed board to be produced are not mounted by one component mounting apparatus, six component mounting apparatuses **101-1** to **101-6** are aligned in series along transfer direction **124** so that three component mounting apparatuses **101-1** to **101-3** of an upstream side mount equal components while component mounting apparatuses **101-4** to **101-6** of a downstream side mount equal components, and one shift device **123** is arranged only between component mounting apparatus **101-3** and component mounting apparatus **101-4**. The component mounting apparatuses **101-1** to **101-3** and the component mounting apparatuses **101-4** to **101-6** mount different components relative to each other. Each of the component mounting apparatuses **101-1** to **101-3** mounts part of all components, and each of the component mounting apparatuses **101-4** to **101-6** mounts a remainder of the components.

In the above constitution, a first unmounted board **7** to a third unmounted board **7** transferred along unprocessed board transfer path **1211** are sequentially supplied to component supply/mounting machines **110-1** to **110-3**, respectively. Each of mounted boards **8** having components mounted by the component supply/mounting machines **110-1** to **110-3** respectively is sequentially carried out to process-finished board transfer path **1221**. In this example, three mounted boards **8** are moved by the shift device **123** at a time from the process-finished board transfer path **1221** to the unprocessed board transfer path **1211**. The three mounted boards **8** carried to the unprocessed board transfer path **1211** are sequentially supplied to component supply/mounting machines **110-4** to **110-6** of the component mounting apparatuses **101-4** to **101-6**, respectively, and a mounting operation is performed by each of the component mounting apparatuses **101-4** to **101-6**. Upon completion of these mounting operations, finished printed boards are sequentially sent out from the component supply/mounting machines **110-4** to **110-6** to the process-finished board transfer path **1221** and transferred along the process-finished board transfer path **1221** to a next process.

The above-referred case, that all electronic components to be mounted to a printed board to be produced are not completely mounted by one component mounting apparatus, corresponds not only to a case where it is impossible to have component supply part **1121** supply necessary components for producing one printed board in one component mounting apparatus **101**, but also to a case where different electronic components are only partly used and common electronic components are used for a remaining part of boards for, e.g., models of portable phones, personal computers or the like. In such case as above when only part of the electronic components are different, the common electronic compo-

nents are mounted, for example, by a plurality of component mounting apparatuses **101** arranged, e.g., at the upstream side, then common electronic component-mounted boards **8** are moved by the shift device **123** from the process-finished board transfer path **1221** to the unprocessed board transfer path **1211**, so that different electronic components are mounted by, e.g., a plurality of component mounting apparatuses **101** arranged, e.g., at the downstream side, respectively. Boards in conformity with each model can thus be produced and a need of setting production lines each corresponding to printed boards of each model is eliminated.

According to the board transferring apparatus and the component mounting apparatus with the board transferring apparatus of the first embodiment as above, when a plurality of component mounting apparatuses **101** are arranged, it can meet various forms of production from when each of the component mounting apparatuses **101** mounts all components to each unmounted board **7** to when each of the component mounting apparatuses **101** mutually mounts different components. In other words, by storing into the controller **180** a processing program based on types and an amount of components to be mounted by the component mounting apparatuses **101** arranged along the transfer direction **124**, a setting position of the shift device **123** and a production form performed for the boards, the controller **180** can control operation of the unprocessed board transfer unit **121**, the process-finished board transfer unit **122** and the shift device **123**, so that it can meet the above various forms of production.

As discussed hereinabove, according to the board transferring apparatus, the board transfer method performed by the board transferring apparatus, and the component mounting apparatus having the board transferring apparatus of the first embodiment, since the shift device **123** is included, various forms of production can be met as described above in a space equal to a space occupied by a component mounting apparatus including the unprocessed board transfer path **1211** and the process-finished board transfer path **1221** and disclosed in the published application of JP, 10-256785, A. A layout in a factory, including a layout of a board production line and incidental equipment, and the like is not necessary to be changed substantially.

Provision of the shift device **123** can improve production efficiency in accordance with kinds of boards to be produced, as described above.

The foregoing description is based on unmounted boards **7** transferred from a previous process of the component mounting apparatus **101**, **102** being identical to one another. As in FIGS. **7** and **8**, when a plurality of component mounting apparatuses **101** are arranged along the transfer direction **124** to mount components, it is hard to determine by which of the component supply/mounting machines **110** each of mounted boards **8**, sent out from a mounting process, is to have components mounted thereto. Therefore, for example, when mounting failures frequently occur, it is difficult to specify the component supply/mounting machine **110** causing a mounting failure.

As such, each component mounting apparatus may have a mark application device, which has a different mark in correspondence to each component mounting apparatus, for applying a mark to mounted boards **8**. In this arrangement, the mark application device can apply a mark, specific to a component mounting apparatus, to a mounted board **8** before the board is carried into a component mounting apparatus of a next stage after being sent out by the process-finished board send-out device **1222** to the process-finished board transfer path **1221**. A component mounting

apparatus causing a mounting failure can be specified accordingly, for instance, by confirming the mark applied to the mounted board **8** with the mounting failure.

As described above, although the first embodiment is based on unmounted boards **7** transferred from a previous process of the component mounting apparatus **101**, **102** being identical to one another, the embodiment is not limited to this. For example, boards of different kinds, because of a difference of, e.g., a board size, components mounted beforehand, and the like can be transferred from a previous process. The controller **180** controls operation of the unprocessed board carry-in device **1212** and the shift device **123** in this constitution alike, so that boards can be supplied to component mounting apparatuses corresponding to kinds of boards to complete target mounted boards **8**.

While an operational control of the shift device **123** is performed in accordance with a mounting program stored in the controller **180** in the above first embodiment, control is not limited to this. For example, a detector may be installed before the shift device **123** in the transfer direction **124**. The detector detects an information part which is formed by, e.g., a bar code or the like, attached to a transferred board **8**, **7**, and has information of operational control for the shift device **123**, thereby controlling operation of the shift device **123**.

The component mounting apparatus is depicted as an example of the component-mounted board production apparatus in the above-described first embodiment. In a case, for instance, of a printing apparatus for printing solder paste to boards, the following arrangement and operation can be devised, for example. Concretely, printing apparatuses with respective masks of different sizes are provided, and boards of different sizes corresponding to the respective masks are sequentially transferred. The shift device **123** is controlled in operation so that each board is supplied to a printing apparatus having a proper mask.

Second Embodiment

FIG. **10** shows a component mounting apparatus **201** provided with a board transferring apparatus **221** in a second embodiment, and includes a component supply/mounting machine **210** for receiving an unmounted board **7** from the board transferring apparatus **221**, mounting electronic components onto this board and sending out an electronic component-mounted board **8** to the board transferring apparatus **221** after this mounting, and a controller **280** for controlling operation of the board transferring apparatus **221** and the component supply/mounting machine **210**. According to the present second embodiment, the above unmounted board **7** corresponds to an example of unprocessed boards before being processed by the component-mounted board production apparatus and, the mounted board **8** corresponds to an example of process-finished boards after being processed by the component-mounted board production apparatus. There are included for the unmounted board **7** one case in which one circuit exerting one function is formed on the board, and another case in which a plurality of circuits each exerting the same function are formed on the board.

Although the controller **280** is illustrated in FIG. **10** to be separately arranged from the component mounting apparatus, the controller may be arranged inside the component mounting apparatus or may be arranged for each part constituting the component mounting apparatus.

The component supply/mounting machine **210** is of a high-speed machine type of a so-called rotary form and includes, as shown in FIG. **12**, a component hold/mounting

unit **211**, a component supply unit **212** for supplying electronic components to the component hold/mounting unit **211**, an XY-table **213** movable in mutually orthogonal XY-directions where unmounted boards **7** are loaded, and a board supply/send unit **214** for supplying an unmounted board **7** to the XY-table **213** and sending out the unmounted board **7** from the XY-table **213**.

The component hold/mounting unit **211** has a rotating device **2111** and a rotary part **2112** intermittently rotatable by a predetermined angle via the rotating device **2111**, with a plurality of component hold/lift parts **2113** being arranged at a periphery of the rotary part **2112** at equal intervals to be movable up and down. The component hold/lift parts **2113** have component hold members **2114** attached to leading ends thereof for holding electronic components, e.g., by suction. The component hold/mounting unit **211** constituted as described above cannot move in the XY-directions.

The component supply unit **212** has component supply parts **2121** and a moving device **2122**. The component supply parts have reels **2123** set for each kind of electronic components **215**. Tapes with the electronic components **215** stored therein are wound about respective reels. The component supply parts let off tapes from respective reels **2123**, thereby supplying electronic components **215**. The moving device **2122** to which the component supply parts **2121** are secured moves the component supply parts **2121** in the X-direction so as to make the component hold/mounting unit **211** hold desired electronic component **215**. Although two component supply units **212** are arranged in the present second embodiment, the number is not limited to this.

The board supply/send unit **214** has a board transfer passage **2141** and a driving device **2142** for transferring an unmounted board **7** and mounted board **8** along the board transfer passage **2141**. The board transfer passage **2141**, which is a passage extending in parallel along a transfer direction **224** of the unmounted board **7** and mounted board **8**, is formed of a fixed side rail **225** and a movable side rail **226** and can be fitted to boards **7**, **8** of various sizes by moving the movable side rail **226** in a breadth direction of boards **7**, **8**. The fixed side rail **225** and the movable side rail **226** are provided with belt conveyors capable of supporting opposite side edge portions of the boards **7**, **8**. The boards **7**, **8** are transferred in the aforementioned transfer direction **224** by driving each belt conveyor by the driving device **2142**.

Each of the above-described component hold/mounting unit **211**, the component supply unit **212**, the XY-table **213** and the board supply/send unit **214** is connected to the controller **280** to be controlled in operation by the controller **280**.

In the component supply/mounting machine **210** of the above constitution, electronic components **215** are supplied and mounted by operations as will be described below. Initially, an unmounted board **7** is placed on the XY-table **213** by the board supply/send unit **214**, the unmounted board **7** is moved to below the rotary part **2112** by the XY-table **213** and is positioned so that a mounting preparation position of the rotary part **2112** agrees with a mounting position on the unmounted board **7**. Meanwhile, the component supply part **2121** which is to supply a desired electronic component **215** is positioned by the moving device **2122** to a component hold position where the component hold member **2114** is to hold the electronic component **215** received from the component supply part **2121**, and the component hold/lift part **2113** moves down to hold the electronic component **215** by the component hold member **2114**. After this holding, the component hold/lift part **2113** moves up and the rotary part

21

2112 is rotated by the rotating device 2111, thereby disposing the component hold/lift part 2113 to the mounting preparation position for mounting the held electronic component 215 to the board 7. Next, the component hold/lift part 2113 is moved down to mount the electronic component 215 to the mounting position on the board 7. After this mounting, the component hold/lift part 2113 moves up and is arranged at the component hold position again by rotation of the rotary part 2112.

Electronic components 215 are sequentially mounted onto the unmounted board 7 by component hold members 2114 through a repetition of the above-described operation.

According to the present second embodiment, the component supply/mounting machine 210 is a high-speed machine type of the so-called rotary form. However, the machine is not limited to this type, and various known component supply/mounting machines such as a so-called multi-function type in which, for example, a mounting head part with component hold members 2114 is freely movable in XY-directions and can supply components also from trays, or the like, may be adopted.

Hereinbelow will be described the above-mentioned board transferring apparatus 221.

The board transferring apparatus 221 has one board transfer path 2211 for transferring an unmounted board 7, to be processed by the above described component supply/mounting machine 210, and a mounted board 8 processed by the component supply/mounting machine 210. Moreover, the board transferring apparatus includes a board carry-in device 2212 which moves between the board transfer path 2211 and the component supply/mounting machine 210, thereby carrying an unmounted board 7 to the component supply/mounting machine 210, and further includes a board send-out device 2222 which moves between the board transfer path 2211 and the component supply/mounting machine 210, thereby sending out a mounted board 8 from the component supply/mounting machine 210 to the board transfer path 2211. The board transferring apparatus also includes an identifying device 2215 disposed at the board transfer path 2211 for recognizing carry-in propriety display parts 2216 on the boards 7, 8, which represent whether or not the unmounted board 7 and the mounted board 8 can be sent into the component supply/mounting machine 210, and also includes the controller 280 for controlling operations of the board carry-in device 2212, the board send-out device 2222 and the identifying device 2215, and also judging whether or not the boards 7, 8 are to be carried into the component supply/mounting machine 210 by controlling operation of the board carry-in device 2212 based on an identification result obtained by identifying the carry-in propriety display part 2216 by the identifying device 2215.

The board transfer path 2211 is constituted of a fixed side rail 225 and a movable side rail 226 extending parallel along the transfer direction 224 of unmounted board 7 and mounted board 8, functioning as a bypass line of the board transfer passage 2141. The board transfer path 2211 can be conformed to unmounted boards 7 and mounted boards 8 of various sizes by moving the movable side rail 226 in a breadth direction of the boards 7 and 8. Belt conveyors capable of supporting opposite side edge portions of an unmounted board 7 and mounted board 8 are equipped to each of the fixed side rail 225 and the movable side rail 226. The unmounted board 7 and mounted board 8 are transferred in the above transfer direction 224 by driving each of the conveyors by a driving device 2213.

The board carry-in device 2212 has, as shown in FIG. 13, a supply side board hold part 22121 and a drive part 22122.

22

As indicated in FIGS. 11 and 13, since the board transfer path 2211 and the board transfer passage 2141 are arranged to be an equal height in the second embodiment, the drive part 22122 reciprocates the supply side board hold part 22121 between the board transfer path 2211 and the board transfer passage 2141. According to the second embodiment, a sensor 22123, for instance, a limit switch, a proximity sensor or the like, for detecting that the supply side board hold part 22121 is positioned at the board transfer path 2211, is installed, so that an arrangement position of the supply side board hold part 22121 is determined by the controller 280 based on a signal supplied from the sensor 22123 to the controller 280.

The drive part 22122 is constructed from a structure including a ball screw in the second embodiment, having a motor 221221 corresponding to a driving source controlled in operation by the controller 280. The supply side board hold part 22121 has the fixed side rail 225 and the movable side rail 226, thus forming part of the board transfer path 2211 when arranged at the board transfer path 2211 and forming part of the board transfer passage 2141 when arranged at the board transfer passage 2141.

The above-constituted board carry-in device 2212 operates as will be discussed below. The supply side board hold part 22121, which is normally arranged at the board transfer path 2211, holds an unmounted board 7 between the fixed side rail 225 and the movable side rail 226 of the supply side board hold part 22121 when it is necessary to send this transferred unmounted board 7 to the component supply/mounting machine 210, and moves the unmounted board 7 by the drive part 22122 to the board transfer passage 2141. The unmounted board 7 moved to the board transfer passage 2141 is subjected to a mounting operation. In the meantime, the supply side board hold part 22121 returns to the board transfer path 2211 after sending the unmounted board 7 to the board transfer passage 2141. When it is not necessary to carry the unmounted board 7 into the component supply/mounting machine 210, the unmounted board 7 passes the supply side board hold part 22121.

As shown in FIG. 14, the board send-out device 2222 has a discharge side board hold part 22221 and a drive part 22222. The drive part 22222 reciprocates the discharge side board hold part 22221 between the board transfer path 2211 and the board transfer passage 2141. In the present second embodiment, for instance, a sensor 22223 such as a limit switch, a proximity sensor or the like is installed to detect that the discharge side board hold part 22221 is positioned at the board transfer path 2211, and an arrangement position of the discharge side board hold part 22221 is determined by the controller 280 on a basis of a signal supplied to the controller 280 from the sensor 22223.

The drive part 22222 is formed from a structure including a ball screw in the second embodiment, and a motor 222221 corresponding to a driving source is controlled in operation by the controller 280. The discharge side board hold part 22221 includes the fixed side rail 225 and the movable side rail 226, thereby forming part of the board transfer path 2211 when positioned at the board transfer path 2211 and forming part of the board transfer passage 2141 when positioned at the board transfer passage 2141.

The above-constituted board send-out device 2222 operates as will be described below. The discharge side board hold part 22221 normally arranged at the board transfer path 2211 is moved by the drive part 22222 from the board transfer path 2211 to the board transfer passage 2141 when a mounted board 8 is to be sent out from the component supply/mounting machine 210. After being positioned at the

board transfer passage **2141**, the discharge side board hold part **22221** holds the mounted board **8** between the fixed side rail **225** and the movable side rail **226** of the discharge side board hold part **22221**, and then is moved from the board transfer passage **2141** to the board transfer path **2211**. The mounted board **8** sent to the board transfer path **2211** is transferred by the driving device **2213** along the board transfer path **2211** in the transfer direction **224**.

The identifying device **2215**, which is one of feature characteristics of the board transferring apparatus **221** of the second embodiment and identifies the carry-in propriety display part **2216** on board **7, 8** as mentioned earlier, will be described next.

Carry-in propriety display part **2216** is a part indicative of supply-propriety information showing whether or not an unmounted board **7** and a mounted board **8**, transferred along the board transfer path **2211**, are to be sent to the component supply/mounting machine **210**, and moreover indicating component supply/mounting machine **210** of the component mounting apparatuses **201** to which the unmounted board **7** and the mounted board **8** are to be supplied, for instance, when a plurality of component mounting apparatuses **201** are arranged in series along the transfer direction **224** as shown in FIG. **15**. The display part **2216** is formed of a bar code in the second embodiment and attached, e.g., to an end part on a mounting face of boards **7, 8** where electronic components **215** are mounted, as shown in FIG. **10**. Form of the carry-in propriety display part **2216** is not limited to the above bar code and can be any kind of form so long as each board can be identified, for example, a geometrical shape such as a circle, a triangle, a quadrilateral or the like, a pattern of a die or the like, a board number formed on boards **7, 8**, a wiring pattern, a part processed by the component-mounted board production apparatus, namely, a part on the board where components are mounted according to the second embodiment, and the like. The carry-in propriety display part **2216** is preferably formed in a state in which supply-propriety information can be rewritten to cope with a change in production form to be described later, and the like. For example, an IC memory or the like is included in the carry-in propriety display part **2216** accordingly.

As indicated in FIG. **11**, the identifying device **2215** for identifying the above described carry-in propriety display part **2216** has a detect part **22151** and a determination part **22152**. Since the determination part **22152** is included in the controller **280** in the constitution adopted according to the second embodiment, the detect part **22151** corresponds to the above identifying device **2215**. The detect part **22151** is a device for detecting carry-in propriety display part **2216** and is a generally used bar code reader using LEDs (light-emitting diode) in the second embodiment. The identifying device **2215** may have a function for rewriting supply-propriety information. According to the second embodiment as indicated in FIG. **10**, the detect part **22151** is arranged above the supply side board hold part **22121** positioned at the board transfer path **2211**, so that it can detect carry-in propriety display part **2216** of boards **7, 8** when the boards **7, 8** are disposed at the carry side board hold part **22121** positioned at the board transfer path **2211**. A position where to arrange the detect part **22151** is not limited to that described above. The detect part **22151** may be arranged at a position before boards **7, 8** are carried into the component mounting apparatus **201**, for example, may be arranged above a stop region **2214** so that it can detect carry-in propriety display part **2216** of boards **7, 8** when the boards

7, 8 are arranged at the stop region **2214** formed immediately before the board carry-in device **2212** in the transfer direction **224**.

The determination part **22152** decides on the basis of an identification result of the carry-in propriety display part **2216**, by the detect part **22151**, whether or not boards **7, 8** are to be carried to the component supply/mounting machine **210** and controls operation of the board carry-in device **2212**.

A detailed operation of a component mounting operation of the identifying device **2215** constituted as described above will be described later.

One component mounting apparatus **201** is thus formed in the above-discussed arrangement. A modified example as will be described below can be constructed.

Specifically, as a component mounting apparatus **202** shown in FIG. **15**, a plurality of component mounting apparatuses **201-1, 201-2, . . .** can be arranged in series in transfer direction **224**. In the second embodiment, since both unmounted board **7** and mounted board **8** are transferred along one board transfer path **2211**, with a plurality of component mounting apparatuses arranged, it is necessary to prevent the board **7** from not being supplied to any of component supply/mounting machines **210-1, 210-2, . . .** and being carried out of the component mounting apparatus **202** without having components mounted thereto, for example, as a result of a detection error of a corresponding one of identifying devices **2215-1, 2215-2, . . .**. A processing part in the component-mounted board production apparatus, i.e., a recognizing device **227**, which detects presence/absence of components on a board in the second embodiment, is preferably arranged corresponding to a component-mounted board production apparatus, located at a trail end in the transfer direction **224**, from among the plurality of component mounting apparatuses. The recognizing device **227** is connected to controller **280**, and the controller **280** controls operation of the component mounting apparatus **201-4** at the trail end based on information from the recognizing device **227**.

Component mounting operation in the above-described component mounting apparatus will be described below by taking as an example a component mounting apparatus **202** having four component mounting apparatuses **201-1** to **201-4** arranged in series along the transfer direction **224** as shown in FIGS. **15-17**. It is to be noted here that a component mounting operation for an unmounted board **7** in the component supply/mounting machine of each component mounting apparatus is similar to the conventional operation and will be briefly described.

In addition, all performances of the component mounting operation are controlled by the controller **280**. In other words, a program in relation to the mounting operation, such as a relationship between mounting positions on unmounted board **7** and electronic components **215** to be mounted to the mounting positions, a mounting order, and the like are stored in the controller **280**. The controller **280** controls operation of each component supply/mounting machine and also controls operations of board transferring apparatus **221** including board carry-in devices **2212-1, 2212-2, . . .** and board send-out devices **2222-1, 2222-2, . . .** and identifying devices **2215-1, 2215-2, . . .**

In the following description, unmounted boards **7** transferred from an upstream side of the component mounting apparatus **202** are identical to each other, and four unmounted boards **7A, 7B, 7C, 7D** are transferred in this order. A carry-in propriety display part **2216A** with information, so that the unmounted board **7A** is supplied to the

component mounting apparatus **201-1**, is attached to the unmounted board **7A**; a carry-in propriety display part **2216B** with information, so that the unmounted board **7B** is supplied to the component mounting apparatus **201-2**, is attached to the unmounted board **7B**; a carry-in propriety display part **2216C** with information, so that the unmounted board **7C** is supplied to the component mounting apparatus **201-3**, is attached to the unmounted board **7C**; and a carry-in propriety display part **2216D** with information, so that the unmounted board **7D** is supplied to the component mounting apparatus **201-4**, is attached to the unmounted board **7D**.

The component mounting apparatuses **201-1** to **201-4** are constructed to mount equal components.

The first unmounted board **7A** transferred on the board transfer path **2211** by driving device **2213**, for transferring unmounted boards from the upstream side of the component mounting apparatus **202**, is temporarily stopped by the supply side board hold part **22121** arranged at the board transfer path **2211** of the board carry-in device **2212-1** of the component mounting apparatus **201-1**. As described before, since the controller **280** confirms an arrangement position of the supply side board hold part **22121** based on a signal from the sensor **22123**, unless the supply side board hold part **22121** is positioned at the board transfer path **2211**, the controller **280** controls operation of the driving device **2213** to stop the unmounted board **7A** at the stop region **2214**, and then the unmounted board **7A** is carried to the supply side board hold part **22121** after the supply side board hold part **22121** is positioned at the board transfer path **2211**.

After the unmounted board **7A** is carried to the supply side board hold part **22121**, the identifying device **2215-1** recognizes the carry-in propriety display part **2216A** of the unmounted board **7A**, and the controller **280** determines, based on information from the carry-in propriety display part **2216A**, whether or not the unmounted board **7A** is to be supplied to the component mounting apparatus **201-1**. In this case, information of supplying the unmounted board **7A** to the component mounting apparatus **201-1** is described in the carry-in propriety display part **2216A**, and therefore the controller **280** controls operation of the motor **221221** of the board carry-in device **2212-1** for arranging the supply side board hold part **22121** at the board transfer passage **2141** so as to supply the unmounted board **7A** to the component mounting apparatus **201-1**, and after this arranging the controller **280** transfers the unmounted board **7A** along the board transfer passage **2141**. The supply side board hold part **22121** returns to the board transfer path **2211** after the unmounted board **7A** is carried to the board transfer passage **2141**.

The unmounted board **7A** is transferred along the board transfer passage **2141** to the XY-table **213** arranged at the board transfer passage **2141**, placed on the XY-table **213**, positioned to a predetermined position and held. After the board is held to the XY-table **213**, the XY-table **213** is arranged below component hold/mounting unit **211**. After this arrangement, an electronic component **215** is mounted onto the unmounted board **7A** by the component supply/mounting machine **210-1** as described earlier. More specifically, the unmounted board **7A** on the XY-table **213** is positioned so that a mounting position on the unmounted board **7A** agrees with a mounting preparation position of rotary part **2112**, and at the same time, component supply part **2121** is positioned by moving device **2122** to the component hold position where component hold member **2114** is to hold the electronic component **215** received from the component supply part **2121**. After the component hold member **2114** holds the electronic component **215** at the

component hold position, the rotary part **2112** rotates to the mounting preparation position, whereby the electronic component **215** is mounted to the mounting position of the unmounted board **7A**. The component hold member **2114** moves up after this mounting and is arranged at the component hold position again through rotation of the rotary part **2112**. Electronic components **215** are sequentially mounted to respective mounting positions on the unmounted board **7A** by component hold members **2114** of the rotary part **2112** in this manner.

On the other hand, while the electronic components **215** are mounted onto the unmounted board **7A**, boards **7B**, **7C**, **7D** are sequentially temporarily stopped by the supply side board hold part **22121** of the component mounting apparatus **201-1**, and the carry-in propriety display parts **2216B**, **2216C**, **2216D** are recognized by the recognizing device **2215-1**. Since the carry-in propriety display parts **2216B**, **2216C**, **2216D** do not include information of ordering supply to the component mounting apparatus **201-1**, each of the unmounted boards **7B**, **7C**, **7D** is determined as not to be taken into the component mounting apparatus **201-1**, and is carried to the component mounting apparatus **201-2** by being passed along the board transfer path **2211** through the supply side board hold part **22121**, the discharge side board hold part **22221** of the component mounting apparatus **201-1**, and a path **2217-1** for connection.

Similar to the earlier-described supply and mounting operation for the unmounted board **7A** at the component mounting apparatus **201-1**, the unmounted board **7B** is permitted to be supplied to the component supply/mounting machine **210-2** of the component mounting apparatus **201-2** through a recognition operation performed by the recognizing device **2215-2** included in the component mounting apparatus **201-2**, and subjected to a mounting operation by the component supply/mounting machine **210-2**. The unmounted board **7C** is permitted to be supplied to the component supply/mounting machine **210-3** of the component mounting apparatus **201-3** by a recognition operation of the recognizing device **2215-3** of the component mounting apparatus **201-3**, and subjected to a mounting operation by the component supply/mounting machine **210-3**. For the unmounted board **7D**, supply to the component supply/mounting machine **210-4** of the component mounting apparatus **201-4** is permitted by a recognition operation of the recognizing device **2215-4** of the component mounting apparatus **201-4**, so that components are mounted to board **7D** by the component supply/mounting machine **210-4**.

In the meantime, mounted board **8A**, formed by mounting all of predetermined electronic components **215** to the unmounted board **7A**, is transferred from the XY-table **213** to board supply/send unit **214**, further sent to discharge side board hold part **22221**, arranged at the board transfer passage **2141**, of board send-out device **2222-1** of the component mounting apparatus **201-1**, and then held by the discharge side board hold part **22221**. This mounted board is then returned to the board transfer path **2211** by the discharge side board hold part **22221**.

While the unmounted boards **7B**, **7C**, **7D** are transferred along the board transfer path **2211** as described above, the controller **280** controls a transfer operation for each board so as to prevent interference of transfer of the unmounted boards **7B**, **7C**, **7D** with transfer of the mounted board **8A**, and to be able to shorten a Tact. For example, a state is shown in FIG. **15** in which, during the mounting operation of the unmounted board **7A** performed by the component mounting apparatus **201-1**, the unmounted board **7B** is supplied to the component supply/mounting machine **210-2**

27

of the component mounting apparatus **201-2**, the unmounted board **7C** is disposed at the discharge side board hold part **22221** of the board send-out device **2222-1** of the component mounting apparatus **201-1**, and the unmounted board **7D** is arranged at the supply side board hold part **22121** of the board carry-in device **2212-1** of the component mounting apparatus **201-1**.

The controller **280** determines that it is possible to supply a next unmounted board **7** to the component supply/mounting machine **210-1** on a basis of factors such as boards **7**, **8** being absent from the XY-table **213**, the component supply/mounting machine **210-1** being at rest, or the like.

FIG. **16** indicates a state wherein the mounted board **8A** is arranged on the board transfer path **2211** while held by the discharge side board hold part **22221** of the component mounting apparatus **201-1**, while the unmounted board **7B** is being subjected to a mounting operation performed by the component supply/mounting machine **210-2** of the component mounting apparatus **201-2**, and the unmounted board **7C** is in the middle of a mounting operation performed by the component supply/mounting machine **210-3** of the component mounting apparatus **201-3**, with the unmounted board **7D** being arranged at the supply side board hold part **22121** of the board carry-in device **2212-4** of the component mounting apparatus **201-4**.

FIG. **17** represents a state in which the mounted board **8A** is transferred to the discharge side board hold part **22221** of the board send-out device **2222-4** of the component mounting apparatus **201-4**, and the mounted board **8B** is transferred to the stop region **2214** located immediately before the board send-out device **2222-4** of the component mounting apparatus **201-3**, while the unmounted board **7C** is being subjected to a mounting operation by the component supply/mounting machine **210-3** of the component mounting apparatus **201-3** and the unmounted board **7D** is being subjected to a mounting operation by the component supply/mounting machine **210-4** of the component mounting apparatus **201-4**.

As is shown in FIG. **17**, when a mounted board is transferred and temporarily stopped at the discharge side board hold part **22221** of the board send-out device **2222-4** of the component mounting apparatus **201-4**, presence/absence of mounted components is detected by the recognizing device **227** in addition to an identification operation performed by the identifying device **2215-4**. When the controller **280** determines presence of mounted components based on output information of the recognizing device **227**, this board is directly transferred to a next process along the board transfer path **2211** in the transfer direction **224**. The next process is, for example, a soldering process or the like. In contrast, when an absence of a mounted component is decided, the controller **280** controls operation of each part so as to supply the board, determined to have no component, to the component supply/mounting machine **210-4** of the component mounting apparatus **201-4** and have components mounted to the board because the component mounting apparatuses **201-1** to **201-4** are designed to mount equal components in the present second embodiment as mentioned before.

Similar to the above-described mounted board **8A**, presence/absence of mounted components is detected for the mounted boards **8B**, **8C** by the recognizing device **227**, and operation based on this detected result is performed.

As discussed hereinabove, in the component mounting apparatus **202** with the board transferring apparatus **221** of the second embodiment, when a plurality of component supply/mounting machines **210** are arranged along the transfer direction **224**, and moreover each of the component

28

supply/mounting machines **210** mounts all components necessary for one complete board, a necessary time for loading boards **7** to each of the component supply/mounting machines **210** is a time for loading one board to one component supply/mounting machine **210** irrespective of the number of the component supply/mounting machines **210**. A production time per board can be accordingly shortened and a production efficiency of the component mounting apparatus can be improved. The embodiment is the same as the conventional component mounting apparatus of FIG. **9** from this view point. However, the conventional component mounting apparatus requires two paths for transferring boards **7**, **8** as a bypass route of board transfer passage **2141** in the component supply/mounting machine **210**. In contrast, one board transfer path **2211** is sufficient in the component mounting apparatus of the present second embodiment, thereby enabling curtailing an apparatus constitution, an apparatus cost, and the like.

Furthermore, in the component mounting apparatus **201**, **202** having the board transferring apparatus **221** of the second embodiment, as compared with the conventional component mounting apparatus shown in FIG. **9**, special effects as follows can be exhibited.

Each of boards **7**, **8** has carry-in propriety display part **2216** applied thereto, so that the component mounting apparatus **201** to which the board is supplied is specified. Therefore, for example, the component mounting apparatus **201** which mounts components to mounted board **8** including a mounting failure can be specified.

According to the present second embodiment, the component mounting apparatus **201** arranged at the trail end is equipped with the recognizing device **227**, so that board **7** without components mounted thereto due to, e.g., machine trouble, an identification error at the identifying device **2215** or the like can be detected. An error of transferring unmounted board **7** to a next process at a down-stream side can hence be prevented.

In the event that all components necessary for one complete board cannot be mounted by one component mounting apparatus **201**, for example, even when part of the electronic components are mounted by the component mounting apparatuses **201-1**, **201-2** and remaining electronic components are mounted by the component mounting apparatuses **201-3**, **201-4**, thereby finishing one printed board in the component mounting apparatus **202** shown in FIG. **15**, it is possible to produce a finished board in the above board transfer path **2211** without constructing a fresh mounting line. Moreover, even if boards to be produced change, production efficiency can be improved in accordance with types of boards to be produced without greatly changing a layout in a factory, including a layout of a board production line, incidental facilities, and the like, which will be discussed in detail below.

In a case of mounting part of electronic components by the component mounting apparatuses **201-1**, **201-2** and mounting remaining electronic components by the component mounting apparatuses **201-3**, **201-4** to complete one printed board, the following operation is performed given that carry-in propriety display part **2216A** of unmounted board **7A** has information that the unmounted board **7A** can be supplied to each of the component supply/mounting machines **210-1**, **210-3** of the component mounting apparatuses **201-1**, **201-3**, while carry-in propriety display part **2216B** of unmounted board **7B** includes information that the unmounted board **7B** can be supplied to each of component supply/mounting machines **210-2**, **210-4** of the component mounting apparatuses **201-2**, **201-4**.

With this arrangement, the carry-in propriety display part **2216A** of the unmounted board **7A** transferred along the transfer path **2211** is identified by the identifying device **2215-1** of the component mounting apparatus **201-1** as described before, whereby supply of board **7A** to the component supply/mounting machine **210-1** is permitted on a basis of this identified result. The unmounted board **7A** is subjected to mounting by the component supply/mounting machine **210-1**. During this mounting operation of the unmounted board **7A**, the carry-in propriety display part **2216B** of the unmounted board **7B** is identified by the identifying device **2215-2** of the component mounting apparatus **201-2**, and supply of board **7B** to the component supply/mounting machine **210-2** is permitted on a basis of this identified result. The mounting operation of the unmounted board **7B** is performed by the component supply/mounting machine **210-2**.

Mounted board **8A** produced by the mounting operation of the unmounted board **7A** in the component supply/mounting machine **210-1** is returned by the board carry-in device **2222-1** to the transfer path **2211** and transferred along the board transfer path **2211** in the transfer direction **224**. Information described in the carry-in propriety display part **2216A** of the mounted board **8A** is not information permitting supply thereof to the component supply/mounting machine **210-2** of the component mounting apparatus **201-2**, and consequently the mounted board **8A** passes the component mounting apparatus **201-2** so as to be transferred to the supply side board hold part **22121** of the component mounting apparatus **201-3**. The carry-in propriety display part **2216A** is identified by the identifying device **2215-3** of the component mounting apparatus **201-3**, and supply of the mounted board **8A** to the component supply/mounting machine **210-3** is permitted on a basis of this identified result. Remaining components are mounted to the mounted board **8A** by the component supply/mounting machine **210-3**.

The same control operation as for the above-described mounted board **8A** is executed for mounted board **8B** produced by a mounting operation of the unmounted board **7B** performed by the component supply/mounting machine **210-2**, whereby remaining components are mounted to the mounted board **8B** by the component supply/mounting machine **210-4** of the component mounting apparatus **201-4**.

After the mounting operation of the mounted board **8A** in the component supply/mounting machine **210-3** and the mounting operation of the mounted board **8B** in the component supply/mounting machine **210-4** are respectively finished, each mounted board **8A**, **8B** is returned to the board transfer path **2211** and is transferred along the board transfer path **2211** in the transfer direction **224** so as to be supplied to a next process.

Since supply propriety to the component supply/mounting machine **210** is identified for each of transferred boards **7**, **8** by the identifying device **2215** as described above, there is no need of constructing a fresh mounting line to mount remaining components. Moreover, even if printed boards to be produced vary, the component mounting apparatus **202** of the present second embodiment can be used by changing a type of components to be mounted by each component supply/mounting machine **210**, and by changing supply-propriety information of the component mount/setting machine **210** which is described in each carry-in propriety display part **2216** of board **7**. In other words, information of supply propriety of the component supply/mounting machine **210** which is described in each carry-in propriety display part **2216** of each board **7** is designed to conform

with a mounting program stored in the controller **280** based on the constitution of the component mounting apparatus and a number of electronic components to be mounted.

According to the board transferring apparatus **221** of the present second embodiment as discussed hereinabove, production efficiency can be improved in accordance with types of boards to be produced without greatly changing a layout in a factory, including a layout of a board production line and incidental facilities, and the like.

The above-described case, that all of electronic components to be mounted to a printed board to be produced are not completely mounted by one component mounting apparatus, corresponds not only to a case where one component mounting apparatus **201** cannot have the number of component supply parts **2121** which supply components of a necessary number to form one printed board, but also to a case where different electronic components are used only partly and common electronic components are used for a remainder among models of boards, for instance, for portable phones, personal computers, and the like. When only part of the electronic components are different, common electronic components are mounted, e.g., by a plurality of component mounting apparatuses **201** arranged, e.g., at an upstream side, thereby forming mounted boards **8** including the common electronic components. Then the mounted boards **8** are transferred to, e.g., a plurality of component mounting apparatuses **201** disposed at a downstream side, where each of supply proprieties, of component supply/mounting machines **210** included in respective component mounting apparatuses **201**, is determined with use of the identifying devices **2215**. Therefore, different electronic components can be mounted in conformity with target models, so that boards conforming to each model can be produced. A need of constructing a production line corresponding to each model of printed boards is eliminated.

According to the board transferring apparatus **221** of this second embodiment, and the component mounting apparatus including the board transferring apparatus, when a plurality of component mounting apparatuses are arranged, coped with can be various production forms from a case where each of component mounting apparatuses **201** mounts all components to each unmounted board **7** to a case where the component mounting apparatuses **201** mount mutually different components. That is, controller **280** is enabled to control operation of board transferring apparatuses **221** and board carry-in devices **2212** to meet various production forms by designing supply-propriety information for component supply/mounting machines **210**, which are described in carry-in propriety display parts **2216** of respective boards **7**, **8** on a basis of a processing program which is performed by the controller **280** according to types and number of components to be mounted by the component mounting apparatuses **201** arranged along transfer direction **224**, and production forms of these boards.

Although unmounted boards **7** transferred from an upstream side are equal ones as described above in the second embodiment, boards are not limited to this. Particularly, when a plurality of kinds of boards, e.g., four kinds of boards **7** are sequentially repeatedly transferred, a number of produced printed boards to be stocked can be made proper. Suppose that one appliance needs, for example, four kinds of printed boards A-D, in the conventional component mounting apparatus of FIG. **9**, boards should be produced for every kind of board because the conventional apparatus cannot produce a plurality of kinds of boards in a mixed condition. Therefore, in order for manufacturing, e.g., 100 units of the appliance, 100 pieces of board "A" should be produced first,

31

100 pieces of board "B" should be produced next, and so on. In other words, a necessary number of boards should be produced sequentially for each kind.

On the other hand, in the component mounting apparatus of the present second embodiment, since boards A-D can be transferred in turn and supplied to respective component supply/mounting machines and then subjected to mounting operations, it is possible to produce in groups of boards A-D, that is, boards for every one set of the appliance can be produced. Thus, a number of printed boards to be stocked can be controlled to be proper as mentioned above.

In the embodiments shown in FIGS. 15-17, both the identifying device 2215 and the recognizing device 227 are equipped with the component mounting apparatus 201-4 arranged at a trail end. However, the arrangement is not limited to this, and only the identifying device 2215 may be provided.

In the above second embodiment, transferred boards 7, 8 are temporarily stopped when carry-in propriety display part 2216 is identified by the identifying device 2215. However, this identifying operation can be performed without stopping the boards 7, 8 by equipping a different type of identifying device 2215, a moving mechanism for the identifying device 2215, or the like.

Although the present invention has been fully described in connection with the preferred embodiments thereof with reference to the accompanying drawings, it is to be noted that various changes and modifications are apparent to those skilled in the art. Such changes and modifications are to be understood as included within the scope of the present invention as defined by the appended claims unless they depart therefrom.

What is claimed is:

1. A board transferring apparatus for transferring boards along a board transfer path in a transfer direction, and for transferring the boards between the board transfer path and first and second component-mounting board production apparatus arranged in series along the board transfer path, comprising:

a first board carry-in device operable to move between the board transfer path and the first component-mounting board production apparatus for carrying a board into the first component-mounting board production apparatus;

a first board send-out device operable to move between the board transfer path and the first component-mounting board production apparatus for carrying a board out from the first component-mounting board production apparatus;

a first identifying device at the board transfer path for identifying a carry-in propriety display part on a board, the carry-in propriety display part being indicative of whether the board is to be carried into the first component-mounting board production apparatus;

a second board carry-in device operable to move between the board transfer path and the second component-mounting board production apparatus for carrying a board into the second component-mounting board production apparatus;

a second board send-out device operable to move between the board transfer path and the second component-mounting board production apparatus for carrying a board out from the second component-mounting board production apparatus;

a second identifying device at the board transfer path for identifying a carry-in propriety display part on a board, the carry-in propriety display part being indicative of

32

whether the board is to be carried into the second component-mounting board production apparatus; and a controller

(i) for determining whether a board is to be carried into the first component-mounting board production apparatus on a basis of the carry-in propriety display part, of this board, as identified by said first identifying device,

(ii) for determining whether a board is to be carried into the second component-mounting board production apparatus on a basis of the carry-in propriety display part, of this board, as identified by said second identifying device, and

(iii) for controlling operation of said first board carry-in device and said second board carry-in device,

wherein, in the transfer direction, a component mounting device of the first component-mounting board production apparatus is positioned between said first board carry-in device and said first board send-out device, said first board send-out device is positioned between the component mounting device of the first component-mounting board production apparatus and said second board carry-in device, said second board carry-in device is positioned between said first board send-out device and a component mounting device of the second component-mounting board production apparatus, and the component mounting device of the second component-mounting board production apparatus is positioned between said second board carry-in device and said second board send-out device.

2. The board transferring apparatus according to claim 1, wherein

said controller is for controlling operation of said first board carry-in device such that, when said controller determines that the board is to be carried into the first component-mounting board production apparatus on the basis of the carry-in propriety display part as identified by said first identifying device, said controller controls operation of said first board carry-in device such that said first board carry-in device carries the board into the first component-mounting board production apparatus, whereby the board is processed by the first component-mounting board production apparatus and then carried by said first board send-out device to the board transfer path, and

said controller is for controlling operation of said second board carry-in device such that, when said controller determines that the board is to be carried into the second component-mounting board production apparatus on the basis of the carry-in propriety display part as identified by said second identifying device, said controller controls operation of said second board carry-in device such that said second board carry-in device carries the board into the second component-mounting board production apparatus, whereby the board is processed by the second component-mounting board production apparatus and then carried by said second board send-out device to the board transfer path.

3. The board transferring apparatus according to claim 2, wherein

said controller is for allowing a board to be transferred along the board transfer path when it is determined that this board is not to be carried into the first component-mounting board production apparatus, and

said controller is for allowing a board to be transferred along the board transfer path when it is determined that

33

this board is not to be carried into the second component-mounting board production apparatus.

4. The board transferring apparatus according to claim 3, further comprising:

a recognizing device, at a most downstream one of the first component-mounting board production apparatus and the second component-mounting board production apparatus, for recognizing a propriety of processing of a board by the first component-mounting board production apparatus and/or the second component-mounting board production apparatus.

5. The board transferring apparatus according to claim 4, wherein

the carry-in propriety display part to be recognized by said first identifying device is a mark that has been preliminarily applied to a board, and

the carry-in propriety display part to be recognized by said second identifying device is a mark that has been preliminarily applied to a board.

6. The board transferring apparatus according to claim 2, further comprising:

a recognizing device, at a most downstream one of the first component-mounting board production apparatus and the second component-mounting board production apparatus, for recognizing a propriety of processing of a board by the first component-mounting board production apparatus and/or the second component-mounting board production apparatus.

7. The board transferring apparatus according to claim 6, wherein

the carry-in propriety display part to be recognized by said first identifying device is a mark that has been preliminarily applied to a board, and

the carry-in propriety display part to be recognized by said second identifying device is a mark that has been preliminarily applied to a board.

8. The board transferring apparatus according to claim 2, wherein

the carry-in propriety display part to be recognized by said first identifying device is a mark that has been preliminarily applied to a board, and

the carry-in propriety display part to be recognized by said second identifying device is a mark that has been preliminarily applied to a board.

9. The board transferring apparatus according to claim 1, further comprising:

a recognizing device, at a most downstream one of the first component-mounting board production apparatus and the second component-mounting board production apparatus, for recognizing a propriety of processing of a board by the first component-mounting board production apparatus and/or the second component-mounting board production apparatus.

10. The board transferring apparatus according to claim 1, wherein

the carry-in propriety display part to be recognized by said first identifying device is a mark that has been preliminarily applied to a board, and

the carry-in propriety display part to be recognized by said second identifying device is a mark that has been preliminarily applied to a board.

11. A component mounting apparatus comprising:

a first component-mounting board production apparatus and a second component-mounting board production apparatus arranged in series along a board transfer path; and

34

a board transferring apparatus for transferring boards along the board transfer path in a transfer direction, and for transferring the boards between the board transfer path and said first and second component-mounting board production apparatus, said board transferring apparatus including

(i) a first board carry-in device operable to move between the board transfer path and said first component-mounting board production apparatus for carrying a board into said first component-mounting board production apparatus,

(ii) a first board send-out device operable to move between the board transfer path and said first component-mounting board production apparatus for carrying a board out from said first component-mounting board production apparatus,

(iii) a first identifying device at the board transfer path for identifying a carry-in propriety display part on a board, the carry-in propriety display part being indicative of whether the board is to be carried into said first component-mounting board production apparatus,

(iv) a second board carry-in device operable to move between the board transfer path and said second component-mounting board production apparatus for carrying a board into said second component-mounting board production apparatus,

(v) a second board send-out device operable to move between the board transfer path and said second component-mounting board production apparatus for carrying a board out from said second component-mounting board production apparatus,

(vi) a second identifying device at the board transfer path for identifying a carry-in propriety display part on a board, the carry-in propriety display part being indicative of whether the board is to be carried into said second component-mounting board production apparatus, and

(vii) a controller

(a) for determining whether a board is to be carried into said first component-mounting board production apparatus on a basis of the carry-in propriety display part, of this board, as identified by said first identifying device,

(b) for determining whether a board is to be carried into said second component-mounting board production apparatus on a basis of the carry-in propriety display part, of this board, as identified by said second identifying device, and

(c) for controlling operation of said first board carry-in device and said second board carry-in device,

wherein, in the transfer direction, a component mounting device of said first component-mounting board production apparatus is positioned between said first board carry-in device and said first board send-out device, said first board send-out device is positioned between the component mounting device of said first component-mounting board production apparatus and said second board carry-in device, said second board carry-in device is positioned between said first board send-out device and a component mounting device of said second component-mounting board production apparatus, and the component mounting device of said second component-mounting board production apparatus is positioned between said second board carry-in device and said second board send-out device.

35

12. The component mounting apparatus according to claim 11, wherein

said controller is for controlling operation of said first board carry-in device such that, when said controller determines that the board is to be carried into said first component-mounting board production apparatus on the basis of the carry-in propriety display part as identified by said first identifying device, said controller controls operation of said first board carry-in device such that said first board carry-in device carries the board into said first component-mounting board production apparatus, whereby the board is processed by said first component-mounting board production apparatus and then carried by said first board send-out device to the board transfer path, and

said controller is for controlling operation of said second board carry-in device such that, when said controller determines that the board is to be carried into said second component-mounting board production apparatus on the basis of the carry-in propriety display part as identified by said second identifying device, said controller controls operation of said second board carry-in device such that said second board carry-in device carries the board into said second component-mounting board production apparatus, whereby the board is processed by said second component-mounting board production apparatus and then carried by said second board send-out device to the board transfer path.

13. The component mounting apparatus according to claim 12, wherein

said controller is for allowing a board to be transferred along the board transfer path when it is determined that this board is not to be carried into said first component-mounting board production apparatus, and

said controller is for allowing a board to be transferred along the board transfer path when it is determined that this board is not to be carried into said second component-mounting board production apparatus.

14. The component mounting apparatus according to claim 13, further comprising:

a recognizing device, at a most downstream one of said first component-mounting board production apparatus and said second component-mounting board production apparatus, for recognizing a propriety of processing of a board by said first component-mounting board production apparatus and/or said second component-mounting board production apparatus.

15. The component mounting apparatus according to claim 14, wherein

the carry-in propriety display part to be recognized by said first identifying device is a mark that has been preliminarily applied to a board, and

36

the carry-in propriety display part to be recognized by said second identifying device is a mark that has been preliminarily applied to a board.

16. The component mounting apparatus according to claim 12, further comprising:

a recognizing device, at a most downstream one of said first component-mounting board production apparatus and said second component-mounting board production apparatus, for recognizing a propriety of processing of a board by said first component-mounting board production apparatus and/or said second component-mounting board production apparatus.

17. The component mounting apparatus according to claim 16, wherein

the carry-in propriety display part to be recognized by said first identifying device is a mark that has been preliminarily applied to a board, and

the carry-in propriety display part to be recognized by said second identifying device is a mark that has been preliminarily applied to a board.

18. The component mounting apparatus according to claim 12, wherein

the carry-in propriety display part to be recognized by said first identifying device is a mark that has been preliminarily applied to a board, and

the carry-in propriety display part to be recognized by said second identifying device is a mark that has been preliminarily applied to a board.

19. The component mounting apparatus according to claim 11, further comprising:

a recognizing device, at a most downstream one of said first component-mounting board production apparatus and said second component-mounting board production apparatus, for recognizing a propriety of processing of a board by said first component-mounting board production apparatus and/or said second component-mounting board production apparatus.

20. The component mounting apparatus according to claim 11, wherein

the carry-in propriety display part to be recognized by said first identifying device is a mark that has been preliminarily applied to a board, and

the carry-in propriety display part to be recognized by said second identifying device is a mark that has been preliminarily applied to a board.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,222,413 B2
APPLICATION NO. : 10/960983
DATED : May 29, 2007
INVENTOR(S) : Kurayasu Hamasaki et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

TITLE PAGE

Section (56) References cited, please add the following U.S. references:

--6,272,743	8/2001	Nishimori et al.
6,257,391	7/2001	Nishimori et al.
4,787,143	11/1988	Yagi et al.
6,643,917	11/2003	Gieskes
3,543,392	12/1970	Perry et al.
6,145,648	11/2000	Teichman et al.--

Column 33

Line 52, "andior the" should read --and/or the--.

Column 34

Line 18, "a cany-in" should read --a carry-in--.

Signed and Sealed this

Sixth Day of November, 2007



JON W. DUDAS

Director of the United States Patent and Trademark Office