

U.S. PATENT DOCUMENTS

3,952,578 A	4/1976	Jacobs	73/64.1	6,889,562 B2	5/2005	Gysling et al.	
4,004,461 A	1/1977	Lynworth	73/861.27	6,898,541 B2	5/2005	Gysling et al.	902/100
4,032,259 A	6/1977	Brown	417/43	6,971,259 B2	12/2005	Gysling	
4,048,853 A	9/1977	Smith et al.	73/861.25	6,988,411 B2 *	1/2006	Gysling et al.	73/645
4,080,837 A	3/1978	Alexander et al.	73/61.45	7,032,432 B2	4/2006	Gysling et al.	
4,195,517 A	4/1980	Kalinoski et al.	73/461.27	2003/0089161 A1	5/2003	Gysling	
4,248,085 A	2/1981	Coulthard	73/861.06	2003/0154036 A1	8/2003	Gysling et al.	
4,320,659 A	3/1982	Lynnworth et al.	73/589	2004/0006409 A1	1/2004	Liljenberg et al.	
4,445,389 A	5/1984	Potzick et al.	73/861.27	2004/0069069 A1	4/2004	Gysling et al.	
4,520,320 A	5/1985	Potzick et al.	328/133	2004/0168522 A1	9/2004	Bailey et al.	
4,561,310 A	12/1985	Barnard et al.	73/861.02	2004/0168523 A1	9/2004	Bailey et al.	
4,677,305 A	6/1987	Ellinger	73/290 V	2004/0194539 A1	10/2004	Gysling	
4,717,159 A	1/1988	Alston et al.	330/129	2004/0199340 A1	10/2004	Gysling et al.	
4,896,540 A	1/1990	Shakkottai et al.	73/861.02	2004/0199341 A1	10/2004	Gysling et al.	
4,932,262 A	6/1990	Wlodarczyk	250/227.3	2004/0210404 A1	10/2004	Gysling et al.	
5,040,415 A	8/1991	Barkhoudarian	73/861.03	2004/0226386 A1	11/2004	Croteau et al.	
5,060,506 A	10/1991	Douglas	73/24.01	2004/0231431 A1	11/2004	Bailey et al.	
5,083,452 A	1/1992	Hope	73/61 R	2004/0255695 A1	12/2004	Gysling et al.	
5,218,197 A	6/1993	Carroll	250/227.19	2005/0000289 A1	1/2005	Gysling et al.	
5,285,675 A	2/1994	Colgate et al.	73/23.2	2005/0005711 A1	1/2005	Gysling et al.	
5,289,726 A	3/1994	Miau et al.	73/861.22	2005/0005712 A1	1/2005	Gysling et al.	
5,359,897 A	11/1994	Hamstead et al.	73/597	2005/0005713 A1	1/2005	Winston et al.	
5,363,342 A	11/1994	Layton et al.	367/149	2005/0005912 A1	1/2005	Gysling et al.	
5,367,911 A	11/1994	Jewell et al.	73/861.08	2005/0011258 A1	1/2005	Gysling et al.	
5,398,542 A	3/1995	Vasbinder	73/40.5	2005/0011283 A1	1/2005	Gysling et al.	
5,524,475 A	6/1996	Kolpak et al.	73/19.03	2005/0011284 A1	1/2005	Davis et al.	
5,526,844 A	6/1996	Kamen et al.	137/614.11	2005/0033545 A1	2/2005	Gysling	
5,591,922 A	1/1997	Segeral et al.	73/861.04	2005/0039520 A1	2/2005	Davis et al.	
5,625,140 A	4/1997	Cadet et al.	73/24.01	2005/0044929 A1	3/2005	Gysling et al.	
5,708,211 A	1/1998	Jepson et al.	73/861.04	2005/0050956 A1	3/2005	Gysling et al.	
5,741,980 A	4/1998	Hill et al.	73/861.04	2005/0061060 A1	3/2005	Banach et al.	
5,770,805 A	6/1998	Castel	73/861.04	2005/0171710 A1	8/2005	Gysling et al.	
5,770,806 A	6/1998	Hiismaki	73/861.29				
5,835,884 A	11/1998	Brown	73/861.04	FOREIGN PATENT DOCUMENTS			
5,856,622 A	1/1999	Yamamoto et al.	73/861.28	EP	0290336	11/1988	
5,948,959 A	9/1999	Peloquin	73/1.83	EP	1186868	3/2002	
6,016,702 A	1/2000	Maron	73/705	GB	2210169	6/1989	
6,151,958 A	11/2000	Letton et al.	73/61.79	WO	WO 93/14382	7/1993	
6,202,494 B1	3/2001	Riebel et al.	73/861.29	WO	WO 99/067629	12/1999	
6,233,374 B1	5/2001	Ogle et al.	385/13	WO	WO 00/00793	1/2000	
6,261,232 B1	7/2001	Yokosawa et al.	600/443	WO	WO 00/046583	8/2000	
6,345,539 B1	2/2002	Rawes et al.	73/861.27	WO	WO 01/02810	1/2001	
6,349,599 B1	2/2002	Lynnworth et al.	73/644	WO	WO 02/050511	6/2002	
6,354,147 B1 *	3/2002	Gysling et al.	73/61.79	WO	WO 2004/063741	7/2004	
6,378,357 B1	4/2002	Han et al.	73/54.41	OTHER PUBLICATIONS			
6,397,683 B1	6/2002	Hagenmeyer et al. ...	73/861.18	Sonar-Based Volumetric Flow Meter for Chemical and Petrochemical Applications—Daniel L. Gysling & Douglas H. Loose—Feb. 14, 2003.			
6,412,353 B1	7/2002	Kleven et al.	73/861.22	New Flowmeter Principle—By Walt Boyes—Flow Control Magazine—Oct. 2003 Issue.			
6,435,030 B1 *	8/2002	Gysling et al.	73/587	SONAR Gets into the Flow—Daniel L. Gysling and Douglas H. Loose—Modern Process—Jan. 2004.			
6,442,996 B1	9/2002	Thurston et al.	73/24.01	“Noise and Vibration Control Engineering Principles and Applications”, Leo L. Beranek and Istvan L. Ver, A. Wiley Interscience Publication, pp. 537-541, Aug. 1992.			
6,450,037 B1	9/2002	McGuinn et al.	73/705	“Two Decades of Array Signal Processing Research”, The Parametric Approach, H. Krim and M. Viberg, IEEE Signal Processing Magazine, Jul. 1996, pp. 67-94.			
6,463,813 B1	10/2002	Gysling	73/862.59	“Development of an array of pressure sensors with PVDF film, Experiments in Fluids 26”, Jan. 8, 1999, Springer-Verlag.			
6,532,827 B1	3/2003	Ohnishi	73/861.27	“Viscous Attenuation of Acoustic Waves in Suspensions” by R.L. Gibson, Jr. and M.N. Toksoz.			
6,536,291 B1	3/2003	Gysling et al.	73/861.42	“Flow Velocity Measurement using Spatial Filter” Yoshio Kurita, Takaharu Matsumoto, Yukitake Shibata—Nov. 1979.			
6,587,798 B2	7/2003	Kersey et al.	702/50				
6,601,005 B1	7/2003	Eryurek et al.	702/104				
6,609,069 B2	8/2003	Gysling	702/48				
6,658,945 B1	12/2003	Kleven	73/861.22				
6,672,163 B2	1/2004	Han et al.	73/597				
6,691,584 B2	2/2004	Gysling et al.	73/861.42				
6,732,575 B2 *	5/2004	Gysling et al.	73/61.79				
6,773,603 B2	8/2004	Moorehead et al.	210/704				
6,782,150 B2	8/2004	Davis et al.	385/12				
6,837,098 B2	1/2005	Gysling et al.	73/61.79				
6,837,332 B1	1/2005	Rodney	181/105				
6,862,920 B2	3/2005	Gysling et al.	73/61.79				

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




Fig. 10

1

**FLOW MEASUREMENT APPARATUS
HAVING STRAIN-BASED SENSORS AND
ULTRASONIC SENSORS**

CROSS-REFERENCE TO RELATED PATENT
APPLICATIONS

This application claims the benefit of U.S. Provisional Patent Application No. 60/510,218 filed Oct. 10, 2003, which is incorporated by reference herein in its entirety.

TECHNICAL FIELD

This invention relates to an apparatus for measuring a parameter of a process flow passing within a pipe, and more particularly to a flow measurement apparatus having ultrasonic sensors and an array of strain-based sensors and for processing data signals therefrom to provide an output indicative of the speed of sound propagating through the process flow and/or a flow parameter of the process flow passing through a pipe.

BACKGROUND ART

Ultra-sonic flow meters are well known for measuring volumetric flow of liquids and gas. Ultra-sonic meters may be mounted within a pipe, mounted within a spool piece, or clamped onto the outer surface of the pipe. While ultra-sonic meters are suitable and in some case accurate flow meters, such as gas custody meters, ultra-sonic meters are not suitable for all fluid flows. For instance, ultra-sonic meters have difficulty measure volumetric flow rate when measuring aerated fluids. The gas bubbles scatter the ultra-sonic waves and therefore, provides an inaccurate or no output at all.

Similarly, an array-based flow meter that uses an array of sensors disposed along the pipe for measuring vortical disturbances and/or acoustic waves propagating through the flow, are suitable for some applications and not as suitable for other applications. The array-based flow meter and the ultra-sonic meter have common applications that they are both suitable for use, however, in other instances, the ultra-sonic meter functions better than the array-based meter in some applications and the array-based flow meter functions better than the ultra-sonic meter in other applications. The present invention combines the two technologies into a single flow meter to provide a flow meter capable of functions in a great number of applications than each flow meter can function alone.

SUMMARY OF THE INVENTION

Objects of the present invention include providing a flow measuring apparatus having a dual function of measuring the parameters of the fluid flow using an array of strain-based sensor and/or ultrasonic sensors to provide a more robust flow measuring apparatus for flows of varying characteristics and process environments.

In one aspect of the present invention, an apparatus for measuring a process flow flowing within a pipe is provided. The apparatus includes at least two strain sensors disposed at different axial locations along the pipe. Each of the strain sensors provides a respective pressure signal indicative of a pressure disturbance within the pipe at a corresponding axial position. At least one ultrasonic sensor is disposed on the pipe that provide a signal indicative of a parameter of the process flow. A signal processor, responsive to said pressure

2

signals and ultrasonic signal, provides a first signal indicative of a velocity of a pressure field moving with the process flow and/or provides a second signal indicative of a speed of sound propagating through the process flow.

The foregoing and other objects, features and advantages of the present invention will become more apparent in light of the following detailed description of exemplary embodiments thereof.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic diagram of a flow measurement apparatus having an array of strain-based sensors and an array of ultrasonic sensors for providing a dual function in accordance with the present invention.

FIG. 2 is a cross-sectional view of a pipe having a turbulent fluid flow or mixture flowing therein, the flow having coherent structures therein, namely acoustic waves and vortical disturbances, in accordance with the present invention.

FIG. 3 is a schematic diagram of a flow logic of an array processor of a flow measuring apparatus in accordance with the present invention.

FIG. 4 is a schematic diagram of a speed of sound (SOS) logic of an array processor of a flow measuring apparatus in accordance with the present invention.

FIG. 5 a $k\omega$ plot of data processed from an apparatus embodying the present invention that illustrates the slope of a convective ridge, and a plot of the optimization function of the convective ridge, in accordance with the present invention.

FIG. 6 a $k\omega$ plot of data processed from an apparatus embodying the present invention that illustrates the slopes of a pair of acoustic ridges, in accordance with the present invention.

FIG. 7 is a plot of mixture sound speed as a function of gas volume fraction for a 5% consistency slurry over a range of process pressures, in accordance with the present invention.

FIG. 8 is a plot of sound speed as a function of frequency for air/particle mixtures with fixed particle size and varying air-to-particle mass ratio in accordance with the present invention.

FIG. 9 is a plot of sound speed as a function of frequency for air/particle mixtures with varying particle size where the air-to-particle mass ratio is fixed in accordance with the present invention.

FIG. 10 is a schematic diagram of another embodiment of a flow measurement apparatus having an ultrasonic sensor and an array of strain-based sensors for providing a dual function in accordance with the present invention.

BEST MODE FOR CARRYING OUT THE
INVENTION

FIG. 1 illustrates a schematic diagram of a flow measurement apparatus 10 that includes a sensing device (sensor head) 16 mounted to a pipe 14 and a processing unit or array processor (transmitter) 24. The apparatus 10 measures a characteristic or parameter of a single phase fluid (e.g., gas and liquid) and/or multiphase fluids 12 (e.g., gas/liquid mixtures, liquid/solid mixtures, gas/solid mixtures, steam, pulp and paper slurries, and aerated liquids and mixtures) flowing through the pipe 14. Specifically, the flow characteristics and flow parameters determined include the volumetric flow of the fluid, the consistency or composition of the fluid, the density of the fluid, the Mach number of the

fluid, the size of particle flowing through the fluid, the air/mass ratio of the fluid, velocity of the flow, volumetric flow rate, gas volume fraction of the flow, the speed of sound propagating through the flow, and/or the percentage of entrained air within a liquid or slurry.

For instance, the apparatus **10**, in accordance with the present invention, can determine the speed at which sound (i.e., acoustic wave **90** in FIG. **2**) propagates through the fluid flow **12** within a pipe **14** to measure particular characteristics of the single or multi-phase fluids. The apparatus may also determine the speed at which pressure disturbances propagate through the pipe **14** to determine the velocity of the fluid flow **12**. The pressure disturbances may be in the form of vortical disturbances **88** (e.g., turbulent eddies FIG. **2**) or other pressure disturbances that convect (or propagate) with the flow. To simplify the explanation of the present invention, the flow propagating through the pipe will be referred to as a process flow with the understanding that the fluid or process flow **12** may be a single phase or multi-phase flow, as described hereinbefore.

The sensing device **16** comprises an array of strain-based sensors or pressure sensors **18-21** for measuring the unsteady pressures produced by vortical disturbances within the pipe and/or speed of sound propagating through the flow, which are indicative of parameters and/or characteristics of the process flow **12**. The sensing device **16** further includes an array of ultrasonic sensors **22-23**, each of which having a transmitter **40** and a receiver **42**, to also measure a parameter of the flow **12**.

The pressure signals $P_1(t)$ - $P_N(t)$ and ultrasonic signals $S_1(t)$ - $S_N(t)$ are provided to the processing unit **24**, which digitizes the signals and computes the appropriate flow parameter(s). A cable electronically connects the sensing device **16** to the processing unit **24**. The analog pressure sensor signals $P_1(t)$ - $P_N(t)$ are typically 4-20 mA current loop signals.

The measurement apparatus **10** may be programmed to provide a flow output parameter **29** corresponding to the pressure signals and/or ultrasonic signals in response to an input/command from an external source, such as control system (not shown) or a user. This capability enables a user to selectively process the input pressure and ultrasonic signals to provide an accurate measurement of the fluid flow **12**. For example, the output measurements **29** may be determined using the pressure signals of the pressure sensors **18-21** for conditions when the fluid flow is aerated. In another example, the output measurements **29** may be determined using the ultrasonic signals of the ultrasonic sensors **22-25** when the fluid flow has no or very little entrained gas, and/or when the pipe is vibrating at a relatively high level. As one skilled in the art can appreciate, the present invention allows a user to install one meter on the pipe and measure parameters of the flow under different operating conditions and flow conditions. The configuration of the apparatus may be static, in other words set by the user at installation, or dynamic wherein the user or control system may dynamically switch between (or simultaneously measure) the ultrasonic sensors and the pressure sensors. The processing unit **24** may also provide intelligence that will switch between utilization of the pressure sensors and ultrasonic sensors when sensing degradation of the output measurement or other external parameter (e.g., vibration).

The array of pressure sensors **18-21** comprises an array of at least two pressure sensors **18,19** spaced axially along the outer surface **17** of the pipe **14**, having a process flow **12** propagating therein. The pressure sensors **18-21** may be clamped onto or generally removably mounted to the pipe

by any releasable fastener, such as bolts, screws and clamps. Alternatively, the sensors may be permanently attached to or integral (e.g., embedded) with the pipe **14**. The array of sensors of the sensing device **16** may include any number of pressure sensors **18-21** greater than two sensors, such as three, four, eight, sixteen or N number of sensors between two and twenty-four sensors. Generally, the accuracy of the measurement improves as the number of sensors in the array increases. The degree of accuracy provided by the greater number of sensors is offset by the increase in complexity and time for computing the desired output parameter of the flow. Therefore, the number of sensors used is dependent at least on the degree of accuracy desired and the desired update rate of the output parameter provided by the apparatus **10**. The pressure sensors **18-19** measure the unsteady pressures produced by acoustic waves propagating through the flow and/or pressure disturbances (e.g., vortical eddies) that convect with the flow within the pipe **14**, which are indicative of the SOS propagating through the fluid flow **12** in the pipe and the velocity of disturbances propagating through the flow **12** of the mixture **12**, respectively. The output signals ($P_1(t)$ - $P_N(t)$) of the pressure sensors **18-21** are provided to a signal amplifier **39** that amplifies the signals generated by the pressure sensors **18-21**. The processing unit **24** processes the pressure measurement data $P_1(t)$ - $P_N(t)$ and determines the desired parameters and characteristics of the flow **12**, as described hereinbefore.

The apparatus **10** also contemplates providing one or more acoustic sources **27** to enable the measurement of the speed of sound propagating through the flow for instances of acoustically quiet flow. The acoustic source may be a device that taps or vibrates on the wall of the pipe, for example. The acoustic sources may be disposed at the input end of output end of the array of sensors **18-21**, or at both ends as shown. One should appreciate that in most instances the acoustics sources are not necessary and the apparatus passively detects the acoustic ridge provided in the flow **12**, as will be described in greater detail hereinafter. The passive noise includes noise generated by pumps, valves, motors, and the turbulent mixture itself.

As suggested and further described in greater detail hereinafter, the apparatus **10** has the ability to measure the speed of sound (SOS) and flow rate (or velocity) using one or both of the following techniques described herein below:

- 1) Determining the speed of sound of acoustical disturbances or sound waves propagating through the flow **12** using the array of pressure sensors **18-21**, and/or
- 2) Determining the velocity of pressure disturbances (e.g., vortical eddies) propagating through the flow **12** using the array of pressure sensors **18-21**.

Generally, the first technique measures unsteady pressures created by acoustical disturbances propagating through the flow **12** to determine the speed of sound (SOS) propagating through the flow. Knowing the pressure and/or temperature of the flow and the speed of sound of the acoustic disturbances or waves, the processing unit **24** can determine parameters that include the volumetric flow of the fluid, the consistency or composition of the fluid, the density of the fluid, the Mach number of the fluid, the average size of particles flowing through the fluid, the air/mass ratio of the fluid, and/or the percentage of entrained air within a liquid or slurry, such as that described in U.S. patent application Ser. No. 10/349,716, filed Jan. 23, 2003, U.S. patent application Ser. No. 10/376,427, filed Feb. 26, 2003, U.S. patent application Ser. No. 10/762,410, filed Jan. 21, 2004, which are all incorporated by reference.

The second technique measures the velocities associated with unsteady flow fields and/or pressure disturbances, such as that created by vortical disturbances or “eddies” **88** (see FIG. **2**), that convect with the process flow **12** to determine the velocity of the process flow. The pressure sensors **18-21** measure the unsteady pressures P_1 - P_N created by the vortical disturbances **88**, for example, as these disturbances convect with the flow **12** through the pipe **14** in a known manner, as shown in FIG. **2**. Therefore, the velocity of these vortical disturbances is related to the velocity of the flow **12** and hence the volumetric flow rate may be determined, as will be described in greater detail hereinafter.

As shown in FIG. **1**, the present invention contemplates a flow measurement apparatus **10** that combines the functionality of an apparatus for measuring the velocity of the process flow and an apparatus for measuring the speed of sound propagating through the flow within a pipe. The pressure signals $P_1(t)$ - $P_N(t)$ of the array of sensors **18-21** of the sensing device **16** are provided to an array processor **31** that includes flow logic **32** for determining the velocity and/or the volumetric flow of the fluid **12** and includes speed of sound (SOS) logic **34** for determining the composition of the flow, the average size of particles within the flow, the air/mass ratio of the flow, phase fraction of the flow, and/or the speed of sound propagating through the flow.

As shown in FIG. **2**, an apparatus **10** embodying the present invention has an array of at least two strain-based or pressure sensors **18,19**, located at two locations x_1, x_2 axially along the pipe **14** for sensing respective stochastic signals propagating between the sensors **18,19** within the pipe at their respective locations. Each sensor **18,19** provides a signal indicating an unsteady pressure at the location of each sensor, at each instant in a series of sampling instants. One will appreciate that the sensor array may include more than two pressure sensors as depicted by pressure sensor **20,21** at location x_3, x_N . The pressure generated by the convective pressure disturbances (e.g., eddies **88**) and acoustic waves **90** (see FIG. **2**) may be measured through strained-based sensors and/or pressure sensors **18-21**. The pressure sensors **18-21** provide analog pressure time-varying signals $P_1(t), P_2(t), P_3(t), P_N(t)$ to the signal processing unit **24**.

The Flow Logic **32** of the processing unit **24** as shown in FIG. **3** receives the pressure signals from the array of sensors **18-21**. A data acquisition unit **40** (e.g., A/D converter) converts the analog signals to respective digital signals. The digitized signals are provided to Fast Fourier Transform (FFT) logic **42**. The FFT logic calculates the Fourier transform of the digitized time-based input signals $P_1(t)$ - $P_N(t)$ and provide complex frequency domain (or frequency based) signals $P_1(\omega), P_2(\omega), P_3(\omega), P_N(\omega)$ indicative of the frequency content of the input signals. Instead of FFT's, any other technique for obtaining the frequency domain characteristics of the signals $P_1(t)$ - $P_N(t)$, may be used. For example, the cross-spectral density and the power spectral density may be used to form a frequency domain transfer functions (or frequency response or ratios) discussed hereinafter.

One technique of determining the convection velocity of the turbulent eddies **88** within the process flow **12** is by characterizing a convective ridge of the resulting unsteady pressures using an array of sensors or other beam forming techniques, similar to that described in U.S. patent application Ser. No. 10/007,736 and U.S. and U.S. patent application Ser. No. 09/729,994, filed Dec. 4, 2000, now U.S. Pat. No. 6,609,069, which are incorporated herein by reference.

A data accumulator **44** accumulates the frequency signals $P_1(\omega)$ - $P_N(\omega)$ over a sampling interval, and provides the data to an array processor **46**, which performs a spatial-temporal

(two-dimensional) transform of the sensor data, from the xt domain to the k - ω domain, and then calculates the power in the k - ω plane, as represented by a k - ω plot.

The array processor **46** uses standard so-called beam forming, array processing, or adaptive array-processing algorithms, i.e. algorithms for processing the sensor signals using various delays and weighting to create suitable phase relationships between the signals provided by the different sensors, thereby creating phased antenna array functionality. In other words, the beam forming or array processing algorithms transform the time domain signals from the sensor array into their spatial and temporal frequency components, i.e. into a set of wave numbers given by $k=2\pi/\lambda$ where λ is the wavelength of a spectral component, and corresponding angular frequencies given by $\omega=2\pi\nu$.

The prior art teaches many algorithms of use in spatially and temporally decomposing a signal from a phased array of sensors, and the present invention is not restricted to any particular algorithm. One particular adaptive array processing algorithm is the Capon method/algorithm. While the Capon method is described as one method, the present invention contemplates the use of other adaptive array processing algorithms, such as MUSIC algorithm. The present invention recognizes that such techniques can be used to determine flow rate, i.e. that the signals caused by a stochastic parameter convecting with a flow are time stationary and have a coherence length long enough that it is practical to locate sensor units apart from each other and yet still be within the coherence length.

Convective characteristics or parameters have a dispersion relationship that can be approximated by the straight-line equation,

$$k=\omega/u,$$

where u is the convection velocity (flow velocity). A plot of k - ω pairs obtained from a spectral analysis of sensor samples associated with convective parameters portrayed so that the energy of the disturbance spectrally corresponding to pairings that might be described as a substantially straight ridge, a ridge that in turbulent boundary layer theory is called a convective ridge. What is being sensed are not discrete events of turbulent eddies, but rather a continuum of possibly overlapping events forming a temporally stationary, essentially white process over the frequency range of interest. In other words, the convective eddies **88** is distributed over a range of length scales and hence temporal frequencies.

To calculate the power in the k - ω plane, as represented by a k - ω plot (see FIG. **5**) of either the signals, the array processor **46** determines the wavelength and so the (spatial) wavenumber k , and also the (temporal) frequency and so the angular frequency ω , of various of the spectral components of the stochastic parameter. There are numerous algorithms available in the public domain to perform the spatial/temporal decomposition of arrays of sensor units **18-21**.

The present invention may use temporal and spatial filtering to precondition the signals to effectively filter out the common mode characteristics $P_{common\ mode}$ and other long wavelength (compared to the sensor spacing) characteristics in the pipe **14** by differencing adjacent sensors and retain a substantial portion of the stochastic parameter associated with the flow field and any other short wavelength (compared to the sensor spacing) low frequency stochastic parameters.

In the case of suitable turbulent eddies **88** (see FIG. **2**) being present, the power in the k - ω plane shown in a k - ω plot of FIG. **5** shows a convective ridge **100**. The convective

ridge represents the concentration of a stochastic parameter that convects with the flow and is a mathematical manifestation of the relationship between the spatial variations and temporal variations described above. Such a plot will indicate a tendency for k - ω pairs to appear more or less along a line **100** with some slope, the slope indicating the flow velocity.

Once the power in the k - ω plane is determined, a convective ridge identifier **48** uses one or another feature extraction method to determine the location and orientation (slope) of any convective ridge **100** present in the k - ω plane. In one embodiment, a so-called slant stacking method is used, a method in which the accumulated frequency of k - ω pairs in the k - ω plot along different rays emanating from the origin are compared, each different ray being associated with a different trial convection velocity (in that the slope of a ray is assumed to be the flow velocity or correlated to the flow velocity in a known way). The convective ridge identifier **48** provides information about the different trial convection velocities, information referred to generally as convective ridge information.

The analyzer **50** examines the convective ridge information including the convective ridge orientation (slope). Assuming the straight-line dispersion relation given by $k=\omega/u$, the analyzer **50** determines the flow velocity, Mach number and/or volumetric flow. The volumetric flow is determined by multiplying the cross-sectional area of the inside of the pipe with the velocity of the process flow.

As shown in FIG. 4, the SOS Logic **34** includes a second data acquisition unit **54** that digitizes the pressure signals $P_1(t)$ - $P_N(t)$ associated with the acoustic waves **14** propagating through the pipe **14**. Similarly to the FFT logic **42**, an FFT logic **56** calculates the Fourier transform of the digitized time-based input signals $P_1(t)$ - $P_N(t)$ and provide complex frequency domain (or frequency based) signals $P_1(\omega)$, $P_2(\omega)$, $P_3(\omega)$, $P_N(\omega)$ indicative of the frequency content of the input signals.

A data accumulator **58** accumulates the signals $P_1(t)$ - $P_N(t)$ from the sensors, and provides the data accumulated over a sampling interval to an array processor **60**, which performs a spatial-temporal (two-dimensional) transform of the sensor data, from the xt domain to the k - ω domain, and then calculates the power in the k - ω plane, as represented by a k - ω plot, similar to that provided by the convective array processor **46**.

To calculate the power in the k - ω plane, as represented by a k - ω plot (see FIG. 6) of either the signals or the differenced signals, the array processor **60** determines the wavelength and so the (spatial) wavenumber k , and also the (temporal) frequency and so the angular frequency ω , of various of the spectral components of the stochastic parameter. There are numerous algorithms available in the public domain to perform the spatial/temporal decomposition of the array of pressure sensors **18-21**.

In the case of suitable acoustic waves **90** being present in both axial directions, the power in the k - ω plane shown in a k - ω plot of FIG. 6 so determined will exhibit a structure that is called an acoustic ridge **110,112** in both the left and right planes of the plot, wherein one of the acoustic ridges **110** is indicative of the speed of sound traveling in one axial direction and the other acoustic ridge **112** being indicative of the speed of sound traveling in the other axial direction.

The acoustic ridges represent the concentration of a stochastic parameter that propagates through the flow and is a mathematical manifestation of the relationship between the spatial variations and temporal variations described above. Such a plot will indicate a tendency for k - ω pairs to appear

more or less along a line **110,112** with some slope, the slope indicating the speed of sound. The power in the k - ω plane so determined is then provided to an acoustic ridge identifier **62**, which uses one or another feature extraction method to determine the location and orientation (slope) of any acoustic ridge present in the left and right k - ω plane. The velocity may be determined by using the slope of one of the two acoustic ridges **110,112** or averaging the slopes of the acoustic ridges **110,112**.

Finally, information including the acoustic ridge orientation (slope) is used by an analyzer **64** to determine the flow parameters **29** relating to measured speed of sound, such as the consistency or composition of the flow, the density of the flow, the average size of particles in the flow, the air/mass ratio of the flow, gas volume fraction of the flow, the speed of sound propagating through the flow, and/or the percentage of entrained air within the flow.

Similar to the array processor **46**, the array processor **60** uses standard so-called beam forming, array processing, or adaptive array-processing algorithms, i.e. algorithms for processing the sensor signals using various delays and weighting to create suitable phase relationships between the signals provided by the different sensors, thereby creating phased antenna array functionality. In other words, the beam forming or array processing algorithms transform the time domain signals from the sensor array into their spatial and temporal frequency components, i.e. into a set of wave numbers given by $k=2\pi/\lambda$ where λ is the wavelength of a spectral component, and corresponding angular frequencies given by $\omega=2\pi v$.

One such technique of determining the speed of sound propagating through the flow **12** is using array processing techniques to define an acoustic ridge in the k - ω plane as shown in FIG. 6. The slope of the acoustic ridge is indicative of the speed of sound propagating through the flow **12**. The speed of sound (SOS) is determined by applying sonar arraying processing techniques to determine the speed at which the one dimensional acoustic waves propagate past the axial array of unsteady pressure measurements distributed along the pipe **14**.

The apparatus **10** of the present invention measures the speed of sound (SOS) of one-dimensional sound waves propagating through the mixture to determine the gas volume fraction of the mixture. It is known that sound propagates through various mediums at various speeds in such fields as SONAR and RADAR fields. The speed of sound propagating through the pipe and flow **12** may be determined using a number of known techniques, such as those set forth in U.S. patent application Ser. No. 09/344,094, filed Jun. 25, 1999, now U.S. Pat. No. 6,354,147; U.S. patent application Ser. No. 10/795,111, filed Mar. 4, 2004; U.S. patent application Ser. No. 09/997,221, filed Nov. 28, 2001, now U.S. Pat. No. 6,587,798; U.S. patent application Ser. No. 10/007,749, filed Nov. 7, 2001, and U.S. patent application Ser. No. 10/762,410, filed Jan. 21, 2004, each of which are incorporated herein by reference.

While the sonar-based flow meter using an array of sensors to measure the speed of sound of an acoustic wave propagating through the mixture is shown and described, one will appreciate that any means for measuring the speed of sound of the acoustic wave may be used to determine the entrained gas volume fraction of the mixture/fluid or other characteristics of the flow described hereinbefore.

The analyzer **64** of the acoustic processing unit **53** provides output signals indicative of characteristics of the process flow **12** that are related to the measured speed of sound (SOS) propagating through the flow **12**. For example,

to determine the gas volume fraction (or phase fraction), the analyzer **64** assumes a nearly isothermal condition for the flow **12**. As such the gas volume fraction or the void fraction is related to the speed of sound by the following quadratic equation:

$$Ax^2+Bx+C=0$$

wherein x is the speed of sound, $A=1+rg/rl*(K_{eff}/P-1)-K_{eff}/P$, $B=K_{eff}/P-2+rg/rl$; $C=1-K_{eff}/rl*a_{meas}^2$; Rg =gas density, rl =liquid density, K_{eff} =effective K (modulus of the liquid and pipewall), P =pressure, and a_{meas} =measured speed of sound.

Effectively,

$$\text{Gas Volume Fraction(GVF)}=\frac{-B+\text{sqrt}(B^2-4*A*C)}{2*A}$$

Alternatively, the sound speed of a mixture can be related to volumetric phase fraction (ϕ_i) of the components and the sound speed (a) and densities (ρ) of the component through the Wood equation.

$$\frac{1}{\rho_{mix}a_{mix\infty}^2}=\sum_{i=1}^N\frac{\phi_i}{\rho_i a_i^2} \text{ where } \rho_{mix}=\sum_{i=1}^N\rho_i\phi_i$$

One dimensional compression waves propagating within a mixture **12** contained within a pipe **14** exert an unsteady internal pressure loading on the pipe. The degree to which the pipe displaces as a result of the unsteady pressure loading influences the speed of propagation of the compression wave. The relationship among the infinite domain speed of sound and density of a mixture; the elastic modulus (E), thickness (t), and radius (R) of a vacuum-backed cylindrical conduit; and the effective propagation velocity (a_{eff}) for one dimensional compression is given by the following expression:

$$a_{eff}=\frac{1}{\sqrt{\frac{1}{a_{mix\infty}^2}+\rho_{mix}\frac{2R}{Et}}} \quad (\text{eq 1})$$

The mixing rule essentially states that the compressibility of a mixture ($1/(\rho a^2)$) is the volumetrically-weighted average of the compressibilities of the components. For gas/liquid mixtures **12** at pressure and temperatures typical of paper and pulp industry, the compressibility of gas phase is orders of magnitudes greater than that of the liquid. Thus, the compressibility of the gas phase and the density of the liquid phase primarily determine mixture sound speed, and as such, it is necessary to have a good estimate of process pressure to interpret mixture sound speed in terms of volumetric fraction of entrained gas. The effect of process pressure on the relationship between sound speed and entrained air volume fraction is shown in FIG. **7**.

As described hereinbefore, the apparatus **10** of the present invention includes the ability to accurately determine the average particle size of a particle/air or droplet/air mixture within the pipe **14** and the air to particle ratio. Provided there is no appreciable slip between the air and the solid coal particle, the propagation of one dimensional sound wave through multiphase mixtures is influenced by the effective mass and the effective compressibility of the mixture. For an air transport system, the degree to which the no-slip assumption applies is a strong function of particle size and fre-

quency. In the limit of small particles and low frequency, the no-slip assumption is valid. As the size of the particles increases and the frequency of the sound waves increase, the non-slip assumption becomes increasing less valid. For a given average particle size, the increase in slip with frequency causes dispersion, or, in other words, the sound speed of the mixture to change with frequency. With appropriate calibration the dispersive characteristic of a mixture **12** will provide a measurement of the average particle size, as well as, the air to particle ratio (particle/fluid ratio) of the mixture.

In accordance with the present invention the dispersive nature of the system utilizes a first principles model of the interaction between the air and particles. This model is viewed as being representative of a class of models that seek to account for dispersive effects. Other models could be used to account for dispersive effects without altering the intent of this disclosure (for example, see the paper titled "Viscous Attenuation of Acoustic Waves in Suspensions" by R. L. Gibson, Jr. and M. N. Toksöz), which is incorporated herein by reference. The model allows for slip between the local velocity of the continuous fluid phase and that of the particles.

The following relation can be derived for the dispersive behavior of an idealized fluid particle mixture.

$$a_{mix}(\omega)=a_f\sqrt{\frac{1}{1+\frac{\phi_p\rho_p}{\rho_f\left(1+\omega^2\frac{\rho_p v_p^2}{K^2}\right)}}$$

In the above relation, the fluid SOS, density (ρ) and viscosity (ϕ) are those of the pure phase fluid, v_p is the volume of individual particles and ϕ_p is the volumetric phase fraction of the particles in the mixture.

Two parameters of particular interest in steam processes and air-conveyed particles processes are particle size and air-to-fuel mass ratio or steam quality. To this end, it is of interest to examine the dispersive characteristics of the mixture as a function of these two variables. FIGS. **8** and **9** show the dispersive behavior in relations to the speed of sound for coal/air mixtures with parameters typical of those used in pulverized coal deliver systems.

In particular FIG. **8** shows the predicted behavior for nominally 50 μm size coal in air for a range of air-to-fuel ratios. As shown, the effect of air-to-fuel ratio is well defined in the low frequency limit. However, the effect of the air-to-fuel ratio becomes indistinguishable at higher frequencies, approaching the sound speed of the pure air at high frequencies (above ~ 100 Hz).

Similarly, FIG. **9** shows the predicted behavior for a coal/air mixture with an air-to-fuel ratio of 1.8 with varying particle size. This figure illustrates that particle size has no influence on either the low frequency limit (quasi-steady) sound speed, or on the high frequency limit of the sound speed. However, particle size does have a pronounced effect in the transition region.

FIGS. **8** and **9** illustrate an important aspect of the present invention. Namely, that the dispersive properties of dilute mixtures of particles suspended in a continuous fluid can be broadly classified into three frequency regimes: low frequency range, high frequency range and a transitional frequency range. Although the effect of particle size and air-to-fuel ratio are inter-related, the predominant effect of

air-to-fuel ratio is to determine the low frequency limit of the sound speed to be measured and the predominate effect of particle size is to determine the frequency range of the transitional regions. As particle size increases, the frequency at which the dispersive properties appear decreases. For typical pulverized coal applications, this transitional region begins at fairly low frequencies, ~2 Hz for 50 μm size particles.

Given the difficulties measuring sufficiently low frequencies to apply the quasi-steady model and recognizing that the high frequency sound speed contains no direct information on either particle size or air-to-fuel ratio, it becomes apparent that the dispersive characteristics of the coal/air mixture should be utilized to determine particle size and air-to-fuel ratio based on speed of sound measurements.

Some or all of the functions within the processing unit **24** may be implemented in software (using a microprocessor or computer) and/or firmware, or may be implemented using analog and/or digital hardware, having sufficient memory, interfaces, and capacity to perform the functions described herein.

While data acquisition units **40,54**, FFT logic **42,56**, data accumulators **44,58**, array processors **46,60** and ridge identifiers **48, 62** are shown as separate elements or separate software/processing routines, one will appreciate that each of these elements may be common and able to process the data associated with both the pressure signals associated with the speed of sound and the pressures that convect with the process flow.

As shown in FIG. 1, the measurement apparatus **10** includes a sensing device **16** comprising an array of ultrasonic sensor units **22-25**. Each sensor unit comprises a pair of ultrasonic sensors **40,42**, one of which functions as a transmitter (Tx) **40** and the other as a receiver (Rx) **42**. The sensor units **22-25** are spaced axially along the outer surface **17** of the pipe **14** having a process flow **12** propagating therein. The pair of sensors **40,42** is diametrically disposed on the pipe at predetermined locations along the pipe to provide a through transmission configuration, such that the sensors transmit and receive an ultrasonic signal that propagates through the fluid substantially orthogonal to the direction of the flow of the fluid within the pipe. The ultrasonic measurement portion of the present invention is similar to shown in U.S. Provisional patent application Ser. No. 10/756,977 filed on Jan. 13, 2004, which is incorporated herein by reference.

As shown in FIG. 1, each pair of ultrasonic sensors **40,42** measures a transit time (i.e., time of flight (TOF), or phase modulation) of an ultrasonic signal propagating through the fluid **12** from the transmitting sensor **40** to the receiving sensor **42**. The transit time measurement or variation is indicative of a coherent properties that convect with the flow within the pipe (e.g., vortical disturbances, inhomogenities within the flow, temperature variations, bubbles, particles, pressure disturbances), which are indicative of the velocity of the process flow **12**. The ultrasonic sensors may operate at any frequency, however, it has be found that the higher frequency sensors are more suitable for single phase fluids while lower frequency sensors are more suitable for multiphase fluids. The optimum frequency of the ultrasonic sensor is dependent on the size or type of particle or substance propagating with the flow **12**. For instance, the larger the air bubbles in an aerated fluid the lower the desirable frequency of the ultrasonic signal. Examples of frequency used for a flow meter embodying the present invention are 1 MHz and 5 MHz. The ultrasonic sensors may also provide a pulsed, chirped or continuous signal through

the fluid flow **12**. An example of the sensors **40,42** that may be used are Model no. 113-241-591, manufactured by Krautkramer.

An ultrasonic signal processor **37** fires the sensors **40** in response to a firing signal **39** from the transmitter **24** and receives the ultrasonic output signals $S_1(t)$ - $S_N(t)$ from the sensors **42**. The signal processor **37** processes the data from each of the sensor units **18-21** to provide an analog or digital output signal $T_1(t)$ - $T_N(t)$ indicative of the time of flight or transit time of the ultrasonic signal through the fluid. The signal processor **37** may also provide an output signal indicative of the amplitude (or attenuation) of the ultrasonic signals. One such signal processor is model no. USPC 2100 manufactured by Krautkramer Ultrasonic Systems. Measuring the amplitude of ultrasonic signal is particularly useful and works best for measuring the velocity of a fluid that includes a substance in the flow (e.g., multiphase fluid or slurry).

The output signals ($T_1(t)$ - $T_N(t)$) of the ultrasonic signal processor **37** are provided to the processor **24**, which processes the transit time measurement data to determine the volumetric flow rate. The transit time or time of flight measurement is defined by the time it takes for an ultrasonic signal to propagate from the transmitting sensor **40** to the respective receiving sensor **42** through the pipe wall and the fluid **12**. The effect of the vortical disturbances (and/or other inhomogenities within the fluid) on the transit time of the ultrasonic signal is to delay or speed up the transit time. Therefore, each sensing unit **22-25** provides a respective output signal $T_1(t)$ - $T_N(t)$ indicative of the variations in the transit time of the ultrasonic signals propagating orthogonal to the direction of the fluid **12**. The measurement is derived by interpreting the convecting coherent property and/or characteristic within the process piping using at least two sensor units **22,23**. The ultrasonic sensors **22-25** may be "wetted" or clamped onto the outer surface **17** of the pipe **14** (e.g. contact or non-contact sensor).

In one example, the flow meter **10** measures the volumetric flow rate by determining the velocity of vortical disturbances or "eddies" **88** (see FIG. 2) propagating with the flow **12** using the array of ultrasonic sensors **22-25**. The flow meter **10** measures the velocities associated with unsteady flow fields created by vortical disturbances or "eddies" **88** and other inhomogenities to determine the velocity of the flow **12**. The ultrasonic sensor units **22-25** measure the transmit time $T_1(t)$ - $T_N(t)$ of the respective ultrasonic signals between each respective pair of sensors **40,42**, which vary due to the vortical disturbances as these disturbances convect within the flow **12** through the pipe **14** in a known manner. Therefore, the velocity of these vortical disturbances is related to the velocity of the flow **12** and hence the volumetric flow rate may be determined, as will be described in greater detail hereinafter. The volumetric flow is determined by multiplying the velocity of the fluid by the cross-sectional area of the pipe.

The Flow Logic **65** processes the ultrasonic signals in substantially similar way as that described for the Flow Logic **32** for the pressure signals shown in FIG. 3. Consequently, the pressure signals and the ultrasonic signals may be processed using a single processor to perform the Flow Logic **32** and the Flow Logic **65** or may be separate processors to enable simultaneous processing of the pressure and ultrasonic signals.

While each of the ultrasonic sensor units **22-25** of FIG. 1 comprises a pair of ultrasonic sensors (transmitter and receiver) **40,42** diametrically-opposed to provide through transmission, the present invention contemplates that one of

the ultrasonic sensors **40,42** of each sensor unit **22-25** may be offset axially such that the ultrasonic signal from the transmitter sensor has an axial component in its propagation direction.

The present invention also contemplates the sensor units **22-25** of the sensing device **16** may be configured in a pulse/echo configuration. In this embodiment, each sensing unit **22-25** comprises one ultrasonic sensor that transmits an ultrasonic signal through the pipe wall and fluid substantially orthogonal to the direction of flow and receives a reflection of the ultrasonic signal reflected back from the wall of the pipe to the ultrasonic sensor.

The sensing device **16** may be configured to function in a pitch and catch configuration. In this embodiment, each sensor unit **22-25** comprises a pair of ultrasonic sensors (transmitter, receiver) **40, 42** disposed axially along the pipe disposed on the same side of the pipe at a predetermined distance apart. Each transmitter sensor **40** provides an ultrasonic signal a predetermined angle into the flow **12**. The ultrasonic signal propagates through the fluid **12** and reflects of the inner surface of the pipe **14** and reflects the ultrasonic signal back through the fluid to the respective receiver sensor **42**.

As shown in FIG. **10**, while the ultrasonic sensor portion **51** comprises an array of ultrasonic sensor units **22-25** (see FIG. **1**), the present invention contemplates that any ultrasonic meter or sensing portion may be used. The ultrasonic meter may be any meter within any of the three classes of flow meters that utilize ultrasonic transducers, which include transit time ultrasonic flow meters (TTUF), doppler ultrasonic flow meters (DUF), and cross correlation ultrasonic flow meters (CCUF). A transit time ultrasonic meter is illustrated in FIG. **10**.

The ultrasonic sensor portion may be any known ultrasonic flow meter, such as U.S. Pat. No. 2,874,568; U.S. Pat. No. 4,004,461; U.S. Pat. No. 6,532,827; U.S. Pat. No. 4,195,517; U.S. Pat. No. 5,856,622; and U.S. Pat. No. 6,397,683, which are all incorporated herein by reference.

The array-based flow meter is similar to that described in U.S. patent application Ser. No. 10/007,749 filed Nov. 7, 2001, U.S. patent application Ser. No. 10/007,736 filed Nov. 8, 2001, U.S. Pat. No. 6,587,798, filed on Nov. 28, 2001, U.S. Provisional Patent Application Ser. No. 60/359,785 filed Feb. 26, 2002, U.S. Provisional Patent Application Ser. No. 60/425,436 filed Nov. 12, 2002, U.S. patent application Ser. No. 09/729,994, filed Dec. 4, 2000, and U.S. patent application Ser. No. 10,875,857 filed Jun. 24, 2004, which are all incorporated herein by reference.

While a single array processor **32** is shown to receive and process input signals from the pressure sensors **18-21** and the ultrasonic sensors **22-25**, the present invention contemplates that an array processor may be dedicated to each of the array of pressure sensor **18-21** and the array of ultrasonic sensors **22-25**.

In one embodiment as shown in FIG. **1**, each of the pressure sensors **18-21** may include a piezoelectric film **50** attached to a unitary multi-band strap **52** to measure the unsteady pressures of the flow **12** using either technique described hereinbefore. The piezoelectric film sensors **18-21** are mounted onto a unitary substrate or web which is mounted or clamped onto the outer surface **22** of the pipe **14**, which will be described in greater detail hereinafter.

The piezoelectric film sensors **18-21** include a piezoelectric material or film **50** to generate an electrical signal proportional to the degree that the material is mechanically deformed or stressed. The piezoelectric sensing element **50** is typically conformed to allow complete or nearly complete

circumferential measurement of induced strain to provide a circumferential-averaged pressure signal. The sensors can be formed from PVDF films, co-polymer films, or flexible PZT sensors, similar to that described in "Piezo Film Sensors Technical Manual" provided by Measurement Specialties, Inc., which is incorporated herein by reference. A piezoelectric film sensor that may be used for the present invention is part number 1-1002405-0, LDT4-028K, manufactured by Measurement Specialties, Inc. While the piezoelectric film material **50** is provided substantially the length of the band **44**, and therefore the circumference of the pipe **14**, the present invention contemplates that the piezoelectric film material may be disposed along a portion of the band of any length less than the circumference of the pipe.

Piezoelectric film ("piezofilm") **50**, like piezoelectric material, is a dynamic material that develops an electrical charge proportional to a change in mechanical stress. Consequently, the piezoelectric material measures the strain induced within the pipe **14** due to unsteady or stochastic pressure variations (e.g., vortical and/or acoustical) within the process flow **12**. Strain within the pipe is transduced to an output voltage or current by the attached piezoelectric sensor **18-21**. The piezoelectric material or film **50** may be formed of a polymer, such as polarized fluoropolymer, polyvinylidene fluoride (PVDF). The piezoelectric film sensors are similar to that described in U.S. patent application Ser. No. 10/712,818, filed Nov. 12, 2003 and U.S. patent application Ser. No. 10/795,111, filed Mar. 4, 2004, which are incorporated herein by reference. The advantages of this clamp-on technique using piezoelectric film include non-intrusive flow rate measurements, low cost, measurement technique requires no excitation source. One will appreciate that the sensor may be installed or mounted to the pipe **14** as individual sensors or all the sensors mounted as a single unit as shown in FIG. **1**.

The pressure sensors **18-21** of FIG. **1** described herein may be any type of sensor, capable of measuring the unsteady (or ac or dynamic) pressures or parameter that convects with the flow within a pipe **14**, such as piezoelectric, optical, capacitive, resistive (e.g., Wheatstone bridge), accelerometers (or geophones), velocity measuring devices, displacement measuring devices, ultra-sonic devices, etc. If optical pressure sensors are used, the sensors **18-21** may be Bragg grating based pressure sensors, such as that described in U.S. patent application Ser. No. 08/925,598, entitled "High Sensitivity Fiber Optic Pressure Sensor For Use In Harsh Environments", filed Sep. 8, 1997, now U.S. Pat. No. 6,016,702, and in U.S. patent application Ser. No. 10/224,821, entitled "Non-Intrusive Fiber Optic Pressure Sensor for Measuring Unsteady Pressures within a Pipe", which are incorporated herein by reference. In an embodiment of the present invention that utilizes fiber optics as the pressure sensors **14** they may be connected individually or may be multiplexed along one or more optical fibers using wavelength division multiplexing (WDM), time division multiplexing (TDM), or any other optical multiplexing techniques.

In certain embodiments of the present invention, a piezoelectric pressure transducer may be used as one or more of the pressure sensors **18-21** and it may measure the unsteady (or dynamic or ac) pressure variations inside the pipe **14** by measuring the pressure levels inside of the pipe. These sensors may be ported within the pipe to make direct contact with the process flow **12**. In an embodiment of the present invention, the sensors comprise pressure sensors manufactured by PCB Piezotronics. In one pressure sensor there are integrated circuit piezoelectric voltage mode-type

15

sensors that feature built-in microelectronic amplifiers, and convert the high-impedance charge into a low-impedance voltage output. Specifically, a Model 106B manufactured by PCB Piezotronics is used which is a high sensitivity, acceleration compensated integrated circuit piezoelectric quartz pressure sensor suitable for measuring low pressure acoustic phenomena in hydraulic and pneumatic systems.

It is also within the scope of the present invention that any strain sensing technique may be used to measure the variations in strain in the pipe, such as highly sensitive piezoelectric, electronic or electric, strain gages and piezo-resistive strain gages attached to the pipe **12**. Other strain gages include resistive foil type gages having a race track configuration similar to that disclosed U.S. patent application Ser. No. 09/344,094, filed Jun. 25, 1999, now U.S. Pat. No. 6,354,147, which is incorporated herein by reference. The invention also contemplates strain gages being disposed about a predetermined portion of the circumference of pipe **12**. The axial placement of and separation distance ΔX_1 , ΔX_2 between the strain sensors are determined as described herein above.

It is also within the scope of the present invention that any other strain sensing technique may be used to measure the variations in strain in the pipe, such as highly sensitive piezoelectric, electronic or electric, strain gages attached to or embedded in the pipe **14**.

While the description has described the apparatus as two separate meters that measure the vortical disturbances and the speed of sound, respectively, as suggested by FIG. 1, the processing could function as two separate meters, a combination (simultaneous operation) of both function, or selectively chose between operations.

The dimensions and/or geometries for any of the embodiments described herein are merely for illustrative purposes and, as such, any other dimensions and/or geometries may be used if desired, depending on the application, size, performance, manufacturing requirements, or other factors, in view of the teachings herein.

It should be understood that, unless stated otherwise herein, any of the features, characteristics, alternatives or modifications described regarding a particular embodiment herein may also be applied, used, or incorporated with any other embodiment described herein. Also, the drawings herein are not drawn to scale.

Although the invention has been described and illustrated with respect to exemplary embodiments thereof, the foregoing and various other additions and omissions may be made therein and thereto without departing from the spirit and scope of the present invention.

What is claimed is:

1. An apparatus for measuring a process flow flowing within a pipe, the apparatus comprising:

at least two strain sensors disposed at different axial locations along the pipe, each of the strain sensors providing a respective pressure signal indicative of pressure disturbances within the pipe at the corresponding axial location;

at least one ultrasonic sensor disposed along the pipe that provides an ultrasonic signal indicative of a parameter of the process flow; and

a signal processor, responsive to said pressure signals and ultrasonic signal, which provides a first signal indicative of a velocity of a pressure field moving with the process flow and/or provides a second signal indicative of a speed of sound propagating through the process flow.

16

2. The apparatus of claim **1**, wherein the processing unit includes a convective processing unit that determines the first signal and/or an acoustic processing unit that determines the second signal.

3. The apparatus of claim **2**, wherein the convective processing unit includes an array processor that determines power in the k - ω plane and determines the convective ridge in the k - ω plane.

4. The apparatus of claim **3**, wherein the convective processing unit includes an analyzer that determines a slope of the convective ridge to determine one of the velocity, the mach number, and volumetric flow rate of the process flow.

5. The apparatus of claim **2**, wherein the acoustic processing unit includes an array processor that determines power in the k - ω plane and determines the acoustic ridge in the k - ω plane.

6. The apparatus of claim **5**, wherein the acoustic processing unit includes an analyzer that determines a slope of the acoustic ridge to determine one of steam quality or "wetness", vapor/mass ratio, liquid/solid ratio, volumetric flow rate, mass flow rate, average size of suspended particles, density, gas volume fraction, and enthalpy of the flow.

7. The apparatus of claim **1**, wherein the process flow is one of a single phase fluid and a multi-phase mixture.

8. The apparatus of claim **1**, wherein the pressure signals are indication of acoustic pressures propagating axially within the flow and unsteady pressures convecting with the flow.

9. The apparatus of claim **8**, wherein the unsteady pressures convecting with the flow are indication of vortical disturbances within the flow.

10. The apparatus of claim **1**, wherein the at least two pressure sensors include one of 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 and 20 pressure sensors.

11. The apparatus of claim **1**, wherein the at least one ultrasonic sensor includes:

an array of at least two ultrasonic sensor disposed at predetermined locations along the elongated body, each ultrasonic sensor including an ultrasonic transmitter and an ultrasonic receiver, each ultrasonic sensor providing a respective signal indicative of a parameter of an ultrasonic signal propagating between each respective ultrasonic transmitter and ultrasonic receiver.

12. The apparatus of claim **11**, wherein the processor samples the ultrasonic signals over a predetermined time period, accumulates the sampled ultrasonic signals over a predetermined sampling period, and processes the sampled ultrasonic signals to define the convective ridge in the k - ω plane.

13. The apparatus of claim **12**, wherein the ultrasonic signals are indicative of vortical disturbances with the fluid.

14. The apparatus of claim **11**, wherein the parameter of the ultrasonic signal is at least one of the signal amplitude and the signal transit time of an ultrasonic signal.

15. The apparatus of claim **11**, wherein the at least two ultrasonic sensor units include one of 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 and 20 ultrasonic sensors.

16. The apparatus of claim **15**, wherein the signal processor defines a convective ridge in the k - ω plane in response to the ultrasonic signals, and determines the slope of at least a portion of the convective ridge to determine the flow velocity of the fluid.

17. The apparatus of claim **15**, wherein the signal processor, in response to the ultrasonic signals, determines the velocity of the process flow using adaptive array processing algorithms.

17

18. The apparatus of claim 1, wherein the signal processor in response to a measured characteristic of the process flow provides one of a first output signal, responsive to the first signal, or a second output signal, responsive to the second signal.

19. The apparatus of claim 18, wherein the measured characteristic of the process flow is the velocity of the process flow.

20. The apparatus of claim 18, wherein the environmental condition is vibration on the pipe.

21. The apparatus of claim 1, wherein the signal processor in response to an environmental condition provides one of a first output signal, responsive to the first signal, or a second output signal, responsive to the second signal.

22. The apparatus of claim 1, wherein the signal processor in response to a user input signal provides one of a first output signal, responsive to the first signal, or a second output signal, responsive to the second signal.

23. An apparatus for measuring a process flow flowing within a pipe, the apparatus comprising:

at least two strain sensors disposed at different axial locations along the pipe, each of the strain sensors providing a respective pressure signal indicative of pressure disturbances within the pipe at the corresponding axial location;

at least one ultrasonic sensor disposed along the pipe that provides an ultrasonic signal indicative of a parameter of the process flow; and

a signal processor which, responsive to said ultrasonic signal, provides a first signal indicative of a velocity of the process flow; and which, responsive to said pressure signals, provides a second signal indicative of a velocity of a pressure field moving with the process flow and/or a third signal indicative of the speed of sound propagating axially through the process flow.

24. The apparatus of claim 23, wherein the processing unit includes a convective processing unit that determines the first and second signal and/or an acoustic processing unit that determines the third signal.

25. The apparatus of claim 24, wherein the convective processing unit includes an array processor that determines power in the k - ω plane, and determines the convective ridge in the k - ω plane.

26. The apparatus of claim 25, wherein the convective processing unit includes an analyzer that determines a slope of the convective ridge to determine one of the velocity, the mach number, and volumetric flow rate of the process flow.

27. The apparatus of claim 24, wherein the acoustic processing unit includes an array processor that determines power in the k - ω plane, and determines the acoustic ridge in the k - ω plane.

28. The apparatus of claim 27, wherein the acoustic processing unit includes an analyzer that determines a slope of the acoustic ridge to determine one of steam quality or "wetness", vapor/mass ratio, liquid/solid ratio, volumetric flow rate, mass flow rate, average size of suspended particles, density, gas volume fraction, and enthalpy of the flow.

29. The apparatus of claim 23, wherein the process flow is one of a single phase fluid and a multi-phase mixture.

30. The apparatus of claim 23, wherein the pressure signals are indication of acoustic pressures propagating axially within the flow and unsteady pressures convecting with the flow.

31. The apparatus of claim 30, wherein the unsteady pressures convecting with the flow are indication of vortical disturbances within the flow.

18

32. The apparatus of claim 23, wherein the at least two pressure sensors include one of 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 and 20 pressure sensors.

33. The apparatus of claim 23, wherein the at least one ultrasonic sensor includes:

an array of at least two ultrasonic sensor disposed at predetermined locations along the elongated body, each ultrasonic sensor including an ultrasonic transmitter and an ultrasonic receiver, each ultrasonic sensor providing a respective signal indicative of a parameter of an ultrasonic signal propagating between each respective ultrasonic transmitter and ultrasonic receiver.

34. The apparatus of claim 33, wherein the signal processor samples the ultrasonic signals over a predetermined time period, accumulates the sampled ultrasonic signals over a predetermined sampling period, and processes the sampled ultrasonic signals to define the convective ridge in the k - ω plane.

35. The apparatus of claim 34, wherein the ultrasonic signals are indicative of vortical disturbances with the fluid.

36. The apparatus of claim 23, wherein the parameter of the ultrasonic signal is at least one of the signal amplitude and the signal transit time of an ultrasonic signal.

37. The apparatus of claim 23, wherein the at least two ultrasonic sensor units include one of 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 and 20 ultrasonic sensors.

38. The apparatus of claim 37, wherein the signal processor defines a convective ridge in the k - ω plane in response to the ultrasonic signals, and determines the slope of at least a portion of the convective ridge to determine the flow velocity of the fluid.

39. The apparatus of claim 37, wherein the signal processor, in response to the ultrasonic signals, determines the velocity of the process flow using adaptive array processing algorithms.

40. The apparatus of claim 23, wherein the signal processor in response to a measured characteristic of the process flow provides one of a first output signal, responsive to the first signal, or a second output signal, responsive to the second signal.

41. The apparatus of claim 40, wherein the measured characteristic of the process flow is the velocity of the process flow.

42. The apparatus of claim 23, wherein the signal processor in response to an environmental condition provides one of a first output signal, responsive to the first signal, or a second output signal, responsive to the second signal.

43. The apparatus of claim 40, wherein the environmental condition is vibration on the pipe.

44. The apparatus of claim 23, wherein the signal processor in response to a user input signal provides one of a first output signal, responsive to the first signal, or a second output signal, responsive to the second signal.

45. A method for measuring a parameter of a process flow flowing within a pipe, the method comprising:

providing respective pressure signal using at least two strain sensors disposed at different axial locations along the pipe, the respective pressure signals being indicative of pressure disturbances within the pipe at the corresponding axial location;

providing an ultrasonic signal using at least one ultrasonic sensor disposed along the pipe, the ultrasonic signal being indicative of a parameter of the process flow; and

determining a first signal indicative of a velocity of a pressure field moving with the process flow in response to said pressure signals and ultrasonic signal; and/or

19

determining a second signal indicative of a speed of sound propagating through the process flow.

46. The method of claim 45, wherein the at least one ultrasonic sensor provides a first signal indicative of a velocity of a pressure field moving with the process flow includes:

an array of at least two ultrasonic sensor disposed at predetermined locations along the elongated body, each ultrasonic sensor including an ultrasonic transmitter and an ultrasonic receiver, each ultrasonic sensor providing a respective signal indicative of a parameter of an ultrasonic signal propagating between each respective ultrasonic transmitter and ultrasonic receiver.

47. The method of claim 45, wherein the parameter of the ultrasonic signal is at least one of the signal amplitude and the signal transit time of an ultrasonic signal.

48. The method of claim 46 wherein the at least two ultrasonic sensor units include one of 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 and 20 ultrasonic sensors.

49. The method of claim 48, further including determining the slope of at least a portion a convective ridge in the k - ω plane to determine the flow velocity of the fluid in response to the ultrasonic signals.

50. The method of claim 48, further including determining, in response to the ultrasonic signals, the velocity of the process flow using adaptive array processing algorithms.

51. A method for measuring a process flow flowing within a pipe, the apparatus comprising:

at least two strain sensors disposed at different axial locations along the pipe, each of the strain sensors providing a respective pressure signal indicative of pressure disturbances within the pipe at the corresponding axial location;

at least one ultrasonic sensor disposed along the pipe that provides an ultrasonic signal indicative of a parameter of the process flow;

determining, in response to said ultrasonic signal, a first signal indicative of a velocity of the process flow; and determining, in response, to said pressure signals, a second signal indicative of a velocity of a pressure field

20

moving with the process flow and/or a third signal indicative of the speed of sound propagating axially through the process flow.

52. The method of claim 51, wherein the at least one ultrasonic sensor includes:

an array of at least two ultrasonic sensor disposed at predetermined locations along the elongated body, each ultrasonic sensor including an ultrasonic transmitter and an ultrasonic receiver, each ultrasonic sensor providing a respective signal indicative of a parameter of an ultrasonic signal propagating between each respective ultrasonic transmitter and ultrasonic receiver.

53. The method of claim 51, wherein the parameter of the ultrasonic signal is at least one of the signal amplitude and the signal transit time of an ultrasonic signal.

54. The method of claim 52, wherein the at least two ultrasonic sensor units include one of 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 and 20 ultrasonic sensors.

55. The method of claim 54, further including determining the slope of at least a portion a convective ridge in the k - ω plane to determine the flow velocity of the fluid in response to the ultrasonic signals.

56. The method of claim 54, further including determining, in response to the ultrasonic signals, the velocity of the process flow using adaptive array processing algorithms.

57. The method of claim 51, further determining, in response to a measured characteristic of the process flow, one of a first output signal, responsive to the first signal, or a second output signal, responsive to the second signal.

58. The method of claim 51, further including determining, in response to an environmental condition, one of a first output signal, responsive to the first signal, or a second output signal, responsive to the second signal.

59. The method of claim 51, further including determining, in response to a user input signal, one of a first output signal, responsive to the first signal, or a second output signal, responsive to the second signal.

* * * * *