



US007254354B2

(12) **United States Patent**
Hirano

(10) **Patent No.:** **US 7,254,354 B2**
(45) **Date of Patent:** ***Aug. 7, 2007**

(54) **IMAGE FORMING APPARATUS AND CONTROL METHOD FOR THE SAME**

(75) Inventor: **Yoshiharu Hirano**, Shizuoka-ken (JP)

(73) Assignees: **Kabushiki Kaisha Toshiba**, Tokyo (JP); **Toshiba Tec Kabushiki Kaisha**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **11/495,529**

(22) Filed: **Jul. 31, 2006**

(65) **Prior Publication Data**

US 2006/0275047 A1 Dec. 7, 2006

Related U.S. Application Data

(63) Continuation of application No. 10/872,473, filed on Jun. 22, 2004, now Pat. No. 7,113,720.

(30) **Foreign Application Priority Data**

Jul. 8, 2003 (JP) 2003-193852

(51) **Int. Cl.**

G03G 15/00 (2006.01)
G03G 21/02 (2006.01)

(52) **U.S. Cl.** **399/80; 399/79**

(58) **Field of Classification Search** 399/79,
399/80

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,694,222	A	12/1997	Yamada
5,708,709	A	1/1998	Rose
5,999,766	A	12/1999	Hisatomi et al.
6,026,258	A	2/2000	Fresk et al.
6,385,675	B1	5/2002	Yamaguchi
6,498,912	B1	12/2002	Leni et al.
6,903,840	B1	6/2005	Maymin et al.
7,113,720	B2 *	9/2006	Hirano 399/80
2003/0131251	A1	7/2003	Fetkovich

FOREIGN PATENT DOCUMENTS

JP	2001-34469	A	2/2001
JP	2002-366245	A	12/2002

* cited by examiner


Primary Examiner—Sandra L. Brase

(74) *Attorney, Agent, or Firm*—Foley & Lardner LLP

(57) **ABSTRACT**

For a network printer function and a network scan function, a trial using mode whose use frequency is limited can be set. When the preset trial using mode is finished, the use of the tried function is permitted according to setting of an exclusive key.

18 Claims, 4 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

1

IMAGE FORMING APPARATUS AND CONTROL METHOD FOR THE SAME

The present application is a continuation of U.S. application Ser. No. 10/872,473, filed Jun. 22, 2004 now U.S. Pat. No. 7,113,720, the entire contents of which is incorporated herein by reference.

CROSS-REFERENCE TO RELATED APPLICATION

This application is based upon and claims the benefit of priority from the prior Japanese Patent Application No. 2003-193852 filed on Jul. 8, 2003; the entire contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a composite image forming apparatus having a plurality of functions such as a copying function, a network scanner function, and a network printer function and a control method therefor.

2. Description of the Related Art

There is a composite image forming apparatus having a plurality of functions such as, in addition to the regular copying function, the network scanner function for externally transmitting an image read by a scanner by attaching it to an electronic mail and the network printer function for printing and outputting an image according to an image signal input externally.

In such a composite image forming apparatus, the copying function can be used immediately as a standard function. However, the network scanner function and network printer function may be permitted to use them under the condition that a user optionally purchases them when necessary.

However, even if the user optionally purchases the network scanner function or network printer function, thereafter he has few chances to use it, thus he may be required for useless expenses.

SUMMARY OF THE INVENTION

An object of the present invention is to provide an image forming apparatus giving superior services such that a user can use one or a plurality of functions on trial and can optionally decide optional purchase of a desired function on the basis of the use and a control method therefor.

According to the present invention, an image forming apparatus having a plurality of functions is provided and the image forming apparatus comprises setting means for setting a trial using mode for limiting a use frequency or use days of at least one function among the plurality of functions; and control means, when the preset trial using mode reaches the limited use frequency or the use days or when the trial using mode is interrupted during the limited use frequency or the use days, for permitting subsequent use of the tried function according to setting of an exclusive key.

Furthermore, according to the present invention, a control method for an image forming apparatus having a plurality of functions is provided and the control method comprises setting a trial using mode for limiting a use frequency or use days of at least one function among the plurality of functions; and permitting subsequent use of the tried function according to an exclusive key when the preset trial using mode reaches the limited use frequency or the use days or

2

when the trial using mode is interrupted during the limited use frequency or the use days.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view showing an embodiment of the image forming apparatus of the present invention;

FIG. 2 is a plan view schematically showing the constitution of the control panel of the image forming apparatus shown in FIG. 1;

FIG. 3 is a block diagram showing the control circuit of the image forming apparatus shown in FIG. 1;

FIG. 4 is a flow chart for explaining the operation of the image forming apparatus shown in FIG. 1;

FIG. 5 is a plan view showing a display example of the control panel shown in FIG. 2;

FIG. 6 is a plan view showing another display example of the control panel shown in FIG. 2; and

FIG. 7 is a plan view showing still another display example of the control panel shown in FIG. 2.

DETAILED DESCRIPTION OF THE INVENTION

An embodiment of the present invention will be explained below with reference to the accompanying drawings. As shown in FIG. 1, on the top of main body 1 of the image forming apparatus, document table 2 is installed. On document table 2, automatic document feeder 3 including an ejection tray is installed so as to be freely opened or closed. In the position at the same height as that of document table 2, control panel 4 shown in FIG. 2 is installed as an operation means for setting operation conditions.

On the lower part of main body 1, paper supply cassettes 5 to 8 storing papers of various sizes which are image forming media are installed.

On the side of main body 1, USB interface 9 for inserting and connecting print enable key 11 or scan enable key 12 is installed. Print enable key 11 and scan enable key 12 are an exclusive key given from a manufacturer or a sales agency to permit use of a function tried. Each exclusive key has a built-in memory storing the use-permitted code. Each exclusive key may be a password given from the manufacturer or sales agency. In this case, when the password is input from control panel 4, the tried function is permitted to be used.

FIG. 3 shows the control circuit inside main body 1.

Reference numeral 20 indicates a CPU which is a center of control and to CPU 20, decoder 21, RAM 22, ROM 23, counter 24, wave clock 25, panel controller 31, copy controller 32, network scanner controller 33, network printer controller 34, and network controller 37.

Decoder 21 reads a code from print enable key 11 or scan enable key 12 inserted and connected to USB interface 9 and decodes the code. The decoded results are supplied to CPU 20. RAM 22 stores decoding data for the aforementioned code, preset value N for printing number of times P which will be described later, and preset value S for scanning number of times L which will be described later. ROM 23 stores various kinds of control programs necessary for the operation of main body 1. Counter 24 counts printing number of times P and scanning number of times L in the trial using mode. Wave clock 25 is equipped with antenna 25a, measures the present time, and successively updates the present time by receiving a standard time wave.

Panel controller 31 controls control panel 4. Copy controller 32 controls the copy function using scanner 35 and printer 36. Network scanner controller 33 controls the net-

work scanner function using scanner **35**. Network printer controller **34** controls the network printer function (the FAX function included) using printer **36**. Network controller **37** controls data transmission and reception from the outside via network interface **38**.

Network interface **38** includes a LAN board and a FAX modem and is connected to many personal computers **41** which are user terminals via external communication line **40**.

CPU **20** has the next means (1) and (2) as main functions.

(1) A setting means for setting a trial using mode for limiting the trial frequency (or use days) of at least one function among the network scanner function and network printer function.

(2) A control means, during or after end of the preset trial using mode, for permitting the subsequent use of the function tried according to the setting (insertion and connection) of print enable key **11** or scan enable key **12**.

Next, the operation of the aforementioned constitution will be explained by referring to the flow chart shown in FIG. **4**.

When main body **1** is installed and then a request for network print trial is input from control panel **4** (YES at Step **101**), the trial using mode of the network printer function is started in main body **1** according to the input (Step **102**). The request for network print trial is received by operation of a serviceman present at the installation. And, trial preset value N of the network printer function is set to, for example, 10,000 sheets and printing number of times P of counter **24** is initialized to 0 (Step **103**).

When in the state that print enable key **11** is not set (NO at Step **104**), a print instruction is input to main body **1** from personal computer **41** via communication line **40** (YES at Step **105**), a print operation according to an image signal input from personal computer **41** is executed by printer **36** (YES at Step **106**). In correspondence with this print operation, printing number of times P of counter **24** is incremented by 1 (Step **107**), and printing number of times P after increment of 1 is subtracted from trial preset value N, and residual trial preset value E is obtained (Step **108**). Obtained residual trial preset value E, as shown in FIG. **5**, is displayed in characters in the display area of control panel **4** as "Print residual: . . . sheets" (Step **109**). When the user looks at the display, he can confirm residual preset value E of trial network print.

Before residual trial preset value E becomes 0 (NO at Step **110**), if in the print instruction, there are a plurality of print jobs, until all the print jobs are finished (YES at Step **111**), the processes from Step **106** to Step **109** are repeated.

Even if residual trial preset value E becomes 0 (YES at Step **110**), when all the print jobs are not finished (NO at Step **112**), the processes from Step **106** to Step **109** are repeated.

When residual trial preset value E becomes 0 or less (YES at Step **110**) and all the print jobs are finished (YES at Step **112**), the trial using mode of the network print function is finished. By doing this, as shown in FIG. **6**, in the display area of control panel **4**, the characters of "Trial using mode end" are displayed (Step **113**).

After end of the trial using mode of the network printer function, if print enable key **11** is not inserted and connected to USB interface **9** (NO at Step **114**), the use of the network printer function is prohibited as it is (Step **115**).

After end of the trial using mode of the network printer function, a user desiring use of the network printer function is given print enable key **11** from a store. In print enable key **11**, an identification code intrinsic to main body **1** is stored

together with a printable code as a condition for permitting use. When print enable key **11** is inserted and connected to USB interface **9** (YES at Step **114**), a code is read from print enable key **11** and the read code is decoded (Step **116**). When the decoded result coincides with the identification code intrinsic to the main body **1** and the printable code (YES at Step **117**), the subsequent use of the network printer function is permitted (Step **118**).

During the trial using mode of the network printer function, print enable key **11** may be inserted and connected to USB interface **9** (YES at Step **104**). In this case, a code is read from print enable key **11** and the read code is decoded (Step **119**). When the decoded result does not coincide with the identification code intrinsic to the main body **1** and the printable code (NO at Step **120**), the effect of inconsistency is displayed in the display area of control panel **4** (Step **121**). The user looking at this display requests to exchange print enable key **11** to a proper one and inserts and connects a new one again to USB interface **9** (YES at Step **104**).

A code is read and decoded from reset print enable key **11** (Step **119**) and when the decoded result coincides with the identification code intrinsic to main body **1** and the printable code (YES at Step **120**), since print enable key **11** is reset (YES at Step **122**), the subsequent use of the network printer function is permitted (Step **118**).

When main body **1** is installed and then a request for network scan trial is input from control panel **4** (YES at Step **123**), the trial using mode of the network scan function is started in main body **1** according to the input (Step **124**). The request for network scan trial is also received by operation of a serviceman present at the installation. And, trial preset value S of the network scan function is set to, for example, 10000 sheets and scanning number of times L of counter **24** is initialized to 0 (Step **125**).

When in the state that scan enable key **12** is not set (NO at Step **104**), a scan instruction is input from main body **1** (YES at Step **126**), a scan operation is executed by scanner **35** according to an operation from main body **1** of the image forming apparatus (Step **127**). In correspondence with this scan operation, scanning number of times L of counter **24** is incremented by 1 (Step **128**), and scanning number of times L after increment of 1 is subtracted from trial preset value S, and residual trial preset value M is obtained (Step **129**). Obtained residual trial preset value M, as shown in FIG. **5**, is displayed in the display area of control panel **4** as "Scan residual: . . . sheets" (Step **130**). When the user looks at the display, he can confirm residual preset value M of trial network scan.

Before residual trial preset value M becomes "0" (NO at Step **131**), if in the scan instruction, there are a plurality of scan jobs, until all the scan jobs are finished (YES at Step **132**), the processes from Step **127** to Step **130** are repeated.

Even if residual trial preset value M becomes 0 (YES at Step **131**), when all the scan jobs are not finished (NO at Step **132**), the processes from Step **127** to Step **130** are repeated.

When residual trial preset value M becomes 0 or less (YES at Step **131**) and all the scan jobs are finished (YES at Step **112**), the trial using mode of the network print function is finished. By doing this, as shown in FIG. **6**, in the display area of control panel **4**, the characters of "Trial using mode end" are displayed (Step **133**).

After end of the trial using mode of the network printer function, if scan enable key **12** is not inserted and connected to USB interface **9** (NO at Step **134**), the use of the network scan function is prohibited as it is (Step **135**).

5

After end of the trial using mode of the network scan function, a user desiring use of the network scan function is given scan enable key **12** from a store. In scan enable key **12**, an identification code intrinsic to main body **1** is stored together with a scannable code as a condition for permitting use.

When scan enable key **12** is inserted and connected to USB interface **9** (YES at Step **134**), a code is read from scan enable key **12** and the read code is decoded (Step **136**). When the decoded result coincides with the identification code intrinsic to the main body **1** and the scannable code (YES at Step **137**), the subsequent use of the network scan function is permitted (Step **138**).

During the trial using mode of the network scan function, scan enable key **12** may be inserted and connected to USB interface **9** (YES at Step **104**). In this case, a code is read from scan enable key **12** and the read code is decoded (Step **119**). When the decoded result does not coincide with the identification code intrinsic to the main body **1** and the scannable code (NO at Step **120**), the effect of inconsistency is displayed in the display area of control panel **4** (Step **121**). The user looking at this display requests to exchange scan enable key **12** to a proper one and inserts and connects a new one again to USB interface **9** (YES at Step **104**).

A code is read and decoded from reset scan enable key **12** (Step **119**) and when the decoded result coincides with the identification code intrinsic to main body **1** and the printable code (YES at Step **120**), since scan enable key **12** is reset (NO at Step **122**), the subsequent use of the network scan function is permitted (Step **138**).

As explained above, the image forming apparatus has, in addition to the copy function which can be used regularly, the network print function and network scan function and a user can use these functions on trial. By doing this, he can sufficiently recognize by his own experience whether the respective functions are necessary or not. As a result, only when the user desires to optionally purchase his desired function, print enable key **11** or scan enable key **12** for permitting use of the function is given, so that efficient business free of disadvantage can be executed by a store or a manufacturer supplying main body **1**. For the user, the present invention is economical because he does not need to pay a rental fee of a useless function which is not used.

Further, in the aforementioned embodiment, as a limit to the trial using mode, residual trial printing number of times P or M is decided. However, simultaneously with first print and first scan, time count by measurement of the wave clock is started and the elapsed days on the basis of the time count may be decided as a limit to the trial using mode. In this case, as shown in FIG. 7, in the display area of control panel **4**, "Trial term: residual . . . days" is displayed.

Further, in the aforementioned embodiment, the exclusive key having a built-in memory storing a use-permitted code is described. However, it may be a password given from a manufacturer or a sales agent. In this case, when this password is input from control panel **4**, the use of the function tried is permitted.

The present invention is not limited to the aforementioned embodiment itself and in the execution stage, as long as the objects of the present invention are accomplished, the components may be modified and materialized. Further, by a proper combination of a plurality of components disclosed in the aforementioned embodiment, various inventions can be formed. For example, from all the components shown in the embodiment, some components may be deleted. Furthermore, components included in different embodiments may be properly combined.

6

As mentioned above, according to the present invention, a plurality of functions can be used on trial by a user and an image forming apparatus realizing superior services such that a user can decide to optionally purchase his desired function on the basis of the use and a control method for it can be provided.

What is claimed is:

1. An image forming apparatus having a plurality of functions, comprising:

a control panel that is adapted to set a trial using mode to a main body of the image forming apparatus for limiting usable times of a network printer function among the plurality of functions;

a printer portion that is adapted to execute a printer operation according to an image signal input from a computer when a print instruction is input to the main body from the computer via a network in the state that a print enable key is not inserted to the main body; and

a CPU that is adapted to control the printer portion to finish the trial using mode of the network print function when a number of printing times reaches the limited usable times in correspondence with the print operation;

wherein the CPU judges whether the print enable key is inserted to the main body or not, and permits subsequent use of the network print function when it is judged that the print enable key is inserted to the main body after the end of the trial using mode and a code read from the print enable key coincides with an identification code intrinsic to the main body.

2. The apparatus according to claim **1**, wherein the CPU controls the control panel to be set a request for trial use to a start condition for the trial using mode.

3. The apparatus according to claim **1**, wherein the print enable key includes a use-permitted password to permit subsequent use of the network print function when the password is input.

4. An image forming apparatus having a plurality of functions, comprising:

a control panel that is adapted to set a trial using mode to a main body of the image forming apparatus for limiting usable times of a network scan function among the plurality of functions;

a scanner portion that is adapted to execute a scan operation according to an operation from the main body of the image forming apparatus when a scan instruction is input to the main body in the state that a scan enable key is not inserted to the main body; and

a CPU that is adapted to control the scanner portion to finish the trial using mode of the network scan function when a number of scanning times reaches the limited usable times in correspondence with the scan operation;

wherein the CPU judges whether the scan enable key is inserted to the main body or not, and permits subsequent use of the network scan function when it is judged that the scan enable key is inserted to the main body after the end of the trial using mode and a code read from the scan enable key coincides with an identification code intrinsic to the main body.

5. The apparatus according to claim **4**, wherein the CPU controls the control panel to be set a request for trial use to a start condition for the trial using mode.

6. The apparatus according to claim **4**, wherein the scan enable key includes a use-permitted password to permit subsequent use of the network scan function when the password is input.

7

7. A control method for an image forming apparatus having a plurality of functions, comprising:

setting a trial using mode to a main body of the image forming apparatus for limiting usable times of a network printer function among the plurality of functions; 5
executing a print operation according to an image signal input from a computer when a print instruction is input to the main body from the computer via a network in the state that a print enable key is not inserted to the main, body; 10

finishing the trial using mode of the network print function when a number of times printing reaches the limited usable times in correspondence with the print operation; 15

judging whether the print enable key is inserted to the main body or not, and 20

permitting subsequent use of the network print function when it is judged that the print enable key is inserted to the main body after the end of the trial using mode and a code read from the print enable key coincides with an identification code intrinsic to the main body. 25

8. The control method according to claim 7, wherein the setting step sets a request for trial use to a start condition for the trial using mode.

9. The control method according to claim 7, wherein the print enable key includes a use-permitted password and the permitting step, when the password is input, permits subsequent use of the network print function. 30

10. A control method for an image forming apparatus having a plurality of functions, comprising: 35

setting a trial using mode to a main body of the image forming apparatus for limiting usable times of a network scan function among the plurality of functions; 40
executing a scan operation according to an operation from the main body of the image forming apparatus when a scan instruction is input to the main body in the state that a scan enable key is not inserted to the main body; 45

finishing the trial using mode of the network scan function when scanning a number of times scanning reaches the limited usable times in correspondence with the scan operation; 50

judging whether the scan enable key is inserted to the main body or not; and 55

permitting subsequent use of the network scan: function when it is judged that the scan enable key is inserted to the main body after the end of the trial using mode and a code read from the scan enable key coincides with an identification code intrinsic to the main body. 60

11. The control method according to claim 10, wherein the setting step sets a request for trial use to a start condition for the trial using mode.

12. The control method according to claim 10, wherein the scan enable key includes a use-permitted password and the permitting step, when the password is input, permits subsequent use of the network scan function.

13. An image forming apparatus having a plurality of functions, comprising:

means for setting a trial using mode to a main body of the image forming apparatus for limiting usable times of a network printer function among the plurality of functions; 60

8

means for executing a print operation according to an image signal input from a computer when a print instruction is input to the mainbody from the computer via a network in the state that a print enable key is not inserted to the main body;

means for finishing the trial using mode of the network print function when a number of times printing reaches the limited usable times in correspondence with the print operation;

means for judging whether the print enable key is inserted to the main body or not; and

means for permitting subsequent use of the network print function when it is judged that the print enable key is inserted to the main body after the end of the trial using mode and a code read from the print enable key coincides with an identification code intrinsic to the main body.

14. The apparatus according to claim 13, wherein the setting means sets a request for trial use to a start condition for the trial using mode.

15. The apparatus according to claim 13, wherein the print enable key includes a use-permitted password and the permitting means, when the password is input, permits subsequent use of the tried network print function.

16. An image forming apparatus having a plurality of functions, comprising:

means for setting a trial using mode to a main body of the image forming apparatus for limiting usable times of a network scan function among the plurality of functions;

means for executing a scan operation according to an operation from the main body of the image forming apparatus when a scan instruction is input to the main body in the state that a scan enable key is not inserted to the main body;

means for finishing the trial using mode of the network scan function when a number of times scanning reaches the limited usable times in correspondence with the scan operation;

means for judging whether the scan enable key is inserted to the main body or not; and

means for permitting subsequent use of the network scan function when it is judged that the scan enable key is inserted to the main body after the end of the trial using mode and a code read from the scan enable key coincides with an identification code intrinsic to the main body.

17. The apparatus according to claim 16, wherein the setting means sets a request for trial use to a start condition for the trial using mode.

18. The apparatus according to claim 16, wherein the scan enable key includes a use-permitted password and the permitting means, when the password is input, permits subsequent use of the tried network scan function.

* * * * *