



US007259482B2

(12) **United States Patent**
Voll et al.

(10) **Patent No.:** **US 7,259,482 B2**
(45) **Date of Patent:** **Aug. 21, 2007**

(54) **DISTANCE EXTENDER AND METHOD**
MAKING USE OF SAME

4,150,429 A	4/1979	Ying	364/200
4,243,984 A	1/1981	Ackley et al.	340/703
4,313,176 A	1/1982	Cecil	364/900
4,468,612 A	8/1984	Starr	324/66
4,479,122 A	10/1984	Redman et al.	340/825.06
4,550,386 A	10/1985	Hirosawa et al.	364/900

(75) Inventors: **Parker J. Voll**, Rochester, NY (US);
Randy J. King, Rochester, NY (US);
Jack E. Priebe, Palmyra, NY (US);
Ronald C. Moffatt, Rochester, NY (US)

(Continued)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Belkin International, Inc.**, Compton, CA (US)

DE 9303716.3 11/1993

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 497 days.

OTHER PUBLICATIONS

NTI Catalog, 2001.

(21) Appl. No.: **10/670,403**

(Continued)

(22) Filed: **Sep. 24, 2003**

Primary Examiner—Robert L. Deberadinis
Assistant Examiner—Hal I. Kaplan

(65) **Prior Publication Data**

(74) *Attorney, Agent, or Firm*—Bryan Cave LLP

US 2005/0063108 A1 Mar. 24, 2005

(57) **ABSTRACT**

(51) **Int. Cl.**
H01B 11/02 (2006.01)
H02B 1/20 (2006.01)
H04B 3/00 (2006.01)
G06F 13/00 (2006.01)
G06F 1/00 (2006.01)

A distance extender (100, 200) for increasing a distance between a first device (145) and a second device (150) in electrical communication with the first device includes an electrical cable (130, 230) electrically coupled between the first device and the second device, a first subsystem (110, 210) electrically coupled to the first end of the electrical cable, and a second subsystem (120, 220) electrically coupled to the second end of the electrical cable. The electrical cable includes a first end (131, 231), a second end (132, 232), and a plurality of wires extending between the first end and the second end. The plurality of wires includes a first wire, the first device generates a data signal and provides an electrical power signal, and the data signal and the electrical power signal are simultaneously transmitted between the first device and the second device over the first wire.

(52) **U.S. Cl.** 307/147; 710/100

(58) **Field of Classification Search** 307/147, 307/3, 4, 5, 6; 713/310


See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,634,830 A	1/1972	Baskin	340/172.5
3,774,158 A	11/1973	Clark	340/172.5
3,955,188 A	5/1976	Viswanathan	340/324 AD
4,078,249 A	3/1978	Lelke et al.	364/200
4,081,797 A	3/1978	Olson	340/324 AD

36 Claims, 15 Drawing Sheets



U.S. PATENT DOCUMENTS			
4,599,611 A	7/1986	Bowker et al.	340/721
4,630,284 A	12/1986	Cooperman	375/36
4,641,262 A	2/1987	Bryan et al.	364/900
4,665,501 A	5/1987	Saldin et al.	364/900
4,680,622 A	7/1987	Barnes et al.	358/22
4,710,917 A	12/1987	Tompkins et al.	370/62
4,730,251 A	3/1988	Aakre et al.	364/200
4,768,083 A	8/1988	Romesburg	358/22
4,800,429 A	1/1989	Perkins	358/148
4,807,184 A	2/1989	Shelor	364/900
4,823,256 A	4/1989	Bishop et al.	364/200
4,876,712 A	10/1989	Brint et al.	379/387
4,879,716 A	11/1989	McNalley et al.	371/8.2
4,907,079 A	3/1990	Turner et al.	358/84
4,939,507 A	7/1990	Beard et al.	340/706
4,941,087 A	7/1990	Kap	364/200
4,949,169 A	8/1990	Lumelsky et al.	358/86
4,949,248 A	8/1990	Caro	364/200
4,953,027 A	8/1990	Tong et al.	358/188
4,953,159 A	8/1990	Hayden et al.	370/62
4,972,470 A	11/1990	Farago	380/3
5,029,111 A	7/1991	Mansell	364/521
5,036,484 A	7/1991	McCoy et al.	364/900
5,043,866 A	8/1991	Myre, Jr. et al.	364/200
5,051,720 A	9/1991	Kittirutsunetorn	340/310 R
5,117,225 A	5/1992	Wang	340/717
5,121,486 A	6/1992	Kurihara et al.	395/325
5,128,766 A	7/1992	Choi	358/183
5,166,674 A	11/1992	Baum et al.	340/825.07
5,181,858 A	1/1993	Matz et al.	439/188
5,214,785 A	5/1993	Fairweather	395/800
5,220,380 A	6/1993	Hirata et al.	355/204
5,222,212 A	6/1993	Johary et al.	395/162
5,226,123 A	7/1993	Vockenhuber	395/325
5,230,066 A	7/1993	Morimi	395/166
5,247,364 A	9/1993	Banker et al.	358/191.1
5,247,615 A	9/1993	Mori et al.	395/200
5,260,778 A	11/1993	Kauffman et al.	358/86
5,261,079 A	11/1993	Celi, Jr.	395/500
5,268,676 A	12/1993	Asprey et al.	345/2
5,280,583 A	1/1994	Nakayama et al.	395/200
5,283,639 A	2/1994	Esch et al.	348/6
5,287,461 A	2/1994	Moore	395/275
5,301,028 A	4/1994	Banker et al.	348/570
5,317,391 A	5/1994	Banker et al.	348/6
5,317,695 A	5/1994	Celi, Jr.	395/275
5,327,156 A	7/1994	Masukane et al.	345/113
5,330,370 A	7/1994	Reddersen et al.	439/502
5,347,113 A	9/1994	Reddersen et al.	235/462
5,347,646 A	9/1994	Hirosawa et al.	395/575
5,349,675 A	9/1994	Fitzgerald et al.	395/800
5,357,276 A	10/1994	Banker et al.	348/7
5,357,420 A	10/1994	Gohi	364/131
5,367,571 A	11/1994	Bowen et al.	380/20
5,369,593 A	11/1994	Papamarcos et al.	364/488
5,381,477 A	1/1995	Beyers, II et al.	380/20
5,392,400 A	2/1995	Berkowitz et al.	395/200
5,396,593 A	3/1995	Mori et al.	395/162
5,440,618 A	8/1995	Riegel et al.	379/95
5,440,632 A	8/1995	Bacon et al.	380/20
5,448,697 A	9/1995	Parks et al.	395/162
5,465,105 A	11/1995	Shatas et al.	345/204
5,477,262 A	12/1995	Banker et al.	348/7
5,485,221 A	1/1996	Banker et al.	348/563
5,486,868 A	1/1996	Shyu et al.	348/524
5,486,869 A	1/1996	Cooper	348/525
5,489,947 A	2/1996	Cooper	348/589
5,499,377 A	3/1996	Lee	395/200.01
5,502,499 A	3/1996	Birch et al.	348/523
5,504,522 A	4/1996	Setogawa	348/185
5,519,874 A	5/1996	Yamagishi et al.	395/800
5,524,362 A	6/1996	Quandt et al.	34/526
5,526,024 A	6/1996	Gaglianello et al.	345/185
5,534,942 A	7/1996	Beyers, Jr. et al.	348/569
5,537,548 A	7/1996	Fin et al.	395/200.04
5,539,822 A	7/1996	Lett	380/20
5,542,053 A	7/1996	Bland et al.	395/309
5,577,210 A	11/1996	Abdous et al.	395/200.1
5,579,057 A	11/1996	Banker et al.	348/589
5,579,087 A	11/1996	Salgado	355/202
5,581,303 A	12/1996	Djabbari et al.	348/524
5,583,993 A	12/1996	Foster et al.	395/200.04
5,592,551 A	1/1997	Lett et al.	380/20
5,603,060 A	2/1997	Weinberger et al.	399/8
5,604,509 A	2/1997	Moore et al.	345/2
5,606,604 A	2/1997	Rosenblatt et al.	379/198
5,608,872 A	3/1997	Schwartz et al.	395/200.04
5,613,096 A	3/1997	Danknick	395/500
5,617,547 A	4/1997	Feeney et al.	395/311
5,642,153 A	6/1997	Chaney et al.	348/7
5,657,414 A	8/1997	Lett et al.	386/35
5,664,229 A	9/1997	Bhargava et al.	395/885
5,674,003 A	10/1997	Andersen et al.	364/514
5,689,671 A	11/1997	Strömberg	395/385
5,699,533 A	12/1997	Sakai	395/311
5,701,161 A	12/1997	Williams et al.	348/468
5,708,961 A	1/1998	Hylton et al.	455/4.2
5,715,515 A	2/1998	Akins, III et al.	455/4.1
5,719,622 A	2/1998	Conway	348/211
5,721,842 A	2/1998	Beasley et al.	395/311
5,724,525 A	3/1998	Beyers, II et al.	395/240
5,724,529 A	3/1998	Smith et al.	395/309
5,732,212 A	3/1998	Perholtz et al.	395/200.11
5,734,334 A	3/1998	Hsieh et al.	340/827
5,742,677 A	4/1998	Pinder et al.	380/4
5,752,032 A	5/1998	Keller et al.	395/681
5,758,099 A	5/1998	Grieco et al.	395/282
5,761,447 A	6/1998	Knox et al.	395/281
5,761,448 A	6/1998	Adamson et al.	395/284
5,768,224 A	6/1998	Tanaka et al.	369/33
5,768,568 A	6/1998	Inui et al.	395/500
5,774,859 A	6/1998	Houser et al.	704/275
5,781,748 A	7/1998	Santos et al.	395/308
5,784,702 A	7/1998	Greenstein et al.	711/173
5,799,171 A	8/1998	Kondou	395/500
5,801,789 A	9/1998	Zeidler et al.	348/589
5,835,791 A	11/1998	Goff et al.	395/882
5,864,708 A	1/1999	Croft et al.	395/821
5,884,096 A	3/1999	Beasley et al.	395/858
5,935,224 A	8/1999	Svancarek et al.	710/63
5,937,176 A	8/1999	Beasley et al.	395/311
5,978,389 A	11/1999	Chen	370/538
5,983,085 A *	11/1999	Zamat et al.	455/127.1
6,006,338 A	12/1999	Longsdorf et al.	713/340
6,038,616 A	3/2000	Thornton et al.	710/2
6,040,817 A	3/2000	Sumikawa	345/113
6,044,428 A	3/2000	Rayabhari	710/129
6,098,116 A	8/2000	Nixon et al.	710/8
6,112,264 A	8/2000	Beasley et al.	710/38
6,119,148 A	9/2000	Chen	709/204
6,141,719 A	10/2000	Rafferty et al.	710/131
6,151,645 A	11/2000	Young et al.	710/63
6,160,543 A	12/2000	Chen	345/213
6,162,078 A	12/2000	Chung	439/188
6,215,907 B1	4/2001	Kumar et al.	382/240
6,256,014 B1	7/2001	Thomas et al.	345/163
6,281,457 B1	8/2001	Chang	200/547
D449,608 S	10/2001	Chang	D14/357
6,304,895 B1	10/2001	Schneider et al.	709/203
6,324,605 B1	11/2001	Rafferty et al.	710/100
6,345,323 B1	2/2002	Beasley et al.	710/38
6,378,009 B1	4/2002	Pinkston, II et al.	710/62
6,378,014 B1	4/2002	Shirley	710/100
6,388,658 B1	5/2002	Ahern et al.	345/168

6,539,418	B2	3/2003	Schneider et al.	709/203
6,615,090	B1	9/2003	Blevins et al.	700/26
6,633,905	B1	10/2003	Anderson et al.	709/219
6,671,756	B1	12/2003	Thomas et al.	710/73
6,672,896	B1	1/2004	Li	439/502
6,989,735	B2 *	1/2006	Fisher et al.	370/482
6,995,658	B2 *	2/2006	Tustison et al.	375/219
6,998,963	B2 *	2/2006	Flen et al.	340/870.01
7,015,397	B2 *	3/2006	Clark	174/113 R
2001/0032275	A1 *	10/2001	Watanabe et al.	710/1
2001/0053711	A1	12/2001	Chou	455/575
2002/0004912	A1	1/2002	Fung	713/300
2002/0027496	A1 *	3/2002	Cern et al.	340/310.01
2002/0038334	A1 *	3/2002	Schneider et al.	709/203
2002/0054029	A1	5/2002	Glancy et al.	345/173
2002/0072892	A1	6/2002	Shirley	703/25
2002/0091850	A1	7/2002	Perholtz et al.	709/231
2002/0097220	A1	7/2002	Ferguson et al.	345/156
2002/0116539	A1	8/2002	Bryczkowski et al.	709/317
2002/0124128	A1	9/2002	Qiu	710/302
2002/0143996	A1	10/2002	Odryna et al.	709/246
2002/0193015	A1	12/2002	Milan	439/752.5
2002/0198934	A1	12/2002	Kistler et al.	709/203
2003/0005186	A1	1/2003	Gough	710/8
2003/0035049	A1	2/2003	Dickens et al.	348/100
2003/0037130	A1	2/2003	Rollins	709/223
2003/0051021	A1	3/2003	Hirschfeld et al.	709/223
2003/0131127	A1 *	7/2003	King et al.	709/238
2003/0135654	A1	7/2003	Chang	709/250
2004/0225804	A1 *	11/2004	Leete	710/305
2004/0232768	A1 *	11/2004	Hung et al.	307/3
2005/0017849	A1 *	1/2005	Flen et al.	340/310.01
2005/0055586	A1 *	3/2005	Flen et al.	713/300

FOREIGN PATENT DOCUMENTS

EP	0 174 099	A2	3/1986
EP	0962663	A2	5/1999
EP	0982663	A2	8/1999
GB	2394124	A	4/2004
JP	10-187303		7/1998
WO	WO87/00317		1/1987
WO	WO94/19749		9/1994
WO	WO95/01055		1/1995
WO	WO98/12641		3/1998

OTHER PUBLICATIONS

NTI Product Information Sheet—no date.
 Belkin OmniView Catalog, 1999.
 NTI. Description of Video Switch, Monitor Switch product [online], [retrieved on Dec. 26, 2001], Retrieved from the Internet. <URL://http://www.networktechinc.com/vidswt.html>.
 KVM. Description of KVM Switch product [online], [retrieved on Dec. 26, 2001], Retrieved from the Internet. <URL://http://www.kvm-switches-online.com/index.html>.
 Belkin. Description of KVM OmniView product [online], [retrieved on Oct. 30, 2001], Retrieved from the Internet. <URL://http://www.belkin.com/moreabout/kvm.html>.
 DeKerf, T and Davis, Gary, D., “The Keyboard/Video Switch White Paper: A Close Look at Modern Keyboard/Video Switching”, Tron International Inc. and the Work-Center Corporation, 1995.
 “Sharp: Recording MD Player Due in Early '94”, *HFD the Weekly Home Furnishings Newspaper*, Jul. 1994.
 “Goldstar Unveils 5 Upgrade . . .”, *HFD the Weekly Home Furnishings Newspaper*, vol. 68, No. 10, Mar. 7, 1994.
 “Electron Components: On Screen Display Ics”, NEC Corporation, Apr. 1994.
 “10comm ThinkSync II CM-2131T: Eye-Pleasing Trinitron CRT”, *Windows Sources: The Magazine for Windows Experts*, vol. 1, No. 3, pp. 240-241, 244, Apr. 1993.
 “Genlocking” Tech Note, S3 Incorporated, Sep. 1993.

News Release “MaxiSwitch, Inc. Introduces Industry’s First Software Utility Permitting On-Screen Display of User-Progaid Keyboard Settings”, Tucson, Arizona, Nov. 23, 1992.
 PR Newswire, “Sony Makes Bold Decision Statement with the Launch of the Trinitron XBR2 Line of Computer Televisions”, New York, Oct. 15, 1992.
 “Lotus Brand Portable, Home TVs Bow”, *HFD The Weekly Home Furnishings Newspaper*, vol. 64, No. 28, pp. 106 and 123, Jul. 9, 1990.
 Gosch, J., “Solid-State Captions”, *Electronics*, pp. 36-37, Apr. 1990.
 Levine, J.A., “TV Makers Focus on Upscale Models”, *HFD The Weekly Home Furnishings Newspaper*, Date unknown.
 “MS Left Breathless by Jaunt through Eugene, OR, Video Countryside”, *Consumer Electronics*, vol. 16, No. 4, Apr. 1988.
 CES '87 Consumer Electronics Show: New Products, Jan. 5, 1987.
 “Panasonic VHS VCR Series Features Rounded Contours”, *HFD The Weekly Home Furnishings Newspaper*, pp. 71 and 84, Jan. 5, 1987.
 PR Newswire, “RCA Announces First Video Disc Player with Programmable Capability”, Indianapolis, Aug. 12, 1983.
 Buchsbaum, W., “RCA Model VGM 2023s 25" Color TV Receiver”, *Computers & Electronics*, pp. 104, 106, 107, 109, Feb. 1983.
 Carrell, J.L. and Boyle, P.R., “ONline System Concentrator”, *PC Magazine*, Date unknown.
 MasterNet Networking Software Product Bulletin, “Zero Slot Lan Software Users Sharing Device” and Instant Control of Your Peripherals. Rose Electronics. Date unknown.
 Motorola Semiconductor Technical Data, “Advanced Monitor On-Screen Display CMOS”, Rev. 2, Feb. 1997.
 General Instrument 2750R Satellite Receiver User’s Guide 2700 Series, Publication No. 72089-1, Rev. C, Apr. 1990.
 Rigney, Steve, “J&L’s server room in a box”, *PC Magazine*, May 30, 1995, v. 14, No. 10, p. NE19.
 “Sharp: Recording MD Player Due I Early 94” , *HFD the Weekly Home furnishings Newspaper*, Jun. 1993.
 “Panasonic’s New Video Line Offers More Styling, User-Friendly Features”, *HFD The Weekly Home Furnishings Newspaper*, Jul. 1992. (copy not available).
 Nguyen, Huy, “Key-view unlocks server problems”, *PC Week*, Mar. 27, 1995, v12, pN20.
 “Promoting Camcorder”, Camcorder mfrs & retailers try creative promotions to reduce heavy inventories, Jul. 20, 1992.
 Article: Belkin Launches New Generation of OmniCube™ SVM Switches Oct. 25, 2001.
 Article: Network Technologies “White Paper KVM Switch Solutions” Mar. 1, 2001.
 European Search Report; dated Jul. 14, 2006; 3 pages.
Hartcomm.org White Papers; HCF - Technical - White Papers - white_papers.html; 1 page.
 Helson, Ron; *The Impact of HART on Process Automation, The Compelling Case for the World’s Most Used Digital Communications Protocol*; Jun. 1, 2004; 3 pages.
 Helson, Ron; *HART Communication: Driving New Product Developments*; Mar. 1, 2004; 11 pages.
The HART® Protocol - a Solution Enabling Technology; Feb. 1, 2004; 5 pages.
Time to Tap Into HART, Seize the Data. There Are Major Asset Management and Process Improvement Gains to Be Realized With HART; Nov. 1, 2003; 3 pages.
 Helson, Ron; *Preventing Process Disruptions, The Solution Could Be in Your Smart Instruments*; Aug. 1, 2002; 4 pages.
 Pratt, Wally; *HART Networks*; Apr. 1, 2002; 32 pages.
 Pratt, Wally; *Evaluating Fieldbus Networks: Choose the Right Tool for the Job, i.e. Sorting Out The Protocols: Network Soup*; Jan. 1, 2002; 17 pages.
Be As Smart As Your Instruments, Getting More from HART Communications; Apr. 1, 2001; 1 page.
 Helson, Ron; *Understanding the Power of HART Communication*; Mar. 1, 2003; 3 pages.
 Adler, Bud; *Continuous HART Communication Increases Safety Integrity Level (SIL)*; Dec. 1, 2000; 3 pages.

List of Articles Regarding Hart Communications; HCF - News-main - articles.html; 2 pages.

Preventing Process Disruptions, The Solution Could Be in Your Smart Instruments; 2002; HCF - Newsmain - Articles - 2002 - Preventing Process Disr Article - prevprocdis.html; 3 pages.

Detroit Water & Sewerage Department Wins Award; Dec. 2003; Valve World Magazine; HCF - Newsmain - Articles - 2003 - valve world - valve_world.html; 3 pages.

Helson, Ron; *You've Got the Power*; 2002; Power of HART Control Magazine Supplement; HCF - Newsmain - Articles - 2002 - Control Suppl 2002 - controlmain1102.html; 1 page.

Leverage Your Assets; 2002; Power of HART Control Magazine Supplement; HCF - Newsmain - Articles - 2002 - Control Suppl 2002 - firstarticle1102.html; 4 pages.

Unleash the Power of HART; 2002; Power of HART Control Magazine Supplement; HCF - Newsmain - Articles - 2002 - Control Suppl 2002 - secondarticle.html; 2 pages.

Powerful Connections; 2002; Power of HART Control Magazine Supplement; HCF - Newsmain - Articles - 2002 - Control Suppl - thirdarticle.html; 2 pages.

HART Plant of the Year; 2002; Power of HART Control Magazine Supplement; HCF - Newsmain - Articles - 2002 - Control Suppl 2002 - splantoftheyear1102.html; 2 pages.

Contents; 2001; Power of HART Control Magazine; HCF - Newsmain - Articles - 2001 - Control Suppl -control2001.html; 2 pages.

Get Started; 2001; Power of HART Control Magazine Supplement; 2 pages.

Put it to Work; 2001; Power of HART Control Magazine Supplement; 6 pages.

Hidden in HART; 2001; Power of HART Control Magazine Supplement; 5 pages.

Helson, Ron; *Get Connected*; 2003; Control Magazine Supplement; HCF - Newsmain - Articles - 2003 - Control2003 - controlmain1103.html; 1 page.

Platform for the Future; 2003; Control Magazine Supplement; HCF - Newsmain - Articles - 2003 - Control Suppl - Platform - platform.html; 3 pages.

HART Capabilities Provide Fundamental Value; 2003; Control Magazine Supplement; 2 pages.

Time to Tap Into HART; 2003; Control Magazine Supplement; HCF - Newsmain - Articles - 2003 - Control Suppl - Time to tap - time_to tap.html; 2 pages.

HART Plant of the Year; 2003; Control Magazine Supplement; HCF - Newsmain - Articles - 2003 - Control Suppl - Plant of the Year - plant_of the_year.html; 3 pages.

Helson, Ron; *Use the Power of HART*; 2001; Power of HART Control Magazine Supplement; 1 page.

Call for Information; 2001; Power of HART Control Magazine Supplement; 4 pages.

* cited by examiner





FIG. 1






FIG. 3





FIG. 4

FIG. 5






FIG. 6




FIG.7




FIG. 8




FIG. 9




FIG. 10




FIG.11





FIG.12



551

FIG.13





FIG.14



1

**DISTANCE EXTENDER AND METHOD
MAKING USE OF SAME**

FIELD OF THE INVENTION

This invention relates generally to electrical signal transmission in electronic systems, and relates more particularly to keyboard, video, and mouse extenders.

BACKGROUND OF THE INVENTION

Electronic systems, such as computer systems, rely for proper operation on the transmission of electronic signals among the various components of the system. In a computer system, for example, electronic signals must be transmitted from the computer to a keyboard, a video monitor, a mouse, and any other peripheral electronic devices coupled to the computer. The acronym KVM will be used herein to mean "keyboard, video monitor, and mouse," following a practice that is standard in the art. Additionally, the phrase "peripheral device" will be used herein to mean any electronic device coupled to a computer or forming a part of any electronic system, including a keyboard, a video monitor, and a mouse.

Under certain circumstances it may be desirable to place the computer in one location and to place the peripheral devices in another location separated from the computer's location by a certain distance. An example of such a circumstance is where the computer must be in an environment, perhaps a particular room in a building, where parameters such as access, temperature, humidity, and the like are carefully controlled but where the peripheral devices may be located in an environment, perhaps another room in the building, where control over such parameters is less critical. Another example of such a circumstance is where a single keyboard, video monitor, and mouse, referred to collectively herein as an "operator control center" or an "OCC," are adapted to control several computers, where the several computers may be located at a distance from the operator control center.

KVM extenders have been developed in order to increase the distance by which an operator control center can be separated from a computer. Existing KVM extenders include a local subsystem, a remote subsystem, and a cable coupled between the local and remote subsystems. The local subsystem is coupled to a computer and/or, if applicable, to a KVM Switch that switches control from one to another of several computers being controlled by an operator control center. The remote subsystem is coupled to the OCC. Electronic signals may be transmitted between the computer and the OCC across the cable via the local and remote subsystems.

Both the local and remote subsystems of existing KVM extenders require the use of power supplies, alternating current (AC) adapters, or the like to provide power to the subsystems. Such power supplies, AC adapters, and the like are bulky and take up a significant amount of space. In many environments, such as in a server rack or in an environmentally controlled room, space is at a premium, and the presence of a power supply or an AC adapter is an inefficient use of that space. Accordingly, there exists a need for a KVM extender providing all of the functionality of existing KVM extenders but that does not require a separate power supply or AC adapter.

2

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be better understood from a reading of the following detailed description, taken in conjunction with the accompanying figures in the drawings in which:

FIG. 1 is a block diagram of a distance extender, according to an embodiment of the invention, shown as part of an electronic system;

FIG. 2 is a block diagram of a distance extender, according to another embodiment of the invention, shown as part of a different electronic system arranged in a first configuration;

FIG. 3 is a block diagram of the distance extender of FIG. 2 shown as part of the electronic system of FIG. 2 arranged in a second configuration;

FIG. 4 is a block diagram of the distance extender of FIG. 2 shown as part of the electronic system of FIG. 2 arranged in a third configuration;

FIG. 5 is a block diagram of a subsystem of the distance extenders of FIGS. 1 and 2, according to an embodiment of the invention;

FIG. 6 is a block diagram of a different subsystem of the distance extenders of FIGS. 1 and 2, according to an embodiment of the invention;

FIG. 7 is a circuit diagram of a modulation/demodulation circuit according to an embodiment of the invention;

FIG. 8 is a graph of an amplitude-modulated signal of the type produced by the modulation/demodulation circuit of FIG. 7 according to an embodiment of the invention;

FIG. 9 is a graph of an amplitude-modulated signal of the type shown in FIG. 8 riding on a boosted electrical voltage signal according to an embodiment of the invention;

FIG. 10 is a graph showing a recovered signal after being modulated and demodulated according to an embodiment of the invention;

FIG. 11 is a circuit diagram illustrating a portion of the modulation/demodulation circuit of FIG. 7 and a filter circuit according to an embodiment of the invention;

FIG. 12 is a circuit diagram illustrating a detection circuit according to an embodiment of the invention;

FIG. 13 is a circuit diagram illustrating a pre-emphasis circuit according to an embodiment of the invention;

FIG. 14 is a circuit diagram illustrating an attenuation/compensation circuit according to an embodiment of the invention; and

FIG. 15 is a flow chart illustrating a method for increasing a distance between a computer and an operator control center in electrical communication with the computer.

For simplicity and clarity of illustration, the drawing figures illustrate the general manner of construction, and descriptions and details of well-known features and techniques may be omitted to avoid unnecessarily obscuring the invention. Additionally, elements in the drawing figures are not necessarily drawn to scale. For example, the dimensions of some of the elements in the figures may be exaggerated relative to other elements to help improve understanding of embodiments of the present invention. The same reference numerals in different figures denote the same elements.

The terms "first," "second," "third," "fourth," and the like in the description and in the claims, if any, are used for distinguishing between similar elements and not necessarily for describing a particular sequential or chronological order. It is to be understood that the terms so used are interchangeable under appropriate circumstances such that the embodiments of the invention described herein are, for example, capable of operation in sequences other than those illustrated or otherwise described herein. Furthermore, the terms "com-

prise,” “include,” “have,” and any variations thereof, are intended to cover a non-exclusive inclusion, such that a process, method, article, or apparatus that comprises a list of elements is not necessarily limited to those elements, but may include other elements not expressly listed or inherent to such process, method, article, or apparatus.

The terms “left,” “right,” “front,” “back,” “top,” “bottom,” “over,” “under,” and the like in the description and in the claims, if any, are used for descriptive purposes and not necessarily for describing permanent relative positions. It is to be understood that the terms so used are interchangeable under appropriate circumstances such that the embodiments of the invention described herein are, for example, capable of operation in other orientations than those illustrated or otherwise described herein. The term “coupled,” as used herein, is defined as directly or indirectly connected in an electrical, mechanical, or other manner.

DETAILED DESCRIPTION OF THE DRAWINGS

In one embodiment of the invention, a distance extender for increasing a distance between a first device and a second device in electrical communication with the first device comprises an electrical cable electrically coupled between the first device and the second device, a first subsystem electrically coupled to the first end of the electrical cable, and a second subsystem electrically coupled to the second end of the electrical cable. The electrical cable comprises a first end, a second end, and a plurality of wires extending between the first end and the second end. The plurality of wires includes a first wire, the first device generates a data signal and provides an electrical power signal, and the data signal and the electrical power signal are simultaneously transmitted between the first device and the second device over the first wire.

FIG. 1 is a block diagram of a distance extender 100, according to an embodiment of the invention, shown as part of an electronic system 101. As illustrated in FIG. 1, distance extender 100 comprises a subsystem 110, a subsystem 120, and an electrical cable 130 electrically coupled between subsystems 110 and 120.

As an example, distance extender 100 can be used to increase a distance between a device 145 and a device 150, where device 150 is in electrical communication with device 145. Subsystem 110 and/or subsystem 120 can comprise a stand-alone box, module, or the like, or subsystem 110 and/or subsystem 120 can comprise firmware implemented within a portion of device 145, device 150, and/or another component of distance extender 100. Electrical cable 130 has an end 131 and an end 132 opposite end 131. Subsystem 110 is electrically coupled to end 131 of electrical cable 130, and subsystem 120 is electrically coupled to end 132 of electrical cable 130. Electrical cable 130 further comprises a plurality of wires, including a first wire, extending between end 131 and end 132.

As will be understood by one having ordinary skill in the art, electrical cable 130 further comprises at least a ground return wire. In at least one embodiment, the first wire is one of a pair of wires, collectively referred to as a first wire pair, and the data signal and the electrical power signal are simultaneously transmitted between device 145 and device 150 over the first wire pair, in the sense that the electrical power signal and either the positive or negative portion of a differential data signal can be transmitted on the first wire, while the other wire in the first wire pair carries the ground return signal as well as the portion of the differential data signal not sent on the first wire.

It will be understood by one of ordinary skill in the art that the data signal is bi-directional, meaning it travels along electrical cable 130 both from device 145 to device 150 as well as from device 150 to device 145. In an embodiment where device 150 is an OCC and device 145 is a computer, the data signal will most often be generated by device 150 and then travel across electrical cable 130 to device 145.

Because the electrical power signal is transmitted, as described, across the first wire pair of electrical cable 130, the separate AC adapters or external power supplies required by existing KVM extenders, as well as the circuitry required to support the AC adapters or external power supplies, are not needed in distance extender 100, and are therefore absent from distance extender 100. For a variety of reasons, the absence of AC adapters and external power supplies can be a significant advantage. As an example, AC adapters typically take up as much as two or three cubic inches. The outlets or power strips to which the AC adapters must be coupled also require relatively large amounts of space. Especially in an environment where multiple KVM extenders are present, such as in a server rack or server room, the space required by the AC adapters and the outlets or power strips can often exceed the space available. Another advantage of the absence of AC adapters and external power supplies is that any concern as to whether an AC adapter will fall out of a wall outlet, power strip, or other electrical outlet may be eliminated. Yet another advantage is that there is no need to take time to physically plug such AC adapters in to an electrical outlet.

In a particular embodiment, electrical cable 130 comprises a plurality of unshielded, twisted wire pairs, one of which is the first wire pair described above. As an example, electrical cable 130 can be a Category 5 (CAT 5) cable, a Category 5e (CAT 5e) cable, a Category 6 (CAT 6) cable, a Category 7 (CAT 7) cable, or the like, collectively referred to herein as Category 5-type cable, each of which comprise four unshielded, twisted wire pairs. CAT 5 cable is a relatively inexpensive cable that is well suited for electrical signal transmission. The other existing cable types referred to above were developed to extend the bandwidth and function of the original CAT 5 specification. In at least one embodiment where electrical cable 130 is a CAT 5 cable, the data signal and the electrical power signal are simultaneously transmitted across the first wire pair, and red, green, and blue color analog signals are transmitted across the other three wire pairs.

As further illustrated in FIG. 1, electrical cable 130 is electrically coupled between device 145 and device 150. Device 145 and/or device 150 generate data signal, and device 145 generates an electrical power signal, and the bi-directional data signal and the electrical power signal are simultaneously transmitted between device 145 and device 150 over the first wire. As an example, the data signal can comprise at least one of mouse data and keyboard data. As another example, device 145 can be a computer, and device 150 can be an OCC comprising a keyboard 151, a video monitor 152, and a mouse 153.

In at least one embodiment, subsystem 110, subsystem 120, keyboard 151, and mouse 153 are powered only by the electrical power signal. As an example, in an embodiment where device 145 is a computer, the electrical power signal can be taken from the positive (+) 5 volt (V) supply pins on the computer ports, such as the PS/2 ports, to which a keyboard or a mouse are normally connected. The simultaneous transmission of the electrical power signal and the data signal between device 145 and device 150 across the first wire pair will be discussed in more detail below. It will

5

be understood by one of ordinary skill in the art that at least a portion of device 150, such as, for example, video monitor 152, may require its own power supply when used in connection with distance extender 100, but any portion so requiring its own power supply is one that would also require its own power when used apart from distance extender 100.

FIG. 2 is a block diagram of a distance extender 200, according to an embodiment of the invention, shown as part of an electronic system 201 arranged in a first configuration. As illustrated in FIG. 2, distance extender 200 comprises a subsystem 210, a subsystem 220, and an electrical cable 230 electrically coupled between subsystems 210 and 220. As an example, subsystem 210, subsystem 220, and electrical cable 230 can be similar to subsystem 110, subsystem 120, and electrical cable 130, respectively, each of which were first shown in FIG. 1. Electrical cable 230 can comprise a plurality of wires, including a first wire, extending between end 231 and end 232. Distance extender 200 further comprises a switch 240 electrically coupled between device 150 and device 145 as well as a device 245. As an example, device 245 can be similar to device 145, first shown in FIG. 1. Additional devices, all of which can also be similar to device 145, can also form a part of electronic system 201, and can also be electrically coupled to switch 240, depending on the configuration and capacity of switch 240. As an example, switch 240 can be a KVM Switch. As another example, distance extender 200 can function in a manner similar to the function of distance extender 100 (FIG. 1).

Switch 240 can be used to selectively route electrical signals to device 150 from one of devices 145, 245, or other device electrically coupled to switch 240, thus enabling any of devices 145, 245, or other device electrically coupled to switch 240 to be controlled from device 150. As an example, in an embodiment where switch 240 is a KVM Switch, device 150 is an OCC, and devices 145 and 245 are computers, switch 240 routes video signals of the selected computer to the video monitor 152 of the OCC so that a user may view the video signals of the selected computer from the OCC. Switch 240 also routes keyboard and mouse signals from the OCC to the respective ports of the selected computer. By using switch 240 in this fashion, the selected computer can be operated from the OCC just as if the OCC's keyboard and mouse were directly attached to the selected computer.

The need to extend a distance separating various components of electronic systems has been mentioned above. FIG. 1 illustrated the use of distance extender 100 to extend a distance separating device 145 from device 150, and, accordingly, subsystem 110 is electrically coupled to device 145 and subsystem 120 is electrically coupled to device 150. In an embodiment where device 145 is a computer and device 150 is an OCC, increasing a distance by which devices 145 and 150 are separated allows a situation in which the computer (device 145) can be located in a room where the environment is carefully controlled while the OCC (device 150) can be located in another room that can be made more comfortable for the user of the OCC. FIG. 2 illustrates a slightly different configuration in which distance extender 200 is used to increase a distance separating device 150 from switch 240, wherein subsystem 210 is electrically coupled to switch 240 and subsystem 220 is electrically coupled to device 150. Such a configuration permits switch 240 and device 150 to be located, for example, in different rooms, yielding a result similar to that described in connection with FIG. 1. Additional configurations are also possible, and desirable, as illustrated below.

6

FIG. 3 is a block diagram of distance extender 200 shown as part of electronic system 201 arranged in a second configuration. FIG. 3 illustrates one of the possible additional configurations mentioned above, in which distance extender 200 is used to increase a distance separating device 145 from switch 240. In the configuration of FIG. 3, subsystem 210 is electrically coupled to device 145, and subsystem 220 is electrically coupled to switch 240. Such a configuration permits switch 240 and device 150 to be located, for example, in different rooms. In an embodiment where device 145 is a computer, such a configuration may be desirable where the available space within, or the environment of, the room or other location in which switch 240 is located is not sufficient or suitable for the computer (device 145), or vice versa. In one embodiment, not illustrated in FIG. 3, a distance by which device 245 is separated from switch 240 can also be extended, using a second distance extender, where the second distance extender is the same or substantially similar to distance extender 200.

FIG. 4 is a block diagram of distance extender 200 shown as part of electronic system 201 arranged in a third configuration. FIG. 4 illustrates another one of the possible additional configurations mentioned above, in which distance extenders according to embodiments of the invention are used to increase both a distance separating device 145 from switch 240 and a distance separating device 150 from switch 240. As illustrated in FIG. 4, distance extender 200 is used to extend a distance separating device 150 from switch 240, such that subsystem 210 is electrically coupled to switch 240, and subsystem 220 is electrically coupled to device 150. A distance extender 400 is used to extend a distance separating device 145 from switch 240. Electrical cable 430 can comprise a plurality of wires, including a first wire, extending between end 431 and end 432. Distance extender 400 comprises a subsystem 410, a subsystem 420, and an electrical cable 430. As an example, subsystem 410, subsystem 420, and electrical cable 430 can be similar to subsystem 110, subsystem 120, and electrical cable 130, respectively, each of which were first shown in FIG. 1. Subsystem 410 is electrically coupled to device 145, and subsystem 420 is electrically coupled to switch 240.

The configuration of FIG. 4 permits switch 240, device 145, and device 150 to each be located, for example, in different rooms. In an embodiment where device 145 is a computer and device 150 is an OCC, such a configuration may be desirable where the available space within, or the environment of, the room or other location in which switch 240 is located is not sufficient or suitable for the computer (device 145), and/or for the OCC (device 150), or vice versa. In one embodiment, not illustrated in FIG. 4, a distance by which device 245 is separated from switch 240 can also be extended, using an additional distance extender, where the additional distance extender is the same or substantially similar to distance extender 200.

FIG. 5 is a block diagram of subsystem 110 of distance extender 100 (FIG. 1), according to an embodiment of the invention. As stated above, in at least one embodiment, subsystem 210 of distance extender 200, both of which were first shown in FIG. 2, and subsystem 410 of distance extender 400, both of which were first shown in FIG. 4, can be the same or substantially similar to subsystem 110. As illustrated in FIG. 5, subsystem 110 comprises a voltage boost circuit 510, a modulation/demodulation circuit 520, a filter circuit 530, a detection circuit 540, and a pre-emphasis circuit 551. Circuits 520, 530, 540, and 551 will each be described in more detail below.

The following description assumes an embodiment where device **150** is a computer. Subsystem **110** receives the data signal and a clock signal through an input header **560**. The data and clock signals are routed directly to a microprocessor **565** where they are multiplexed and coded before being transmitted to modulation/demodulation circuit **520** via an internal Universal Asynchronous Receiver Transmitter (UART) **567**.

Power for the circuitry of subsystem **110** is taken from the +5V supply pins on the PS2 ports of the computer. Electrical power signals enter subsystem **110** through input header **560** and are passed to voltage boost circuit **510** and to a local power supply **515**. Local power supply **515** supplies five volts or another voltage to the circuitry of subsystem **110**. Voltage boost circuit **510** boosts the incoming voltage from 5V to a higher voltage in order to overcome and/or compensate for losses, such as IR losses, in electrical cable **130** (FIGS. **1**) during the transmission of the electrical power signal across electrical cable **130**. As an example, voltage boost circuit **510** can boost the incoming voltage to 30V. The electrical power signal, with boosted voltage, is passed to filter circuit **530**, where it will be combined with the coded data signal as described below.

As illustrated in FIG. **5**, input header **560** also receives video signals, comprising red, green, and blue video signals, and synchronization signals (sync signals) in addition to receiving data, clock, and electrical power signals. The sync signals are mixed, or multiplexed, into the video signals, and the resulting combined signals (comprising video signals and sync signals) are amplified by a video amplifier **550**, passed into end **131** of electrical cable **130** (FIGS. **1**) and transmitted differentially along electrical cable **130**. In one embodiment, the sync signals are mixed into the red and blue video signals only, amplified, and differentially transmitted. In the same or another embodiment, connector **131** is an RJ45 connector. Pre-emphasis circuit **551**, in at least one embodiment, forms a part of video amplifier **550**. Pre-emphasis circuit **551** pre-emphasizes, or increases, the high-frequency portion of the video signals before the video signals are transmitted across electrical cable **130** because higher frequency video signals are attenuated during such transmission to a greater extent than are lower frequency signals. Pre-emphasizing the high-frequency portion of the video signals in this way makes it easier to recover those signals after they have arrived at subsystem **120** (FIG. **1**).

After passing through microprocessor **565** and UART **567**, the data signal is passed to modulation/demodulation circuit **520** where it is modulated. The data signal is then coupled onto the boosted voltage at filter circuit **530**. The combined signal, comprising: (1) the power signal with the boosted electrical voltage signal; and (2) the data signal, is then sent to filter circuit **530** and then to end **131** of electrical cable **130** (FIGS. **1**) before being sent across electrical cable **130**. Filter circuit **530** prevents the data signal from interfering with power supply **515**, as will be discussed in more detail below.

FIG. **6** is a block diagram of subsystem **120** of distance extender **100** (FIG. **1**), according to an embodiment of the invention. As stated above, in at least one embodiment, subsystem **220** of distance extender **200**, both of which were first shown in FIG. **2**, and subsystem **420** of distance extender **400**, both of which were first shown in FIG. **4**, can be the same or substantially similar to subsystem **120**.

As illustrated in FIG. **6**, subsystem **120** comprises a voltage conversion circuit **610**, a modulation/demodulation circuit **620**, a filter circuit **630**, and an attenuation compensation circuit **651**. A power supply **615** supplies power for

the circuitry of subsystem **120**. As an example, modulation/demodulation circuit **620** can be similar to modulation/demodulation circuit **520** (FIG. **5**), and filter circuit **630** can be similar to filter circuit **530** (FIG. **5**). Circuit **651** will be described in more detail below. Circuits **620** and **630** will not be separately described because of their similarity to circuits **520** and **530**, respectively.

As further illustrated in FIG. **6**, multiplexed differential video and sync signals are received through end **132**, which can be an RJ45 connector, of electrical cable **130** (FIGS. **1-4**) and passed to a video amplifier **650**. In one embodiment, differential-to-single-ended amplifiers within video amplifier **650** receive the multiplexed differential video and sync signals. In an embodiment where the sync signals are mixed into the red and blue video signals, the red and blue video signals are routed to a sync stripper circuit **670** and a sync detection and polarization circuit **690** before being sent to a connector **680**. Sync detection and polarization circuit **690** recovers the sync polarity from the original video signals, and the polarity-corrected sync signals are sent to connector **680**. As an example, connector **680** can be an HDDB15 connector. Referring still to the embodiment where the sync signals are mixed onto the red and blue video signals, the green video is routed directly from the differential-to-single-ended amplifiers to connector **680**.

Subsystem **120** also receives the combined signal through end **132** and passes the combined signal through filter circuit **630** to voltage conversion circuit **610** and modulation/demodulation circuit **620**. Filter circuit **630** prevents the modulated data signal from interfering with the circuitry of power supply **615**. Voltage conversion circuit **610** converts the boosted voltage to a lower voltage, which in at least one embodiment can be 5V, which lower voltage is passed to power supply **615** and used to power the circuitry of subsystem **120**.

Modulation/demodulation circuit **620** demodulates the data signal. The demodulated data signal is then sent to a UART **667** on microprocessor **665** where the demodulated data signal is separated into keyboard and mouse data signals and sent to the appropriate one of ports **695**. As an example, ports **695** can be PS/2 ports, one of which can receive a keyboard and the other of which can receive a mouse.

FIG. **7** is a circuit diagram of modulation/demodulation circuit **520** according to an embodiment of the invention. FIG. **8** is a graph **800** of an amplitude-modulated signal of the type produced by modulation/demodulation circuit **520** according to an embodiment of the invention. FIG. **9** is a graph **900** of an amplitude-modulated signal of the type shown in FIG. **8** riding on a boosted electrical voltage signal according to an embodiment of the invention. FIG. **10** is a graph **1000** showing a recovered signal after being modulated and demodulated according to an embodiment of the invention.

As discussed earlier in connection with FIG. **5**, the data signal is routed from input header **560** to microprocessor **565**, where the data signal is multiplexed and coded prior to being sent to modulation/demodulation circuit **520**. The coded data signal is then transmitted by data UART **567** to modulation/demodulation circuit **520**. As illustrated in FIG. **7**, the data signal enters modulation/demodulation circuit **520** on a line **701**, and is labeled "data_from_controller." The data line is a single-ended square wave 0 to 5V signal. A logic "1" is indicated by a 5 volt direct current (DC) level and a logic "0" is indicated by a 0 volt DC level. This signal is inverted and applied to pin **3** of a transceiver **710**, which in the illustrated embodiment is an RS485 transceiver. Pin **3**

of transceiver 710 is an enable pin. A one megahertz (MHz) signal is applied to the data input of transceiver 710. Whenever pin 3 of transceiver 710 is high the one MHz signal is passed through transceiver 710 to the differential outputs present on pin 6 and pin 7 of transceiver 710. The resultant waveform on pin 6 of transceiver 710 is an amplitude-modulated signal of the type shown in FIG. 8. Since the output of transceiver 710 is a differential signal, the same signal is present on pin 7 of transceiver 710, except that the signal on pin 7 of transceiver 710 is 180 degrees out of phase with the signal on pin 6 of transceiver 710.

A 110 ohm resistor, R35, loads the differential signals present at pins 6 and 7 of transceiver 710. Resistors R32, R33, R37, and R38 bias pins 6 and 7 of transceiver 710 so that the steady state level of pin 1 of transceiver 710 is a logical "0." The signals present at pins 6 and 7 of transceiver 710 are AC coupled through capacitors C33 and C35 to connector pins 7 and 8 of end 131, which is illustrated as an RJ45 connector in FIG. 7. Resistors R51 and R54 and capacitors C33 and C35 are used to match the differential signal to the impedance of electrical cable 130 (FIGS. 1-4) and to the receiver input impedance.

As illustrated in FIG. 8, graph 800 comprises a channel 810 and a channel 820. Channel 810 represents data input on line 701 (FIG. 7) of modulation/demodulation circuit 520 (FIGS. 5 and 7). Channel 820 represents an amplitude-modulated signal such as may be present on pin 6 or pin 7 of transceiver 710.

FIG. 9, in graph 900, illustrates a modulated data signal of the type produced by modulation/demodulation circuit 520 riding on an electrical power signal having a boosted voltage produced by voltage boost circuit 510 (FIG. 5). Graph 900 comprises a channel 910 and a channel 920. Channel 910 represents data input on line 701 (FIG. 7) of modulation/demodulation circuit 520 (FIGS. 5 and 7). Channel 920 represents modulated data riding on an electrical power signal having a boosted voltage of 30 volts. As described above, the modulated data signal and the boosted electrical voltage signal are simultaneously carried on a single wire pair in electrical cable 130 (FIG. 1). As an example, pins 7 and 8 of end 131, shown in FIG. 7, correspond to the two wires of the single wire pair on which the combined signal is carried. In a CAT 5 cable, the two wires form a twisted wire pair, as mentioned above.

To demodulate the data signal, the modulated differential signal is received at pins 6 and 7 of transceiver 710. Transceiver 710 converts this signal to a single-ended output on pin 1 of transceiver 710. An example of the type of single-ended output that may be on pin 1 of transceiver 710 is illustrated in a graph 1000 of FIG. 10. Referring still to FIG. 7, the single-ended output is demodulated using a diode D3, a capacitor C34, and a resistor R34. The signal is inverted and then input to data UART 567 of microprocessor 565.

Referring again to FIG. 10, graph 1000 comprises a channel 1010 and a channel 1020. Channel 1010 represents a modulated data signal such as may be received on pin 1 of transceiver 710. Channel 1020 represents a recovered signal present at an output of a buffer 720, which buffer is labeled "Data_Input_To_Controller" in FIG. 7.

FIG. 11 is a circuit diagram illustrating a portion of modulation/demodulation circuit 520 and a filter circuit 530 according to an embodiment of the invention. Filter circuit 530 prevents the one MHz signal (first discussed in connection with FIG. 7) from interfering with power supply 515 and the circuitry of subsystem 110. As illustrated in FIG. 11, the data signal is coupled onto the connector pins 7 and 8 of

end 131 through capacitors C33 and C35. The data signal is blocked from the power of power supply 515 and from the ground signals by inductors L4, L2, L3, and L1, and by a capacitor C46. In the embodiment illustrated in FIG. 11, the modulated data signal is riding on the boosted voltage power line, and on the ground line, but is prevented from back-feeding into power supply 515 by filter circuit 530. As discussed above, filter circuit 630 (FIG. 6) of subsystem 120 is the same or substantially similar to filter circuit 530. Accordingly, the data signal can be transmitted bi-directionally down a single twisted pair of a CAT5 cable or other electrical cable 130 (FIGS. 1) and the DC voltage can be delivered to subsystem 120 on the same twisted pair without interfering with the circuitry of subsystem 110 or subsystem 120.

FIG. 12 is a circuit diagram illustrating detection circuit 540. A portion 1210 of detection circuit 540 is located on subsystem 110, and a portion 1220 of detection circuit 540 is located on subsystem 120. Subsystem 110 only applies the 5V DC "logic '1'" signal to pin 7 of end 131 until it is determined that subsystem 120 is connected. When it has been determined that subsystem 120 unit is connected, subsystem 110 enables voltage boost circuit 510 which supplies boosted voltage to pin 7 of end 131 (FIG. 1) which in FIG. 12 is illustrated as an RJ45 connector. The detection mechanism of detection circuit 540 comprises a simple circuit to designed to detect that a correct load is attached to the wire pair carrying the combined data and power signal. As illustrated in FIG. 12, 5V DC is applied through a diode D1 and a resistor R59 to pin 7 of the RJ45 connector. With subsystem 120 connected via electrical cable 130 (FIGS. 1-4), resistors R59 and R62 form a voltage divider to ground. With a transistor Q2 turned on by the "CNTR_5V_32V_SELECT" signal, a transistor Q1 passes the voltage at the node of resistors R59 and R62 to the ADC input pin on microprocessor 665 (FIG. 6) of subsystem 120. Microprocessor 665 samples this voltage and, if it is within a predetermined range, transistor Q2 is turned off and the boosted voltage will be applied to pin 7 of the RJ45 connector. On the other hand, if subsystem 120 is not connected to subsystem 110, or if subsystem 110 is connected to a network device, such as a hub, a switch, a router, or the like, the voltage at the node of resistors R59 and R62 will not be in the predetermined acceptable range, and the boosted voltage will not be enabled.

FIG. 13 is a circuit diagram illustrating pre-emphasis circuit 551, which is designed to emphasize the high frequency component of the video signals, before such signals are transmitted, in anticipation of the high frequency attenuation that occurs over long lengths of electrical cable 130 (FIG. 1). As illustrated in FIG. 13, capacitors C51 and C52 and resistors R69 and R70 are switched into the feedback legs of a differential driver U6 by a transistor Q6 and Q7, respectively. Capacitors C51 and C52 and resistors R69 and R70 give a low impedance feedback path for high frequencies, thus peaking the gain of the high frequency components in the amplifier. A switch on subsystem 120 ultimately controls transistor Q6. The switch is read by microprocessor 665 of subsystem 120, and the status of the switch is transmitted back to subsystem 110 over wire pair carrying the combined data and power signal. Capacitors C17 and C27 and resistors R63 and R64 are also used to adjust the amplifier frequency response.

FIG. 14 is a circuit diagram illustrating attenuation/compensation circuit 651. As was first discussed above in connection with FIG. 6, subsystem 120 accepts the differential video signals from subsystem 110, amplifies the video

signals, and outputs a single-ended video signal to connector **680** (FIG. 6). As the length of electrical cable **130** (FIGS. 1) increases, the higher frequency components of the video signals are increasingly more attenuated during their transmission along electrical cable **130**, as discussed above. To compensate for the loss of amplitude, a series resistor and capacitor are placed in parallel with a gain resistor **R20** of the differential-to-signal-ended amplifier that forms a part of video amplifier **650** (FIG. 6). In this way, various compensation legs can be switched into the feedback path. A resistor **R61** and a capacitor **C48**, a resistor **R60** and a capacitor **C47**, and a resistor **R59** and a capacitor **C46** respectively form the three resistor-capacitor (RC) pairs.

A microprocessor control signal enables or disables one RC pair at a time depending on a user control switch read by microprocessor **665**. These capacitors and resistors give a low impedance feedback path for high frequencies, thus peaking the gain of the high frequency components in the amplifier. The range of frequencies that are peaked and the final gain is dependent on the RC pair that is switched in parallel with gain resistor **R20**. In this way compensation for attenuation of high frequencies in electrical cable **130** (FIGS. 1-4) is accomplished for varying lengths of electrical cable **130**.

FIG. 15 is a flow chart illustrating a method **1500** for increasing a distance between a computer and an operator control center in electrical communication with the computer, where the electrical communication is accomplished via a cable having a first wire pair and a second wire pair. A step **1510** of method **1500** is to provide a first subsystem to be coupled to a first end of the cable. As an example, the cable can be similar to electrical cable **130**, the computer can be similar to device **145**, and the operator control center can be similar to device **150**, all of which were first shown in FIG. 1. As a further example, the first subsystem can be similar to subsystem **110**, also first shown in FIG. 1.

A step **1520** of method **1500** is to provide a second subsystem to be coupled to a second end of the cable such that an electrical power signal provided by the computer and a data signal generated by the computer or the operator control center are transmitted simultaneously across the first wire pair between the computer and the operator control center. As an example, the second subsystem can be similar to subsystem **120**, first shown in FIG. 1.

A step **1530** of method **1500** is to modulate the data signal to create a modulated data signal. As an example, the modulated data signal can be similar to the signal shown on channel **820** in FIG. 8. As an example, the modulated data signal can be created using modulation/demodulation circuit **520**, first shown in FIG. 5, or modulation/demodulation circuit **620**, first shown in FIG. 6.

A step **1540** of method **1500** is to modify the electrical power signal to create a boosted electrical voltage signal. As an example, the boosted electrical voltage signal can be created using voltage boost circuit **510**.

A step **1550** of method **1500** is to couple the modulated data signal onto the boosted electrical power voltage to create a combined signal. As an example, the combined signal can be similar to the signal shown on channel **920** in FIG. 9.

A step **1560** of method **1500** is to transmit the combined signal across the first wire pair between the computer and the operator control center. In one embodiment, step **1530** or another step can further comprise using the computer to generate a video signal, and step **1560** or another step can further comprise transmitting the video signal across the second wire pair between the computer and the operator

control center. In the same or another embodiment, step **1560** or another step further comprises demodulating the modulated data signal after transmitting the modulated data signal across the first wire pair, and/or reducing the boosted electrical voltage signal after transmitting the boosted electrical voltage signal across the first wire pair. In the same or another embodiment, step **1560** or another step further comprises compensating for attenuation of the video signal before transmitting the video signal across the second wire pair and/or compensating for attenuation of the video signal after transmitting the video signal across the second wire pair. In the same or another embodiment, step **1560** or another step further comprises filtering the combined signal to prevent the modulated data signal from interfering with the boosted electrical voltage signal. In the same or another embodiment, step **1560** or another step further comprises detecting the presence of the second subsystem at the first subsystem before enabling the electrical power signal.

In the same or another embodiment of method **1500**, step **1510** or another step further comprises providing a switch and electrically coupling the switch between the computer and the operator control center. As an example, the switch can be similar to switch **240**, first shown in FIG. 2. In an embodiment where the distance extender comprises a switch, step **1510** or another step further comprises: (1) electrically coupling the switch between the computer and the first subsystem; and (2) electrically coupling the second subsystem between the first subsystem and the operator control center. In another embodiment, step **1510** or another step further comprises: (1) electrically coupling the switch between the second subsystem and the operator control center; and (2) electrically coupling the first subsystem between the computer and the second subsystem. In another embodiment, step **1510** or another step further comprises: (1) providing a third subsystem substantially similar to the first subsystem; (2) providing a fourth subsystem substantially similar to the second subsystem; (3) electrically coupling the third subsystem between the switch and the fourth subsystem; (4) electrically coupling the fourth subsystem between the third subsystem and the operator control center; and (5) electrically coupling the switch between the second subsystem and the third subsystem.

Although the invention has been described with reference to specific embodiments, it will be understood by those skilled in the art that various changes may be made without departing from the spirit or scope of the invention. Various examples of such changes have been given in the foregoing description. Accordingly, the disclosure of embodiments of the invention is intended to be illustrative of the scope of the invention and is not intended to be limiting. It is intended that the scope of the invention shall be limited only to the extent required by the appended claims. For example, to one of ordinary skill in the art, it will be readily apparent that the distance extender discussed herein may be implemented in a variety of embodiments, and that the foregoing discussion of certain of these embodiments does not necessarily represent a complete description of all possible embodiments.

All elements claimed in any particular claim are essential to the invention claimed in that particular claim. Consequently, replacement of one or more claimed elements constitutes reconstruction and not repair. Additionally, benefits, other advantages, and solutions to problems have been described with regard to specific embodiments. The benefits, advantages, solutions to problems, and any element or elements that may cause any benefit, advantage, or solution to occur or become more pronounced, however, are not to be

13

construed as critical, required, or essential features or elements of any or all of the claims.

Moreover, embodiments and limitations disclosed herein are not dedicated to the public under the doctrine of dedication if the embodiments and/or limitations: (1) are not expressly claimed in the claims; and (2) are or are potentially equivalents of express elements and/or limitations in the claims under the doctrine of equivalents.

What is claimed is:

1. A distance extender for increasing a distance between a first device and a second device in electrical communication with the first device, the distance extender comprising:
 - an electrical cable electrically coupled between the first device and the second device and comprising:
 - a first end;
 - a second end; and
 - a plurality of wires extending between the first end and the second end;
 - a first subsystem electrically coupled to the first end of the electrical cable and to the first device;
 - wherein the first subsystem includes a voltage boost circuit;
 - a second subsystem electrically coupled to the second end of the electrical cable and to the second device;
 - a switch electrically coupled to the second end of the electrical cable and to the second device;
 - a third subsystem including a voltage boost circuit; and
 - a fourth subsystem including a voltage boost circuit;
 wherein:
 - the first device or the second device generates a data signal and the first device provides an electrical power signal;
 - the plurality of wires includes a first wire;
 - the data signal and the electrical power signal are simultaneously transmitted between the first device and the second device over the first wire;
 - the third subsystem is electrically coupled between the switch and the fourth subsystem;
 - the fourth subsystem is electrically coupled between the third subsystem and the second device; and
 - the switch is electrically coupled between the second subsystem and the third subsystem.
2. A distance extender for increasing a distance between a first device and a second device in electrical communication with the first device, the distance extender comprising:
 - an electrical cable electrically coupled between the first device and the second device and comprising:
 - a first end;
 - a second end; and
 - a plurality of wires extending between the first end and the second end;
 - a first subsystem electrically coupled to the first end of the electrical cable and to the first device;
 - the first subsystem includes a pre-emphasis circuit; and
 - a second subsystem electrically coupled to the second end of the electrical cable and to the second device,
 wherein:
 - the first device or the second device generates a data signal and the first device provides an electrical power signal;
 - the plurality of wires includes a first wire; and
 - the data signal and the electrical power signal are simultaneously transmitted between the first device and the second device over the first wire.

14

3. The distance extender of claim 2 wherein:
 - the data signal comprises at least one of mouse data and keyboard data and is transmitted from the first device to the second device and from the second device to the first device.
4. The distance extender of claim 2 wherein:
 - the first wire forms a portion of a first wire pair; and
 - the data signal and the electrical power signal are simultaneously transmitted between the first device and the second device over the first wire pair.
5. The distance extender of claim 2 further comprising:
 - a switch electrically coupled between the first device and the second device.
6. The distance extender of claim 5 wherein:
 - the switch is a keyboard, video, and mouse switch.
7. The distance extender of claim 5 wherein:
 - the switch is electrically coupled between the first device and the first subsystem.
8. The distance extender of claim 5 wherein:
 - the switch is electrically coupled between second subsystem and the second device.
9. The distance extender of claim 5 further comprising:
 - a third subsystem include a voltage boost circuit; and
 - a fourth subsystem include a voltage boost circuit,
 wherein:
 - the third subsystem is electrically coupled between the switch and the fourth subsystem;
 - the fourth subsystem is electrically coupled between the third subsystem and the second device; and
 - the switch is electrically coupled between the second subsystem and the third subsystem.
10. The distance extender of claim 2 wherein:
 - the plurality of wires comprises four unshielded twisted wire pairs; and
 - the first wire is a portion of one of the four unshielded twisted wire pairs.
11. The distance extender of claim 2 wherein:
 - power to operate at least a portion of the second device is provided only by the electrical power signal.
12. The distance extender of claim 2 wherein:
 - the first subsystem comprises:
 - a modulation/demodulation circuit;
 - a filter and
 - a detection circuit.
13. The distance extender of claim 2 wherein:
 - the second subsystem comprises:
 - a voltage conversion circuit; and
 - an attenuation compensation circuit.
14. A distance extender for increasing a distance between a computer and an operator control center in electrical communication with the computer, the distance extender comprising:
 - a Category 5-type cable comprising:
 - a first end;
 - a second end; and
 - a plurality of wires extending between the first end and the second end, the plurality of wires comprising:
 - a first twisted pair;
 - a second twisted pair;
 - a third twisted pair; and
 - a fourth twisted pair;
 - a first subsystem electrically coupled between the first end of the Category 5-type cable and the computer; and
 - a second subsystem electrically coupled between the second end of the Category 5-type cable and the operator control center,

15

wherein:

the operator control center comprises:

- a computer keyboard;
- a computer video monitor; and
- a computer mouse;

the computer provides an electrical power signal and the computer or the operator control center generates a data signal and a plurality of video signals;

the plurality of video signals are transmitted between the first subsystem and the second subsystem over the first, second, and third twisted pairs; and

the data signal and the electrical power signal are simultaneously transmitted between the first subsystem and the second subsystem over the fourth twisted pair.

15. The distance extender of claim **14** wherein:

the first subsystem, the second subsystem, the computer keyboard, and the computer mouse are powered only by the electrical power signal.

16. The distance extender of claim **15** wherein:

the first subsystem comprises:

- a voltage boost circuit;
- a modulation/demodulation circuit;
- a filter circuit;
- a detection circuit; and
- a pre-emphasis circuit.

17. The distance extender of claim **16** wherein:

the second subsystem comprises:

- a voltage conversion circuit;
- a modulation/demodulation circuit;
- a filter circuit; and
- an attenuation compensation circuit.

18. The distance extender of claim **17** wherein:

the pre-emphasis circuit increases a high-frequency portion of the plurality of video signals before the plurality of video signals are transmitted across the first, second, and third twisted pairs; and

the attenuation compensation circuit compensates for a loss of amplitude in the plurality of video signals after the plurality of video signals are transmitted across the first, second, and third twisted pairs.

19. The distance extender of claim **16** wherein:

the first subsystem receives the electrical power signal from the computer; and

the voltage boost circuit boosts the electrical voltage signal before passing the electrical power signal to the Category 5-type cable.

20. The distance extender of claim **15** further comprising: a keyboard, video, and mouse switch electrically coupled between the computer and the operator control center.

21. The distance extender of claim **20** wherein:

the keyboard, video, and mouse switch is electrically coupled between the first subsystem and the computer.

22. The distance extender of claim **20** wherein:

the keyboard, video, and mouse switch is electrically coupled between the second subsystem and the operator control center.

23. The distance extender of claim **20** further comprising:

a third subsystem include a voltage boost circuit; and a fourth subsystem include a voltage boost circuit,

wherein:

the third subsystem is electrically coupled between the keyboard, video, and mouse switch and the fourth subsystem;

the fourth subsystem is electrically coupled between the third subsystem and the operator control center; and

the keyboard, video, and mouse switch is electrically coupled between the second subsystem and the third subsystem.

16

24. A method for increasing a distance between a computer and an operator control center in electrical communication with the computer where the electrical communication is accomplished via a cable having a first wire pair and a second wire pair, the method comprising:

providing a first subsystem to be coupled to a first end of the cable;

providing a second subsystem to be coupled to a second end of the cable such that an electrical power signal provided by the computer and a data signal generated by the computer or the operator control center are transmitted simultaneously across the first wire pair between the computer and the operator control center; using the computer to generate a video signal;

transmitting the video signal across the second wire pair between the computer and the operator control center compensating for attenuation of the video signal before transmitting the video signal across the second wire pair.

25. The method of claim **24** further comprising:

providing a switch; and electrically coupling the switch between the computer and the operator control center.

26. The method of claim **25** further comprising:

electrically coupling the switch between the computer and the first subsystem; and electrically coupling the second subsystem between the first subsystem and the operator control center.

27. The method of claim **25** further comprising:

electrically coupling the switch between the second subsystem and the operator control center; and electrically coupling the first subsystem between the computer and the second subsystem.

28. The method of claim **25** further comprising:

providing a third subsystem; providing a fourth subsystem; electrically coupling the third subsystem between the switch and the fourth subsystem; electrically coupling the fourth subsystem between the third subsystem and the operator control center; and electrically coupling the switch between the second subsystem and the third subsystem.

29. A method for increasing a distance between a computer and an operator control center in electrical communication with the computer where the electrical communication is accomplished via a cable having a first wire pair and a second wire pair, the method comprising:

providing a first subsystem to be coupled to a first end of the cable;

providing a second subsystem to be coupled to a second end of the cable such that an electrical power signal provided by the computer and a data signal generated by the computer or the operator control center are transmitted simultaneously across the first wire pair between the computer and the operator control center; modulating the data signal to create a modulated data signal;

modifying the electrical power signal to create a boosted electrical voltage signal;

coupling the modulated data signal onto the electrical power signal to create a combined signal; and transmitting the combined signal across the first wire pair between the computer and the operator control center.

30. The method of claim **29** further comprising:

using the computer to generate a video signal; and transmitting the video signal across the second wire pair between the computer and the operator control center.

17

31. The method of claim **30** further comprising:
demodulating the modulated data signal after transmitting
the modulated data signal across the first wire pair; and
reducing the boosted electrical voltage signal after trans-
mitting the boosted electrical voltage signal across the
first wire pair. 5

32. The method of claim **31** further comprising:
compensating for attenuation of the video signal after
transmitting the video signal across the second wire
pair. 10

33. The method of claim **31** further comprising:
compensating for attenuation of the video signal before
transmitting the video signal across the second wire
pair.

18

34. The method of claim **33** further comprising:
compensating for attenuation of the video signal after
transmitting the video signal across the second wire
pair.

35. The method of claim **32** further comprising:
filtering the combined signal to prevent the modulated
data signal from interfering with the boosted electrical
voltage signal.

36. The method of claim **35** further comprising:
detecting the presence of the second subsystem at the first
subsystem before enabling the electrical power signal.

* * * * *