

US007293880B2

(12) **United States Patent**
Sakata et al.

(10) **Patent No.:** **US 7,293,880 B2**
(45) **Date of Patent:** **Nov. 13, 2007**

(54) **LIGHT SOURCE INCLUDING MULTIPLE LIGHT EMITTING DEVICES DRIVEN BY A CONTROL DEVICE, AND PROJECTOR**

6,802,613	B2 *	10/2004	Agostinelli et al.	353/31
7,029,129	B2 *	4/2006	Shimada	353/94
7,118,221	B2 *	10/2006	Shimada	353/31
2003/0214633	A1 *	11/2003	Roddy et al.	353/31
2003/0234911	A1	12/2003	Horvath et al.	
2004/0070736	A1	4/2004	Roddy et al.	
2004/0263500	A1	12/2004	Sakata	

(75) Inventors: **Hidefumi Sakata**, Tatsuno-cho (JP);
Masatoshi Yonekubo, Hara-mura (JP)

(73) Assignee: **Seiko Epson Corporation**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 194 days.

FOREIGN PATENT DOCUMENTS

EP	1 365 598	11/2003
JP	A 2001-042431	2/2001

(21) Appl. No.: **11/114,136**

(22) Filed: **Apr. 26, 2005**

(65) **Prior Publication Data**

US 2005/0248733 A1 Nov. 10, 2005

(30) **Foreign Application Priority Data**

May 7, 2004 (JP) 2004-138559

(51) **Int. Cl.**

G03B 21/26	(2006.01)
G03B 21/00	(2006.01)
G02F 1/1335	(2006.01)
G02F 1/00	(2006.01)
H04N 5/70	(2006.01)

(52) **U.S. Cl.** **353/94; 353/33; 353/37; 349/8; 348/801; 348/751; 348/757; 362/612**

(58) **Field of Classification Search** **353/94, 353/31, 33, 37; 349/8; 348/801, 750, 751, 348/757; 362/612**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,648,475 B1 11/2003 Roddy et al.

* cited by examiner

Primary Examiner—W. B. Perkey


Assistant Examiner—Magda Cruz

(74) *Attorney, Agent, or Firm*—Oliff & Berridge, PLC

(57) **ABSTRACT**

Aspects of the invention can provide a light source that can reduce the optical system in size while enlarging a color reproducible range and achieving higher luminance. The system can include a cross dichroic prism to combine an R light, a G₁ light, a G₂ light, and a B light, and an LED R to generate the R light, an LED G₁ to generate the G₁ light, an LED G₂ to generate the G₂ light, and an LED B, disposed near the LED G₂ to be side by side, to generate the B light, as well as a control portion to drive these LED R, LED G₁, LED G₂, and LED B under control. The peak wavelengths of the G₂ light and the B light are adjacent to each other, and the control portion can drive the LED G₂ and the LED B under its control by switching in time division.

5 Claims, 11 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13
Related Art




FIG. 14
Related Art

**LIGHT SOURCE INCLUDING MULTIPLE
LIGHT EMITTING DEVICES DRIVEN BY A
CONTROL DEVICE, AND PROJECTOR**

BACKGROUND

Aspects of the invention can relate to a light source and a projector. More particularly, the invention can have an object to provide a light source and a projector capable of reducing an optical system in size while enlarging a color reproducible range and achieving higher luminance.

There has been a need to increase luminance for a light source used in a projector. In order to satisfy this need, a method of increasing luminance by combining two lights each having a different wavelength using a dichroic mirror has been proposed in the related art. See, for example, JP-A-2001-42431. FIG. 13 is a plan view showing the configuration of a light source 100 in the related art. The light source 100 adopts the method of increasing luminance as described above, and is used, for example, in a projector.

Referring to FIG. 13, an LED 101R, an LED 101G₁, an LED 101G₂, and an LED 101B are provided in the vicinity of three sides of a cross dichroic prism 104 described below, and they are solid-state light-emitting devices to generate, respectively, a red light (hereinafter, referred to as an R light), a first green light (hereinafter, referred to as a G₁ light), a second green light (hereinafter, referred to as a G₂ light), and a blue light (hereinafter, referred to as a B light). As is shown in FIG. 14, the R light, the G₁ light, the G₂ light, and the B light have spectrums having different peak wavelengths λ_R , λ_{G_1} , λ_{G_2} , and λ_B , respectively. By using lights of four colors, including the R light, G₁ light, G₂ light, and B light, in this manner, a color reproducible range can be enlarged in comparison with a case using lights of three colors (RGB).

Referring to FIG. 13 again, a liquid crystal light valve 102R is provided in close proximity to the LED 101R, and it is a transmission liquid crystal display device to modulate the R light emitted from the LED 101R according to an image signal. In other words, a video responding to a color corresponding to the R light is formed in the liquid crystal light valve 102R and the R light is modulated when it passes through the liquid crystal light valve 102R.

A dichroic mirror 103 is provided at an angle such that it can allow the G₁ light emitted from the LED 101G₁ and the G₂ light emitted from the LED 101G₂ to come incident thereon at 45 degrees, and it is an optical device having an optical characteristic to transmit the G₁ light (peak wavelength: λ_{G_1}) while reflecting the G₂ light (peak wavelength: λ_{G_2}). In short, the dichroic mirror 103 is an optical device to combine the G₁ light and the G₂ light. The light source 100 in the related art combines the G₁ light and the G₂ light in the dichroic mirror 103 as has been described, and thereby achieves high luminance with a green light. A white light is formed by combining a red light, a green light, and a blue light in the ratio of 2:7:1. It is therefore necessary for the light source 100 to increase luminance of a green light than lights of the other colors, and in order to satisfy this need, high luminance is achieved with a green light by combining the G₁ light and the G₂ light in the dichroic mirror 103.

A liquid crystal light valve 102G can be provided in close proximity to the dichroic mirror 103, and it is a transmission liquid crystal display device to modulate a green light (hereinafter, referred to as a G₁G₂ light) combined in the dichroic mirror 103 according to an image signal. In other words, a video responding to a color of the G₁G₂ light is formed in the liquid crystal light valve 102G, and the G₁G₂

light is modulated when it passes through the liquid crystal light valve 102G. A liquid crystal light valve 102B is provided in close proximity to the LED 101B, and it is a transmission liquid crystal display device to modulate the B light emitted from the LED 101B according to an image signal. That is to say, a video responding to a color corresponding to the B light is formed in the liquid crystal light valve 102B, and the B light is modulated when it passes through the liquid crystal light valve 102B.

The cross dichroic prism 104 has two filters, including a dichroic filter 105 and a dichroic filter 106. These dichroic filter 105 and dichroic filter 106 are disposed to intersect with each other at right angles in the shape of a capital X. The dichroic filter 105 has a transmission characteristic indicated by a broken line in FIG. 14, and thereby transmits the G₂ light, the G₁ light, and the B light while reflecting the R light. The dichroic filter 106 has a transmission characteristic indicated by an alternate long and short dash line in FIG. 14, and thereby transmits the R light, the G₁ light, and the G₂ light while reflecting the B light. The cross dichroic mirror 104 shown in FIG. 13 is furnished with a function of combining the R light, the G₁G₂ light (G₁ light and G₂ light), and the B light as has been described. A projection lens 107 is a lens to project lights combined in the cross dichroic mirror 104 onto a screen (not shown).

SUMMARY

Incidentally, the light source 100 in the related art achieves high luminance with a green light by providing the dichroic mirror 103, the LED 101G₁, and the LED 101G₂ in close proximity to the liquid crystal light valve 102G as is shown in FIG. 13. This configuration, however, needs a large space to provide the dichroic mirror 103, the LED 101G₁, and the LED 101G₂, which raises a problem that the optical system is increased in size.

An object of the invention can be to provide a light source and a projector capable of reducing the optical system in size while enlarging a color reproducible range and achieving higher luminance.

In order to solve the foregoing problems and achieve the above and other objects, one aspect of the invention can include a light combining device for combining a first color light through a fourth color light that come incident from first through third optical paths, a first light emitting device, provided in the first optical path, for generating the first color light, a second light emitting device, provided in the second optical path, for generating the second color light, a third light emitting device, provided in the third optical path, for generating the third color light, a fourth light emitting device, provided in the third optical path near the third light emitting device to be side by side, for generating the fourth color light, and a control device for driving the first through fourth light emitting device under control. Of the first color light through the fourth color light, peak wavelengths of the third color light and the fourth color light are adjacent to each other, and the control device drives, under control, the third light emitting device and the fourth light emitting device by switching in time division.

According to this aspect of the invention, the light combining device for combining the first color light through the fourth color light, the first through fourth light emitting device, and the control device for driving the first through fourth light emitting device under control are provided. The third light emitting device and the fourth light emitting device are provided side by side, so that the peak wavelengths of the third color light and the fourth color light are

adjacent to each other. The control device thereby drives, under its control, the third light emitting device and the fourth light emitting device by switching in time division. It is thus possible to reduce the optical system in size while enlarging the color reproducible range and achieving higher luminance.

Another aspect of the invention is characterized by further including first through third modulating device, provided, respectively, in the first through third optical paths on a light incident-side of the light combining device, for modulating the first color light through the fourth color light to correspond to videos of respective colors, wherein the control device drives, under control, the third modulating device in association with switching between the third light emitting device and the fourth light emitting device.

According to this aspect of the invention, the first through third modulating device for modulating the first color light through the fourth color light to correspond to videos of respective colors are provided, respectively, in the first through third optical paths on a light incident-side of the light combining device, and the control device drives, under control, the third modulating device in association with switching between the third light emitting device and the fourth light emitting device. It can thus be possible to reduce the optical system of a device displaying a video in size while enlarging the color reproducible range and achieving higher luminance.

Still another aspect of the invention can further include fifth light emitting device, provided in the first optical path near the first light emitting device to be side by side, for generating a fifth color light. Peak wavelengths of the first color light and the fifth color light can be adjacent to each other, and the control device drives, under control, the first light emitting device and the fifth light emitting device by switching in time division.

According to this aspect of the invention, the fifth light emitting device for generating the fifth color light can be provided in the first optical path near the first light emitting device to be side by side, so that the peak wavelengths of the first color light and the fifth color light are adjacent to each other. The control device thereby drives, under its control, the first light emitting device and the fifth light emitting device by switching in time division. It is thus possible to further reduce the optical system in size while enlarging the color reproducible range and achieving higher luminance.

Still another aspect of the invention can further include a first through third modulating device, provided, respectively, in the first through third optical paths on a light incident-side of the light combining device, for modulating the first color light through the fifth color light to correspond to videos of respective colors. The control device drives, under control, the first modulating device in association with switching between the first light emitting device and the fifth light emitting device, and drives, under control, the third modulating device in association with switching between the third light emitting device and the fourth light emitting device.

According to this aspect of the invention, a first through third modulating device for modulating the first color light through the fifth color light to correspond to videos of respective colors can be provided, respectively, in the first through third optical paths on a light incident-side of the light combining device, and the control device can drive, under control, the first modulating device in association with switching between the first light emitting device and the fifth light emitting device, and drives, under control, the third modulating device in association with switching between the third light emitting device and the fourth light emitting

device. It is thus possible to further reduce the optical system of a device displaying a video in size while enlarging the color reproducible range and achieving higher luminance.

Still another aspect of the invention can provide a projector employing the light source according to any of the above aspects. According to this aspect of the invention, it is possible to reduce the optical system in size employed in the projector while enlarging the color reproducible range and achieving higher luminance.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be described with reference to the accompanying drawings, wherein like numerals reference like elements, and wherein:

FIG. 1 is a plan view showing the configuration of a light source **200** according to a first exemplary embodiment of the invention;

FIG. 2 is a view showing optical spectrums and transmission characteristics of the light source **200** shown in FIG. 1;

FIG. 3 is an x-y chromaticity diagram in the first exemplary embodiment;

FIG. 4 is a view showing driving control timings in the first exemplary embodiment;

FIG. 5 is a plan view showing the configuration of a light source **300** according to a second exemplary embodiment of the invention;

FIG. 6 is a view showing optical spectrums and transmission characteristics of the light source **300** shown in FIG. 5;

FIG. 7 is an x-y chromaticity diagram in the second exemplary embodiment;

FIG. 8 is a view showing driving control timings in the second exemplary embodiment;

FIG. 9 is a plan view showing the configuration of a light source **400** according to a third exemplary embodiment of the invention;

FIG. 10 is a view showing optical spectrums and transmission characteristics of the light source **400** shown in FIG. 9;

FIG. 11 is an x-y chromaticity diagram in the third exemplary embodiment;

FIG. 12 is a view showing driving control timings in the third exemplary embodiment;

FIG. 13 is a plan view showing the configuration of a light source **100** in the related art; and

FIG. 14 is a view showing optical spectrums and transmission characteristics of the light source **100** shown in FIG. 13.

DETAILED DESCRIPTION OF EMBODIMENTS

Exemplary embodiments of a light device and a projector of the invention will now be described in detail with reference to the drawings. It should be appreciated, however, that the invention is not limited to the exemplary embodiments described below.

FIG. 1 is a plan view showing the configuration of a light source **200** according to a first exemplary embodiment of the invention. The light source **200** is used, for example, in a projector. In the light source **200**, an LED **201R**, an LED **201G₁**, an LED **201G₂**, and an LED **201B** are provided in the vicinity of three sides of a cross dichroic prism **203** described below, and they are solid-state light-emitting devices to generate, respectively, a red light (hereinafter, referred to as an R light), a first green light (hereinafter,

5

referred to as a G_1 light), a second green light (hereinafter, referred to as a G_2 light), and a blue light (hereinafter, referred to as a B light). As is shown in FIG. 2, the R light, G_1 light, G_2 light, and B light have spectrums having different peak wavelengths λ_R , λ_{G_1} , λ_{G_2} , and λ_B , respectively.

By using lights of four colors, including the R light, the G_1 light, the G_2 light, and the B light, in this manner, as is shown in an x-y chromaticity diagram in FIG. 3, a color reproducible range (see a color range A2) can be enlarged in comparison with a case using lights of three colors (RGB) (see color range A1).

The LED 201R can be provided in close proximity to a liquid crystal light valve 202R. The liquid crystal light valve 202R is a transmission liquid crystal display device to modulate the R light emitted from the LED 201R according to an image signal. That is to say, a video responding to a color corresponding to the R light is formed in the liquid crystal light valve 202R and the R light is modulated when it passes through the liquid crystal light valve 202R.

The LED 201 G_1 can be provided in close proximity to a liquid crystal light valve 202 G_1 . The liquid crystal light valve 202 G_1 is a transmission liquid crystal display device to modulate the G_1 light emitted from the LED 201 G_1 according to an image signal. That is to say, a video responding to a color of the G_1 light is formed in the liquid crystal light valve 202 G_1 , and the G_1 light is modulated when it passes through the liquid crystal light valve 202 G_1 .

The LED 201 G_2 and the LED 201B can be provided side by side in close proximity to a liquid crystal light valve 202 BG_2 . The G_2 light and the B light are emitted, respectively, from the LED 201 G_2 and the LED 201B alternately in time division toward a liquid crystal light valve 202 BG_2 . The liquid crystal light valve 202 BG_2 is a transmission liquid crystal display device furnished with a function of modulating the G_2 light emitted from the LED 201 G_2 according to an image signal and a function of modulating the B light emitted from the LED 201B according to an image signal. In other words, a video responding to a color corresponding to the G_2 light and a video responding to a color corresponding to the B light are formed alternately in time division in the liquid crystal light valve 202 BG_2 .

The cross dichroic prism 203 has two filters, including a dichroic filter 204 and a dichroic filter 205. These dichroic filter 204 and dichroic filter 205 are disposed to intersect with each other at right angles in the shape of a capital X. The dichroic filter 204 has a transmission characteristic indicated by a broken line in FIG. 2, and thereby transmits the G_1 light, the G_2 light, and the B light while reflecting the R light. The dichroic filter 205 has a transmission characteristic indicated by an alternate long and short dash line in FIG. 2, and thereby transmits the R light and the G_1 light while reflecting the G_2 light the B light. The cross dichroic mirror 203 shown in FIG. 1 is furnished with a function of combining the R light, the G_1 light, the G_2 light, and the B light as has been described. A projection lens 206 is a lens to project lights combined in the cross dichroic mirror 203 onto a screen (not shown).

In the configuration describe above, a control portion (not shown) drives, under its control, the LED 201R, the liquid crystal light valve 202R, the LED 201 G_1 , the liquid crystal light valve 202 G_1 , the LED 201B, the LED 201 G_2 , and the liquid crystal light valve 202 BG_2 independently at timings shown in FIG. 4. To be more specific, the LED 201R and the LED 201 G_1 are driven constantly under the control of the control portion. The R light and the G_1 light are thereby emitted constantly, respectively, from the LED 201R and the

6

LED 201 G_1 shown in FIG. 1. Both the liquid crystal light valve 202R and the liquid crystal light valve 202 G_1 are driven at a time t1 and a time t3 shown in FIG. 4 under the control of the control portion, and modulate the R light and the G_1 light, respectively.

Writing times T referred to herein are times needed for the writing from the first line to the last line by the line-sequential writing method using the liquid crystal light valve 202R, the liquid crystal light valve 202 G_1 , and the liquid crystal light valve 202 BG_2 .

Meanwhile, the LED 201B and the LED 201 G_2 are driven alternately in time division under the control of the control portion. To be more specific, the liquid crystal light valve 202 BG_2 is driven at a time t1, a time t2, and a time t3, and modulates the B light and the G_2 light alternately. The LED 201B is driven at a time t1+ α after the writing of all the lines is completed by driving the liquid crystal light valve 202 BG_2 at a time t1. Meanwhile, the LED 201 G_2 is driven at a time t2+ α after the writing of all the lines is completed by driving the liquid crystal light valve 202 BG_2 at a time t2.

The R light, the G_1 light, the G_2 light, and the B light are combined in the cross dichroic prism 203 by the control at the timings specified above, and the lights thus combined are projected on a screen (not shown) by a projection lens 206.

As has been described, according to the first exemplary embodiment, the cross dichroic prism 203 to combine the R light, the G_1 light, the G_2 light, and the B light, and the LED 201R, the LED 201 G_1 , the LED 201 G_2 , and the LED 201B, as well as the control portion (not shown) to drive these LED 201R, LED 201 G_1 , LED 201 G_2 , and LED 201B under control are provided. Then, the LED 201 G_2 and the LED 201B are provided side by side, so that, as is shown in FIG. 2, the peak wavelengths of the G_2 light and the B light are adjacent to each other. This exemplary configuration enables the control portion to drive the LED 201 G_2 and the LED 201B under its control by switching in time division. It is thus possible to reduce the optical system in size while enlarging the color reproducible region and achieving higher luminance.

Also, according to the first exemplary embodiment, the liquid crystal light valve 202R, the liquid crystal light valve 202 G_1 , and the liquid crystal light valve 202 BG_2 to modulate, respectively, the R light, the G_1 light, and the G_2 light and the B light to correspond to videos of respective colors are provided on the light incident-side of the cross dichroic prism 203, and the control portion drives, under its control, the liquid crystal light valve 202 BG_2 in association with the switching between the LED 201 G_2 and the LED 201B. It can thus be possible to reduce the optical system of a projector displaying a video in size while further enlarging the color reproducible range and achieving higher luminance.

While the first exemplary embodiment has been described by way of an example of the configuration using lights of four colors, including the R light, the G_1 light, the G_2 light, and the B light, the invention may have a configuration using lights of five colors including a third green light (hereinafter, referred to as the G_3 light) in addition to lights of four colors specified above. An example of this configuration will now be described as a second exemplary embodiment.

FIG. 5 is a plan view showing the configuration of a light source 300 according to the second exemplary embodiment of the invention. The light source 300 is used, for example, in a projector. In this drawing, like components are labeled with like reference numerals with respect to FIG. 1. In the light source 300 shown in FIG. 5, an LED 201 G_3 is additionally provided, and the liquid crystal light valve 202R shown in FIG. 1 is replaced with a liquid crystal light valve

202RG₃. The LED **201G₃** is a solid-state light-emitting device to generate the G₃ light. As is shown in FIG. 6, the R light, the G₁ light, the G₂ light, the G₃ light, and the B light have spectrums having different peak wavelengths λ_R , λ_{G_1} , λ_{G_2} , λ_{G_3} , and λ_B . In other words, the wavelength of the G₃ light is longer than the wavelength of the G₁ light and shorter than the wavelength of the R light.

By using lights of five colors, including the R light, the G₁ light, the G₂ light, the G₃ light, and the B light, in this manner, as is shown in an x-y chromaticity diagram in FIG. 7, a color reproducible range (see a color range A3) can be further enlarged in comparison with a case using lights of three colors (RGB) (see color range A1).

Referring to FIG. 5 again, the LED **201G₃** can be provided near the LED **201R** to be side by side, and is also provided in close proximity to the liquid crystal light valve **202RG₃**. The G₃ light and the R light are emitted, respectively, from the LED **201G₃** and the LED **201R** alternately in time division toward the liquid crystal light valve **202RG₃**. The liquid crystal light valve **202RG₃** is a transmission liquid crystal display device furnished with a function of modulating the G₃ light emitted from the LED **201G₃** according to an image signal and a function of modulating the R light emitted from the LED **201R** according to an image signal. In other words, a video responding to a color corresponding to the G₃ light and a video responding to a color corresponding to the R light are formed alternately in time division in the liquid crystal light valve **202RBG₃**.

In the second exemplary embodiment, the dichroic filter **204** has a transmission characteristic indicated by a broken line in FIG. 6, and thereby transmits the G₁ light, the G₂ light, and the B light while reflecting the G₃ light and the R light. The dichroic filter **205** has a transmission characteristic indicated by an alternate long and short dash line in FIG. 6, and thereby transmits the R light, the G₃ light, and the G₁ light while reflecting the G₂ light and the B light.

In the configuration describe above, a control portion (not shown) drives, under its control, the LED **201R**, the LED **201G₃**, the liquid crystal light valve **202RG₃**, the LED **201G₁**, the liquid crystal light valve **202G₁**, the LED **201B**, the LED **201G₂**, and the liquid crystal light valve **202BG₂** independently at timings shown in FIG. 8. To be more specific, the LED **201G₁** is driven constantly under the control of the control portion. The G₁ light is thereby emitted constantly from the LED **201G₁** shown in FIG. 5. The liquid crystal light valve **202G₁** is driven at a time t1 and a time t3 shown in FIG. 8 under the control of the control portion, and modulates the G₁ light.

Writing times T referred to herein are times needed for the writing from the first line to the last line by the line-sequential writing method using the liquid crystal light valve **202RG₃**, the liquid crystal light valve **202G₁**, and the liquid crystal light valve **202BG₂**.

The LED **201R** and the LED **201G₃** are driven alternately in time division under the control of the control portion. To be more specific, the liquid crystal light valve **202RG₃** is driven at a time t1, a time t2, and a time t3, and modulates the R light and the G₃ light alternately. The LED **201R** is driven at a time t1+ α after the writing of all the lines is completed by driving the liquid crystal light valve **202RG₃** at a time t1. Meanwhile, the LED **201G₃** is driven at a time t2+ α after the writing of all the lines is completed by driving the liquid crystal light valve **202RG₃** at a time t2.

The LED **201B** and the LED **201G₂** are driven alternately in time division under the control of the control portion. To be more specific, the liquid crystal light valve **202BG₂** is driven at a time t1, a time t2, and a time t3, and modulates

the B light and the G₂ light alternately. The LED **201B** is driven at a time t1+ α after the writing of all the lines is completed by driving the liquid crystal light valve **202BG₂** at a time t1. Meanwhile, the LED **201G₂** is driven at a time t2+ α after the writing of all the lines is completed by driving the liquid crystal light valve **202BG₂** at a time t2.

The R light, the G₁ light, the G₂ light, the G₃ light, and the B light are combined in the cross dichroic prism **203** by the control at the timings specified above, and the lights thus combined are projected on the screen (not shown) by the projection lens **206**.

As has been described, according to the second exemplary embodiment, the LED **201G₃**, disposed near the LED **201R** to be side by side, to generate the G₃ light is provided, so that, as is shown in FIG. 6, the peak wavelengths of the R light and the G₃ light are adjacent to each other. This configuration enables the control portion to drive the LED **201R** and the LED **201G₃** by switching in time division under its control. It is thus possible to further reduce the optical system in size while enlarging the color reproducible range and achieving higher luminance.

Also, according to the second exemplary embodiment, the liquid crystal light valve **202RG₃** is provided, and the control portion drives, under its control, the liquid crystal light valve **202RG₃** in association with the switching between the LED **201R** and the LED **201G₃**. It can thus be possible to further reduce the optical system of a projector displaying a video in size while further enlarging the color reproducible range and achieving higher luminance.

While the second exemplary embodiment has been described by way of an example of the configuration using lights of five colors, including the R light, the G₁ light, the G₂ light, the G₃ light, and the B light, the invention may have a configuration using lights of four colors excluding the G₂ light from lights of five colors specified above. An example of this configuration will now be described as a third exemplary embodiment.

FIG. 9 is a plan view showing the configuration of a light source **400** according to the third exemplary embodiment of the invention. The light source **400** is used, for example, in a projector. In this drawing, like components are labeled with like reference numerals with respect to FIG. 5 and FIG. 1. In the light source **400** shown in FIG. 9, the LED **201G₂** shown in FIG. 5 is omitted, and the liquid crystal light valve **202BG₂** shown in FIG. 5 is replaced with a liquid crystal light valve **202B**. The light valve **202B** is provided in close proximity to the LED **201B**, and it is a transmission liquid crystal display device to modulate the B light emitted from the LED **201B** according to an image signal. In other words, a video responding to a color corresponding to the B light is formed in the liquid crystal light valve **202B**, and the B light is modulated when it passes through the liquid crystal light valve **202B**.

In the third exemplary embodiment, by using lights of four colors, including the R light, the G₁ light, the G₃ light, and the B light, in this manner, as is shown in an x-y chromaticity diagram in FIG. 11, a color reproducible range (see a color range A4) can be enlarged in comparison with a case using lights of three colors (RGB) (see color range A1).

In the third exemplary embodiment, the dichroic filter **204** has a transmission characteristic indicated by a broken line in FIG. 10, and thereby transmits the G₁ light and the B light while reflecting the G₃ light and the R light. The dichroic filter **205** has a transmission characteristic indicated by an

alternate long and short dash line in FIG. 10 and thereby transmits the R light, the G_3 light, and the G_1 light while reflecting the B light.

In the configuration describe above, a control portion (not shown) drives, under its control, the LED 201R, the LED 201 G_3 , the liquid crystal light valve 202R G_3 , the LED 201 G_1 , the liquid crystal light valve 202 G_1 , the LED 201B, and the liquid crystal light valve 202B independently at timings shown in FIG. 12. To be more specific, the LED 201 G_1 and the LED 201B are driven constantly under the control of the control portion. The G_1 light and the B light are thereby emitted constantly, respectively, from the LED 201 G_1 and the LED 201B shown in FIG. 9. Both the liquid crystal light valve 202 G_1 and the liquid crystal light valve 202B are driven at a time t1 and a time t3 shown in FIG. 12 under the control of the control portion, and modulate the G_1 light and the B light, respectively.

Writing times T referred to herein are times needed for the writing from the first line to the last line by the line-sequential writing method using the liquid crystal light valve 202R G_3 , the liquid crystal light valve 202 G_1 , and the liquid crystal light valve 202B.

The LED 201R and the LED 201 G_3 are driven alternately in time division under the control of the control portion. To be more specific, the liquid crystal light valve 202R G_3 is driven at a time t1, a time t2, and a time t3, and modulates the R light and the G_3 light alternately. The LED 201R is driven at a time t1+ α after the writing of all the lines is completed by driving the liquid crystal light valve 202R G_3 at a time t1. Meanwhile, the LED 201 G_3 is driven at a time t2+ α . after the writing of all the lines is completed by driving the liquid crystal light valve 202R G_3 at a time t2.

The R light, the G_1 light, the G_3 light, and the B light are combined in the cross dichroic prism 203 by the control at the timings specified above, and the lights thus combined are projected on the screen (not shown) by the projection lens 206.

As has been described, according to the third exemplary embodiment, the same advantages as those of the first embodiment can be achieved.

As has been described, the light source and the projector of the invention are useful to reduce the optical system in size while enlarging the color reproducible range and achieving higher luminance.

While this invention has been described in conjunction with the specific embodiments thereof, it is evident that many alternatives, modifications, and variations will be apparent to those skilled in the art. Accordingly, preferred embodiments of the invention as set forth herein are intended to be illustrative, not limiting. There are changes that may be made without departing from the spirit and scope of the invention.

What is claimed is:

1. A light source, comprising:

a light combining device that combines a first color light through a fourth color light that are incident from a first through third optical path;

a first light emitting device, provided in the first optical path, that generates the first color light;
 a second light emitting device, provided in the second optical path, that generates the second color light;
 a third light emitting device, provided in the third optical path, that generates the third color light;
 a fourth light emitting device, provided in the third optical path near the third light emitting device to be side by side, that generates the fourth color light;
 a control device that drives the first through fourth light emitting device under control; and
 of the first color light through the fourth color light, peak wavelengths of the third color light and the fourth color light being adjacent to each other, and the control device driving, under control, the third light emitting device and the fourth light emitting device by switching in time division.

2. The light source according to claim 1, further comprising:

a first through third modulating device provided, respectively, in the first through third optical paths on a light incident-side of the light combining device that modulate the first color light through the fourth color light to correspond to videos of respective colors; and
 the control device driving, under control, the third modulating device in association with switching between said third light emitting device and the fourth light emitting device.

3. The light source according to claim 1, further comprising:

a fifth light emitting device, provided in the first optical path near the first light emitting device to be side by side, that generates a fifth color light, and
 peak wavelengths of the first color light and the fifth color light being adjacent to each other, and the control device driving, under control, the first light emitting device and the fifth light emitting device by switching in time division.

4. The light source according to claim 3, further comprising:

a first through third modulating device provided, respectively, in the first through third optical paths on a light-incident side of the light combining device that modulates the first color light through the fifth color light to correspond to videos of respective colors; and
 the control device driving, under control, the first modulating device in association with switching between the first light emitting device and the fifth light emitting device, and driving, under control, the third modulating device in association with switching between the third light emitting device and the fourth light emitting device.

5. A projector employing the light source according to claim 1.

* * * * *