

US007293920B2

(12) **United States Patent**
Arena

(10) **Patent No.:** **US 7,293,920 B2**
(45) **Date of Patent:** **Nov. 13, 2007**

(54) **SELF-ALIGNING BEARING ASSEMBLY
CAPABLE OF REACTING RADIAL AND
AXIAL LOADS**

2,987,351 A	6/1961	Aberle
3,009,747 A	11/1961	Pitzer
3,476,454 A	11/1969	Markey
3,762,240 A	10/1973	Adams
5,718,517 A	2/1998	Morando
5,828,151 A	10/1998	Bustamante et al.
5,885,006 A	3/1999	Sheedy

(75) Inventor: **Aldo Arena**, Smithtown, NY (US)

(73) Assignee: **Northrop Grumman Corporation**, Los Angeles, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 108 days.

FOREIGN PATENT DOCUMENTS

JP 61-175313 8/1986

Primary Examiner—Lenard A. Footland
(74) *Attorney, Agent, or Firm*—Alan G. Towner, Esq.;
Pietragallo Bosick & Gordon, LLP

(21) Appl. No.: **11/080,164**

(22) Filed: **Mar. 14, 2005**

(65) **Prior Publication Data**
US 2006/0204160 A1 Sep. 14, 2006

(51) **Int. Cl.**
F16C 19/49 (2006.01)

(52) **U.S. Cl.** **384/495**

(58) **Field of Classification Search** 384/494,
384/495, 126, 127, 420
See application file for complete search history.

(57) **ABSTRACT**


A self-aligning bearing assembly is disclosed which is capable of reacting both radial and axial loads. An inner bearing race is connected to a rotatable shaft that is subjected to such loads. An outer bearing race is installed within a housing and is capable of movement in multiple directions with respect to the housing. The outer bearing race can rotate in planes corresponding to longitudinal sections of the outer race, i.e., rotational displacement. In addition, the outer bearing race can translate with respect to an inner wall of the housing in an axial direction of the housing, i.e., axial displacement. Such movement is enabled by the use of radially displaceable thrust rings which contact the outer bearing race, and control of the geometry of the outer bearing race and inner wall of the housing.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,832,312 A	11/1931	Lutz
1,995,408 A	3/1935	Wallgren
2,975,007 A	3/1961	Zwicker

36 Claims, 7 Drawing Sheets






FIG. 1





FIG. 2






FIG. 4




FIG. 5a




FIG. 5b





FIG. 5c






FIG. 7

1

**SELF-ALIGNING BEARING ASSEMBLY
CAPABLE OF REACTING RADIAL AND
AXIAL LOADS**

FIELD OF THE INVENTION

The present invention relates to bearing assemblies, and more particularly relates to bearing assemblies that are capable of reacting radial and axial loads in various applications such as in the rotating flight shafts that support the rotodomes of surveillance aircrafts.

BACKGROUND INFORMATION

Bearing assemblies are often used in applications where a rotating shaft is subjected to radial and axial loads. For example, the gearbox and rotating flight shaft of radar-equipped aircraft such as the rotodome of early warning command and control aircraft are subjected to substantial radial loads on the rotodome flight shaft due to air loads acting on the rotodome during flight. In addition, the flight shaft is subjected to substantial axial loads due to the weight of the rotodome and the aerodynamic forces applied during flight on the disk-shaped rotodome. In conventional rotodome gearbox and flight shaft designs, a highly complex bearing system is used, including upper and lower bearing assemblies offset along the length of the shaft from a lower "X" bearing assembly in the rotodome gearbox that is required in order to react the substantial axial loads on the shaft. This arrangement has several drawbacks including substantial wear of the upper and lower pylon bearing assemblies when the flight shaft bends, which causes unwanted walking, rotation at the inner and outer diameters of the bearings that, in turn, causes scoring of the structural support assembly. Other disadvantages of the conventional design include uneven loading of the "X" bearing that results in brinelling of the bearing races and reduced life. The current arrangement also requires time consuming maintenance procedures due to the fact that the flight shaft and gearbox are secured with common fasteners requiring removal of the flight shaft load from the gearbox as a prerequisite for removal and replacement of the gearbox.

The present invention has been developed in view of the foregoing, and to address other deficiencies of prior bearing assembly designs.

SUMMARY OF THE INVENTION

The present invention provides a self-aligning bearing assembly which is capable of reacting both radial and axial loads, as well as moment loads. An inner bearing race is connected to a rotatable shaft that is subjected to such loads. An outer bearing race is installed within a housing and is capable of movement in multiple directions with respect to the housing. The outer bearing race can rotate in planes corresponding to longitudinal sections of the outer race, i.e., "rotational displacement". In addition, the outer bearing race can translate within limits with respect to an inner wall of the housing in an axial direction of the housing, i.e., "axial displacement". Such movement is achieved by controlling the geometry of the outer bearing race and inner wall of the housing, and by the use of radially displaceable thrust rings which contact the outer bearing race.

An aspect of the present invention is to provide a bearing assembly comprising a bearing housing, an outer bearing race and inner bearing race. The inner bearing race can be singular or made up of multiple segments. A portion of a

2

radial outer surface of the outer bearing race contacts an inner wall of the bearing housing. When a radial or bending load is applied to a rotatable shaft connected to the inner race, the axial centerlines of the inner and outer races are displaced with respect to the axial centerline of the bearing housing, causing both rotational displacement and axial displacement of the outer bearing race with respect to the inner wall of the bearing housing.

Another aspect of the present invention is to provide a rotatable shaft and bearing assembly comprising a bearing housing, an outer bearing race disposed in the bearing housing, an inner bearing race disposed radially inside the outer bearing race, and a rotatable shaft connected to the inner bearing race, wherein a radial load applied to the rotatable shaft causes axial displacement of the outer bearing race with respect to the bearing housing.

These and other aspects of the present invention will be more apparent from the following description.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a longitudinal sectional view of a rotodome flight shaft and a self-aligning bearing assembly in accordance with an embodiment of the present invention.

FIG. 2 is a longitudinal sectional view of the lower portion of the rotodome flight shaft and the self-aligning bearing assembly shown in FIG. 1.

FIG. 3 is an isometric view of a self-aligning bearing assembly in accordance with an embodiment of the present invention.

FIG. 4 is a longitudinal sectional view of the self-aligning bearing assembly of FIG. 3.

FIGS. 5a-5c are isometric longitudinal sectional views showing a portion of a self-aligning bearing assembly in accordance with an embodiment of the present invention. FIG. 5a illustrates the positions of inner and outer bearing races, and upper and lower thrust rings, within the bearing assembly when a rotating shaft connected to the inner race is aligned with the axial centerline of the bearing assembly housing. FIGS. 5b and 5c illustrate rotational displacement and axial displacement of the bearing races, as well as radial displacements of the thrust rings, when the axis of the rotating shaft is misaligned with respect to the axial centerline of the bearing assembly.

FIG. 6 is a longitudinal sectional view of a portion of a self-aligning bearing assembly showing an anti-rotation pin and a lubricant port extending through the housing of the bearing assembly in accordance with an embodiment of the present invention.

FIG. 7 is a longitudinal sectional view of a self-aligning bearing assembly having an extended inner race with a scalloped lower surface in accordance with an embodiment of the present invention.

DETAILED DESCRIPTION

FIG. 1 is a longitudinal sectional view of a rotatable shaft 5 connected to a self-aligning bearing assembly 10 in accordance with an embodiment of the present invention. In the embodiment shown in FIG. 1, the rotatable shaft 5 is the rotodome flight shaft of an early warning command and control aircraft. Although a rotodome flight shaft is primarily described herein, it is to be understood that other types of rotatable shafts may be used in association with the self-aligning bearing assembly of the present invention. For example, the rotatable shaft could be part of a jet engine drive shaft, electrical generator drive shaft or the like.

3

As illustrated in FIG. 1, the rotatable shaft **5** rotates about its longitudinal axis as shown by the arrow R. The rotatable shaft **5** is subjected to a radial load L_R and an axial load L_A . Such loads may be generated in various ways. For example, when the rotatable shaft **5** is part of an aircraft rotodome support structure, the radial load L_R may be generated during takeoff, flight and landing of the aircraft due to acceleration, air resistance and deceleration of the aircraft. In this case, the direction of the radial load L_R on the rotatable shaft **5** generally corresponds to either the fore or aft direction of the aircraft. When the rotatable shaft **5** is part of a rotodome support structure, the axial load L_A may be generated from downward forces developed during flight of the aircraft as a result of the slight forward slope of the disk-shaped rotodome. In addition, at least part of the axial load L_A may be generated by the weight of the rotodome. The rotodome weight imposes a significant load factor, particularly during landing and take off as might be the case on catapult and arrestment during carrier operations.

In certain embodiments, it may be desirable to include additional bearing assemblies for the rotatable shaft **5**. For example, when the shaft **5** is a rotodome flight shaft, an upper bearing assembly **110** may be connected to the shaft **5**, as shown in FIG. 1.

As shown in FIG. 2, the lower portion of the rotatable shaft **5** is connected directly or indirectly to an inner race **12** of the self-aligning bearing assembly **10**. The bearing assembly **10** also includes an outer race **20**. The bottom end of the rotatable shaft **5** may have holes **7** for connection to a drive assembly (not shown). Although holes **7** are shown in FIG. 2, any other suitable means for connection of the rotatable shaft **5** to a drive assembly may be used. The connection between the rotatable shaft **5** and inner race **12** may be of any suitable design, such as vertically oriented fasteners that pass through vertically oriented clearance holes integral to the inner race and engage threaded holes integral to the flight shaft, mechanical fasteners radially disposed to attach a separate collar that traps the bearing inner race between the collar and the lower shoulder of the flight shaft, and the like.

As shown in FIG. 3, the self-aligning bearing assembly **10** includes a bearing housing **30** within which the inner race **12** is located. As more fully described below, an upper retaining ring **50** and locking tabs **54** secure the various components of the bearing assembly within the housing **30**. As also more fully described below, a pin **60** extends through the bearing housing **30** for securing the outer race **20** against rotation. Holes **34** may be provided through the bottom portion of the bearing housing **30** in order to facilitate attachment of the bearing housing to any suitable type of support structure. The connection between the housing **30** of the bearing assembly and the support structure may be of any suitable design, such as holes **34** integral to a flange located on the upper portion of the housing **30**, or holes integral to flanges on both upper and lower positions of the bearing housing, which may facilitate access to the mechanical connections.

FIG. 4 is a longitudinal sectional view of the self-aligning bearing assembly **10** including the inner race **12**, outer race **20**, upper thrust ring **40**, lower thrust ring **42** and upper retaining ring **50**. The inner race **12** includes a roller bearing channel **14**, and upper and lower ball bearing channels **15** and **16**, respectively. The outer race **20** has an outer spherical curved surface **21**, an upper spherical curved surface **22** and a lower spherical curved surface **23**. As shown in FIG. 4, these curved surfaces can be defined by longitudinal sections taken through the outer bearing race **20**. The outer race **20** includes a roller bearing channel **24**, and upper and lower ball bearing channels **25** and **26**, respectively. Although not

4

shown in FIG. 4, any suitable number and size of roller bearings may be provided in opposing channels **14** and **24**, and any suitable number and size of ball bearings may be provided in opposing channels **15** and **25**, and opposing channels **16** and **26**. Although three bearing channels are shown in FIG. 4, any other desirable number and type of ball bearing and/or roller bearing channels may be used. The rollers and ball bearings used are well known and any configuration may be used, such as angular contact ball bearings, x-type ball bearings and crowned or tapered rollers.

As shown in FIG. 4, the bearing housing **30** includes an inner wall **32** having a cylindrical shape against which a portion of the outer curved surface **21** of the outer race **20** is contacted. A lower retaining rim **36** extends radially inward near the bottom of the housing **30**. An upper retaining ring **50** helps retain the outer race **20** and other components of the bearing assembly within the housing **30**. The upper retaining ring **50** is secured to the housing **30** by locking tabs **54**.

As illustrated in FIG. 4, an upper thrust ring **40** is positioned against the upper curved surface **22** of the outer race **20** and against a thrust surface **52** of the upper retaining ring **50**. A lower thrust ring **42** is positioned against the lower curved surface **23** of the outer race **20** and against a thrust surface of the lower retaining rim **36**. As more fully described below, the upper and lower thrust rings **40** and **42** move radially in opposite directions within the bearing housing **30** when the rotating shaft **5** connected to the inner race **12** is dislocated due to radial or bending loads L_R applied thereto. As illustrated in FIG. 4, in a preferred embodiment of the present invention, the bearing assembly is provided with sliding clearances between components, as more fully described below.

As shown in FIG. 4, the outer spherical curved surface **21** of the outer race **20**, defined by a longitudinal section taken through the outer race, has a radius of curvature R_O that has its center on the axial centerline of the bearing. This central axis coincides with the center axis of the rotating shaft **5**. The radius of curvature R_O is in close proximity to the inner cylindrical surface **32** of the housing **30** while allowing rotational clearance between the center sphere and the cylindrical surface **32**. The upper curved surface **22** of the outer race **20** has a spherical radius of curvature R_U , while the lower curved surface **23** of the outer race **20** has a spherical radius of curvature of R_L . In accordance with an embodiment of the present invention, the radius of curvature R_O of the outer surface **21** is less than the radius of curvature R_U of the upper curved surface **22** and the radius of curvature R_L of the lower curved surface **23**. The upper and lower radii of curvature R_U, R_L are typically 1.05 to 3.5 times greater than the outer radius of curvature R_O , i.e., $R_U, R_L : R_O$ is from about 1.05:1 to about 3.5:1. The upper surface **22** of the outer race **20** defines a spherical surface with its center on the axis of rotation of the bearing. However, the center of the sphere defined by the spherical radius R_U of the upper surface **22** is vertically disposed below the spherical radius R_O of the outer surface **21**. Similarly, the lower surface **23** of the outer race **20** defines a spherical surface with its center on the axis of rotation of the bearing. However, the center of the sphere defined by the spherical radius R_L of the lower surface **23** is vertically disposed above the spherical radius R_O of the outer surface **21**.

In one embodiment, the radius of curvature R_U of the upper curved surface **22** is the same as the radius of curvature R_L of the lower curved surface **23** of the outer race **20**. While this feature is not a necessity, provisions would

5

have to be made in the configuration of the bearing assembly if the the radius of curvature R_U of the upper curved surface **22** is not the same as the radius of curvature R_L of the lower curved surface **23**.

The magnitude of the vertical displacements of the upper and lower spherical surfaces **22** and **23** may be influenced by the magnitude of the axial load to be reacted by the bearing. The smaller the vertical disposition between each of the upper and lower spheres (having radii R_U and R_L , respectively) to the center sphere (having radius R_O), the smaller the projected area available to react axial loads. Conversely, the greater the vertical disposition between the upper and lower sphere to the center sphere, the greater the projected area available to react axial loads.

As shown in FIG. 4, the upper thrust ring **40** has an outer race contact surface **40a** which contacts the upper curved surface **22** of the outer race **20**. The outer race contact surface **40a** of the upper thrust ring **40** may have a shape which substantially matches the curvature of the upper curved surface **22** of the outer race **20**. However, it may be preferred to provide a substantially straight conical shape for the outer race contact surface **40a** in order to reduce and simplify fabrication of the upper thrust ring **40**. In this case, only a limited portion of the outer race contact surface **40a** may touch the upper curved surface **22** of the outer race **20**. The upper thrust ring **40** also has an upper retaining ring contact surface **40b** which contacts the thrust surface **52** of the upper retaining ring **50**. The upper retaining ring contact surface **40b** may be substantially flat in order to conform with the substantially flat thrust surface **52**.

The lower thrust ring **42** preferably has a shape and size that mirrors the upper thrust ring **40**. Thus, the lower thrust ring **42** has an outer race contact surface **42a** which contacts the lower curved surface **23** of the outer race **20**. The lower thrust ring **42** also has a lower retaining rim contact surface **42b** which contacts and slides radially against the thrust surface of the lower retaining rim **36**.

The various components of the bearing assembly **10** may be made of any suitable materials. For example, the housing **30** may be made of steel, bronze, titanium or aluminum, while the inner and outer bearing races **12** and **20** may be made of steel, bronze, titanium or aluminum. The upper and lower thrust rings **40** and **42** may be made of any suitable material such as steel or the like. In one embodiment, the outer race contact surfaces **40a** and **42a** and/or the retaining ring or rim contact surfaces **40b** and **42b** of the thrust rings **40** and **42** may be coated with a lubricant and/or friction reducing material, such as polytetrafluoroethylene or the like.

FIG. 5a illustrates the positions of the inner and outer bearing races **12** and **20**, and the positions of the upper and lower thrust rings **40** and **42**, within the bearing housing **30** when the rotating shaft (not shown) connected to the inner race **12** is aligned with the axial centerline of the bearing housing **30**. In FIG. 5a, the inner and outer races **12** and **20** are positioned within the bearing housing **30** such that all of their axial centerlines are aligned.

FIGS. 5b and 5c illustrate rotational displacements and axial displacements of the bearing races **12** and **20**, as well as radial displacements of the thrust rings **40** and **42**, when the axis of the rotating shaft connected to the inner race **12** is misaligned with respect to the axial centerline of the bearing housing **30** and a downward axial load L_A is applied on the shaft. In FIGS. 5b and 5c, the axial centerlines of the inner and outer races **12** and **20** are misaligned with respect to the axial centerline of the bearing housing **30** due to radial or bending movement in the direction L_R of the rotating shaft

6

to which the inner race **12** is attached. In FIG. 5b, the upper portion of the rotating shaft (not shown) is radially displaced in a leftward or counterclockwise direction shown by the arrow L_R , while in FIG. 5c the upper portion of the rotating shaft (not shown) is radially displaced in a rightward or clockwise direction shown by the arrow L_R .

In FIG. 5b, under load conditions where the axial load L_A on the shaft is in a downward direction and the shaft is displaced in a counterclockwise direction L_R , the outer race **20** undergoes counterclockwise rotational displacement D_R in relation to the straight cylindrical inner wall surface **32** of the bearing housing **30**. In addition, due to the downward axial force L_A on the shaft, the outer race **20** undergoes an upward axial displacement D_A with respect to the straight cylindrical inner wall surface **32** of the bearing housing **30**. The upward axial displacement D_A is caused by a downward vertical displacement of the center of the sphere defined by the lower spherical surface **23** of the outer race **20**, which has the radius R_L shown in FIG. 4. Axial loads push the lower surface **23** of the outer race **20** against the outer race contact surface **42a** of the lower thrust ring **42**. When the center of the sphere defined by radius R_L tries to move in a downward direction, the center of the sphere defined by the radius R_O of the outer race surface **21** (shown in FIG. 4) will be lifted up since the thrust ring **42** is in immediate contact with respect to the lower surface **23**. It follows that when the shaft bends, e.g., due to aerodynamic loading, and the axis of rotation of the shaft misaligned with respect to the housing **30**, the center of the sphere defined by the radius R_L of the lower surface **23** of the outer race **20** will move radially from its undeflected position. Since the thrust ring **42** is always in immediate contact with respect to the lower surface **23** it will be displaced radially in the same direction as the the center of the sphere defined by the radius R_L by virtue of the fact that surface **23** is nested in the conical shape of surface **42**. Similarly, the center of the sphere defined by the radius R_U of the upper surface **22** of the outer race **20** will displace in equal but opposite direction to that of surface **23**. As a consequence, since the thrust ring **40** is always in immediate contact with respect to the upper surface **22**, it will be displaced radially in the same direction as the the center of the sphere defined by the radius R_U by virtue of the fact that surface **22** is nested in the conical shape of surface **40**.

FIG. 5c illustrates what happens when the rotating shaft is radially displaced in a rightward or clockwise direction shown by the arrow L_R , i.e., in the opposite direction compared with FIG. 5b. In FIG. 5c, the outer race **20** undergoes clockwise rotational displacement D_R in relation to the straight cylindrical inner wall surface **32** of the bearing housing **30**. In addition, due to the downward axial force L_A on the shaft, the outer race **20** undergoes an upward axial displacement D_A with respect to the straight cylindrical inner wall surface **32** of the bearing housing **30**. The upward axial displacement D_A is caused by a downward vertical displacement of the center of the sphere defined by radius R_L . Axial loads push the lower surface **23** of the outer race **20** against the outer race contact surface **42a** of the lower thrust ring **42**. When the center of the sphere defined by radius R_L tries to move in a downward direction, the center of the sphere defined by radius R_O will be lifted up since the thrust ring **42** is in immediate contact with respect to the lower surface **23**. It follows that when the flight shaft bends due to aerodynamic loading, and the axis of rotation of the lower portion of the flight shaft misaligned with respect to the housing **30**, the center of the sphere defined by the radius R_L of the lower surface **23** of the outer race **20** will move radially from its undeflected position. Since the thrust ring **42** is always in

immediate contact with respect to the lower surface **23** it will be displaced radially in the same direction as the center of the sphere by virtue of the fact that surface **23** is nested in the conical shape of surface **42**. Similarly, the center of the sphere defined by the radius R_U of the upper surface **22** of the outer bearing **20** will displace in equal but opposite direction to that of surface **23**. As a consequence, since the thrust ring **40** is always in immediate contact with respect to the upper surface **22**, it will be displaced radially in the same direction as the center of the sphere by virtue of the fact that surface **22** is nested in the conical shape of surface **40**.

FIGS. **5b** and **5c** illustrate the rotational and axial displacements D_R and D_A which occur when a downward axial load L_A is applied through the shaft to which the inner race **12** is connected. As shown in both FIGS. **5b** and **5c**, the axial displacement D_A is in an upward direction when the axial load L_A is downward. Alternatively, if the axial load L_A is in an upward direction, the axial displacement D_A would be in a downward direction. In this case, when the axial load L_A is upward, the direction of the arrows D_A would be switched to a downward direction in FIGS. **5b** and **5c**, while the directions of the rotational displacement arrows D_R would remain the same.

FIG. **6** illustrates details of the pin **60** which extends through the bearing housing **30**. The pin **60** has a generally cylindrical shape with a slightly larger diameter portion extending radially inward from the housing **30**. This portion of the pin **60** is received in a groove **61** on the outside of the outer race **20**, which prevents rotation of the outer race **20** around its central axis with respect to the housing, while allowing the displacements D_R and D_A illustrated in FIGS. **5b** and **5c**. Further, the pin **60** may rotate about its axis due to the rotational and axial displacements D_R and D_A of the outer race **20**. Thus, the pin **60** can slide in the groove **61** but prevents the outer race **20** from rotating around its central axis within the housing **30**. The pin **60** includes a lubricant port having a grease fitting **62**. The grease fitting **62** may be of any known design and may be used in conjunction with the application of conventional high pressure grease guns for the injection of a lubricating grease to the rotating elements of the bearing assembly. The port extending through the pin **60** allows lubricating grease to be injected into the housing **30**. A lubricant hole **64** is provided through the outer bearing race **20** in order to allow access of the lubricant to the bearing channels of the inner and outer races **12** and **20**. In a preferred embodiment, two pins **60** are located at diametrically opposed locations around the circumference of the bearing housing **30**. The particular circumferential locations of the pins **60** may be selected based on the likely radial loading direction of the rotatable shaft **5**. For example, when the shaft **5** is a rotodome flight shaft which is typically radially loaded in either the fore or aft direction of the aircraft, the pins **60** may be positioned circumferentially on the sides of the shaft, i.e., rotated 90 degrees from the fore/aft direction of the aircraft. In this manner, misalignment of the pins **60** with the lubricant hole **64** through the outer race **20** may be minimized. Further, contact surfaces **21** and **32** are maximized in the direction of highest load.

FIG. **7** illustrates an alternative inner bearing race configuration for a self-aligning bearing assembly in accordance with an embodiment of the present invention. In this embodiment, the inner race **112** has an extended lower portion having a scalloped edge **114**. Holes **116** are provided through the lower extended portions of the scalloped edge. The holes **116** and scalloped edge **114** configuration may be connected to a drive assembly (not shown). The embodiment

shown in FIG. **7** also includes a sleeve **31** inside the bearing housing **30** which contacts the outer race **20**.

Whereas particular embodiments of this invention have been described above for purposes of illustration, it will be evident to those skilled in the art that numerous variations of the details of the present invention may be made without departing from the invention as defined in the appended claims.

The invention claimed is:

1. A bearing assembly comprising:

a bearing housing having an axial centerline and an inner wall; and

an outer bearing race having an axial centerline and an outer surface, wherein a portion of the outer surface of the outer bearing race contacts the inner wall of the bearing housing, and displacement of the axial centerline of the outer race with respect to the axial centerline of the bearing housing under an axial load applied to the outer race causes rotational displacement and axial displacement of the outer surface of the outer bearing race with respect to the inner wall of the bearing housing, wherein the axial displacement of the outer surface of the outer bearing race is in a direction opposite to the applied axial load.

2. The bearing assembly of claim 1, wherein at least a portion of the inner wall of the bearing housing contacting the outer surface of the outer bearing race is cylindrical.

3. The bearing assembly of claim 1, wherein the inner wall of the bearing housing is integrally formed with the bearing housing.

4. The bearing assembly of claim 1, wherein the outer surface of the outer bearing race is spherical and has a center on the axial centerline of the outer race.

5. The bearing assembly of claim 1, wherein the displacement of the axial centerline of the outer bearing race with respect to the axial centerline of the bearing housing causes a different portion of the outer surface of the outer bearing race to contact the inner wall of the bearing housing.

6. The bearing assembly of claim 1, wherein the displacement of the axial center of the outer bearing race with respect to the axial center of the bearing housing causes a different portion of the inner surface of the bearing housing to contact the outer surface of the outer bearing race.

7. The bearing assembly of claim 1, further comprising an upper thrust ring contacting an upper surface of the outer bearing race, and a lower thrust ring contacting a lower surface of the outer bearing race.

8. The bearing assembly of claim 7, wherein the upper and lower thrust rings are radially displaceable with respect to the axial centerline of the bearing housing.

9. The bearing assembly of claim 8, wherein the radial displacements of the upper and lower thrust rings are in opposite radial directions.

10. The bearing assembly of claim 7, wherein the upper and/or lower surfaces of the outer bearing race are spherically curved along a longitudinal section of the outer bearing race.

11. The bearing assembly of claim 10, wherein the spherically curved upper and lower surfaces of the outer bearing race have substantially the same radius of curvature.

12. The bearing assembly of claim 10, wherein the outer surface of the outer bearing race is spherically curved along a longitudinal section of the outer bearing race.

13. The bearing assembly of claim 12, wherein the radius of curvature of the outer surface of the outer bearing race defines a sphere with a plane of symmetry contacting the inner surface of the bearing housing.

14. The bearing assembly of claim 12, wherein the spherically curved outer surface of the outer bearing race has a radius of curvature less than a radius of curvature of the curved upper or lower surfaces of the outer bearing race.

15. The bearing assembly of claim 14, wherein the radii of curvature of each of the curved upper and lower surfaces of the outer bearing race are from about 1.05 to about 3.5 times greater than the radius of curvature of the curved outer surface of the outer bearing race.

16. The bearing assembly of claim 10, wherein the upper and lower thrust rings have surfaces contacting the outer bearing race which are curved along a longitudinal section of the thrust rings.

17. The bearing assembly of claim 7, wherein the bearing housing comprises a lower retaining rim, and the lower thrust ring is radially slidable in the housing against the lower retaining rim.

18. The bearing assembly of claim 7, further comprising an upper retaining ring installed in the bearing housing, wherein the upper thrust ring is radially slidable in the housing against the upper retaining ring.

19. The bearing assembly of claim 1, further comprising at least one pin extending radially inward from the inner wall of the bearing housing and contacting the outer bearing race, wherein the pin prevents the outer bearing race from rotating around its axial centerline within the bearing housing.

20. The bearing assembly of claim 19, wherein the pin is slidably engaged in a groove in the outer race which is substantially parallel with the axial centerline of the outer race.

21. The bearing assembly of claim 19, wherein the pin includes a lubricant port extending therethrough.

22. The bearing assembly of claim 1, further comprising an inner bearing race disposed radially inside the outer bearing race.

23. The bearing assembly of claim 22, wherein each of the inner and outer bearing races comprise at least one oppositely disposed bearing channel.

24. The bearing assembly of claim 23, wherein the at least one bearing channel is structured and arranged to receive ball bearings.

25. The bearing assembly of claim 23, wherein the at least one bearing channel is structured and arranged to receive roller bearings.

26. The bearing assembly of claim 22, wherein each of the inner and outer bearing races comprise at least two oppositely disposed bearing channels.

27. The bearing assembly of claim 26, wherein the oppositely disposed bearing channels are structured and arranged to receive ball bearings and/or roller bearings.

28. The bearing assembly of claim 22, further comprising at least one lubricant port extending through the bearing housing and communicating with the outer bearing race and the inner bearing race.

29. The bearing assembly of claim 28, wherein the at least one lubricant port extends through a pin which prevents the outer bearing race from rotating around its axial centerline within the bearing housing.

30. The bearing assembly of claim 22, wherein the inner bearing race is structured and arranged for attachment to a rotatable shaft.

31. The bearing assembly of claim 30, wherein the inner bearing race is structured and arranged for attachment near a lower end of the rotatable shaft.

32. The bearing assembly of claim 30, wherein the rotatable shaft is a rotodome flight shaft.

33. A bearing assembly comprising:

a bearing housing having an axial centerline and an inner wall;

an outer bearing race having an axial centerline and an outer surface, wherein a portion of the outer surface of the outer bearing race contacts the inner wall of the bearing housing, and displacement of the axial centerline of the outer race with respect to the axial centerline of the bearing housing causes rotational displacement and axial displacement of the outer surface of the outer bearing race with respect to the inner wall of the bearing housing;

an upper thrust ring contacting an upper surface of the outer bearing race; and

a lower thrust ring contacting a lower surface of the outer bearing race, wherein the upper and lower thrust rings are radially displaceable with respect to the axial centerline of the bearing housing.

34. A bearing assembly comprising:

a bearing housing having an axial centerline and an inner wall;

an outer bearing race having an axial centerline and an outer surface, wherein a portion of the outer surface of the outer bearing race contacts the inner wall of the bearing housing, and displacement of the axial centerline of the outer race with respect to the axial centerline of the bearing housing causes rotational displacement and axial displacement of the outer surface of the outer bearing race with respect to the inner wall of the bearing housing; and

at least one pin extending radially inward from the inner wall of the bearing housing and contacting the outer bearing race, wherein the pin prevents the outer bearing race from rotating around its axial centerline within the bearing housing and the pin includes a lubricant port extending therethrough.

35. A bearing assembly comprising:

a bearing housing having an axial centerline and an inner wall;

an outer bearing race having an axial centerline and an outer surface, wherein a portion of the outer surface of the outer bearing race contacts the inner wall of the bearing housing, and displacement of the axial centerline of the outer race with respect to the axial centerline of the bearing housing causes rotational displacement and axial displacement of the outer surface of the outer bearing race with respect to the inner wall of the bearing housing;

an inner bearing race disposed radially inside the outer bearing race; and

at least one lubricant port extending through the bearing housing and communicating with the outer bearing race and the inner bearing race.

36. A bearing assembly comprising:

a bearing housing having an axial centerline and an inner wall;

an outer bearing race having an axial centerline and an outer surface, wherein a portion of the outer surface of the outer bearing race contacts the inner wall of the bearing housing, and displacement of the axial centerline of the outer race with respect to the axial centerline of the bearing housing causes rotational displacement and axial displacement of the outer surface of the outer bearing race with respect to the inner wall of the bearing housing; and

an inner bearing race disposed radially inside the outer bearing race, wherein the inner bearing race is structured and arranged for attachment to a rotodome flight shaft.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,293,920 B2
APPLICATION NO. : 11/080164
DATED : November 13, 2007
INVENTOR(S) : Aldo Arena

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 6, Line 28 should read


It follows that when the shaft bends, e.g., due to aerodynamic loading, and the axis of rotation of the shaft misaligns with respect to the housing **30**, the center of the sphere defined by the radius R_L of the lower surface **23** of of the outer race **20** will move radially from its undeflected position.

Column 6, Line 64 should read

It follows that when the flight shaft bends due to aerodynamic loading, and the axis of rotation of the lower portion of the flight shaft misaligns with respect to the housing **30**, the center of the sphere defined by the radius R_L of the lower surface **23** of the outer race **20** will move radially from its undeflected position.

Signed and Sealed this

Ninth Day of December, 2008



JON W. DUDAS

Director of the United States Patent and Trademark Office