

US007294259B2

(12) **United States Patent**  
**Cote et al.**

(10) **Patent No.:** **US 7,294,259 B2**  
(45) **Date of Patent:** **Nov. 13, 2007**

(54) **MEMBRANE MODULE FOR GAS TRANSFER**

(75) Inventors: **Pierre Lucien Cote**, Dundas (CA);  
**Hidayat Husain**, Brampton (CA); **Ian Glenn Towe**, Caledon Village (CA)

(73) Assignee: **Zenon Technology Partnership**,  
Wilmington, DE (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 413 days.

(21) Appl. No.: **10/895,959**

(22) Filed: **Jul. 22, 2004**

(65) **Prior Publication Data**

US 2005/0054087 A1 Mar. 10, 2005

**Related U.S. Application Data**

(63) Continuation-in-part of application No. 10/801,660, filed on Mar. 17, 2004, now Pat. No. 7,169,295, which is a continuation of application No. PCT/CA2004/000206, filed on Feb. 13, 2004, and a continuation-in-part of application No. 10/777,204, filed on Feb. 13, 2004, now Pat. No. 7,118,672, and a continuation-in-part of application No. PCT/CA2004/000206, filed on Feb. 13, 2004.

(60) Provisional application No. 60/496,178, filed on Aug. 18, 2003, provisional application No. 60/447,025, filed on Feb. 13, 2003.

(30) **Foreign Application Priority Data**

Aug. 22, 2003	(CA)	2438050
Aug. 22, 2003	(CA)	2438101
Aug. 22, 2003	(CA)	2438432
Aug. 22, 2003	(CA)	2438441
Aug. 22, 2003	(CA)	2438444

(51) **Int. Cl.**  
**C02F 3/00** (2006.01)

(52) **U.S. Cl.** ..... 210/220

(58) **Field of Classification Search** ..... 210/620-628,  
210/220

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

2,458,163 A 1/1949 Hays

(Continued)

**FOREIGN PATENT DOCUMENTS**

CA 1096976 3/1961

(Continued)

**OTHER PUBLICATIONS**

Dr. Michael J. Semmens and Denise Hanus, "Studies of a Membrane Aerated Bioreactor for Wastewater Treatment", Cranfield University, Jun. 1999.

(Continued)


*Primary Examiner*—Chester T. Barry

(74) *Attorney, Agent, or Firm*—Bereskin & Parr

(57) **ABSTRACT**

A membrane module apparatus to transfer a gas to or from a liquid has a sheet having at least one gas transfer surface. The gas transfer surface is in flow communication with a header through a gas channel. The module may be used to support a biofilm on the gas transfer surface. A plurality of sheets or portions of sheets may be separated by spacers.

**10 Claims, 17 Drawing Sheets**



U.S. PATENT DOCUMENTS

4,126,544	A	11/1978	Baensch et al.
4,181,604	A	1/1980	Onishi et al.
4,328,102	A	5/1982	Bellhouse et al.
4,416,993	A	11/1983	McKeown
4,664,681	A	5/1987	Anazawa et al.
4,746,435	A	5/1988	Onishi et al.
4,883,594	A	11/1989	Sekoulov et al.
5,015,421	A	5/1991	Messner
5,034,164	A	7/1991	Semmens
5,116,506	A	5/1992	Williamson et al.
5,126,050	A	6/1992	Irvine et al.
5,149,649	A	9/1992	Miyamori et al.
5,238,562	A	8/1993	Rogut
5,482,859	A	1/1996	Biller
5,486,475	A	1/1996	Kramer et al.
5,518,620	A	5/1996	Eguchi et al.
5,520,812	A	5/1996	Ryhiner et al.
5,543,039	A	8/1996	Odegaard
5,716,689	A	2/1998	Rogut
5,945,002	A	8/1999	Leukes et al.
6,001,585	A	12/1999	Gramer
6,013,511	A	1/2000	Diels et al.
6,183,643	B1	2/2001	Goodley
6,209,855	B1	4/2001	Glassford
6,214,226	B1 *	4/2001	Kobayashi et al. .... 210/500.23
6,241,867	B1	6/2001	Mir
6,309,550	B1	10/2001	Iversen et al.
6,354,444	B1	3/2002	Mahendran et al.
6,361,695	B1	3/2002	Husain et al.
6,387,262	B1	5/2002	Rittmann et al.
6,531,062	B1	3/2003	Whitehill
6,558,549	B2	5/2003	Cote et al.
6,592,759	B2	7/2003	Rable et al.
6,686,832	B2	2/2004	Mahendran et al.
2001/0037967	A1	11/2001	Rabie et al.
2002/0020666	A1	2/2002	Cote et al.
2003/0104192	A1	6/2003	Hester et al.

2004/0115782 A1 6/2004 Paterek


FOREIGN PATENT DOCUMENTS

CA	2005959	8/1990
CA	2100002	2/1994
CA	2102156	7/1994
CA	2182915	2/1997
CA	2356316	8/2000
CA	2300719	9/2001
DE	3544382	6/1987
DE	4440464	6/1996
EP	0 049 954	4/1982
JP	54-21057	2/1979
WO	WO87/03615	8/1987


OTHER PUBLICATIONS

Brindle et al., Nitrification and Oxygen Utilisation in a Membrane Aeration Bioreactor, *Journal of Membrane Science*, 1998.  
 Cote et al., "Bubble-free Aeration Using Membranes: Process Analysis", *Journal Water Pollution Control Federation*, Nov. 1998.  
 Cote et al., "Bubble-free Aeration Using Membranes: Mass Transfer Analysis", *Journal of Membrane Science*, 1989.  
 Yeh, Show-Jong and Charles R. Jenkins, "Pure Oxygen Fixed Film Reactor", *Journal of the Environmental Engineering Division*, Aug. 1978, pp. 611-623.  
 Woolard, C.R., "The Advantages of periodically Operated Biofilm Reactors for the Treatment of Highly Variable Wastewater", *Wat. Sci. Tech.* vol. 35, No. 1. pp. 199-206. 1997.  
 Twarowska-Schmidt, Krystyna and Andrzej Wlochowicz, "Melt-spun Asymmetric Poly(4-methyl-1-pentene) Hollow Fibre Membranes", *Journal of Membrane Science* 137 (1997) 55-61.  
 Yamagiwa et al., "Simultaneous Organic Carbon Removal and Nitrification by Biofilm Formed on Oxygen Enrichment Membrane". *Journal of Chemical Engineering of Japan*, 27(1994) October 638-643.  
 Casey et al., "Review of Membrane Aerated Biofilm Reactors", *Resources, Conservation and Recycling* 27 (1999) 203-215.


\* cited by examiner




**FIG. 1**




**FIG. 2**




**FIG. 3**




**FIG. 4**




**FIG. 5**




**FIG. 6**




**FIG. 7**




**FIG. 8**




**FIG. 9**




**FIG. 10**




**FIG. 11**




**FIG. 12**



**FIG. 13**




**FIG. 14**




**FIG. 15**







**FIG. 16**




**FIG. 17**




**FIG. 18**



**FIG. 19**



**FIG. 20**



**FIG. 21**




FIG. 22







FIG. 23




**FIG. 24**




**FIG. 25**




**FIG. 26**




**FIG. 27**




**FIG. 28**




**FIG. 29**






**FIG. 30**




**FIG. 31**




**FIG. 32**











**FIG. 36**



**FIG. 37**





**FIG. 41**

## 1

MEMBRANE MODULE FOR GAS  
TRANSFER

This application is (1) a continuation-in-part of U.S. Ser. No. 10/801,660 filed Mar. 17, 2004 now U.S. Pat. No. 7,169,295 which is (i) a continuation-in-part of U.S. Ser. No. 10/777,204 filed Feb. 13, 2004 now U.S. Pat. No. 7,118,672 which is an application claiming the benefit under 35 USC 119(e) of U.S. Provisional Patent Application Ser. No. 60/447,025 filed Feb. 13, 2003 (ii) an application claiming the benefit under 35 USC 119(e) of U.S. Provisional Patent Application Ser. No. 60/496,178 filed Aug. 18, 2003; and (iii) a continuation of PCT Application Ser. No. PCT/CA2004/000206, filed Feb. 13, 2004 (2) an application claiming the benefit under 35 USC 119(e) of U.S. Provisional Application Ser. No. 60/496,178 filed Aug. 18, 2003; and (3) a continuation-in-part of PCT Application Ser. No. PCT/CA2004/000206, filed Feb. 13, 2004. This application also claims priority from Canadian Patent Application Nos. 2,438,444; 2,438,441; 2,438,432; 2,438,050; and, 2,438,101 all filed Aug. 22, 2003. All of the applications listed above are incorporated herein in full by this reference to them.

## FIELD OF THE INVENTION

This invention relates to membrane modules to transfer a gas to or from another gas or a liquid for purposes, for example, such as waste water treatment.

## BACKGROUND OF THE INVENTION

Recently, development work has been done on a membrane supported bioreactor concept. For example, U.S. Pat. Nos. 4,181,604 and 4,746,435 describe a process for treating wastewater by supplying oxygen from one side of a gas-permeable membrane to micro-organisms growing on the other side of the membrane. Hollow fibers with porous walls were used as the membrane. In U.S. Pat. No. 5,116,506, a gas permeable membrane divides a reactor vessel into a liquid compartment and a gas compartment. A biofilm is grown on the gas permeable membrane on the liquid side of the membrane. Oxygen and alternate gases pass through the membrane to the bacteria growing on the liquid side of the membrane.

## SUMMARY OF THE INVENTION

It is an object of the invention to improve on the prior art. It is another object of the present invention to provide a membrane module to transfer a gas to or from another gas or a liquid. The following summary provides an introduction to the invention which may reside in a combination or sub-combination of features provided in this summary or in other parts of this document.

According to one aspect of the present invention, membrane modules of various configurations are described. The modules generally include one or more membranes in a planar or sheet form having an inlet for gas at one edge and/or an outlet for gas at another edge. The planar or sheet form may be a continuous surface or a fabric or other structure made up of hollow fibers. The planar or sheet form has a gas transfer surface. A gas channel is connected in flow communication between the gas transfer surface and the inlet or outlet.

In the various embodiments, headers are attached to one or both of these edges to form modules of various configurations. In some embodiments, the modules are further

## 2

assembled into cassettes. Within a cassette, the planar or sheet forms may be separated by spaces of various configurations. The modules are adapted to support a biofilm on the membrane surface but some or all of the embodiments may also be used for other purposes.

## BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding of the present invention and to show more clearly how it may be carried into effect, reference will now be made by way of example, to the accompanying drawings that show embodiments of the present invention, and in which:

FIG. 1 is a front view of one embodiment of a bioreactor apparatus according to the present invention;

FIG. 2 is an enlarged detailed view of a portion of the apparatus of FIG. 1;

FIG. 3 is a perspective view of one embodiment of a growth support sheet according to the present invention;

FIG. 4 is a detailed view of a portion of the sheet of FIG. 3;

FIG. 5 is an enlarged cross-sectional view of a fiber of the sheet of FIG. 3;

FIG. 6 is one embodiment of a membrane module for the apparatus of FIG. 1;

FIG. 7 is a cross sectional view of a portion of the module of FIG. 6;

FIG. 8 is a cross-sectional view of a portion of the module of FIG. 6 taken along the lines 8-8;

FIG. 9 is cross-sectional view of a portion of the module of FIG. 6 taken along the lines 9-9;

FIG. 10 is a perspective view of the module of FIG. 6 having alternative spacing structure;

FIG. 11 is a detailed perspective view of a portion of the spacing structure of FIG. 10;

FIG. 12 is a perspective view of an alternative spacing structure to that of FIG. 11;

FIG. 13 is a perspective view of another alternative spacing structure for the module of FIG. 6;

FIG. 14 is front view of a plurality of the modules of FIG. 6 shown in a vertically stacked arrangement;

FIG. 15 is a perspective view of a plurality of the modules of FIG. 6 shown in a horizontally stacked arrangement;

FIG. 16 is another embodiment of a membrane module for the apparatus of FIG. 1;

FIG. 17 is an enlarged side view of a portion of the module of FIG. 16;

FIG. 18 is a schematic illustration of the module of FIG. 16 during a drain cycle;

FIG. 19 is an alternate configuration of the membrane module of FIG. 16;

FIG. 20 is a top view another embodiment of a membrane module for the apparatus of FIG. 1, having a spiral configuration;

FIG. 21 is a top view of the module of FIG. 20 in an unwound state;

FIG. 22 is a perspective view of the module of FIG. 20;

FIG. 23 is a top view of an alternate configuration of the module of FIG. 20, having adjacent central headers;

FIGS. 24 and 25 show the module of FIG. 23 in an unwound and folded state, respectively;

FIG. 26 shows modules according to FIG. 23 installed in a tank.

FIGS. 27, 28 and 29 shown an unfolded element, folded element and wound element respectively of a square spiral embodiment.

FIGS. 30, 31 and 32 show alternate embodiments of wound modules.

FIG. 33 shows a single sheet module.

FIGS. 34 and 35 show a closed and unfolded view of a header on the module of FIG. 33 respectively.

FIGS. 36 and 37 show elevation and plan views respectively of the module of FIG. 33 installed.

FIG. 38 shows an alternate embodiment of a single sheet module.

FIGS. 39 and 40 show details of the headers of the module of FIG. 38.

FIG. 41 shows an isometric view of an embodiment using a fabric having open portions.

#### DETAILED DESCRIPTION OF THE INVENTION

A bioreactor having a membrane supported biofilm according to the present invention is shown generally at reference character 10 in FIG. 1 and FIG. 2. The bioreactor 10 has a tank 12 containing tank water 14. A biomass or biofilm growth support element 16 is provided in the tank water 14, having a gas permeable membrane portion 17 with a support surface 18 on which microorganisms or biomass 20 can grow.

The membrane portion 17 of the biomass growth support element 16 has a gas interface surface 22 provided opposite the support surface 18. The gas interface surface 22 is open to an air channel 24 with which the growth support element 16 is provided. Gas, such as oxygen or components of air, can diffuse through the membrane portion 17 of the growth support element 16 from the air channel 24 to the support surface 18, and thereby supply oxygen to the biomass 20. Excess gases, if any, may be released to the tank water 14 or ducted back to the atmosphere. The biomass growth support element 16 may optionally have two or more support surfaces 18 and support a biomass 20 on both sides, rather than only on one side as shown.

The growth support elements 16 can be provided in the form of sheets 28, each sheet 28 providing one or more membrane portions 17 with support surfaces 18 and air channels 24.

Referring now to FIG. 3, the sheets 28 can be in the form of a textile sheet 30, constructed of, for example, but not limited to, a set of hollow fibers 32 extending in one direction, and a set of inert fibers 34 extending in a direction transverse to the first set. The sheet 30 may support a layer of biomass 20 on two sides. The sheet 30 has opposed active edges 33 defined by open ends of the hollow fibers 32, and inert edges 35 extending between the active edges 33. Inert edges 35 may have inert fibres 34 folded back to make the adjacent inert fibre 34 or may be confined by a strip of hot melt glue, a hem, or additional lines of stitching or mechanical clips to prevent fraying or unraveling. In making the sheet 30, it can be that two or more adjacent hollow fibers 32 are formed of a single continuous fiber that is folded back on itself at a fold portion 37. The fold portion 37 of the hollow fibers 32 can be severed or punctured to generate the active edges 33. Optionally, the sheet 30 may have hollow fibers 32 running in both directions such that all four of its edges are active edges 33.

The inert fibers 34 can be interconnected with the hollow fibers 32 by means of, for example, but not limited to, various types of knitting, stitching, or weaving so that a cohesive textile sheet 30 is provided. In the embodiment illustrated, the hollow fibers 32 and inert fibers 34 are interconnected by weaving, as best seen in FIG. 4. The fibers

32, 34 are generally parallel and extend directly between the edges 33, 35, but other configurations may also be used.

As best seen in FIG. 5, the hollow fibers 32 have tubular walls 36 that provide the sheet 30 with membrane portions 17. The interior of each hollow fiber 32 defines a lumen 38 that provides the air channel 24 for the sheet 30. The hollow fibers 32 can be made from polymethyl pentene (PMP), which has a high diffusion coefficient for oxygen. The PMP fibers may have dense but gas permeable walls. The hollow fibers 32 may also be made of other substances such as silicone or polyolefins such as PE or PP, also having dense walls or a dense layer, or from hydrophobic materials such as chemically treated PP or PE which has been stretched to create microporous walls, or other substances which are permeable to gases but non-welting and impermeable to liquid water. A sheet construction is described in U.S. Provisional Patent Application Ser. No. 60/447,025, filed on Feb. 13, 2003. The entire text of 60/447,025 is incorporated herein by this reference to it. Sheets 30 can also be planar structures such as those shown in U.S. Pat. No. 6,558,549. The entire text of U.S. Pat. No. 6,558,549 is incorporated herein by this reference to it.

The sheets 28, 30 can be configured in modules, each module providing a header to supply air or other gas to the gas channels 24. The modules can have more than one sheet 28, 30. The sheets 28, 30 in a module can be of a generally flat, planar configuration, or can be in other configurations, such as, for example, but not limited to, spiral configurations.

Referring now to FIG. 6, a first embodiment of a module constructed of the sheet 30 is shown at 100. The module 100 has a plurality of sheets 30 extending between two parallel headers 102a and 102b. In FIG. 6, the module 100 is designed to have about 12 sheets 30, three of which have been illustrated and identified as sheets 30a, 30b, and 30c. The headers 102 may be oriented generally vertically when installed in the tank 12. The header 102a is a gas delivery header, and the header 102b is a gas exhaust header. In some embodiments, the gas exhaust header 102b may be replaced by a dead end header holding one set of ends of the hollow fibers 32 closed or the gas exhaust header 102b may be omitted with one set of ends of the hollow fibers 32 optionally loose or positionally restrained and either closed or open.

The sheets 30 are oriented such that the hollow fibers 32 extend between the headers 102. In this configuration, the hollow fibers 32 may be oriented generally horizontally in use, although they may not follow a straight line across the horizon depending on the method used to make the fabric. The inert fibers 34 may be oriented generally vertically when the module 100 is installed in the tank 12. As best seen in FIG. 7, the headers 102 each have an internal chamber 104, and the ends of the fibers 32 (defining the active edge 33) are potted in the headers 102 so that the lumens 38 of the fibers 32 are in flow communication with the chambers 104 of the headers 102. Ports 106 can be provided in the headers 102, extending through the housing of the headers 102 to the chambers 104.

Spacers 110 may be provided between adjacent sheets 30 in the module 100. As best seen in FIG. 8, in the embodiment illustrated, each spacer 110 has a base portion 112 that is generally square-shaped with connection means 114 extending from either side of the base 112 so that adjacent spacers 110 can be connected together in a snap-fit arrangement. The connection means 114 can comprise a recess 116 with a retaining lip 118 on one side of the base portion 112, and axially extending fingers 120 with transverse protrusions

122 on the other side of the base portion 112, to engage the lip 118. Alternately spacers 110 may be made of simple blocks or buttons glued to the sheets 30. As a further alternate embodiment, spacers 110' can be provided having a central through-hole 12' through which a retaining rod 123 5 can be inserted (see FIG. 6). The ends of the rod 123 can be bent or capped to hold a set of adjacent spacers 10' together. Further alternatively, the headers 102 may be held apart by a restraining structure and the sheets 30 tensioned so that they stay apart without the aid of spacers. The sheets 30 may be tensioned, for example, by increasing the space between the headers 102 or by heat shrinking the sheets 30 between headers 102 spaced at a fixed distance.

The spacers 110 can be further provided with an abutment surface 124 to keep the base portions 112 of adjacent spacers 110 from contacting each other when assembled, or in other words, to maintain a gap 125 to accommodate the hollow fibers 32 extending between adjacent spacers 110 without being pinched or crushed flat. The spacers 110 can be constructed of an injection molded polymer material.

To install the spacers 110, the fingers 120 of one spacer 110 can be forced between the weaved hollow fibers 32 and inert fibers 34 of the sheet 30, and then into the recess 116 of an adjacent spacer 110 to snap the spacers together. When assembling the adjacent spacers 110, care should be taken to clear any hollow fibers 32 off of the abutment surface 124 before snapping the spacers 110 together. One or more hollow fibers 32 can be inserted in the recess 126 between the fingers 120 so that any hollow fibers 32 between the two fingers 120 will not be pinched. Alternatively, the spacers 110 can be configured to connect to each other outside the edges 35 of the sheets 30.

The spacers 110 can be attached spaced in a row along the lower inert edges 35 of the sheets 30. By providing a row of spacers 110 adjacent the bottom of the sheets 30 in the module 100, the lower inert edges 35 of the sheets can be maintained in spaced apart relation, and upwardly directed currents in the tank water 14 may be sufficient to maintain the spacing and/or to control sludge build-up across adjacent sheets 30 upward of the lower edges 35. Maintaining a space between adjacent sheets 30 is useful as it inhibits the biofilm 20 of one sheet 30 from merging with the biofilm 20 of an adjacent sheet 30 and allows entry of air bubbles which can be used to remove excess biofilm 20.

The module 100 can have an additional row of spacers 110 along the upper inert edges 35 of the sheets 30. Spacers 110 can also be provided between the upper and lower inert edges 35 of the sheets 30. By aligning the spacers 110 in rows and columns, the spacers 110 can be provided in a grid 50 pattern.

As an example, a module 100 having six sheets 30 pulled taut between the headers 102a and 102b was provided. Each sheet 30 had a length of 1-5 m (extending between the headers 102a and 102b) and a height of 0.5 m. Rows of spacers 110' were provided along the lower edge of the parallel sheets 30, at 20 cm intervals between the headers 102a and 102b. Each row of spacers 110' included five spacers 110', each of the five spacers 110' being positioned between two adjacent sheets 30. Each spacer 110' was 15 mm×15 mm×6 mm thick. The lower edges 35 of the sheets 30 were hemmed to prevent unraveling, and a rod 123 was pressed through the hemmed portion (and through the holes 121 in the spacers 110') and the ends of the rod 123 were bent over to secure the spacers 110' in position. Aeration was applied from below the module 100 at a rate of 0.8 SCFM, per foot of module length, with satisfactory results.

Referring now to FIG. 9, the spacing between the fibers 32 at the fiber ends potted in the header can be reduced. For example, the ends of the fibers 32 can converge towards a narrower header 102. This can reduce the size of the headers 102, which can improve circulation fluid flow characteristics in the tank 12 around the headers 102, and can reduce costs by, for example, reducing the volume of potting resin in the header 102. An offset block 108 can be provided adjacent one or both sides of the narrowed header 102 so that multiple modules 100 can be packed together in side-by-side arrangements (see also FIG. 15). The offset block 108 may connect to side plates 109 to keep tank water from reaching an area of un-spaced sheets 30.

Referring now to FIGS. 10 and 11, as an alternative to one or more of the rows of spacers 110, the module 100 can be provided with fluid permeable spacing strips 150. In the embodiment illustrated, the spacing strips 150 are provided adjacent the lower and upper inert edges of the sheets 30. Each spacing strip 150 comprises a length of a flow permeable spacing structure 154 extending between the headers 102. The spacing strips 150 have opposed ends 152 that are secured to the headers 102. The ends 152 can be potted in the headers 102.

The spacing strips 150 have sufficient compressive stiffness to maintain the desired spacing between adjacent sheets 30 in the module 100, yet are porous or otherwise minimally obstructing to tank water 14 circulating in the tank 12 in a generally upward direction, through the spacing strip 150, between adjacent sheets 30.

As best seen in an embodiment illustrated in FIG. 11, the flow-permeable spacing structure 154 can comprise a lattice arrangement of plastic segments 156 providing a generally hollow elongate structure with a rectangular cross-section. The spacing structure 154 may also be a rigid plastic mesh of a configuration and construction as used as a spacer for spiral wound reverse osmosis modules. In embodiment illustrated in FIG. 12, the flow-permeable spacing structure 154 of the spacing strip 150 comprises a length of plastic 158 having vertical through-holes 160 along its length. The spacing structure 150 can be formed of, for example, but not limited to, an injection-molded polymer. The spacing strips 150 can present side surfaces 151 to which the sheets 30 can be adhered.

Referring now to FIG. 13, another alternative spacing structure 170 can be provided for the module 100. The spacing structure 170 comprises a substantially rigid band folded over to form a thin clip that can be secured to the sheet 30 adjacent the inert edges 35. The spacing structure 170 can be provided with horizontally outwardly protruding ridges 172 extending from one or both sides of the structure 170, at discrete points along its length. The ridges 172 can abut the spacing structures 170 attached to adjacent sheets 30 in the module 100, so that the desired gap is maintained between the sheets 30. Circulation currents in the tank water 14 can flow between the ridges 172 and adjacent spacing structures 170.

Referring now to FIGS. 14 and 15, the modules 100 can be conveniently stacked vertically and/or horizontally (side-by-side) to provide a reactor cube or cluster that efficiently uses the available space in the tank 12. The headers 102 may be provided with snap-fitting male and female elements in the ports 106 so that vertically adjacent headers 102 are releasably attached to each other (FIG. 14). A duct 107 can extend across and be releasably attached to the upper ports 106 of a side-by-side stack of modules 100 (FIG. 15). The modules 100 may rest on blocks on the bottom of a tank 12. Solid plates (not shown), for example of PVC, may be

placed between horizontally adjacent headers **102** and attached to at least one, and optionally both headers **102** of a module **100**. The plates may be shared between and attached to each of a pair of adjacent headers **102** or attached only to one header **102**. By any of these methods, modules **100** or sets of modules **100** attached to each may have their headers **102** spaced by the plates. The modules **100**, or sets of modules **100**, may be placed in an oven to shrink and tension the sheets **30** which may remove the need for spacers **110**.

A second module embodiment is shown generally at **200** in FIG. **16**. The module **200** has a single header **202** that may be oriented horizontally when installed in the tank **12**.

Sheets **30** extend upwardly from the header **202**, and the sheets **30** are oriented such that the hollow fibers **32** extend generally vertically and the inert fibers **34** extend generally horizontally. The lower active edges **33** of the sheets **30** are potted in the header **202**.

In the embodiment illustrated, the upper active edges **33** of the sheets **30** extend above the surface of the tank water **14** in the tank **12**, and are open to atmosphere. Alternately, the upper active edges **33** may be sealed shut to produce a dead end module. An optional cap **205** may be provided adjacent the upper ends of the hollow fibers **32** to protect the upper ends from intrusion of dirt or debris, and prevent the fabric sheet **30** from unraveling. The cap **205** can be buoyant to support the upper active edge **33** of the sheets **30** above the surface of the tank water **14**. Alternatively, the upper edges **33** of the sheets **30** can be below the surface of the tank water **14** if the gas pressure in the lumens **38** is sufficient to prevent water intrusion.

As best seen in FIGS. **16** and **17**, in the embodiment illustrated, the cap **205** is in the form of an elongate tubular member **207** that is clipped on to, and extends horizontally in use along, the upper active edges **33** of the sheets **30**. The tubular member **207** has a width **209** (or diameter) such that the outer surfaces of caps **205** of adjacent sheets **30** abut each other and thereby assist in maintaining a desired gap **211** between adjacent sheets **30** in the module **200**.

To facilitate holding the upper active edges **33** of the sheets **30** above the surface of the tank water **14**, the module **200** can be provided with hooks **213** extending upwards from the upper edges **33** of the sheets **30**. Suspending means **215**, such as, for example, but not limited to, a cable or rod, can engage the hooks **213** to support the upper edges **33** of the sheets **30**. The hooks **213** can extend from the caps **205**.

Referring now to FIG. **19**, the single header module **200** can be configured to have the header **202** at the upper end of the sheets, with the sheets **30** extending vertically downward from the header **30** when installed in the tank **12**. Weights **221** can be attached to the lower active edges **33** of the sheets **30** to maintain the vertical orientation of the hollow fibers **32**. This may be particularly necessary where the sheets **30** are buoyant.

The lower edges **33** of the sheets **30** may be left open to release excess gas supplied to the fibers and/or to vent any gasses that may have diffused from the biomass **20** into the lumens **38**. The tank water **14** adjacent the open ends may provide some back pressure to the gas in the hollow fibers **32** which may encourage greater transfer of oxygen through the membrane portions **17**. Alternately, a single sheet header as shown for other embodiments may be used to collect gases at the lower end of the sheets **30** and connected to a tube to release those gases above the water surface.

As a further alternative, the module **200** can be provided with hollow fibers **32** oriented in a U-shaped configuration, such that the second end of the hollow fibers **32** are

supported above the surface of the tank water, adjacent the header **202**, and the central section of each fiber is secured to a lower portion of the tank **12**, or weighted down.

A third module embodiment **300**, having sheets configured in a spiral arrangement, is shown in FIG. **20**. The module **300** is formed of at least one sheet **30** having hollow fibers **32** extending between opposed headers **302a** and **302b**, and a spacing structure **310** provided adjacent the sheets **30** (FIG. **21**). In the embodiment illustrated, the spacing structure **310** comprises a corrugated layer provided adjacent the sheet **30**, providing vertical channels **331** through which tank water **14** can circulate when the module **300** is installed in the tank **12**. Other spacing structures **310** may also be used, such as a rigid plastic mesh, for example, of the configuration and construction of spacers for spiral wound reverse osmosis modules. The corrugated layer **310** can be made of an extruded plastic.

Referring to FIGS. **20** and **22**, the spiral configuration of the module **300** can be provided by winding one of the headers **302** with its attached one or more sheets **30** and corrugated layers **310** around the other header **302** in spirals of increasing radius. The wound bundle can be inserted into a generally cylindrical tank or cage **321** to hold the sheets/layers in the spiral configuration. The module **300** according to this configuration has one header (**302a**) extending generally along the axis of the spiral module **300**, and the second header (**302b**) disposed adjacent the outer periphery of the spiral.

It can be advantageous (for piping and/or other reasons) to provide the delivery and exhaust headers **302a** and **302b** in closer proximity to one another. Such an arrangement is shown in the module **300** in FIG. **23**, where the two headers **302a** and **302b** extend adjacent each other generally along the axis of the spiral module **300**. This module can be formed by providing sheets **30** spacing structures **310** between the headers **302a** and **302b** (FIG. **24**), and folding the sheet layers in half so that the headers **302a** and **302b** are adjacent each other (FIG. **25**). The folded portion of the sheet is then wound around both headers **302a** and **302b** in spirals of increasing radius. In the embodiment illustrated, the module **300** has a single sheet **30** extending between the headers **302**, sandwiched by a spacing structure (corrugated layer) **310** on either side. The corrugated layer **310** itself is only about the half the actual desired spacing width, since the layer **310** will generally be doubled (two layers **310** side-by-side) when the module **300** is configured in the spiral arrangement (FIG. **23**).

The spacing structure **310** need not be in the form of a corrugated layer, but can take the form of, for example, but not limited to, sheets **30** having lateral protrusions extending from the surface of the sheets **30**. The protrusions can be formed from the sheets **30** by pressing or embossing, or the protrusions can be separately attached buttons that are adhered to the surface of the sheets. As a further alternative spacing structure **310**, the sheets **30** can be provided with a stiffness that can urge the sheets **30** to unwind from the confined spiral form. To obtain the desired stiffness, horizontal stiffener elements can be secured to the sheets **30**. Alternatively, the hollow fibers can be constructed to have an inherent stiffness that may provide sufficient unwinding force without the addition of separate stiffener elements. As a result of the unwinding force, each spiral portion of the sheets **30** in the module **300** can space itself evenly apart from adjacent spiral portions, thus providing the desired gap.

As best seen in FIG. **26**, the modules **300** can be packed in the tank **12** to provide a reactor. The modules **300** can be packed in rows, and the upper ends of the delivery headers

**302a** in each row can be attached to a single channel gas delivery manifold **335**, which can in turn be connected to a supply main **337**. A module **300** may also be placed inside of a hollow pipe which functions as a container for a reactor.

The upper ends of the exhaust headers **302b** can exhaust to atmosphere. Alternatively, the manifolds **335** can be dual channel manifolds having a delivery conduit **335a** and an exhaust conduit **335b**. The headers **302a** and **302b** can be connected to the conduits **335a** and **335b**, respectively.

As best seen in FIG. 27, the sheets **30** (and layers **310** in the embodiment illustrated) of the modules **300** can be wound in a generally square spiral rather than a circular spiral to increase the packing density of the modules **300** in the tank **12**. To facilitate forming a square spiral in the embodiment illustrated, corner elements **350** are provided along the length of the corrugated layer **310** on one side of the sheet **30**, at selected locations along the length of the layer **310** (FIG. 29). The locations for the corner elements **350** are selected so that when the module **300** is folded over (FIG. 29) and wrapped into a spiral (FIG. 27), the corner elements **350** are aligned at desired corner locations of the spiral. The sheet **30** and layers **310** of the spiral module **300** can follow the contour of the corner elements **350** to assist in forming a square shaped spiral. The corner elements **350** can be formed of, for example, but not limited to, an extruded right angle bracket that extends the height of the module **300**. Alternately, the corner elements **350** can be inserted as the sheets **30** are being wound.

Alternate spiral designs for the module **300** are also possible. As an example, module **300** as illustrated in FIG. 30 has a single central gas delivery header **302a** disposed as a hub with a plurality of sheets **30** and exhaust header **302b** extending radially outwardly from the header **302a**. The sheets **30** with exhaust headers **302b** can be wound together around the header **302a** to form a spiral configuration (FIG. 31). Any suitable spacing structure **310** (not illustrated) can be provided between the wound sheets **30** to provide a desired spacing between the sheets **30**.

Another spiral configuration for the module **300**, best seen in FIG. 32, has the sheet **30** extending between the headers **302a** and **302b**. A portion of the sheet **30** is wound around the header **302b**, and another portion of the sheet **30** is wound around the header **302a**, thereby forming a double spiral configuration.

Referring now to FIG. 33, another embodiment of a module **400** has a sheet **30** with a fixed width **401** and a continuous length extending transverse to the width **401**. The hollow fibers **32** extend along the width **401** of the sheet **30**, and are oriented in the weft direction. The inert fibers **34** are oriented in the warp direction. By being formed with a continuous length, the sheet **30** can be customized to have a length fit for any particular size of tank **12**.

The module **400** has headers **402** in the form of ducts that extend continuously along the length of the sheet **30**. More particularly, a gas delivery duct **402a** and a gas exhaust duct **402b** extend along opposite active edges **33** of the sheet **30**. The headers or ducts **402** are also formed of a continuous length, and can be, for example, an extruded polymer material.

Further details of the ducts **402** can be seen in FIGS. 34 and 35. The duct **402** can be an extrusion having two concave shell portions **433** and **435**, which can be positioned opposite each other to form a hollow interior cavity **437**. The shells **433**, **435** can be positioned along the active edge **33** of the sheet **30** so that the open ends of the hollow fibers **32** are inside the cavity **437**. A sealant bead **441** can be applied between the edges of the shells **433**, **435** adjacent the sheet

**30** to seal the duct **402**. The shells **433**, **435** can also be sealed opposite the sheet **30**, or that side can be provided with a hinge portion **439** so that the duct **402** has just the one seam along the sheet **30**.

In use, the modules **400** are oriented in the tank **12** such that the ducts **402** are oriented vertically as shown in FIGS. 36 and 37. The length of the module **400** can conveniently be cut to fit the height of the tank **12**. Multiple modules **400** can be arranged side-by-side within the tank **12**, and the ducts **402** can have a width **443** such that the ducts **402** of adjacent modules **400** abut to maintain a desired gap between the sheets **30** (FIG. 37). Feed and exhaust mains **452a** and **452b**, respectively, can be provided for attachment to the headers **402a** and **402b**. The bottom of the sheet **30** may be weighted or otherwise biased towards or attached to the bottom of a tank **12**. Lower ends of the ducts **402** are sealed closed.

Referring now to FIG. 38, a modified module **500** is similar to module **400** but has the sheet **30** formed with the hollow fibers **32** extending along a continuous length in the warp direction. Gas delivery and exhaust headers **502a**, **502b** extend along the width **501** of the module **500**, spaced apart from each other periodically along the length of the module **500**. The distance between the headers **502a**, **502b** can be determined based on a number of process factors such as the pressure drop per unit length of hollow fiber **32**. Lower ends of the headers **502** may be sealed. Upper ends of headers **502** may be connected to larger exhaust or inlet pipes. The module **500** may be folded in a Z-pattern such that feed headers **502a** form a line and exhaust headers **502b** form a second line to facilitate connection to larger feed or exhaust pipes.

The headers **502** can be of two-piece construction having two concave shell portions **533** and **535** positioned opposite each other to form a hollow interior cavity **537**. The shells **533**, **535** are on opposite sides of the hollow fibers **32**, which extend perpendicularly and continuously between the shells **533**, **535** (FIG. 39). A sealant bead **541** can be applied between the edges of the shells **533**, **535** adjacent the sheet **30** to seal the edges against the sheet **30**. A hollow cylindrical punch can then be pressed through the length of the cavity **537** to cut open the ends of the hollow fibers **32** so that the hollow fibers **32** are in flow communication with the headers **502**.

Referring now to FIG. 41, another module embodiment **600** has sheets **30** with pattern weaving extending between headers **602**. The pattern weaved sheets **30** have alternating loosely weaved zones **631** and tightly weaved zones **633**. The modules **600** may be oriented flat (i.e. in a substantially horizontal plane) when installed in the tank **12**. Multiple modules **600** can be stacked on top of each other to form a reactor cluster. Adjacent modules can have loose and tight weave zones **631**, **633** in reverse locations so that the loose weave zones **631** in one module is sandwiched by tight weave zones **633** of adjacent modules. This arrangement can provide a sinuous flow path for circulation currents in the tank water **14**. Alternatively, the loose and tight weave zones **631**, **633** of adjacent modules **600** can be in vertical alignment so that the aligned loose weave zones **633** provide vertical flow paths that are generally straight. The sheets **30** of this embodiment may be closely spaced, for example less than 4 mm or less than 2 mm spacing, or be adjacent each other, or separated only by the potting materials. Other modules may have a larger spacing, for example between 2 mm and 20 mm or between 4 mm and 12 mm.

While preferred embodiments of the invention have been described herein in detail, it is to be understood that this



## 11

description is by way of example only, and is not intended to be limiting. Other embodiments may be made or performed within the scope of the invention which is defined by the following claims.

We claim:

1. A membrane module apparatus to transfer a gas to or from another gas or a liquid, the apparatus comprising:

- a) a sheet having at least one gas transfer surface,
- b) a gas channel in flow communication with the gas transfer surface; and
- c) a header in flow communication with the gas channel, wherein the sheet is a textile sheet comprising hollow fibers.

2. The apparatus according to claim 1, wherein the walls of the hollow fibers comprise the gas transfer surface.

3. The apparatus according to claim 1, wherein the hollow fibers are constructed of a thermoplastic polymer.

4. The apparatus according to claim 1, wherein the sheet further comprises inert fibers.

5. The apparatus according to claim 4, wherein the hollow fibers and inert fibers are knitted, weaved, or stitched together to form the sheet.

## 12

6. The apparatus according to claim 1, comprising a gas delivery header and a gas exhaust header.

7. The apparatus according to claim 6, wherein the hollow fibers extend between and are in fluid communication with the gas delivery header and gas exhaust header.

8. A membrane module apparatus to transfer a gas to or from another gas or a liquid, the apparatus comprising:

- a) two headers and a plurality of generally parallel sheets extending between the two headers;
- b) each sheet having at least one gas transfer surface;
- c) a gas channel in flow communication with the at least one gas transfer surface, the headers in flow communication with the gas channel; and
- d) spacers between adjacent parallel sheets.

9. The apparatus according to claim 8 wherein the spacers comprise a spacer block positioned between adjacent sheets.

10. The apparatus according to claim 8 wherein the headers pull each sheet taut so that adjacent sheets remain spaced apart from each other.

\* \* \* \* \*