



US007320405B2

(12) **United States Patent**
Stahl

(10) **Patent No.:** **US 7,320,405 B2**
(45) **Date of Patent:** ***Jan. 22, 2008**

(54) **MULTI-LEVEL STACKING/NESTING TRAY**

(56) **References Cited**

(75) Inventor: **Edward L. Stahl**, Tyler, TX (US)

U.S. PATENT DOCUMENTS

(73) Assignee: **Norseman Plastics, Ltd.**, Rexdale, Ontario (CA)

2,026,204 A 12/1935 Andrews
(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 121 days.

FOREIGN PATENT DOCUMENTS

CA 892971 2/1972
(Continued)

This patent is subject to a terminal disclaimer.

OTHER PUBLICATIONS

Canadian Office Action issued Nov. 24, 2005 in Canadian Application No. 2,408,247.

(21) Appl. No.: **10/275,735**

(Continued)

(22) PCT Filed: **May 9, 2001**

Primary Examiner—Anthony D. Stashick

Assistant Examiner—Harry A. Grosso

(86) PCT No.: **PCT/CA01/00640**

(74) *Attorney, Agent, or Firm*—Katten Muchin Rosenman LLP; Mark W. Hrozenchik; Richard P. Bauer

§ 371 (c)(1),
(2), (4) Date: **Jun. 17, 2003**

(87) PCT Pub. No.: **WO01/85558**

PCT Pub. Date: **Nov. 15, 2001**

(65) **Prior Publication Data**

US 2004/0060844 A1 Apr. 1, 2004

(51) **Int. Cl.**
B65D 21/00 (2006.01)
B65D 85/62 (2006.01)


(57) **ABSTRACT**

A novel container (20) for transport or storage of products such as bread, buns, or other goods. In one embodiment, there is provided a nestable container with a base (24) and sidewalls (28, 32) that can be stacked in two positions for different products and can be nested when empty for compact storage. The container has levered positions for lifting out of each stacking position and into a corresponding sliding position. The sliding positions can be used to offset the container or containers from the stack and reduce the strain on the operator when lifting for destacking. Alternatively, the container can slide in the opposite direction for stacking in either position. Thus the operator can set the container down, offset from the stack, in the sliding position and slide into stacking position. Back strain can be reduced during stacking and destacking as the operator does not have to extend or lean over the stack to pick up or set down the containers.

(52) **U.S. Cl.** **206/509; 206/519**

(58) **Field of Classification Search** 206/507,
206/509, 505, 511, 518, 519, 520; 220/4.27
See application file for complete search history.

34 Claims, 24 Drawing Sheets



U.S. PATENT DOCUMENTS					
2,029,746 A	2/1936	Tufts et al.	D348,342 S	6/1994	Lang-Ree et al.
2,061,414 A	11/1936	Tufts et al.	D348,343 S	6/1994	Lang-Ree et al.
2,389,010 A	11/1945	Traumuller	D350,028 S	8/1994	Apps
2,442,723 A	6/1948	Economakis	D350,437 S	9/1994	Apps et al.
2,457,841 A *	1/1949	Smith et al. 220/1.5	5,344,021 A	9/1994	Rose
2,457,842 A *	1/1949	Smith et al. 220/1.5	5,344,022 A	9/1994	Stahl 206/507
2,641,383 A	8/1953	Coursey	5,372,257 A	12/1994	Beauchamp et al.
3,375,953 A	4/1968	Miller, Jr.	D354,167 S	1/1995	Stahl
3,379,339 A	4/1968	Asenbauer	5,377,858 A	1/1995	Morris, Sr.
3,387,740 A	6/1968	Bockenstette	5,415,293 A	5/1995	Ackermann et al.
3,392,875 A	7/1968	Bockenstette	5,469,986 A	11/1995	Jang
3,420,402 A	1/1969	Frater et al.	5,494,163 A	2/1996	Apps
3,421,656 A	1/1969	Asenbauer	D374,555 S	10/1996	McMath
3,507,697 A	4/1970	Korman	5,582,296 A	12/1996	Beauchamp et al.
3,659,743 A	5/1972	Box	5,609,254 A	3/1997	Loftus et al.
3,752,352 A	8/1973	Senecal	D379,718 S	6/1997	Raghunathan
3,780,905 A	12/1973	Herolzer	D381,203 S	7/1997	Ackermann et al.
D236,168 S	7/1975	Johnson	D384,975 S	10/1997	Jackson
3,907,111 A	9/1975	Levenhagen 206/511	5,735,431 A	4/1998	LeTrudet
3,934,724 A	1/1976	Johnson	5,752,602 A	5/1998	Ackermann et al. 206/507
3,951,265 A	4/1976	Carroll	5,772,033 A	6/1998	Loftus et al.
3,952,903 A	4/1976	Sanders et al.	D398,448 S	9/1998	Zanni
3,993,211 A	11/1976	Astle	5,816,406 A	10/1998	Jupille et al. 206/561
4,000,817 A	1/1977	Sanders et al.	D400,711 S	11/1998	Hwang
4,093,070 A	6/1978	Stahl	D401,066 S	11/1998	Ackermann
4,093,071 A	6/1978	Stahl et al.	D401,412 S	11/1998	LeTrudet
4,102,453 A	7/1978	Carroll et al.	5,860,527 A	1/1999	Frankenberg et al. 206/509
4,105,117 A	8/1978	Atkin et al.	5,881,902 A *	3/1999	Ackermann 206/509
4,106,623 A	8/1978	Carroll et al.	5,896,987 A	4/1999	Bettenhausen 206/370
4,106,624 A	8/1978	Thurman	5,975,324 A	11/1999	Schmitt
4,106,625 A	8/1978	Carroll et al.	5,992,673 A	11/1999	Hwang
4,109,791 A	8/1978	Clipson et al.	D420,219 S	2/2000	Jensen et al.
4,189,052 A	2/1980	Carroll et al.	6,036,049 A	3/2000	Hwang
4,194,626 A	3/1980	Boller 206/509	D423,217 S	4/2000	Varfeldt
4,211,327 A	7/1980	Stahl et al.	D424,299 S	5/2000	Varfeldt
D258,050 S	1/1981	Cornou	D429,565 S	8/2000	Aiken
4,247,004 A	1/1981	Bird	6,098,827 A	8/2000	Overholt et al.
4,249,671 A	2/1981	Crolli	D436,729 S	1/2001	Aiken
4,320,837 A	3/1982	Carroll et al.	D439,049 S	3/2001	Koefeld
D269,017 S	5/1983	Martin	6,209,742 B1	4/2001	Overholt et al.
4,391,369 A	7/1983	Stahl et al.	6,250,490 B1	6/2001	Loftus
4,423,813 A	1/1984	Kreeger et al.	D444,950 S	7/2001	Hwang
4,426,001 A	1/1984	Stahl et al.	6,260,706 B1 *	7/2001	Koefeld 206/505
4,440,302 A	4/1984	Ehrman et al.	D446,017 S	8/2001	Koefeld
4,466,541 A	8/1984	Tabler et al.	D446,939 S	8/2001	Koefeld
4,520,928 A	6/1985	Wilson	6,273,259 B1	8/2001	Stahl
4,523,681 A	6/1985	Kreeger	6,293,418 B1	9/2001	Ogden et al.
4,573,577 A	3/1986	Miller	6,308,858 B1	10/2001	Koefeld
4,577,759 A	3/1986	Kreeger	6,338,181 B1	1/2002	Hwang
4,600,103 A	7/1986	Tabler	6,386,388 B1	5/2002	Overholt
4,601,393 A	7/1986	Veenman et al.	6,394,274 B1	5/2002	Cheeseman
RE32,223 E	8/1986	Kreeger et al.	6,398,054 B1	6/2002	Overholt et al.
4,619,366 A	10/1986	Kreeger	D460,619 S	7/2002	Koefeld
4,619,371 A	10/1986	Rehrig	D463,667 S	10/2002	Hwang
4,643,310 A	2/1987	Deaton et al.	D477,146 S	7/2003	Hwang
4,671,411 A	6/1987	Rehrig et al.	D478,421 S	8/2003	Overholt
D292,634 S	11/1987	Chabot	6,601,724 B1	8/2003	Koefeld et al.
4,848,578 A	7/1989	Schafer	6,607,199 B2	8/2003	Gruber
4,905,833 A	3/1990	Kreeger et al.	6,631,822 B1	10/2003	Overholt
4,936,458 A	6/1990	Tabler et al.	6,811,125 B1	11/2004	Koefeld et al.
4,960,207 A *	10/1990	Tabler et al. 206/507	6,857,642 B2	2/2005	Gruber
4,982,844 A	1/1991	Madan et al.	6,880,705 B2	4/2005	Otting et al.
5,035,326 A	7/1991	Stahl	6,886,710 B2	5/2005	Verna et al.
D319,908 S	9/1991	Stahl	6,918,502 B1	7/2005	Overholt et al.
D320,298 S	9/1991	Apps et al.	6,918,508 B2	7/2005	Hwang
5,163,587 A	11/1992	Apps et al.	7,044,319 B2	5/2006	Overholt et al.
D334,412 S	3/1993	Feer	7,104,553 B2	9/2006	Gruber
D343,042 S	1/1994	Apps et al.	2002/0056717 A1	5/2002	Hwang
D344,387 S	2/1994	Holliday	2002/0130132 A1	9/2002	Overholt
5,287,966 A	2/1994	Stahl	2002/0153682 A1	10/2002	Gruber
D348,138 S	6/1994	Lang-Ree et al.			

2004/0050742 A1 3/2004 Gruber
2006/0070906 A1 4/2006 Verna

FOREIGN PATENT DOCUMENTS

CA	1273881	9/1990
CA	2032012	6/1991
CA	2130973	1/1995
CA	2129617	2/1995
CA	2212239	8/1996
CA	2484830	8/1996
CA	2313137	7/1999
CA	2296895	7/2000
CA	2 389 010 A1	3/2001
CA	2326118	5/2001
CA	2387491	5/2001
CA	2392265	6/2001
CA	2395367	7/2001
CA	2397522	8/2001
CA	2384941	1/2002
CA	2421595	3/2002
CA	2426949	5/2002
CA	2442723	10/2002
CA	2455355	2/2003
CA	2458773	3/2003
CA	2472360	7/2003
CA	2475531	9/2003
CA	2485544	12/2003
CA	2248920	7/2004
EP	0370771 A2 *	5/1990
FR	1131652	10/1956

FR	2678585	8/1993
GB	2067167	7/1981
GB	2129401	5/1984
GB	2137167	10/1984
GB	2141778	1/1985
GB	2171980	9/1986
GB	2180821	4/1987
TW	338405	8/1998
TW	372539	10/1999
WO	00/0027716	5/2000
WO	00/66440	11/2000
WO	01/085558	11/2001

OTHER PUBLICATIONS

European Patent Office Action dated May 27, 2004 (2 pages).
European Patent Office Action Jun. 2, 2005 (2 pages).
Mexican Foreign Associate Letter dated May 9, 2006 with copy of Mexican Office Action issued in Mexican Appln. No. 2011009 dated Apr. 12, 2006 (5 pages).
Office Action dated May 27, 2004, issued in EP Application No. 01 931 263.6-2308 (2 pages).
Office Action dated Jun. 2, 2005, issued in EP Application No. 01 931 263.6-2308 (3 pages).
Office Action dated Jan. 16, 2006, issued in Canadian Application No. 2,448,920 (2 pages).
Iper; PCT/CA01/00640; Sep. 10, 2002; 11 pages.
Mexican Official Action; Pa/a/2002/011009; Apr. 12, 2006; 4 pages.

* cited by examiner




FIG. 1




FIG. 3




FIG. 2




FIG. 4




FIG. 5




FIG. 6




FIG. 7





FIG. 8

156
160
144
152
164
168
136
140
Fuller
rail
diamonds
162
158
beveled edge
Foot
receptacle






FIG. 9b





FIG. 9C






FIG. 10





FIG. 11






FIG. 12b




FIG. 12C




FIG. 12d




FIG. 13




FIG. 14




FIG. 15a




FIG. 15b




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21

MULTI-LEVEL STACKING/NESTING TRAY

FIELD OF THE INVENTION

The present invention relates to injection molded containers. In particular, the present invention relates to a transport and storage container.

BACKGROUND OF THE INVENTION

Many transport and storage containers are known. Certain containers are used to transport and store goods such as bread or buns and other foods. Containers are typically injection molded plastic and rectangular in shape.

Containers for transportation and storage of bread products commonly have a base with a protruding base edge, a pair of opposing long sidewalls, and a pair of opposing short sidewalls. The sidewalls protrude in the opposite direction of the base edge. The opposing long sidewalls generally do not protrude as far from the base as the short sidewalls and may have a merchandiser or open section for viewing the contents held therein. The containers are stackable such that the base edge of one container is typically received by a complimentary configuration on the opposing short sidewalls of a second container. The base of the container can have a plurality of apertures for material and weight reduction. Similarly, each short sidewall commonly has a plurality of apertures and a handle in the centre for gripping the container.

When stacking, the container is gripped by placing one hand on each handle. The container is centred above a second container and placed directly down such that the base edge of the first container is received by the footprint of the second container. Similarly, when removing one container from a stack, the container is gripped by placing one hand on each handle. The container is then lifted away from and in a direction normal to the complimentary container. Because of the configuration of the container, stacking and destacking can be awkward and ergonomically unsafe as the person lifting the container can experience lower back strain. The operator carries the load with extended arms to place the container into a stack or when removing from a stack. The container is even more awkward to destack when full. If the operator removes more than one container when destacking, the potential for back strain is further increased.

When moving many containers at one time, a two wheeled cart is typically used. In order to slide the blade edge of the cart under the container it is generally preferred to tilt the stack of containers so that the blade will run under the stack. A stack of containers can be difficult to tilt forward while manoeuvring a two wheeled cart into place. It can be even more difficult to tilt the stack of containers due to lack of space in a packed truck. The cart also applies pressure to the base of the bottom container of the stack. This causes flexing of the base of the container thus crushing the contents of the bottom container. Overall, using a two wheeled cart to lift a stack of containers can be awkward and/or can damage the container.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide a novel container that obviates or mitigates at least one of the disadvantages of the prior art.

In one aspect of the invention there is provided a container with a base and at least one pair of opposing sidewalls. The sidewalls have a rail edge distal from the base and a plurality

of receptacles. The sidewalls have runners complementary to the receptacles that project from an edge adjacent the base. The sidewalls also have a fulcrum at the junction of a rail edge and one of the receptacles. The container has a stacked position with an identical container when the runners are received in complementary receptacles of the identical container. The container has a sliding position when the runners abut a rail edge of the identical container. The container has a levered position intermediate the stacked and sliding positions when the runner respective to a fulcrum of the identical container is pivoted thereon. In a preferred embodiment of the first aspect, there are two outer runners, or feet, and a central runner respective to the fulcrum.

In a second aspect of the invention there is provided a container with a base and at least one pair of opposing sidewalls projecting normally from the base. The sidewalls have a base edge proximal to the base and a distal edge opposite the base edge. One of the base edge and the distal edge has a plurality of receptacles and the opposite one has a plurality of runners complementary to the receptacles. The sidewalls also have a fulcrum at a junction of one of the receptacles and the respective edge. The container has a stacked position with an identical container when the runners are received in complementary receptacles of the identical container.

The container has a sliding position when the runners abut the opposite edge of the identical container. The container has a levered position intermediate the stacked and sliding positions when the runner respective to the fulcrum of the identical container is pivoted thereon.

In a third aspect of the invention there is provided a container with a base and a pair of opposing sidewalls projecting normally from the base. A pair of opposing long walls project normally from the base and extend between the pair of opposing sidewalls. A skirt around the periphery of the base interconnects the base with the sidewalls and the base with the long walls. The skirt is further defined by an outward taper and a pair of notches between each of the long sides and the base. The base comprises a grid of interconnected, inverted u-shaped channels. The u-shaped channels have at least one closed end and two opposing sides. The sidewalls have a rail and a rail edge distal from the base. The rail edge has a plurality of foot receptacles with a bevelled edge and at least one runner receptacle. The sidewalls have feet with a bevelled edge that are complementary to the foot receptacles and project from an edge proximal to the base. The sidewalls have at least one runner complementary to the runner receptacle that projects from the edge proximal to the base. Each of the opposing sidewalls have at least one handle with finger grips on one of the opposing sidewalls. One of the opposing sidewalls also has a serrated edge distal from the base and adjacent to the rail. The container has a fulcrum at a junction of the rail edge and the runner receptacle. The container has a first stacked position with an identical container when the feet are received in complementary foot receptacles of the identical container and the runner is received in complementary runner receptacle of the identical container. The container has a first sliding position, in relation to a second identical container, when the runner abuts the rail edge of the identical container. The container also has a first levered position, in relation to a second identical container, that is intermediate the first stacked and first sliding positions and the runner respective to a fulcrum of the identical container is pivoted thereon. The container has a second stacking position when the feet are received in complementary foot receptacles of an opposite sidewall of the identical container. The container has a second sliding

position when the feet abut the rail on the opposite sidewall of the identical container. The container also has a second levered position intermediate the second stacked and second sliding positions when one of the feet respective to one foot receptacle on the opposite sidewall of the second container is pivoted thereon.

In another aspect of the invention there is provided a container comprising a base, a sidewall projecting from the base and comprising an upper edge, a recess, and a fulcrum disposed between the upper edge and the recess, a foot depending from the sidewall, wherein the foot is configured to reside in the recess of an identical container and to be pivotable against the fulcrum of the identical container.

In a further aspect of the invention there is provided a container comprising a base, including a locator hole, a sidewall, including a locator pin depending therefrom, wherein the locator pin is configured to be received within the locator hole in an identical container.

In yet another aspect of the invention, there is provided a container comprising a base, first and second opposed sidewalls projecting from the base, each of the first and second sidewalls including a recessed channel, and a foot depending therefrom, wherein the foot is configured to reside in the channel of an identical container, and a third sidewall projecting from the base and extending between the first and second sidewalls comprising a second foot depending from the third sidewall, a support surface including a floor, and an upstanding wall extending from the floor and presenting a surface substantially parallel with the third sidewall, wherein the support surface is configured to support the second foot of an identical container.

A novel container for transport or storage of products such as bread, buns, or other goods. In one embodiment, there is provided a nestable container with a base and sidewalls that can be stacked in two positions for different products and can be nested when empty for compact storage. The container has levered positions for lifting out of each stacking position and into a corresponding sliding position. The sliding positions can be used to offset the container or containers from the stack and reduce the strain on the operator when lifting for destacking. Alternatively, the container can slide in the opposite direction for stacking. Thus the operator can set the container down (offset from the stack) in the sliding position and then slide into stacking position. Back strain can be reduced during stacking and destacking as the operator does not have to extend or lean over the stack to pick up or set down the containers.

BRIEF DESCRIPTION OF THE DRAWINGS

Preferred embodiments of the present invention will now be described, by way of example only, with reference to the attached Figures, wherein:

FIG. 1 is a top perspective view of the container, in accordance with a first embodiment of the invention;

FIG. 2 is a sectional view of the u-shaped channel of the base of the container of FIG. 1;

FIG. 3 is a bottom perspective view of the container of FIG. 1;

FIG. 4 is a rear view of the container of FIG. 1;

FIG. 5 is a front view of the container of FIG. 1;

FIG. 6 is a right side view of the container of FIG. 1;

FIG. 7 is a left side view of the container of FIG. 1;

FIG. 8 is a top view of the container of FIG. 1;

FIG. 9a is a partial perspective view of two of the containers of FIG. 1, stacked in first stacking position;

FIG. 9b is a side view of two of the containers stacked in a first stacking position;

FIG. 9c is a side view, opposite the side view opposite the side view of FIG. 9b, of two of the containers stacked in the first stacking position;

FIG. 9d is a partial sectional side view of two of the containers stacked in the first stacking position shown in FIG. 9c;

FIG. 10 is the partial sectional side view of FIG. 9c showing the first container in a first levered position with respect to the second container;

FIG. 11 is the partial sectional side view of FIG. 9c showing the first container in a first sliding position with respect to the second container;

FIG. 12a is a top perspective view of two of the containers of FIG. 9a stacked in a second stacking position;

FIG. 12b is a side view of two of the containers stacked in the second stacking position;

FIG. 12c is a side view of two of the containers, opposite the side view of FIG. 12b, stacked in the second stacking position;

FIG. 12d is a partial sectional side view of two of the containers stacked in the second stacking position shown in FIG. 12b;

FIG. 13 is the partial sectional side view of FIG. 12d showing the first container in a second levered position with respect to the second container;

FIG. 14 is the partial sectional side view of FIG. 12d showing the first container in a first sliding position with respect to the second container;

FIG. 15a is a top perspective view of the containers of FIG. 13d in a nested position;

FIG. 15b is a sectional side view of the containers of FIG. 15a in the nested position;

FIG. 16 is a top perspective view of a container of another embodiment of the present invention;

FIG. 17 is a top plan view of the container shown in FIG. 16;

FIG. 18 is a detailed view of the junction between;

FIG. 19 is a second detailed view of the junction between;

FIG. 20 is a side elevation view of two containers, identical to the container illustrated in FIG. 16, stacked in a stacking position; and

FIG. 21 is a top perspective view of two containers, identical to the container illustrated in FIG. 16, stacked in a nested position.

DETAILED DESCRIPTION OF THE INVENTION

Referring to FIG. 1, a container in one embodiment of the invention is indicated generally at 20. Container 20 is preferably used to transport and/or store products such as bread or buns. In a present embodiment, container 20 is an injection-molded polymer such as high-density polyethylene but other materials and forming processes can be used. Container 20 comprises a substantially rectangular base 24 and two sidewalls 28, 32 that project substantially normal to base 24. Opposing long sides 36, 40 extend between sidewalls 28, 32 and project substantially normal to base 24.

Base 24 is slightly bowed such that it has a convex side 44 towards the interior of container 20. Base 24 is comprised of a grid of interconnected inverted u-shaped channels 48. The grid of u-shaped channels 48 forms a plurality of apertures 52 in base 24. As best seen in FIG. 2, u-shaped channels 48 have a closed end 56 and two opposing sides 60 extending therefrom. Closed end 56 and opposing sides 60

form channel opening 62. Channel 48 is tapered such that each of opposing sides 60 is at an obtuse angle with end 56. It is believed that the angle can be from about one degree to about fifteen degrees with respect to the normal from closed end 56. Preferably, the angle is from about two degrees to about ten degrees with respect to the normal from closed end 56. More preferably, the angle is about three degrees with respect to the normal from closed end 56.

Referring to FIG. 3, a skirt 64 runs along the periphery of base 24 and interconnects base 24 with sidewalls 28, 32 and long sides 36, 40. There are two notches 68 in skirt 64 between each of long sides 36, 40 and base 24.

Referring now to FIGS. 4 and 5, long side 40 is substantially rectangular with a flange 76 on each end adjoining sidewalls 28, 32. Similarly, long side 36 has flange 76 on each end adjoining sidewall 28, 32. A substantially rectangular merchandiser window 80 is framed by long side 36 and flanges 76. Skirt 64 is further defined by an outward taper 72 that runs adjacent to long sides 36, 40 and is for slideably receiving the blade of a two-wheeled cart.

Referring to FIGS. 6 and 7, sidewalls 28, 32 are substantially rectangular with a base edge 84 and a first rail edge 88 opposite base edge 84. Sidewall 28 has a central handle 92 substantially centred on sidewall 28. Also, sidewall 28 has a rectangular end handle 96 at one end and a triangular end handle 100 at the opposite end. Similarly, sidewall 32 has a central handle 94 substantially centred on sidewall 32. Also, sidewall 32 has a rectangular end handle 98 at one end and a triangular end handle 102 at the opposite end. Each sidewall 28, 32 has ribs 104 proximal to each handle 92, 96, 100, 94, 98, 102 for supporting sidewalls 28, 32 and handles 92, 96, 100, 94, 98, 102. Sidewall 28 is substantially the mirror-image of sidewall 32. However, sidewall 28 has finger grips 108 respective to each handle 92, 96, 100, and a serrated edge 112, each of which can be used to identify sides 28, 32.

Referring to FIGS. 4, 5, 6 and 7, a first guide foot 116 extends from base edge 84 of each sidewall 28, 32 and is substantially aligned with rectangular handle 96, 98. Guide foot 116 is substantially rectangular with an inwardly facing bevelled edge 124. A second guide foot 120 extends from base edge 84 of each sidewall 28, 32 and is closer to central handle 92 than first guide foot 116. Each guide foot 120 is substantially rectangular with an inwardly facing bevelled edge 126. Each foot 116, 120 has a groove 128 between its extremity and skirt 64.

As best seen in FIG. 6, a substantially rectangular runner 132 is integral with skirt 64 and projects from base side 84. Runner 132 is substantially centred between central handle 92 and rectangular end handle 96. As best seen in FIG. 7, sidewall 28 and its respective guide feet 116, 120 and runner 132 are substantially the mirror image of sidewall 32.

As best seen in FIGS. 1 and 8, a channel 135 is recessed from first rail edge 88 and extends substantially along the inner length of each sidewall 28, 32. Each channel 135 includes inwardly facing sidewalls 1351 and 1352 extending from track 1353. Sidewall 1351 includes an upper edge, defining first rail edge 88. Similarly, sidewall 1352 includes an upper edge, defining second rail edge 140. Each channel 135 includes a rail 136, a first depression 144, a second depression 148, a first foot receptacle 156, second foot receptacle 158, and runner receptacle 164. First depression 144 is aligned with guide foot 116 on each of sidewalls 28, 32. Second depression 148 is aligned with second guide foot 120 on each of sidewalls 28, 32. Second depression 148 has an inwardly bevelled edge 152 between depression 148 and rail 136. First foot receptacle 156 is proximal to long side 40

with an inwardly bevelled edge 160. First foot receptacle 158 is configured to received guide foot 116 and permit pivotal rotation of guided foot 116 therein about end of sidewall 28 nearest rectangular handle 96, and also permit pivotal rotation of guide foot 116 about fulcrum 168, as will be further described hereafter. Second foot receptacle 158 includes an inwardly facing bevelled edge 162. Second foot receptacle 158 is closer to central handle 92 than first foot receptacle 156. Runner receptacle 164 is disposed between rail 136 and second depression 148. A fulcrum 168 intersects receptacle 164 and rail edge 140 on the side of receptacle 164 nearest to central handle 92 on each sidewall 28, 32.

The positions for transportation and storage of container 20 will now be described with reference to the foregoing and the attached Figures. Container 20 has two stacked positions shown in FIGS. 9a to 9d and FIGS. 12a to 12d, two levered positions for destacking shown in FIGS. 10 and 13, two sliding positions for stacking and destacking shown in FIGS. 11 and 14, and a nested position for storage shown in FIG. 15. In each of the above listed positions, container 20 is positioned with an identical container 20b. Note that all parts of container 20b are given the same number designations as that of container 20 but are succeeded by the label "b".

In the first stacked position, shown in FIGS. 9a to 9d, container 20 is stacked with container 20b such that side 28 is aligned with side 32b. Likewise, side 32 is aligned with side 28b. Each guide foot 116, 120 is received by complimentary foot receptacle 156b, 158b. Bevelled edge 124 of each guide foot 116 is adjacent to bevelled edge 160b of complimentary foot receptacle 156b. Similarly, bevelled edge 126 of each guide foot 120 is adjacent to bevelled edge 162b of complimentary foot receptacle 158b. Each runner 132 is received by complimentary runner receptacle 164b. In this configuration, central handle 92 is aligned with central handle 94b. End handles 96, 96b, 100, 100b, 98, 98b, 102, 102b are oppositely aligned such that rectangular handle 96 is aligned with triangular handle 102b and triangular handle 100 is aligned with rectangular handle 98b. Similarly, central handle 94 is aligned with central handle 92b. Triangular handle 102 is aligned with rectangular handle 96b and rectangular handle 98 is aligned with triangular handle 100b. Serrated edges 112 and 112b are on opposing sides of stacked containers 20, 20b. As will now be apparent to those of skill in the art, a plurality of substantially identical containers 20 can be stacked together in the first stacked position.

Container 20 can be levered out of the first stacked position and into the first sliding position when destacking. From the first stacked position as shown in FIG. 9d, triangular handles 100, 102 of container 20 are grasped and container 20 is urged in the direction of arrow A. The opposing ends of sidewalls 28, 32, nearest rectangular handles 96, 98 maintains contact with respective ends of sidewalls 32b and 28b of container 20b. Referring to FIG. 10, container 20 is advanced in the direction of arrow B until guide foot 116 contacts rail edge 140b. Container 20 is then lowered in the direction of arrow C such that runner 132 contacts fulcrum 168b. Container 20 is urged in the direction of arrow C while a force is applied in the direction of arrow B, thereby maintaining contact between runner 132 and fulcrum 168b and lifting each first guide foot 116 out of respective receptacles 156b. When container 20 is seated again on container 20b, runner 132 is seated on rail 136b and skirt 64 is seated on flanges 76b of long side 40b, as best seen in FIG. 11. This is the first sliding position.

Referring to FIG. 11, container 20 is in the first sliding position with runner 132 seated on rail 136b and skirt 64

seated on flanges 76b. Container 20 can be urged in the direction of arrow A, for destacking or arrow B for stacking, sliding runner 132 along rail 136b and skirt 64 along flanges 76b. With a plurality of substantially identical containers 20 in a stack, container 20 can be destacked by sliding in the direction of arrow A. Container 20 is thus offset from the stack and the operator can lift container 20 by grasping central handles 92, 94. Offsetting container 20 from the stack before lifting can allow the operator to remain substantially upright, without bending, when lifting the container. Alternatively, container 20 can be seated in the sliding position and then urged in the direction of arrow B for stacking, again allowing the operator to remain substantially upright.

In the second stacked position, shown in FIGS. 12a to 12d, container 20 is stacked with container 20b such that sidewall 28 is aligned with sidewall 28b. Likewise, sidewall 32 is aligned with sidewall 32b. On each of sidewall pairs 28, 28b and 32, 32b, guide foot 116 is seated on complimentary rail depression 144b. Guide foot 120 is seated on complimentary rail depression 148b. Bevelled edge 126 of guide foot 120 is adjacent to bevelled edge 152b of depression 148b. Runner 132 is adjacent rail edge 140b. Guide foot 116 is aligned with guide foot 116b and guide foot 120 is aligned with guide foot 120b. Runner 132 is aligned with runner 132b. In this configuration, central handle 92 is aligned with central handle 92b. Rectangular end handles 96 and 96b are aligned, triangular end handles 100 and 100b are aligned, and serrated edges 112 and 112b are aligned. Similarly, central handles 94 and 94b are aligned, rectangular handles 98 and 98b are aligned, and triangular handles 102 and 102b are aligned. The distance between base 24 and base 24b is greater in the second stacked position than in the first stacked position. As will now be apparent to those of skill in the art, a plurality of substantially identical containers 20 can be stacked together in the second stacked position.

Container 20 can be levered out of the second stacked position when destacking. From the second stacked position as shown in FIG. 12d, rectangular end handles 96, 98 are grasped and container 20 is urged in the direction of arrow A. On each of sidewall pairs 28, 28b and 32, 32b, second guide foot 120 maintains contact with depression 148b while first guide foot 116 is urged out of depression 144b. Referring to FIG. 13, container 20 is advanced in the direction of arrow B causing bevelled edge 124 of guide foot 120 to slide against bevelled edge 152b of depression 148b, thereby urging guide foot 120 out of depression 144b and onto rail 136b. Container 20 is then moved in the direction of arrow C. When container 20 is seated on container 20b, guide foot 120 is seated on rail 136b and skirt 64 is seated on flanges 76b, as best seen in FIG. 14. This is the second sliding position.

Referring now to FIG. 14, container 20 is in the second sliding position with guide foot 120 seated on rail 136b and skirt 64 seated on flanges 76b. Container 20 can be urged in the direction of arrow D for destacking or arrow E for stacking, by sliding guide foot 120 on rail 136b and skirt 64 on flanges 76b. With a stack of substantially identical containers 20, container 20 can be destacked by sliding in the direction of arrow D. Container 20 is thus offset from the stack and the operator can lift container 20 by grasping central handles 92, 94. Offsetting container 20 from the stack before lifting can allow the operator to remain substantially upright, without bending, when lifting the container. Alternatively, container 20 can be seated in the sliding position and then urged in the direction of arrow E for stacking.

Seating the container in the sliding position before stacking, again, can allow the operator to remain substantially upright.

In the nested position, shown in FIGS. 15a and 15b, container 20 is seated perpendicular to container 20b. Long sides 36b, 40b of container 20b are received by notches 68 of container 20. A stack of containers 20 in either stacked position can be lifted and moved using, for example, a two-wheeled cart. The blade of the cart is slideably received under skirt 64 of container 20 at taper 72. Tilting the cart thus lifts the stack of containers as base 24 and skirt 64 are in contact with the cart blade.

The stacking configuration of a plurality of containers 20 and the orientation of a container can be determined by the operator by using tactile or visual means. The operator can recognize sidewall 28 of container 20 by touching any of serrated edge 112 or finger grips 108 on each handle 92, 96, 100. Alternatively, the operator can recognize sidewall 28 of container 20 by visual recognition of the above mentioned features.

FIG. 16 illustrates another embodiment of the container of the present invention, and is generally indicated at 200. Container 200 is similar to container 20. Like container 20, container 200 includes a substantially rectangular base 224, a pair of opposed sidewalls 228, 232 that project normally to base 224 and a pair of opposed long sidewalls 236, 240 that also project substantially normal to base 224. Opposed long sidewalls 236, 240 extend between and merge with sidewalls 228, 232. Base 224 includes a plurality of apertures 252, one of which is relatively oversized to define a locator hole 253 (see FIG. 17).

Referring to FIG. 16, a skirt 264 runs along and extends from the periphery of base 224 and interconnects base 224 with sidewalls 228, 232 and long sidewalls 236, 240. Skirt 264 includes a first skirt section 2641, a second skirt section 2642, a third skirt section 2643, and a fourth skirt section 2644. Skirt section 2641 runs along sidewall 228 and interconnects sidewall 228 to base 224. Skirt section 2642 runs along long side 236 and interconnects sidewall 236 to base 224. Skirt section 2643 runs along sidewall 232 and interconnects sidewall 232 to base 224. Skirt section 2644 runs along long side 240 and interconnects sidewall 240 to base 224. Two notches 268 are formed along the bottom edge of skirt sections 2642 and 2644. Skirt 264 further includes an outward taper 272 that runs adjacent to long sides 236 and 240 and is provided for engaging the blade of a two-wheeled cart.

Sidewall 228 is formed with handles 292, 296, and 308. Similarly, sidewall 232 is formed with handles 294, 298, and 302.

Each of sidewalls 228 and 232 includes a base edge 284 and a first rail edge 288 opposite base edge 284. A first guide foot 316, a second guide foot 320, and a runner 332 are provided extending from base edge 284 of each sidewall 228 and 232. Runner 332 is disposed between first guide foot 316 and second guide foot 320. Sidewall 228 is substantially the mirror-image of sidewall 232.

A channel 335 is recessed from first rail edge 288 and extends substantially along the inner length of each sidewall 228 and 232. Each channel 335 includes inwardly facing sidewalls 3351 and 3352 extending from a track 3353. Each sidewall 3351 includes an upper edge, defining first rail edge 288. Similarly, each sidewall 3352 includes an upper edge, defining second rail edge 340. Each track 3353 includes a track surface 336, a first depression 344, a second depression 348, a first foot receptacle 356, a second foot receptacle 358, and a runner receptacle 364. First depression 344 is aligned with first guide foot 316. Second depression 348 is aligned

with second guide foot **320**. First foot receptacle **356** is proximal to long side **240**, and is configured to receive first foot **316** of a second identical container **200**. Second foot receptacle **358** is closer to central handle **292** or **294** than first foot receptacle **356**, and is configured to receive second foot **320** of a second identical container **200**. Runner receptacle **364** is configured to receive runner **332** of a second identical container **200**. A fulcrum **368** is defined by the intersection of receptacle **364** and rail edge **340** on the side of receptacle **364** nearest central handle **292** or **294**.

Long sidewall **236** includes an upper edge **402** and a lower edge **404**. First foot **406** and second foot **408** extend from lower edge **404** at either end of long sidewall **236**.

Referring to FIGS. **16**, **18** and **19**, long sidewall **240** includes a first support surface **410** and a second support surface **412**, both disposed above base **224**. Support surfaces **410**, **412** are configured to provide seating and support for first foot **406** and second foot **408**, respectively, of a second identical container **200**. Each of support surfaces **410**, **412** includes a floor **414** and an upstanding wall **416** extending from floor **414** and presenting a surface substantially parallel to that of long side **240**. In this respect, wall **416** functions as a stop, for blocking lateral movement of first foot **406** or second foot **408**. Spaced inwardly from and opposing wall **416**, inclined surface or ramp **418** extends from floor **414**, thereby impeding travel of first foot **406** or second foot **408** in the direction of inclined surface **418** and mitigating untimely unseating of first foot **406** or second foot **408** from support surfaces **410** and **412**, respectively. Inclined surface **418** also facilitates seating and unseating of first foot **406** or second foot **408** with relative little difficulty.

Long sidewall **240** also includes a locator pin **2401**, extending from upper edge **402** proximate to sidewall **228**. Locator pin **2401** is trapezoidal-shaped and is configured to restrict the stacking of identical containers **200** to a single desired directional orientation. In this respect, of all the apertures **252**, locator hole **253** is the only aperture **252** capable of receiving locator pin **2401**. Referring to FIG. **17**, locator hole **253** is disposed in base **224** of container **200**, and configured to be located over locator pin **2401** of an identical container **200b** to effect stacking of containers **200** and **200b** in a desired directional orientation.

The positions for storage and transportation of container **200** will now be described. Container **200** is shown positioned with identical containers **200b** and **200c**. Note that all parts of containers **200b** and **200c** are given the same number designations as that of container **200** but are succeeded by the reference characters "b" and "c" respectively.

Referring to FIG. **20**, in a stacked position, container **200** is stacked with container **200b** such that sidewall **228** is aligned with sidewall **228b**. Likewise, sidewall **232** is aligned with sidewall **232b**. This configuration is very similar to that illustrated in FIGS. **12a** to **12d** with the exception that first foot **404b** and second foot **406b** of second container **200b** are seated upon support surfaces **410**, **412**, respectively, in the FIG. **20** embodiment.

In the nested position, shown in FIG. **21**, container **200b** is seated perpendicular to and upon container **200**. In this respect, skirt section **2641** hangs over long sidewall **240**, and sidewall **218** is substantially parallel with long sidewall **240**. Similarly, skirt section **2642** hangs over long sidewall **236**, and sidewall **232** is substantially parallel with long sidewall **236**. Long sidewalls **236**, **240** of container **200** are received by notches **268b** of container **200b** to stabilize the stacked/nested configuration. Locator pin **2401** is received by locator hole **253b** to effect the above described orientation of container **200b** relative to container **200**. A third container

200c can then be seated perpendicular to container **200b**, in a manner similar to that described above with respect to containers **200** and **200b**, by positioning locator hole **253c** over locator pin **2401** and receiving long sidewalls **236b** and **240b** within notches **268c**. The resultant orientation of container **200c** relative to container **200** dictates that first foot **316c** is received by first foot receptacle **356**, second foot **320c** is received by second foot receptacle **358**, and runner **332** is received by runner receptacle **364**. Similarly, first foot **404c** and second foot **406c** are seated upon support surfaces **410** and **412** respectively. Such configuration minimizes stacking height of containers **200**, **200b**, and **200c**.

Containers **200**, stacked in this manner, can be lifted and moved using, for example, a two-wheeled cart. The blade of the cart is slideably received under skirt **64** of container **200** at taper **72**, and particularly under the section of skirt **264** running adjacent to long side **236**. Tilting the cart thus lifts the stack of containers as base **224** and skirt **264** are in contact with the cart blade. Interaction between first foot **404** and second foot **406** with support surfaces **410** and **412** mitigate the possibility of containers **200** losing their stacking relationship with one another as the cart is tilted.

In a presently preferred embodiment, the first stacking position can be used for transportation and storage of buns such as hot dog or hamburger buns. The second stacking position can be used for the transportation and storage of loaves of bread. Alternatively, the container can be used for the storage and transportation of other goods such as produce or sweet goods eg. cakes.

While the embodiments discussed herein are directed to particular implementations of the present invention, it will be apparent that the subsets and variations to these embodiments are within the scope of the invention. For example, the size of the sidewalls or long sides can differ from above or may all be equal in length. Alternatively, the feet and runner positions may be interchanged with the rail, rail edge and receptacles such that the feet and runner are on the edge of the sidewall distal to the base and the rail, rail edge and receptacles may be on the edge of the sidewall adjacent the base. The container may have only one stacking position when stacked with an identical container. Also, the container may or may not have a merchandiser window on either or both of the long sides. The container may have a logotype on one side and not the other for easy identification of the stacking position. Other ribs may be added or a different arrangement of ribs may be present on the sides of the container for additional strength and rigidity. The shape of any of the features can differ while still performing the same function. Furthermore, collectively, runner **132** and feet **116**, **120** can be considered to be a plurality of runners.

The present invention provides a novel container for transport or storage of products such as bread, buns, or other goods. In one embodiment, there is provided a nestable container with a base and sidewalls that can be stacked in two positions for different products and can be nested when empty for compact storage. The container has levered positions for lifting out of each stacking position and into a corresponding sliding position. The sliding positions can be used to offset the container or containers from the stack and can allow the operator to remain substantially upright, without bending, and can thus reduce the back strain on the operator when lifting for destacking. Alternatively, the container can slide in the opposite direction for stacking in either position. Thus the operator can set the container down (on the uppermost container of the stack, and offset therefrom) into the sliding position and then slide the container into the stacking position. Back strain can be reduced during

11

stacking and destacking as the operator does not have to extend or lean over the stack to pick up or set down the containers. The container has a serrated edge on one sidewall and finger grips on each handle of the same sidewall. Thus, the orientation of the container or stacking configuration of a plurality of containers is easily recognized by either tactile or visual means. The container has a skirt with a tapered section around the periphery of the base for slideably receiving a cart when moving containers. Thus the stack of containers does not require awkward tilting and manoeuvring of the cart. Also, the front of the containers is not damaged from frequent impact with the edge of a two-wheeled cart. The base of the container is slightly bowed so that the interior is convex and is comprised of many interconnected tapered u-shaped channels. The bowed base and the tapered channels increase the strength and resistance to deformation of the base. When lifting these containers with a two-wheeled cart, pressure is applied to the base of the container. The increased strength of the base can reduce damage to the contained goods.

I claim:

1. A container comprising:

a base;

at least one pair of opposing sidewalls projecting normally from said base, said sidewalls including

a pair of stacking feet, each of said stacking feet including

a first and second substantially vertical surface,

a substantially horizontal surface substantially orthogonal to and joined to the first substantially vertical surface, and

an angled portion joined at a first end to the second substantially vertical surface and joined at a second end to the substantially horizontal surface, and

a pair of stacking feet receptacles, said stacking feet receptacles configured to receive the stacking feet and including

an angled portion substantially similar to the angled portion of each of a corresponding stacking foot;

at least one pair of opposing longwalls projecting normally from said base;

each of said sidewalls further including

a channel defining a rail edge distal from said base and having a plurality of runner receptacles;

said sidewalls having runners complementary to said runner receptacles and projecting from an edge adjacent to said base; and

a fulcrum at a junction of said rail edge and one of said runner receptacles and substantially centrally located between a center of the sidewall and one longwall such that said container has

a stacked position with an identical container when said runners are received in complementary runner receptacles of said identical container,

a sliding position when at least one of said runners is received within a channel of said identical container,

a levered position intermediate said stacked and sliding positions when said runner is pivoted with respect to a fulcrum of said identical container, and

a lifted position intermediate the stacked and levered position, wherein the container is lifted upwardly by the longwall furthest from said fulcrum to rotate the container about the stacking feet located closest to the fulcrum as a result of the angled portion of the

12

stacking foot sliding with respect to the angled portion of the corresponding stacking foot receptacle.

2. The container according to claim 1 having a second stacked position with said identical container wherein said runners are received in complementary runner receptacles of an opposite one of said sidewalls of said identical container.

3. The container according to claim 2 wherein said first stacked position has a different height between said base and a base of said identical container than said second stacked position.

4. The container according to claim 3 wherein said first stacked position is for transportation and storage of buns and said second stacked position is for transportation and storage of bread.

5. The container according to claim 2 wherein said container has a second sliding position when said runners abut said rail edge on said opposite one of said sidewalls of said identical container.

6. The container according to claim 5 wherein said container has a second levered position intermediate to said second stacked and said second sliding position when one of said runners respective to one of said receptacles on said opposite one of said sidewalls of said second container is pivoted thereon.

7. The container according to claim 2 wherein each of said opposing sidewalls has at least one handle, said handle having finger grips on one of said opposing sidewalls for determining orientation of said container when stacked with said second identical container.

8. The container according to claim 2 wherein one of said opposing sidewalls has a serrated edge, said serrated edge for determining orientation of said container when stacked with said second identical container.

9. The container according to claim 1 wherein said container further comprises:

a skirt around the periphery of said base, interconnecting said base with said sidewalls.

10. The container according to claim 7 wherein said skirt has an outward taper for slidably receiving the lifting edge of a cart when moving said container.

11. The container according to claim 1 wherein said container further comprises:

a pair of long walls projecting normally from said base, extending between said one pair of said opposing sidewalls; and

a skirt around the periphery of said base, interconnecting said base with said sidewalls and said base with said long walls;

said skirt having a plurality of notches for receiving said long walls of said second container when said container is seated perpendicular to said second container.

12. The container according to claim 11 wherein at least one of said long walls frames a merchandiser window.

13. The container according to claim 1 wherein said base is comprised of a grid of interconnected, inverted u-shaped channels, said u-shaped channels having at least one closed end and two opposing sides.

14. The container according to claim 13 wherein said u-shaped channels are tapered such that each of said opposing sides form an angle of from about one degree to about fifteen degrees from the normal of said closed end.

15. The container according to claim 13 wherein said u-shaped channels are tapered such that each of said opposing sides form an angle of from about two degrees to about ten degrees from the normal of said closed end.

13

16. The container according to claim 13 wherein said u-shaped channels are tapered such that each of said opposing sides form an angle of about three degrees from the normal of said closed end.

17. The container according to claim 1 wherein said channel includes a web and a pair of opposing sides extending therefrom for guided travel of said runners within the channel.

18. A container comprising:

a base, including a support surface for supporting goods and a locator hole;

a first pair of opposed sidewalls projecting from the base, each of the sidewalls of the first pair including;

a channel, distal from said base,

a plurality of stacking feet, wherein each stacking foot includes

a first and second substantially vertical surface,

a substantially horizontal surface substantially orthogonal to and joined to the first substantially vertical surface, and

an angled portion joined at a first end to the second substantially vertical surface and joined at a second end to the substantially horizontal surface, and

a pair of stacking feet receptacles, said stacking feet receptacles configured to receive the stacking feet and including

an angled portion substantially similar to the angled portion of each of a corresponding stacking foot;

a plurality of runner receptacles, and

runners projecting from an edge adjacent to said base, wherein

the runners are received within a channel of an identical container and are complementary to said runner receptacles,

a third side wall, projecting from the base and extending between the first and second sidewalls;

a fulcrum at a junction of said rail edge and one of said runner receptacles and substantially centrally located between a center of the sidewall and the third sidewall; and

a locator pin projecting from said base so as not to interfere with the supporting of the goods by said base, said locator pin configured to be received within a locator hole of an identical container when said identical container is nested with said container;

wherein said locator pin and said locator hole of said identical container co-operate to effect said nesting of said identical container upon said container in a single predetermined transverse directional orientation relative to said container.

19. A container comprising:

a base comprising a grid of interconnected, inverted u-shaped channels, said u-shaped channels having at least one closed end and two opposing sides;

at least one pair of opposing sidewalls projecting normally from said base;

each of said sidewalls including a channel defining a rail edge distal from said base and having a plurality of receptacles;

said sidewalls having runners complementary to said receptacles and projecting from an edge adjacent to said base; and

a fulcrum at a junction of said rail edge and one of said receptacles and substantially centrally located between a center of the sidewall and one longwall such that said

14

container has a stacked position with an identical container when said runners are received in complementary receptacles of said identical container, a sliding position when at least one of said runners is received within a channel of said identical container and a levered position intermediate said stacked and sliding positions when said runner is pivoted with respect to a fulcrum of said identical container.

20. The container according to claim 19 having a second stacked position with said identical container wherein said runners are received in complementary receptacles of an opposite one of said sidewalls of said identical container.

21. The container according to claim 20 wherein said first stacked position has a different height between said base and a base of said identical container than said second stacked position.

22. The container according to claim 21 wherein said first stacked position is for transportation and storage of buns and said second stacked position is for transportation and storage of bread.

23. The container according to claim 20 wherein said container has a second sliding position when said runners abut said rail edge on said opposite one of said sidewalls of said identical container.

24. The container according to claim 23 wherein said container has a second levered position intermediate to said second stacked and said second sliding position when one of said runners respective to one of said receptacles on said opposite one of said sidewalls of said second container is pivoted thereon.

25. The container according to claim 20 wherein each of said opposing sidewalls has at least one handle, said handle having finger grips on one of said opposing sidewalls for determining orientation of said container when stacked with said second identical container.

26. The container according to claim 20 wherein one of said opposing sidewalls has a serrated edge, said serrated edge for determining orientation of said container when stacked with said second identical container.

27. The container according to claim 19 wherein said container further comprises; a skirt around the periphery of said base, interconnecting said base with said sidewalls.

28. The container according to claim 27 wherein said skirt has an outward taper for slidably receiving the lifting edge of a cart when moving said container.

29. The container according to claim 19 wherein said container further comprises:

a pair of long walls projecting normally from said base, extending between said one pair of said opposing sidewalls; and

a skirt around the periphery of said base, interconnecting said base with said sidewalls and said base with said long walls;

said skirt having a plurality of notches for receiving said long walls of said second container when said container is seated perpendicular to said second container.

30. The container according to claim 29 wherein at least one of said long walls frames a merchandiser window.

31. The container according to claim 19 wherein said u-shaped channels are tapered such that each of said opposing sides form an angle of from about one degree to about fifteen degrees from the normal of said closed end.

32. The container according to claim 19 wherein said u-shaped channels are tapered such that each of said oppos-

15

ing sides form an angle of from about two degrees to about ten degrees from the normal of said closed end.

33. The container according to claim **19** wherein said u-shaped channels are tapered such that each of said opposing sides form an angle of about three degrees from the normal of said closed end. 5

16

34. The container according to claim **19** wherein said channel includes a web and a pair of opposing sides extending therefrom for guided travel of said runners within the channel.

* * * * *