

US007364377B2

(12) **United States Patent**
Silverbrook

(10) **Patent No.:** **US 7,364,377 B2**
(45) **Date of Patent:** **Apr. 29, 2008**

(54) **PRINT ENGINE ASSEMBLY WITH AN ELONGATE CONVERGING INK DISTRIBUTION ASSEMBLY**

(75) Inventor: **Kia Silverbrook**, Balmain (AU)

(73) Assignee: **Silverbrook Research Pty Ltd**, Balmain, New South Wales (AU)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/225,173**

(22) Filed: **Sep. 14, 2005**

(65) **Prior Publication Data**

US 2006/0008307 A1 Jan. 12, 2006

Related U.S. Application Data

(63) Continuation of application No. 10/728,936, filed on Dec. 8, 2003, now Pat. No. 6,984,080, which is a continuation of application No. 10/172,024, filed on Jun. 17, 2002, now Pat. No. 6,796,731, which is a continuation of application No. 09/575,111, filed on May 23, 2000, now Pat. No. 6,488,422.

(51) **Int. Cl.**
B41J 2/155 (2006.01)

(52) **U.S. Cl.** **400/693**; 347/12; 347/42; 347/44; 347/84; 347/85

(58) **Field of Classification Search** 347/12, 347/42, 44, 47, 84, 85, 86, 87; 400/61, 693
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,417,259 A 11/1983 Maeda

4,555,717 A	11/1985	Miura et al.
4,883,219 A	11/1989	Anderson et al.
4,959,662 A	9/1990	Kobayashi
5,017,947 A	5/1991	Masuda
5,040,908 A	8/1991	Matsuya et al.
5,051,761 A	9/1991	Fisher et al.
5,065,169 A	11/1991	Vincent et al.
5,081,472 A	1/1992	Fisher
5,108,205 A	4/1992	Stone
5,172,987 A	12/1992	Stellmach et al.
5,276,468 A	1/1994	Faes et al.
5,309,176 A	5/1994	Faes et al.
5,316,395 A	5/1994	Imai
5,366,301 A	11/1994	Martin et al.
5,412,411 A	5/1995	Anderson et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP 313204 4/1989



(Continued)

Primary Examiner—Daniel J. Colilla
Assistant Examiner—Kevin D. Williams

(57) **ABSTRACT**

A print engine assembly includes an elongate chassis. A platen is mounted on the chassis. A feed mechanism feeds print media over the platen and along a print feed path. An elongate printhead assembly is mounted on the chassis for carrying out a printing operation on the print media. The printhead assembly includes an elongate ink distribution assembly having an inlet side, an outlet side, a plurality of ink paths that converge laterally to a longitudinally extending central region and a plurality of printhead chip mounting formations in fluid communication with the ink paths. A plurality of printhead chips is mounted in respective mounting formations to receive ink from the ink paths.

7 Claims, 22 Drawing Sheets



US 7,364,377 B2

Page 2

U.S. PATENT DOCUMENTS

5,500,661 A * 3/1996 Matsubara et al. 347/41
 5,570,959 A 11/1996 Moriwaki et al.
 5,594,481 A 1/1997 Keefe et al.
 5,610,636 A 3/1997 Hanabusa et al.
 5,757,398 A 5/1998 Anderson et al.
 5,806,992 A 9/1998 Ju
 5,876,582 A 3/1999 Frazier
 5,929,877 A 7/1999 Hetzer et al.
 5,963,234 A 10/1999 Miyazawa et al.
 6,047,816 A 4/2000 Moghadam et al.
 6,050,679 A * 4/2000 Howkins 347/72
 6,065,825 A 5/2000 Anagnostopoulos et al.
 6,123,260 A 9/2000 Menzenski
 6,172,691 B1 1/2001 Belon et al.
 6,250,738 B1 6/2001 Waller et al.
 6,259,808 B1 7/2001 Martinez et al.
 6,318,920 B1 11/2001 Silverbrook
 6,322,206 B1 11/2001 Boyd et al.
 6,332,677 B1 * 12/2001 Steinfield et al. 347/87
 6,350,013 B1 2/2002 Scheffelin et al.
 6,398,330 B1 6/2002 Chua et al.
 6,409,323 B1 6/2002 Silverbrook
 6,457,810 B1 10/2002 King et al.
 6,485,135 B1 11/2002 Foote et al.
 6,488,422 B1 12/2002 Silverbrook
 6,561,608 B1 5/2003 Yamamoto et al.
 6,796,731 B2 9/2004 Silverbrook
 6,984,080 B2 * 1/2006 Silverbrook 400/77
 6,988,840 B2 * 1/2006 Silverbrook 400/77

2002/0018090 A1* 2/2002 Takazawa et al. 347/19

FOREIGN PATENT DOCUMENTS

EP 336870 10/1989
 EP 566540 10/1993
 EP 584823 A 3/1994
 EP 597621 5/1994
 EP 0598701 A 5/1994
 EP 604029 6/1994
 EP 694401 A 1/1996
 EP 921008 A 6/1999
 EP 1078755 2/2001
 GB 2115748 A 9/1983
 GB 2267255 A 12/1993
 GB 2297521 8/1996
 GB 2358947 8/2001
 JP 57163588 A 10/1982
 JP 59115863 7/1984
 JP 03234539 10/1991
 JP 08324065 12/1996
 JP 8336984 A 12/1996
 JP 09141858 6/1997
 JP 09286148 A 11/1997
 JP 10153453 6/1998
 JP 10193626 A 7/1998
 JP 10264390 10/1998
 JP 10324003 A 12/1998
 JP 11179900 7/1999
 JP 11348373 12/1999
 WO WO 01/42027 A 6/2001

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9a




FIG. 9b




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 22




FIG. 21




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27

**PRINT ENGINE ASSEMBLY WITH AN
ELONGATE CONVERGING INK
DISTRIBUTION ASSEMBLY**

CROSS REFERENCE TO RELATED
APPLICATIONS

The present application is a continuation of U.S. application Ser. No. 10/728,936, filed on Dec. 8, 2003, now issued as U.S. Pat. No. 6,984,080, which is a continuation of U.S. application Ser. No. 10/172,024 filed on Jun. 17, 2002, now issued as U.S. Pat. No. 6,796,731, which is a continuation of U.S. application Ser. No. 09/575,111 filed on May 23, 2000, now issued as U.S. Pat. No. 6,488,422, the entire contents of which are herein incorporated by reference.

CO-PENDING APPLICATIONS

Various methods, systems and apparatus relating to the present invention are disclosed in the following co-pending applications filed by the applicant or assignee of the present invention simultaneously with the present application: 6428133 6526658 6315399 6338548 6540319 6328431 6328425 6991320 6383833 6464332 6390591 7018016 6328417 6322194 6382779 6629745 09/575197 7079712 09/575123 6825945 09/575165 6813039 6987506 7038797 6980318 6816274 7102772 09/575186 6681045 6728000 09/575145 7088459 09/575181 7068382 7062651 6789194 6789191 6644642 6502614 6622999 6669385 6549935 6987573 6727996 6591884 6439706 6760119 09/575198 6290349 6428155 6785016 6870966 6822639 6737591 7055739 09/575129 6830196 6832717 6957768 09/575162 09/575172 09/575170 7106888 7123239 6409323 6281912 6604810 6318920 6488422 6795215 09/575109 6859289 6924907 6712452 6416160 6238043 6958826 6812972 6553459 6967741 6956669 6903766 6804026 09/575120 6975429

The disclosures of these co-pending applications are incorporated herein by reference.

6428133	6526658	6315399	6338548	6540319	6328431
6328425	6991320	6383833	6464332	6390591	7018016
6328417	6322194	6382779	6629745	09/575197	7079712
09/575123	6825945	09/575165	6813039	6987506	7038797
6980318	6816274	7102772	09/575186	6681045	6728000
09/575145	7088459	09/575181	7068382	7062651	6789194
6789191	6644642	6502614	6622999	6669385	6549935
6987573	6727996	6591884	6439706	6760119	09/575198
6290349	6428155	6785016	6870966	6822639	6737591
7055739	09/575129	6830196	6832717	6957768	09/575162
09/575172	09/575170	7106888	7123239	6409323	6281912
6604810	6318920	6488422	6795215	09/575109	6859289
6924907	6712452	6416160	6238043	6958826	6812972
6553459	6967741	6956669	6903766	6804026	09/575120
6975429					

BACKGROUND OF THE INVENTION

The following invention relates to a laminated ink distribution structure for a printer.

More particularly, though not exclusively, the invention relates to a laminated ink distribution structure and assembly for an A4 pagewidth drop on demand printhead capable of printing up to 1600 dpi photographic quality at up to 160 pages per minute.

The overall design of a printer in which the structure/assembly can be utilized revolves around the use of replace-

able printhead modules in an array approximately 8 inches (20 cm) long. An advantage of such a system is the ability to easily remove and replace any defective modules in a printhead array. This would eliminate having to scrap an entire printhead if only one chip is defective.

A printhead module in such a printer can be comprised of a "Memjet" chip, being a chip having mounted thereon a vast number of thermo-actuators in micro-mechanics and micro-electromechanical systems (MEMS). Such actuators might be those as disclosed in U.S. Pat. No. 6,044,646 to the present applicant, however, there might be other MEMS print chips.

The printhead, being the environment within which the laminated ink distribution housing of the present invention is to be situated, might typically have six ink chambers and be capable of printing four color process (CMYK) as well as infra-red ink and fixative. An air pump would supply filtered air to the printhead, which could be used to keep foreign particles away from its ink nozzles. The printhead module is typically to be connected to a replaceable cassette which contains the ink supply and an air filter.

Each printhead module receives ink via a distribution molding that transfers the ink. Typically, ten modules butt together to form a complete eight inch printhead assembly suitable for printing A4 paper without the need for scanning movement of the printhead across the paper width.

The printheads themselves are modular, so complete eight inch printhead arrays can be configured to form printheads of arbitrary width.

Additionally, a second printhead assembly can be mounted on the opposite side of a paper feed path to enable double-sided high speed printing.

OBJECTS OF THE INVENTION

It is an object of the present invention to provide an ink distribution assembly for a printer.

It is another object of the present invention to provide an ink distribution structure suitable for the pagewidth printhead assembly as broadly described herein.

It is another object of the present invention to provide a laminated ink distribution assembly for a printhead assembly on which there is mounted a plurality of print chips, each comprising a plurality of MEMS printing devices.

It is yet another object of the present invention to provide a method of distributing ink to print chips in a printhead assembly of a printer.

SUMMARY OF THE INVENTION

The present invention provides an ink distribution assembly for a printhead to which there is mounted an array of print chips, the assembly serving to distribute different inks from respective ink sources to each said print chip for printing on a sheet, the assembly comprising:

a longitudinal distribution housing having a duct for each said different ink extending longitudinally therealong,

a cover having an ink inlet port corresponding to each said duct for connection to each said ink source and for delivering said ink from each said ink source to a respective one of said ink ducts, and

a laminated ink distribution structure fixed to said distribution housing and distributing ink from said ducts to said print chips.

Preferably the laminated ink distribution structure includes multiple layers situated one upon another with at least one of said layers having a plurality of ink holes

therethrough, each ink hole conveying ink from one of said ducts enroute to one of said print chips.

Preferably one or more of said layers includes ink slots therethrough, the slots conveying ink from one or more of said ink holes in an adjacent layer enroute to one of said print chips.

Preferably, the slots are located with ink holes spaced laterally to either side thereof.

Preferably the layers of the laminated structure sequenced from the distribution housing to the array of print chips include fewer and fewer said ink holes.

Preferably one or more of said layers includes recesses in the underside thereof communicating with said holes and transferring ink therefrom transversely between the layers enroute to one of said slots.

Preferably the channels extend from the holes toward an inner portion of the laminated structure over the array of print chips, which inner portion includes said slots.

Preferably each layer of the laminated is a micro-molded plastics layer.

Preferably, the layers are adhered to one another.

Preferably, the slots are parallel with one another.

Preferably, at least two adjacent ones of said layers have an array of aligned air holes therethrough.

The present invention also provides a laminated ink distribution structure for a printhead, the structure comprising:

a number of layers adhered to one another, each layer including a plurality of ink holes formed therethrough, each ink hole having communicating therewith a recess formed in one side of the layer and allowing passage of ink to a transversely located position upon the layer, which transversely located position aligns with a slot formed through an adjacent layer.

Preferably the slot in any layer of the structure is aligned with another slot in an adjacent layer of the structure and the aligned slots are aligned with a respective print chip slot formed in a final layer of the structure.

Preferably the layers are micro-molded plastics layers.

The present invention also provides a method of distributing ink to an array of print chips in a printhead assembly, the method serving to distribute different inks from respective ink sources to each said print chip for printing on a sheet, the method comprising:

supplying individual sources of ink to a longitudinal distribution molding having a duct for each said different ink extending longitudinally therealong,

causing ink to pass along the individual ducts for distribution thereby into a laminated ink distribution structure fixed to the distribution housing, wherein

the laminated ink distribution structure enables the passage therethrough of the individual ink supplies to the print chips, which print chips selectively eject the ink onto a sheet.

The present invention also provides a method of distributing ink to print chips in a printhead assembly of a printer, the method utilizing a laminated ink distributing structure formed as a number of micro-molded layers adhered to one another with each layer including a plurality of ink holes formed therethrough, each ink hole communicating with a channel formed in one side of a said layer and allowing passage of ink to a transversely located position within the structure, which transversely located position aligns with an aperture formed through an adjacent layer of the laminated structure, an adjacent layer or layers of the laminated structure also including slots through which ink passes to the print chips.

As used herein, the term "ink" is intended to mean any fluid which flows through the printhead to be delivered to a sheet. The fluid may be one of many different colored inks, infra-red ink, a fixative or the like.

BRIEF DESCRIPTION OF THE DRAWINGS

A preferred form of the present invention will now be described by way of example with reference to the accompanying drawings wherein:

FIG. 1 is a front perspective view of a print engine assembly

FIG. 2 is a rear perspective view of the print engine assembly of FIG. 1

FIG. 3 is an exploded perspective view of the print engine assembly of FIG. 1.

FIG. 4 is a schematic front perspective view of a printhead assembly.

FIG. 5 is a rear schematic perspective view of the printhead assembly of FIG. 4.

FIG. 6 is an exploded perspective illustration of the printhead assembly.

FIG. 7 is a cross-sectional end elevational view of the printhead assembly of FIGS. 4 to 6 with the section taken through the center of the printhead.

FIG. 8 is a schematic cross-sectional end elevational view of the printhead assembly of FIGS. 4 to 6 taken near the left end of FIG. 4.

FIG. 9A is a schematic end elevational view of mounting of the print chip and nozzle guard in the laminated stack structure of the printhead

FIG. 9B is an enlarged end elevational cross section of FIG. 9A

FIG. 10 is an exploded perspective illustration of a printhead cover assembly.

FIG. 11 is a schematic perspective illustration of an ink distribution molding.

FIG. 12 is an exploded perspective illustration showing the layers forming part of a laminated ink distribution structure according to the present invention.

FIG. 13 is a stepped sectional view from above of the structure depicted in FIGS. 9A and 9B,

FIG. 14 is a stepped sectional view from below of the structure depicted in FIG. 13.

FIG. 15 is a schematic perspective illustration of a first laminate layer.

FIG. 16 is a schematic perspective illustration of a second laminate layer.

FIG. 17 is a schematic perspective illustration of a third laminate layer.

FIG. 18 is a schematic perspective illustration of a fourth laminate layer.

FIG. 19 is a schematic perspective illustration of a fifth laminate layer.

FIG. 20 is a perspective view of the air valve molding

FIG. 21 is a rear perspective view of the right hand end of the platen

FIG. 22 is a rear perspective view of the left hand end of the platen

FIG. 23 is an exploded view of the platen

FIG. 24 is a transverse cross-sectional view of the platen

FIG. 25 is a front perspective view of the optical paper sensor arrangement

FIG. 26 is a schematic perspective illustration of a printhead assembly and ink lines attached to an ink reservoir cassette.

FIG. 27 is a partly exploded view of FIG. 26.

5

DETAILED DESCRIPTION OF THE
INVENTION

In FIGS. 1 to 3 of the accompanying drawings there is schematically depicted the core components of a print engine assembly, showing the general environment in which the laminated ink distribution structure of the present invention can be located. The print engine assembly includes a chassis 10 fabricated from pressed steel, aluminum, plastics or other rigid material. Chassis 10 is intended to be mounted within the body of a printer and serves to mount a printhead assembly 11, a paper feed mechanism and other related components within the external plastics casing of a printer.

In general terms, the chassis 10 supports the printhead assembly 11 such that ink is ejected therefrom and onto a sheet of paper or other print medium being transported below the printhead then through exit slot 19 by the feed mechanism. The paper feed mechanism includes a feed roller 12, feed idler rollers 13, a platen generally designated as 14, exit rollers 15 and a pin wheel assembly 16, all driven by a stepper motor 17. These paper feed components are mounted between a pair of bearing moldings 18, which are in turn mounted to the chassis 10 at each respective end thereof.

A printhead assembly 11 is mounted to the chassis 10 by means of respective printhead spacers 20 mounted to the chassis 10. The spacer moldings 20 increase the printhead assembly length to 220 mm allowing clearance on either side of 210 mm wide paper.

The printhead construction is shown generally in FIGS. 4 to 8.

The printhead assembly 11 includes a printed circuit board (PCB) 21 having mounted thereon various electronic components including a 64 MB DRAM 22, a PEC chip 23, a QA chip connector 24, a microcontroller 25, and a dual motor driver chip 26. The printhead is typically 203 mm long and has ten print chips 27 (FIG. 13), each typically 21 mm long. These print chips 27 are each disposed at a slight angle to the longitudinal axis of the printhead (see FIG. 12), with a slight overlap between each print chip which enables continuous transmission of ink over the entire length of the array. Each print chip 27 is electronically connected to an end of one of the tape automated bond (TAB) films 28, the other end of which is maintained in electrical contact with the undersurface of the printed circuit board 21 by means of a TAB film backing pad 29.

The preferred print chip construction is as described in U.S. Pat. No. 6,044,646 by the present applicant. Each such print chip 27 is approximately 21 mm long, less than 1 mm wide and about 0.3 mm high, and has on its lower surface thousands of MEMS inkjet nozzles 30, shown schematically in FIGS. 9A and 9B, arranged generally in six lines—one for each ink type to be applied. Each line of nozzles may follow a staggered pattern to allow closer dot spacing. Six corresponding lines of ink passages 31 extend through from the rear of the print chip to transport ink to the rear of each nozzle. To protect the delicate nozzles on the surface of the print chip each print chip has a nozzle guard 43, best seen in FIG. 9A, with microapertures 44 aligned with the nozzles 30, so that the ink drops ejected at high speed from the nozzles pass through these microapertures to be deposited on the paper passing over the platen 14.

Ink is delivered to the print chips via a distribution molding 35 and laminated stack 36 arrangement forming part of the printhead 11. Ink from an ink cassette 93 (FIGS. 26 and 27) is relayed via individual ink hoses 94 to individual ink inlet ports 34 integrally molded with a plastics

6

duct cover 39 which forms a lid over the plastics distribution molding 35. The distribution molding 35 includes six individual longitudinal ink ducts 40 and an air duct 41 which extend throughout the length of the array. Ink is transferred from the inlet ports 34 to respective ink ducts 40 via individual cross-flow ink channels 42, as best seen with reference to FIG. 7. It should be noted in this regard that although there are six ducts depicted, a different number of ducts might be provided. Six ducts are suitable for a printer capable of printing four color process (CMYK) as well as infra-red ink and fixative.

Air is delivered to the air duct 41 via an air inlet port 61, to supply air to each print chip 27, as described later with reference to FIGS. 6 to 8, 20 and 21.

Situated within a longitudinally extending stack recess 45 formed in the underside of distribution molding 35 are a number of laminated layers forming a laminated ink distribution stack 36. The layers of the laminate are typically formed of micro-molded plastics material. The TAB film 28 extends from the undersurface of the printhead PCB 21, around the rear of the distribution molding 35 to be received within a respective TAB film recess 46 (FIG. 21), a number of which are situated along a chip housing layer 47 of the laminated stack 36. The TAB film relays electrical signals from the printed circuit board 19 to individual print chips 27 supported by the laminated structure.

The distribution molding, laminated stack 36 and associated components are best described with reference to FIGS. 7 to 19.

FIG. 10 depicts the distribution molding cover 39 formed as a plastics molding and including a number of positioning spigots 48 which serve to locate the upper printhead cover 49 thereon.

As shown in FIG. 7, an ink transfer port 50 connects one of the ink ducts 40 (the fourth duct from the left) down to one of six lower ink ducts or transitional ducts 51 in the underside of the distribution molding. All of the ink ducts 40 have corresponding transfer ports 50 communicating with respective ones of the transitional ducts 51. The transitional ducts 51 are parallel with each other but angled acutely with respect to the ink ducts 40 so as to line up with the rows of ink holes of the first layer 52 of the laminated stack 36 to be described below.

The first layer 52 incorporates twenty four individual ink holes 53 for each of ten print chips 27. That is, where ten such print chips are provided, the first layer 52 includes two hundred and forty ink holes 53. The first layer 52 also includes a row of air holes 54 alongside one longitudinal edge thereof.

The individual groups of twenty four ink holes 53 are formed generally in a rectangular array with aligned rows of ink holes. Each row of four ink holes is aligned with a transitional duct 51 and is parallel to a respective print chip.

The undersurface of the first layer 52 includes underside recesses 55. Each recess 55 communicates with one of the ink holes of the two center-most rows of four holes 53 (considered in the direction transversely across the layer 52). That is, holes 53a (FIG. 13) deliver ink to the right hand recess 55a shown in FIG. 14, whereas the holes 53b deliver ink to the left most underside recesses 55b shown in FIG. 14.

The second layer 56 includes a pair of slots 57, each receiving ink from one of the underside recesses 55 of the first layer.

The second layer 56 also includes ink holes 53 which are aligned with the outer two sets of ink holes 53 of the first layer 52. That is, ink passing through the outer sixteen ink

holes **53** of the first layer **52** for each print chip pass directly through corresponding holes **53** passing through the second layer **56**.

The underside of the second layer **56** has formed therein a number of transversely extending channels **58** to relay ink passing through ink holes **53c** and **53d** toward the center. These channels extend to align with a pair of slots **59** formed through a third layer **60** of the laminate. It should be noted in this regard that the third layer **60** of the laminate includes four slots **59** corresponding with each print chip, with two inner slots being aligned with the pair of slots formed in the second layer **56** and outer slots between which the inner slots reside.

The third layer **60** also includes an array of air holes **54** aligned with the corresponding air hole arrays **54** provided in the first and second layers **52** and **56**.

The third layer **60** has only eight remaining ink holes **53** corresponding with each print chip. These outermost holes **53** are aligned with the outermost holes **53** provided in the first and second laminate layers. As shown in FIGS. **9A** and **9B**, the third layer **60** includes in its underside surface a transversely extending channel **61** corresponding to each hole **53**. These channels **61** deliver ink from the corresponding hole **53** to a position just outside the alignment of slots **59** therethrough.

As best seen in FIGS. **9A** and **9B**, the top three layers of the laminated stack **36** thus serve to direct the ink (shown by broken hatched lines in FIG. **9B**) from the more widely spaced ink ducts **40** of the distribution molding to slots aligned with the ink passages **31** through the upper surface of each print chip **27**.

As shown in FIG. **13**, which is a view from above the laminated stack, the slots **57** and **59** can in fact be comprised of discrete co-linear spaced slot segments.

The fourth layer **62** of the laminated stack **36** includes an array of ten chip-slots **65** each receiving the upper portion of a respective print chip **27**.

The fifth and final layer **64** also includes an array of chip-slots **65** which receive the chip and nozzle guard assembly **43**.

The TAB film **28** is sandwiched between the fourth and fifth layers **62** and **64**, one or both of which can be provided with recesses to accommodate the thickness of the TAB film.

The laminated stack is formed as a precision micro-molding, injection molded in an Acetal type material. It accommodates the array of print chips **27** with the TAB film already attached and mates with the cover molding **39** described earlier.

Rib details in the underside of the micro-molding provides support for the TAB film when they are bonded together. The TAB film forms the underside wall of the printhead module, as there is sufficient structural integrity between the pitch of the ribs to support a flexible film. The edges of the TAB film seal on the underside wall of the cover molding **39**. The chip is bonded onto one hundred micron wide ribs that run the length of the micro-molding, providing a final ink feed to the print nozzles.

The design of the micro-molding allow for a physical overlap of the print chips when they are butted in a line. Because the printhead chips now form a continuous strip with a generous tolerance, they can be adjusted digitally to produce a near perfect print pattern rather than relying on very close toleranced moldings and exotic materials to perform the same function. The pitch of the modules is typically 20.33 mm.

The individual layers of the laminated stack as well as the cover molding **39** and distribution molding can be glued or otherwise bonded together to provide a sealed unit. The ink paths can be sealed by a bonded transparent plastic film serving to indicate when inks are in the ink paths, so they can

be fully capped off when the upper part of the adhesive film is folded over. Ink charging is then complete.

The four upper layers **52**, **56**, **60**, **62** of the laminated stack **36** have aligned air holes **54** which communicate with air passages **63** formed as channels formed in the bottom surface of the fourth layer **62**, as shown in FIGS. **9b** and **13**. These passages provide pressurized air to the space between the print chip surface and the nozzle guard **43** whilst the printer is in operation. Air from this pressurized zone passes through the micro-apertures **44** in the nozzle guard, thus preventing the build-up of any dust or unwanted contaminants at those apertures. This supply of pressurized air can be turned off to prevent ink drying on the nozzle surfaces during periods of non-use of the printer, control of this air supply being by means of the air valve assembly shown in FIGS. **6** to **8**, **20** and **21**.

With reference to FIGS. **6** to **8**, within the air duct **41** of the printhead there is located an air valve molding **66** formed as a channel with a series of apertures **67** in its base. The spacing of these apertures corresponds to air passages **68** formed in the base of the air duct **41** (see FIG. **6**), the air valve molding being movable longitudinally within the air duct so that the apertures **67** can be brought into alignment with passages **68** to allow supply the pressurized air through the laminated stack to the cavity between the print chip and the nozzle guard, or moved out of alignment to close off the air supply. Compression springs **69** maintain a sealing inter-engagement of the bottom of the air valve molding **66** with the base of the air duct **41** to prevent leakage when the valve is closed.

The air valve molding **66** has a cam follower **70** extending from one end thereof, which engages an air valve cam surface **71** on an end cap **74** of the platen **14** so as to selectively move the air valve molding longitudinally within the air duct **41** according to the rotational positional of the multi-function platen **14**, which may be rotated between printing, capping and blotting positions depending on the operational status of the printer, as will be described below in more detail with reference to FIGS. **21** to **24**. When the platen **14** is in its rotational position for printing, the cam holds the air valve in its open position to supply air to the print chip surface, whereas when the platen is rotated to the non-printing position in which it caps off the micro-apertures of the nozzle guard, the cam moves the air valve molding to the valve closed position.

With reference to FIGS. **21** to **24**, the platen member **14** extends parallel to the printhead, supported by a rotary shaft **73** mounted in bearing molding **18** and rotatable by means of gear **79** (see FIG. **3**). The shaft is provided with a right hand end cap **74** and left hand end cap **75** at respective ends, having cams **76**, **77**.

The platen member **14** has a platen surface **78**, a capping portion **80** and an exposed blotting portion **81** extending along its length, each separated by 120°. During printing, the platen member is rotated so that the platen surface **78** is positioned opposite the printhead so that the platen surface acts as a support for that portion of the paper being printed at the time. When the printer is not in use, the platen member is rotated so that the capping portion **80** contacts the bottom of the printhead, sealing in a locus surrounding the micro-apertures **44**. This, in combination with the closure of the air valve by means of the air valve arrangement when the platen **14** is in its capping position, maintains a closed atmosphere at the print nozzle surface. This serves to reduce evaporation of the ink solvent (usually water) and thus reduce drying of ink on the print nozzles while the printer is not in use.

The third function of the rotary platen member is as an ink blotter to receive ink from priming of the print nozzles at printer start up or maintenance operations of the printer. During this printer mode, the platen member **14** is rotated so

that the exposed blotting portion **81** is located in the ink ejection path opposite the nozzle guard **43**. The exposed blotting portion **81** is an exposed part of a body of blotting material **82** inside the platen member **14**, so that the ink received on the exposed portion **81** is drawn into the body of the platen member.

Further details of the platen member construction may be seen from FIGS. **23** and **24**. The platen member consists generally of an extruded or molded hollow platen body **83** which forms the platen surface **78** and receives the shaped body of blotting material **82** of which a part projects through a longitudinal slot in the platen body to form the exposed blotting surface **81**. A flat portion **84** of the platen body **83** serves as a base for attachment of the capping member **80**, which consists of a capper housing **85**, a capper seal member **86** and a foam member **87** for contacting the nozzle guard **43**.

With reference again to FIG. **1**, each bearing molding **18** rides on a pair of vertical rails **101**. That is, the capping assembly is mounted to four vertical rails **101** enabling the assembly to move vertically. A spring **102** under either end of the capping assembly biases the assembly into a raised position, maintaining cams **76**, **77** in contact with the spacer projections **100**.

The printhead **11** is capped when not in use by the full-width capping member **80** using the elastomeric (or similar) seal **86**. In order to rotate the platen assembly **14**, the main roller drive motor is reversed. This brings a reversing gear into contact with the gear **79** on the end of the platen assembly and rotates it into one of its three functional positions, each separated by 120°.

The cams **76**, **77** on the platen end caps **74**, **75** co-operate with projections **100** on the respective printhead spacers **20** to control the spacing between the platen member and the printhead depending on the rotary position of the platen member. In this manner, the platen is moved away from the printhead during the transition between platen positions to provide sufficient clearance from the printhead and moved back to the appropriate distances for its respective paper support, capping and blotting functions.

In addition, the cam arrangement for the rotary platen provides a mechanism for fine adjustment of the distance between the platen surface and the printer nozzles by slight rotation of the platen **14**. This allows compensation of the nozzle-platen distance in response to the thickness of the paper or other material being printed, as detected by the optical paper thickness sensor arrangement illustrated in FIG. **25**.

The optical paper sensor includes an optical sensor **88** mounted on the lower surface of the PCB **21** and a sensor flag arrangement mounted on the arms **89** protruding from the distribution molding. The flag arrangement comprises a sensor flag member **90** mounted on a shaft **91** which is biased by torsion spring **92**. As paper enters the feed rollers, the lowermost portion of the flag member contacts the paper and rotates against the bias of the spring **92** by an amount dependent on the paper thickness. The optical sensor detects this movement of the flag member and the PCB responds to the detected paper thickness by causing compensatory rotation of the platen **14** to optimize the distance between the paper surface and the nozzles.

FIGS. **26** and **27** show attachment of the illustrated printhead assembly to a replaceable ink cassette **93**. Six different inks are supplied to the printhead through hoses **94** leading from an array of female ink valves **95** located inside the printer body. The replaceable cassette **93** containing a six compartment ink bladder and corresponding male valve array is inserted into the printer and mated to the valves **95**.

The cassette also contains an air inlet **96** and air filter (not shown), and mates to the air intake connector **97** situated beside the ink valves, leading to the air pump **98** supplying filtered air to the printhead. A QA chip is included in the cassette. The QA chip meets with a contact **99** located between the ink valves **95** and air intake connector **96** in the printer as the cassette is inserted to provide communication to the QA chip connector **24** on the PCB.

I claim:

1. A print engine assembly that comprises
 an elongate chassis;
 a platen mounted on the chassis;
 a feed mechanism for feeding print media over the platen and along a print feed path; and
 an elongate printhead assembly mounted on the chassis for carrying out a printing operation on the print media, the printhead assembly comprising
 an elongate ink distribution assembly having an inlet side, an outlet side, a plurality of ink paths that converge laterally from the inlet side to a longitudinal axis at the outlet side so as to distribute all ink at the inlet side to the outlet side and a plurality of printhead integrated circuit mounting formations along said longitudinal axis; and
 a plurality of printhead integrated circuits mounted in respective said mounting formations to form a single row of printhead integrated circuits, said printhead integrated circuits being mounted to receive ink from the ink paths.

2. A print engine as claimed in claim 1, in which the printhead assembly includes a control circuitry component mounted on the inlet side of the ink distribution assembly and including control circuitry connected to the printhead integrated circuits to control operation of the printhead integrated circuits.

3. A print engine as claimed in claim 2, which includes a number of tape automated bond films interposed between respective printhead integrated circuits and said control circuitry.

4. A print engine as claimed in claim 3, in which the ink distribution assembly includes an ink distribution member that defines a plurality of longitudinally extending ducts and a duct cover mounted on the ink distribution member to cover the ducts, the duct cover defining a number of ink inlet ports in fluid communication with respective ducts so that inks can be fed to the ducts.

5. A print engine as claimed in claim 4, in which the ink distribution assembly includes an ink distribution structure mounted on the ink distribution member, the ink distribution structure defining a plurality of holes in fluid communication with the ducts and contiguous passages and transverse channels that define the converging ink paths.

6. A print engine as claimed in claim 5, in which the ink distribution structure includes a laminated stack having a first layer that defines the holes and a number of subsequent layers, each subsequent layer having formed in it, said contiguous passages and transverse channels for bringing ink, via the holes of the first layer, to the printhead integrated circuits, the mounting formations being in the form of an array of slots in a integrated circuit restraining layer.

7. A print engine as claimed in claim 6, in which the integrated circuit restraining layer defines recesses to accommodate the tape automated bond film.