



US007414345B2

(12) **United States Patent**  
**Kageyama et al.**

(10) **Patent No.:** **US 7,414,345 B2**  
(45) **Date of Patent:** **Aug. 19, 2008**

(54) **COMMUTATOR AND ARMATURE**

(75) Inventors: **Ryohei Kageyama**, Hamamatsu (JP);  
**Nobuo Kasao**, Kosai (JP); **Toshiyuki Osawa**, Hamamatsu (JP)

(73) Assignee: **Asmo Co., Ltd.**, Kosai-shi (JP)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 22 days.

(21) Appl. No.: **11/489,283**

(22) Filed: **Jul. 19, 2006**

(65) **Prior Publication Data**

US 2007/0096582 A1 May 3, 2007

(30) **Foreign Application Priority Data**

Jul. 19, 2005 (JP) ..... 2005-209130

(51) **Int. Cl.**

**H02K 13/04** (2006.01)

**H01R 39/04** (2006.01)

(52) **U.S. Cl.** ..... 310/234; 310/233; 310/204

(58) **Field of Classification Search** ..... 310/204,  
310/233, 234, 197, 200

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,854,438 A \* 8/1989 Weissenberger et al. 192/107 R

6,181,046 B1 *	1/2001	Daikoku et al. ....	310/236
6,236,137 B1 *	5/2001	Tanaka et al. ....	310/233
6,246,141 B1 *	6/2001	Bailey .....	310/211
6,727,627 B1 *	4/2004	Sasaki et al. ....	310/211
2004/0095036 A1 *	5/2004	Yamamoto et al. ....	310/233
2005/0189841 A1 *	9/2005	Potocnik .....	310/236

**FOREIGN PATENT DOCUMENTS**

JP	2000-134873	5/2000
JP	2005137193 A *	5/2005

\* cited by examiner

*Primary Examiner*—Burton Mullins

(74) *Attorney, Agent, or Firm*—Fulwider Patton LLP

(57) **ABSTRACT**

A commutator including a commutator main body having a plurality of commutator pieces and a short-circuit member having a short-circuit conductor for short-circuiting commutator pieces. The short-circuit conductor includes superimposed first and second short-circuit member formation groups. The first short-circuit member formation group is thinner than the second short-circuit member formation group. The first and second short-circuit member formation groups are fixed to each other by crimping projections, which are formed on the second short-circuit member formation group through punching, in a state inserted through holes, which are formed in the second short-circuit member formation group.

**13 Claims, 5 Drawing Sheets**







Fig. 1




**Fig. 2**




**Fig. 3**




**Fig. 4**




**Fig. 5**




**Fig. 6A**




**Fig. 6B**




**Fig. 7A**




**Fig. 7B**



**Fig. 8**



**Fig. 9**



## COMMUTATOR AND ARMATURE

## RELATED APPLICATIONS

This application claims the benefit of foreign priority from Japanese Patent Application No. 2005-209130, filed Jul. 19, 2005.

## BACKGROUND OF THE INVENTION

The present invention relates to a commutator in which predetermined commutator pieces are short-circuited, and to an armature.

In the prior art, an armature for a motor having power feeding brushes may include a commutator in which a plurality of commutator pieces are short-circuited. Such a motor allows electric current to flow even to commutator pieces that are not in contact with power feeding brushes by short-circuiting predetermined commutator pieces. This enables a reduction in the number of power feeding brushes required in the motor.

In one example, in a rotating armature described in Japanese Laid-Open Patent Publication No. 2000-134873, a plurality of short-circuit conductors for short-circuiting commutator pieces of a commutator are arranged to overlap one another at an axial end portion of the commutator.

However, when the short-circuit conductors are arranged to overlap one another at the axial end portion of the commutator, the overlapping short-circuit conductors increase the length of the commutator in the axial direction, which in turn, increases the length of the armature in the axial direction. Further, the overlapping short-circuit conductors may rub against one another. This may rub off the coating of the short-circuit conductors. In such a case, the short-circuit conductors may be electrically connected (layer short). This may lower the manufacturing yield of the armature or cause erroneous operations of the armature and may eventually lower the reliability of the armature.

## SUMMARY OF THE INVENTION

It is an object of the present invention to provide a commutator and an armature that may be shortened in the axial direction and have high reliability.

To achieve the above object, one aspect of the present invention provides a commutator including a commutator main body and a short-circuit member. The commutator main body includes a cylindrical main body insulator and a plurality of commutator pieces held on an outer circumferential surface of the main body insulator so that the commutator pieces are arranged in a circumferential direction of the main body insulator. The short-circuit member is attached to the commutator main body and includes a short-circuit conductor that short-circuits the commutator pieces. The short-circuit conductor includes first and second short-circuit member formation groups arranged with one superimposed over the other. Each of the short-circuit member formation groups has a plurality of outer terminals arranged about an axis of the commutator, a plurality of inner terminals arranged about the axis of the commutator radially inward from the outer terminals, and a plurality of linking portions linking each of the outer terminals to one of the inner terminals. The linking portions in at least one of the first and second short-circuit member formation groups links the outer terminals and the inner terminals that are separated from each other by a predetermined angle in the circumferential direction. Each of the outer terminals in the first short-circuit member formation

group contacts one of the outer terminals in the second short-circuit member formation group, and each of the inner terminals in the first short-circuit member formation group contacts one of the inner terminals in the second short-circuit member formation group. The linking portions in the first short-circuit member formation group are maintained in non-contact with the linking portions in the second short-circuit member formation groups. The first short-circuit member formation group is thinner than the second short-circuit member formation group. The second short-circuit member formation group has a plurality of projections formed through punching, and the first short-circuit member formation group has a plurality of holes respectively corresponding to the projections. The first short-circuit member formation group and the second short-circuit member formation group are fixed to each other by crimping the projections in a state inserted through the corresponding holes.

A further aspect of the present invention provides an armature including the above commutator. The armature includes a rotation shaft extending through the axis of the commutator, and an armature core fixed to the rotation shaft so as to be axially aligned with the commutator. The armature core has a plurality of teeth. A plurality of coils are wound around the teeth.

## BRIEF DESCRIPTION OF THE DRAWINGS

The features of the present invention believed to be novel will become apparent from the attached claims. The invention, together with objects and advantages thereof, may best be understood by reference to the following description of the presently present embodiments together with the accompanying drawings in which:

FIG. 1 is a schematic cross-sectional view of an armature according to one embodiment of the present invention;

FIG. 2 is a plan view showing a short-circuit member included in the armature of FIG. 1;

FIG. 3 is a plan view illustrating a method for manufacturing the armature of FIG. 1;

FIG. 4 is a plan view illustrating the method for manufacturing the armature of FIG. 1;

FIG. 5 is a plan view illustrating the method for manufacturing the armature of FIG. 1;

FIGS. 6A and 6B are partially enlarged cross-sectional views illustrating the method for manufacturing the armature of FIG. 1;

FIGS. 7A and 7B are partially enlarged cross-sectional views illustrating the method for manufacturing the armature of FIG. 1;

FIG. 8 is a cross-sectional view of a short-circuit member according to another example of the present invention; and

FIG. 9 is a cross-sectional view of a short-circuit member according to a further example of the present invention.

## DETAILED DESCRIPTION OF THE PRESENT EMBODIMENTS

A present embodiment of the present invention will now be described with reference to FIGS. 1 to 7B. A motor includes a stator (not shown) and an armature 1, which is shown in FIG. 1. The stator has a plurality of permanent magnets that are arranged in the circumferential direction around a rotation axis L of the motor. FIG. 1 only shows one side of the armature 1 with respect to its axis, or with respect to the rotation axis L of the motor.

The armature 1 includes a metal rotation shaft 2, an armature core 3 fixed to the rotation shaft 2, a commutator 4 fixed

## 3

to the rotation shaft 2, and a plurality of coils 5. The rotation shaft 2 is rotatably supported by the stator. The armature core 3 is surrounded by the permanent magnets of the stator.

The armature core 3 has a tubular portion 3a, through which the rotation shaft 2 is inserted, and a plurality of teeth 3b (only one is shown in FIG. 1), which extend radially outward from the tubular portion 3a. The coils 5 are respectively wound around the teeth 3b.

The commutator 4 includes a commutator main body 11 and a short-circuit member 12, which is arranged at an axial end portion of the commutator main body 11. The commutator main body 11 includes a plurality of commutator pieces 13 that are arranged in the circumferential direction. In the present embodiment, the commutator main body 11 includes twenty-four commutator pieces 13 arranged in 15-degree intervals. The commutator main body 11 further includes a generally cylindrical main body insulator 14, which holds the radially inner side of the commutator pieces 13. More specifically, the commutator pieces 13 are fixed on the outer circumferential surface of the main body insulator 11 in a state spaced from one another in the circumferential direction so as to form a cylindrical shape as a whole. Anode and cathode power feeding brushes (not shown) are pressed against the commutator pieces 13 in a slidable manner from the radially outer side of the commutator 4.

One end (lower ends in FIG. 1) of each commutator piece 13 projects axially from the main body insulator 14 and is bent radially outward to form a wire connection portion 13a for hooking a coil 5. The main body insulator 14 is made of a thermosetting resin (a phenol resin in the present embodiment). A cylindrical portion 14a extending in the axial direction is formed at the center of one end surface of the main body insulator 14. The inner diameter of the cylindrical portion 14a is equal to the inner diameter of the main body insulator 14. The inner diameter of the main body insulator 14 is set to enable the rotation shaft 2 to be pressed-fitted into the main body insulator 14.

The short-circuit member 12 includes a short-circuit conductor 21 and a short-circuit insulator 22. The short-circuit conductor 21 short-circuits commutator pieces 13 that are arranged at predetermined angular intervals (120 degrees in the present embodiment). The short-circuit insulator 22 holds the short-circuit conductor 21 in a state embedded in the short-circuit insulator 22.

The short-circuit conductor 21 includes two superimposed short-circuit member formation groups 31 and 32. In FIG. 1, the first short-circuit member formation group 31 is arranged under the second short-circuit member formation group 32. As shown in FIG. 2, the short-circuit member formation groups 31 and 32 include a plurality of outer terminals 31a and 32a, a plurality of inner terminals 31b and 32b, and a plurality of linking portions 31c and 32c. The outer terminals 31a and 32a are arranged in the circumferential direction of the rotation shaft 2. The inner terminals 31b and 32b are arranged in the circumferential direction of the rotation shaft 2 inward from the outer terminals 31a and 32a. The linking portions 31c and 32c link the outer terminals 31a and 32a and the inner terminals 31b and 32b. The short-circuit member formation groups 31 and 32 are formed as layers respectively arranged along two substantially parallel flat planes. Thus, the short-circuit member formation group 31 never intersects the other short-circuit member formation group 32. In the present embodiment, the short-circuit member formation group 31 includes twenty-four outer terminals 31a, twenty-four inner terminals 31b, and twenty-four linking portions 31c, and the short-circuit member formation group 32 includes twenty-

## 4

four outer terminals 32a, twenty-four inner terminals 32b, and twenty-four linking portions 32c.

The linking portions 31c and 32c in the short-circuit member formation groups 31 and 32 link the corresponding outer terminals 31a and 32a and the corresponding inner terminals 31b and 32b at positions separated from each other by a predetermined angle (60 degrees corresponding to four terminals in the present embodiment). As shown in FIG. 3, each linking portion 31c in the lower first short-circuit member formation group 31 links one of the outer terminals 31a to one of the inner terminals 31b, which is located at a position separated from that outer terminal 31a by the predetermined angle in the counterclockwise direction. As shown in FIG. 4, each linking portion 32c in the upper second short-circuit member formation group 32 links one of the outer terminals 32a to one of the inner terminals 32b, which is located at a position separated from that outer terminal 32a by the predetermined angle in the clockwise direction. Further, the linking portions 31c and 32c in the present embodiment extends along an involute curve.

The first short-circuit member formation group 31 is thinner than the second short-circuit member formation group 32. Further, the first short-circuit member formation group 31 is formed from a material having a smaller electric resistivity than that of the second short-circuit member formation group 32. In the present embodiment, the first short-circuit member formation group 31 is formed from a copper material and the second short-circuit member formation group 32 is formed from a brass material. In the short-circuit member formation groups 31 and 32, the different parts (the outer terminals 31a and 32a, the inner terminals 31b and 32b, and the linking portions 31c and 32c) each have a constant thickness.

The linking portions 31c in the first short-circuit member formation group 31 are curved toward one side in the axial direction (the lower side in FIG. 1) with respect to the outer terminals 31a and the inner terminals 31b. More specifically, the linking portions 31c are curved away from the second short-circuit member formation group 32. To ease of visual understanding, FIG. 1 shows cross-sections taken along the linking portions 31c and 32c. Further, the linking portions 32c in the second short-circuit member formation group 32 lie along the same plane as the outer terminals 32a and the inner terminals 32b. When the short-circuit member formation groups 31 and 32 are superimposed, each outer terminal 31a comes in contact with one of the outer terminals 32a in the superimposing direction of the short-circuit member formation groups 31 and 32 and each inner terminal 31b comes in contact with one of the inner terminals 32b in the superimposing direction. However, the linking portions 31c and 32c do not come in contact with each other.

The short-circuit member formation groups 31 and 32 are crimped and fixed to each other. In detail, the outer terminals 31a and the inner terminals 31b in the first short-circuit member formation group 31 have holes 31d and 31e (refer to FIG. 6A). A conical inclined surface T is formed at the opening of each of the holes 31d and 31e in the side opposite to the second short-circuit member formation group 32. The inclined surface T is formed in a manner that the diameter of the hole enlarges at outer sides. The outer terminals 32a and the inner terminals 32b in the second short-circuit member formation group 32 are formed to have projections 32d and 32e (refer to FIG. 6A). The projections 32d and 32e, prior to the crimping, have a height that is high enough to reach at least the inclined surfaces T formed in the holes 31e and 31e when the short-circuit member formation groups 31 and 32 are superimposed. In the present embodiment, the height of



## 5

each of the projections **32d** and **32e** is set greater than the plate thickness of the first short-circuit member formation group **31** (refer to FIG. 6A).

The short-circuit member formation groups **31** and **32** are superimposed in a manner that the projections **32d** and **32e** are inserted into and through the corresponding holes **31d** and **31e** and crimped so that the short-circuit member formation groups **31** and **32** are fixed to each other (refer to FIG. 6B). The crimping deforms the tips of the projections **32d** and **32e** and covers the openings (the inclined surfaces T) of the corresponding holes **31d** and **31e**. The crimping is performed in a manner that the crimped projections **32d** and **32e** cover the entire inclined surfaces T but do not project from the surface of the first short-circuit member formation group **31**. The short-circuit member **12** with this structure electrically connects three outer terminals **31a** (**32a**) arranged at 120-degree intervals and three inner terminals **31b** (**32b**) arranged at 120-degree intervals.

In the short-circuit member formation groups **31** and **32**, each pair of the overlapping outer terminals **31a** and **32a** and each pair of the overlapping inner terminals **31b** and **32b** are also welded together (spot-welded) (not shown). In detail, the surfaces of the short-circuit member formation groups **31** and **32** are tin-plated in advance. The above welding melts the tin plating between the outer terminals **31a** and **32a** or between the inner terminals **31b** and **32b** and bonds the outer terminals **31a** and **32a** and the inner terminals **31b** and **32b** together. This stabilizes and reduces the contact resistance of the outer terminals **31a** and **32a** and the inner terminals **31b** and **32b**.

The short-circuit insulator **22** is made of a thermoplastic resin and differs in material from the main body insulator **14**, which is made of a thermosetting resin. The short-circuit insulator **22** is arranged between different parts of the short-circuit member formation groups **31** and **32** that form the short-circuit conductor **21** (the outer terminals **31a** and **32a**, the inner terminals **31b** and **32b**, and the linking portions **31c** and **32c**) to keep these parts spaced from one another. The short-circuit insulator **22** is also arranged at both sides of the short-circuit conductor **21** with respect to the axial direction to cover the short-circuit conductor **21** except for the outer terminals **31a** and **32a**.

As shown in FIG. 1, a boss **22a**, which extends from the axial end portion of the commutator main body **11**, is integrally formed with the short-circuit insulator **22**. Further, the short-circuit insulator **22** has a large-diameter portion **22b** at a basal end portion of the boss **22a**. The large-diameter portion **22b** projects downward in the axial direction from the axial end portion of the commutator main body **11** and has an outer diameter greater than the outer diameter of the boss **22a**. The inner diameter of the tubular short-circuit insulator **22** is equal to the outer diameter of the cylindrical portion **14a** of the main body insulator **14**. The short-circuit insulator **22** enables the cylindrical portion **14a** to be fitted therein. The short-circuit insulator **22** has a circular cross-section in a manner that its outer diameter changes smoothly from the large-diameter portion **22b** to the boss **22a**.

The short-circuit member **12** is arranged on the axial end portion of the commutator main body **11** to electrically connect its outer terminals **31a** and **32a** to the commutator pieces **13**. In detail, axial end portions (lower ends in FIG. 1) of the commutator pieces **13** are formed to have recesses **13b** (refer to FIG. 7A) corresponding to the outer terminals **31a** and **32a**. In a state in which the outer terminals **31a** and **32a** are arranged in the recesses **13b**, the two side walls of the recesses **13b** are crimped. The crimped walls are deformed to partially

## 6

cover the outer terminals **31a** and **32a**. As a result, the short-circuit member **12** is fixed to the commutator main body **11** (refer to FIG. 7B).

FIGS. 7A and 7B do not show the short-circuit insulator **22** of the short-circuit member **12** and schematically shows only the short-circuit conductor **21** of the short-circuit member **12**. FIG. 7B additionally shows a jig or, punch **41**, used for crimping. As shown in FIG. 1, the cylindrical portion **14a** of the main body insulator **14** is fitted in the short-circuit insulator **22**.

As shown in FIG. 1, the armature core **3** and the commutator **4** of the above-described structure are fixed arranged adjacent to each other in the axial direction with respect to the rotation shaft **2**, which is inserted through the tubular portion **3a** and the cylindrical portion **14a**. Further, the commutator **4** comes in contact with the tubular portion **3a** of the armature core **3** at the distal surface of the boss **22a**. The boss **22a** functions to guide and support a portion of each coil **5** that extends from a wire connection portion **13a** of the commutator piece **13** to a predetermined tooth **3b** located at a position separated from that wire connection portion **13a** in the circumferential direction. Such a portion of the coil **5** is referred to as a crossover wire **5a**. More specifically, the boss **22a** guides the coil **5** to prevent the coil **5** from coming into direct contact with the rotation shaft **2**, or to prevent each coil **5** from being abruptly bent with a sharp curvature.

The method for manufacturing the commutator **4** for the armature **1** with the above-described structure will now be described. First, a method for manufacturing the short-circuit member **12** will be described. The method for manufacturing the short-circuit member **12** includes a punching process, a superimposing process, an insulator filling process, and a removing process.

In the punching process, as shown in FIGS. 3 and 4, conductive plates **55** and **56** are punched out in a manner that the linking portions **31c** and **32c** in the short-circuit member formation groups **31** and **32** are formed spaced from one another in the circumferential direction, and inner linking portions **51** and **52** and outer linking portions **53** and **54** for annularly linking the linking portions **31c** and **32c** respectively at the inner side and the outer side in the radial direction are formed. In this state, the conductive plates **55** and **56** are punched out in a manner that the outer terminals **31a** and **32a** are formed spaced from one another in the circumferential direction, and the inner terminals **31b** and **32b** are formed spaced from one another in the circumferential direction. At the same time, the holes **31d** and **31e** and the projections **32d** and **32e** are formed. Further, at the same time, the linking portions **31c** in the first short-circuit member formation group **31** are curved to project toward one side in the axial direction from the outer terminals **31a** and the inner terminals **31b**.

The conductive plates **55** and **56** are punched out from the side of the surfaces of the second short-circuit member formation groups **31** and **32** facing each other toward the opposite surfaces. More specifically, the conductive plate **55** corresponding to the first short-circuit member formation group **31** is punched out downward in FIG. 1. The conductive plate **56** corresponding to the second short-circuit member formation group **32** is punched out upward in FIG. 1. Further, the conductive plate **55**, which corresponds to the first short-circuit member formation group **31**, is thinner than the conductive plate **56**, which corresponds to the second short-circuit member formation group **32**, and is formed from a material having a smaller electrical resistivity than the conductive plate **56**. More specifically, the conductive plate **55** is formed from a copper material, and the conductive plate **56** is

formed from a brass material. The surfaces of the conductive plates **55** and **56** are tin-plated in advance.

In the superimposing process, the two conductive plates **55** and **56** that have been punched out are superimposed as shown in FIG. 5. Here, the projections **32d** and **32e** are inserted through the holes **31d** and **31e** (refer to FIG. 6A) and crimped in this state. As a result, the tips of the projections **32d** and **32e** are deformed to cover the openings of the holes **31d** and **31e** and fix the two conductive plates **55** and **56** each other (refer to FIG. 6B).

After the crimping, the overlapping outer terminals **31a** and **32a** and the overlapping inner terminals **31b** and **32b** are further spot-welded. In detail, the tin plating between the outer terminals **31a** and **32a** and between the inner terminals **31b** and **32b** is melted to bond the terminals together.

In the insulator filling process, the short-circuit insulator **22** is formed in the conductive plates **55** and **56** as shown by double-dashed lines in FIG. 5. In detail, the superimposed conductive plates **55** and **56** are placed in a mold (not shown), and molten resin material is filled into the mold and solidified. As a result, resin flows into the space between parts of the conductive plates **55** and **56**. This forms a resin portion including the short-circuit insulator **22**.

The resin material used here is a thermosetting resin material. The molten resin material is first injected into spaces between the linking portions **31c** and linking portions **32c** facing one another. The resin material then flows toward other parts including a part corresponding to the boss **22a** through gaps between the linking portions **31c** and gaps between the linking portions **32c**. This forms the resin portion including the short-circuit insulator **22**. The mold used for forming the resin portion has a resin material injection inlet through which the molten resin material is first injected into the gaps between the linking portions **31c** and the linking portions **32c**.

In the removing process, the inner linking portions **51** and **52** and the outer linking portions **53** and **54** of the conductive plates **55** and **56** are punched out and removed. This completes the manufacture of the short-circuit member **12** shown in FIG. 2.

Next, in a commutator manufacturing process, the short-circuit member **12** is attached to an intermediate member, which becomes the commutator main body **11**. In detail, in a process separate from the manufacturing processes of the short-circuit member **12**, the intermediate member (not shown) is manufactured by molding the main body insulator **14** in a conductive tubular member (not shown), which includes the commutator pieces **13**. More specifically, in a state in which the conductive tubular member is arranged in a mold (not shown), a molten resin material is filled into the mold and solidified. This forms a resin portion including the main body insulator **14** surrounded by the conductive tubular member. In a process described later, the conductive tubular member is divided to form the twenty-four commutator pieces **13**. The resin material used for the molding is the thermosetting resin (phenol resin etc.) described above. The mold used for the molding has projections (not shown) for forming the recess **13b** (refer to FIG. 7A). Thus, the recesses **13b** are formed in the conductive tubular member with the mold that molds the resin portion (main body insulator **14**) when the mold is clamped.

The short-circuit member **12** is fixed to the axial end portion of the intermediate member so that its outer terminals **31a** and **32a** are electrically connected to the conductive tubular member. In detail, in a state in which the outer terminals **31a** and **32a** are arranged in the recesses **13b**, the short-circuit member **12** undergoes crimping. More specifically, in a state in which the outer terminals **31a** and **32a** are arranged in the

recesses **13b**, the two side walls of the recesses **13b** are crimped by the jig (punch) **41**. As a result, the crimped walls partially cover the outer terminals **31a** and **32a** (refer to FIG. 7B).

Next, the conductive tubular member is cut into a plurality of portions in the circumferential direction to form a plurality (twenty-four) of the commutator pieces **13**. This completes the manufacture of the commutator **4**. In this state, the wire connection portions **13a** of the commutator **4** are not yet bent and the coils **5** are yet to be hooked to the wire connection portions **13a**.

Next, in a provisional assembly process, the armature core **3** and the commutator **4** are assembled with the rotation shaft **2** by pressing the rotation shaft **2** into the armature core **3** and the commutator **4**. In this state, to prevent the distal surface of the boss **22a** from coming into contact with the tubular portion **3a** of the armature core **3**, a gap is formed between the boss **22a** and the tubular portion **3a** of the armature core **3** in the axial direction.

Next, in a coiling process, in a state in which the coils **5** are hooked on the wire connection portions **13a**, the coils **5** are wound around predetermined teeth **3b** of the armature core **3** by concentrated winding or distributed winding. In this state, the portion of each coil **5** extending from the corresponding wire connection portion **13a** to the corresponding predetermined tooth **3b**, that is, the crossover wire **5a**, is entwined to and supported by the boss **22a**. More specifically, the crossover wire **5a** is guided free from direct contact with the rotation shaft **2** so that it is not abruptly bent at a sharp curvature in accordance with the diameter of the rotation shaft **2**.

In a main assembly process, at least one of the armature core **3** and the commutator **4** is pressed and moved along the rotation shaft **2** in a manner that the distal surface of the boss **22a** is pressed against the tubular portion **3a** of the armature core **3** as shown in FIG. 1. This completes the manufacture of the armature **1**.

The armature **1** with the above-described structure enables electric current to flow not only through the commutator pieces **13** that are in direct contact with the anode and cathode power feeding brushes but also through the commutator pieces **13** that are short-circuited with the commutator pieces **13** that are in contact with the brushes through the short-circuit conductor **21** of the short-circuit member **12**. This structure reduces the number of the anode and cathode power feeding brushes required, and enables electric current to be simultaneously supplied to a larger number of coils **5**.

The present embodiment has the advantages described below.

(1) The short-circuit conductor **21** is formed by superimposing the two short-circuit member formation groups **31** and **32**, each of which is formed as a single layer. The short-circuit conductor **21** of the present embodiment electrically connects three outer terminals **31a** (**32a**), which are arranged at 120-degree intervals, and connect the outer terminals **31a** and **32a** to the twenty-four commutator pieces **13**. This short-circuits the commutator pieces **13** that are arranged at 120-degree intervals. More specifically, the short-circuit conductor **21** of the present embodiment has a smaller thickness (axial dimension) than the conventional short-circuit conductors. Such a thin short-circuit conductor **21** enables the commutator pieces **13** to be short-circuits. Further, the short-circuit member formation groups **31** and **32** are generally flat and may easily be formed by punching the conductive plates **55** and **56**.

The first short-circuit member formation group **31** is thinner than the second short-circuit member formation group **32**. In other words, the second short-circuit member formation

group **32** is thicker than the first short-circuit member formation group **31** (refer to FIG. 6A). Thus, when the projections **32d** and **32e** of the second short-circuit member formation group **32** are formed through punching, the projections **32d** and **32e** are easily projected by a large amount. Further, because the first short-circuit member formation group **31** is thinner than the second short-circuit member formation group **32**, the holes **31d** and **31e** of the first short-circuit member formation group **31** are formed with a relatively short length in the axial direction. This facilitates crimping when the projections **32d** and **32e** are inserted through the holes **31d** and **31e**. In detail, the structure in which the tips of the projections **32d** and **32e** are crimped to cover the openings of the holes **31d** and **31e** (refer to FIG. 6B) is easily obtained. As a result, the electrical and mechanical connection between the two short-circuit member formation groups **31** and **32** is strong and easily realized. Further, the linking portions **31c** and **32c** are spaced from each other in the superimposing direction and do not come in contact with each other. As a result, the linking portions **31c** and **32c** are prevented from rubbing against each other and are prevented from being electrically connected to each other (layer short). This improves the electrical reliability of the commutator.

(2) The first short-circuit member formation group **31** is thinner than the second short-circuit member formation group **32** but is formed from a copper material, which has a smaller electric resistivity than the brass material used for the second short-circuit member formation group **32**. As a result, the short-circuit member formation groups **31** and **32** have substantially the same electric resistance. The second short-circuit member formation group **32**, which is formed from a material having a greater electric resistivity than the material of the first short-circuit member formation group **31**, may be formed from a low-cost material such as a brass material. This prevents a cost increase.

(3) The short-circuit conductor **21** excluding the outer terminals **31a** and **32a** is embedded in the short-circuit insulator **22**. Thus, the linking portions **31c** and **32c** remain spaced away from each other. This prevents the linking portions **31c** and **32c** from rubbing against each other and prevents the short-circuit conductor **21** and the coils **5** from rubbing against each other. Thus, they are not electrically connected to each other (layer short).

(4) The main body insulator **14** of the commutator main body **11** and the short-circuit insulator **22** of the short-circuit member **12** are formed from different materials. More specifically, the main body insulator **14** is formed from a material having superior heat expansion and contraction characteristics and a high mechanical strength (a thermosetting resin, namely, a phenol resin in the present embodiment). This reduces displacement of the commutator pieces **13** in the radial direction. The short-circuit member **12** including the short-circuit insulator **22** is arranged on the axial end portion of the commutator main body **11**. Thus, even though the short-circuit insulator **22** is formed from a material having relatively poor heat expansion and contraction characteristics and a relatively low mechanical strength (a thermoplastic resin in the present embodiment), the short-circuit insulator **22** does not greatly increase displacement of the commutator pieces **13** from one another in the radial direction. Thus, the short-circuit insulator **22** may be formed from a material having poor heat expansion and contraction characteristics and a low mechanical strength. In this case, the short-circuit member **12** is manufactured at a low cost and is easily recycled.

(5) The conical inclined surfaces **T** are formed at the openings of the holes **31d** and **31e**. Thus, the tips of the projections

**32d** and **32e**, which are crimped, easily cover the openings of the holes **31d** and **31e**. More specifically, when the inclined surfaces **T** are not formed in the openings of the holes, the projections inserted through the holes need to be formed sufficiently larger than the plate thickness of the first short-circuit member formation group **31** to ensure that crimping is performed. However, such long projections are difficult to form by punching. Further, when the inclined surfaces **T** are not formed in the openings of the holes, parts of the crimped projections may protrude from the surface of the short-circuit member formation group. Such problem does not occur with the present embodiment since the inclined surfaces **T** are formed in the openings of the holes **31d** and **31e**.

(6) The length of the projections **32d** and **32e** is greater than the plate thickness of the first short-circuit member formation group **31**. Thus, parts of the projections **32d** and **32e** that are crimped cover the entire inclined surfaces **T**. This increases the fixing strength of the short-circuit member formation groups **31** and **32**.

The above embodiment may be modified in the following forms.

In the above embodiment, the commutator **4** includes the twenty-four commutator pieces **13**, with three commutator pieces **13** arranged at 120-degree intervals short-circuited with one another. However, the number of the commutator pieces **13** included in the commutator **4** should not be limited to twenty-four, and the angular interval at which the short-circuited commutator pieces **13** are arranged is not limited to 120 degrees. For example, the commutator **4** may include sixteen commutator pieces **13**, with two commutator pieces **13** arranged at 180-degree intervals short-circuited with each other. In this case, the structure of the short-circuit member **12** is modified accordingly.

In the above embodiment, the linking portions **31c** in the first short-circuit member formation group **31** are curved in a direction in which the linking portions **31c** are spaced from the linking portions **32c** in the second short-circuit member formation group **32**. However, this may be changed to other structures. It is only required that the linking portions **31c** and **32c** are prevented from coming into contact with each other.

For example, as shown in FIG. 8, linking portions **61a** and **62a** in two short-circuit member formation groups **61** and **62** may be bent with respect to outer terminals **61b** and **62b** and inner terminals **61c** and **62c** in a direction in which the linking portions **61a** and **62a** included in the two short-circuit member formation groups **61** and **62** are spaced from each other so that the linking portions **61a** and **62a** do not come in contact with each other in the superimposing direction of the short-circuit member formation groups **61** and **62**.

Further, as shown in FIG. 9, linking portions **71a** and **72a** in two short-circuit member formation groups **71** and **72** may be formed to be thinner than outer terminals **71b** and **72b** and inner terminals **71c** and **72c**. In this case, the linking portions **71a** and **72a** do not come in contact with each other in the superimposing direction of the short-circuit member formation groups **71** and **72**.

Further, an insulator paper may be arranged between the linking portions in the two short-circuit member formation groups to prevent the linking portions from coming into contact with each other in the superimposing direction. Further, instead of the short-circuit insulator **22**, such an insulator paper may be used to maintain the intervals between different parts of a short-circuit conductor.

In the above embodiment, the linking portions **31c** and **32c** in the short-circuit member formation groups **31** and **32** respectively link the outer terminals **31a** and **32a** and the inner terminals **31b** and **32b** that are arranged at positions

## 11

separated from one another by the predetermined angle in the circumferential direction. However, it is only required that the linking portions in at least one of the short-circuit member formation groups link the outer terminals and the inner terminals that are arranged at positions separated from each other by the predetermined angle in the circumferential direction. That is, the linking portions in the other one of the short-circuit member formation groups may extend only in the radial direction to link the outer terminals and the inner terminals that are not separated in the circumferential direction.

In the above embodiment, each of the linking portions **31c** and **32c** extends along an involute curve. However, the curve along which each linking portion extends should not be limited to an involute curve. Further, the linking portions **31c** and **32c** may extend along a straight line inclined with respect to the radial direction.

In the above embodiment, the first short-circuit member formation group **31** is formed from a material having a smaller electric resistivity than the material used for the second short-circuit member formation group **32**. The present invention should not be limited to this structure. The two short-circuit member formation groups **31** and **32** may be formed from the same material.

In the above embodiment, the two short-circuit member formation groups **31** and **32** are fixed through crimping and spot-welding. However, the present invention should not be limited to this structure. The welding need not be performed, or welding other than the spot welding may be performed. In the above embodiment, the short-circuit member formation groups **31** and **32** are bonded together by melting the tin plating applied in advance to the short-circuit member formation groups **31** and **32**. However, the base materials of the short-circuit member formation groups **31** and **32** may be melted to bond the short-circuit member formation groups **31** and **32** together.

In the above embodiment, the main body insulator **14** of the commutator main body **11** and the short-circuit insulator **22** of the short-circuit member **12** are formed from different materials. However, the present invention should not be limited to this structure. The main body insulator and the short-circuit insulator may both be formed from a thermosetting resin (a phenol resin etc.).

In the above embodiment, the boss **22a** is integrally formed with the short-circuit insulator **22**. However, the present invention should not be limited to this structure. The boss **22a** may be omitted from the short-circuit insulator **22**. Further, in the above embodiment, the short-circuit insulator **22** has the large-diameter portion **22b**. However, the large-diameter portion **22b** may be omitted from the short-circuit insulator **22**.

In the above embodiment, the boss **22a** functions to position the commutator **4** with respect to the armature core **3** in the axial direction and also functions to guide the crossover wires **5a**. However, the boss **22a** does not have to have the two functions and may have only one of the functions.

In the above embodiment, the conical inclined surfaces T are formed at the holes **31d** and **31e**. However, the inclined surfaces T do not have to be formed.

The short-circuit member **12**, the commutator **4**, and the armature **1** in the above embodiment do not have to be manufactured using the manufacturing methods described above.

The invention claimed is:

**1.** A commutator comprising:

a commutator main body including a cylindrical main body insulator and a plurality of commutator pieces held on an outer circumferential surface of the main body insulator

## 12

so that the commutator pieces are arranged in a circumferential direction of the main body insulator; and

a short-circuit member attached to the commutator main body and including a short-circuit conductor that short-circuits the commutator pieces;

wherein the short-circuit conductor includes first and second short-circuit member formation groups arranged with one of said first and second short-circuit member formation groups superimposed over the other with respect to a direction of an axis of the commutator, with each of the short-circuit member formation groups having a plurality of outer terminals arranged about the axis of the commutator, a plurality of inner terminals arranged about the axis of the commutator radially inward from the outer terminals, and a plurality of linking portions linking each of the outer terminals to one of the inner terminals, wherein the linking portions in at least one of the first and second short-circuit member formation groups links the outer terminals and the inner terminals that are separated from each other by a predetermined angle in the circumferential direction;

wherein each of the outer terminals in the first short-circuit member formation group contacts one of the outer terminals in the second short-circuit member formation group, each of the inner terminals in the first short-circuit member formation group contacts one of the inner terminals in the second short-circuit member formation group, and the linking portions in the first short-circuit member formation group are maintained in non-contact with the linking portions in the second short-circuit member formation group; and

wherein the first short-circuit member formation group is thinner than the second short-circuit member formation group with respect to the direction of the axis of the commutator, the second short-circuit member formation group has a plurality of projections formed through punching, the first short-circuit member formation group has a plurality of holes respectively corresponding to the projections, and the first short-circuit member formation group and the second short-circuit member formation group are fixed to each other by crimping the projections in a state inserted through the corresponding holes.

**2.** The commutator according to claim **1**, wherein the first short-circuit member formation group is formed from a material having a smaller electric resistivity than the second short-circuit member formation group.

**3.** The commutator according to claim **2**, wherein the first short-circuit member formation group is formed from a copper material, and the second short-circuit member formation group is formed from a brass material.

**4.** The commutator according to claim **1**, wherein the short-circuit member includes a short-circuit insulator for holding the short-circuit conductor in a state embedded in the short-circuit insulator.

**5.** The commutator according to claim **4**, wherein the main body insulator and the short-circuit insulator are formed from different materials.

**6.** The commutator according to claim **5**, wherein the main body insulator is formed from a thermosetting resin, and the short-circuit insulator is formed from a thermoplastic resin.

**7.** The commutator according to claim **1**, wherein the holes have openings opposite the second short-circuit member formation group and include conical inclined surfaces having a diameter that is outwardly enlarged.

**13**

**8.** The commutator according to claim **7**, wherein the projections are punched out to have a length greater than a plate thickness of the first short-circuit member formation group.

**9.** The commutator according to claim **1**, wherein the projections are formed on the outer terminals and the inner terminals in the second short-circuit member formation group, and the holes are formed in the outer terminals and the inner terminals in the first short-circuit member formation group.

**10.** The commutator according to claim **1**, wherein at least either one of the linking portions in the first short-circuit member formation group and the linking portions in the second short-circuit member formation group are curved or bent to be spaced from the other one of the linking portions in the first short-circuit member formation group and the linking portions in the second short-circuit member formation group in a superimposing direction of the two short-circuit member formation groups.

**14**

**11.** The commutator according to claim **1**, wherein the linking portions are thinner than the outer terminals and the inner terminals in at least one of the first short-circuit member formation group and the second short-circuit member formation group.

**12.** The commutator according to claim **1**, wherein the short-circuit member is arranged at one axial end of the commutator main body.

**13.** An armature comprising:

the commutator according to claim **1**;

a rotation shaft extending through the axis of the commutator;

an armature core fixed to the rotation shaft so as to be axially aligned with the commutator, wherein the armature core has a plurality of teeth; and

a plurality of coils wound around the teeth.

\* \* \* \* \*