

US007422243B2

(12) **United States Patent**
Kudo et al.

(10) **Patent No.:** **US 7,422,243 B2**
(45) **Date of Patent:** **Sep. 9, 2008**

(54) **STRUCTURE OF FUEL PUMP
INSTALLATION AREA FOR TWO-WHEELED
VEHICLE**

(75) Inventors: **Takashi Kudo**, Saitama (JP); **Yoshitaka Yanagibashi**, Saitama (JP)

(73) Assignee: **Honda Motor Co., Ltd.**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 728 days.

(21) Appl. No.: **10/874,382**

(22) Filed: **Jun. 24, 2004**

(65) **Prior Publication Data**

US 2005/0045399 A1 Mar. 3, 2005

(30) **Foreign Application Priority Data**

Jul. 29, 2003 (JP) 2003-282204
Jul. 29, 2003 (JP) 2003-282206

(51) **Int. Cl.**

B62D 61/02 (2006.01)
B60P 3/22 (2006.01)
F02M 37/00 (2006.01)

(52) **U.S. Cl.** **280/834**; 280/833; 280/835;
180/219; 123/509

(58) **Field of Classification Search** 123/509;
137/565.17; 180/219; 224/413; 280/833,
280/834, 835

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,717,163 A * 1/1988 Tsukiji 280/835

4,871,041 A * 10/1989 Saito et al. 180/219
5,490,573 A * 2/1996 Hagiwara et al. 180/68.1
6,182,640 B1 * 2/2001 Nakashima et al. 123/516
6,253,790 B1 * 7/2001 Hara 137/565.17
6,401,750 B2 * 6/2002 Tokunaga 137/565.34
6,588,451 B2 * 7/2003 Kuroshita et al. 137/565.17
6,616,187 B2 * 9/2003 Nagasaka 280/835
6,655,363 B2 * 12/2003 Kobayashi et al. 123/509
6,907,865 B1 * 6/2005 Hanby 123/509
6,913,693 B2 * 7/2005 Unuki 210/416.4

FOREIGN PATENT DOCUMENTS

JP 2000-72074 A 3/2000
JP 3370888 B2 11/2002

* cited by examiner


Primary Examiner—Lesley D. Morris
Assistant Examiner—Marc A Scharich

(74) *Attorney, Agent, or Firm*—Birch, Stewart, Kolasch & Birch, LLP

(57) **ABSTRACT**

A fuel pump installation area for a vehicle for enhancing the stiffness of the fuel pump built in a fuel tank and for enhancing the stiffness of an installation area of a tank installation stay on the fuel tank side. In a motorcycle in which a fuel tank is installed to the body frame and a fuel pump is provided within this fuel tank, the fuel pump is installed to the fuel tank via a pump installation member. To the pump installation member, a tank installation stay for fixing the fuel tank to the body frame is installed. The left and right side walls may be formed by depressing the center of the underside of the fuel tank upwardly over the front and the rear. Concave-shaped engaging members are installed by engaging left and right convex portions provided on the body frame with these engaging members, respectively.

20 Claims, 16 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11(a)




FIG. 11(b)




FIG. 12(b)




FIG. 12(a)





FIG. 13






FIG. 15




FIG. 16

1

**STRUCTURE OF FUEL PUMP
INSTALLATION AREA FOR TWO-WHEELED
VEHICLE**

CROSS-REFERENCE TO RELATED
APPLICATIONS

The present application claims priority under 35 USC 119 to Japanese Patent Application Nos. 2003-282204 and 2003-282206 both filed on Jul. 29, 2003 the entire contents thereof are hereby incorporated by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to structure of a fuel pump installation area for a two-wheeled vehicle.

2. Description of Background Art

Conventionally, as the structure of a fuel pump installation area for a two-wheeled vehicle, there is known a structure in which a fuel pump is arranged within a fuel tank and installed on a bottom wall of the fuel tank. See, for example, Japanese Patent Laid-Open No. 2000-72074.

FIG. 2 of Japanese Patent Laid-Open No. 2000-72074 will be explained with reference to FIG. 15 of the attached drawings. In this respect, the reference numerals have been re-designated.

FIG. 15 is a cross-sectional view showing conventional structure of a fuel pump installation area for a two-wheeled vehicle wherein a fuel pump unit 303 has been arranged within a fuel tank 300 by installing a cup 302 on a bottom 301, located in the rear of the fuel tank 300, that is curved in a convex shape downwardly and installing the fuel pump unit 303 onto this cup 302.

In FIG. 15, a main frame 305 is provided for constituting a body frame 306; 307, a fuel tank installation stay for installing the rear portion of the fuel tank 300 on the body frame 306 side; 311, an engine; and 312, 313, a throttle body and an air cleaner which are air intake system parts installed to the engine 311, respectively.

The fuel pump unit 303 is long and narrow in shape with one end portion being mounted to the cup 302. However, the fuel pump unit 303 is equipped with articles that have a weight such as a motor. Therefore, a large moment occurs on the fuel pump unit 303 when the vehicle is in operation. Accordingly, in order to support this moment, the cup 302 and the bottom 301 of the fuel tank 300 require a high stiffness.

Also, although the fuel tank installation stay 307 has been directly installed to the bottom 301 of the fuel tank 300, the bottom 301 requires a high stiffness in order to support the fuel tank 300 filled with fuel.

Conventionally, a structure for installing a fuel tank on a two-wheeled vehicle, is known wherein on an inner wall of the front part of the fuel tank there is provided a concave portion with a body frame being provided with a convex portion. The convex portion is caused to engage with the concave portion to thereby install the fuel tank. See, for example, Japanese Patent No. 3370888.

FIG. 7 of Japanese Patent No. 3370888 will be explained with reference to the following FIG. 16. In this respect, in FIG. 16, only the upper half part of FIG. 7 of Japanese Patent No. 3370888 is shown, and reference numerals have been re-designated.

FIG. 16 is a front view (partially cross-sectional view) of principal part showing a conventional structure for installing a fuel tank for a two-wheeled vehicle. A left inside plate 1302 of a left tank portion 1301 is provided on the fuel tank 1300

2

and a right inside plate 1304 of a right tank portion 1303 is provided. An engaging member 1306 is installed, respectively; in the lower part of a main frame 1307. A gusset 1308 is installed and to this gusset 1308, a spindle 1311 for extending from side to side is installed so as to penetrate there-through. A rubber shock absorbing member 1312 is fitted in both end portions of this spindle 1311, respectively. The rubber shock absorbing members 1312, 1312 are caused to engage with those engaging members 1306, 1306 on the fuel tank 1300 side. In this respect, a concave portion 1313 is formed between the left and right inside plates 1302, 1304 of the fuel tank 1300.

In a case of installing the above-described engaging members 1306 to the left and right inside plates 1302, 1304 of the fuel tank 1300 by welding, if a distance between the left and right inside plates 1302, 1304 is small, it will become difficult to insert, within the concave portion 1313, a welding jig for positioning or fixing the engaging member 1306 in advance on a welder or the fuel tank 1300 during welding. Thus, the workability during welding will be degraded. Further, if the distance between the left and right inside plates 1302, 1304 is made larger, the capacity of the fuel tank 1300 will be reduced. If there is made an attempt to secure the capacity of the fuel tank 1300, the fuel tank 1300 will become large-sized.

Also, in order to reduce the cost, there is a demand for applying the same engaging members 1306 to different types of two-wheeled vehicles. If usable for other vehicle types by a slight change even if not the same engaging members, the cost will be able to be reduced. Further, if setting (for example, size) of the rubber shock absorbing member 1312 could be simply changed by a slight change in the engaging member 1306 depending upon the vehicle type, a condition suitable for the vehicle type will be obtained, which is more preferable.

SUMMARY AND OBJECTS OF THE
INVENTION

It is an object of the present invention to enhance the stiffness of an installation area of a fuel pump built in the fuel tank to the fuel tank, and to enhance also the stiffness of an installation area of the tank installation stay on the fuel tank side concerning the structure of a fuel pump installation area for a two-wheeled vehicle.

According to the present invention, there is provided a two-wheeled vehicle in which a fuel tank is installed on a body frame and a fuel pump is provided within this fuel tank. The fuel pump is installed on the fuel tank via a pump installation member and to this pump installation member, a tank installation stay for fixing the fuel tank to the body frame is installed.

The present invention provides an axis of a cylinder of an engine arranged below the fuel tank that is caused to stand up, an air intake system part for extending toward the rear is installed to the rear of the cylinder. The pump installation member and the tank installation stay are arranged substantially above the air intake system part.

In the present invention, since the fuel pump is installed on the fuel tank via the pump installation member and to this pump installation member, the tank installation stay has been installed, as compared with, for example, a case where the fuel pump has been directly installed to the bottom wall of the fuel tank, the stiffness of the fuel pump installation area can be enhanced by the pump installation member. By installing the tank installation stay to such a fuel pump installation area with enhanced stiffness, the stiffness of the fuel pump instal-

3

lation area can be further enhanced, and stiffness of the installation area of the tank installation stay onto the fuel tank side can be also enhanced. Therefore, the fuel pump can be further reliably supported and sound vibration performance of the vehicle can be improved.

According to the present invention, the engine in which the axis of the cylinder has been caused to stand up is shaped such that the front part of the bottom wall of the fuel tank is depressed upwardly and the rear part of the bottom wall of the fuel tank bulges downwardly. In an engine in which the fuel pump has been arranged within the fuel tank, the fuel pump is to be installed in the rear part of the bottom wall at the lowest position of portions of the fuel tank. Further, if the air intake system parts extends toward the rear from the engine, the rear part of the bottom wall of the fuel tank which is located above the air intake system parts will become substantially flat, and the pump installation member will become substantially flush with the tank installation stay so that it becomes possible to combine by making them to come in close proximity to each other. If the pump installation member comes in close proximity to the tank installation stay, it will be possible to shorten the tank installation stay, and to firmly install the fuel tank to the body frame side. Also, the weight of the tank installation stay will be able to be saved.

It is a problem of the present invention to prevent, concerning the structure for installing a fuel tank for a two-wheeled vehicle, the fuel tank from becoming large-sized while securing the capacity thereof, and to enhance general-purpose properties of an installation member for installing the fuel tank to the body frame. Further the present invention makes it possible to perform a slight change in the installation member while restraining the cost from increasing.

According to the present invention, there is provided a structure for installing a body frame for a two-wheeled vehicle in which on left and right inner walls caused by depressing the center of the underside of the fuel tank upwardly over the front and the rear, concave-shaped engaging members are installed, respectively; and the fuel tank is installed to the body frame by engaging left and right convex portions provided on the body frame with these engaging members, respectively. Each engaging member is constructed of two members, a base member welded to the fuel tank and an engaging body and an engaging body for fastening to this base member by means of fastening means.

The present invention includes a concave portion to be provided on the engaging member that is constructed of a first concave portion provided on the base member and a second concave portion provided on the engaging body.

The present invention includes a tank-side rear part installation area provided in the rear of the fuel tank that is constructed such that a tank installation stay for integrally extending from a pump installation member for installing a fuel pump arranged within the fuel tank to the fuel tank is installed to the body frame.

In the present invention aim 1, since the engaging member is constructed of two members, a base member welded to the fuel tank and an engaging body for fastening to this base member by means of fastening means, it is possible to reduce a size of the base member of the present invention to be smaller than the conventional engaging member. In a case of installing the base member to the fuel tank by welding it is easy to insert a welding jig or a welder for positioning or fixing the base member on left and right inner walls inside the fuel tank without interfering with the left and right inner walls.

Accordingly, the workability of the base member during welding can be enhanced, and the capacity of the fuel tank can

4

be secured, or the fuel tank can be prevented from becoming large-sized. Further, since the base member can be made of a small-size, the same engaging member can be installed to fuel tanks for different types of two-wheeled vehicles, and general-purpose properties can be enhanced. When changing a shape of the engaging member depending upon the vehicle type, it is possible to change only one of the base member and the engaging body, to apply the other, and to restrain the cost from increasing.

In the present invention, since the concave portion of the engaging member is constructed of a first concave portion of the base member and a second concave portion of the engaging body, it is possible to prevent the second concave portion from becoming large-sized as compared with, for example, an engaging member, the concave portion of which is constructed of only the second concave portion.

In the present invention, since the tank-side rear part installation area in the rear of the fuel tank has been constructed such that the tank installation stay for integrally extending from the pump installation member is installed to the body frame, the strength/stiffness of the tank-side rear part installation area can be enhanced by the pump installation member and the tank installation stay without increasing a number of parts of the tank-side rear part installation area of the fuel tank as compared with the conventional case even if the engaging member of the fuel tank front part is made into two-parts divided structure. This becomes preferable as the structure for installing the fuel tank.

Further scope of applicability of the present invention will become apparent from the detailed description given hereinafter. However, it should be understood that the detailed description and specific examples, while indicating preferred embodiments of the invention, are given by way of illustration only, since various changes and modifications within the spirit and scope of the invention will become apparent to those skilled in the art from this detailed description.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will become more fully understood from the detailed description given hereinbelow and the accompanying drawings which are given by way of illustration only, and thus are not limitative of the present invention, and wherein:

FIG. 1 is a side view showing a two-wheeled vehicle according to the present invention;

FIG. 2 is a side view showing a body frame for a two-wheeled vehicle according to the present invention;

FIG. 3 is a side view showing a principal part of the front part of the two-wheeled vehicle according to the present invention;

FIG. 4 is a view taken along the arrow 4 of FIG. 3;

FIG. 5 is a side view showing a fuel tank for the two-wheeled vehicle according to the present invention;

FIG. 6 is a perspective view showing an installation structure for a front part of the fuel tank for the two-wheeled vehicle according to the present invention;

FIG. 7 is a cross-sectional view taken on line 7-7 of FIG. 5;

FIG. 8 is an exploded perspective view showing a structure and installation procedure for a fuel tank engaging member for the two-wheeled vehicle according to the present invention;

FIG. 9 is a cross-sectional view of a principal part showing an installation structure for a rear part of a fuel tank for the two-wheeled vehicle according to the present invention;

5

FIG. 10 is a bottom view showing a structure of a fuel tank installation area for the two-wheeled vehicle according to the present invention;

FIG. 11 is a first working view showing an installation procedure for a fuel pump and the fuel tank according to the present invention;

FIG. 12 is a second working view showing an installation procedure for a fuel pump and the fuel tank according to the present invention;

FIG. 13 is a cross-sectional view showing an engine supporting structure for the two-wheeled vehicle according to the present invention;

FIG. 14 is a working view showing a procedure for installing the engine to a rear upper engine hanger of the two-wheeled vehicle according to the present invention;

FIG. 15 is a cross-sectional view showing a conventional structure of fuel pump installation area for the two-wheeled vehicle; and

FIG. 16 is a front view of a principal part showing a conventional structure for installing a fuel tank for a two-wheeled vehicle.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Hereinafter, with reference to the accompanying drawings, the description will be made of the best mode for carrying out the present invention. In this respect, the drawings will be viewed in the direction of the symbol.

FIG. 1 is a side view showing a two-wheeled vehicle according to the present invention. A motorcycle 10 is a vehicle including a head pipe 12 provided in the front part of a cradle type body frame 11 with a front fork 13 installed in such a manner as to be freely steered. At the lower end of this front fork 13, a front wheel 14 is installed. On the upper part of the front fork 13, handlebars 16 are installed. On the inside of the body frame 11, an engine 18 is installed. In the lower part of the rear part of the body frame 11, a swing arm 21 is installed in such a manner as to be freely swingable in the up-and-down direction. At the rear end of the swing arm 21, a rear wheel 22 is installed. Between the upper part of the rear part of the body frame 11 and the rear part of the swing arm 21, a pair of left and right rear shock absorber units 23, 24 (only a symbol 23 on this side is shown) are mounted. On the upper part of the body frame 11, a fuel tank 25 made of aluminum alloy is installed. In addition, an axis 26 of the head pipe 12 is provided.

The engine 18 is an engine in which each cylinder has been arranged in a direction of the vehicle width as a series four-cylinder engine, and is composed of a crankcase 31 and a cylinder portion 32 substantially vertically installed to the front part of the crankcase 31. In the engine 18, from the front part of the cylinder head 33 for constituting the cylinder portion 32, exhaust pipes 35, 36, 37, 38 (here, only exhaust pipes 35, 36 are shown) extend downwardly toward the front for each cylinder. In the rear part of the cylinder head 33, a carburetor 41 and an air cleaner 42 are installed in order; and the engine is installed to the body frame 11 by means of a front engine hanger 43, a rear upper engine hanger 44 and a rear engine hanger 46.

An axis 47 is illustrated for each cylinder of the engine 18. The axis 47 is caused to intersect an axis 26 of the head pipe 12, in other words, the axis 47 is caused to point upwardly of the head pipe 12, whereby the cylinder portion 32 has been set to a substantially upright standing state.

6

The fuel tank 25 is a part installed to a front part installation area 48 and a rear part installation area 51 provided on the body frame 11.

An upper case 56 and a lower case 57 are provided for constituting the crankcase 31 respectively. A self-starter 58 and a battery 61 are installed to the upper part of the rear part of the crankcase 31, respectively. A cover 62 is provided for an AC generator for projecting from the crankcase 31 sideways of the vehicle body. A crankshaft 63 is operatively connected to the engine with a water pump 64 installed on the side surface of the crankcase 31. A counter shaft 66 and an output shaft 67 are provided on a transmission 68 integrally provided in the rear part of the engine 18, respectively. A drive sprocket 71 is installed on the output shaft 67 with a chain 72 operatively positioned between a driven sprocket 73 integrally installed to the rear wheel 22 and a drive sprocket 71.

An upper cowl 75 is provided for covering the front part of the upper part of the motorcycle 10. A front fender 76 is provided for covering the upper part of the front wheel 14. A radiator 77 is provided for cooling the engine 18. An oil cooler 78 is installed on the lower part of the front part of the engine 18. An oil element 81 is installed on an oil cooler 78. A rear exhaust pipe 82 is connected to each exhaust pipe 35 to 38. A muffler 83 is connected to the rear exhaust pipe 82. An under cowl 84 is provided for covering the lower parts of the engine 18, the exhaust pipes 35 to 38 and the rear exhaust pipe 82. A seat 86 is arranged in the rear of the fuel tank 25.

FIG. 2 is a side view showing a body frame of a two-wheeled vehicle according to the present invention. The body frame 11 is composed of a head pipe 12, a pair of left and right main pipes 92, 92 (only reference numeral 92 on this side is shown) for obliquely extending so as to extend rearwardly and backward from the head pipe 12 and further obliquely extending backward toward the lower part. Front pipes 93, 93 (only reference numeral 93 on this side is shown) are laid over to the main pipes 92, 92 from the lower part of the head pipe 12 with a pair of left and right down tubes 94, 94 (only reference numeral 94 on this side is shown) extending substantially toward the lower part from the front pipes 93, 93. Lower pipes 96, 96 (only reference numeral 96 on this side is shown) are provided for extending so as to curve rearwardly from the lower ends of these down tubes 94, 94. Seat rails 98, 98 (only reference numeral 98 on this side is shown) extend rearwardly from the upper part of the rear part of the main pipes 92, 92. Sub-pipes 101, 101 (only reference numeral 101 on this side is shown) are provided for connecting to respective intermediate parts of the seat rails 98, 98 and the rear end portions of the main pipes 92, 92, the lower ends of which are connected to the lower pipes 96, 96.

Reinforcement pipes 105, 105 (only reference numeral 105 on this side is shown), 106, 106 (only reference numeral 106 on this side is shown) are provided between the front pipes 93, 93, the down tubes 94, 94 and the head pipe 12. A first cross pipe 107 is mounted between the down tubes 94, 94 in order to install a front engine hanger 43. A second cross pipe 108 is mounted between the main pipes 92, 92 in order to install a rear upper engine hanger 44. A third cross pipe 111 is mounted between the sub-pipes 101, 101 in order to install a rear lower engine hanger 46. Pivot plates 112, 112 (only reference numeral 112 on this side is shown) are installed to connected portions between the main pipes 92, 92 and the sub-pipes 101, 101 in order to install a swing shaft (that is, a pivot shaft) of a swing arm 21 (See FIG. 1). Shock absorber installation plates 113, 113 (only reference numeral 113 on this side is shown) are installed to connected portions

between the seat rails **98, 98** and the sub-pipes **101, 101** in order to install each upper end of the rear shock absorber units **23, 24** (See FIG. 1).

Front installation areas **48** for installing the fuel tank **25** to the body frame **11** are installed to the main pipe **92** and the front pipe **93**, and are provided on the left and right of these main pipe **92** and front pipe **93**.

Rear installation areas **51** for installing the rear part of the fuel tank **25** to the body frame **11** are installed on the respective insides of the seat rails **98, 98**.

FIG. 3 is a side view showing a principal part of the front part of a two-wheeled vehicle according to the present invention wherein in order to support the front engine hanger **43**, in the front part of the first cross pipe **107** mounted between the down tubes **94, 94** (only reference numeral **94** on this side is shown), there are provided circular-arc-shaped concave portions **107a, 107a** (only reference numeral **107a** on this side is shown). Within the circular-arc-shaped concave portions **107a, 107a**, in the front part of the exhaust pipes **35** to **38** (exhaust pipes **35, 38** are not shown), the radiator **77** is arranged through a part of the exhaust pipes **36, 37** (in this case, only the exhaust pipes **36, 37** connected to two cylinders on the inside are shown, of the front cylinders of the engine **18**) for extending so as to curve downwardly from the front part of the engine **18**. A radiator cap **116** is mounted on the radiator **77**. An upper installation stay **117** is provided for installing the upper part of the radiator **77** to the reinforcement pipe **106**. A lower installation stay **118** is provided for installing the lower part of the radiator **77** to the down tube **94**.

FIG. 4 is a view taken along an arrow **4** of FIG. 3 with the exhaust pipes **35** to **38** being illustrated in cross-sectional views. The arrow (FRONT) in the figure indicates the front part of the vehicle (and so forth).

A first cross pipe **107** is provided for constituting the body frame **11** and is a member in which circular-arc-shaped concave portions **107a, 107a** have been formed at the left and right in the front part. Within these circular-arc-shaped concave portions **107a, 107a**, exhaust pipes **36, 37** have been arranged in proximity to each other. Further, a substantially circular-arc shaped radiator **77**, the central part of which is convex toward the rear part of the vehicle, has been arranged in proximity to the exhaust pipes **36, 37**. A left hanger **43a** and a right hanger **43b** are provided which constitute a front engine hanger **43**, and are composed of two members, respectively.

As described above, the first cross pipe **107** is provided with circular-arc-shaped concave portions **107a, 107a**. One portion each of the exhaust pipes **36, 37** is arranged within the circular-arc-shaped concave portions **107a, 107a** with the exhaust pipes **36, 37** being arranged further in the rear. The radiator **77** is also arranged in the rear in closer proximity to the exhaust pipes **36, 37**. This is because in the space between a locus **121** (locus is the place when the front wheel **14** is moved by the handlebars **16** (See FIG. 1) and a side of the front wheel **14** comes extremely close to the radiator **77**) of the outer periphery of the front wheel **14** (See FIG. 3) indicated by an imaginary line in the FIG. 4, and the first cross pipe **107** a thickness **T** of the radiator **77** is made as large as possible. Thus, the capacity of the radiator **77** is increased to enhance the heat radiation effect. Also, in the present invention, the position of the lower end portion **77a** of the radiator **77** is arranged at substantially the same position as or lower than the first cross member **107**, whereby the height **A** of the radiator **77** has been made larger to increase the capacity of the radiator **77**.

Particularly, in a two-wheeled vehicle of a race specification in which the engine **18** (See FIG. 3) is continuing to be

driven at high speed, since the output and durability of the engine **18** are greatly affected by the cooling performance of the radiator **77**, it becomes an indispensable condition to have a large-sized radiator **77** having a large capacity.

Reverting to FIG. 3, with respect to an axle **123** of the front wheel **14** and assuming a straight line which passes through a central point **123a**, which is the center of the axle **123**, and intersects a down tube **94** at right angles to be **124**, the first cross pipe **107** has been provided below this straight line **124**. The positional relationship between the straight line **124** at this time and the first cross pipe **107** is in a so-called "1G state" in which only a driver rides on a motorcycle **10**.

A distance **D** between the front wheel **14** and the down tube **94** becomes extremely small on the straight line **124**. The first cross member **107** is provided below the straight line **124** as described above, whereby since the first cross member **107** can be arranged apart from the position whereat the distance **D** between the front wheel **14** and the down tube **94** becomes extremely small, a distance between the front wheel **14** and the exhaust pipe **36, 37** can be easily secured. For example, in a case where the first cross member **107** is provided above the straight line **124**, the distance **D** becomes small when the front wheel **14** strokes on the handlebars **16** side.

FIG. 5 is a side view showing a fuel tank for a two-wheeled vehicle according to the present invention. The fuel tank **25** includes a rear part of the bottom wall **25a** wherein a fuel pump **127** is installed and arranged within the fuel tank **25**. On the inside of the front part, there are provided a pair of left and right engaging members **128, 128** for engaging with a front part installation area **48** (See FIG. 2) on the body frame **11** (See FIG. 2) side. In the lower part of the rear part, there is provided a tank rear part side installation area **131** to be installed to a rear part installation area **51** (See FIG. 2) on the body frame **11** side. In addition, an oil feeding port **133** is provided.

FIG. 6 is a perspective view showing the structure for installing a front part of a fuel tank for a two-wheeled vehicle according to the present invention. The front part installation area **48** on the body frame **11** side is composed of left and right installation areas **135, 135**. The installation area **135** is composed of a U-shaped plate **136** installed to the main pipe **92** and the front pipe **93**, a supporting pin **137** is provided for extending from the U-shaped plate **136** sideways of the vehicle, and a shock absorbing rubber **138** is provided for being fitted in this supporting pin **137**.

The engaging member **128** on the fuel tank **25** (See FIG. 5) side includes two members, a base member **141** made of aluminum alloy welded to a side wall **25b** of the fuel tank **25**, and an engaging body **143** installed to the base member **141** with bolts **142 . . .** (. . . represents a plurality, and so forth). A first concave portion **145** is provided at the base member **141**. A second concave portion **146** is provided at the engaging body **143**. The first concave portion **145** and second concave portion **146** are portions for constituting an engaging concave portion **147**.

FIG. 7 is a cross-sectional view taken on line 7-7 of FIG. 5, and illustrating that on the inside of the fuel tank **25**, there is formed a concave inner wall **25c** composed of left and right side walls **25b, 25b** and a bottom wall **25a** for connecting upper ends of these side walls **25b, 25b**. A base member **141** of the engaging member **128** is welded to the side wall **25b**. The engaging body **143** is installed to this base member **141** with bolts **142 . . .**. The engaging member **128** is caused to engage with an installation area **135** of the front part installation area **48** on the body frame **11** (See FIG. 2) side, that is,

the engaging member **128** is supported by the supporting pin **137** and the U-shaped plate **136** via the shock absorbing rubber **138**.

FIG. **8** is an exploded perspective view showing the structure and assembly procedure of a fuel tank engaging member for a two-wheeled vehicle according to the present invention.

The base member **141** of the engaging member **128** is composed of a flat portion **151**, the edge of which is welded to the side wall **25b** of the fuel tank **25** (See FIG. **7**) and a U-shaped stand-up wall **152** for standing up from the flat portion **151**. First female threads **153**, **153** are provided on each end portion of the U-shaped stand-up wall **152** with pillar-shaped portions **154**, **154** for standing up from the flat portion **151**, integrally molded to the U-shaped stand-up wall **152**. Second female threads **156**, **156** are provided on the pillar-shaped portions **154**, **154**. The base member **141** is a member wherein on the inside of the U-shaped stand-up wall **152**, there has been formed the first concave portion **145**.

The engaging body **143** is composed of an U-shaped flat portion **161** with a U-shaped stand-up wall **162** for standing up from this U-shaped flat portion **161**. First bolt insertion holes **163**, **163** are provided at each end portion of the U-shaped stand-up wall **162** with pillar-shaped portions **164**, **164** for standing up from the U-shaped flat portion **161**, integrally molded with the U-shaped stand-up wall **162**. Second bolt insertion holes **166**, **166** are provided on these pillar-shaped portions **164**, **164**. The engaging body **143** is a member wherein on the inside of the U-shaped stand-up wall **162**, there is formed the second concave portion **146**.

Hereinafter, the description will be made of the procedure of installing the engaging member **128** to the fuel tank **25** in order.

Positioning and tack fixing are performed on the side wall **25b** of the fuel tank **25** through the use of a welding jig in such a manner that an aperture **145a** of the first concave portion **145** of the base member **141** faces ahead, and four sides of the flat portion **151** of the base member **141** are continuously welded to the side wall **25b** of the fuel tank. A side **151a** of the flat portion **151** on the rear side is made shorter than a side **151b** on the front side, whereby the welding operation can be further facilitated.

An aperture **146a** of the second concave portion **146** of the engaging body **143** is caused to face ahead, and bolts **142** . . . are caused to pass through the first bolt insertion holes **163**, **163** and the second bolt insertion holes **166**, **166** of the engaging body **143**, respectively, to be screwed into the first female threads **153**, **153** and the second female threads **156**, **156** of the base member **141**. Installation of the engaging member **128** to the fuel tank **25** is completed.

Conventionally, the engaging member has been integrally formed, but in the present invention, the engaging member **128** is composed of two members the base member **141** and the engaging body **143**. Thus, when the engaging member **128** is welded, since the dimension, particularly the height H (See FIG. **7**) of the base member **141** is small, a welding operation of the base member **141** within the concave inner wall **25c** can be easily performed, and a welding jig or a welder can be easily inserted into the concave inner wall **25c**.

FIG. **9** is a cross-sectional view of principal part showing a structure for installing a rear part of a fuel tank for a two-wheeled vehicle according to the present invention, and illustrating that at the end portion of the fuel pump **127**, a supporting plate **171** for supporting the fuel pump **127** is installed with bolts **172** In the rear part of the bottom wall **25a** of the fuel tank **25**, a pump installation member **173** is made of an aluminum alloy for installing the fuel pump **127** and is welded thereto. To the pump installation member **173**, the

supporting plate **171** is installed with bolts **174** In the rear of the pump installation member **173**, the tank installation stay **176** for installing the fuel tank **25** to the body frame **11** (to be precise, a rear part installation portion **51** provided at the seat rails **98**, **98** (one seat rail is not shown)) is installed with bolts **177**

The supporting plate **171** is a part obtained by integrally molding pillar portions **171a** . . . to be installed to a pump-side plate **181** provided on the fuel pump **127** side, and is installed to the pump installation member **173** via an O-ring **182**.

A tank-side rear part installation area **183** is provided in the rear part of the fuel tank **25** for installation to the body frame **11** and is composed of the above-described tank installation stay **176** and a pump installation member **173** for supporting this tank installation stay **176**.

The rear part installation area **51** on the body frame **11** side is composed of a tank rear part supporting plate **185**, the cross section of which is substantially a crank-shape, mounted between the left and right seat rails **98**, **98**. A nut **186** is welded to this tank rear part supporting plate **185** with a cushion rubber **187** fitted in a frame-side installation hole (not shown) provided on the tank installation stay **176**. A washer **191** is inserted between this cushion rubber **187** and the tank rear part supporting plate **185**, respectively. A flanged collar **192** is provided through which the cushion rubber **187** has been inserted from above the cushion rubber **187**. A fitting bolt **193** is provided for penetrating the flanged collar **192** with the washer **191** and the tank rear part supporting plate **185** is screwed into the nut **186**. In this respect, for any other parts other than the tank rear part supporting plate **185** of the rear part installation area **51**, a pair is provided to the left and right respectively.

FIG. **10** is a bottom view showing structure of a fuel tank rear part installation area for a two-wheeled vehicle according to the present invention. On a frame-shaped pump installation member **173**, there are formed stay installation areas **196** . . . for projecting outward. The stay installation areas **196** . . . are formed with female threads **197**, respectively. In a substantially U-shaped tank installation stay **176**, bored bolt insertion holes **198** . . . are provided together with frame-side installation holes **201**, **201**. Each bolt insertion hole **198** of the tank installation stay **176** is matched with each female thread **197** of the pump installation member **173** and the bolts **177** (See FIG. **9**) are passed through, respectively, whereby the tank installation stay **176** is installed to the pump installation member **173**.

In the tank installation stay **176**, forward projecting portions **203**, **203** are provided at left and right end portions thereof, and at the tip portions of these forward projecting portions **203**, **203**, bolt insertion holes **198** are provided, respectively. Thus, the bolt insertion holes **198** are caused not to be in line with bolt insertion holes **198** at three other places, and the tank installation stay **176** is firmly combined with the pump installation member **173** to restrain the tank installation stay **176** from deflecting.

The frame-side installation holes **201**, **201** are circular holes bored in rearwardly projecting portions **204**, **204** respectively for projecting rearwardly from the tank installation stay **176**.

In this case, a plate installation area **211** is provided for installing the supporting plate **171** (See FIG. **9**) on the fuel pump **127** (See FIG. **9**) side to the pump installation member **173**. Female threads **212** . . . are formed on the plate installation area **211**. An O-ring groove **213** is provided for mounting the O-ring **182** (See FIG. **9**).

Next, an installation procedure for the above-described fuel pump and fuel tank will be explained.

11

FIGS. 11(a) and 11(b) are first working views showing the installation procedure for the fuel pump and the fuel tank according to the present invention.

In FIG. 11(a), the fuel pump 127 mounted with the supporting plate 171 (portion indicated by a thick line) is inserted into the fuel tank 25 through an aperture 25d provided on the bottom wall 25a of the fuel tank 25 and an aperture 173a of the pump installation member 173 as shown by the arrow. Thus, the supporting plate 171 is installed on the pump installation member 173 with a bolt (not shown).

In FIG. 11(b), the tank installation stay 176 is installed on the pump installation member 173 with bolts 177

FIGS. 12(a) and 12(b) are second working views showing the installation procedure for the fuel pump and the fuel tank according to the present invention.

In FIG. 12(a), an engaging member 128 of the fuel tank 25 is caused to engage with the front part installation part 48 of the body frame 11.

In FIG. 12(b), the cushion rubber 187 is fitted into the frame-side installation hole 201 of the tank installation stay 176. The washer 191 engages with the underside of the cushion rubber 187 with the flanged collar 192 being inserted into the cushion rubber 187. The fitting bolt 193 is caused to penetrate the flanged collar 192, the washer 191 and the tank rear part supporting plate 185 and is screwed into a nut 186. Thereby, the installation of the fuel tank 25 to the body frame 11 is completed.

As explained in FIGS. 1, 5 and 9, according to the present invention, there is firstly provided a motorcycle 10 as a two-wheeled vehicle in which the fuel tank 25 is installed to the body frame 11. Within this fuel tank 25, there is provided the fuel pump 127, wherein the fuel tank 25 is installed to the body frame 11 via the pump installation member 173. To the pump installation member 173, there is installed the tank installation stay 176 for fixing the fuel tank 25 to the body frame 11.

Since the fuel pump 127 is installed to the fuel tank 25 via the pump installation member 173 and to the pump installation member 173, the tank installation stay 176 has been installed, as compared with, for example, a case where the fuel pump is directly installed to the bottom wall of the fuel tank, the stiffness of the fuel pump installation area can be enhanced by the pump installation member 173, and by installing the tank installation stay 176 to such a fuel pump installation area with enhanced stiffness. Thus, the stiffness of the fuel pump installation area can be further enhanced and the stiffness of the installation area of the tank installation stay 176 to the fuel tank 25 side can be also enhanced as compared with a case where the tank installation stay 176 is directly installed to the bottom wall of the fuel tank. Therefore, the fuel pump 127 can be further reliably supported, the tank installation stay 176 becomes firmer, and sound vibration performance of the vehicle can be improved.

As explained in FIGS. 5 to 9, according to the present invention, there is provided a structure for installing a body frame for a motorcycle 10 in which on the side walls 25b, 25b as left and right inner walls caused by depressing the center of the underside of the fuel tank 25 upwardly over the front and the rear, concave-shaped engaging members 128 are installed, respectively. The fuel tank 25 is installed to the body frame 11 by engaging installation areas 135, 135 as left and right convex portions provided on the body frame 11 with these engaging members 128, respectively. The engaging member 128 is constructed of two members, a base member 141 welded to the fuel tank 25 and an engaging body 143 for fastening to this base member 141 by means of bolts 142 . . . as fastening means.

12

Since the engaging member 128 is constructed of two members, a base member 141 welded to the fuel tank 25 and an engaging body 143 for fastening to this base member 141 with bolts 142 . . . , it is possible to reduce a size, particularly the height H of the base member 141 of the present invention smaller than the conventional engaging member. In the case of installing the base member 141 to the fuel tank 25 by welding, it is easy to insert a welding jig or a welder for positioning or fixing the base member 141 on side walls 25b, 25b as left and right inner walls inside the fuel tank 25 without interfering with the left and right side walls 25b, 25b.

Accordingly, the workability of the base member 141 during welding can be enhanced, and the capacity of the fuel tank 25 can be secured, or the fuel tank 25 can be prevented from becoming large-sized. Further, since the base member 141 can be made to be small-sized, the same engaging member 128 can be installed to fuel tanks for different types of two-wheeled vehicles, and the general-purpose properties can be enhanced. When changing a shape of the engaging member 128 depending upon the vehicle type, it is possible to change only one of the base member 141 and the engaging body 143, to apply the other, and to restrain the cost from increasing.

The present invention is secondly characterized in that an axis 47 of the cylinder of the engine 18 arranged below the fuel tank 25 is caused to extend upwardly with air intake system parts such as a carburetor 41 and an air cleaner 42 for extending toward the rear being installed in the rear of the cylinder. The pump installation member 173 and the tank installation stay 176 have been arranged substantially above the air intake system parts.

The engine 18 in which the axis 47 of the cylinder has been caused to extend upwardly is shaped such that the front part of the bottom wall 25a of the fuel tank 25 is depressed upwardly and the rear part of the bottom wall 25a of the fuel tank 25 bulges downwardly. In an engine in which the fuel pump 127 has been arranged within the fuel tank 25, the fuel pump 127 is to be installed in the rear part of the bottom wall 25a at the lowest position of portions of the fuel tank 25. Further, if the air intake system parts extend toward the rear from the engine 18, the rear part of the bottom wall 25a of the fuel tank 25 which is located above the air intake system parts will become substantially flat. Thus, the pump installation member 173 will become substantially flush with the tank installation stay 176 so that it becomes possible to be combined by making them to come in close proximity to each other. If the pump installation member 173 comes in close proximity to the tank installation stay 176, it will be possible to shorten the tank installation stay 176 and to firmly install the fuel tank 25 to the body frame 11 side. Also, the weight of the tank installation stay 176 will be able to be saved.

The present invention includes an engaging concave portion 147 that is a concave portion to be provided on the engaging member 128 that is constructed of a first concave portion 145 provided on the base member 141 and a second concave portion 146 provided on the engaging body 143.

Since the engaging concave portion 147 of the engaging member 128 is constructed of a first concave portion 145 of the base member 141 and a second concave portion 146 of the engaging body 143, it is possible to prevent the second concave portion 146 from becoming large-sized, that is, the engaging body 143 from becoming large-sized in the present invention as compared with, for example, an engaging member, the engaging concave portion of which is constructed of only the second concave portion.

In the present invention the tank-side rear part installation area 183 is provided in the rear of the fuel tank 25 that has been constructed such that the tank installation stay 176 for

integrally extending from the pump installation member 173 for installing, to the fuel tank 25, the fuel pump 127 arranged within the fuel tank 25 is installed to the body frame 11.

Since the tank-side rear part installation area 183 in the rear of the fuel tank 25 has been constructed such that the tank installation stay 176 for integrally extending from the pump installation member 173 is installed to the body frame 11, the strength/stiffness of the tank-side rear part installation area 183 can be enhanced by the pump installation member 173 and the tank installation stay 176 without increasing a number of parts of the tank-side rear part installation area 183 of the fuel tank 25 as compared with the conventional case even if the engaging member 128 in the front part of the fuel tank 25 is made into a two-part divided structure. This becomes preferable as the structure for installing the fuel tank.

FIG. 13 is a cross-sectional view showing engine supporting structure for a two-wheeled vehicle according to the present invention illustrating the structure for supporting the engine 18 with a rear upper engine hanger 44.

The rear upper engine hanger 44 is composed of a left hanger 221 and a right hanger 222 which have been caused to project forward from the left and right of the second cross pipe 108, respectively.

The left hanger 221 is composed of a left extending member 224 having a U-shape in cross section obtained by press-forming a plate, and a cylindrical member 225 installed to the tip of this extending member 224.

The cylindrical member 225 is obtained by pressing a first flanged collar 227 made of metal and a second flanged collar 228 made of metal in from the end portion respectively. The first flanged collar 227 and the second flanged collar 228 are members in which a bolt insertion hole 227a, 228a has been bored, respectively.

The right hanger 222 is composed of a base member 231 having a L-shape in cross section obtained by press-forming a plate and a right extending member 234 coupled by a nut 232 and a bolt 233 installed to this base member 231.

The right extending member 234 is a member at the tip portion of which a through-hole 234a has been bored and is obtained by pressing a pipe bushing 236 into this through-hole 234a.

The pipe bushing 236 is composed of an outer cylinder 237, an inner cylinder 238 arranged on the inside of this outer cylinder 237 and shock absorbing rubber 241 adhered by vulcanization between these outer cylinder 237 and inner cylinder 238.

A body-side left installation area 245 and a body-side right installation area 246 are provided and project upwardly toward the rear from the rear part of the crankcase 31 of the engine 18, respectively. The body-side left installation area 245 and body-side right installation area 246 include bored bolt insertion holes 245a, 246a, respectively. Within the bolt insertion hole 227a of the first flanged collar 227, the bolt insertion hole 228a of the second flanged collar 228, the bolt insertion holes 245a, 246a and the inner cylinder 238 of the pipe bushing 236, a hollow supporting bolt 248 is passed through. Into the tip of the supporting bolt 248, a supporting nut 251 is screwed. Thus, the upper part of the rear part of the engine 18 is supported by the rear upper engine hanger 44. In this respect, the washer 253 is interposed between the body-side right installation area 246 and the inner cylinder 238 of the pipe bushing 236.

The engine 18 is, as shown in FIG. 1, supported by the front engine hanger 43, the rear upper engine hanger 44 and the rear lower engine hanger 46.

Since the front engine hanger 43 and the rear lower engine hanger 46 support the engine 18 via the collar made of metal

as in the case of the above-described left hanger 221 the combination with the engine 18 becomes firmer. As described above, of the three engine hangers 43, 44, 46, the rear upper engine hanger 44 and particularly the right hanger 222 is elastically supported via the pipe bushing 236. This is because the stiffness of the body frame 11 to which the engine 18 has been added is adjusted by changing the setting of the hardness of rubber. In other words, as compared with a case where all places of the engine hangers are combined in a so-called rigid way via collars made of metal, the body frame 11 has been slightly provided with flexibility in the present invention.

Another reason why the engine 18 has been elastically supported by the right hanger 222 is that it is easier to maintain than other engine hangers 43, 46 and the left hanger 221.

If the supporting nut 251 is loosened to be removed from the supporting bolt 248, and the bolt 233 of the right hanger 222 is loosened to remove the right extending member 234 from the base member 231, the pipe bushing 236 will be able to be easily attached or detached to or from the right extending member 234.

Also, as regards the supporting bolt 248, the weight thereof has been saved by making it hollow.

Next, the description will be made of the procedure for installing the engine 18 to the above-described rear upper engine hanger 44.

FIGS. 14(a) to 14(d) are working views illustrating the procedure for installing the engine to a rear upper engine hanger for a two-wheeled vehicle according to the present invention.

In FIG. 14(a), the pipe bushing 236 is pressed into a through-hole 234a in the right extending member 234, and the washer 253 is touched to the side of the pipe bushing 236.

In FIG. 14(b), the first flanged collar 227 and the second flanged collar 228 are pressed into the inner surface of the cylindrical member 225 of the left hanger 221.

In FIG. 14(c), between the left hanger 221 and the right hanger 222, there are arranged the body-side left installation area 245 and the body-side right installation area 246 of the engine 18. The supporting bolt 248 is caused to pass through the bolt insertion hole 227a in the first flanged collar 227, the bolt insertion hole 228a in the second flanged collar 228, the bolt insertion hole 245a in the body-side left installation area 245, the bolt insertion hole 246a in the body-side right installation area 246 and the inner cylinder 238 of the pipe bushing 236.

In FIG. 14(d), the supporting nut 251 is screwed into the tip of the supporting bolt 248. Thereby, installation of the engine 18 to the rear upper engine hanger 44 is completed.

In the embodiment of the present invention, the tank installation stay has been installed to the pump installation member with bolts, but the present invention is not limited thereto. The tank installation stay may be installed to the pump installation member by welding and the pump installation member and the tank installation stay may be made into an integrally-molded article made of an aluminum alloy.

The body frame structure according to the present invention is suitable for a two-wheeled vehicle in which the fuel pump has been built in the fuel tank and the fuel pump has been arranged in the rear within the fuel tank.

The invention being thus described, it will be obvious that the same may be varied in many ways. Such variations are not to be regarded as a departure from the spirit and scope of the invention, and all such modifications as would be obvious to one skilled in the art are intended to be included within the scope of the following claims.

15

What is claimed is:

1. A structure of a fuel pump installation area for a fuel tank is installed to a body frame and a fuel pump is provided within this fuel tank, comprising:

a pump installation member for installing the fuel pump in said fuel tank; and

a tank installation stay for fixing said fuel tank to the body frame, said tank installation stay being mounted on the pump installation member,

wherein the tank installation stay is substantially U-shaped, and includes a pair of forward projecting portions that extend along right and left sides of the pump installation member.

2. The structure of a fuel pump installation area for a vehicle according to claim 1, wherein:

an axis of a cylinder of an engine arranged below said fuel tank is caused to extend upwardly and an air intake system part extends toward the rear of the vehicle and is installed to the rear of said cylinder, and

said pump installation member and said tank installation stay are arranged substantially above said air intake system part.

3. The structure of a fuel pump installation area for a vehicle according to claim 1, wherein said pump installation member is secured to said fuel tank and said plate member includes an aperture disposed therein for permitting said fuel pump to be positioned within said fuel tank.

4. The structure of a fuel pump installation area for a vehicle according to claim 1, wherein said tank installation stay is secured to said pump installation member and to the body frame for enhancing stiffness of the fuel pump disposed within the fuel tank.

5. The structure of a fuel pump installation area for a vehicle according to claim 1, wherein the tank installation stay includes a rear side projecting portion with a first bolt insertion hole disposed therein, and

wherein the structure further comprises:

a tank rear part supporting plate having a projecting portion with a second bolt insertion hole disposed therein, and a securing member being received within the first and second bolt insertion holes for mounting the tank rear part supporting plate and the fuel tank to the body frame.

6. The structure of a fuel pump installation area for a vehicle according to claim 5, wherein a cushion member is disposed between the projecting portion and the tank rear part supporting plate for absorbing shock.

7. The structure of a fuel pump installation area for a vehicle according to claim 1, wherein said tank installation stay includes a tank rear part supporting plate for operatively positioning the fuel pump relative to an interior of the fuel tank.

8. The structure of a fuel pump installation area for a vehicle according to claim 7, wherein said tank rear part supporting plate includes attaching portions for corresponding to attaching portions on a pump-side plate for ensuring the correct positioning of the fuel pump relative to the interior of the fuel tank.

9. The structure of a fuel pump installation area for a vehicle according to claim 7, and further including a seal mounted between the tank installation stay and the pump installation member for sealing fuel disposed within the fuel tank.

10. The structure of a fuel pump installation area for a vehicle according to claim 7, wherein the attaching portions on the tank rear part supporting plate and the attaching portions on the pump-side plate permit bolts to be mounted therethrough for mounting the fuel pump relative to the interior of the fuel tank.

16

11. The structure of a fuel pump installation area for a vehicle according to claim 1, the structure further comprising:

a tank rear part supporting plate attached to said body frame and said tank installation stay for mounting the fuel tank to the body frame,

wherein the tank rear part supporting plate is substantially crank-shaped.

12. The structure of a fuel pump installation area for a vehicle according to claim 1, further comprising:

left and right inner walls of said fuel tank being formed by depressing the center of an underside of the fuel tank upwardly over the front and rear;

concave-shaped engaging members are installed on the left and right inner walls for mounting said fuel tank relative to the body frame by engaging left and right convex portions provided on the body frame with the engaging members, respectively;

a base member welded to said fuel tank forming one of said engaging members; and

an engaging body for fastening to the base member by means of fastening means forming the other of said engaging members.

13. The structure of a fuel pump installation area for a vehicle according to claim 12, wherein a concave portion to be provided on each of said engaging members is constructed of a first concave portion provided on said base member and a second concave portion provided on said engaging body.

14. The structure of a fuel pump installation area for a vehicle according to claim 13, wherein a tank-side rear part installation area provided in the rear of said fuel tank is formed such that the tank installation stay is installed to said body frame.

15. The structure of a fuel pump installation area for a vehicle according to claim 12, wherein a tank-side rear part installation area provided in the rear of said fuel tank is formed such that the tank installation stay is installed to said body frame.

16. The structure of a fuel pump installation area for a vehicle according to claim 12, wherein the base member includes a U-shaped wall mounted thereon and projecting therefrom.

17. The structure of a fuel pump installation area for a vehicle according to claim 16, wherein the engaging body includes a U-shaped wall mounted thereon for mating with the U-shaped wall formed on the base member.

18. The structure of a fuel pump installation area for a vehicle according to claim 17, wherein apertures are formed in the engaging body and the base member for enabling the fastening means to secure the two relative to each other.

19. The structure of a fuel pump installation area for a vehicle according to claim 18, wherein the fastening means are bolts received within threaded apertures formed in the base member.

20. A structure of a fuel pump installation area for a fuel tank is installed to a body frame and a fuel pump is provided within this fuel tank, comprising:

a pump installation member for installing the fuel pump in said fuel tank;

a tank installation stay attached to left, right, and rear parts of the pump installation member; and

a tank rear part supporting plate attached to said body frame and said tank installation stay for mounting the fuel tank to the body frame,

wherein the tank rear part supporting plate is substantially crank-shaped.