



US007437998B2

(12) **United States Patent**
Burger et al.

(10) **Patent No.:** **US 7,437,998 B2**
(45) **Date of Patent:** **Oct. 21, 2008**

- (54) **WATER-RIDE FACILITY**
- (75) Inventors: **Guenter Burger**, Waldkirch (DE);
Frank Sornik, Waldkirch (DE);
Thorsten Koebele, Riegel (DE); **Jens Gessner**, Voerstetten (DE)
- (73) Assignee: **Mack Rides GmbH & Co. KG**,
Waldkirch (DE)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 346 days.

3,113,528 A *	12/1963	Morgan et al.	104/73
3,404,635 A *	10/1968	Bacon et al.	104/70
3,930,450 A *	1/1976	Symons	104/73
4,063,517 A *	12/1977	Nardoizzi, Jr.	104/35
4,149,469 A *	4/1979	Bigler	104/73
4,337,704 A *	7/1982	Becker et al.	104/70
4,392,434 A *	7/1983	Durwald et al.	104/70
5,006,072 A *	4/1991	Letovsky et al.	434/61
5,011,134 A *	4/1991	Langford	472/117
5,016,540 A *	5/1991	Barber	104/53

- (21) Appl. No.: **11/305,198**
- (22) Filed: **Dec. 19, 2005**
- (65) **Prior Publication Data**
US 2006/0130698 A1 Jun. 22, 2006
- (30) **Foreign Application Priority Data**
Dec. 20, 2004 (DE) 10 2004 062 315

- (51) **Int. Cl.**
A63G 7/00 (2006.01)
A63G 1/00 (2006.01)
- (52) **U.S. Cl.** **104/73; 104/23.1**
- (58) **Field of Classification Search** 104/23,
104/23.1, 23.2, 73, 72, 70, 59, 139, 154,
104/161, 60, 243; 472/117, 129, 135, 128,
472/127, 134
See application file for complete search history.

- (56) **References Cited**
U.S. PATENT DOCUMENTS
1,357,995 A * 11/1920 Kitterman 472/13
1,440,661 A * 1/1923 Dickinson 104/66
1,563,855 A * 12/1925 Held 280/18
1,607,771 A * 11/1926 Miller 104/63
2,064,035 A * 12/1936 Rynearson 104/71
2,235,563 A * 3/1941 Ridgway 104/73
3,003,430 A * 10/1961 Hamel 104/72

(Continued)

FOREIGN PATENT DOCUMENTS



DE 298 23 592 U1 11/1999

Primary Examiner—J. Allen Shriver
Assistant Examiner—Jason C Smith
(74) *Attorney, Agent, or Firm*—Nath Law Group; Jerald L. Meyer; Jon A. Kidney

(57) **ABSTRACT**

A water ride containing at least one watercraft is described, having at least a floating body and a chassis which is connected thereto in an articulated manner and which serves as a guide unit, and a guide for the chassis which runs in the water, and a drive for the watercraft, wherein the floating body is connected to the chassis via a connection unit which comprises flexible elements and which allows relative movements of the floating body with respect to the chassis, wherein arranged on the floating body and on the chassis are associated coupling elements which serve for rigidly connecting the floating body and the chassis in at least one relative position, and in that the coupling elements are designed in such a way that the floating body is fixed on the chassis after being lowered.

16 Claims, 3 Drawing Sheets



US 7,437,998 B2

Page 2

U.S. PATENT DOCUMENTS

5,215,015	A *	6/1993	Iida et al.	104/23.1	6,237,499	B1 *	5/2001	McKoy	104/59
5,473,990	A *	12/1995	Anderson et al.	104/85	6,354,223	B2 *	3/2002	McKoy	104/72
5,542,356	A *	8/1996	Richert et al.	104/289	6,533,670	B1 *	3/2003	Drobnis	472/60
5,564,984	A *	10/1996	Mirabella et al.	472/43	6,553,915	B2 *	4/2003	Tseng	104/23.1
5,566,620	A *	10/1996	Siewert	104/124	6,592,374	B1 *	7/2003	Kim	434/58
5,613,443	A *	3/1997	Ariga et al.	104/70	6,629,501	B2 *	10/2003	McKoy	104/72
5,623,878	A *	4/1997	Baxter et al.	104/85	6,860,209	B2 *	3/2005	McKoy	104/72
5,669,308	A *	9/1997	Gerhardt	104/155	6,964,614	B1 *	11/2005	Tsai	472/58
5,732,635	A *	3/1998	McKoy	104/73	6,971,317	B2 *	12/2005	McKoy	104/72
5,775,226	A *	7/1998	Futami et al.	104/71	7,094,157	B2 *	8/2006	Fromyer et al.	472/59
5,860,364	A *	1/1999	McKoy	104/59	2006/0130698	A1 *	6/2006	Burger et al.	104/73
6,095,926	A *	8/2000	Hettema et al.	472/59	2006/0219124	A1 *	10/2006	Jordan	104/23.1
6,170,403	B1 *	1/2001	Behringer	104/59	2007/0089635	A1 *	4/2007	Blanco Montejo	104/139
					2007/0207869	A1 *	9/2007	Hunter	472/117

* cited by examiner

FIG 1




FIG 2




FIG 3




FIG 4




FIG 5





FIG 6



1

WATER-RIDE FACILITY

BACKGROUND

The invention relates to a water-ride facility.

Rides of this kind, which are very popular in leisure parks, provide water lanes, including ones of a type resembling roller coasters, with a pre-established path for a watercraft, e.g., a boat or similar floating body.

In order to give the passenger as a realistic as possible a sense of boat travel the watercraft should float freely in the areas containing water.

In order to achieve this end, the watercraft are usually guided in channels which are made, at least in part, of concrete or plastic and which are powered by drives that are most often provided under the surface of the water. This drive may be a wire cable guided in different directions over guide rollers, such that the floating body of the watercraft, which is attached to this wire cable, is pulled through the water. Furthermore, the vessel may be driven by local current pumps or by means of the channel gradient.

Also known are white-water lanes, which are designed like roller coasters. Here the watercraft pass through a schuss section and reach an area of water located at a lower elevation. Since the vessel is exposed to high forces and high load changes, safety is of special importance in the schuss section. Consequently the floating body of the watercraft is firmly attached to an undercarriage that is guided by rails, at least in the area of the schuss section.

In order to realize an operation that is as naturalistic as possible, the undercarriage of the watercraft can leave the guide system after the schuss section has been traversed, with the result that the watercraft floats more or less freely inside of the channel.

To be sure, controlling the vessel inside this area, particularly given a varying load on the boat, is problematic, or at least extraordinarily costly. It is also impossible to prevent the watercraft from colliding with the channel walls during operation, and this fact disrupts the passenger's sense that the vessel is floating freely.

Threading the undercarriage into the guide mechanism after leaving behind the area in which the watercraft floats freely is particularly difficult. No less problematic is unthreading the undercarriage after passing through a schuss section, since for reasons of safety this can only occur if the floating body has stabilized after entering the water. For example, forces that arise after the craft enters the water can be used to only a limited degree in influencing the travel effect.

The continuous guidance of an undercarriage firmly attached to the floating body is generally preferred across the entire body of water, and for the reasons indicated above, though the price paid for this is that the floating motion of the vessel body is comparatively unrealistic.

It is true that DE 298 23 591 U1 describes a watercraft in which a floating body is connected in a flexible manner to an undercarriage acting as a guide unit. However, this flexible connection does not make it possible for the floating body to float naturalistically.

The present invention is based on the problem of creating a water-ride in which the watercraft is safely conducted in all areas, including schuss sections where there are large differences in elevation, and the floating body nonetheless executes largely naturalistic movements in the remaining areas of water, even given a varying load and a varying water level, and the unnaturalistic guidance of the vessel through the water channel is eliminated.

2

SUMMARY

Therefore, the above problem is solved in that the floating body is connected to the undercarriage, which serves as a guide unit, by a connecting unit exhibiting flexible or articulated elements and permitting the floating body to execute limited transverse or lifting motions relative to the undercarriage.

In this solution the floating body can execute rocking and rolling movements typical of travel by boat, and it can adapt to different water levels, while being safely conducted over the entire course of the trip.

If the watercraft is to pass through a schuss section, the floating body, in accordance with a basic idea of the invention, is firmly connected to the carriage for a given period of time.

In one embodiment, a water ride containing at least one watercraft, is provided, comprising: a floating body and a chassis which is connected thereto in an articulated manner and which serves as a guide unit; a guide for the chassis which runs in the water; and a drive for the watercraft, wherein the floating body is connected to the chassis via a connection unit which comprises flexible elements and which allows relative movements of the floating body with respect to the chassis, wherein arranged on the floating body and on the chassis are associated coupling elements which serve for rigidly connecting the floating body and the chassis in at least one relative position, and in that the coupling elements are designed in such a way that the floating body is fixed on the chassis after being lowered. Consequently, coupling elements that are assigned to one another and that lock together are provided on the floating body and on the undercarriage; these coupling elements serve to create the firm connection between the floating body and the undercarriage in at least one relative position. In this way the watercraft is safely guided during schuss sections that resemble a roller-coaster, but has the realistic characteristics of a freely floating boat when the water section is reached.

Since the watercraft can be designed with an undercarriage typical of roller-coasters, it is able to pass through typical roller-coaster sections, such as schusses, loops, Immelmann curves, horseshoe curves, lifts, helical curves, and the like, despite having the typical characteristics of a freely floating boat. The important factor here is an absolutely secure lock between the coupling elements, e.g., by means of redundant locking and/or dead-center locking. Also suitable are coupling elements designed as king pins and pivot bearings, such as those used in trucks to connect a semi-trailer truck and a semi-trailer.

Particularly useful are coupling elements which utilize the force of gravity and are so designed that, given an appropriate track layout, the floating body, upon dropping onto the undercarriage, will automatically connect with the undercarriage and preferably will lock with it. The locking mechanism here will permit controlled unlocking.

A large range of possibilities presents itself for designing the connecting unit that is employed to connect the floating body to the undercarriage.

In accordance with another embodiment, the flexible connecting unit may consist joint rods, telescope bars, linear guides, or also a rotating assembly, arranged to form transverse and longitudinal guides.

A flexible connection may also be considered, according to which the flexible elements of the connecting unit can be cords, chains, belts, or air pillows.

To actuate these connecting elements, hydraulic or pneumatic cylinders are suitable, as are cable feeds in the case of

cables or the like, e.g., in the form of motor-driven cable drums, which preferably will be controllable.

Likewise, an entire spectrum of possibilities is available for embodying the floating body. Suitable for this are boats with a single or multiple fuselage, e.g., catamarans or rafts. The boats can take the form of sailboats, motorboats, or rowboats.

Known drives are suitable for the water-ride facility according to the invention, e.g., cable drives or conveyor chain drives that are connected to the vehicle; friction gear drives or gearwheel drives provided on the guidance system; and fluid drives, particularly fluid pump drives, where controllable outlet nozzles preferably will be provided in the water, i.e., below the surface of the water, close to the guidance system. Finally, it is possible to use induction drives, particularly linear induction motor drives.

When the layout includes schuss sectors, the watercraft can be driven by gravity.

Many maneuvers and effects can be realized when these technical possibilities are made use of.

Depending on the requirements, the guidance system may consist of a rail, as in monorail tracks, or of rail forms that are typical of roller-coasters, where running and support wheels—provided on the undercarriage and resting in rolling fashion on the tracks, even during the execution of complicated curves and loops—provide for an always secure connection.

In the water-ride facility according to the invention, controllable braking devices which can be positioned either on the undercarriage or on the guidance system will provide for the necessary reduction in speed and for bringing the craft to a defined stop.

The subject matter of the invention is next described in detail on the basis of a preferred exemplary embodiment, which is schematically depicted in the drawings. Shown in the drawings are:

BRIEF DESCRIPTION OF THE FIGURES

FIG. 1

Front view of the watercraft according to the invention, on a guide rail typical of roller coasters, showing the floating body while it is floating

FIG. 2

Reduced-scale lateral view of the watercraft of FIG. 1, inside a channel

FIG. 3

Front view of the watercraft of FIG. 1, outside of the water

FIG. 4

Reduced-scale lateral view of the vehicle of FIG. 3

FIG. 5

Top view of the watercraft

FIG. 6

Perspective view of a section through the water-ride facility according to the invention.

DETAILED DESCRIPTION

The watercraft according to the invention consists of a floating body **10** designed in the form of a boat. The floating body **10** is connected to the undercarriage **30** by means of an articulated connecting unit **20**. With its running and support wheels, which have a pivoted mounting in the chassis **31** and are only suggested in the drawing, the undercarriage **30** rests on parallel tubular rails **40**, which are connected to the base pedestal **50** of the water-ride facility by means of rail supports **41**.

In the depicted exemplary embodiment the connecting unit **20** consists of joint rods **21**, which are designed and positioned in the manner of transverse and longitudinal guides. The ball-shaped heads **22** of these joint rods **21** are pivot-mounted on all sides in corresponding bearings **11** and **33**, which belong to the floating body **10** or the undercarriage **30**.

Provided on the lower side of the floating body **10** and on the upper side of the undercarriage **30** are matching coupling elements **14** and **34** which connect with each other and lock together. The joints rods **21** and the bearings **11** and **33** for the ball-shaped heads are so dimensioned and positioned that the coupling elements **14** and **34** engage with each other when the floating body **10** drops. This is depicted in FIGS. 3 and 4. In this position the floating body **10** can be firmly connected to the undercarriage, so that the vessel is able to pass through all the conceivable curves and slopes of a roller coaster without difficulty.

In the positions shown in FIGS. 1 and 2, on the other hand, the articulated connecting unit **20** permits the floating body **10** to execute relative movements vis-a-vis the undercarriage **20**, so that, like a boat that is floating freely, the floating body can execute the rocking and rolling movements typical of a floating body, even given varying water levels **63** and varying loads.

Consequently, the floating body **10**, whose passenger seats **12** are indicated in FIG. 5, can be conducted through the water in a naturalistic manner by means of the undercarriage **30** and the rails **40** that are located beneath the surface of the water **63**.

As depicted in FIG. 6, the body of water can be a water channel **60**, which is bordered by the channel floor **61** and the channel walls **62**. The body of water can also take the form of a large-scale lake or a winding river.

LIST OF REFERENCE NUMERALS

- 10** floating body
- 11** ball-headed bearing
- 12** passenger seats
- 14** coupling element
- 20** connecting unit
- 21** joint rods
- 22** ball-shaped head
- 30** undercarriage
- 31** chassis
- 32** running and support wheels
- 34** coupling element
- 40** guide rails
- 41** rail supports
- 50** base pedestal
- 60** channel
- 61** channel floor
- 62** channel wall
- 63** surface of water

The invention claimed is:

1. A water ride containing at least one watercraft, comprising:

- a floating body and a chassis which is connected thereto in an articulated manner and which serves as a guide unit;
- a guide for the chassis which runs in the water; and
- a drive for the watercraft, wherein the floating body is connected to the chassis via a connection unit which comprises flexible elements and which allows relative movements of the floating body with respect to the chassis, wherein arranged on the floating body and on the chassis are associated coupling elements which serve for rigidly connecting the floating body and the chassis in at

5

least one relative position, and in that the coupling elements are designed in such a way that the floating body is fixed on the chassis after being lowered.

2. The water ride according to claim 1, wherein the coupling elements can be locked, and wherein the locked coupling elements can be released in a controlled manner.

3. The water ride according to claim 1, wherein the connection unit is at least one of articulated rods which form transverse and longitudinal control arms, and of telescopic rods, linear guides, and rotation assemblies.

4. The water ride according to claim 1, wherein the flexible elements are at least one of cables, chains, belts and air cushions.

5. The water ride according to claim 3, wherein the connection unit is connected to at least one of a hydraulic, pneumatic cylinders, and cable feeds, which can be controlled.

6. The water ride according to claim 1, wherein the coupling elements have a redundant locking mechanism and/or a dead-centre locking mechanism or are designed as a king pin and a king pin bearing.

7. The water ride according to claim 1, wherein the floating body is a single-hulled or multi-hulled boat or a raft.

8. The water ride according to claim 7, wherein the boat is a sailing boat, a motorboat or a rowing boat.

6

9. The water ride according to claim 1, wherein drives are at least one of a cable drive and conveyor belt drive, which is mechanically connected to the craft.

10. The water ride according to claim 1, wherein the drive is at least one of a friction wheel drive and a toothed wheel drive.

11. The water ride according to claim 1, wherein the drive is a flow drive, comprising a pumped flow drive, with controllable outlet nozzles arranged in the water close to the guide.

12. The water ride according to claim 1, wherein the drive is an inductive motor drive.

13. The water ride according to claim 1, wherein the guide has downhill sections in which the watercraft is driven by gravity.

14. The water ride according claim 1, wherein the guide comprises at least one or more rails.

15. The water ride according to claim 1, further comprising running wheels or support wheels provided on the chassis, the running or support wheels resting on the guide rails in a rolling manner.

16. The water ride according to claim 1, wherein brake devices are arranged on the chassis and/or on the guide.

* * * * *