



US007443601B2

(12) **United States Patent**
Yoshida et al.

(10) **Patent No.:** **US 7,443,601 B2**
(45) **Date of Patent:** **Oct. 28, 2008**

(54) **ZOOM OPTICAL SYSTEM**

(75) Inventors: **Hirofumi Yoshida**, Yokohama (JP);
Koshi Hatakeyama, Kita-ku (JP)

(73) Assignee: **Canon Kabushiki Kaisha**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/453,120**

(22) Filed: **Jun. 13, 2006**

(65) **Prior Publication Data**
US 2006/0291069 A1 Dec. 28, 2006

(30) **Foreign Application Priority Data**
Jun. 27, 2005 (JP) 2005-186981
Jun. 27, 2005 (JP) 2005-186984

(51) **Int. Cl.**
G02B 15/14 (2006.01)

(52) **U.S. Cl.** **359/683; 359/720**

(58) **Field of Classification Search** 359/676,
359/683, 708, 720
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,305,294 A 2/1967 Alvarez
3,583,790 A 6/1971 Baker
6,850,372 B1 * 2/2005 Stenton 359/676
7,193,785 B2 * 3/2007 Yoshida et al. 359/676

FOREIGN PATENT DOCUMENTS

JP 2-119103 A 5/1990

OTHER PUBLICATIONS

Keisuke Araki, "Paraxial Analysis for Off-Axial Optical Systems", Japanese Journal of Optics, vol. 29, No. 3, 2000.

* cited by examiner

Primary Examiner—Darryl J Collins

(74) *Attorney, Agent, or Firm*—Canon U.S.A. Inc., IP Division

(57) **ABSTRACT**

At least one exemplary embodiment is directed to a zoom optical system which includes a plurality of variable power optical units of which optical power varies accompanied by variable power, a fixed optical unit of which optical power does not vary accompanied by variable power, and a moving optical unit which moves accompanied by variable power.

20 Claims, 58 Drawing Sheets




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5





FIG. 6




FIG. 7A





FIG. 7B



— 650 nm
····· 550 nm
- - - 450 nm

FIG. 7C




FIG. 8






FIG. 9

T: TELEPHOTO END



M: MIDDLE



W: WIDE-ANGLE END




FIG. 10






FIG. 11A



TELEPHOTO END

————— 650 nm
..... 550 nm
- - - - - 450 nm


FIG. 11B



MIDDLE

————— 650 nm
- - - - - 550 nm
- · - · - 450 nm

FIG. 11C



WIDE-ANGLE END

————— 650 nm
- - - - - 550 nm
- · - · - 450 nm

FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16






FIG. 17A



TELEPHOTO END

— 650 nm
- - - 550 nm
- · - · 450 nm


FIG. 17B



MIDDLE

— 650 nm
- - - 550 nm
- · - 450 nm


FIG. 17C



WIDE-ANGLE END

————— 650 nm
- - - - - 550 nm
- · - · - 450 nm

FIG. 18







FIG. 21




FIG. 22






FIG. 23A




TELEPHOTO END

FIG. 23B



MIDDLE

FIG. 23C



WIDE-ANGLE END

FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28






FIG. 29A




TELEPHOTO END

FIG. 29B




MIDDLE

FIG. 29C



WIDE-ANGLE END

FIG. 30







FIG. 33




FIG. 34






FIG. 35A




TELEPHOTO END

FIG. 35B



MIDDLE

FIG. 35C



WIDE-ANGLE END

FIG. 36




FIG. 37




FIG. 38




FIG. 39







FIG. 40A



TELEPHOTO END

— 650 nm
- - - 550 nm
- · - 450 nm


FIG. 40B



MIDDLE

— 650 nm
- - - 550 nm
- · - 450 nm

FIG. 40C



WIDE-ANGLE END

————— 650 nm
- - - - - 550 nm
- · - · - 450 nm

FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45






FIG. 46A



TELEPHOTO END

————— 650 nm
- - - - - 550 nm
- · - · - 450 nm


FIG. 46B



MIDDLE

— 650 nm
- - - 550 nm
- · - · 450 nm

FIG. 46C



WIDE-ANGLE END

————— 650 nm
- - - - - 550 nm
- · - · - 450 nm

FIG. 47





FIG. 48



1

ZOOM OPTICAL SYSTEM

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a zoom optical system and an imaging apparatus using the zoom optical system.

2. Description of the Related Art

In recent years, there has been an increased demand for small high resolution zoom optical systems, such as digital cameras, and cellular phones with cameras.

With a small high-resolution zoom optical system, zooming is commonly performed by moving a plurality of lens groups (lens units) in the optical-axis direction as to a photo-accepting surface (CCD). At this time, a zoom method for moving lens groups (lens units) in the object direction causes the entire optical length (length from a first lens surface to the image plane) to be lengthened, and this contributes to restricting reductions in size of the entire lens system.

In order to reduce the above factor, heretofore, an optical system employing optical elements called Alvarez lenses has been discussed for changing the power of the entire system by moving the optical elements in a direction different from the optical-axis direction (see U.S. Pat. Nos. 3,305,294, 3,583,790, and Optics Vol. 29, No. 3 (2000)).

Subsequently, various types of zoom optical systems for performing zooming using these Alvarez lenses have been discussed (see Japanese Patent Laid-Open No. 1990-119103).

With the optical system discussed in U.S. Pat. No. 3,305,294, power is changed by providing two lenses, which can have a surface represented with a tertiary function, and shifting these lenses in the direction different from the optical-axis direction. This optical system does not send out the lens groups (lens units) in the optical-axis direction, so employing this for a zoom optical system can reduce the entire lens length.

Also, the optical system discussed in U.S. Pat. No. 3,583,790 reduces an aberration by providing lenses, which can have a curved surface represented with an order term higher than a tertiary term, particularly a quintic term.

Further, in Japanese Patent Laid-Open No. 1990-119103 there is discussed an example in which two lens are employed for a zoom optical system. Subsequently, a theory for changing power while maintaining an image point in a steady manner has been discussed by disposing at least the two above lenses.

On the other hand, Optics Vol. 29, No. 3 (2000) describes an optical system including a rotational asymmetric optical element. This optical system has no common axis (optical axis), which is different from a normal coaxial lens system. Such a non-coaxial optical system is called as an Off-Axial optical system, which can be defined as an optical system including a curved surface (Off-Axial curved surface) where when assuming that the route in which the ray passing through the image center and the pupil center traces is taken as a reference axis, a surface normal at an intersection with the reference axis of constituent surfaces is not present on the reference axis. In this case, the reference axis has a folded and bent shape. Accordingly, this needs to employ a paraxial theory based on the Off-Axial theory other than the paraxial theory of a coaxial system such as usually employed for calculation of the paraxial amount. The optical principle of the method thereof has been introduced in the optics Vol. 29, No. 3 (2000), which is performed by calculating 4×4 determinants based on a surface curvature, for example.

2

With U.S. Pat. Nos. 3,305,294, 3,305,294, and 3,583,790, descriptions have been made regarding a method for changing power with a pair of rotational asymmetric lenses and correction of an aberration, but they cannot maintain an image plane in a steady manner when changing power.

Also, with Japanese Patent Laid-Open No. 1990-119103, the principle for changing power while maintaining an image point in a steady manner has been described, but has not reached the design level of a zoom optical system for obtaining an actual appropriate image by performing correction of an aberration.

In order to configure a zoom optical system with Alvarez lenses, it can be necessary in some circumstances to configure the system so as to have a steady image plane even at the time of zooming, and reduce the aberration fluctuation due to zooming.

SUMMARY OF THE INVENTION

At least one exemplary embodiment is directed to a zoom optical system and an imaging apparatus using the zoom optical system for example a projector, exposure apparatus, and reader.

At least one exemplary embodiment is directed to a zoom optical system which realizes a steady image plane even at the time of zooming, less aberration fluctuation due to zooming, high optical capabilities straddling the entire zoom range, and reduction in the entire optical length by appropriately employing an optical group, which can have a plurality of optical elements which include a rotationally asymmetrical surface and move in the direction different from the optical axis, and one or more optical groups.

According to at least one exemplary embodiment, a zoom optical system includes a plurality of variable power optical units of which optical power changes as magnification varies, where the plurality of variable power optical units each has plural optical elements moving in a direction different from an optical axis as magnification varies, a fixed optical unit of which optical power does not change as magnification varies, a moving optical unit which moves as magnification varies.

According to at least one exemplary embodiment, an imaging apparatus includes the zoom optical system, and a photoelectric conversion element for photo-accepting an image to be formed by the zoom optical system.

Further features and aspects of the present invention will become apparent from the following description of exemplary embodiments with reference to the attached drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a lens cross-sectional view according to an example 1 of at least one exemplary embodiment.

FIG. 2 is a diagram describing the Off-Axial optical system of a comparative example 2.

FIG. 3 is a plot of the power allocation of the lens designed based on the comparative example 1.

FIG. 4 is a cross-sectional view of the lens designed based on the comparative example 1.

FIG. 5 is a lens cross-sectional view of the comparative example 2.

FIG. 6 is a lens cross-sectional view of the telephoto end, middle, and wide-angle end according to the comparative example 2.

FIG. 7A is an aberration chart according to the comparative example 2.

FIG. 7B is an aberration chart according to the comparative example 2.

5

FIG. 48 is a chart illustrating change in power of an optical group G1 and an optical group G2 according to the example 7 of at least one exemplary embodiment.

DESCRIPTION OF THE EMBODIMENTS

The following description of at least one exemplary embodiment is merely illustrative in nature and is in no way intended to limit the invention, its application, or uses.

Processes, techniques, apparatus, and materials as known by one of ordinary skill in the relevant art may not be discussed in detail but are intended to be part of the enabling description where appropriate, for example the fabrication of the lens elements and their materials.

In all of the examples illustrated and discussed, herein any specific values, for example the zoom ratio and F number, should be interpreted to be illustrative only and non limiting. Thus, other examples of the exemplary embodiments could have different values.

Notice that similar reference numerals and letters refer to similar items in the following figures, and thus once an item is defined in one figure, it may not be discussed for following figures.

Note that herein when referring to correcting or corrections of an error (e.g., an aberration), a reduction of the error and/or a correction of the error is intended.

First, prior to describing examples of at least one exemplary embodiment, description will be made regarding the rotationally asymmetrical surface of the Off-Axial optical system making up the zoom optical system of at least one exemplary embodiment, and how to represent configuration specifications thereof.

With the Off-Axial optical system, as shown in FIG. 2 illustrated as a later-described comparative example 2 of at least one exemplary embodiment, a surface SO on the light incident side is taken as a reference plane, and an absolute coordinates system is set with the center PO of the reference plane SO as the origin. Let us say that the route traced by a ray passing through the origin PO and the pupil center is taken as a reference axis. Also, let us say that the straight line connecting an image center IPO and the origin of the absolute coordinates system serving as the center PO of the reference plane SO is taken as the Z axis, and the orientation headed to the image center from a first surface is positive. We will refer to this Z axis as the optical axis. Further, let us say that the Y axis is taken as the straight line passing through the origin PO, and originating 90 degrees in the counterclockwise direction as to the Z axis in accordance with the definition of the right-hand coordinates system, and the X axis is taken as the straight line passing through the origin, which is perpendicular to each axis of the Z and Y axes.

The paraxial values shown below are the results of performing Off-Axial paraxial tracing. Let us say that the Off-Axial paraxial tracing is performed, and the calculated results are taken as paraxial values, unless otherwise stated.

An optical system according to at least one exemplary embodiment has a rotational asymmetric shaped aspheric surface, and the shape is represented with the following equation.

$$z=C02y^2+C20x^2+C03y^3+C21x^2y+C04y^4+C22x^2y^2+C40x^4+C05y^5+C23x^2y^3+C41x^4y+C06y^6+C24x^2y^4+C42x^4y^2+C60x^6 \quad [\text{Equation 1}]$$

Equation 1 has even order terms alone regarding x, so the curved surface stipulated with Equation 1 has a surface-symmetric shape which takes the y-z surface (see FIG. 2) as a symmetric surface.

6

Also, in the event of satisfying the following condition, the shape represents a shape symmetric as to the x-z surface (see FIG. 2).

$$C03=C21=C05=C23=C41=t=0 \quad [\text{Equation 2}]$$

Further, in the event of satisfying the following conditions, the shape represents a rotational symmetric shape.

$$C02=C20 \quad [\text{Equation 3}]$$

$$C04=C40=C22/2 \quad [\text{Equation 4}]$$

$$C06=C60=C24/3=C42/3 \quad [\text{Equation 5}]$$

In the event of not satisfying the above conditions, the shape is a rotational asymmetric shape.

The rotational symmetric surface and rotationally asymmetrical surface shapes shown in the following examples and comparative examples are based on Equation 1 through Equation 5.

EXAMPLE 1

FIG. 1 is a lens cross-sectional view according to an example 1 of at least one exemplary embodiment. In FIG. 1, T, M, and W are lens cross-sectional views at the telephoto end (the zoom position where the power of the entire system is the minimum), at a middle zoom position, and at the wide-angle end (the zoom position where the power of the entire system is the maximum) respectively.

FIG. 10 is a lens cross-sectional view for selecting the middle zoom position of example 1 in FIG. 1 (M in FIG. 1) as an example and describing respective factors.

A zoom optical system according to example 1 is a photography lens system employed for an imaging apparatus, with the left hand side the object side, and the right hand side the image side in the lens cross-sectional view.

Note that the zoom optical system according to example 1 can be employed as a projector, and in this case, on the left hand side is a screen, and on the right hand side is a projection surface.

In FIG. 1 and FIG. 10, G1 and G3 are optical groups in which optical power is variable (optical power and focal distance vary at the time of zooming of the zoom optical system in the present example). G2 is an optical group in which optical power is substantially unchangeable (essentially unchangeable).

G4 is an optical group having symmetry as to at least one surface (one surface taken as a symmetric center), and including one or more optical elements Ls capable of decentering. With the present example, the term "optical group" is employed, but this can be referred to as "optical unit", "lens unit", or "lens group." In other words, the optical elements Ls can have a rotational asymmetric shape symmetric as to multiple surfaces (e.g., toric surfaces or other related or equivalent surfaces as known by one of ordinary skill in the relevant art), but in at least one exemplary embodiment, which are optical elements having a rotational asymmetric shaped surface symmetric as to only one surface (only one surface serving as a symmetric center exists). This can be also applied to the optical elements included in the G1 and G3.

Zooming is performed while maintaining the image plane IP in a steady manner by changing the power of the two optical groups G1 and G3 each of which optical power is variable.

The two optical groups G1 and G3 each of which optical power is variable each include a rotationally asymmetrical surface, move in the direction substantially different from the

optical axis, and include two optical elements E1 and E2 which change the power within the optical group G1, and two optical elements E5 and E6 which change the power within the optical group G3, respectively.

Note that the term "optical power" refers to the power of a surface positioned on the optical axis, and when the surface on the optical axis varies by the optical element having a rotationally asymmetrical surface being decentered, optical power is also changed in response to that change.

In example 1 of at least one exemplary embodiment, seven optical elements (lenses) are employed in total. In order from the object side, the optical elements E1, E2, E5, and E6 have a rotational asymmetric shape, these optical elements are decentered in the Y-axis direction, and the amount of decentering continuously varies. Also, the absolute value of the amount thereof is set so as to be equal with mutually positive/negative reverse. The optical elements E3 and E4 have a rotational symmetric spherical surface. In the event that an asymmetric aberration remains on the optical axis, the optical elements E3 and E4 can have a rotational asymmetric shape to reduce this. The optical element E7 has a rotational asymmetric shape symmetric as to at least one surface. This reduces the on-axis coma aberration which may not have been reduced in the optical elements E1 through E6 by shifting or tilting this aberration. Also, the first group G1 comprises the optical elements E1 and E2. Similarly, the second group G2 comprises the optical elements E3 and E4, and the third group G3 comprises the optical elements E5 and E6. The fourth group G4 comprises the optical element E7. As for surface numbers, the reference plane serving as the origin of the absolute coordinates system is determined as a surface S0, the first surface of the optical element E1 is determined as S1, and in order, the corresponding surfaces are surfaces S2, S3, S4, and so on, and following the surface S6 (backward of the optical element E3) a diaphragm S7 (SP) is disposed. The first surface of the optical element E4 is determined as S8, and the subsequent numbers are assigned in order, and the image plane IP is S16. Hereinafter, decentering continues in the Y-axis direction, and let us say that the rotational asymmetric groups (G1 and G3), which contribute to change in power, the rotational symmetric group (G2), and the fourth group G4 made up of the optical element (E7) configured to suppress the above residual aberration by decentering are referred to as decentering movable blocks G1 and G3, auxiliary block G2, and auxiliary movable block G4, respectively. Disposing the decentering movable blocks G1 and G3 alone makes the power thereof too strong, and can make it difficult to perform correction of an aberration, and accordingly, the auxiliary block G2 is disposed.

The lens data of the example 1 is shown in Table 7. The amount of shift from the Z axis of the respective optical elements is shown in Table 8. The values of the respective coefficients of the polynomial surfaces represented with Equation 1 are shown in Tables 9-1 and 9-2. FIG. 1 is a lens cross-sectional view at the telephoto end (T), middle zoom position (M), and wide-angle end (W) shown in Table 8. The optical elements E1 and E2 are decentered in the Y-axis direction, and the absolute value of the amount thereof is so as to be equal with mutually positive/negative reverse, as shown in Table 8. Thus, the power of the first group G1 is changed from positive to negative between the telephoto end and the wide-angle end. The ray emitted from the first group G1 passes through the optical element E3, diaphragm SP, and optical element E4, and illuminates the optical elements E5 and E6. The optical elements E5 and E6 are decentered in the Y-axis direction, and the absolute value of the amount thereof is so as to be equal with mutually positive/negative reverse, as

shown in Table 8. Thus, the power of the third group G3 is changed from negative to positive between the telephoto end and the wide-angle end. The ray passed through these decentering movable blocks G1 and G3 illuminates the next auxiliary movable block G4. The auxiliary movable block G4 compensates the power necessary for the decentering movable blocks G1 and G3. The ray passed through these optical elements forms an image without changing the image plane IP.

Next, the aberration charts at the telephoto end, middle zoom position, and wide-angle end are shown in FIG. 11A through FIG. 11C, respectively. The horizontal axis represents the position of a ray on the pupil, and the vertical axis represents the shift from the chief ray on the image plane. The range of the vertical axis is about $\pm 20 \mu\text{m}$. The numbers within FIG. 11A through FIG. 11C are angle-of-view numbers, which on the image plane are such as illustrated in FIG. 8. The shapes of the optical elements are symmetric as to the X axis, so only the positive case should be taken into consideration regarding the X direction. When viewing the ray at an angle of view of 0° , it can be understood that a coma aberration can be reduced from the telephoto end to the wide-angle end. Also, FIG. 12 illustrates the distortion reactor lattices at a telephoto end T, middle zoom position M, and wide-angle end W. The lengthwise and crosswise size of the lattices is about $\frac{1}{4}$ inch (vertically 2.7 mm \times horizontally 3.6 mm). When viewing this figure, it can be understood that distortion can be suppressed, but when viewing the ray at an angle of view of 0° , it can be understood that some amount of a coma aberration can remain.

FIG. 13 is a chart plotting change in power $\Phi 1$ and $\Phi 3$ of the first group G1 and the third group G3 caused by zooming, and the sum thereof $\Phi 13$ ($\Phi 1 + \Phi 3$) as to the power of the entire system.

At this time, when assuming that the maximum value of the absolute value of the power in the first group G1 and the third group G3 is $|\Phi|_{\text{max}}$, and the power of the sum of the first group G1 and the third group G3 is $\Phi 13$, the following condition

$$-|\Phi|_{\text{max}} \leq \Phi 13 \leq |\Phi|_{\text{max}}$$

can be satisfied.

Satisfying the conditional expression (5) reduces the Petzval sum and the image plane distortion.

FIG. 14 illustrates change in the principal-point positions before and after the first group G1 and the third group G3 (H1 is the forward principal-point position of the first group G1, H1' is the backward principal-point position of the first group G1, H2 is the forward principal-point position of the third group G3, and H2' is the backward principal-point position of the third group G3). The first group G1 is made up of meniscus-shaped optical elements, so the principal-point position thereof greatly moves. Also, when comparing the change thereof with FIG. 13, it can be understood that the power of the first group G1 moves in the object direction in the positive range as the power of the entire system increases, and expands the interval of the H1 and H2. Also, it can be understood that the power of the first group G1 moves in the object direction even in the negative range as the power of the entire system increases, and expands the interval of the H1 and H2. Also, when assuming that the forward principal-point position and the backward principal-point position of the first group G1 are H1 and H1' respectively, the forward principal-point position and the backward principal-point position of the third group G3 are H2 and H2' respectively, the distance between the object point and the H1 is e_0 , the distance between the H1' and

H2 is e, the distance between the H2' and the image point is ei, and smaller distance between the eo and ei is e', the relationships between e and e' and the relationships of e/e' are shown in Table 10. When viewing this, it can be understood that the e and e' are essentially the same at any zoom position.

Particularly,

$$0.7 < e/e' < 1.4$$

can be satisfied.

Further, when assuming that the backward principal-point position of the first group G1 is H1', the forward principal-point position of the third group G3 is H2, the of the entire system is the smallest in the positive range of the power of the first group G1 at zooming is et1, the distance between the H1' and H2 in a case in which the power of the entire system is the greatest is ew1, the distance between the H1' and H2 in a case in which the power of the entire system is the smallest in the negative range of the power of the first group G1 at zooming is et2, and the distance between the H1' and H2 in a case in which the power of the entire system is the greatest is ew2, it can be understood from FIG. 14 that

$$et1 < ew1$$

$$et2 < ew2$$

can be satisfied.

With the example 1, the sign of the optical power of the optical group G4 is substantially unchangeable within the entire zoom range.

Thus, correction of the residual aberration in the optical groups G1 and G3 of which optical power is variable, and correction of aberration fluctuation due to zooming can be performed.

When the maximum value of the absolute value of the optical power in the optical groups G1 and G3 of which optical power is variable is $|\Phi|_{\max}$ at the entire zoom positions, the maximum value of the absolute value of the optical power in the optical group G4 is $|\Phi_s|_{\max}$ at the entire zoom positions, the condition

$$|\Phi_s|_{\max} < |\Phi|_{\max}$$

can be satisfied.

This facilitates a predetermined zoom ratio to be readily obtained, and also reduces the aberration fluctuation caused by zooming.

Also, when assuming that the optical elements E1, E2, E5, and E6 shift, the maximum value of the absolute value of the shift amount at this time at the entire zoom positions is $|Dd|_{\max}$, and the maximum value of the absolute value of the shift amount of the optical element Lss at the entire zoom positions is $|Ds|_{\max}$, the condition

$$|Ds|_{\max} < |Dd|_{\max}$$

can be satisfied.

This facilitates a predetermined zoom ratio to be readily obtained, and also enables the aberration fluctuation accompanied by zooming to be preferably corrected, in the event that the optical group of which optical power is variable performs zooming by changing the optical power.

Note that with the present example and the following examples, focusing can be performed by moving the entire system, or by moving one optical group in substantially the vertical direction as to the optical axis.

Hereinafter, description will be made regarding examples 2 through 4 of at least one exemplary embodiment.

With the examples 2 through 4, description will be made with a focus on the other features other than the features of the above example 1.

EXAMPLE 2

FIG. 15 is a lens cross-sectional view according to an example 2 of at least one exemplary embodiment.

The specifications are substantially similar to example 1. Seven optical elements (lenses) are employed in total. In order from the object side, the optical elements E1b, E2b, E5b, and E6b have a rotational asymmetric shape, these optical elements are decentered in the Y-axis direction, and the amount of decentering thereof continuously varies. Also, the absolute value of the amount thereof is set so as to be equal with mutually positive/negative reverse. The optical elements E3b and E4b have a rotational symmetric spherical surface. In the event that an asymmetric aberration remains on the optical axis, the optical elements E3b and E4b can have a rotational asymmetric shape to reduce this. The optical element E7b has a rotational asymmetric shape symmetric as to at least one surface. This reduces the on-axis coma aberration which has not been able to be reduced in the optical elements E1b and E2b by tilting this aberration. Also, the first group G1b comprises the optical elements E1b and E2b. Similarly, the second group G2b comprises the optical elements E3b and E4b, and the third group G3b comprises the optical elements E5b and E6b. As for surface numbers, the reference plane serving as the origin of the absolute coordinates system is determined as a surface S0, the first surface of the optical element E1b is determined as S1b, and in order, the corresponding surfaces are surfaces S2b, S3b, S4b, and so on, and following the surface S6b (backward of the optical element E3b) a diaphragm S7b (SP) is disposed. The first surface of the optical element E4b is determined as S8b, and the subsequent numbers are assigned in order, and the image plane IP is S16b. Hereinafter, decentering continues in the Y-axis direction, and let us say that the rotational asymmetric groups (G1b and G3b), which contribute to change in power, the rotational symmetric group (G2b), and the optical element (E7b) configured to suppress the above residual aberration by decentering are referred to as decentering movable blocks, auxiliary block, and auxiliary movable block, respectively. Disposing the decentering movable blocks G1b and G3b alone makes the power thereof too strong, and can make it difficult to perform correction of aberrations, and accordingly, the auxiliary blocks G2b and E7b are disposed.

The lens data of the example 2 is shown in Table 11. The amount of shift from the Z axis of the respective optical elements is such as shown in Table 12, the amount of tilt of the optical element E7b is such shown in Table 13. The values of the respective coefficients of the polynomial surfaces represented with Equation 1 are shown in Tables 14-1 and 14-2. FIG. 16 illustrates the optical path diagrams at this time in order of a telephoto end T, middle zoom position M, and wide-angle end W. The optical elements E1b and E2b are decentered in the Y-axis direction, and the absolute value of the amount thereof is so as to be equal with mutually positive/negative reverse, as shown in Table 12. Thus, the power of the first group G1b is changed from positive to negative between the telephoto end and the wide-angle end. The ray emitted from the first group G1b passes through the optical element E3b, diaphragm S7b (SP), and optical element E4b, and illuminates the optical elements E5b and E6b. The optical elements E5b and E6b are decentered in the Y-axis direction, and the absolute value of the amount thereof is so as to be equal with mutually positive/negative reverse, as shown in Table 10.

11

Thus, the power of the third group $G3b$ is changed from negative to positive between the telephoto end and the wide-angle end. The ray passed through these decentering movable blocks illuminates the next auxiliary block $E7b$. The auxiliary block $E7b$ compensates the power necessary for the decentering movable blocks $G1b$ and $G3b$. The ray passed through these optical elements forms an image without changing the image plane IP.

Next, the aberration charts at the telephoto end, middle zoom position, and wide-angle end are shown in FIG. 17A through FIG. 17C, respectively. The horizontal axis represents the position of a ray on the pupil, and the vertical axis represents the shift from the chief ray on the image plane. The range of the vertical axis is about $\pm 20 \mu\text{m}$. The numbers within FIG. 17A through FIG. 17C are angle-of-view numbers, which on the image plane are such as illustrated in FIG. 8. The shapes of the optical elements can be symmetric as to the X axis, so the positive case should be taken into consideration regarding the X direction. When viewing the ray at an angle of view of 0° , it can be understood that a coma aberration can be reduced from the telephoto end to the wide-angle end. Also, FIG. 18 illustrates the distortion reactor lattices at a telephoto end T, middle zoom position M, and wide-angle end W. The lengthwise and crosswise size of the lattices is about $\frac{1}{4}$ inch (vertically 2.7 mm horizontally 3.6 mm). When viewing this figure, it can be understood that distortion can be suppressed, but when viewing the ray at an angle of view of 0° , it can be understood that some amount of a coma aberration can remain.

FIG. 19 is a chart plotting change in power $\Phi 1$ and $\Phi 3$ of the first group $G1b$ and the third group $G3b$, and the sum thereof $\Phi 13$ as to the power of the entire system.

At this time, when assuming that the maximum value of the absolute value of the power in the first group $G1b$ and the third group $G3b$ is $|\Phi|_{\text{max}}$, and the power of the sum of the first group $G1b$ and the third group $G3b$ is $\Phi 13$, the following condition

$$-|\Phi|_{\text{max}} \leq \Phi 13 \leq |\Phi|_{\text{max}}$$

can be satisfied.

FIG. 20 illustrates change in the principal-point positions before and after the first group $G1b$ and the third group $G3b$ ($H1$ is the forward principal-point position of the first group $G1b$, $H1'$ is the backward principal-point position of the first group $G1b$, $H2$ is the forward principal-point position of the third group $G3b$, and $H2'$ is the backward principal-point position of the third group $G3b$). The first group $G1b$ is made up of meniscus lenses, so the principal-point position thereof greatly moves. Also, when viewing the change thereof, it can be understood that the power of the first group $G1b$ moves in the object direction in the positive range as the power of the entire system increases, and expands the interval of the $H1$ and $H2$.

Also, when assuming that the forward principal-point position and the backward principal-point position of the first group $G1b$ are $H1$ and $H1'$ respectively, the forward principal-point position and the backward principal-point position of the third group $G3b$ are $H2$ and $H2'$ respectively, the distance between the object point and the $H1$ is e_0 , the distance between the $H1'$ and $H2$ is e , the distance between the $H2'$ and the image point is e_i , and smaller distance between the e_0 and e_i is e' , the relationships between e and e' and the relationships of e/e' are shown in Table 15. When viewing this, the relationships of e/e' at the telephoto end are as follows except for a zoom state 4:

$$0.7 < e/e' < 1.4$$

12

Further, when assuming that the backward principal-point position of the first group $G1b$ is $H1'$, the forward principal-point position of the third group $G3b$ is $H2$, the distance between the $H1'$ and $H2$ in a case in which the power of the entire system is the smallest in the positive range of the power of the first group $G1b$ is $et1$, the distance between the $H1'$ and $H2$ in a case in which the power of the entire system is the greatest is $ew1$, the distance between the $H1'$ and $H2$ in a case in which the power of the entire system is the smallest in the negative range of the power of the first group $G1b$ is $et2$, and the distance between the $H1'$ and $H2$ in a case in which the power of the entire system is the greatest is $ew2$, it can be understood from FIG. 20 that

$$et1 < ew1$$

$$et2 < ew2$$

can be satisfied. The features other than this are substantially similar to example 1.

EXAMPLE 3

FIG. 21 is a lens cross-sectional view according to an example 3 of at least one exemplary embodiment.

The specifications of the present example are substantially similar to example 1. Seven optical elements (lenses) are employed in total. In order from the object side, the optical elements $E1c$, $E2c$, $E5c$, and $E6c$ have a rotational asymmetric shape, these optical elements are decentered in the Y-axis direction, and the amount of decentering thereof continuously varies. Also, the absolute value of the amount thereof is set so as to be equal with mutually positive/negative reverse. The optical elements $E3c$ and $E4c$ have a rotational symmetric spherical surface. In the event that an asymmetric aberration remains on the optical axis, the optical elements $E3c$ and $E4c$ can have a rotational asymmetric shape to reduce this. The optical element $E7c$ also has a rotational symmetric shape. This reduces the on-axis coma aberration which may not have been reduced in the optical elements $E1c$ and $E2c$ by shifting this aberration. Also, the first group $G1c$ comprises the optical elements $E1c$ and $E2c$. Similarly, the second group $G2c$ comprises the optical elements $E3c$ and $E4c$, and the third group $G3c$ comprises the optical elements $E5c$ and $E6c$. As for surface numbers, the reference plane serving as the origin of the absolute coordinates system is determined as a surface $S0$, the first surface of the optical element $E1c$ is determined as $S1c$, and in order, the corresponding surfaces are $S2c$, $S3c$, $S4c$, and so on, and following the surface $S6c$ (backward of the optical element $E3c$) a diaphragm $S7c$ (SP) is disposed. The first surface of the optical element $E4$ is determined as $S8c$, and the subsequent numbers are assigned in order, and the image plane IP is $S16c$. Hereinafter, decentering continues in the Y-axis direction, and let us say that the rotational asymmetric groups ($G1c$ and $G3c$), which contribute to change in power, the rotational symmetric group ($G2c$), and the optical element ($E7c$) configured to suppress the above residual aberrations by decentering are referred to as decentering movable blocks, auxiliary block, and auxiliary movable block, respectively. Disposing the decentering movable blocks $G1c$ and $G3c$ alone makes the power thereof too strong, and can make it difficult to perform correction of an aberration, and accordingly, the auxiliary blocks $G2c$ and $E7c$ are disposed.

The lens data of the example 3 is shown in Table 16. The amount of shift from the Z axis of the respective optical elements is such as shown in Table 17, and the amount of shift of the optical element E7 is such as shown in Table 18. The

values of the respective coefficients of the polynomial surfaces represented with Equation 1 are shown in Table 19. FIG. 22 illustrates the optical path diagrams at this time in order of a telephoto end T, middle zoom position M, and wide-angle end W. The lenses of the optical elements E1c and E2c are decentered in the Y-axis direction, and the absolute value of the amount thereof is so as to be equal with mutually positive/negative reverse, as shown in Table 17. Thus, the power of the first group G1c is changed from positive to negative between the telephoto end and the wide-angle end. The ray emitted from the first group G1c passes through the optical element E3c, diaphragm S7c (SP), and optical element E4c, and illuminates the optical elements E5c and E6c. The optical elements E5c and E6c are decentered in the Y-axis direction, and the absolute value of the amount thereof is so as to be equal with mutually positive/negative reverse, as shown in Table 17. Thus, the power of the third group G3c is changed from negative to positive between the telephoto end and the wide-angle end. The ray passed through these decentering movable blocks illuminates the next auxiliary block E7c. The auxiliary block E7c compensates the power necessary for the decentering movable blocks G1c and G3c. The ray passed through these optical elements forms an image without changing the image plane IP.

Next, the aberration charts at the telephoto end, middle zoom position, and wide-angle end are shown in FIG. 23A through FIG. 23C, respectively. The horizontal axis represents the position of a ray on the pupil, and the vertical axis represents the shift from the chief ray on the image plane. The range of the vertical axis is about $\pm 20 \mu\text{m}$. The numbers within FIG. 23A through FIG. 23C are angle-of-view numbers, which on the image plane are such as illustrated in FIG. 8. The shapes of the optical elements are symmetric as to the X axis, so only the positive case should be taken into consideration regarding the X direction. When viewing the ray at an angle of view of 0° , it can be understood that a coma aberration can be reduced from the telephoto end to the wide-angle end. Also, FIG. 24 illustrates the distortion reactor lattices at a telephoto end T, middle zoom position M, and wide-angle end W. The lengthwise and crosswise size of the lattices is about $\frac{1}{4}$ inch (vertically 2.7 mm \times horizontally 3.6 mm). When viewing this figure, it can be understood that distortion can be suppressed, but when viewing the ray at an angle of view of 0° , it can be understood that some amount of a coma aberration can remain.

FIG. 25 is a chart plotting change in power $\Phi 1$ and $\Phi 33$ of the first group G1c and the third group G3c, and the sum thereof $\Phi 13$ as to the power of the entire system.

At this time, when assuming that the maximum value of the absolute value of the power in the first group G1c and the third group G3c is $\Phi 10$, max, and the power of the sum of the first group G1c and the third group G3c is ($\Phi 13$, the following condition

$$-|\Phi|_{\text{max}} \leq \Phi 13 \leq |\Phi|_{\text{max}}$$

can be satisfied.

FIG. 26 illustrates change in the principal-point positions before and after the first group G1c and the third group G3c (H1 is the forward principal-point position of the first group G1c, H1' is the backward principal-point position of the first group G1c, H2 is the forward principal-point position of the third group G3c, and H2' is the backward principal-point position of the third group G3c). The first group G1c is made up of meniscus lenses, so the principal-point position thereof greatly moves. Also, when viewing the change thereof, it can be understood that the power of the first group G1c moves in

the object direction in the positive range as the power of the entire system increases, and expands the interval of the H1 and H2. Also, it can be understood that the power of the first group G1c moves in the object direction even in the negative range as the power of the entire system increases, and expands the interval of the H1 and H2. Also, when assuming that the forward principal-point position and the backward principal-point position of the first group G1c are H1 and H1' respectively, the forward principal-point position and the backward principal-point position of the third group G3c are H2 and H2' respectively, the distance between the object point and the H1 is e_0 , the distance between the H1' and H2 is e , the distance between the H2' and the image point is e_i , and smaller distance between the e_0 and e_i is e' , the relationships between e and e' and the relationships of e/e' are shown in Table 20. When viewing this, the following condition

$$0.7 < e/e' < 1.4$$

can be satisfied except for a zoom state 5.

Further, when assuming that the backward principal-point position of the first group G1c is H1', the forward principal-point position of the third group G3c is H2, the distance between the H1' and H2 in a case in which the power of the entire system is the smallest in the positive range of the power of the first group G1c is e_{t1} , the distance between the H1' and H2 in a case in which the power of the entire system is the greatest is e_{w1} , the distance between the H1' and H2 in a case in which the power of the entire system is the smallest in the negative range of the power of the first group G1c is e_{t2} , and the distance between the H1' and H2 in a case in which the power of the entire system is the greatest is e_{w2} , it can be understood from FIG. 26 that

$$e_{t1} < e_{w1}$$

$$e_{t2} < e_{w2}$$

can be satisfied.

The features other than this are substantially similar to example 1.

EXAMPLE 4

FIG. 27 is a lens cross-sectional view according to an example 4 of at least one exemplary embodiment.

The specifications are substantially similar to example 1. Seven optical elements (lenses) are employed in total. In order from the object side, the optical elements E1d, E2d, E5d, and E6d have a rotational asymmetric shape, these optical elements are decentered in the Y-axis direction, and the amount of decentering thereof continuously varies. Also, the absolute value of the amount thereof is set so as to be equal with mutually positive/negative reverse. The optical elements E3d and E4d have a rotational symmetric spherical surface. In the event that an asymmetric aberration remains on the optical axis, the optical elements E3d and E4d can have a rotational asymmetric shape to reduce this. The optical elements E7d and E8d have a rotational asymmetric shape symmetric as to at least one surface. This reduces the on-axis coma aberration which has not been able to be reduced in the optical elements E1d and E2d by tilting this aberration. Also, the first group G1d comprises the optical elements E1d and E2d. Similarly, the second group G2d comprises the optical elements E3d and E4d, the third group G3d comprises the optical elements E5d and E6d, and the fourth group G4d comprises the optical elements E7d and E8d. As for surface numbers, the reference plane serving as the origin of the absolute coordinates system

is determined as a surface S0, the first surface of the optical element E1d is determined as S1d, and in order, the corresponding surfaces are S2d, S3d, S4d, and so on, and following the surface S6d (backward of the optical element E3d) a diaphragm S7d (SP) is disposed. The first surface of the optical element E4d is determined as S8d, and the subsequent numbers are assigned in order, and the image plane IP is S18d. Hereinafter, decentering continues in the Y-axis direction, and let us say that the rotational asymmetric groups (G1d and G3d), which contribute to change in power, the rotational symmetric group (G2d), and the group (G4d) configured to suppress the above residual aberrations by decentering are referred to as decentering movable blocks, auxiliary block, and auxiliary movable block, respectively. Disposing the decentering movable blocks G1d and G3d alone makes the power thereof too strong, and can make it difficult to perform correction of aberrations, and accordingly, the auxiliary block G2d is disposed.

The lens data of the example 4 is shown in Table 21. Table 22 shows the amount of shift from the Z axis of the respective optical elements, and Table 23 shows the amount of tilt in the optical elements E7d and E8d. The values of the respective coefficients of the polynomial surfaces represented with Equation 1 are shown in Table 24. FIG. 28 illustrates the optical path diagrams at this time in order of a telephoto end T, middle zoom position M, and wide-angle end W. The optical elements E1d and E2d are decentered in the Y-axis direction, and the absolute value of the amount thereof is so as to be equal with mutually positive/negative reverse, as shown in Table 22. Thus, the power of the first group G1d is changed from positive to negative between the telephoto end and the wide-angle end. The ray emitted from the first group G1d passes through the optical element E3d, diaphragm S7 (SP), and optical element E4d, and illuminates the optical elements E5d and E6d. The optical elements E5d and E6d are decentered in the Y-axis direction, and the absolute value of the amount thereof is so as to be equal with mutually positive/negative reverse, as shown in Table 22. Thus, the power of the third group G3d is changed from negative to positive between the telephoto end and the wide-angle end. The ray passed through these decentering movable blocks illuminates the next auxiliary block G4d. The auxiliary block G4d compensates the power necessary for the decentering movable blocks. The ray passed through these optical elements forms an image without changing the image plane.

Next, the aberration charts at the telephoto end, middle zoom position, and wide-angle end are shown in FIG. 29A through FIG. 29C, respectively. The horizontal axis represents the position of a ray on the pupil, and the vertical axis represents the shift from the chief ray on the image plane. The range of the vertical axis is about $\pm 20 \mu\text{m}$. The numbers within FIG. 29A through FIG. 29C are angle-of-view numbers, which on the image plane are such as illustrated in FIG. 8. The shapes of the optical elements can be symmetric as to the X axis, so the positive case should be taken into consideration regarding the X direction. When viewing the ray at an angle of view of 0° , it can be understood that a coma aberration can be reduced from the telephoto end to the wide-angle end. Also, FIG. 30 illustrates the distortion reactor lattices at a telephoto end T, middle zoom position M, and wide-angle end W. The lengthwise and crosswise size of the lattices is about $\frac{1}{4}$ inch (vertically 2.7 mm horizontally 3.6 mm). When viewing this figure, it can be understood that distortion can be suppressed, but when viewing the ray at an angle of view of 0° , it can be understood that some amount of a coma aberration can remain.

FIG. 31 is a chart plotting change in power $\Phi 1$ and $\Phi 3$ of the first group G1d and the third group G3d, and the sum thereof $\Phi 13$ as to the power of the entire system.

At this time, when assuming that the maximum value of the absolute value of the power in the first group G1d and the third group G3d is $|\Phi|_{\text{max}}$, and the power of the sum of the first group G1d and the third group G3d is $\Phi 13$, the following condition

$$-|\Phi|_{\text{max}} \leq \Phi 13 \leq |\Phi|_{\text{max}}$$

can be satisfied.

FIG. 32 illustrates change in the principal-point positions before and after the first group G1d and the third group G3d (H1 is the forward principal-point position of the first group G1d, H1' is the backward principal-point position of the first group G1d, H2 is the forward principal-point position of the third group G3d, and H2' is the backward principal-point position of the third group G3d). The first group G1d is made up of meniscus lenses, so the principal-point position thereof greatly moves. Also, when viewing the change thereof, it can be understood that the power of the first group G1d moves in the object direction in the positive range as the power of the entire system increases, and expands the interval of the H1 and H2. Also, it can be understood that the power of the first group G1d moves in the object direction even in the negative range as the power of the entire system increases, and expands the interval of the H1 and H2. Also, when assuming that the forward principal-point position and the backward principal-point position of the first group G1d are H1 and H1' respectively, the forward principal-point position and the backward principal-point position of the third group G3d are H2 and H2' respectively, the distance between the object point and the H1 is e_0 , the distance between the H1' and H2 is e , the distance between the H2' and the image point is e_i , and smaller distance between the e_0 and e_i is e' , the relationships between e and e' and the relationships of e/e' are shown in Table 25. When viewing this, the following condition

$$0.7 < e/e' < 1.4$$

can be satisfied except for a zoom state 5.

Further, when assuming that the backward principal-point position of the first group G1d is H1', the forward principal-point position of the third group G3d is H2, the distance between the H1' and H2 in a case in which the power of the entire system is the smallest in the positive range of the power of the first group G1d is $et1$, the distance between the H1' and H2 in a case in which the power of the entire system is the greatest is $ew1$, the distance between the H1' and H2 in a case in which the power of the entire system is the smallest in the negative range of the power of the first group G1d is $et2$, and the distance between the H1' and H2 in a case in which the power of the entire system is the greatest is $ew2$, it can be understood from FIG. 32 that

$$et1 < ew1$$

$$et2 < ew2$$

can be satisfied.

The features other than this are substantially similar to example 1.

As described above, according to the respective examples, zooming can be performed while preferably eliminating an aberration by moving the rotational asymmetric optical elements in the direction different from the optical axis, and also a compact optical system having excellent optical capabilities can be obtained.

FIG. 33 is a lens cross-sectional view according to an example 5 of at least one exemplary embodiment.

In FIG. 33, T, M, and W are lens cross-sectional views at the telephoto end (the zoom position where the power of the entire system is the minimum), at a middle zoom position, and at the wide-angle end (the zoom position where the power of the entire system is the maximum) respectively.

FIG. 34 is a lens cross-sectional view for selecting the middle zoom position of the example 5 in FIG. 33 (M in FIG. 33) as an example and describing respective factors.

A zoom optical system according to the example 5 is a photography lens system employed for an imaging apparatus, and the left hand is the object side, and the right hand is the image side in the lens cross-sectional view.

Note that the zoom optical system according to the example 5 can be employed as a projector, and in this case, the left hand is a screen, and the right hand is a projection surface.

In FIG. 33 and FIG. 34, G1e and G2e are optical groups of which optical power is variable.

G3e is an optical group having symmetry as to at least one surface, and including one or more optical elements Ls capable of decentering.

Zooming is performed by changing the power in the two optical groups G1e and G2e each of which optical power is variable.

The two optical groups G1e and G2e each of which optical power is variable each include a rotationally asymmetrical surface, move in the direction different from the optical axis, and include two optical elements E1e and E2e which change the power within the optical group G1e, and two optical elements E3e and E4e which change the power within the optical group G2e, respectively.

Note that the term "optical power" refers to the power of a surface positioned on the optical axis, and when the surface on the optical axis varies by the optical element having a rotationally asymmetrical surface being decentered, optical power is also changed in response to that change.

With the example 5 of at least one exemplary embodiment, five optical elements (lenses) are employed in total. In order from the object side, the optical elements E1e, E2e, E3e, and E4e have a rotational asymmetric shape, these optical elements are decentered in the Y-axis direction, and the amount of decentering continuously varies. The optical element E5e has a rotational asymmetric shape symmetric as to at least one surface. This reduces the on-axis coma aberration which may not have been reduced in the optical elements E1e through E4e by shifting or tilting this aberration. Also, the first group G1e comprises the optical elements E1e and E2e. Similarly, the second group G2e comprises the optical elements E3e and E4e, and the third group G3e comprises the optical element E7e. As for surface numbers, the reference plane serving as the origin of the absolute coordinates system is determined as a surface S0, the first surface of the optical element E1e is determined as S1e, and in order, the corresponding surfaces are surfaces S2e, S3e, and S4e, and following the surface S4e (backward of the optical element E2e) a diaphragm S5e (SP) is disposed. The first surface of the optical element E3e is determined as S6e, and the subsequent numbers are assigned in order, and the image plane IP is S12e. Hereinafter, decentering continues in the Y-axis direction, and let us say that the rotational asymmetric groups (G1e and G2e), which contribute to change in power, and the third group G3e made up of the optical element (E5e) configured to suppress the above

residual aberrations by decentering are referred to as decentering movable blocks G1e and G2e, and auxiliary movable block G3, respectively.

The lens data of the example 5 is shown in Table 26. The amount of shift from the Z axis of the respective optical elements is shown in Table 27. The values of the respective coefficients of the polynomial surfaces represented with Equation 1 are shown in Tables 28-1 and 28-2. The optical elements E1e and E2e are decentered in the Y-axis direction. Thus, the power of the first group G1e is changed from positive to negative between the telephoto end and the wide-angle end. The ray emitted from the first group G1e passes through the diaphragm SP, and illuminates the optical elements E3e and E4e. The optical elements E3e and E4e are decentered in the Y-axis direction. Thus, the power of the second group G2e is changed from negative to positive between the telephoto end and the wide-angle end. The ray passed through these decentering movable blocks G1e and G2e illuminates the next auxiliary movable block G3e. The auxiliary movable block G3e compensates the power necessary for the decentering movable blocks G1e and G2e. The ray passed through these optical elements forms an image without changing the image plane IP.

Next, the aberration charts at the telephoto end, middle zoom position, and wide-angle end are shown in FIG. 35A through FIG. 35C, respectively. The horizontal axis represents the position of a ray on the pupil, and the vertical axis represents the shift from the chief ray on the image plane. The range of the vertical axis is about $\pm 20 \mu\text{m}$. The numbers within FIG. 35A through FIG. 35C are angle-of-view numbers, which on the image plane are such as illustrated in FIG. 8. The shapes of the optical elements are symmetric as to the X axis, so only the positive case should be taken into consideration regarding the X direction. When viewing the ray at an angle of view of 0° , it can be understood that a coma aberration can be reduced from the telephoto end to the wide-angle end. Also, FIG. 36 illustrates the distortion reactor lattices at a telephoto end T, middle zoom position M, and wide-angle end W. The lengthwise and crosswise size of the lattices is about $\frac{1}{4}$ inch (vertically 2.7 mm \times horizontally 3.6 mm). When viewing this figure, it can be understood that distortion can be suppressed, but when viewing the ray at an angle of view of 0° , it can be understood that some amount of a coma aberration can remain. Table 29 shows comparisons of the power in the first group G1e and third group G3e in the above design example, and the examples 1 through 5 (the first group G1e and second group G2e in the example 5), and the auxiliary movable block (E7a-c in the examples 1 through 3, G4d in the example 4, and E5e in the example 5). The shaded portions show the maximum value of the absolute value of the auxiliary movable block and the decentering movable block ($|\Phi_s|_{\text{max}}$ and $|\Phi_d|_{\text{max}}$, respectively).

When comparing these, it can be understood that change in power of the auxiliary movable block does not include change in positive/negative, and the absolute value $|\Phi_s|_{\text{max}}$ of the maximum value of the power of the auxiliary movable block is smaller than the $|\Phi_d|_{\text{max}}$ of the decentering movable block in any embodiment. In other words, $|\Phi_s|_{\text{max}} < |\Phi_d|_{\text{max}}$ holds.

Further, when assuming that the absolute value of the value obtained by subtracting the minimum value from the maximum value of the power of the decentering auxiliary block straddle the entire zoom area is $\Delta|\Phi_s|$, $\Delta|\Phi_s| < 0.1$ holds, and when assuming that the absolute value of the value obtained by subtracting the minimum value from the maximum value of the power of the auxiliary movable block straddle the entire zoom area is $\Delta|\Phi_d|$, $\Delta|\Phi_d| > 0.5$ holds. When comparing

$\Delta|\Phi|$ between the $G1a-d$ and $G3a-d$, and assuming that the smaller one is determined as $\Delta|\Phi|_{\min}$, $\Delta|\Phi|_{\min}/\Delta|\Phi|>6$ holds, and also $\Delta|\Phi|_{\min}/\Delta|\Phi|>25$ holds except for the example 5. Accordingly, it can be understood from comparison between aberration charts that the auxiliary movable block does not affect upon the power fluctuation of the entire system, and relates to elimination of a on-axis coma aberration.

Note that with the above respective examples, three or more optical groups of which optical power is variable can be employed. Also, two or more optical groups having symmetry as to at least one surface, and including one or more optical elements capable of decentering can be employed.

Also, optical groups of which optical power is substantially unchangeable can be omitted, or two or more optical groups of which optical power is variable can be employed.

Next, an example of a digital still camera (imaging apparatus) to which a zoom optical system according to at least one exemplary embodiment can be applied as a photographic optical system will be described with reference to FIG. 37.

In FIG. 37, reference numeral 20 denotes a camera body, 21 denotes a photographic optical system made up of a zoom optical system according to at least one exemplary embodiment, 22 denotes a solid-state imaging device (photoelectric conversion element) such as a CCD sensor or CMOS sensor which receives a subject image using the photographic optical system 21, 23 denotes memory for recording the subject image photo-accepted by the imaging device 22, and 24 denotes a finder for observing the subject image displayed on an unshown display element.

The above display element is made up of a liquid crystal panel or other related or equivalent display apparatus as known by one of ordinary skill in the relevant art, on which the subject image formed on the imaging device 22 is displayed.

Thus, the present example realizes an imaging apparatus which is small and has high optical capabilities by applying the zoom optical system according to the present example to the imaging apparatus such as a digital still camera. It is needless to say that as for the zoom optical system to be applied to this imaging apparatus, the zoom optical system according to any one of not the above examples 1 through 5 but also later-described examples 6 and 7 can be employed.

COMPARATIVE EXAMPLE 1

Next, a comparative example 1 of at least one exemplary embodiment will be shown. The comparative example 1 has been designed with reference to Japanese Patent Laid-Open No. 1990-119103. FIG. 4 illustrates a lens cross-sectional view of the comparative example 1.

The zoom optical system according to the comparative example 1 is made up of two optical groups $G1f$ and $G2f$ each including two rotational asymmetric optical elements as illustrated in FIG. 4, which are referred to as the first group $G1f$, and the second group $G2f$ in order from the object side. This first group $G1f$ comprises optical elements $E1f$ and $E2f$, and the second group $G2f$ comprises optical elements $E3f$ and $E4f$. First, a paraxial calculation is performed by approximating these groups using one thin-thickness lens. Next, let us say that the power of the thin-thickness lens of the first group $G1f$ and the power of the thin-thickness lens of the second group $G2f$ are Φ_1 and Φ_2 respectively, and a principal interval and back focus are e and S_k respectively. Also, when assuming that the power of the entire system is Φ , and the focal distance is f , the following equation holds.

$$\phi = \frac{1}{f} = \phi_1 + \phi_2 - e\phi_1\phi_2 \quad [\text{Equation 6}]$$

Also, as for the back focus S_k , the following equation holds from the paraxial calculation.

$$S_k = \frac{1 - e\phi_1}{\phi} \quad [\text{Equation 7}]$$

Here, if the principal-point interval e and the back focus S_k are determined, the power Φ_1 and Φ_2 are represented as the function of the power Φ of the entire system from Equations 6 and 7. That is to say, the track of change in power in the first group $G1f$ and second group $G2f$ according to change in power of the entire system can be represented. Accordingly, when assuming that the principal-point interval $e=3$, and the back focus $S_k=15$, the power Φ_1 and Φ_2 are as follows:

$$\phi_1 = -5\phi + \frac{1}{3} \quad [\text{Equation 8}]$$

$$\phi_2 = \frac{1}{45\phi} - \frac{2}{5} \quad [\text{Equation 9}]$$

Upon the relationships of the power Φ_1 and Φ_2 as to the power Φ of the entire system being represented with a graph, the graph such as illustrated in FIG. 3 will be obtained. When viewing this, it can be understood that as the power Φ of the entire system increases, the power of the first group $G1f$ changes to negative from positive, and inversely, the power of the second group $G2f$ changes to positive from negative. Here, a rotational asymmetric curved surface is represented with Equation 10, and the relationships between the coefficient thereof "a" and the power results in Equation 11.

$$z = ay^3 + 3ax^2y \quad [\text{Equation 10}]$$

$$\Phi = 12a\delta(n-1) \quad [\text{Equation 11}]$$

Here, x , y , and z are the above axes. δ is the amount of shift toward the Y-axis direction from the Z axis of the two rotational asymmetric optical elements $E1f$ and $E2f$ ($E3f$ and $E4f$), and n is the refractive index of the lens. The coefficients a and n of the rotational asymmetric optical elements $E1f$ through $E4f$ are shown in Table 1, in which the amount of shift δ from the z axis is also shown in order of the telephoto end, middle zoom position, and wide-angle end. Also, Table 2 shows the surface-types of the respective surfaces $S0$ through $S9f$, and surface intervals.

In FIG. 4, the ray illuminated a reference plane $S0$ first illuminates the first group $G1f$. Let us say that the first group $G1f$ is made up of the two optical elements (lenses) $E1f$ and $E2f$, and the surface numbers are $S1f$ through $S4f$ in order. The optical elements $E1f$ and $E2f$ are decentered in the Y-axis direction, and the amount of decentering continuously varies. Also, the absolute value of the amount thereof is set so as to be equal with mutually positive/negative reverse. This causes the power Φ_1 of the first group $G1f$ to be changed from positive to negative at the time of zooming from the telephoto end to the wide-angle end (hereinafter, the zoom direction is the same) such as illustrated in FIG. 3. The ray emitted from the first group $G1f$ next passes through the diaphragm $S5f$, and illuminates the second group $G2f$. Let us say that the second

group $G2f$, as with the first group $G1f$, comprises two optical elements $E3f$ and $E4f$, and the surface numbers thereof are $S6f$ through $S9f$. The optical elements $E3f$ and $E4f$ are decentered in the Y-axis direction, and the amount of decentering continuously varies. Also, the absolute value of the amount thereof is set so as to be equal with mutually positive/negative reverse. This causes the power $\Phi2$ of the second group $G2f$ to be changed from negative to positive such as illustrated in FIG. 3.

The ray passed through these groups $G1f$ and $G2f$ forms an image without changing the image plane IP. However, when viewing the image plane, it can be understood that the image is formed, but an aberration greatly occurs. This occurs regardless of the paraxial allocations determined with Equations 8 and 9. For example, a coma aberration which occurs on the axis cannot be reduced with paraxial allocations alone anyway. As the above result, it can be understood that with the comparative example, an aberration cannot be completely corrected in the following points. This is caused by (a) an optical system having rotational asymmetric optical elements is asymmetric as to the optical axis, so shift is caused upon the upper line and underline, and consequently, a coma aberration occurs event on the marginal ray, and (b) curvature of field occurs.

Accordingly, with the examples of at least one exemplary embodiment, a zoom optical system capable of sufficiently eliminating an aberration is realized by moving the optical element (lens) in the direction different from the optical axis to perform zooming.

COMPARATIVE EXAMPLE 2

Next, a comparative example 2 of at least one exemplary embodiment will be described.

Generally, if eliminating a coma aberration on the marginal ray and increasing the power of a decentering movable block (also referred to as optical power which is the inverse number of a focal distance) can be achieved contemporaneously, a zoom optical system with high precision and a high zoom ratio can be achieved. However, generally, upon increasing the power of a decentering movable block, the tilt of each surface is also increased, and consequently, it becomes difficult to suppress on-axis coma aberration. Accordingly, with at least one exemplary embodiment, correction of power is performed by disposing a coaxial lens (coaxial optical element) within an optical path to suppress the power of the decentering movable block, thereby suppressing an on-axis coma aberration.

With the comparative example 2 of at least one exemplary embodiment, the optical element $E7a-d$ of the fourth group $G4a-d$ according to the examples 1 through 4 comprises one optical element made up of a rotational symmetric sphere, which is fixed at the time of zooming (not decentered in the optical-axis direction).

Next, description will be made regarding the optical capabilities of the comparative example 2 at this time.

FIG. 2 is a lens cross-sectional view at the middle zoom position of the comparative example 2. FIG. 5 is an optical-path diagram according to a comparative example 2 of at least one exemplary embodiment. With the comparative example 2, let us say that a CCD is employed as an imaging surface, and the size thereof is about $\frac{1}{4}$ inch (vertically 2.7 mm \times horizontally 3.6 mm). Also, the incident pupil diameter is assumed to be about 0.8. The number of optical elements (lenses) are seven in total, in order from the object side to the image side, the optical elements $E1g$, $E2g$, $E5g$, and $E6g$ have a rotational asymmetric shape, these optical elements are

decentered in the Y-axis direction, and the amount of decentering thereof continuously varies. Also, the absolute value of the amount thereof is set so as to be equal with mutually positive/negative reverse. The optical elements $E3g$, $E4g$, and $E7g$ have a rotational symmetric spherical shape, but in the event that an asymmetric aberration remains on the optical axis, optical elements having a rotational asymmetric shape can be disposed to reduce this. Also, the first group $G1g$ comprises the optical elements $E1g$ and $E2g$.

Similarly, the second group $G2g$ comprises the optical elements $E3g$ and $E4g$, and the third group $G3g$ comprises the optical elements $E5g$ and $E6g$. As for surface numbers, the reference plane serving as the origin of the absolute coordinates system is determined as a reference plane $S0$, the first surface of the optical element $E1g$ is determined as $S1g$, and in order, the corresponding surfaces are $S2g$, $S3g$, $S4g$ and so on, and following the surface $S6g$ (backward of the optical element $E3g$) a diaphragm SP is disposed, which is determined as $S7g$. The first surface of the optical element $E4g$ is determined as $S8g$, and the subsequent numbers are assigned in order, and the image plane IP is $S16g$. Hereinafter, let us say that the rotational asymmetric groups (group $G1g$ and group $G3g$), which are continuously decentered in the Y-axis direction, and the rotational symmetric groups (group $G2g$ and optical element $E7g$) are referred to as decentering movable blocks and auxiliary blocks. Disposing the decentering movable blocks $G1g$ and $G3g$ alone makes the power thereof too strong, and can make it difficult to perform correction of an aberration, and accordingly, the auxiliary blocks $G2g$ and $E7g$ are disposed.

The lens data of the comparative example 2 is shown in Table 3. The amount of shift from the Z axis (optical axis) of the respective optical elements (lenses) is such as shown in Table 4, and the values of the respective coefficients of the polynomial surfaces represented with Equation 1 is shown in Table 5. The optical-path diagram at this time is shown in FIG. 6 in order of the telephoto end, middle, and wide-angle end. The optical elements $E1g$ and $E2g$ are decentered in the Y-axis direction, and the absolute value of the amount thereof is so as to be equal with mutually positive/negative reverse, as shown in Table 4. This causes the power of the first group $G1g$ to be changed from positive to negative. The ray emitted from the first group $G1g$ passes through the optical element $E3g$, diaphragm $S7g$, and optical element $E4g$, and illuminates the optical elements $E5g$ and $E6g$. The optical elements $E5g$ and $E6g$ are decentered in the Y-axis direction, and the absolute value of the amount thereof is so as to be equal with mutually positive/negative reverse, as shown in Table 4. This causes the power of the $G3g$ to be changed from negative to positive. The ray passed through these decentering movable blocks $G1g$ and $G3g$ illuminates the next auxiliary block $E7g$. The auxiliary block $E7g$ compensates the power necessary for the decentering movable blocks $G1g$ and $G3g$. The ray passed through these optical elements forms an image without changing the image plane at the time of zooming.

Next, the aberration charts at the telephoto end, middle zoom position, and wide-angle end are shown in FIG. 7A through FIG. 7C, respectively. The horizontal axis represents the position of a ray on the pupil, and the vertical axis represents the shift from the chief ray on the image plane. The range of the vertical axis is about $\pm 20 \mu\text{m}$. The numbers within FIG. 7A through FIG. 7C are angle-of-view numbers, which on the image plane are such as illustrated in FIG. 8. The shapes of the optical elements are symmetric as to the X-axis direction, so only the positive case should be taken into consideration regarding the X direction. When viewing the ray at an angle of view of 0° , it can be understood that a coma

aberration can be reduced from the telephoto end to the wide-angle end. Also, FIG. 9 illustrates the distortion reactor lattices at a telephoto end T, middle zoom position M, and wide-angle end W. The lengthwise and crosswise size of the lattices is about ¼ inch (vertically 2.7 mm×horizontally 3.6 mm). When viewing this figure, it can be understood that distortion can be suppressed, but when viewing the ray at an angle of view of 0°, it can be understood that some amount of a coma aberration can remain.

This is because when moving the decentering movable blocks G1g and G3g, the angle as to the ray of the surface varies as the optical power of the entire system varies, so the aberration has not been completely corrected. Accordingly, in order to reduce this, at least one exemplary embodiment is directed to another correction block for correcting and/or reducing angle of a marginal ray to be changed along with the movement of the decentering movable blocks G1g and G3g.

That is to say, with at least one exemplary embodiment, a zoom optical system comprising multiple optical groups G1g and G3g made up of multiple optical elements each having a rotationally asymmetrical surface, and changing optical power by the optical elements E1g and E2g (E5g and E6g) within the respective groups G1g (G3g) of the multiple optical groups moving mutually in the direction different from the optical axis, which provides at least one optical element (auxiliary movable block) E7g having symmetry as to at least one surface for decentering to reduce the residual aberration of the zoom optical system. Further, the auxiliary movable block E7g is disposed to reduce the residual aberration, so the power and the amount of decentering are less than those in the decentering movable blocks G1g and G3g. Accordingly, the auxiliary movable block E7g has no change in positive/negative refracting power, and further, is arranged so as to satisfy the following conditions when assuming that the maximum value of the absolute value of the optical power in the decentering movable blocks G1g and G3g is $|\Phi d|_{\max}$, and the maximum value of the absolute value of the optical power in the auxiliary movable block is $|\Phi s|_{\max}$.

$$|\Phi s|_{\max} < |\Phi d|_{\max} \quad [\text{Equation 12}]$$

Further, when assuming that the absolute value of the value obtained by subtracting the minimum value from the maximum value of the power of the decentering auxiliary block straddle the entire zoom area is $\Delta|\Phi s|$, the following range can be satisfied.

$$\Delta|\Phi s| < 0.2$$

Or in at least one exemplary embodiment,

$$\Delta|\Phi s| < 0.1$$

Upon exceeding this range, the asymmetric aberration, i.e., the features of the decentering auxiliary block are reduced, and this block results in being classified as a decentering movable block.

Also, when assuming that the absolute value of the value obtained by subtracting the minimum value from the maximum value of the power in the auxiliary movable block straddle the entire zoom area is $\Delta|\Phi d|$, the following range can be satisfied.

$$\Delta|\Phi d| < 0.2$$

Or in at least one exemplary embodiment,

$$\Delta|\Phi d| < 0.5$$

Upon exceeding this range, the asymmetric aberration, i.e., the features of the decentering movable block are reduced, and this block results in being classified as a decentering auxiliary block.

Further, when assuming that $\Delta|\Phi d|$ is compared with the G1g and G3g, and the smaller one is taken as $\Delta|\Phi d|_{\min}$, the following range can be satisfied.

$$\Delta|\Phi d|_{\min}/\Delta|\Phi d| > 6$$

or in at least one exemplary embodiment,

$$\Delta|\Phi d|_{\min}/\Delta|\Phi d| > 25$$

This is caused by the same reason as the above. Also, in the event of the auxiliary movable block E7g performing aid with shift, when assuming that the maximum value of the absolute value of the amount of shift (amount of movement) thereof is $|Ds|_{\max}$, and the maximum value of the absolute value of the amount of shift of the decentering movable block is $|Dd|_{\max}$, the following condition can be satisfied.

$$|Ds|_{\max} < |Dd|_{\max} \quad [\text{Equation 13}]$$

Further, it has been known that if the Petzval is great, the curvature of field also becomes great, and if the Petzval is small, the curvature of field also becomes small. Accordingly, at least one exemplary embodiment suppresses the curvature of field to small by reducing the Petzval. When the power at lenses E_i ($i=1$ through n) is ΦE_i , and the refractive index of a material is $n E_i$, the Petzval is obtained with the following equation.

$$P E_i = \Phi E_i / n E_i \quad [\text{Equation 14}]$$

With a normal zoom optical system using a coaxial optical element, this value can be constant. However, with an optical system such as in at least one exemplary embodiment where an optical element is continuously decentered, and power varies, this value is not constant. Also, the refractive index of a nitrifying material is around 1.45 through 1.9, so change thereof is small, and accordingly, change in the Petzval can be referred to change in power. Accordingly, in order to suppress this Petzval, when assuming that the maximum value of the absolute value of the power in the first group G1g and the third group G3g is $|\Phi|_{\max}$, and the power in total of the first group G1g and the third group G3g is $\Phi 13$, the range of change in power is determined so as to satisfy the following equation.

$$-|\Phi|_{\max} \leq \Phi 13 \leq |\Phi|_{\max} \quad [\text{Equation 15}]$$

Next, description will be made from the perspective of a principal-point position.

In order to perform zooming while maintaining compactness, it can be necessary in some circumstances to move a principal-point position greatly from a certain position of each group. With the conventional optical system in which a tertiary curve is simply given to a single surface, a principal-point position exists only upon the surface with the tertiary coefficient thereof, and does not fluctuate greatly. As for a method for fluctuating a principal-point position greatly, for example, an arrangement can be made where curvature is given to a single surface, and the shape of a rotational asymmetric lens is changed into a meniscus shape. The lens which can have a meniscus shape, which is different from a positive lens and a negative lens, is a lens capable of disposing a principal point outside of the lens, and employing this shape for the rotational asymmetric lens enables a principal point to be greatly fluctuated outside of the group. However, when making the rotational asymmetric lens into a meniscus shape, shifting occurs upon the upper line and underline of the marginal ray at the telephoto end or the wide-angle end (when the ray passes through the end of the lens). Accordingly, it is useful for another lens to correct this. With a method for solving this, the lens for correction is changed into a meniscus shape having a reverse tilt to cancel out the shift of the upper

line and underline. A coefficient is determined by focusing attention on this at the time of introducing a higher order coefficient than a tertiary coefficient. Also, a meniscus shape can be shaped in the direction for reducing the mutual distance. This is because reducing the distance between the lenses enables a on-axis coma aberration to be reduced while suppressing this to the minimum upon each surface. Thus, on-axis coma aberration can be reduced.

With the comparative example 2, elimination of a on-axis coma aberration is performed by obtaining Equations 6 through 9, and obtaining change in power of each group as to the focal distance as illustrated in FIG. 3. Upon increasing the power of each group, an aberration occurs, so in order to increase a variable power ratio without increasing the power of each group, it can be necessary in some circumstances to reduce the tilt of change in power of each group as to the power of the entire system shown in FIG. 3. Thus, the range of change in power of the entire system can be expanded while maintaining the range of change in power of each group in a steady manner. Here, in order to realize the above, paraxial allocations for performing thin-thickness approximation will be reconsidered. The following equations can be derived from Equations 6 and 7 with the back focus S_k and the principal-point interval e serving as variables. However, the respective paraxial values of the focal distance, forward principal-point position, and backward principal-point position can be defined as values derived from Optics Vol. 29, No. 3 (2000). Deriving these values is performed by calculating 4×4 determinants based on the curvature of each surface and each surface interval.

$$\begin{aligned}\phi_1 &= \frac{-S_k}{e} \phi + \frac{1}{e} \\ \phi_2 &= \frac{-1}{eS_k} \phi + \frac{e+S_k}{eS_k}\end{aligned}\quad [\text{Equations 16 and 17}]$$

It can be understood from the above equations that the tilts of the two can be determined by the principal-point interval e and the back focus S_k . Consequently, the following equations are derived by differentiating the two with the power Φ .

$$\begin{aligned}\frac{d\phi_1}{d\phi} &= \frac{-S_k}{e} \\ \frac{d\phi_2}{d\phi} &= \frac{1}{eS_k\phi^2}\end{aligned}\quad [\text{Equations 18 and 19}]$$

The power Φ_1 varies in a linear curve, so the tilt thereof is constant. On the other hand, the tilt of the power Φ_1 varies depending on the power Φ of the entire system. Also, if the principal-point interval e increases, the tilts of the power Φ_1 and Φ_2 decrease to realize large magnification, but if the back focus S_k increases, the power Φ_1 increases, on the other hand the power Φ_2 decreases, and consequently, the direction of change in the back focus S_k as to large magnification cannot be determined.

Here, the tilts of the power Φ_1 and Φ_2 as to change in the power Φ of the entire system are compared. At a point of

$$\phi = \frac{1}{e+S_k} \quad [\text{Equation 20}]$$

in which $\Phi_2=0$ holds,

$$\left| \frac{d\phi_1}{d\phi} \right| = \left| \frac{d\phi_2}{d\phi} \right| = \frac{(e+S_k)^2}{eS_k} \quad [\text{Equation 21}]$$

holds, in the range of

$$\phi < \frac{1}{e+S_k} \quad [\text{Equation 22}]$$

$$\left| \frac{d\phi_1}{d\phi} \right| < \left| \frac{d\phi_2}{d\phi} \right| \quad [\text{Equation 23}]$$

holds, in the range of

$$\phi > \frac{1}{e+S_k} \quad [\text{Equation 24}]$$

$$\left| \frac{d\phi_1}{d\phi} \right| > \left| \frac{d\phi_2}{d\phi} \right| \quad [\text{Equation 25}]$$

holds.

A table in which these were compared is shown in Table 6. It can be understood from this table that in a wide range

$$\left| \frac{d\phi_1}{d\phi} \right| < \left| \frac{d\phi_2}{d\phi} \right| \quad [\text{Equation 26}]$$

holds. Accordingly, large magnification can be achieved if the tilt of the power Φ_2 of which tilt is great in a wide range can be reduced. Accordingly, it can be understood that upon increasing both the principal-point interval e and the back focus S_k , the tilt can be reduced when focusing attention on the tilt of the power Φ_2 within Equation 20.

$$\frac{d\phi_2}{d\phi} \quad [\text{Equation 27}]$$

Also, the distance (the entire length in thin-thickness approximation) from the principal-point position of the first group which is the sum of the principal-point interval e and the back focus S_k is constant, the tilt of the power Φ_2 at the time of $e=S_k$ becomes minimal. Thus, the zoom ratio becomes maximal.

With at least one exemplary embodiment, the above principal-point interval e is substituted with the distance between the H1' and H2 as thickness increases from approximation at thin thickness, and thin principal-point interval e is shifted. At least one exemplary embodiment takes this point into consideration, and makes the following arrangement.

$$0.7 < \frac{e}{e'} < 1.4 \quad [\text{Equation 28}]$$

However, when assuming that the distance between the object point and the H1 is e_o , the distance between the H1' and

H2 is e , and the distance between the H2' and the image point is e_i , e' is a smaller distance between the e_o and e_i . Also, if the back focus Sk is constant, and a principal point can be moved, the tilts of the power Φ_1 and Φ_2 can be reduced to realize large magnification by increasing the principal-point interval e . Accordingly, employing an optical element where a principal-point interval is increased by the shape of the surface of an optical element making up a group as a rotational asymmetric lens enables the principal-point interval to be increased while keeping the surface interval as is, and further, enables large magnification to be achieved.

If a curved surface with a single surface alone such as described with Equation 10 as described above is employed, both forward and backward principal-points simply move upon the same surface. Simply employing this optical element cannot move a principal-point position greatly. Accordingly, the zoom ratio cannot be increased as well. If a principal-point interval can be increased by moving this principal point forward or backward of the optical element, large magnification can be achieved without increasing the surface interval. Here, consideration is made regarding the principal-point positions of three lenses of a positive lens of which both lens surfaces have a convex shape (biconvex lens) as a coaxial lens, a negative lens of which both lens surfaces have a concave shape (biconcave lens), and a meniscus-shaped lens. The biconvex lens and the biconcave lens both have a principal point within the lens, so it cannot be expected to move a principal point outside of the lens greatly. On the other hand, the meniscus-shaped lens, which is different from the biconvex lens and the biconcave lens, is a lens of which a principal point can be moved outside of the lens. Accordingly, employing this shape even for a rotational asymmetric lens enables a principal point to be moved outside of the lens greatly. If this is employed for a rotational asymmetric lens such as the zoom optical system according to at least one exemplary embodiment, a principal-point interval can be increased to expect large magnification.

If a principal-point interval is set small on the telephoto side, and is set large on the wide-angle side, further large magnification can be realized. It can be understood from Equation 6. When assuming that the power of the entire system on the wide-angle side is Φ_w , the power of the first group and the second group at that time are Φ_{1w} and Φ_{2w} respectively, and the principal-point interval thereof is e_w , and similarly, the power of the entire system on the telephoto side is Φ_t , the power of the first group and the second group are Φ_{1t} and Φ_{2t} respectively, and the principal-point interval thereof is e_t , Equation 6 is modified as follows.

$$\Phi_w = \Phi_{1w} + \Phi_{2w} - e_w \Phi_{1w} \Phi_{2w} \quad [\text{Equation 29}]$$

$$\Phi_t = \Phi_{1t} + \Phi_{2t} - e_t \Phi_{1t} \Phi_{2t} \quad (\text{however, } \Phi_w > \Phi_t) \quad [\text{Equation 30}]$$

Here, the power Φ_1 and power Φ_2 have a different sign, so when assuming that

$$\Phi_{1w} + \Phi_{2w} > 0, \Phi_{1t} + \Phi_{2t} > 0, \text{ and} \quad [\text{Equation 31}]$$

$$e_w > e_t, \quad [\text{Equation 32}]$$

it can be understood that the difference between the power Φ_w and power Φ_t becomes great, and large magnification is realized.

EXAMPLE 6

FIG. 38 is a lens cross-sectional view according to an example 6 of at least one exemplary embodiment.

In FIG. 38, T, M, and W are lens cross-sectional views at the telephoto end (the zoom position where the power of the entire system is the minimum), at a middle zoom position, and at the wide-angle end (the zoom position where the power of the entire system is the maximum), respectively.

FIG. 39 is a lens cross-sectional view for selecting the middle zoom position of the example 6 in FIG. 38 (M in FIG. 38) as an example and for describing respective factors.

A zoom optical system according to the example 6 is a photography lens system employed for an imaging apparatus, and the left hand is the object side, and the right hand is the image side in the lens cross-sectional view.

Note that the zoom optical system according to the example 6 can be employed as a projector, and in this case, the left hand is a screen, and the right hand is a projection surface.

In FIG. 38 and FIG. 39, G1h and G3h are optical groups of which optical power is variable. G2h is an optical group in which optical power is substantially unchangeable.

G4h is an optical group S having symmetry as to at least one surface, and including one or more optical elements Ls capable of moving in the optical-axis direction.

Zooming is performed while maintaining the image plane IP in a steady manner by changing the power in the two optical groups G1h and G3h each of which optical power is variable.

The two optical groups G1h and G3h each of which optical power is variable each include a rotationally asymmetrical surface, move in the direction different from the optical axis, and include two optical elements E1h and E2h which change the power within the optical group G1h, and two optical elements E5h and E6h which change the power within the optical group G3h, respectively.

Note that the term "optical power" refers to the power of a surface positioned on the optical axis, and when the surface on the optical axis varies by the optical element having a rotationally asymmetrical surface being decentered, optical power is also changed in response to that change.

With the example 6 of at least one exemplary embodiment, seven optical elements (lenses) are employed in total. In order from the object side, the optical elements E1h, E2h, E5h, and E6h have a rotational asymmetric shape, these optical elements are decentered in the Y-axis direction, and the amount of decentering continuously varies. Also, the absolute value of the amount thereof is set so as to be equal with mutually positive/negative reverse. The optical elements E3h and E4h have a rotational symmetric spherical surface. In the event that an asymmetric aberration remains on the optical axis, the optical elements E3h and E4h can have a rotational asymmetric shape to reduce this. An optical element E7h has a rotational asymmetric shape which has symmetry as to at least one surface (one surface is taken as a center of symmetry). In other words, the optical element E7h can have a rotational asymmetric shape symmetric as to multiple surfaces (e.g., toric surfaces), but in at least one exemplary embodiment, which is an optical element which can have a rotational asymmetric shaped surface symmetric as to only one surface (only one surface serving as a symmetric center exists). The same is true of E1h, E2h, E3h, E4h, E5h, and E6h. This is substantially similar in the following respective examples.

This reduces the on-axis coma aberration which may not have been completely reduced in the optical elements E1h through E6h by moving the on-axis coma aberration on the optical axis. Also, the first group G1h comprises the optical elements E1h and E2h.

Similarly, the second group G2h comprises the optical elements E3h and E4h, and the third group G3h comprises the optical elements E5h and E6h. The fourth group G4h com-

prises the optical element E7h. As for surface numbers, the reference plane serving as the origin of the absolute coordinates system is determined as a surface S0, the first surface of the optical element E1h is determined as S1h, and in order, the corresponding surfaces are surfaces S2h, S3h, S4h, and so on, and following the surface S6h (backward of the optical element E3h) a diaphragm S7h (SP) is disposed.

The first surface of the optical element E4h is determined as S8h, and the subsequent numbers are assigned in order, and the image plane IP is S16h. Hereinafter, decentering continues in the Y-axis direction, and let us say that the rotational asymmetric groups (G1h and G3h), which contribute to change in power, the rotational symmetric group (G2h), and the fourth group G4h made up of the optical element (E7h) configured to suppress the above residual aberration by decentering are referred to as decentering movable blocks G1h and G3h, auxiliary block G2h, and auxiliary movable block G4h, respectively. Disposing the decentering movable blocks G1h and G3h alone makes the power thereof too strong, and can make it difficult to perform correction of aberrations, and accordingly, the auxiliary block G2h is disposed.

The lens data of the example 6 is shown in Table 7. The amount of shift from the Z axis of the respective optical elements is shown in Table 8.

The amount of movement in the optical-axis direction accompanied with zooming of the optical element E7h is shown in Table 9. In Table 9, change in intervals before and after the optical element E7h is shown with S13h and S14h.

The values of the respective coefficients of the polynomial surfaces represented with Equation 1 are shown in Table 10. FIG. 38 is a lens cross-sectional view at the telephoto end (T), middle zoom position (M), and wide-angle end (W) shown in Table 8. The optical elements E1h and E2h are decentered in the Y-axis direction, and the absolute value of the amount thereof is so as to be equal with mutually positive/negative reverse, as shown in Table 8. Thus, the power of the first group G1h is changed from positive to negative between the telephoto end and the wide-angle end. The ray emitted from the first group G1h passes through the optical element E3h, diaphragm SP, and optical element E4h, and illuminates the optical elements E5h and E6h. The optical elements E5h and E6h are decentered in the Y-axis direction, and the absolute value of the amount thereof is so as to be equal with mutually positive/negative reverse, as shown in Table 8. Thus, the power of the third group G3h is changed from negative to positive between the telephoto end and the wide-angle end. The ray passed through these decentering movable blocks G1h and G3h illuminates the next auxiliary movable block G4h. The auxiliary movable block G4h compensates the power necessary for the decentering movable blocks G1h and G3h. The ray passed through these optical elements forms an image without changing the image plane IP.

With the present example, one or more optical elements capable of moving in the optical-axis direction at the time of zooming include an optical element having positive refracting power.

With the present example, when assuming that the amount of movement in the entire zoom range of one optical element (the optical element E7h having positive refracting power in the example 6) of one or more optical elements capable of moving in the optical-axis direction at the time of zooming is

d, and the entire length of the entire system is T, the following condition

$$d/T < 0.6$$

can be satisfied.

Thus, an aberration fluctuation caused by zooming is appropriately corrected while restricting the entire length from being enlarged.

The entire length (the distance between the first surface and the image plane) T of the example 6 is 10 mm, and the movement amount d of the optical element (auxiliary movable block) E7 is 1.34475 mm, and consequently,

$$d/T = 1.3$$

is obtained.

Next, the aberration charts at the telephoto end, middle zoom position, and wide-angle end are shown in FIG. 40A through FIG. 40C, respectively. The horizontal axis represents the position of a ray on the pupil, and the vertical axis represents the shift from the chief ray on the image plane. The range of the vertical axis is about $\pm 20 \mu\text{m}$. The numbers within FIG. 40A through FIG. 40C are angle-of-view numbers, which on the image plane are such as illustrated in FIG. 8. The shapes of the optical elements are symmetric as to the X axis, so only the positive case should be taken into consideration regarding the X direction. When viewing the ray at an angle of view of 0° , it can be understood that a coma aberration can be reduced from the telephoto end to the wide-angle end.

Also, FIG. 41 illustrates the distortion reactor lattices at a telephoto end T, middle zoom position M, and wide-angle end W. The lengthwise and crosswise size of the lattices is about $\frac{1}{4}$ inch (vertically 2.7 mm \times horizontally 3.6 mm). When viewing this figure, it can be understood that distortion can be suppressed, but when viewing the ray at an angle of view of 0° , it can be understood that some amount of the coma aberration can remain.

FIG. 42 is a chart plotting change in power $\Phi 1$ and $\Phi 3$ of the first group G1h and the third group G3 caused by zooming, and the sum thereof $\Phi 13 (\Phi 1 + \Phi 3)$ as to the power of the entire system.

At this time, when assuming that the maximum value of the absolute value of the power in the first group G1 and the third group G3h is $|\Phi|_{\text{max}}$, and the power of the sum of the first group G1h and the third group G3h is $\Phi 13$,

$$-|\Phi|_{\text{max}} \leq \Phi 13 \leq |\Phi|_{\text{max}}$$

can be satisfied.

Satisfying the conditional expression (5) reduces the Petzval sum and the image plane distortion.

FIG. 43 illustrates change in the principal-point positions before and after the first group G1h and the third group G3h (H1 is the forward principal-point position of the first group G1h, H1' is the backward principal-point position of the first group G1h, H2 is the forward principal-point position of the third group G3h, and H2' is the backward principal-point position of the third group G3h). The first group G1h is made up of meniscus-shaped optical elements, so the principal-point position thereof greatly moves. Also, when comparing the change thereof with FIG. 42, it can be understood that the power of the first group G1h moves in the object direction in the positive range as the power of the entire system increases, and expands the interval of the H1 and H2.

Also, it can be understood that the power of the first group G1h moves in the object direction even in the negative range as the power of the entire system increases, and expands the

interval of the H1 and H2. Also, when assuming that the forward principal-point position and the backward principal-point position of the first group G1h are H1 and H1' respectively, the forward principal-point position and the backward principal-point position of the third group G3h are H2 and H2' respectively, the distance between the object point and the H1 is eo, the distance between the H1' and H2 is e, the distance between the H2' and the image point is ei, and smaller distance between the eo and ei is e', the relationships between e and e' and the relationships of e/e' are shown in Table 11. When viewing this, it can be understood that the e and e' are essentially the same at any zoom position.

Particularly,

$$0.7 < e/e' < 1.4$$

can be satisfied.

Further, as illustrated in FIG. 43, when assuming that the backward principal-point position of the first group G1h is H1', the forward principal-point position of the third group G3h is H2, the distance between the H1' and H2 in a case in which the power of the entire system is the smallest in the positive range of the power of the first group G1h at zooming (telephoto end) is et1, the distance between the H1' and H2 in a case in which the power of the entire system is the greatest (wide-angle end) is ew1, the distance between the H1' and H2 in a case in which the power of the entire system is the smallest in the negative range of the power of the first group G1h at zooming is et2, and the distance between the H1' and H2 in a case in which the power of the entire system is the greatest is ew2, it can be understood from FIG. 43 that

$$et1 < ew1, et2 < ew2$$

can be satisfied.

Also, with the present example, when assuming that within the entire zoom range, the maximum value of the values obtained by dividing the maximum value of the absolute value of each image-forming magnification of the multiple optical elements E1h, E2h, E5h, and E6h of the multiple optical groups G1h and G3h of which optical power is variable by the minimum value is Bd max, and the maximum value of the values obtained by dividing the minimum value of the absolute value of each image-forming magnification of the one or more optical elements (the optical element E7h alone in the present example) E7h capable of moving in the optical-axis direction by the minimum value is Bs min, the following condition

$$Bs \text{ min} < Bd \text{ max}$$

can be satisfied.

Also, when assuming that the amount of change in the optical-axis direction caused by zooming from the telephoto end to the wide-angle end of the forward principal-point position H_A of the optical group G1h of the multiple optical groups G1h and G3h of which optical power is variable is ΔH_A, the amount of change in the optical-axis direction caused by zooming from the telephoto end to the wide-angle end of the forward principal-point position H_B of the optical group G3h closer to the image side than the optical group G1h is ΔH_B, greater amount of change between the amount of change ΔH_A and the amount of change ΔH_B is ΔH_A max, and the amount of change of the forward principal-point position of the one or more optical elements E7h is ΔH_S, the following condition

$$\Delta H_S < \Delta H_A \text{ max}$$

can be satisfied.

Specifically, as illustrated in FIG. 43, the ΔH_A max is 2.025 from change in the principal-point interval of the first group G1h, and ΔH_S is 1.489 by calculating the amount of movement of the S13 from Table 9. That is to say, it can be understood that ΔH_A max < ΔH_S is satisfied.

Next, Table 12 shows change in image-forming magnification at the telephoto end, middle, and wide-angle end for each of the optical elements E1h, E2h, E5h, E6h, and E7h.

The optical elements E1h, E2h, E5h, and E6h are optical elements Ld which are decentering movable, and the optical element E7h is an optical element Ls which moves in the optical-axis direction. The maximum value Bd max is 263.97 at the optical element E5h, and on the other hand, the minimum value Bs min is 1.0193 at the optical element E7h. That is to say, it can be understood that Bd max > Bs min holds.

Note that with the present example and the following examples, focusing can be performed by moving the entire system, or by moving one optical group in the vertical direction as to the optical axis.

EXAMPLE 7

FIG. 44 is a lens cross-sectional view at the telephoto end (T), middle zoom position (M), and wide-angle end (W) according to the example 7 of at least one exemplary embodiment.

FIG. 45 is a lens cross-sectional view for selecting the middle zoom position of the example 7 in FIG. 44 as an example and for describing respective factors.

With the example 7, six optical elements are employed in total. In order from the object side (forward) to the image side, optical elements E1i, E2i, E3i, and E4i have a rotational asymmetric shape, these optical elements are decentered in the Y-axis direction, and the amount of decentering continuously varies.

Also, the absolute value of the amount thereof is set so as to be equal with mutually positive/negative reverse. The optical elements E5i and E6i have a rotational symmetric aspheric surface. In the event that an asymmetric aberration remains on the optical axis, the optical elements E5i and E6i can have a rotational asymmetric shape to reduce this.

The optical elements E5i and E6i perform aid of movement power integrally in the optical-axis direction at the time of zooming. Also, a first group G1i comprises the optical elements E1i and E2i, and similarly, a second group G2i comprises the optical elements E3i and E4i.

As for surface numbers, the reference plane serving as the origin of the absolute coordinates system is determined as a surface S0, the first surface of the optical element E1i is determined as S1i, and in order, the corresponding surfaces are surfaces S2i, S3i, and S4i, and following the surface S4i (backward of the optical element E2i) a diaphragm S5i (SP) is disposed. The first surface of the optical element E3i is determined as S6i, and the subsequent numbers are assigned in order, and the image plane is S17i.

Hereinafter, let us say that the rotational asymmetric groups (optical elements E1i through E4i), which are continuously decentered in the Y-axis direction, and the rotational symmetric groups (optical elements E5i and E6i) are referred to as decentering movable blocks G1i and G2i, and an auxiliary movable block G3i.

Disposing the decentering movable blocks G1i and G2i alone makes the power thereof too strong, and can make it difficult to perform correction of an aberration, and accordingly, the auxiliary movable block is disposed. Also, both surfaces of the optical elements E1i through E4i having a rotational asymmetric shape have a rotationally asymmetrical

surface shape. A flat-plate glass block Ga disposed immediately prior to a CCD surface, a CMOS surface, or other related or equivalent image pickup apparatus as known by one of ordinary skill in the relevant art is an infrared cut filter and the cover glass of a CCD (e.g., or CMOS).

The lens data of the example 7 is shown in Table 13. The amount of shift from the Z axis of each of the optical elements E1*i* through E4*i* is shown in Table 14, and the amount of movement in the optical-axis direction of the optical elements E5*i* and E6*i* shown in the surface S9*i* and surface S13*i* is shown in Table 15. Further, the coefficients of the rotational symmetric aspheric shapes represented with the following equation are shown in Table 16, and the coefficients represented with Equation 33 are shown in Table 17.

$$Z = \frac{ch^2}{1 + \sqrt{1 - c^2h^2}} + Ah^4 + Bh^6 \quad [\text{Equation 33}]$$

Here, Z is the displacement in the optical-axis direction at a position of a height h from the optical axis on the basis of a surface peak.

However, with the above equation, $h^2 = X^2 + Y^2$ can be satisfied, c is a curvature radius, and A and B are coefficients.

It can be understood that the entire length is 6.9 mm, so when calculating a ratio between this and 0.06062 mm, 0.00879 is obtained, and this is included in the range of Equation 23.

In FIG. 44, the ray illuminated a reference plane S0 first illuminates the first group G1*i*. The first group G1*i* is made up of the two optical elements E1*i* and E2*i*, and the surface numbers are S1*i* through S4*i*. The optical elements E1*i* and E2*i* are decentered in the Y-axis direction, and the absolute value of the amount thereof is so as to be equal with mutually positive/negative reverse, as shown in Table 4. Thus, the power of the first group G1*i* is changed from positive to negative at the time of zooming from the telephoto end to the wide-angle end.

The ray emitted from the first group G1*i* next passes through the diaphragm S5*i*, and illuminates the second group G2*i*. The second group G2*i*, as with the first group G1*i*, comprises two optical elements E3*i* and E4*i*, and the surface numbers thereof are S6*i* through S9*i*. The optical elements E3*i* and E4*i* are decentered in the Y-axis direction, and the absolute value of the amount thereof is so as to be equal with mutually positive/negative reverse, as shown in Table 4.

Thus, the power of the second group G2*i* is changed from negative to positive at the time of zooming from the telephoto end to the wide-angle end. The ray passed through these decentering movable blocks G1*i* and G2*i* illuminates the next auxiliary movable block G3*i*. The auxiliary movable block G3*i* compensates the power necessary for the decentering movable blocks G1*i* and G2*i*. The auxiliary movable block G3*i* comprises the optical elements E5*i* and E6*i* made up of surfaces S10*i* through S13*i* which are rotational symmetric aspheric surfaces. The ray passed through these optical elements passes through an infrared cut filter and the cover glass of a CCD (e.g., or CMOS), and forms an image without changing the image plane.

Next, the aberration charts at the telephoto end, middle zoom position, and wide-angle end are shown in FIG. 46A through FIG. 46C, respectively. The horizontal axis represents the position of a ray on the pupil, and the vertical axis represents the shift from the chief ray on the image plane. The range of the vertical axis is about $\pm 20 \mu\text{m}$. The numbers within FIG. 46A through FIG. 46C are angle-of-view num-

bers, which on the image plane are such as illustrated in FIG. 8. The shapes of the optical elements are symmetric as to the X axis, so only the case of the positive X direction should be taken into consideration.

When viewing the ray at an angle of view of 0° , it can be understood that a coma aberration can be reduced from the telephoto end to the wide-angle end. Also, FIG. 47 illustrates distortion lattices. The lengthwise and crosswise size of the lattices is about $\frac{1}{4}$ inch (vertically 2.7 mm \times horizontally 3.6 mm). When viewing this, it can be understood that distortion is appropriately suppressed.

FIG. 48 is a chart plotting change in power $\Phi 1$ and $\Phi 2$ of the first group G1*i* and second group G2*i*, and the sum thereof $\Phi 1 + \Phi 2$ as to the power of the entire system.

When assuming that the maximum value of the absolute value of the power in the first group G1*i* and second group G2*i* is $|\Phi|_{\text{max}}$, the total value of the power in the first group G1*i* and second group G2*i* at an arbitrary zoom position is $\Phi 2$, a greater value between the absolute value of the power of the first group G1*i* and the absolute value of the power of the second group G2*i* at the wide-angle end is $|\Phi_{\text{gw}}|_{\text{max}}$, and a smaller value between the absolute value of the power of the first group G1*i* and the absolute value of the power of the second group G2*i* at the telephoto end is $|\Phi_{\text{gt}}|_{\text{min}}$,

$$|\Phi_{\text{gw}}|_{\text{max}} < |\Phi_{\text{gt}}|_{\text{min}}$$

can be satisfied.

Also,

$$-|\Phi|_{\text{max}} \leq \Phi 1 2 \leq |\Phi|_{\text{max}}$$

can be satisfied.

Also, the intersection of change in power $\Phi 1$ and $\Phi 2$ of the first group G1*i* and second group G2*i* is disposed closer to the side having great optical power (wide-angle end) than the zoom middle position. Thus, zooming is effectively performed.

Next, Table 18 shows change in the image-forming magnification of each of the optical elements E1*i* through E6 at the telephoto end, middle, and wide-angle end. The optical elements E1*i*, E2*i*, E3*i*, and E4*i* are optical elements Ld which are decentering movable, and the optical elements E5*i* and E6*i* are optical elements Ls which move in the optical-axis direction. The maximum value Bd_{max} is 10.384 at the optical element E3*i*, and on the other hand, the minimum value Bs_{min} is 1.00056 at the optical element E6*i*. That is to say, it can be understood that $Bd_{\text{max}} > Bs_{\text{min}}$ holds.

As described above, according to each of the examples, zooming is performed employing a block including an optical element which moves in the optical-axis direction as well as the decentering movable blocks, thereby performing zooming while appropriately eliminating an aberration, and also obtaining a compact zoom optical system.

Note that with the above respective examples, three or more optical groups of which optical power is variable can be employed. Also, two or more optical groups having symmetry as to at least one surface, and including one or more optical elements capable of moving in the optical-axis direction can be employed. Also, an optical group of which optical power is substantially unchangeable can be omitted, or two or more optical groups of which optical power is substantially unchangeable can be employed.

The above examples 6 and 7 achieve a zoom optical system capable of sufficiently eliminating an aberration even at the time of zooming by adding an optical element capable of moving in the optical-axis direction to solve the problems (a) and (b) in the above comparative example 1.

Also, with the examples 6 and 7, correction of power can be performed by disposing a coaxial lens (coaxial optical element) within an optical path to suppress the power of the decentering movable block, thereby suppressing an on-axis coma aberration.

Also, comparison will be made between the examples 6 and 7 and the comparative example 2. With the above equations, it is a condition for large magnification that the e and e' are essentially equal. Further, when assuming that the entire length is 1, it can be understood that the e or e' is greater than 0.4167 but less than 0.588 from

$$e+e'=1$$

$$0.7 < e/e' < 1.4 \quad \text{[Equation 34]}$$

If we consider inserting an auxiliary movable block therebetween such as in at least one exemplary embodiment, it can be understood that the maximum value of the amount of movement in the optical-axis direction of the auxiliary movable block can be less than 0.588. Further, at least one exemplary embodiment takes the shift of a principal point into consideration, and sets the amount of movement of the auxiliary movable block to the following range.

$$d/T < 0.6 \quad \text{[Equation 35]}$$

Further, setting the auxiliary movable block to positive power enables the power of the decentering movable block to be loosed.

Also, the auxiliary movable block is provided for correction of the decentering movable block, so is a block of which change in magnification is loosed as compared with the decentering movable block. That is to say, satisfying the following range enables the power of the decentering movable block to be loosed, and consequently, an aberration is reduced as a whole.

$$B_d \max > B_s \min \quad \text{[Equation 36]}$$

Also, for the same reason as the above, it can be necessary in some circumstances to compare change in the principal-point position of the decentering movable block with that of the auxiliary movable block, and enlarge the former. Accordingly, an aberration is suppressed by satisfying the following range.

$$\Delta H_d \max > \Delta H_s \quad \text{[Equation 37]}$$

As described above, an asymmetric aberration such as a on-axis coma aberration is suppressed by moving the auxiliary movable block.

Also, the power of the decentering movable block can be set as follows.

When assuming that a greater absolute value between the absolute value of the power of the first group G1 and that of the third group G3 at the wide-angle end is $|\Phi_{gw}|_{\max}$, a smaller absolute value between the power of the respective groups at the telephoto end is $|\Phi_{gt}|_{\min}$, the power at the wide-angle end is earned by satisfying Equation 38.

$$|\Phi_{gw}|_{\max} < |\Phi_{gt}|_{\min} \quad \text{[Equation 38]}$$

Further, it has been known that if the Petzval is great, the curvature of field also becomes great, and if the Petzval is small, the curvature of field also becomes small.

Accordingly, at least one exemplary embodiment suppresses the curvature of field to small by reducing the Petzval. When the power at lenses E_i ($i=1$ through n) is ΦE_i , and the refractive index of a material is $n E_i$, the Petzval is obtained with the following equation.

$$P E_i = \Phi E_i / n E_i \quad \text{[Equation 39]}$$

With a normal zoom optical system using a coaxial optical element, this value can be constant. However, this value is not constant with an optical system such as in at least one exemplary embodiment where an optical element is continuously decentered, and power varies. Also, the refractive index of a nitrifying material is around 1.45 through 1.9, so change thereof is small, and accordingly, change in the Petzval can be referred to change in power.

Accordingly, in order to suppress this Petzval, when assuming that the maximum value of the absolute value of the power in the A group and the B group is $|\Phi|_{\max}$, and the power in total of the A group and the third group G3a-i is Φ_{13} , the range of change in power is determined so as to satisfy the following equation.

$$-|\Phi|_{\max} \leq \Phi_{13} \leq |\Phi|_{\max} \quad \text{[Equation 40]}$$

Next, description will be made from the perspective of a principal-point position.

In order to perform zooming while maintaining compactness, it can be necessary in some circumstances to move a principal-point position greatly from a certain position of each group. With the conventional optical system in which a tertiary curve is simply given to a single surface, a principal-point position exists only upon the surface with the tertiary coefficient thereof, and does not fluctuate greatly.

As for a method for fluctuating a principal-point position greatly, for example, an arrangement can be made where curvature is given to a single surface, and the shape of a rotational asymmetric lens is changed into a meniscus shape. The lens which can have a meniscus shape, which is different from a positive lens and a negative lens, is a lens capable of disposing a principal point outside of the lens, and employing this shape for the rotational asymmetric lens enables a principal point to be greatly fluctuated outside of the group. However, when making the rotational asymmetric lens into a meniscus shape, shifting occurs upon the upper line and underline of the marginal ray at the telephoto end or the wide-angle end (when the ray passes through the end of the lens). Accordingly, it is useful for another lens to correct this.

With a method for solving this, the lens for correction is changed into a meniscus shape, which can have a reverse tilt to cancel out the shift of the upper line and underline. A coefficient is determined by focusing attention on this at the time of introducing a higher order coefficient than a tertiary coefficient. Also, a meniscus shape can be shaped in the direction for reducing the mutual distance. This is because reducing the distance between the lenses enables a on-axis coma aberration to be reduced while suppressing this to the minimum upon each surface.

As described above, the present examples 6 and 7 reduce a on-axis coma aberration.

TABLE 1

a: 4.0000E-03 n: 1.51742				
Amount of δ deviation				
	E1	E2	E3	E4
Telephoto end	3.00 mm	-3.00 mm	-1.18 mm	1.18 mm
Middle	0.29 mm	-0.29 mm	2.18 mm	-2.18 mm
Wide-angle end	-1.65 mm	1.65 mm	3.89 mm	-3.89 mm

TABLE 2

Type of surface		Surface interval
Object surface		Infinity
S0 Reference plane		0
S1	Flat surface	1
S2	Polynomial surface	0.5
S3	Polynomial surface	1
S4	Flat surface	0.4
S5 Diaphragm surface		0.4
S6	Flat surface	1
S7	Polynomial surface	0.5
S8	Polynomial surface	1
S9	Flat surface	1

TABLE 5-continued

C21:	-1.38E-01	C22:	7.36E-02	C23:	-1.47E-02
C24:	-2.46E-03	C40:	3.38E-02	C41:	-2.19E-02
C42:	-4.05E-03	C60:	-1.28E-03		
C2:	-2.00E-02	C3:	2.91E-02	C4:	6.76E-03
C5:	-2.34E-03	C6:	-2.23E-03	C20:	1.19E-02
C21:	8.79E-02	C22:	6.91E-03	C23:	-1.83E-02
C24:	-1.06E-02	C40:	2.13E-02	C41:	-2.43E-02
C42:	-2.76E-02	C60:	-6.62E-03		
C2:	-4.15E-02	C3:	7.74E-02	C4:	8.72E-03
C5:	-1.55E-03	C6:	-2.17E-03	C20:	-1.00E-01
C21:	1.58E-01	C22:	2.16E-02	C23:	-1.26E-02
C24:	-9.10E-03	C40:	6.61E-03	C41:	-2.38E-02
C42:	-1.94E-02	C60:	-1.42E-03		
C2:	-5.49E-03	C3:	3.23E-02	C4:	-1.21E-02
C5:	-1.63E-03	C6:	9.65E-04	C20:	-1.61E-01
C21:	8.58E-02	C22:	1.15E-03	C23:	-3.03E-03

TABLE 3

Type of surface	Curvature radius	Surface interval	Refractive index	Abbe number
Object surface				
Reference plane s0		0		
s1	Polynomial surface	0.5	1.538604	65.5527
s2	Polynomial surface	0.3		
s3	Polynomial surface	0.5	1.589647	62.0231
s4	Polynomial surface	0.1		
s6	Spherical surface	0.712795	1.48749	70.4058
s7	Spherical surface	0.853974		
Diaphragm surface		0.251098		
s8				
s9	Spherical surface	0.452264	1.48749	70.4058
s10	Spherical surface	0.246629		
s11	Polynomial surface	0.6	1.62041	60.3236
s12	Polynomial surface	0.5		
s13	Polynomial surface	0.6	1.62041	60.3236
s14	Polynomial surface	0.2		
s15	Spherical surface	0.19521	1.48749	70.4058
s16	Spherical surface	0.05331		
Image plane				

TABLE 4

Lens number	Amount of deviation		
	Telephoto end	Middle	Wide-angle end
E1	0.89952	0.49385	-0.60408
E2	-0.89952	-0.49385	0.60408
E5	-1.22297	-0.29356	0.58002
E6	1.22297	0.29356	-0.58002

TABLE 5-continued

C24:	-1.78E-04	C40:	-2.17E-04	C41:	2.42E-03
C42:	-2.40E-03	C60:	-2.36E-03		
C2:	-2.64E-02	C3:	-1.02E-02	C4:	-7.90E-03
C5:	-2.20E-03	C6:	7.70E-04	C20:	-1.11E-01
C21:	-4.63E-02	C22:	1.04E-02	C23:	-3.82E-03
C24:	-1.01E-04	C40:	1.27E-02	C41:	-2.64E-03
C42:	4.33E-04	C60:	-9.88E-05		

TABLE 5

S1	C2:	7.25E-02	C3:	-2.17E-02	C4:	-6.26E-03
	C5:	1.22E-03	C6:	5.61E-04	C20:	1.44E-01
	C21:	-4.85E-02	C22:	-1.05E-02	C23:	-1.59E-03
	C24:	1.95E-03	C40:	2.90E-04	C41:	1.37E-03
	C42:	2.20E-03	C60:	-4.96E-04		
S2	C2:	8.88E-02	C3:	4.58E-04	C4:	-6.74E-03
	C5:	1.68E-03	C6:	6.93E-04	C20:	1.41E-01
	C21:	1.98E-02	C22:	-1.06E-02	C23:	-1.32E-03
	C24:	1.47E-03	C40:	1.08E-02	C41:	6.24E-03
	C42:	2.97E-03	C60:	-7.26E-04		
S3	C2:	4.49E-02	C3:	5.69E-03	C4:	6.07E-03
	C5:	2.35E-04	C6:	-4.21E-05	C20:	1.02E-01
	C21:	-2.38E-02	C22:	4.02E-02	C23:	2.44E-03
	C24:	-4.75E-03	C40:	2.87E-02	C41:	-3.42E-03
	C42:	-7.96E-03	C60:	-1.15E-03		
S4	C2:	6.12E-02	C3:	-2.26E-02	C4:	1.06E-02
	C5:	-1.41E-03	C6:	5.87E-05	C20:	1.71E-01

TABLE 6

ϕ	...	$\frac{1}{e + S_k}$...	$\frac{1}{S_k}$...
$\left \frac{d\phi_1}{d\phi} \right $	Small	Small	Small	Equal	Great
$\left \frac{d\phi_2}{d\phi} \right $	Great	Great	Great	Equal	Small

40

45

50

55

60

65

TABLE 7

	Type of surface	Surface interval	Refractive index	Abbe number
Object surface		Infinity		
Reference plane s0	Flat surface	0		
s1	Polynomial surface	0.5	1.48749	70.4
s2	Polynomial surface	0.3		
s3	Polynomial surface	0.5	1.48749	70.4
s4	Polynomial surface	0.1		
s5	Spherical surface	0.5	1.48749	70.4
s6	Spherical surface	0.929645		
Diaphragm surface	Flat surface	0.251071		
s7				
s8	Spherical surface	0.5	1.48749	70.4
s9	Spherical surface	0.819284		
s10	Polynomial surface	0.6	1.5759	62.9
s11	Polynomial surface	0.5		
s12	Polynomial surface	0.6	1.518951	67.2
s13	Polynomial surface	0.2		
s14	Polynomial surface	0.7	1.48749	70.4
s15	Polynomial surface	3		
Image plane	Flat surface			

TABLE 8

Lens number	Amount of deviation		
	Telephoto end	Middle	Wide-angle end
E1	0.9722	0.53763	-0.51577
E2	-0.9722	-0.53763	0.51577
E5	-1.25554	-0.39583	0.50539
E6	1.25554	0.39583	-0.50539
E7	-0.68683	-0.09902	0.13684

TABLE 9

S1	C2	4.78E-02	C3	-2.66E-02	C4	-6.58E-03
	C5	9.93E-04	C6	5.80E-04	C20	1.15E-01
	C21	-2.81E-02	C22	-1.31E-03	C23	8.59E-04
	C24	1.43E-03	C40	-3.96E-04	C41	2.11E-03
	C42	2.44E-04	C60	-3.19E-04		
S2	C2	7.97E-02	C3	-1.73E-03	C4	-6.48E-03
	C5	1.28E-03	C6	5.89E-04	C20	1.41E-01
	C21	4.90E-02	C22	4.78E-03	C23	4.28E-03
	C24	1.60E-03	C40	1.42E-02	C41	9.64E-03
	C42	1.92E-03	C60	-2.41E-03		
S3	C2	3.70E-02	C3	2.38E-02	C4	-2.77E-03
	C5	-9.88E-04	C6	6.87E-04	C20	8.86E-02
	C21	1.13E-02	C22	1.74E-02	C23	-9.86E-04
	C24	-7.13E-04	C40	2.02E-02	C41	2.41E-03
	C42	-3.74E-03	C60	-4.76E-03		
S4	C2	7.25E-02	C3	-9.45E-03	C4	8.74E-04
	C5	-2.60E-03	C6	9.37E-04	C20	1.65E-01
	C21	-1.04E-01	C22	4.03E-02	C23	-1.37E-02
	C24	1.45E-03	C40	1.80E-02	C41	-7.75E-03
	C42	-2.20E-03	C60	-3.26E-03		
S10	C2	-2.61E-02	C3	3.20E-02	C4	7.15E-03
	C5	6.86E-04	C6	-2.70E-03	C20	1.24E-02
	C21	-1.37E-02	C22	1.49E-02	C23	-7.80E-03
	C24	-1.13E-02	C40	-4.54E-03	C41	8.90E-03
	C42	-1.89E-02	C60	-7.19E-04		
S11	C2	-3.79E-02	C3	8.01E-02	C4	1.19E-02
	C5	2.87E-03	C6	-1.77E-03	C20	1.62E-02
	C21	8.61E-02	C22	2.45E-02	C23	-1.27E-03
	C24	-8.91E-03	C40	-3.90E-02	C41	1.95E-02
	C42	-8.91E-03	C60	4.55E-03		

TABLE 9-continued

S12	C2	-1.74E-02	C3	3.03E-02	C4	-1.01E-02
	C5	-9.73E-04	C6	5.68E-04	C20	6.62E-02
30	C21	8.09E-03	C22	-8.75E-03	C23	4.91E-03
	C24	-9.23E-04	C40	-1.73E-02	C41	1.43E-02
S13	C42	-6.34E-03	C60	-2.61E-03		
	C2	-3.94E-02	C3	-1.80E-02	C4	-6.10E-03
35	C5	-1.82E-03	C6	5.02E-04	C20	2.07E-02
	C21	-1.54E-01	C22	2.16E-03	C23	2.85E-03
40	C24	3.73E-04	C40	3.29E-03	C41	6.87E-03
	C42	-1.49E-03	C60	3.77E-03		
S14	C2	1.12E-01	C3	9.54E-03	C4	-1.83E-02
	C5	-7.46E-04	C6	-4.60E-03	C20	2.61E-01
45	C21	-8.66E-02	C22	-2.18E-02	C23	-6.73E-03
	C24	4.42E-03	C40	-4.66E-02	C41	1.69E-02
S15	C42	1.60E-02	C60	2.59E-03		
	C2	6.96E-02	C3	9.14E-03	C4	-2.20E-02
50	C5	-1.33E-03	C6	-5.00E-03	C20	2.43E-01
	C21	-1.16E-02	C22	-2.15E-02	C23	-1.64E-02
55	C24	2.79E-03	C40	-4.71E-02	C41	1.02E-02
	C42	1.42E-02	C60	-9.36E-05		

TABLE 10

	e	e'	e/e'
1	4.66486	4.40074	1.060017
2	4.77492	4.43732	1.076082
3	4.99275	4.47979	1.114505
4	5.891	4.61327	1.276968
5	3.5578	3.80655	0.934652
6	4.21107	4.29634	0.980153

TABLE 11

	Type of surface	Surface interval	Refractive index	Abbe number
Object surface		Infinity		
Reference plane	Flat surface	0		
s0				
s1	Polynomial surface	0.5	1.48749	70.4
s2	Polynomial surface	0.3		
s3	Polynomial surface	0.5	1.48749	70.4
s4	Polynomial surface	0.1		
s5	Spherical surface	0.5	1.48749	70.4
s6	Spherical surface	0.929645		
Diaphragm surface s7	Flat surface	0.251071		
s8	Spherical surface	0.5	1.48749	70.4
s9	Spherical surface	0.819284		
s10	Polynomial surface	0.6	1.549101	64.7
s11	Polynomial surface	0.5		
s12	Polynomial surface	0.6	1.582253	67.2
s13	Polynomial surface	1.43067		
s14	Polynomial surface	0.7	1.744251	44.2
s15	Polynomial surface	1.76933		
Image plane	Flat surface			

TABLE 12

Lens number	Amount of deviation		
	Telephoto end	Middle	Wide-angle end
E1	0.90459	0.51376	-0.56819
E2	-0.90459	-0.51376	0.56819
E5	-1.25999	-0.31844	0.59454
E6	1.25999	0.31844	-0.59454

TABLE 13

Lens number	Amount of tilt		
	Telephoto end	Middle	Wide-angle end
E7	-0.68683	-0.09902	0.13684

TABLE 14

S1	C2	6.50E-02	C3	-2.42E-02	C4	-6.49E-03
	C5	8.62E-04	C6	6.90E-04	C20	1.22E-01
	C21	-3.62E-02	C22	-2.16E-03	C23	-4.12E-04
	C24	1.58E-03	C40	4.36E-03	C41	1.12E-03
	C42	3.67E-04	C60	-5.42E-04		
S2	C2	8.79E-02	C3	1.17E-03	C4	-6.78E-03
	C5	1.03E-03	C6	6.84E-04	C20	1.34E-01
	C21	4.33E-02	C22	4.58E-04	C23	9.45E-04
	C24	9.73E-04	C40	1.37E-02	C41	6.02E-03
	C42	8.06E-04	C60	-2.68E-03		
S3	C2	3.48E-02	C3	1.04E-02	C4	5.84E-03
	C5	-4.63E-04	C6	-1.20E-04	C20	8.33E-02
	C21	7.76E-03	C22	2.98E-02	C23	3.16E-03
	C24	-3.16E-03	C40	2.02E-02	C41	1.08E-04
	C42	-6.92E-03	C60	-4.05E-03		
S4	C2	6.14E-02	C3	-2.31E-02	C4	1.05E-02
	C5	-2.32E-03	C6	3.23E-05	C20	1.59E-01
	C21	-1.15E-01	C22	5.30E-02	C23	-7.61E-03
	C24	-1.91E-03	C40	2.33E-02	C41	-1.09E-02
	C42	-6.00E-03	C60	-2.54E-03		
S10	C2	-2.08E-02	C3	3.15E-02	C4	5.00E-03
	C5	-2.72E-04	C6	-2.39E-03	C20	2.75E-02
	C21	4.81E-03	C22	9.22E-03	C23	-5.95E-03
	C24	-1.33E-02	C40	2.36E-02	C41	1.18E-04
	C42	-2.04E-02	C60	-6.02E-03		
S11	C2	-3.50E-02	C3	8.07E-02	C4	9.08E-03
	C5	1.28E-03	C6	-2.44E-03	C20	-2.99E-02

TABLE 14-continued

25	C21	1.48E-01	C22	2.60E-02	C23	-6.29E-04	
	C24	-1.33E-02	C40	1.14E-02	C41	2.89E-03	
	C42	-1.46E-02	C60	-3.61E-03			
	S12	C2	-2.10E-02	C3	2.70E-02	C4	-1.09E-02
		C5	-2.30E-03	C6	3.99E-04	C20	-5.77E-02
30	C21	6.67E-03	C22	2.16E-02	C23	6.06E-03	
	C24	-2.39E-03	C40	7.33E-03	C41	9.82E-03	
	C42	-1.07E-02	C60	-2.46E-03			
	S13	C2	-2.89E-02	C3	-2.22E-02	C4	-8.53E-03
		C5	-2.74E-03	C6	3.05E-04	C20	-9.03E-02
35	C21	-1.40E-01	C22	3.33E-02	C23	5.08E-03	
	C24	-1.55E-03	C40	2.18E-02	C41	1.39E-03	
	C42	-5.96E-03	C60	3.64E-03			
	S14	C2	2.48E-01	C3	-4.50E-02	C4	-7.67E-03
		C5	4.22E-03	C6	-6.63E-03	C20	1.03E-01
40	C21	-9.87E-02	C22	-2.17E-02	C23	9.05E-03	
	C24	2.51E-03	C40	-2.17E-03	C41	1.23E-02	
	C42	5.53E-03	C60	-2.54E-03			
	S15	C2	2.73E-01	C3	-6.77E-02	C4	-1.10E-02
		C5	1.46E-02	C6	-1.37E-02	C20	1.23E-01
45	C21	-1.00E-01	C22	-1.76E-02	C23	8.90E-03	
	C24	2.15E-04	C40	-3.09E-03	C41	1.44E-02	
	C42	2.72E-03	C60	-4.45E-03			
	50	C2	2.48E-01	C3	-4.50E-02	C4	-7.67E-03
		C5	4.22E-03	C6	-6.63E-03	C20	1.03E-01
55	C21	-9.87E-02	C22	-2.17E-02	C23	9.05E-03	
	C24	2.51E-03	C40	-2.17E-03	C41	1.23E-02	
	C42	5.53E-03	C60	-2.54E-03			
	S15	C2	2.73E-01	C3	-6.77E-02	C4	-1.10E-02
		C5	1.46E-02	C6	-1.37E-02	C20	1.23E-01
60	C21	-1.00E-01	C22	-1.76E-02	C23	8.90E-03	
	C24	2.15E-04	C40	-3.09E-03	C41	1.44E-02	
	C42	2.72E-03	C60	-4.45E-03			
	65	C2	2.48E-01	C3	-4.50E-02	C4	-7.67E-03
		C5	4.22E-03	C6	-6.63E-03	C20	1.03E-01

TABLE 15

	e	e'	e/e'
1	4.6555	4.36899	1.065578
2	4.74743	4.39491	1.080211
3	4.89929	4.42095	1.108198
4	5.30788	4.51597	1.175358
5	1.68025	4.07459	0.412373
6	4.08146	4.30733	0.947561

TABLE 16

	Type of surface	Curvature radius	Surface interval	Refractive index	Abbe number
Object surface			Infinity		
Reference plane s0	Flat surface		0		
s1	Polynomial surface		0.5	1.538604	65.6
s2	Polynomial surface		0.3		
s3	Polynomial surface		0.5	1.589647	62.06
s4	Polynomial surface		0.1		
s5	Spherical surface	1.513485	0.5	1.48749	70.46
s6	Spherical surface	1.281722	0.896555		
Diaphragm surface	Flat surface		0.166764		
s7					
s8	Spherical surface	2.336814	0.5	1.48749	70.46
s9	Spherical surface	5.596556	0.936681		
s10	Polynomial surface		0.6	1.62041	60.36
s11	Polynomial surface		0.5		
s12	Polynomial surface		0.6	1.62041	60.36
s13	Polynomial surface		0.2		
s14	Spherical surface	3.728692	0.7	1.48749	70.46
s15	Spherical surface	6.173476	3		
Image plane	Flat surface				

TABLE 17

Lens number	Amount of deviation		
	Telephoto end	Middle	Wide-angle end
E1	0.90725	0.50479	-0.56622
E2	-0.90725	-0.50479	0.56622
E5	-1.23808	-0.32928	0.55396
E6	1.23808	0.32928	-0.55396

TABLE 18

Lens number	Amount of deviation		
	Telephoto end	Middle	Wide-angle end
E7	-0.18878	0.01009	0.00099

TABLE 19

S1	C2	6.57E-02	C3	-2.26E-02	C4	-7.34E-03
	C5	7.69E-04	C6	6.69E-04	C20	1.42E-01
	C21	-4.40E-02	C22	-6.74E-03	C23	-3.97E-04
	C24	1.85E-03	C40	9.76E-04	C41	9.37E-04
S2	C42	1.77E-03	C60	-8.97E-04		
	C2	8.88E-02	C3	-7.93E-05	C4	-8.01E-03
	C5	9.31E-04	C6	7.17E-04	C20	1.29E-01
	C21	2.33E-02	C22	-4.38E-03	C23	1.43E-03
S3	C24	1.54E-03	C40	1.27E-02	C41	6.95E-03
	C42	2.84E-03	C60	-9.50E-04		
	C2	3.94E-02	C3	5.74E-03	C4	3.40E-03
	C5	-1.89E-04	C6	-9.92E-05	C20	8.19E-02
S4	C21	-1.09E-02	C22	3.71E-02	C23	1.98E-04
	C24	-4.10E-03	C40	2.00E-02	C41	-1.28E-03
	C42	-5.83E-03	C60	-1.14E-03		
	C2	6.29E-02	C3	-2.27E-02	C4	7.39E-03
S5	C5	-2.15E-03	C6	1.97E-04	C20	1.68E-01
	C21	-1.18E-01	C22	6.86E-02	C23	-1.63E-02
	C24	-1.60E-03	C40	1.83E-02	C41	-1.26E-02
	C42	-4.47E-03	C60	-1.57E-03		

TABLE 19-continued

S10	C2	-1.77E-02	C3	2.80E-02	C4	7.40E-03
	C5	-1.08E-03	C6	-2.12E-03	C20	2.08E-02
	C21	3.33E-02	C22	1.28E-02	C23	-1.51E-02
	C24	-1.09E-02	C40	1.74E-02	C41	-2.60E-02
	C42	-3.01E-02	C60	-7.57E-03		
S11	C2	-4.30E-02	C3	7.36E-02	C4	1.16E-02
	C5	3.34E-04	C6	-2.18E-03	C20	-8.35E-02
	C21	1.75E-01	C22	3.14E-02	C23	-1.00E-02
	C24	-1.15E-02	C40	1.85E-02	C41	-2.37E-02
	C42	-2.60E-02	C60	-6.31E-03		
S12	C2	-1.20E-02	C3	3.04E-02	C4	-7.73E-03
	C5	-1.46E-03	C6	7.05E-04	C20	-1.57E-01
	C21	9.49E-02	C22	-1.03E-02	C23	-9.48E-03
	C24	2.28E-03	C40	1.40E-02	C41	-6.51E-03
	C42	2.67E-03	C60	-3.79E-03		
S13	C2	-3.31E-02	C3	-9.97E-03	C4	-5.24E-03
	C5	-1.89E-03	C6	7.18E-04	C20	-1.14E-01
	C21	-3.38E-02	C22	8.50E-04	C23	-9.86E-03
	C24	1.67E-03	C40	1.43E-02	C41	-7.61E-03
	C42	3.01E-03	C60	-4.04E-04		

TABLE 20

	e	e'	e/e'
1	4.58012	4.40445	1.039885
2	4.67492	4.4328	1.05462
3	4.84519	4.46744	1.084556
4	5.31689	4.64737	1.144064
5	2.1566	4.21798	0.511287
6	3.93389	4.3934	0.895409

TABLE 21

Type of surface	Curvature radius	Surface interval	Refractive index	Abbe number
Object surface		Infinity		
Reference plane s0	Flat surface	0		
s1	Polynomial surface	0.5	1.48749	70.4
s2	Polynomial surface	0.3		
s3	Polynomial surface	0.5	1.48749	70.4
s4	Polynomial surface	0.1		
s5	Spherical surface	1.778863	0.5	1.48749
s6	Spherical surface	1.549574	0.929645	
Diaphragm surface	Flat surface	0.251071		
s7				
s8	Spherical surface	2.574972	0.5	1.48749
s9	Spherical surface	37.2687	0.819284	
s10	Polynomial surface	0.6	1.556781	64.8
s11	Polynomial surface	0.5		
s12	Polynomial surface	0.6	1.62041	60.3
s13	Polynomial surface	0.50847		
s14	Polynomial surface	0.7	1.755201	27.6
s15	Polynomial surface	0.222088		
s16	Polynomial surface	0.7	1.755201	27.6
s17	Polynomial surface	1.76944		
Image plane	Flat surface			

TABLE 22

Lens number	Amount of deviation		
	Telephoto end	Middle	Wide-angle end
E1	0.9074	0.51109	-0.56432
E2	-0.9074	-0.51109	0.56432
E5	-1.2605	-0.32101	0.59761
E6	1.2605	0.32101	-0.59761

TABLE 23

Lens number	Amount of tilt		
	Telephoto end	Middle	Wide-angle end
E7	-4.35122	-0.2827	1.43592
E8	-2.42017	-0.76772	-1.46017

TABLE 24

S1	C2	5.97E-02	C3	-2.31E-02	C4	-5.57E-03
	C5	1.01E-03	C6	6.79E-04	C20	1.16E-01
	C21	-3.49E-02	C22	-4.36E-03	C23	-1.56E-03
	C24	2.03E-03	C40	5.09E-03	C41	5.04E-04
	C42	-9.55E-05	C60	-9.17E-04		
S2	C2	8.57E-02	C3	2.21E-03	C4	-5.59E-03
	C5	1.11E-03	C6	6.39E-04	C20	1.50E-01
	C21	5.01E-02	C22	-4.53E-04	C23	-6.01E-04
	C24	1.36E-03	C40	1.80E-02	C41	6.80E-03
S3	C2	4.70E-04	C60	-2.69E-03		
	C2	2.65E-02	C3	8.82E-03	C4	5.52E-03
	C5	-7.09E-04	C6	-1.80E-04	C20	8.42E-02
	C21	2.81E-02	C22	1.70E-02	C23	1.80E-03
S4	C24	-2.28E-03	C40	1.84E-02	C41	-9.73E-04
	C42	-2.91E-03	C60	-2.54E-03		
	C2	6.02E-02	C3	-2.71E-02	C4	1.14E-02
	C5	-3.05E-03	C6	1.16E-04	C20	1.46E-01
S10	C21	-9.51E-02	C22	3.53E-02	C23	-7.42E-03
	C24	-7.56E-04	C40	1.84E-02	C41	-1.03E-02
	C42	-1.95E-03	C60	-1.36E-03		
	C2	-1.16E-03	C3	2.41E-02	C4	7.57E-03
S17	C5	1.40E-04	C6	-2.42E-03	C20	6.13E-02
	C21	-1.73E-02	C22	-9.72E-04	C23	-3.76E-03
	C24	-1.24E-02	C40	2.09E-02	C41	2.17E-03
	C42	-1.24E-02	C60	-7.28E-03		

25

TABLE 24-continued

S11	C2	-3.66E-02	C3	7.74E-02	C4	1.09E-02
	C5	1.78E-03	C6	-1.91E-03	C20	-4.09E-02
	C21	1.24E-01	C22	1.66E-02	C23	-7.87E-04
	C24	-1.11E-02	C40	8.04E-03	C41	6.33E-03
S12	C42	-2.80E-03	C60	-1.36E-03		
	C2	-7.34E-03	C3	2.08E-02	C4	-1.03E-02
	C5	-2.79E-03	C6	1.45E-04	C20	-6.60E-02
	C21	8.10E-02	C22	1.89E-02	C23	-8.15E-04
S13	C24	-1.28E-03	C40	-8.07E-03	C41	-1.81E-02
	C42	-5.14E-03	C60	-3.59E-03		
	C2	-3.20E-02	C3	-2.87E-02	C4	-1.03E-02
	C5	-3.43E-03	C6	3.99E-04	C20	-7.99E-02
S14	C21	-9.48E-02	C22	3.32E-02	C23	-4.09E-04
	C24	3.92E-04	C40	-1.53E-02	C41	-2.33E-02
	C42	3.53E-03	C60	-4.54E-04		
	C2	-2.18E-01	C3	4.56E-03	C4	-2.58E-02
S15	C5	-3.07E-03	C6	1.22E-02	C20	-2.29E-01
	C21	-5.18E-02	C22	8.42E-02	C23	2.59E-02
	C24	8.84E-04	C40	-3.23E-02	C41	1.53E-02
	C42	-5.35E-03	C60	1.33E-02		
S16	C2	-1.67E-01	C3	1.49E-02	C4	-2.87E-02
	C5	-8.32E-03	C6	1.43E-02	C20	-6.27E-02
	C21	-1.68E-03	C22	7.45E-02	C23	9.49E-03
	C24	3.21E-03	C40	-2.11E-02	C41	3.64E-03
S17	C42	-1.41E-02	C60	1.11E-02		
	C2	1.80E-01	C3	1.02E-03	C4	-5.50E-03
	C5	3.65E-05	C6	-9.26E-03	C20	2.19E-01
	C21	-1.40E-02	C22	3.77E-02	C23	6.55E-03
S55	C24	-6.45E-03	C40	3.38E-02	C41	-1.26E-03
	C42	-7.92E-03	C60	-4.67E-03		
	C2	1.99E-01	C3	-8.04E-03	C4	1.96E-02
	C5	6.80E-03	C6	-2.56E-02	C20	1.21E-01
S65	C21	-2.10E-02	C22	4.81E-02	C23	8.57E-03
	C24	-1.03E-02	C40	8.75E-02	C41	-3.80E-04
	C42	-1.02E-02	C60	-1.60E-02		

TABLE 25

	e	e'	e/e'
1	4.74959	4.29297	1.106365
2	4.83084	4.32908	1.115905
3	5.01599	4.34547	1.154303
4	5.71758	4.338	1.318022
5	2.75974	4.33504	0.636612
6	4.0421	4.38994	0.920764

TABLE 26

Object surface	Type of surface	Surface interval	Refractive index	Abbe number
Reference plane s0	Flat surface	0		
s1	XY polynomial surface	0.6	1.48749	70.4
s2	XY polynomial surface	0.2		
s3	XY polynomial surface	0.6	1.48749	70.4
s4	XY polynomial surface	0.6		
Diaphragm surface s5	Flat surface	1.6		
s6	XY polynomial surface	0.5	1.5219	67
s7	XY polynomial surface	0.1		
s8	XY polynomial surface	0.5	1.615232	51.2
s9	XY polynomial surface	0.9		
s10	XY polynomial surface	0.5	1.48749	70.4
s11	XY polynomial surface	3.0466		
Image plane	Flat surface			

TABLE 27

Lens number	Amount of deviation		
	Telephoto end	Middle	Wide-angle end
E1	1.20411	1.03695	0.69269
E2	-1.19577	-0.82654	-0.12914
E3	-0.96144	-0.34862	0.7032
E4	-0.43232	-0.28899	-0.47989
E5	1.03109	0.40512	-0.28936

TABLE 28

s1	C2	-2.90E-02	C3	-4.82E-02	C4	-5.36E-03
	C5	9.16E-04	C6	3.08E-04	C20	9.01E-02
	C21	-8.09E-02	C22	-9.40E-04	C23	1.18E-02
	C24	3.99E-03	C40	-6.81E-03	C41	1.06E-02
s2	C42	7.80E-03	C60	1.88E-03		
	C1	-1.00E-01	C2	-4.88E-02	C3	-2.09E-02
	C4	-3.09E-03	C5	1.35E-03	C6	2.94E-04
	C20	5.63E-02	C21	-3.53E-02	C22	8.12E-03
s3	C23	1.82E-02	C24	4.66E-03	C40	-2.02E-02
	C41	2.09E-02	C42	1.06E-02	C60	1.03E-02
	C1	-2.22E-02	C2	5.87E-03	C3	4.20E-02
	C4	-5.51E-03	C5	-4.97E-04	C6	3.47E-04
	C20	-2.68E-02	C21	1.41E-01	C22	1.41E-02
	C23	-1.93E-02	C24	6.55E-03	C40	1.48E-03
	C41	-3.87E-02	C42	1.83E-02	C60	4.02E-03

TABLE 28-continued

5	s4	C2	2.06E-02	C3	1.42E-02	C4	-4.73E-03
		C5	-2.94E-03	C6	7.68E-04	C20	-4.00E-02
		C21	9.09E-02	C22	3.21E-02	C23	-2.29E-02
		C24	3.82E-03	C40	2.80E-02	C41	-5.20E-02
10		C42	1.86E-02	C60	-6.72E-03		
	s5	C2	-6.00E-02	C3	-6.72E-02	C4	-5.53E-03
		C5	8.74E-03	C6	1.06E-03	C20	-1.21E-02
		C21	7.62E-02	C22	1.81E-02	C23	-2.88E-02
15		C24	-8.36E-03	C40	9.74E-03	C41	-2.50E-02
		C42	-1.82E-02	C60	8.84E-03		
	s7	C1	-9.23E-04	C2	-1.25E-02	C3	-1.16E-02
		C4	4.78E-03	C5	9.30E-03	C6	1.11E-04
20		C20	2.66E-02	C21	1.55E-01	C22	3.01E-02
		C23	-1.29E-02	C24	-4.03E-03	C40	-1.43E-01
		C41	-2.42E-03	C42	-1.01E-02	C60	6.56E-02
	s8	C1	5.94E-02	C2	-2.95E-02	C3	1.79E-02
25		C4	3.27E-03	C5	5.06E-03	C6	-2.95E-03
		C20	4.76E-02	C21	1.50E-01	C22	2.89E-03
		C23	-2.59E-02	C24	6.41E-03	C40	-1.41E-01
		C41	5.46E-03	C42	-1.64E-02	C60	2.85E-02
30	s9	C1	1.27E-01	C2	-1.22E-01	C3	-2.06E-02
		C4	9.78E-03	C5	3.74E-03	C6	-3.52E-03
		C20	-7.64E-02	C21	1.27E-01	C22	-6.38E-03
		C23	-2.48E-02	C24	7.39E-04	C40	2.57E-05
35		C41	-9.17E-03	C42	-2.01E-02	C60	-1.28E-03
	s10	C1	-2.89E-02	C2	-1.21E-01	C3	3.59E-02
		C4	-2.18E-02	C5	-5.47E-03	C6	3.16E-03
		C20	-2.69E-01	C21	1.38E-01	C22	-2.02E-02
40		C23	-1.76E-02	C24	-7.12E-03	C40	3.86E-02
		C41	-2.21E-02	C42	-1.40E-02	C60	8.06E-03
	s11	C2	3.66E-02	C3	3.51E-02	C4	-1.22E-02
		C5	-3.40E-03	C6	2.64E-03	C20	-7.75E-02
45		C21	5.37E-02	C22	9.63E-03	C23	-5.73E-03
		C24	-1.98E-03	C40	1.13E-02	C41	-9.72E-03
		C42	-5.94E-03	C60	-3.64E-04		

TABLE 29

	Comparative example 2	Example 1	Example 2	Example 3	Example 4	Example 5
ϕ of E7						
Telephoto end		0.070555	0.0524264	0.026859	0.0568105	-0.048357 -0.176985
Middle		0.070555	0.0451396	0.0244142	0.0568155	-0.044729 -0.160276
Wide-angle		0.070555	0.0441824	0.0250744	0.0568155	-0.043986 -0.159685
Differences		0	0.008244	0.0024448	5E-06	0.0043708 0.0173
Difference \times diagonal length		0	0.037098	0.0110016	2.25E-05	0.0196686 0.07785
ϕ of G1						
Telephoto end		0.092751	0.092899	0.100731	0.0994485	0.0915985 0.202515
Middle		0.021375	0.0248308	0.0387807	0.0346099	0.0296608 0.151895
Wide-angle		-0.18425	-0.16593	-0.158782	-0.16345	-0.175728 0.0666744

TABLE 29-continued

	Comparative example 2	Example 1	Example 2	Example 3	Example 4	Example 5
Differences	0.276998	0.258829	0.259513	0.2628985	0.2673265	0.1358406
Difference × diagonal length	1.246491	1.1647305	1.1678085	1.1830433	1.2029693	0.6112827
ϕ of G3						
Telephoto end	-0.58115	-0.552922	-0.515653	-0.455917	-0.512315	-0.07615
Middle	-0.10308	-0.099618	-0.086842	-0.053169	-0.049238	0.0498576
Wide-angle	0.197742	0.188682	0.216735	0.224316	0.277264	0.212012
Differences	0.778892	0.741604	0.732388	0.680233	0.789579	0.2881619
Difference × diagonal length	3.505014	3.337218	3.295746	3.0610485	3.5531055	1.2967286
$\Delta \phi _{\min}/\Delta \phi $	—	31.396046	106.14897	52579.7	61.161915	7.8520578

TABLE 30

Type of surface	Curvature radius	Surface interval	Refractive index	Abbe number
Object surface		Infinity		
S1	Polynomial surface	0.5	1.48749	70.4
S2	Polynomial surface	0.3		
S3	Polynomial surface	0.5	1.48749	70.4
S4	Polynomial surface	0.1		
S5	Spherical surface	1.811351	1.48749	70.4
S6	Spherical surface	1.593065	0.837525	
S7(diaphragm surface)	Flat surface	0.337252		
S8	Spherical surface	2.618194	1.48749	70.4
S9	Spherical surface	9.964944	0.825224	
S10	Polynomial surface	0.6	1.48749	70.4
S11	Polynomial surface	0.5		
S12	Polynomial surface	0.6	1.48749	70.4
S13	Polynomial surface	Variable		
S14	Spherical surface	2.997087	1.563804	63.7
S15	Spherical surface	2.925063	Variable	
Image plane	Flat surface			

35

TABLE 31

Lens number	Amount of deviation		
	Telephoto end	Middle	Wide-angle end
E1	0.8603	0.40646	-0.8496
E2	-0.8603	-0.40646	0.8496
E5	-1.42634	-0.47734	0.74018
E6	1.42635	0.47734	-0.74018

TABLE 32

Surface interval	Amount of movement in optical-axis direction		
	Telephoto end	Middle	Wide-angle end
S13	0.1161	1.60533	1.46085
S15	3.0839	1.59467	1.73915

TABLE 33

S2	C2	0.064011	C3	-0.03116	C4	-0.01175
	C5	-0.00116	C6	0.000393	C20	0.075119
	C21	-0.04918	C22	0.002403	C23	0.002028
	C24	0.002764	C40	0.005307	C41	0.002913
	C42	-0.00149	C60	-0.00124		
S3	C2	7.73E-02	C3	-1.15E-02	C4	-1.31E-02
	C5	-1.25E-03	C6	3.24E-04	C20	7.44E-02
	C21	1.20E-02	C22	7.50E-03	C23	4.11E-03

TABLE 33-continued

40	S4	C24	2.40E-03	C40	2.53E-02	C41	7.20E-03
		C42	-1.87E-03	C80	-3.60E-03		
		C2	-2.22E-04	C3	2.72E-02	C4	1.07E-03
		C5	-1.16E-03	C6	3.30E-04	C20	1.15E-01
		C21	2.09E-02	C22	2.34E-02	C23	-6.92E-03
45	S5	C24	-2.12E-03	C40	1.88E-02	C41	4.24E-04
		C42	-1.82E-03	C60	-2.35E-03		
		C2	1.07E-02	C3	1.99E-03	C4	2.77E-03
		C5	-2.07E-03	C6	4.49E-04	C20	1.66E-01
		C21	-7.04E-02	C22	4.04E-02	C23	-1.87E-02
50	S11	C24	-2.97E-04	C40	4.18E-03	C41	-9.75E-03
		C42	5.91E-04	C60	-1.83E-04		
		C2	-6.17E-04	C3	1.68E-02	C4	7.78E-03
		C5	-1.69E-03	C6	-1.27E-03	C20	6.32E-02
		C21	2.77E-02	C22	1.45E-02	C23	-1.51E-02
55	S12	C24	-8.81E-03	C40	1.39E-02	C41	-2.23E-02
		C42	-2.21E-02	C60	-4.24E-03		
		C2	-3.47E-02	C3	5.86E-02	C4	1.11E-02
		C5	-1.03E-03	C6	-9.77E-04	C20	-5.60E-02
		C21	1.62E-01	C22	3.50E-02	C23	-1.26E-02
60	S13	C24	-7.53E-03	C40	1.04E-02	C41	-2.22E-02
		C42	-1.79E-02	C60	-1.83E-03		
		C2	3.67E-02	C3	4.05E-02	C4	-1.63E-02
		C5	-3.14E-03	C6	6.66E-04	C20	-7.27E-02
		C21	6.55E-02	C22	-1.64E-02	C23	-6.86E-03
65	S14	C24	2.62E-03	C40	-4.94E-03	C41	9.24E-04
		C42	-6.16E-05	C60	-4.63E-03		
		C2	3.53E-03	C3	5.92E-03	C4	-1.10E-02
		C5	-4.34E-03	C6	4.31E-04	C20	-4.00E-02
		C21	-5.69E-02	C22	-5.75E-04	C23	-8.40E-03

TABLE 34

	e	e'	e/e'
1	4.64019	4.45874	1.040695
2	4.68524	4.47408	1.047196
3	4.84857	4.49115	1.079583
4	5.38721	4.45972	1.20797
5	3.2979	4.56394	0.722599
6	4.32296	4.55333	0.949406

5

10

TABLE 39

	A	B
S10	-0.00775	-0.02033
S11	0.042386	0.00162
S12	0.01989	-0.00842
S13	-0.00943	-0.00301

TABLE 35

	Magnifying power				
	E1	E2	E5	E6	E7
Telephoto end	0	0.466035	1.507369	2.039752	0.879476
Middle	0	0.437331	1.117957	1.117665	0.896435
Wide-angle end	0	0.381325	0.00571	0.574456	0.89421

15

TABLE 40

	A	B
S10	-0.00775	-0.02033
S11	0.042386	0.00162
S12	0.01989	-0.00842
S13	-0.00943	-0.00301

TABLE 36

	Type of surface	Curvature radius	Surface interval	Refractive index	Abbe number
Object surface			Infinity		
S1	Polynomial surface		0.5	1.563839	60.7
S2	Polynomial surface		0.1		
S3	Polynomial surface		0.5	1.697002	48.5
S4	Polynomial surface		0.1		
S5(diaphragm surface)	Flat surface		0		
S6	Polynomial surface		0.5	1.743198	49.3
S7	Polynomial surface		0.3		
S8	Polynomial surface		0.5	1.697002	48.5
S9	Polynomial surface		Variable		
S10	Aspheric surface		0.5	1.48749	70.2
S11	Aspheric surface	-3	1.62536		
S12	Aspheric surface	-1.38429	0.5	1.48749	70.2
S13	Aspheric surface	-20.5692	Variable		
S14	Flat surface	2.970165		1.494	75
S15	Flat surface			1.51633	64.1
S16	Flat surface				
Image plane	Flat surface				

TABLE 37

Lens number	Amount of deviation		
	Telephoto end	Middle	Wide-angle end
E1	0.89063	0.0945	-0.20408
E2	-0.89063	-0.0945	0.20408
E3	-1.14918	-0.22964	0.09379
E4	1.14918	0.22964	-0.09379

45

50

55

60

TABLE 38

Surface interval	Amount of movement in optical-axis direction		
	Telephoto end	Middle	Wide-angle end
S9	2.77832	2.85902	2.83894
S13	0.496332	0.415639	0.43571

65

TABLE 41

S1	C2	0.049804	C3	-0.01866	C4	-0.00222
	C5	-0.00043	C6	-3.8E-05	C20	0.039089
	C21	-0.10081	C22	0.009658	C23	0.015455
	C24	0.004319	C40	-0.01888	C41	0.00384
	C42	0.007769	C60	0.010441		
S2	C2	-1.04E-03	C3	3.35E-03	C4	1.34E-03
	C5	1.06E-03	C6	2.40E-04	C20	-2.75E-02
	C21	-6.05E-02	C22	3.06E-02	C23	3.32E-02
	C24	5.75E-03	C40	6.26E-04	C41	1.09E-02
	C42	8.73E-03	C60	3.84E-02		
S3	C2	4.72E-02	C3	4.13E-02	C4	-8.18E-03
	C5	6.82E-04	C6	1.94E-04	C20	-2.05E-02
	C21	1.16E-01	C22	-2.36E-02	C23	-2.41E-03
	C24	1.29E-02	C40	3.49E-02	C41	-4.08E-02
	C42	1.85E-02	C60	5.50E-03		
S4	C2	3.57E-03	C3	1.52E-02	C4	4.27E-04
	C5	-1.37E-03	C6	2.17E-04	C20	-3.19E-02
	C21	3.86E-02	C22	9.80E-03	C23	-8.82E-03
	C24	6.36E-03	C40	2.86E-02	C41	-1.41E-01
	C42	3.92E-02	C60	-3.15E-02		
S6	C2	1.77E-02	C3	8.83E-03	C4	7.32E-03
	C5	5.07E-04	C6	-6.67E-04	C20	3.76E-02
	C21	2.14E-02	C22	2.27E-02	C23	1.57E-02
	C24	-1.90E-02	C40	-3.08E-02	C41	-6.30E-02
	C42	1.02E-03	C60	-1.31E-02		

TABLE 41-continued

S7	C2	9.50E-03	C3	4.16E-02	C4	2.00E-03
	C5	1.66E-03	C6	-4.20E-04	C20	-2.57E-02
	C21	1.11E-01	C22	1.08E-02	C23	1.54E-02
	C24	-1.43E-02	C40	-8.12E-02	C41	1.96E-02
S8	C42	-1.07E-02	C60	3.53E-02		
	C2	3.94E-03	C3	2.01E-02	C4	6.19E-03
	C5	4.43E-04	C6	-2.59E-04	C20	-1.91E-02
	C21	1.32E-03	C22	5.29E-02	C23	3.14E-02
S9	C24	-1.75E-03	C40	-4.54E-02	C41	1.25E-03
	C42	-4.47E-03	C60	3.60E-02		
	C2	-2.81E-03	C3	-4.45E-03	C4	4.62E-03
	C5	5.88E-04	C6	5.69E-05	C20	1.87E-02
	C21	-4.74E-02	C22	3.77E-02	C23	2.52E-02
	C24	1.58E-03	C40	-5.16E-03	C41	3.37E-04
	C42	-2.97E-03	C60	8.63E-03		

TABLE 42

	Magnifying power					
	E1	E2	E3	E4	E5	E6
Tele-photo end	0	0.486578	1.445043	1.764707	0.424062	1.261455
Middle	0	0.481248	1.120378	1.104816	0.424243	1.261209
Wide-angle end	0	-0.80056	-0.13916	0.575994	0.42375	1.261915

Also, embodiments and modifications of at least one exemplary embodiment include the following.

A zoom optical system in which multiple optical groups of which optical power is variable and one or more optical groups are disposed in the optical-axis direction for performing zooming by changing the power of the multiple optical groups of which optical power is variable, where the multiple optical groups of which optical power is variable have multiple optical elements Ld each including a rotationally asymmetrical surface for moving in the direction in the direction different from the optical axis to change the power within the optical group, and the one or more optical groups include an optical group S having one or more optical elements Ls which have symmetry as to at least one surface and can perform decentering.

A zoom optical system in which multiple optical groups of which optical power is variable and two or more optical groups are disposed in the optical-axis direction for performing zooming by changing the power of the multiple optical groups of which optical power is variable, where the multiple optical groups of which optical power is variable have multiple optical elements Ld each including a rotationally asymmetrical surface for moving in the direction in the direction different from the optical axis to change the power within the optical group, and where the two or more optical groups include an optical group S having one or more optical elements Ls which have symmetry as to at least one surface and can perform decentering, and an optical group C of which optical power is substantially unchangeable.

The one or more optical elements Ls can be capable of decentering include an optical element Lss for shifting in the direction different from the optical axis.

The one or more optical elements Ls can be capable of decentering include an optical element Lst for tilting.

The sign of the optical power of the optical group C can be unchangeable within the entire zoom range.

When the maximum value of the absolute value of the optical power in the multiple optical groups of which optical power is variable is $|\Phi d|_{\max}$ at the entire zoom positions, the maximum value of the absolute value of the optical power in the optical group S is $|\Phi s|_{\max}$ at the entire zoom positions, the following condition

$$|\Phi s|_{\max} < |\Phi d|_{\max}$$

can be satisfied.

The one or more optical elements Ls can be capable of decentering include an optical element Lss for shifting in the direction different from the optical axis, the multiple optical elements Ld include an optical element Lds for shifting in the direction different from the optical axis, and when assuming that the maximum value of the absolute value of the amount of shift of the optical element Lds is $|Dd|_{\max}$ at the entire zoom positions, and the maximum value of the absolute value of the amount of shift of the optical element Lss is $|Ds|_{\max}$ at the entire zoom positions, the following condition

$$|Ds|_{\max} < |Dd|_{\max}$$

can be satisfied.

When moving in the direction different from the optical axis, the principal-point position of an optical group including the multiple optical elements Ld is the optical-axis direction, the multiple optical elements Ld include an optical element, which can have a shape for moving outside of the optical group.

When assuming that the forward principal-point position and backward principal-point position of an optical group A of the multiple optical groups of which optical power is variable are H_A and H_A' respectively, the forward principal-point position and backward principal-point position of an optical group B closer to the image side than the optical group A are H_B and H_B' , the distance between the object point and the forward principal-point position H_A is e_0 , the distance between the backward principal-point position H_A' and forward principal-point position H_B is e , the distance between the backward principal-point position H_B' and the image point is e_i , and a smaller distance between the distance e_0 and distance e_i is e' , the distance e and distance e' are essentially the same at an arbitrary zoom position.

Here, the following condition

$$0.7 < e/e' < 1.4$$

can be satisfied.

When assuming that of the multiple optical groups of which optical power is variable, the backward principal-point position of the optical group A is H_A' , the forward principal-point position of the optical group B closer to the image side than the optical group A is H_B , the distance between the backward principal-point position H_A' and forward principal-point position H_B in a case in which the power of the entire system is the minimum within the range of the positive optical power of the area where the optical power of the optical group A is variable is $et1$, the distance between the backward principal-point position H_A' and forward principal-point position H_B in a case in which the power of the entire system is the maximum within the range of the positive optical power of the area where the optical power of the optical group A is variable is $ew1$, the distance between the backward principal-point position H_A' and forward principal-point position H_B in a case

55

in which the power of the entire system is the minimum within the range of the negative optical power of the area where the optical power of the optical group A is variable is et_2 , and the distance between the backward principal-point position H_A' and forward principal-point position H_B in a case in which the power of the entire system is the maximum within the range of the negative optical power of the area where the optical power of the optical group A is variable is ew_2 , the following conditions

$$et_1 < ew_1$$

$$et_2 < ew_2$$

can be satisfied.

When assuming that an optical group of the multiple optical groups of which optical power is variable is an optical group A, and an optical group closer to the image side than the optical group A is an optical group B, the maximum value of the absolute value of the optical power between the optical groups A and B in the entire zoom range is $|\Phi|_{max}$. Furthermore, a first variable optical power Φ_1 , a second variable optical power Φ_2 , and the value of sum of the optical power in an arbitrary zoom position of the first and second variable optical power units can be expressed as $\Phi_{AB} = \Phi_1 + \Phi_2$, where the following condition

$$-|\Phi|_{max} \leq \Phi_{AB} \leq |\Phi|_{max}$$

can be satisfied.

The zoom optical system can include an optical group of which optical power is variable, a lens group (lens unit) of which optical power is substantially unchangeable, an optical group of which optical power is variable, and an optical group having an optical element capable of decentering, in order from the object side toward the image side.

The one or more optical elements Ls can be capable of decentering perform decentering so as to correct and/or reduce the residual aberration of the optical group of which optical power is variable or/and an aberration to be generated when attempting to change optical power.

A zoom optical system in which multiple optical groups of which optical power is variable and one or more optical groups are disposed in the optical-axis direction for performing zooming by changing the power of the multiple optical groups of which optical power is variable, where the multiple optical groups of which optical power is variable have multiple optical elements Ld each including a rotationally asymmetrical surface for moving in the direction in the direction different from the optical axis to change the power within the optical group, and the one or more optical groups include an optical group S having one or more optical elements Ls which have symmetry as to at least one surface and can move in the optical-axis direction.

A zoom optical system in which multiple optical groups of which optical power is variable and one or more optical groups are disposed in the optical-axis direction for performing zooming by changing the power of the multiple optical groups of which optical power is variable, where the multiple optical groups of which optical power is variable have multiple optical elements Ld each including a rotationally asymmetrical surface for moving in the direction different from the optical axis to change the power within the optical group, and the one or more optical groups include an optical group S having one or more optical elements Ls which have symmetry as to at least one surface and can move in the optical-axis direction, and an optical group C of which optical power is substantially unchangeable.

56

The optical elements Ls can move at the time of zooming.

The one or more optical elements, which can move in the optical-axis direction, can include an optical element having positive refracting power.

When assuming the amount of movement in the entire zoom range of one optical element of the one or more optical elements which can move in the optical-axis direction is d , and the entire length of the entire system is T , the following condition

$$d/T < 0.6$$

can be satisfied.

When moving in the direction different from the optical axis, the principal-point position of an optical group including the multiple optical elements Ld is the optical-axis direction, and the multiple optical elements Ld include an optical element, which can have a shape for moving outside of the optical group.

When assuming that the forward principal-point position and backward principal-point position of an optical group A of the multiple optical groups of which optical power is variable are H_A and H_A' respectively, the forward principal-point position and backward principal-point position of an optical group B closer to the image side than the optical group A are H_B and H_B' , the distance between the object point and the forward principal-point position H_A is eo , the distance between the backward principal-point position H_A' and forward principal-point position H_B is e , the distance between the backward principal-point position H_B' and the image point is ei , and a smaller distance between the distance eo and distance ei is e' , the distance e and distance e' are essentially the same at an arbitrary zoom position.

Here, the following condition

$$0.7 < e/e' < 1.4$$

can be satisfied.

When assuming that of the multiple optical groups of which optical power is variable, the backward principal-point position of the optical group A is H_A' , the forward principal-point position of the optical group B closer to the image side than the optical group A is H_B , the distance between the backward principal-point position H_A' and forward principal-point position H_B in a case in which the power of the entire system is the minimum within the range of the positive optical power of the area where the optical power of the optical group A is variable is et_1 , the distance between the backward principal-point position H_A' and forward principal-point position H_B in a case in which the power of the entire system is the maximum within the range of the positive optical power of the area where the optical power of the optical group A is variable is ew_1 , the distance between the backward principal-point position H_A' and forward principal-point position H_B in a case in which the power of the entire system is the minimum within the range of the negative optical power of the area where the optical power of the optical group A is variable is et_2 , and the distance between the backward principal-point position H_A' and forward principal-point position H_B in a case in which the power of the entire system is the maximum within the range of the negative optical power of the area where the optical power of the optical group A is variable is ew_2 , the following conditions

$$et_1 < ew_1$$

$$et_2 < ew_2$$

can be satisfied.

57

When assuming that an optical group of the multiple optical groups of which optical power is variable is an optical group A, and an optical group closer to the image side than the optical group A is an optical group B, in the event of zooming from the telephoto end toward the wide-angle end, the power of the optical group A changes from positive to negative, the power of the optical group B changes from negative to positive, a zoom position where the optical power of the optical group A matches with the optical power of the optical group B exists in the entire zoom range, and the matched zoom position is closer to the wide-angle side than the middle zoom position within the entire zoom range.

When assuming that of an optical group A and an optical group B closer to the image side than the optical group A of the multiple optical groups of which optical power is variable, a greater one of which the absolute value of the optical power at the wide-angle end is $|\Phi_{gw}|_{\max}$, and a smaller one of which the absolute value of the optical power at the telephoto end is $|\Phi_{gt}|_{\min}$, the following condition

$$|\Phi_{gw}|_{\max} < |\Phi_{gt}|_{\min}$$

can be satisfied.

When assuming that an optical group of the multiple optical groups of which optical power is variable is an optical group A, and an optical group closer to the image side than the optical group A is an optical group B, the maximum value of the absolute value of the optical power between the optical groups A and B in the entire zoom range is $|\Phi|_{\max}$, and the total value of the optical power of the optical group A and optical group B at an arbitrary zoom position is Φ_{AB} , the following condition

$$-|\Phi|_{\max} \leq \Phi_{AB} \leq |\Phi|_{\max}$$

can be satisfied.

When assuming that of the entire zooming range, the maximum value of the values obtained by dividing the maximum value of the absolute value of the image-forming magnification of each of the multiple optical elements Ld by the minimum value is Bd max, and the minimum value of the values obtained by dividing the maximum value of the absolute value of the image-forming magnification of each of the one or more optical elements Ls by the minimum value is Bs min, the following condition

$$Bs_{\min} < Bd_{\max}$$

can be satisfied.

When assuming that the amount of change in the optical-axis direction caused by zooming from the telephoto end toward the wide-angle end of the forward principal-point position H_A of the optical group A of the multiple optical groups of which optical power is variable is ΔH_A , the amount of change in the optical-axis direction caused by zooming from the telephoto end toward the wide-angle end of the forward principal-point position H_B of the optical group B closer to the image side than the optical group A is ΔH_B , greater amount of change between the amount of change ΔH_A and the amount of change ΔH_B is ΔH_d max, and the amount of change of the forward principal-point position of the one or more optical elements Ls is ΔH_s , the following condition

$$\Delta H_s < \Delta H_d \max$$

can be satisfied.

58

An image can be formed on a photoelectric conversion element.

An imaging apparatus can including the zoom optical system, and a photoelectric conversion element for photo-accepting an image formed by the zoom optical system.

While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all modifications, equivalent structures and functions.

This application claims the benefit of Japanese Applications No. 2005-186984 filed Jun. 27, 2005, and No. 2005-186961 filed Jun. 27, 2005, which are hereby incorporated by reference herein in their entirety.

What is claimed is:

1. A zoom optical system comprising:

a plurality of variable power optical units of which optical power changes as magnification varies, wherein the plurality of variable power optical units each has plural optical elements moving in a direction different from an optical axis as magnification varies;

a fixed optical unit of which optical power does not change as magnification varies; and

a moving optical unit which moves as magnification varies, wherein when the maximum value of the absolute value of the optical power in an optical group of the plurality of variable power optical units is $|\Phi_d|_{\max}$ within the entire range of variable power positions, and the maximum value of the absolute value of the optical power of the moving optical unit is $|\Phi_s|_{\max}$ within the entire range of variable power positions, the following condition

$$|\Phi_s|_{\max} < |\Phi_d|_{\max}$$

is satisfied.

2. The zoom optical system according to claim 1, wherein the plurality of variable power optical units each include a rotational asymmetrical surface and have an optical element for moving in the direction different from the optical axis.

3. The zoom optical system according to claim 1, wherein the moving optical unit moves in the direction different from the optical axis as magnification varies.

4. The zoom optical system according to claim 1, wherein the moving optical unit moves along the optical axis as magnification varies.

5. The zoom optical system according to claim 4, wherein when the amount of movement within the entire zoom range of the moving optical unit is d, and the entire length of the entire system is T, the following condition

$$d/T < 0.6$$

is satisfied.

6. The zoom optical system according to claim 1, wherein the moving optical unit is made up of one optical element.

7. The zoom optical system according to claim 1, wherein the sign of the optical power of the moving optical unit is unchangeable over the entire variable power range.

8. The zoom optical system according to claim 1, wherein the moving optical unit has an optical element for moving in the direction different from the optical axis; and

wherein when the maximum value of the absolute value of the amount of shift of an optical element of the plurality of variable optical units within the entire range of variable power positions is $|Dd|_{\max}$, and the maximum value of the absolute value of the amount of shift of the

59

optical element of the moving optical units within the entire range of variable power positions is $|Ds|_{\max}$, the following condition

$$|Ds|_{\max} < |Dd|_{\max}$$

is satisfied.

9. The zoom optical system according to claim 1, wherein the moving optical unit includes an optical element having positive refracting power.

10. The zoom optical system according to claim 1, wherein the plurality of variable power optical units have a first variable power optical unit and a second variable power optical unit; and

wherein when a greater absolute value of the optical power at the wide-angle end of the first and second variable power optical units is $|\Phi_{gw}|_{\max}$, and a smaller absolute value of the optical power at the telephoto end of the first and second optical units is $|\Phi_{gt}|_{\min}$, the following condition

$$|\Phi_{gw}|_{\max} < |\Phi_{gt}|_{\min}$$

is satisfied.

11. The zoom optical system according to claim 1, wherein the plurality of variable power optical units have a first variable power optical unit and a second variable power optical unit; and

wherein when the maximum value of the absolute value of the optical power in the first and second variable power optical units in the entire zoom range is $|\Phi|_{\max}$ and Φ_1 is the first variable power optical unit optical power and Φ_2 is the second variable power optical unit optical power then when the value of sum of the optical powers in an arbitrary zoom position of the first and second variable power optical units is $\Phi_{AB} = \Phi_1 + \Phi_2$, the following condition

$$-|\Phi|_{\max} \leq \Phi_{AB} \leq |\Phi|_{\max}$$

is satisfied.

12. An imaging apparatus comprising: the zoom optical system according to claim 1; and

a photoelectric conversion element for photo-accepting an image to be formed by the zoom optical system.

13. A zoom optical system comprising:

a plurality of variable power optical units of which optical power changes as magnification varies, wherein the plurality of variable power optical units each has plural optical elements moving in a direction different from an optical axis as magnification varies;

a fixed optical unit of which optical power does not change as magnification varies; and

a moving optical unit which moves as magnification varies, wherein the moving optical unit has an optical element for moving in the direction different from the optical axis; and

wherein when the maximum value of the absolute value of the amount of shift of an optical element of the plurality of variable optical units within the entire range of variable power positions is $|Dd|_{\max}$, and the maximum value of the absolute value of the amount of shift of the optical element of the moving optical units within the entire range of variable power positions is $|Ds|_{\max}$, the following condition

$$|Ds|_{\max} < |Dd|_{\max}$$

is satisfied.

60

14. An imaging apparatus comprising: the zoom optical system according to claim 13; and a photoelectric conversion element for photo-accepting an image to be formed by the zoom optical system.

15. A zoom optical system comprising:

a plurality of variable power optical units of which optical power changes as magnification varies, wherein the plurality of variable power optical units each has plural optical elements moving in a direction different from an optical axis as magnification varies;

a fixed optical unit of which optical power does not change as magnification varies; and

a moving optical unit which moves as magnification varies, wherein when the amount of movement within the entire zoom range of the moving optical unit is d , and the entire length of the entire system is T , the following condition

$$d/T < 0.6$$

is satisfied.

16. An imaging apparatus comprising:

the zoom optical system according to claim 15; and a photoelectric conversion element for photo-accepting an image to be formed by the zoom optical system.

17. A zoom optical system comprising:

a plurality of variable power optical units of which optical power changes as magnification varies, wherein the plurality of variable power optical units each has plural optical elements moving in a direction different from an optical axis as magnification varies;

a fixed optical unit of which optical power does not change as magnification varies; and

a moving optical unit which moves as magnification varies, wherein the plurality of variable power optical units have a first variable power optical unit and a second variable power optical unit; and

wherein when the maximum value of the absolute value of the optical power in the first and second variable power optical units in the entire zoom range is $|\Phi|_{\max}$ and Φ_1 is the first variable power optical unit optical power and Φ_2 is the second variable power optical unit optical power then when the value of sum of the optical powers in an arbitrary zoom position of the first and second variable power optical units is $\Phi_{AB} = \Phi_1 + \Phi_2$, the following condition

$$-|\Phi|_{\max} \leq \Phi_{AB} \leq |\Phi|_{\max}$$

is satisfied.

18. An imaging apparatus comprising:

the zoom optical system according to claim 17; and a photoelectric conversion element for photo-accepting an image to be formed by the zoom optical system.

19. A zoom optical system comprising:

a plurality of variable power optical units of which optical power changes as magnification varies, wherein the plurality of variable power optical units each has plural optical elements moving in a direction different from an optical axis as magnification varies;

a fixed optical unit of which optical power does not change as magnification varies; and

a moving optical unit which moves in the direction different from the optical axis as magnification varies.

20. An imaging apparatus comprising: the zoom optical system according to claim 19; and a photoelectric conversion element for photo-accepting an image to be formed by the zoom optical system.