

US007463786B2

(12) **United States Patent**
Kim et al.

(10) **Patent No.:** **US 7,463,786 B2**
(45) **Date of Patent:** **Dec. 9, 2008**

(54) **METHOD OF REDUCING A BLOCKING ARTIFACT WHEN CODING MOVING PICTURE**

(75) Inventors: **Hyun Mun Kim**, Rockville, MD (US); **Jong Beom Ra**, Taejeon-si (KR); **Sung Deuk Kim**, Taejeon-si (KR); **Young Su Lee**, Seoul (KR)

(73) Assignee: **LG Electronics Inc.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **12/105,332**

(22) Filed: **Apr. 18, 2008**

(65) **Prior Publication Data**

US 2008/0193041 A1 Aug. 14, 2008

Related U.S. Application Data

(63) Continuation of application No. 11/770,260, filed on Jun. 28, 2007, now Pat. No. 7,391,921, which is a continuation of application No. 09/506,728, filed on Feb. 18, 2000, now Pat. No. 7,239,755, which is a continuation of application No. 09/010,446, filed on Jan. 22, 1998, now Pat. No. 6,028,967.

(30) **Foreign Application Priority Data**

Jul. 30, 1997 (KR) 1997-36231

(51) **Int. Cl.**

G06T 5/00 (2006.01)

H03M 13/47 (2006.01)

(52) **U.S. Cl.** **382/268**; 382/261; 375/240.27; 375/240.29

(58) **Field of Classification Search** 382/268, 382/269, 260, 261, 275, 205, 251; 375/240.24, 375/240.27, 240.29, 240.26; 358/463, 3.26; 348/420.1, 607

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,903,138 A 2/1990 Aragaki

(Continued)

FOREIGN PATENT DOCUMENTS

EP 808068 A2 * 11/1997

(Continued)

OTHER PUBLICATIONS

G. de Haan et al.; "IC For Motion-Compensation 100Hz TV with Natural-Motion Movie-Mode"; *IEEE Transactions On Consumer Electronics*, vol. 42; pp. 165-174; Feb. 1996.

Yung-Kai Lai et al.; "Image Enhancement for Low Bit-rate JPEG and MPEG Coding via Postprocessing"; *Proc. SPIE*, vol. 2727; pp. 1484-1494; Feb. 1996.

(Continued)

Primary Examiner—Scott A Rogers


(74) *Attorney, Agent, or Firm*—Fish & Richardson P.C.

(57) **ABSTRACT**

A method of coding a moving picture is provided that reduces blocking artifacts. The method can include defining a plurality of defining pixels S_0 , S_1 , and S_2 , which are centered around a block boundary. If a default mode is selected then frequency information of the surroundings of the block boundary is obtained. A magnitude of a discontinuous component in a frequency domain belonging to the block boundary is adjusted based on a magnitude of a corresponding discontinuous component selected from a pixel contained entirely within a block adjacent the block boundary. The frequency domain adjustment is then applied to a spatial domain. Or, a DC offset mode can be selected to reduce blocking artifacts in smooth regions where there is little motion.

2 Claims, 3 Drawing Sheets

(block boundary)



U.S. PATENT DOCUMENTS

4,941,043	A	7/1990	Jass	
5,229,864	A *	7/1993	Moronaga et al.	382/261
5,337,088	A	8/1994	Honjo	
5,422,964	A	6/1995	Devimeux	
5,454,051	A	9/1995	Smith	
5,590,064	A	12/1996	Astle	
5,629,778	A	5/1997	Reuman	
5,677,736	A	10/1997	Suzuki et al.	
5,680,477	A	10/1997	Asada	
5,787,204	A	7/1998	Fukuda	
5,796,875	A	8/1998	Read	
5,852,682	A	12/1998	Kim	
5,903,679	A	5/1999	Park	
5,937,101	A	8/1999	Jeon	
6,028,967	A	2/2000	Kim	
6,151,420	A	11/2000	Wober	
6,240,135	B1	5/2001	Kim	
6,317,522	B1	11/2001	Rackett	
6,320,905	B1	11/2001	Konstantinides	
6,614,946	B1	9/2003	Edgar	
6,724,944	B1	4/2004	Kalevo	
7,003,170	B1	2/2006	Martucci	
7,003,174	B2	2/2006	Kryukov	
7,031,393	B2	4/2006	Kondo	
7,054,503	B2	5/2006	Ishikawa	
7,209,594	B1	4/2007	Martucci	
7,233,706	B1	6/2007	Kim	
7,289,682	B2	10/2007	Kim	
7,305,142	B2	12/2007	Kim	
7,397,853	B2 *	7/2008	Kwon et al.	375/240.03
2003/0138160	A1	7/2003	Ishikawa	
2003/0194013	A1	10/2003	Alvarez	
2005/0243911	A1	11/2005	Kwon	

2005/0243912	A1	11/2005	Kwon
2005/0243913	A1	11/2005	Kwon
2005/0243914	A1	11/2005	Kwon
2005/0243915	A1	11/2005	Kwon
2005/0243916	A1	11/2005	Kwon
2005/0244063	A1	11/2005	Kwon
2006/0274959	A1	12/2006	Piastowski

FOREIGN PATENT DOCUMENTS

JP	2002-232889	8/2002
WO	WO 2096117 A1 *	11/2002

OTHER PUBLICATIONS

Shigenobu Minami et al.; "An Optimization Approach for Removing Blocking Effects in Transform Coding"; *IEEE Transactions on Circuits and Systems for Video Technology*, vol. 5, No. 2; pp. 74-82; Apr. 1995.

Yasuyuki Nakajima et al.; "A PEL Adaptive Reduction of Coding Artifacts for MPEG Video Signals"; *IEEE*; pp. 928-932; 1994.

Taner Özeelik et al.; "Image and Video Compression Algorithms Based on Recovery Techniques Using Mean Field Annealing"; *Proceedings of the IEEE*, vol. 83, No. 2; pp. 304-316; Feb. 1995.

Gary J. Sullivan et al.; "Motion Compensation for Video Compression Using Control Grid Interpolation"; *IEEE International Conference*; pp. 2713-2716; 1991.

Yongyi Yang et al.; "Regularized Reconstructions to Reduce Blocking Artifacts of Block Discrete Cosine Transform Compressed Images"; *IEEE Transactions on Circuits and Systems for Video Technology*; vol. 3, No. 6; pp. 421-432; Dec. 1993.

Avideh Zahor; "Iterative Procedures for Reduction of Blocking Effects in Transform Image Coding"; *IEEE Transaction on Circuits and Systems for Video Technology*, vol. 2, No. 1; pp. 91-95; Mar. 1992.

* cited by examiner

FIG. 1

(block boundary)




FIG. 2





FIG. 3



METHOD OF REDUCING A BLOCKING ARTIFACT WHEN CODING MOVING PICTURE

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 11/770,260, filed Jun. 28, 2007, which is a continuation of U.S. application Ser. No. 09/506,728, filed Feb. 18, 2000, now U.S. Pat. No. 7,239,755, which is a continuation of U.S. application Ser. No. 09/010,446, filed Jan. 22, 1998, now U.S. Pat. No. 6,028,967, which claims the benefit of a foreign priority application filed in KOREA on Jul. 30, 1997, as Ser. No. 36231/1997. This application claims priority to all of these applications, and all of these applications are incorporated by reference.

TECHNICAL FIELD

The present invention relates to a moving picture process, and in particular to a method for processing blocks of a moving picture to increase a compression ratio and to improve coding efficiency.

BACKGROUND

To efficiently compress a time variable video sequence, redundancy in the temporal domain as well as in the two dimensional spatial domain must be reduced. MPEG uses a discrete cosine transform (DCT) to reduce the redundancy in the two dimensional spatial domain and a motion compensation method to reduce the redundancy in the temporal domain.

The DCT is a method of reducing the correlativity between data through a two dimensional spatial transformation. Each block in a picture is spatially transformed using the DCT after the picture is divided into blocks. Data that has been spatially transformed tends to be driven to a certain direction. Only a group of the data driven in the certain direction is quantized and transmitted.

Pictures, which are consecutive in the temporal domain, form motions of a human being or an object at the center of the frame. This property is used to reduce the redundancy of the temporal domain in the motion compensation method. A volume of data to be transmitted can be minimized by taking out a similar region from the preceding picture to fill a corresponding region, which has not been changed (or has very little change), in the present picture. The operation of finding the most similar blocks between pictures is called a motion estimation. The displacement representing a degree of motion is called a motion vector. MPEG uses a motion compensation-DCT method so that the two methods combine.

When a compression technique is combined with a DCT algorithm, the DCT transform is usually performed after input data is sampled in a unit size of 8×8 , and the transform coefficients are quantized with respect to a visual property using quantization values from a quantization table. Then, the data is compressed through a run length coding (RLC). The data processed with the DCT is converted from a spatial domain to a frequency domain and compressed through the quantization with respect to the visual property of human beings, not to be visually recognized. For example, since eyes of human beings are insensitive to a high frequency, a high frequency coefficient is quantized in a large step size. Thus, a quantization table is made according to external parameters,

such as a display characteristic, watching distance, and noise, to perform an appropriate quantization.

For the quantized data, the data having a relatively high frequency is coded with a short code word. The quantized data having a low frequency is coded with a long code word. Thus, the data is finally compressed.

In processing a moving picture as discussed above, blocks are individually processed to maximize the compression ratio and coding efficiency. However, the individual process causes blocking artifacts that disturb the eyes of human beings at boundaries between blocks.

Accordingly, various methods for reducing a blocking artifact in a coding system, which individually processes blocks, are presented. For example, attempts to reduce the blocking artifact by changing processes of coding and decoding have been implemented. However, this method of changing the processes of coding and decoding increases the amount of bits to be transmitted.

Another method for reducing the blocking artifact is based on the theory of projection onto convex sets (POCS). However, this method is applied to only a still picture because of an iteration structure and convergence time.

The blocking artifact is a serious problem in a low transmit rate moving picture compression. Since a real-time operation is necessary in coding and decoding a moving picture, it is difficult to reduce the blocking artifact with a small operation capacity.

Consequently, the related art methods involve various problems and disadvantages when reducing a blocking artifact created in coding a moving picture. A calculation for performing an algorithm is complicated, and the calculation amount and time become correspondingly large. Further, the blocking artifacts are not reduced in either complex regions or smooth regions in a picture. In addition, the amount of bits to be transmitted increases.

The above references are incorporated by reference herein where appropriate for appropriate teachings of additional or alternative details, features and/or technical background.

SUMMARY

An object of the present invention is to provide a method for reducing a blocking artifact appearing when coding a moving picture that substantially obviates one or more of the limitations and disadvantages of the related art.

Another object of the present invention is to provide an MPEG-4 video coding method that reduces a blocking artifact in a real-time moving picture using a frequency property around boundaries between blocks.

A further object of the present invention is to provide a method for reducing a blocking artifact that increases a compression ration and increases a coding efficiency.

To achieve these and other advantages in whole or in parts, and in accordance with the purpose of the present invention as embodied and broadly described, a blocking artifact reduction method includes defining pixels centered around a block boundary and setting a default mode. Frequency information of the surroundings of the block boundary is obtained for each pixel using a 4-point kernel. A magnitude of a discontinuous component that belongs to the block boundary is adjusted in a frequency domain to a minimum value of a magnitude of a discontinuous component that belongs to the surrounding of the block boundary. The adjusting operation is then applied to a spatial domain. In addition, a DC offset mode is established, and in the DC offset mode the blocking artifact is also reduced, for example, in a smooth region where there is little motion.

Additional advantages, objects, and features of the invention will be set forth in part in the description which follows and in part will become apparent to those having ordinary skill in the art upon examination of the following or may be learned from practice of the invention. The objects and advantages of the invention may be realized and attained as particularly pointed out in the appended claims.

DESCRIPTION OF DRAWINGS

The invention will be described in detail with reference to the following drawings in which like reference numerals refer to like elements wherein:

FIG. 1 is a diagram that illustrates horizontal and vertical block boundaries;

FIG. 2 is a diagram that illustrates a 4-point DCT kernel; and,

FIG. 3 is a flow chart that illustrates a preferred embodiment of a method that reduces a blocking artifact when coding a moving picture according to the present invention.

DETAILED DESCRIPTION

Reference will now be made to preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings. FIG. 1 illustrates typical horizontal and vertical block boundaries.

As shown in FIG. 1, in the dimensional image formed with respective four points of S_0 , S_1 , and S_2 located around the block boundary, S_1 and S_2 are individually processed with a block-unit compression method. Thus, S_1 and S_2 are not influenced by the blocking artifact. However, S_0 is located across a block boundary. Thus, S_0 is directly influenced by the blocking artifact. The blocking artifact appears at the boundary between fixed block patterns in the form of a line of discontinuity.

Preferred embodiments of the present invention use, for example, a frequency property to preserve complex regions at block boundaries. The frequency property around the boundary is preferably obtained by using a 4-point DCT kernel, which can be easily calculated. However, the present invention is not intended to be limited to this. In this case, the complex region at a block boundary can be effectively processed by extending the smoothness of a picture from a frequency domain to a spatial domain.

As shown in FIG. 1, S_0 is located across the block boundary. Thus, S_0 is directly influenced by the blocking artifact. To reduce the blocking artifact from S_0 , a first preferred embodiment of the present invention uses frequency information in S_1 and S_2 . The blocking artifact can be removed from S_0 by replacing the frequency component in S_0 , which is influenced by the blocking artifact, with the frequency components of S_1 and S_2 . In other words, S_0 contains a discontinuity. However, S_1 and S_2 , which are completely included inside respective blocks, are not related to the discontinuity. Since S_1 and S_2 are not involved with the discontinuity at a block boundary, S_1 and S_2 can accurately represent features of the respective neighboring blocks.

When images change smoothly, image features of S_0 , S_1 and S_2 are similar. This means that frequency domains of S_0 , S_1 and S_2 have similar features. The preferred embodiments use a DCT, or the like as a frequency analysis tool. DCT is widely used in an image compression technique.

FIG. 2 is a diagram illustrating a 4-point DCT basis. As shown in FIG. 2, the 4-point DCT kernel basis has symmetric and anti-symmetric properties around the center of 4 points. In FIG. 2, $a_{0,0}$, $a_{1,0}$, $a_{2,0}$, and $a_{3,0}$ are defined as the 4-point

DCT coefficients of S_0 . Although both $a_{2,0}$, and $a_{3,0}$ are high frequency components, $a_{2,0}$ is symmetric, and $a_{3,0}$ is anti-symmetric around the center.

The center of S_0 is located at a block boundary as shown in FIG. 1. Thus, a factor directly affecting the block discontinuity is not the symmetric component but the anti-symmetric component. The magnitude of $a_{3,0}$ in a frequency domain is thus adjusted based on the anti-symmetric component being a major factor affecting the discontinuity. Accordingly, the proper adjustment of $a_{3,0}$ is directly related to the reduction of block discontinuity in the spatial domain. Reduction of the block discontinuity will now be described.

In a first preferred embodiment, the magnitude of $a_{3,0}$ is replaced with the minimum value of the magnitudes of $a_{3,1}$ and $a_{3,2}$, which are contained in a single block in an area surrounding a block boundary. By doing this, a large blocking artifact that appears when one side of the block boundary to be processed is smooth can be reduced. For a complex image where both S_1 and S_2 are the objects of motion (i.e., all the values of the magnitudes of $a_{3,0}$, $a_{3,1}$ and $a_{3,2}$ are large), there is little influence on the block boundary.

A method for reducing a blocking artifact in a default mode is as follows:

$$v_3' = v_3 - d;$$

$$v_4' = v_4 + d; \text{ and}$$

$$d = \text{CLIP}(c_2(a_{3,0}' - a_{3,0}) / c_{3,0}, (v_3 - v_4) / 2) * \delta(|a_{3,0}| < QP)$$

In the method, $a_{3,0}' = \text{SIGN}(a_{3,0}) * \text{MIN}(|a_{3,0}|, |a_{3,1}|, |a_{3,2}|)$, and q is the component of DCT kernel. The condition $|a_{3,0}| < QP$ is used to count the influence of the quantization parameter on the blocking artifact. The $|a_{3,0}| < QP$ condition also prevents over-smoothing when the blocking artifact is not very serious. The clipping operation on the compensated value prevents the direction of the gradient at the boundary from being large or changed in an opposite direction. The boundary pixel values, v_3 and v_4 , are replaced with v_3' and v_4' . QP is the quantization parameter of the macroblock where v_4 belongs. Values, c_1 , c_2 , and c_3 are kernel constants used in the 4-point DCT. To simplify an equation according to a first preferred embodiment of the present invention, the values of c_1 and c_2 are approximated to an integer, and the value of c_3 is approximated to a multiple of 2. The values of a_1 , a_2 , and a_3 are evaluated from the simple inner product of the DCT kernel and pixels, S_0 , S_1 , and S_3 .

$$a_{3,0} = ([c_1 - c_2 \ c_2 - c_1] * [v_2 \ v_3 \ v_4 \ v_5]^T) / c_3$$

$$a_{3,0} = ([c_1 - c_2 \ c_2 - c_1] * [v_0 \ v_1 \ v_2 \ v_3]^T) / c_3$$

$$a_{3,0} = ([c_1 - c_2 \ c_2 - c_1] * [v_4 \ v_5 \ v_6 \ v_7]^T) / c_3$$

Such processes are performed in both horizontal and vertical block boundaries. In this manner, the blocking artifacts in the whole frame can be reduced.

The first embodiment reduces a blocking artifact in the default mode. However, in the default mode, only the boundary pixel values, v_3 and v_4 , are compensated. Thus, the default mode is not sufficient to reduce the blocking artifact in a very smooth region, such as a setting in a picture.

To reduce the blocking artifact in the smooth region, a second preferred embodiment of a method for reducing blocking artifacts in a moving picture according to the present invention includes a DC offset mode. The method in the DC offset mode is as follows:

$$v_3' = v_3 - d;$$

$$v_4' = v_4 + d;$$

5

$$v_2' = v_2 - d_2;$$

$$v_5' = v_5 + d_2;$$

$$v_1' = v_1 - d_3; \text{ and}$$

$$v_6' = v_6 + d_3.$$

In the second preferred embodiment,

$$d_1 = (3(v_3 - v_4)/8) * \delta(|a_{3,0}| < QP)$$

$$d_2 = (3(v_3 - v_4)/16) * \delta(|a_{3,0}| < QP), \text{ and}$$

$$d_3 = (3(v_3 - v_4)/32) * \delta(|a_{3,0}| < QP).$$

The blocking artifact in the region where there is little motion, or which is a very small setting, is reduced through the above-described method or the like in the DC offset mode. An appropriate mode between the DC offset mode and default mode can be determined using the following conditional expression:

$$\text{If } (v_0 == v_1 \& \& v_1 == v_2 \& \& v_2 == v_3 \& \& v_3 == v_4 \& \& v_4 == v_5 \& \& v_5 == v_6 \& \& v_6 == v_7)$$

DC offset mode is applied; Else Default mode is applied.

When the DC offset mode or the default mode is selected according to the above conditional expression, the blocking artifacts are reduced in each mode. After determining the proper mode between the DC offset mode and the default mode, the block discontinuity at the boundary is compensated to form a consecutive line, which reduces the blocking artifact. In the second preferred embodiment, the DC offset mode and the default mode are set using S_0 , S_1 and S_2 . However, the present invention is not intended to be limited to this. Alternative sets of points or the like can be used.

An exemplary method for reducing a blocking artifact when coding a moving picture, according to the second preferred embodiment of the present invention, is described with reference to the flow chart shown in FIG. 3.

After beginning in FIG. 3, control continues to step 101. In step 101, a plurality of pixels, S_0 , S_1 , and S_2 are defined centering around a block boundary. From step 101, control continues to step 102. In step 102, if a mode is selected, a default mode is set, and control continues to step 103.

In step 103, frequency information of the surroundings of the block boundary for each pixel is obtained using, for example, the 4-point DCT kernel. From step 103, control continues to step 104. In step 104, the magnitude of discontinuous component belonging to the block boundary is replaced with the minimum magnitude of the discontinuous components belonging to the surroundings of the block boundary in the frequency domain. From step 104, control continues to step 105, where the adjusting operation is applied to the spatial domain. The default mode is effective in reducing the blocking artifact in a complex region of a picture. However, the default mode is less successful in a smooth region such as a setting in a picture.

6

Therefore, in a smooth region it is necessary to reduce the blocking artifact in another mode, the DC offset mode. In step 106, the DC offset mode is established. From step 106, control continues to step 107. In step 107, the blocking artifact in the region where there is little motion, such as a setting, is reduced. From step 107, the process ends. Thus, the overall blocking artifacts can be reduced according to the preferred embodiments.

As described above, the blocking artifact reduction methods according to the preferred embodiments of the present invention have various advantages and effects. The blocking artifact is more easily and effectively reduced using features of the frequency domain. The preferred embodiments provide a visually finer quality of a picture by reducing the blocking artifacts in both the complex and smooth regions. Further, calculations are simple. Accordingly, the amount of bits does not increase.

The foregoing embodiments are merely exemplary and are not to be construed as limiting the present invention. The present teaching can be readily applied to other types of apparatuses. The description of the present invention is intended to be illustrative, and not to limit the scope of the claims. Many alternatives, modifications, and variations will be apparent to those skilled in the art.

What is claimed is:

1. A computer-implemented method comprising:
 - obtaining blocks that each include multiple pixels, a first block being separated from a neighboring second block by a block boundary;
 - obtaining information on first and second non-overlapping groups of n successive pixels of the first and second blocks, respectively, n being two or greater;
 - obtaining information on a third group of n pixels successive pixels, the third group overlapping the first and second groups, n being two or greater;
 - comparing the information of the third group with quantization parameter information; and
 - adjusting the n successive pixels of the third group based on the comparison.
2. A device comprising a deblocking filter configured to:
 - obtain blocks that each include multiple pixels, a first block being separated from a neighboring second block by a block boundary,
 - obtain information on first and second non-overlapping groups of n successive pixels of the first and second blocks, respectively, n being two or greater,
 - obtain information on a third group of n pixels successive pixels, the third group overlapping the first and second groups, n being two or greater,
 - compare the information of the third group with quantization parameter information, and
 - adjust the n successive pixels of the third group based on the comparison.

* * * * *