

US007466675B2

(12) **United States Patent**
Hart et al.

(10) **Patent No.:** **US 7,466,675 B2**
(45) **Date of Patent:** **Dec. 16, 2008**

(54) **METHOD AND APPARATUS FOR SUPPORTING A REDUCED RESOURCE DORMANT STATE FOR PACKET DATA**

(75) Inventors: **Thomas B. Hart**, West Dundee, IL (US);
Jay Jayapalan, Buffalo Grove, IL (US)

(73) Assignee: **Motorola, Inc.**, Schaumburg, IL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 930 days.

(21) Appl. No.: **10/759,654**

(22) Filed: **Jan. 16, 2004**

(65) **Prior Publication Data**

US 2005/0073969 A1 Apr. 7, 2005

Related U.S. Application Data

(60) Provisional application No. 60/447,656, filed on Feb. 14, 2003.

(51) **Int. Cl.**
H04B 7/216 (2006.01)

(52) **U.S. Cl.** **370/329; 370/395.2; 370/431; 370/400**

(58) **Field of Classification Search** None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,654,360	B1	11/2003	Abrol	
6,781,999	B2	8/2004	Eyuboglu et al.	
6,965,588	B2 *	11/2005	Schmidt et al.	370/338
7,031,291	B2 *	4/2006	Chen et al.	370/342
7,154,903	B2 *	12/2006	Sivalingham	370/429
2002/0186696	A1 *	12/2002	Lim	370/395.52
2003/0128676	A1 *	7/2003	Lee	370/328


* cited by examiner

Primary Examiner—Wing F Chan
Assistant Examiner—Brian Roberts

(57) **ABSTRACT**

The present embodiments address the need for a reduced resource dormant state for packet data systems (100) that substantially provides the benefits of current dormant mode operation but without the resource maintenance costs. After a period of MS session inactivity, PCF resources, certain PDSN resources, and the PCF-PDSN tunnel are released in order to enter a new reduced resource dormant state. When data arrives for a reduced-resource-dormant MS (101), PDSN-initiated messaging (303) is used to trigger the re-establish PCF resources, a PDSN-PCF tunnel connection (320), and released PDSN resources.

19 Claims, 5 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3





FIG. 4

**FIG. 5**

1

METHOD AND APPARATUS FOR SUPPORTING A REDUCED RESOURCE DORMANT STATE FOR PACKET DATA

REFERENCE(S) TO RELATED APPLICATION(S)

The present application claims priority from provisional application Ser. No. 60/447,656, entitled "METHOD AND APPARATUS FOR SUPPORTING A REDUCED RESOURCE DORMANT STATE FOR PACKET DATA," filed Feb. 14, 2003, which is commonly owned and incorporated herein by reference in its entirety.

FIELD OF THE INVENTION

The present invention relates generally to wireless communication systems and, in particular, to supporting a reduced resource dormant state for packet data.

BACKGROUND OF THE INVENTION

In IS-2000 packet data systems, a mobile station (MS) needs to have a packet data session (as defined by IS-835 P.S0001-0) already established and be in either an active or a dormant state to receive data packets. While radio resources and the selectors may be released in a dormant state, there are still significant static resources maintained in the packet control function (PCF) and the packet data serving node (PDSN) devices. Current standards work in 3GPP2 is defining an "Always-On" feature in which MSs can stay in a dormant state for very long periods of time. As more MSs are deployed with this type of feature and more "push" or "telemetry" type data applications (i.e., applications sending unsolicited data such as stock quotes, sports scores, etc.) are developed, maintaining the static resources, as is done presently, for numerous dormant MSs and for long periods of time is likely to become equipment and cost prohibitive. Therefore, a need exists for an apparatus and method to support a reduced resource dormant state for packet data that substantially provides the benefits of present dormant mode operation without the resource maintenance costs.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram depiction of a communication system in accordance with an embodiment of the present invention.

FIG. 2 is a block diagram depiction of the PCF and PDSN of the communication system in accordance with an embodiment of the present invention.

FIG. 3 is a messaging flow diagram of messaging performed in accordance with an embodiment of the present invention.

FIG. 4 is a logic flow diagram of functions performed by a PCF in accordance with an embodiment of the present invention.

FIG. 5 is a logic flow diagram of functions performed by a PDSN in accordance with an embodiment of the present invention.

DETAILED DESCRIPTION OF EMBODIMENTS

The present embodiments address the need for a reduced resource dormant state for packet data systems that substantially provides the benefits of current dormant mode operation but without the resource maintenance costs. After a period of MS session inactivity, PCF resources, certain PDSN

2

resources, and the PCF-PDSN tunnel are released in order to enter a new reduced resource dormant state. When data arrives for a reduced-resource-dormant MS, PDSN-initiated messaging is used to trigger the re-establish PCF resources, a PDSN-PCF tunnel connection, and released PDSN resources.

The disclosed embodiments can be more fully understood with reference to FIGS. 1-6. FIG. 1 is a block diagram depiction of a communication system 100 in accordance with a first embodiment of the present invention. Communication system 100 is a well-known Code Division Multiple Access (CDMA) system, specifically a cdma2000 system, which is based on the Telecommunications Industry Association/Electronic Industries Association (TIA/EIA) standard IS-2000, suitably modified to implement the present invention. (The TIA/EIA can be contacted at 2001 Pennsylvania Ave. NW, Washington, D.C. 20006). Alternative embodiments of the present invention may be implemented in other wireless technologies that include components equivalent to PCFs and PDSNs.

Communication system 100 includes network entities such as radio access network (RAN) IP network 120, base transceiver station (BTS) 110, base station controller/PCF (BSC/PCF) 111, PDSN/foreign agent (PDSN/FA) 112, mobile switching center (MSC) 113, router 114, IP network 121, application server or Correspondent Node (CN) 115, home agent (HA) 116, and Authentication, Authorization and Accounting (AAA) server 117. Communication system 100 also includes remote units such as mobile station (MS) 101. However, the present invention is not limited to MSs that are mobile. For example, an MS may comprise a desktop computer wirelessly connected to the RAN. FIG. 2 is a more detailed depiction of PCF 111 and PDSN 112 of communication system 100 in accordance with a first embodiment of the present invention.

Those skilled in the art will recognize that FIG. 1 and FIG. 2 do not depict all of the network equipment nor remote units necessary for system 100 to operate but only those system blocks and logical entities particularly relevant to the description of embodiments of the present invention. Those skilled in the art are aware of the many ways each of these entities can be implemented and/or purchased from wireless networking companies such as "MOTOROLA."

PCF 111 and PDSN 112 comprise network interfaces 202 and 212 and processors 201 and 211, both respectively. Those skilled in the art are aware of the many ways these entities, both physical and logical, can be either implemented or purchased. Network interfaces, for example, typically comprise components such as communications microprocessors, memory, and/or logic circuitry designed to implement algorithms that have been expressed as computer instructions and/or in circuitry. Likewise, processors typically comprise microprocessors, various memory devices, and/or logic circuitry designed to implement algorithms that have been expressed as computer instructions and/or in circuitry. Given an algorithm or a logic flow, those skilled in the art are aware of the many design and development techniques available to implement communications platforms such as PCFs and PDSNs to perform the given logic.

In a first embodiment of the present invention, a known CDMA2000 PCF and a known CDMA2000 PDSN is adapted using known telecommunications design and development techniques to implement the PCF and PDSN aspects of the present invention. The result is a PCF that performs the method described with respect to FIG. 4 and a PDSN that performs the method described with respect to FIG. 5. Those skilled in the art will recognize that the PCF and PDSN

aspects of the present invention may be implemented in and across various physical components, whether co-located or not, of system **100** and are not meant to be limited to PCF and PDSN devices physically.

In general, the present reduced resource dormant state (RRD) provides the capability to deliver data traffic routed by IP address to an idle (as viewed by the infrastructure network) mobile station. This capability is applicable to mobile terminals that utilize Simple IP, Mobile IP, or Proxy Mobile IP. For a mobile that is not actively exchanging data, RRD provides the capability for the data network to release most data resources (R-P tunnel, PPP session, data buffers, etc.) after the session transitions to the RRD state. The session at the mobile can be in an idle or dormant state. The network retains the MIP tunnel and enough context information at the serving system to re-establish the data connection when a new packet of data arrives for the mobile. Once the data connection has been re-established the data packet can be delivered.

Mobiles capable of RRD initiate a data call to establish the PDSN maintained context and then constantly monitor the paging channel to respond to pages for packet data when they are idle or dormant. The PDSN/FA will forward (for Mobile IP) or initiate (for Proxy Mobile IP) a Mobile IP registration to set up HA to PDSN/FA tunnels. As the mobiles move to an area served by a new PDSN, new Mobile IP Registration occurs, which triggers setting up a new HA-to-PDSN/FA tunnel. Mobile IP lifetime renewal also consumes air interface resources. In RRD, this could be avoided by marking the mobile as always on. (Current standards depend on Mobile IP lifetime for always on). In RRD, the network may consider the mobile to be idle when network data resources have been released and only context information is retained, while the mobile may remain in dormant mode to accomplish packet zone triggered data registrations.

Operation of a first embodiment occurs substantially as follows with reference to the FIGS. FIG. **3** is a messaging flow diagram of messaging performed in accordance with the first embodiment of the present invention. Through its registration process, MS **101** is assigned a traffic channel and established in an active data session. While this session is active, processor **211** of PDSN **112** maintains session context information for MS **101**. In the first embodiment, this session context information comprises session information such as a MIP tunnel binding, a mobile-identifier-to-IP-address mapping (e.g., MIN-to-IP or IMSI-to-IP), a PPP context for MS **101**, PCF **111**'s address, and an A10 tunnel mapping. When PDSN processor **211** receives data for MS **101** via network interface **212**, processor **211** forwards the data via network interface **212**, a PDSN-PCF A10 tunnel, network **120**, and network interface **202** to PCF processor **201**. PCF processor **201**, which also maintains session resources for MS **101**, receives the data and forwards it on to MS **101**.

After a period of session inactivity (e.g., a predetermined period of 5 minutes), PCF processor **201** releases the PDSN-PCF tunnel for this session and all the other session resources. Likewise, PDSN processor **211** also releases the PDSN-PCF tunnel for this session and a portion of its session context information. Specifically, PDSN processor **211** releases session context information such as PPP context information maintained for MS **101**, PCF **111**'s address, and the A10 tunnel mapping.

In the first embodiment, unlike PCF **111**, PDSN **112** does retain some session context information for MS **101**. Retained session information includes the MIP tunnel binding and the mobile-identifier-to-IP-address mapping. In alternative embodiments, however, the PCF address may be retained as well as some of the PPP context information in

order to save PPP-renegotiation time. PDSN processor **211** retains the MIP tunnel binding for the duration of the MIP Registration Lifetime or longer for mobiles designated as 'always on' capable. However, to limit the proliferation of old mappings at the PDSN, these mappings may expire based on long duration timers (e.g., MIP Registration Lifetime set to 6-12 hours). Thus, mobiles may be required to periodically initiate a data registration even if not crossing a packet zone. The PDSN could then refresh the MIP tunnel and maintain the mobile-identifier-to-IP-address mapping. To assist in this, RRD mobiles may be paged when their timer is about to expire.

When the session is in the RRD state and PDSN processor **211** receives new data (**302**) for MS **101** (from CN **115**, e.g.), PDSN processor **211** sends (**303**) a reconnection request for establishment of a new tunnel. This reconnection request sent to PCF **111** is noteworthy because it is initiated by PDSN **112**. It is a new message that will be under consideration as a new A11 message (i.e., the A11 Reconnection Request message). The reconnection request will indicate to PCF **111** that the request pertains to MS **101**.

In response to receiving the reconnection request, PCF processor **201** requests (**305**) BSC **111** to initiate the paging of MS **101**. This request takes the form of an A9-BS Service Request message in the first embodiment. Also, to indicate that the reconnection request is being serviced, PCF processor **201** sends a reconnection response (**304**) to PDSN **112**. Like the reconnection request, the reconnection response is a new message that will be under consideration as a new A11 message (i.e., the A11 Reconnection Response message). When received by PDSN **112**, this response serves as an acknowledgment of the PDSN's reconnection request.

As depicted in messaging flow diagram **300**, the A9-BS Service Request message triggers a messaging sequence that re-establishes a traffic channel for MS **101** and a request to PDSN processor **211** from PCF processor **201** to setup a new tunnel for MS **101**'s session. After PDSN **112** and PCF **111** setup (**320**) the new tunnel, PDSN processor **211** establishes a new PPP session with MS **101** through PPP renegotiation messaging (**330**). For mobile IP, MS **101** signals to renew its MIP registration, and PDSN **112** and HA **116** exchange subscriber authentication and MIP refresh messaging (**331**). Once the PPP session is established PDSN **112** can forward any buffered data (**333**) to MS **101** via the new tunnel and PCF **111**. An active data connection now exists between MS **101** and PDSN/FA **112**.

FIG. **4** is a logic flow diagram of functions performed by a PCF in accordance with the first embodiment of the present invention. Logic flow **400** begins with the PCF supporting an active data session for an MS by maintaining (**402**) session resources, including a PDSN-PCF tunnel through which data for the MS is received (**404**). The PCF continues to maintain session resources and receive data for the MS until a predefined period of inactivity (5 minutes, e.g.,) elapses (**406**). At this point, the PCF releases (**408**) the PDSN-PCF tunnel and the other resources it has been maintaining for the session.

At some point after releasing the resources, the PCF may receive (**410**) a reconnection request from the PDSN for the MS. In response to this request but not necessarily in the order depicted in FIG. **4**, the PCF sends (**412**) a reconnection response to the PDSN and requests (**414**) a BSC to initiate the paging of the MS. After the MS responds and is assigned a traffic channel, the PCF initiates the messaging required to setup a new PDSN-PCF tunnel. In the first embodiment, the PCF sends (**416**) an A11-Registration Request message to the PDSN to setup the new tunnel. Eventually, the PCF receives (**418**) data for the MS via the new PDSN-PCF tunnel.

FIG. 5 is a logic flow diagram of functions performed by a PDSN in accordance with the first embodiment of the present invention. Logic flow 500 begins with the PDSN supporting an active data session for an MS by maintaining (502) session context information and a PDSN-PCF tunnel through which data for the MS is forwarded (504) to a PCF. The PDSN continues to maintain session context information and forward data for the MS until a predefined period of inactivity (5 minutes, e.g.,) elapses (506). At this point, the PDSN releases (508) the PDSN-PCF tunnel and some of the session context information it has been maintaining, such as the tunnel mapping and PPP context information.

At some point after releasing the PDSN-PCF tunnel, the PDSN may receive (510) new data for the MS. Buffering the data until a connection to the MS can be established, the PDSN sends (512) a reconnection request for the MS to the PCF. In response to this request, the PDSN should receive a reconnection response from the PCF to indicate that the request is being serviced as well as a request to setup a new PDSN-PCF tunnel. The PDSN then performs messaging to setup (514) the new tunnel and to establish a new PPP session with the MS. Once the new PPP session is established, the PDSN can forward (516) any buffered data for the MS to the PCF via the new PDSN-PCF tunnel. Also, since an active data connection now exists between the MS and PDSN, subsequent data for the MS can simply be forwarded via the PDSN-PCF tunnel as described with respect to blocks 502 and 504.

In the foregoing specification, the present invention has been described with reference to specific embodiments. However, one of ordinary skill in the art will appreciate that various modifications and changes may be made without departing from the spirit and scope of the present invention as set forth in the appended claims. Accordingly, the specification and drawings are to be regarded in an illustrative rather than a restrictive sense, and all such modifications are intended to be included within the scope of the present invention. In addition, those of ordinary skill in the art will appreciate that the elements in the drawings are illustrated for simplicity and clarity, and have not necessarily been drawn to scale. For example, the dimensions of some of the elements in the drawings may be exaggerated relative to other elements to help improve an understanding of the various embodiments of the present invention.

Benefits, other advantages, and solutions to problems have been described above with regard to specific embodiments of the present invention. However, the benefits, advantages, solutions to problems, and any element(s) that may cause or result in such benefits, advantages, or solutions, or cause such benefits, advantages, or solutions to become more pronounced are not to be construed as a critical, required, or essential feature or element of any or all the claims. As used herein and in the appended claims, the term "comprises," "comprising," or any other variation thereof is intended to refer to a non-exclusive inclusion, such that a process, method, article of manufacture, or apparatus that comprises a list of elements does not include only those elements in the list, but may include other elements not expressly listed or inherent to such process, method, article of manufacture, or apparatus.

The terms a or an, as used herein, are defined as one or more than one. The term plurality, as used herein, is defined as two or more than two. The term another, as used herein, is defined as at least a second or more. The terms including and/or having, as used herein, are defined as comprising (i.e., open language). The term coupled, as used herein, is defined as connected, although not necessarily directly, and not necessarily mechanically. The term program, as used herein, is

defined as a sequence of instructions designed for execution on a computer system. A program, or computer program, may include a subroutine, a function, a procedure, an object method, an object implementation, an executable application, an applet, a servlet, a source code, an object code, a shared library/dynamic load library and/or other sequence of instructions designed for execution on a computer system.

What is claimed is:

1. A method for supporting a reduced-resource dormant state for packet data, the method comprising:
 - forwarding data for a mobile station (MS) via a tunnel;
 - maintaining session context information for the MS;
 - releasing the tunnel to support a reduced-resource dormant state;
 - releasing a portion of the session context information to support the reduced-resource dormant state,
 - receiving new data for the MS after releasing the tunnel;
 - in response to receiving new data for the MS, sending a reconnection request for establishment of a new tunnel;
 - and
 - forwarding the new data via the new tunnel;
 - wherein forwarding data via the tunnel comprises forwarding data to a packet control function (PCF) via the tunnel;
 - wherein sending the reconnection request comprises sending the reconnection request to the PCF for establishment of the new tunnel; and
 - wherein forwarding the new data comprises forwarding the new data to the PCF via the new tunnel.
2. The method of claim 1, wherein releasing the tunnel and a portion of the session context information comprises releasing the tunnel and a portion of the session context information after a period of MS session inactivity.
3. The method of claim 1, wherein the session context information comprises session information from the group consisting of MIP tunnel binding, mobile-identifier-to-IP-address mapping, PPP context, PCF address, and A10 tunnel mapping.
4. The method of claim 3, wherein the mobile-identifier-to-IP-address mapping comprises at least one of a MIN-to-IP address mapping and an IMSI-to-IP address mapping.
5. The method of claim 1, wherein releasing the tunnel and a portion of the session context information comprises releasing at least a portion of maintained PPP context information.
6. The method of claim 5, wherein releasing the tunnel and a portion of the session context information comprises releasing all maintained PPP context information.
7. The method of claim 1, wherein releasing the tunnel and a portion of the session context information comprises releasing a PCF address.
8. The method of claim 1, wherein releasing the tunnel and a portion of the session context information comprises releasing an A10 tunnel mapping.
9. The method of claim 1, wherein sending the reconnection request comprises sending an A11 Reconnection Request message.
10. The method of claim 1, further comprising receiving a reconnection response from the PCF in response to sending the reconnection request to the PCF.
11. The method of claim 10, wherein receiving the reconnection response comprises receiving an A11 Reconnection Response message.
12. The method of claim 1, further comprising establishing a new PPP session with the MS in response to receiving new data for the MS.
13. A method to support a reduced resource dormant state for packet data, the method comprising:

7

maintaining session resources for a mobile station (MS);
 receiving data for the MS from a packet data serving node
 (PDSN) via a tunnel;
 after a period of MS session inactivity, releasing the tunnel
 and the session resources;
 receiving a reconnection request from the PDSN for estab-
 lishment of a new tunnel; and
 receiving new data for the MS from the PDSN via the new
 tunnel.

14. The method of claim **13**, wherein releasing the tunnel
 and the session resources after a period of MS session inac-
 tivity comprises releasing the tunnel and the session resources
 after a predetermined period of MS dormancy elapses.

15. The method of claim **13**, further comprising sending a
 reconnection response to the PDSN in response to receiving
 the reconnection request from the PDSN, wherein sending the
 reconnection response comprises sending at least one of an
 A11 Reconnection Response message and an indication that
 the reconnection request is being serviced.

16. The method of claim **13**, further comprising requesting
 a base site controller (BSC) to initiate paging of the MS in
 response to receiving the reconnection request from the
 PDSN, wherein requesting the BSC to initiate paging of the
 MS comprises sending an A9-BS Service Request message to
 the BSC.

8

17. The method of claim **13**, further comprising requesting
 the PDSN to setup the new tunnel.

18. A packet control function (PCF) apparatus supporting a
 reduced resource dormant state for packet data, the PCF com-
 prising:

a network interface; and

a processor, communicatively coupled to the network
 interface,

adapted to maintain session resources for a mobile sta-
 tion (MS),

adapted to receive data for the MS from a packet data
 serving node (PDSN) via a tunnel,

adapted to release the tunnel and the session resources
 after a period of MS session inactivity,

adapted to receive a reconnection request from the
 PDSN for establishment of a new tunnel, and

adapted to receive new data for the MS from the PDSN
 via the new tunnel.

19. The PCF apparatus of claim **18**, wherein the tunnel
 comprises an A10 Tunnel and wherein the new tunnel com-
 prises an A10 Tunnel.

* * * * *