

US007500988B1

(12) **United States Patent**
Butaric et al.

(10) **Patent No.:** **US 7,500,988 B1**
(45) **Date of Patent:** **Mar. 10, 2009**

(54) **STENT FOR USE IN A STENT GRAFT**

4,580,568 A 4/1986 Gianturco
4,604,762 A 8/1986 Robinson
4,617,932 A 10/1986 Kornberg
4,627,437 A * 12/1986 Bedi et al. 128/334 C

(75) Inventors: **Frank Butaric**, Pembroke Pines, FL (US); **Bill K. Ng**, Sunnyvale, CA (US); **Marc Ramer**, Weston, FL (US); **Dieter Stoeckel**, Los Altos, CA (US); **Gregory Mast**, Fremont, CA (US); **Luis A. Davila**, Pleasanton, CA (US); **Kenneth S. Solovay**, Ft. Lauderdale, FL (US)

(Continued)

FOREIGN PATENT DOCUMENTS

CA 2188233 10/1997

(Continued)

OTHER PUBLICATIONS

European Search Report, EP03250107, Apr. 14, 2003.

(Continued)

Primary Examiner—Corrine McDermott

Assistant Examiner—Cheryl Miller

(73) Assignee: **Cordis Corporation**, Miami Lakes, FL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/714,093**

(22) Filed: **Nov. 16, 2000**

(51) **Int. Cl.**
A61F 2/06 (2006.01)

(52) **U.S. Cl.** **623/1.16; 623/1.15**

(58) **Field of Classification Search** 623/1.15, 623/1.16, 1.2, 1.3, 1.31, 1.13, 1.14, 1.36
See application file for complete search history.

(56) **References Cited**


U.S. PATENT DOCUMENTS

3,585,707 A 6/1971 Stevens
3,657,744 A 4/1972 Ersek
4,169,464 A 10/1979 Obrez
4,317,451 A 3/1982 Cerwin et al.
4,441,216 A 4/1984 Ionescu et al.
RE31,618 E 7/1984 Mano
4,503,569 A 3/1985 Dotter
4,553,545 A 11/1985 Maass
4,562,596 A 1/1986 Kornberg

(57) **ABSTRACT**

A stent-graft for insertion into a body lumen, such as a blood vessel, is utilized in order to repair such lumen. The stent-graft includes a substantially cylindrical hollow expandable stent comprising a plurality of interconnected struts. The stent has a distal end and a proximal end, and an interior surface and an exterior surface. At least one strut of the stent has first and second apertures extending therethrough from the interior surface to the exterior surface. The stent-graft also includes a graft member covering a predetermined portion of least one of the interior surface and the exterior surface of the stent. In addition, the stent-graft further includes a staple for attaching the graft member to the stent. The staple has a crown and two legs extending therefrom. At least one of the legs of the staple extends through the graft material and through the first aperture. Both of the legs are bent inwardly towards said crown such that they evert back and extend through the second aperture.

4 Claims, 17 Drawing Sheets



US 7,500,988 B1

U.S. PATENT DOCUMENTS				
		5,246,445 A	9/1993	Yachia et al.
		5,246,452 A	9/1993	Sinnott
4,655,771 A	4/1987 Wallsten	5,254,107 A	10/1993	Soltesz
4,665,906 A	5/1987 Jervis	5,258,021 A	11/1993	Duran
4,681,110 A	7/1987 Wiktor	5,258,027 A	11/1993	Berghaus
4,705,517 A	11/1987 DiPisa, Jr.	5,266,073 A	11/1993	Wall
4,728,328 A	3/1988 Hughes	5,275,622 A	1/1994	Lazarus et al.
4,731,073 A	3/1988 Robinson	5,282,823 A	2/1994	Schwartz et al.
4,732,152 A	3/1988 Wallsten	5,282,824 A	2/1994	Gianturco
4,733,665 A	3/1988 Palmaz 128/343	5,282,847 A	2/1994	Trescony et al.
4,739,762 A	4/1988 Palmaz	5,282,860 A	2/1994	Matsuno
4,769,029 A	9/1988 Patel	5,290,305 A	3/1994	Inoue
4,776,337 A	10/1988 Palmaz	5,292,331 A	3/1994	Boneau
4,784,137 A	11/1988 Kulik et al.	5,304,197 A	4/1994	Pinchuk
4,787,899 A	11/1988 Lazarus	5,304,200 A	4/1994	Spaulding
4,800,882 A	1/1989 Gianturco	5,306,294 A	4/1994	Winston
4,822,341 A	4/1989 Colone	5,314,444 A	5/1994	Gianturco
4,850,999 A	7/1989 Planck	5,314,472 A	5/1994	Fontaine
4,856,516 A	8/1989 Hillstead	5,316,023 A	5/1994	Palmaz
4,875,480 A	10/1989 Imbert	5,318,535 A	6/1994	Miraki
4,886,062 A	12/1989 Wiktor	5,321,109 A	6/1994	Bosse
4,907,336 A	3/1990 Gianturco	5,330,490 A	7/1994	Wilk
4,913,141 A	4/1990 Hillstead	5,330,500 A	7/1994	Song
4,925,445 A	5/1990 Sakamoto	5,330,528 A	7/1994	Lazim
4,950,227 A	8/1990 Savin	5,334,201 A	8/1994	Cowan
4,955,899 A	9/1990 Della Corna	5,334,301 A	8/1994	Heinke et al.
4,969,458 A	11/1990 Wiktor	5,342,387 A	8/1994	Summersq
4,990,131 A	2/1991 Dardik	5,354,257 A	10/1994	Roubin et al.
4,990,151 A	2/1991 Wallsten	5,354,308 A	10/1994	Simon et al.
4,990,155 A	2/1991 Wilkoff	5,358,493 A	10/1994	Schweich, Jr. et al.
4,994,071 A	2/1991 MacGregor	5,360,443 A	11/1994	Barone
5,015,253 A	5/1991 MacGregor	5,366,473 A	11/1994	Winston
5,019,085 A	5/1991 Hillstead	5,366,504 A	11/1994	Andersen et al.
5,026,337 A	6/1991 Miura et al. 475/283	5,370,683 A	12/1994	Fontaine
5,026,377 A	6/1991 Burton	5,370,691 A	12/1994	Samson
5,035,694 A	7/1991 Kasprzyk et al.	5,375,612 A	12/1994	Cottenceau et al.
5,035,706 A	7/1991 Gianturco	5,376,112 A	12/1994	Duran
5,041,126 A	8/1991 Gianturco	5,380,328 A	1/1995	Morgan
5,045,072 A	9/1991 Castillo	5,382,261 A	1/1995	Palmaz
5,064,435 A	11/1991 Porter	5,383,892 A *	1/1995	Cardon et al. 606/198
5,078,726 A	1/1992 Creamer	5,383,927 A	1/1995	DeGoicoechea
5,084,065 A	1/1992 Weldon	5,387,235 A	2/1995	Chuter
5,100,422 A	3/1992 Berguer	5,389,106 A	2/1995	Tower
5,102,417 A	4/1992 Palmaz	5,395,390 A	3/1995	Simon et al.
5,104,399 A	4/1992 Lazarus	5,397,345 A	3/1995	Lazarus
5,104,400 A	4/1992 Berguer	5,397,355 A	3/1995	Marin et al.
5,104,404 A	4/1992 Wolff	5,403,341 A	4/1995	Solar
5,114,423 A	5/1992 Kasprzyk et al.	5,405,322 A	4/1995	Lennox et al.
5,116,365 A	5/1992 Hillstead	5,405,377 A	4/1995	Cragg
5,122,154 A	6/1992 Rhodes	5,411,507 A	5/1995	Heckele
5,123,917 A	6/1992 Lee	5,411,549 A	5/1995	Peters
5,131,908 A	7/1992 Dardik et al.	5,417,708 A	5/1995	Hall et al.
5,133,732 A	7/1992 Wiktor	5,419,324 A	5/1995	Dillow
5,135,536 A	8/1992 Hillstead	D359,802 S	6/1995	Fontaine
5,151,105 A	9/1992 Kwan-Gett	5,421,955 A	6/1995	Lau et al.
5,152,782 A	10/1992 Kowligi	5,423,885 A	6/1995	Williams
5,156,620 A	10/1992 Pigott	5,439,446 A	8/1995	Barry
5,159,920 A	11/1992 Cordon	5,441,515 A	8/1995	Khosravi et al.
5,163,951 A	11/1992 Pinchuk	5,441,516 A	8/1995	Wang et al.
5,163,958 A	11/1992 Pinchuk	5,443,477 A	8/1995	Marin et al.
5,171,262 A	12/1992 MacGregor	5,443,496 A	8/1995	Schwartz et al.
5,176,660 A	1/1993 Truckai	5,443,498 A	8/1995	Fontaine
5,178,618 A	1/1993 Kandarpa	5,443,500 A	8/1995	Sigwart
5,192,297 A	3/1993 Trescony et al.	5,449,372 A	9/1995	Schmaltz et al.
5,192,307 A	3/1993 Wall	5,449,373 A	9/1995	Pinchasik et al.
5,195,984 A	3/1993 Schatz	5,449,382 A	9/1995	Dayton
5,207,695 A	5/1993 Trout, III	5,453,090 A	9/1995	Martinez et al.
5,209,756 A *	5/1993 Seedhom et al. 606/151	5,453,235 A	9/1995	Calcote
5,211,658 A	5/1993 Clouse	5,456,713 A	10/1995	Chuter
5,217,483 A	6/1993 Tower	5,466,509 A	11/1995	Kowligi
5,219,355 A	6/1993 Parodi	5,468,138 A	11/1995	Bosse
5,222,971 A	6/1993 Willard et al.	5,476,506 A	12/1995	Lunn
5,236,447 A	8/1993 Kubo	5,480,423 A	1/1996	Ravenscroft

US 7,500,988 B1

5,484,444 A	1/1996	Braunchweiler	5,716,365 A	2/1998	Goicoechea et al.
5,489,295 A	2/1996	Piplani et al.	5,718,159 A	2/1998	Thompson
5,496,365 A	3/1996	Fontaine et al.	5,718,724 A	2/1998	Goicoechea et al.
5,507,767 A	4/1996	Maeda et al.	5,720,735 A	2/1998	Dorros
5,507,769 A	4/1996	Marin	5,720,776 A	2/1998	Chuter et al.
5,507,771 A	4/1996	Gianturco	5,723,003 A	3/1998	Winston
5,507,995 A	4/1996	Schweich, Jr. et al.	5,723,004 A	3/1998	Dereume et al.
5,512,229 A	4/1996	Bosse	5,725,534 A	3/1998	Rasmussen
5,522,880 A	6/1996	Barone	5,725,568 A	3/1998	Hastings
5,522,882 A	6/1996	Gaterud	5,725,570 A	3/1998	Heath
5,527,354 A	6/1996	Fontaine et al.	5,728,065 A	3/1998	Follmer et al.
5,549,662 A	8/1996	Fordenbacher	5,728,068 A	3/1998	Leone et al.
5,549,663 A	8/1996	Cottone, Jr.	5,728,131 A	3/1998	Frantzen et al.
5,562,698 A	10/1996	Parker	5,733,328 A	3/1998	Fordenbacher
5,562,724 A	10/1996	Vorwerk	5,735,892 A	4/1998	Myers
5,562,726 A	10/1996	Chuter	5,746,709 A	5/1998	Rom et al.
5,569,295 A	10/1996	Lam	5,749,880 A	5/1998	Banas
5,571,170 A	11/1996	Palmaz	5,749,920 A	5/1998	Quiachon et al.
5,571,171 A	11/1996	Barone	5,749,921 A	5/1998	Lenker et al.
5,571,173 A	11/1996	Parodi	5,752,966 A	5/1998	Chang
5,578,071 A	11/1996	Parodi	5,755,734 A	5/1998	Richter et al.
5,578,072 A	11/1996	Barone	5,755,735 A	5/1998	Richter et al.
5,591,196 A	1/1997	Marin et al.	5,755,770 A	5/1998	Ravenscroft
5,591,197 A	1/1997	Orth et al.	5,755,771 A	5/1998	Penn et al.
5,591,228 A	1/1997	Edoga	5,755,772 A	5/1998	Evans et al.
5,591,229 A	1/1997	Parodi	5,755,773 A	5/1998	Evans et al.
5,593,412 A	1/1997	Martinez et al.	5,755,777 A	5/1998	Chuter
5,607,444 A	3/1997	Lam	5,755,781 A *	5/1998	Jayaraman 623/1
5,607,464 A	3/1997	Trescony et al.	5,758,562 A	6/1998	Thompson
5,609,624 A	3/1997	Kalis	5,760,006 A	6/1998	Shank
5,609,625 A	3/1997	Piplani et al.	5,766,201 A	6/1998	Ravenscroft et al.
5,609,627 A	3/1997	Goicoechea et al.	5,769,882 A	6/1998	Fogarty et al.
5,617,878 A	4/1997	Taheri	5,769,885 A	6/1998	Quiachon et al.
5,618,300 A	4/1997	Marin et al.	5,776,180 A	7/1998	Goicoechea et al.
5,628,783 A	5/1997	Quiachon et al.	5,782,765 A	7/1998	Jonkman
5,628,786 A	5/1997	Banas	5,782,906 A	7/1998	Marshall et al.
5,628,788 A	5/1997	Pinchuk	5,782,909 A	7/1998	Quiachon et al.
5,632,763 A	5/1997	Glastra	5,788,626 A	8/1998	Thompson
5,632,778 A	5/1997	Goldstein	5,797,953 A	8/1998	Tekulve
5,639,278 A	6/1997	Dereume et al.	5,800,456 A	9/1998	Maeda et al.
5,641,443 A	6/1997	Calcote et al.	5,800,508 A	9/1998	Goicoechea et al.
5,643,312 A	7/1997	Fischell et al.	5,800,516 A	9/1998	Fine et al.
5,645,559 A	7/1997	Hachtman	5,800,518 A	9/1998	Piplani et al.
5,649,952 A	7/1997	Lam	5,800,520 A	9/1998	Fogarty et al.
5,653,743 A	8/1997	Martin	5,810,870 A	9/1998	Myers
5,653,745 A	8/1997	Trescony et al.	5,824,036 A	10/1998	Lauterjung
5,653,747 A	8/1997	Dereume	5,824,037 A	10/1998	Fogarty et al.
5,662,700 A	9/1997	Lazarus	5,824,039 A	10/1998	Piplani et al.
5,662,703 A	9/1997	Yurek et al.	5,824,040 A	10/1998	Cox et al.
5,667,523 A	9/1997	Bynon	5,824,041 A	10/1998	Lenker et al.
5,669,924 A	9/1997	Shaknovich	5,824,042 A	10/1998	Lombardi et al.
5,669,936 A	9/1997	Lazarus	5,824,043 A	10/1998	Cottone, Jr.
5,674,241 A	10/1997	Bley	5,824,044 A	10/1998	Yazici et al.
5,674,276 A	10/1997	Andersen et al.	5,824,046 A	10/1998	Smith
5,676,696 A	10/1997	Marcade	5,824,054 A	10/1998	Khosravi
5,676,697 A	10/1997	McDonald	5,824,055 A	10/1998	Spiridigliozzi et al.
5,681,345 A	10/1997	Euteneuer	5,827,310 A	10/1998	Marin et al.
5,681,346 A	10/1997	Orth et al.	5,827,320 A	10/1998	Richter et al.
5,683,448 A	11/1997	Cragg	5,827,327 A	10/1998	McHaney
5,683,449 A	11/1997	Marcade	5,830,229 A	11/1998	Konya et al.
5,683,450 A	11/1997	Goicoechea et al.	5,833,651 A	11/1998	Donovan et al.
5,683,451 A	11/1997	Lenker et al.	5,840,011 A	11/1998	Landgrebe et al.
5,685,847 A	11/1997	Barry	5,843,031 A	12/1998	Hermann et al.
5,693,083 A	12/1997	Baker et al.	5,843,120 A	12/1998	Israel
5,693,084 A	12/1997	Chuter	5,843,158 A	12/1998	Lenker et al.
5,693,085 A	12/1997	Limon et al.	5,843,160 A	12/1998	Rhodes
5,693,086 A	12/1997	Goicoechea et al.	5,855,598 A	1/1999	Pinchuk
5,695,517 A	12/1997	Marin et al.	5,855,600 A *	1/1999	Alt 623/1
5,697,948 A	12/1997	Marin et al.	5,857,998 A	1/1999	Barry
5,697,971 A	12/1997	Fischell et al.	5,858,556 A	1/1999	Eckert
5,700,285 A	12/1997	Myers	5,860,998 A	1/1999	Robinson et al.
5,702,418 A	12/1997	Ravenscroft	5,861,027 A	1/1999	Trapp
5,713,917 A	2/1998	Leonhardt et al.	5,868,777 A	2/1999	Lam

US 7,500,988 B1

5,871,537 A	2/1999	Holman et al.	6,099,560 A	8/2000	Penn et al.
5,871,538 A	2/1999	Dereume	6,102,938 A	8/2000	Evans et al.
5,876,397 A	3/1999	Edelman et al.	6,102,942 A	8/2000	Ahari
5,893,868 A	4/1999	Hanson et al.	6,110,191 A	8/2000	Dehdashtian et al.
5,893,887 A	4/1999	Jayaraman	6,110,198 A	8/2000	Fogarty et al.
5,899,890 A	5/1999	Chiang et al.	6,117,117 A	9/2000	Mauch
5,902,308 A	5/1999	Murphy	6,117,156 A	9/2000	Richter et al.
5,904,713 A	5/1999	Leschinsky	6,117,157 A	9/2000	Tekulve
5,906,619 A	5/1999	Olson et al.	6,117,167 A	9/2000	Goicoechea et al.
5,906,640 A	5/1999	Penn et al.	6,123,722 A	9/2000	Fogarty et al.
5,906,641 A	5/1999	Thompson et al.	6,126,685 A	10/2000	Lenker et al.
5,908,448 A	6/1999	Roberts et al.	6,129,754 A	10/2000	Hanson et al.
5,916,263 A	6/1999	Goicoechea et al.	6,132,450 A	10/2000	Hanson et al.
5,916,264 A	6/1999	Von Oepen	6,132,459 A	10/2000	Piplani et al.
5,919,224 A	7/1999	Thompson et al.	6,143,022 A *	11/2000	Shull et al. 623/1.13
5,928,260 A	7/1999	Chin et al.	6,193,745 B1 *	2/2001	Fogarty et al. 623/1.12
5,931,867 A *	8/1999	Haindl 623/1	6,200,336 B1	3/2001	Pavenik et al.
5,935,667 A	8/1999	Calcote	6,206,911 B1 *	3/2001	Milo 623/1.15
5,938,696 A	8/1999	Goicoechea et al.	6,231,598 B1 *	5/2001	Berry et al. 623/1.15
5,944,726 A	8/1999	Blaeser et al.	6,270,524 B1 *	8/2001	Kim 623/1.15
5,944,750 A	8/1999	Tanner et al.	6,302,906 B1	10/2001	Goicoechea et al.
5,951,599 A	9/1999	McCrary	6,306,164 B1	10/2001	Kujawski
5,954,693 A	9/1999	Barry	6,325,819 B1	12/2001	Pavenik et al.
5,957,973 A	9/1999	Quiachon et al.	6,336,938 B1 *	1/2002	Kavteladze et al. 623/1.15
5,957,974 A	9/1999	Thompson et al.	6,344,056 B1	2/2002	Dehdashtian
5,961,548 A	10/1999	Shmulewitz	6,346,119 B1	2/2002	Kuwahara et al.
5,968,069 A	10/1999	Dusbabek et al.	6,355,057 B1 *	3/2002	DeMarais et al. 623/1.15
5,968,088 A	10/1999	Hansen et al.	6,361,557 B1 *	3/2002	Gittings 623/1.13
5,980,552 A *	11/1999	Pinchasik et al. 606/198	6,395,018 B1	5/2002	Castaneda
5,980,565 A	11/1999	Jayaraman	6,468,300 B1 *	10/2002	Freidberg 623/1.13
5,984,955 A	11/1999	Wisselink	6,547,814 B2 *	4/2003	Edwin et al. 623/1.13
5,993,481 A	11/1999	Marcade et al.	6,554,858 B2	4/2003	Dereume et al.
6,007,543 A	12/1999	Ellis et al.	6,579,314 B1 *	6/2003	Lombardi et al. 623/1.44
6,015,431 A	1/2000	Thornton et al.	6,585,756 B1	7/2003	Strecker
6,015,432 A	1/2000	Rakos et al.	6,592,615 B1	7/2003	Marcade et al.
6,016,810 A	1/2000	Ravenscroft	6,656,214 B1	12/2003	Fogarty et al.
6,017,363 A	1/2000	Hojeibane	6,699,277 B1 *	3/2004	Freidberg et al. 623/1.13
6,017,364 A	1/2000	Lazarus	6,709,453 B2 *	3/2004	Pinchasik et al. 623/1.15
6,019,778 A	2/2000	Wilson et al.	2001/0003801 A1	6/2001	Strecker
6,019,786 A	2/2000	Thompson	2001/0027338 A1	10/2001	Greenberg
6,019,789 A *	2/2000	Dinh et al. 623/1	2002/0082684 A1	6/2002	Mishaly
6,024,763 A	2/2000	Lenker et al.	2003/0009212 A1	1/2003	Kerr
6,027,526 A *	2/2000	Limon et al. 623/1			
6,027,529 A	2/2000	Roychowdhury et al.			
6,030,413 A	2/2000	Lazarus			
6,030,415 A	2/2000	Chuter			
6,033,435 A	3/2000	Penn et al.			
6,036,697 A	3/2000	DiCaprio			
6,036,723 A	3/2000	Anidjar et al.			
6,036,725 A	3/2000	Avellanet			
6,039,749 A	3/2000	Marin et al.			
6,039,758 A	3/2000	Quiachon et al.			
6,048,356 A	4/2000	Ravenscroft et al.			
6,051,020 A	4/2000	Goicoechea et al.			
6,053,941 A *	4/2000	Lindenberg et al. 623/1			
6,056,775 A	5/2000	Borghi et al.			
6,059,821 A	5/2000	Anidjar et al.			
6,059,823 A	5/2000	Holman et al.			
6,059,824 A	5/2000	Taheri			
6,063,111 A	5/2000	Hieshima et al.			
6,068,655 A	5/2000	Seguin et al.			
6,070,589 A	6/2000	Keith et al.			
6,077,273 A	6/2000	Euteneuer et al.			
6,078,832 A	6/2000	Lenker et al.			
6,083,259 A *	7/2000	Frantzen 623/1.15			
6,086,577 A	7/2000	Ken et al.			
6,086,611 A	7/2000	Duffy et al.			
6,090,127 A	7/2000	Globerman			
6,090,128 A	7/2000	Douglas			
6,090,133 A	7/2000	Richter et al.			
6,093,199 A	7/2000	Brown et al.			
6,097,978 A	8/2000	Demarais et al.			
6,099,558 A	8/2000	White et al.			

FOREIGN PATENT DOCUMENTS

CA	2211097	3/1998
DE	3205942 A1	9/1983
EP	0 540 290 A3	5/1993
EP	0579523 A1	1/1994
EP	0 657 147 A2	10/1994
EP	0657147 A2	10/1994
EP	0 667 132 A2	8/1995
EP	0686379 B1	12/1995
EP	734698 A2	10/1996
EP	783 873	7/1997
EP	783873 A2	7/1997
EP	0 800 801 A1	10/1997
EP	800801 A1	10/1997
EP	880 948	2/1998
EP	830853 A1	3/1998
EP	832616 A1	4/1998
EP	0855170 A2	7/1998
EP	880948 A1	12/1998
EP	0928606 A1	7/1999
EP	937442 A2	8/1999
EP	0947179 A2	10/1999
EP	1000590	5/2000
EP	1000590 A1	5/2000
EP	1 025 811 A2	8/2000
EP	1086665 A	3/2001
FR	0 566 807 A1	2/1924
FR	2 743 293	1/1996
FR	2733682 A1	11/1996

US 7,500,988 B1

Page 5

FR	2740346	A1	4/1997
FR	2743293	A1	7/1997
GB	0 662 307	A2	9/1948
GB	1 205 743		9/1970
JP	5524095	A	2/1980
JP	60220030	A	11/1985
JP	62231657	A	3/1988
JP	464367	A	2/1992
JP	4263852	A	4/1992
JP	5 76603	A	3/1993
JP	5 269199	A	10/1993
JP	7529	A	10/1994
JP	6282730	A	10/1994
JP	7 24072	A	1/1995
JP	7100210	A	4/1995
JP	6 86827	A	6/1998
SU	1680055		5/1988
WO	8704935	A1	8/1987
WO	WO87/04935		8/1987
WO	9516406	A1	6/1995
WO	WO95/16406		6/1995
WO	9521592	A1	8/1995
WO	WO95/21592		8/1995
WO	WO95/32757	A1	12/1995
WO	9626689	A1	9/1996
WO	96/34580	A1	11/1996
WO	WO97/12562	A1	4/1997

WO	9724081	A1	7/1997
WO	9725000	A1	7/1997
WO	9733532	A2	9/1997
WO	WO97/33532		9/1997
WO	9807389	A1	2/1998
WO	WO98/07389		2/1998
WO	98/19628	A1	5/1998
WO	9823322	A1	6/1998
WO	9836709	A1	8/1998
WO	9853761	A1	12/1998
WO	9908744	A1	2/1999
WO	9911199	A1	3/1999
WO	WO99/11199		3/1999
WO	WO 99/60953		12/1999
WO	WO 00/53122	A1	9/2000
WO	WO 00/74598	A	12/2000
WO	WO 0174270	A	10/2001

OTHER PUBLICATIONS

European Search Report EP 03 25 0105 dated Jun. 11, 2003, which is related to the present application.

European Search Report EP dated Oct. 22, 2003, for corresponding EP application 01309629.2, which is related to the present application.

* cited by examiner

FIG. 1





FIG. 3






FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24





FIG. 25



STENT FOR USE IN A STENT GRAFT

FIELD OF THE INVENTION

The present invention relates to percutaneously delivered 5
stent-grafts for repairing abdominal aortic aneurysms.

BACKGROUND OF THE INVENTION

An abdominal aortic aneurysm is a sac caused by an abnormal 10
dilation of the wall of the aorta, a major artery of the body, as it passes through the abdomen. The abdomen is that portion of the body which lies between the thorax and the pelvis. It contains a cavity, known as the abdominal cavity, separated by the diaphragm from the thoracic cavity and lined with a membrane, the peritoneum. The aorta is the main trunk, or artery, from which the systemic arterial system proceeds. It arises from the left ventricle of the heart, passes upward, bends over and passes down through the thorax and through the abdomen to about the level of the fourth lumbar vertebra, 20
where it divides into the two common iliac arteries.

The aneurysm often arises in the infrarenal portion of the diseased aorta, for example, below the kidneys. When left untreated, the aneurysm will eventually cause rupture of the sac with ensuing fatal hemorrhaging in a very short time. 25
High mortality associated with the rupture has led to the present state of the art and the trans-abdominal surgical repair of abdominal aortic aneurysms. Surgery involving the abdominal wall, however, is a major undertaking with associated high risks. There is considerable mortality and morbidity associated with this magnitude of surgical intervention, which in essence involves replacing the diseased and aneurysmal segment of blood vessel with a prosthetic device which typically is a synthetic tube, or graft, usually fabricated of either DACRON®, TEFLON®, GORTEX®, or other suitable material. 35

To perform the surgical procedure requires exposure of the aorta through an abdominal incision, which can extend from the rib cage to the pubis. The aorta must be cross-clamped both above and below the aneurysm, so that the aneurysm can 40
then be opened and the thrombus, or blood clot, and arteriosclerotic debris removed. Small arterial branches from the back wall of the aorta are tied off. The DACRON® tube, or graft, of approximately the same size of the normal aorta is sutured in place, thereby replacing the aneurysm. Blood flow 45
is then reestablished through the graft. It is necessary to move the intestines in order to get to the back wall of the abdomen prior to clamping off the aorta.

If the surgery is performed prior to rupturing of the abdominal aortic aneurysm, the survival rate of treated 50
patients is markedly higher than if the surgery is performed after the aneurysm ruptures, although the mortality rate is still relatively high. Although abdominal aortic aneurysms can be detected from routine examinations, the patient may not experience any pain from the condition. Thus, if the patient is not receiving routine examinations, it is possible that the aneurysm will progress to the rupture stage. 55

Disadvantages associated with the conventional, prior art surgery, in addition to the high mortality rate, are: the extended recovery period associated with the large surgical 60
exposure in such open procedures; difficulties in suturing the graft, or tube, to the aorta; the loss of the existing thrombosis to support and reinforce the graft; the unsuitability of the surgery for many patients having abdominal aortic aneurysms; and the problems associated with performing the surgery on an emergency basis after the aneurysm has ruptured. 65
As to the extent of recovery, a patient can expect to spend

from 1 to 2 weeks in the hospital after the surgery, a major portion of which is spent in the intensive care unit, and a convalescence period at home from 2 to 3 months, particularly if the patient has other illness such as heart, lung, liver, and/or kidney disease, in which case the hospital stay is also lengthened. Since the graft must be secured, or sutured, to the remaining portion of the aorta, it is often difficult to perform the suturing step because of thrombosis present on the remaining portion of the aorta, and that remaining portion of the aorta wall may be friable, or easily crumbled.

Since the thrombosis is totally removed in the prior art surgery, the new graft does not have the benefit of the previously existing thrombosis therein, which could be utilized to support and reinforce the graft, were the graft to be able to be 15
inserted within the existing thrombosis. Since many patients having abdominal aortic aneurysms have other chronic illnesses, such as heart, lung, liver, and/or kidney disease, coupled with the fact that many of these patients are older, these patients are not ideal candidates for such surgery, which is considered major surgery. Such patients have difficulties in surviving the operation. Lastly, once the aneurysm has ruptured, it is difficult to perform a conventional surgery on an expedited basis because of the extent of the surgery.

Accordingly, the prior art teaches various methods and apparatuses for repairing an abdominal aortic aneurysm which is believed to lower morbidity and mortality rate by not requiring an abdominal incision and general anesthesia, not requiring suturing the graft to the remaining aortic wall, and which permits the existing aortic wall and thrombosis therein 25
to be retained to reinforce and support the aortic graft. An example of such a method and apparatus is given in U.S. Pat. No. 5,316,023 issued to Palmaz et al. on May 31, 1994; U.S. Pat. No. 5,360,443 issued to Barone et al. on Nov. 1, 1994; U.S. Pat. No. 5,578,071 issued to Parodi on Nov. 26, 1996; and U.S. Pat. No. 5,591,229 issued to Parodi on Jan. 7, 1997, all of which are hereby incorporated herein by reference. 35

Devices, such as the one shown in the above referenced Barone patent, use an improved method for repairing an abdominal aortic aneurysm in an aorta having two iliac arteries associated therewith. The device includes first and second tubes, preferably made from a variety of materials such as DACRON® and other polyester materials, TEFLON® (polytetrafluoroethylene), TEFLON® coated DACRON®, porous polyurethane, silicone, expanded polytetrafluoroethylene, and expanded polyurethane. It is preferred that all of the foregoing materials be porous to allow for an intimal layer to form on the tubes. Each of the tubes are connected to expandable and deformable tubular members, or stents. These stents can be similar in structure to those described in disclosed in 40
U.S. Pat. No. 4,733,665 issued on Mar. 29, 1988; U.S. Pat. No. 4,739,762, issued on Apr. 26, 1988; and U.S. Pat. No. 4,776,337 issued on Oct. 11, 1988, all of the foregoing patents being in the name of Julio C. Palmaz, each of which is incorporated herein by reference. Each of the tube/stent structures 55
are then disposed on the end of a balloon catheter. Either both tubes are inserted into the same femoral artery or one of the tubes is inserted into one femoral artery of the patient and the other tube is inserted into the other femoral artery of the patient. Thereafter the tubes are intraluminally delivered to the aorta, thereby disposing at least a portion of each tube within the abdominal aortic aneurysm. The balloons on the distal ends of the catheters are then expanded to expand and deform the tubular members, to force the tubular members radially outwardly into contact with the aorta and each other. 60
This secures the tubular members and a least a portion of each tube within the aorta, whereby the tubes provide a bilateral fluid passageway through the abdominal aortic aneurysm. 65

While the above mentioned devices would seem to work well, there is a desire to improve upon the device. More particularly, there was a need to ensure that most of the blood flowing through the abdomen flows through the bilateral fluid passageways and not around them where it could cause further damage. The precursor stent gasket described in commonly assigned European Patent Application EP 0947179, filed on Mar. 29, 1999, European Patent Application EP 1000590 (A1), filed on Nov. 8, 1999, and pending U.S. patent application Ser. No. 09/404,660 filed on Sep. 24, 1999, the disclosures of which are hereby incorporated herein by reference, limits the amount of blood which could leak around the bilateral fluid passageways and into the aneurysm. The precursor stent gasket is positioned within the infrarenal neck, between an abdominal aortic aneurysm and the renal arteries, of a patient to assist in repairing the abdominal aortic aneurysm. The stent is designed to be coupled to the bilateral grafts for directing blood flow. The graft has a distal end for positioning distal to the aneurysm, and a proximal end for positioning proximal to the aneurysm. The precursor stent gasket includes a substantially cylindrical expandable member having a proximal end, a distal end and an interior. The stent gasket further includes a compressible gasket member located within the interior of the expandable member and attached thereto. The compressible member is substantially impervious to blood when in a compressed state and is coupled the graft. This is so the coupled device can direct blood flow through the graft, with the gasket member substantially preventing blood from flowing into the aneurysm.

While the above described devices are large improvements over the prior art, there has been a need for improvement. There has been a desire to have a better device for attaching the graft material to the grafts used in the above described devices. There has been a desire to have an improved stent gasket member for better attachment of the stent gasket member to aortic wall. There has been a desire to have a mechanism for ensuring that the stent gasket member is not prematurely deployed. There has been a desire to improve the design of the stent grafts to make them perform better. Lastly, there has been a desire to improve the grafts on the stent grafts themselves to make them perform better during deployment. The following described invention provides such an improved device.

SUMMARY OF THE INVENTION

In accordance with the present invention there is provided a hollow substantially cylindrical radially expandable stent having proximal and distal open ends and a longitudinal axis extending therebetween. The stent is for deployment within a human body vessel, and is particularly useful in the manufacture of stent-grafts. The stent includes a plurality of hoops comprising a plurality of interconnected struts. The stent has a proximal end hoop and a distal end hoop wherein the distal end hoop and the proximal end hoop have greater radial and longitudinal strength than the hoops therebetween. The stent further includes a plurality of sinusoidal rings connecting adjacent hoops to one another.

BRIEF DESCRIPTION OF DRAWINGS

The foregoing and other aspects of the present invention will best be appreciated with reference to the detailed description of the invention in conjunction with the accompanying drawings, wherein:

FIG. 1 is a perspective view of a precursor stent (shown without the gasket, in an expanded state) made in accordance with the present invention.

FIG. 2 is a view similar to that of FIG. 1 but including a gasket member made in accordance with the present invention.

FIG. 3 is a cross-sectional view of the precursor stent of FIG. 2 taken along section line 3—3 of FIG. 2.

FIG. 4 is a side elevational view of an endograft stent prior to the application of the graft material and shown in an expanded state.

FIG. 5 is a side elevational view of a longitudinally pleated graft to be used in conjunction with the stent of FIG. 4 wherein the pleats are discontinuous.

FIG. 6 is a partial side elevational view of another embodiment of the graft wherein the longitudinal pleats are interrupted by circumferential pleats.

FIG. 7 is an end elevational view of the graft as taken along view line 7—7 of FIG. 5, the broken line work representing the graft in a compressed state.

FIG. 8 is a side elevational view of a complete stent-graft assembly shown in a deployed state.

FIG. 9 is an enlarged partial plan view of an attachment tab at the cranial end of the stent as shown in the encircled area of FIG. 4.

FIG. 10 is a partial, exploded cross-sectional view of the attachment tab as taken along section line 10—10 of FIG. 9 and includes a staple and a portion of the graft material prior to affixing the graft to the stent.

FIG. 11 is a partial cross-sectional view of the attachment means after crimping the staple.

FIG. 12 is an enlarged partial plan view of an attachment node at the caudal end of the stent as shown in the encircled area of FIG. 4.

FIG. 13 is a partial, exploded cross-sectional view of the attachment node as taken along section line 13—13 of FIG. 12 and includes a staple and a portion of the graft material prior to affixing the graft to the stent.

FIG. 14 is a partial cross-sectional view of the attachment means after crimping the staple.

FIG. 15 is a partial, exploded perspective view of the caudal end of the stent-gasket, or endograft, and a portion of the delivery system shown after its release from the delivery system.

FIGS. 16, 17 and 18 are sequential schematic perspective views showing the method of positioning and deploying the stent-grafts, or endografts, after the precursor stent has already been deployed.

FIG. 19 is an elevational view of a fully deployed abdominal aortic repair system made in accordance with the present invention.

FIG. 20 is a top plan view of the precursor stent as seen along view line 20—20 of FIG. 19.

FIG. 21 is a photomicrograph of the gasket material prior to substantial cell ingrowth, as taken along section line 21—21 of FIG. 3.

FIG. 22 is a photomicrograph of the gasket material after substantial cell ingrowth, or biofusion, has taken place as taken along line 22—22 of FIG. 19.

FIG. 23 is an elevational view of a delivery system for a stent gasket made in accordance with the present invention, wherein the delivery system is inserted into an abdominal aortic aneurysm.

FIG. 24 is a view similar to that of FIG. 23 but showing the stent gasket partially deployed from its delivery system.

FIG. 25 is a view similar to that of FIG. 24 but showing the stent gasket fully deployed from its delivery system.

DETAILED DESCRIPTION OF THE INVENTION

One preferred use of the present invention is to treat abdominal aortic aneurysms. A better understanding of the present device and its use in treating abdominal aortic aneurysms will be achieved by reading the following description in conjunction with the above incorporated references. In addition, the terms cranial and distal, will refer to the direction towards the head of the patient, and the terms caudal or proximal will refer to the direction away from the head of the patient.

Referring now to the drawings wherein like numerals indicate the same element throughout the views, there is shown in FIG. 1 a precursor stent 10, shown in FIG. 1. As will be discussed below, precursor stent 10 is to be deployed within the infrarenal neck, between an abdominal aortic aneurysm and the renal arteries of a patient to assist in repairing the abdominal aortic aneurysm. The precursor stent 10 is designed to be coupled to one or more stent-grafts for directing blood flow through the aneurysm. The precursor stent 10 includes a substantially cylindrical self-expanding member 12 made from a plurality of interconnected struts. Self-expanding member 12 having two open ends, a proximal end 14, a distal end 16, and a longitudinal axis extending therebetween and an interior 18. The precursor stent 10 further includes at least two, but preferably 8 as shown in FIG. 1, spaced apart longitudinal legs 20 each having proximal and distal ends 24 and 26 respectively. Preferably, there is a leg extending from each apex 11 of diamonds 13 (such diamonds being formed by the struts). The distal ends 26 of the legs are attached to the proximal end 14 of the self-expanding member 12, the legs extending proximally away from the self-expanding member. At least one, but preferably each leg includes a flange 28 adjacent its proximal end which, as is described in greater detail below, allows for the stent to be retrieved into its delivery apparatus after partial or full deployment of self-expanding member 12 so that it can be turned, or otherwise repositioned for proper alignment.

The self-expanding stents described herein are preferably made from superelastic Nickel Titanium alloys (Nitinol). Descriptions of medical devices which use such alloys can be found in U.S. Pat. No. 4,665,906 issued to Jervis on May 19, 1987, and European Patent Application EP 0928606 filed on Jan. 8, 1999, both of which are hereby incorporated herein by reference. Precursor stent 10 is preferably laser cut from a tubular piece of Nickel Titanium Alloy and thereafter treated so as to exhibit superelastic properties at body temperature. Precursor stent 10 is shown in the figures as being a diamond patterned stent, having approximately 8 diamonds, and when the stent is fully expanded the diamonds would have angles of 45–55 degrees at their distal and proximal ends. However, precursor stent 10 can take on many different patterns or configurations.

In one embodiment of precursor stent 10, shown in most of the figures but removed from FIG. 1 for clarity, precursor stent 10 further includes a gasket member 30 (thereby forming a stent gasket or stent graft). This feature can be better understood by referring to FIGS. 2 and 3. As seen from those figures, precursor stent 10 further includes a gasket member 30. Gasket member 30 surrounds the self-expanding member 12 and can be located along the interior of self-expanding member 12, the exterior of self-expanding member 12 or both. The gasket member 30 helps impede any blood trying to flow around the stent grafts, described below, after they have been inserted (as shown in FIG. 19) and from flowing around the precursor stent 10 itself. For this embodiment gasket

member 30 is a compressible member located along both the interior and the exterior of self-expanding member 12.

Gasket member 30 can be made from any number of materials known to those skilled in the art. Preferably, gasket member 30 is made from an open cell polyurethane foam, however other flexible foams could be used, such as polyethylene, polytetrafluoroethylene, other various polymer materials which are woven or knitted to provide a flexible structure such as Dacron, polyurethane, polypropylene, polytetrafluoroethylene can also be used. Preferably, the polyurethane foam has a cell size of 50–100 pores per inch, and the density of the foam is 1.5–3.5 pounds per cubic foot. Foams having these qualities absorb the blood like a sponge, contributing to blood stagnation which leads to thrombosis. In addition, it provides a trellis for cellular infiltration, and eventually scaffolds tissue incorporation. This helps to better anchor the device within the body, thereby preventing stent migration. An example of such a foam is shown in the photograph of FIG. 21. FIG. 21 shows a scanning electron microscope of a open cell polyurethane foam having approximately 200–500 micrometer pores.

This ability of the tissue from the artery wall to incorporate the open-pore foam structure has been termed by assignee as “Biofusion”. This tissue incorporation effect can best be seen by referring to the photographs of FIGS. 21 and 22. FIG. 22 shows histological photographs of connective tissue infiltrating and healing into the gasket member 30 upon a 1 month follow-up of a device implanted into a target vessel. This ability of the tissue to heal into the foam creates a long term stable biological interface which, upon about six weeks after implantation, cannot be separated from the tissue without tearing the foam material. The “Biofusion” effect has many advantages. It has the potential to obviate late endo-leakage by preventing areas of non-organized clot from being displaced or recanalized. It is also believed that “Biofusion” creates a connective tissue collar around the gasket that would prevent the aortic neck from dilating over time. Restriction of neck dilation avoids endoleakage paths and implant migration that can be caused by an insufficient fit with the aorta. The use of such above described foams on stent grafts is not limited to abdominal aortic aneurysm repair, but could be applied in many stent graft applications such as other aneurysm repair and vessel malformation and occlusion.

The foams described above are preferably highly compressible, so as to keep the crimped profile low for better delivery. In addition, it is preferable that the gasket member be substantially impervious to the flow of blood, at least when in a partially compressed state. When used throughout for the present invention, materials which are substantially impervious to the flow of blood include materials which become substantially impervious to the flow of blood after being saturated with blood. When the stent tubes and graft members, described below, are inserted and expanded within the gasket 30, the gasket 30 will compress. In this state, the gasket should be substantially impervious to blood so as to prevent blood from flowing through the interior 18 of self-expanding member 12 and into the aneurysm. Gasket 30 can be attached to self-expanding member 12 by any number of means including polyurethane glue, a plurality of conventional sutures of polypropylene, DACRON®, or any other suitable material and attached thereto. Other methods of attaching gasket 30 to self-expanding member 12 include adhesives, ultrasonic welding, mechanical interference fit and staples.

As seen from FIG. 2, precursor stent 10 preferably includes a number of radiopaque markers 15. As shown, markers 15 are coils of radiopaque metal, wrapped around the struts of the precursor stent. The markers are positioned along the stent

so that the physician can better know the exact position of the stent during deployment when viewed under fluoroscopy. Markers **15** are preferably made from 0.010" diameter tantalum (Ta) wire wrapped tightly around the struts. Three markers are used; two near the distal end of the device, and one proximal thereto. The distal two are 180° apart, and the proximal one is equally spaced between the distal two when viewed from a rotation where the top two are spaced as far apart as possible. This proximal marker then aids proper rotational positioning of the device. Specifically, one of the distal markers is 5 mm long and is adjacent to the aperture **34** in the gasket; the other is 2 mm long and is adjacent to the hole **36**. Since hole **36** should be placed adjacent to the right side of the aneurysm, as shown in FIG. **19**, the small distal marker should be placed on the right side; the proximal marker (also 2 mm long) should appear fluoroscopically to be midway between the upper two markers.

As seen from FIGS. **2** and **3**, the precursor stent further includes an occlusive member **32** attached to self-expanding member **12**. The occlusive member covers at least a portion of the interior of the self-expanding member. The occlusive member covers the interior of self-expanding member **12** in such a way that a lumen **5** of the expandable member which provides passageway from its proximal end **14** to its distal **16** is at least partially blocked. Occlusive member **32** further includes two openings **34** and **36** extending therethrough. Opening **34** is relatively small and is designed to receive a guidewire, wherein such guidewire helps deliver precursor stent **10** to the target site. Opening **36** is relatively large, and is designed to receive another guidewire having a loaded stent graft proximal thereto. As will be explained below, the occlusive member helps to ensure proper side by side placement of the two stent-grafts.

Precursor stent **10** acts to temporarily scaffold the gasket member within the body, until the stent-grafts are deployed (see FIG. **19**). Shown in FIG. **4** is a preferred embodiment of a stent **40** for use in a stent-graft in accordance with the present invention. Stent **40** is made from a plurality of interconnected struts **44**, and has an interior surface **43A** and an exterior surface **43B** (shown in FIG. **15**). FIG. **4** shows stent **40** in its fully deployed, un-crimped state. As will be appreciated by those skilled in the art, stent **40** should be crimped to a smaller diameter prior to insertion into a patient. Stent **40** is preferably made from superelastic Nitinol, and have enough outward force to stay within the body, without the use of the precursor stent **10**. Stent **40** is preferably made from a single tube of Nitinol, having the following features laser cut therein. Stent **40** has a number of hoops **42** comprising a number of struts **44** making a diamond shape configuration, wherein each hoop preferably has 9 diamonds. Stent **40** further includes a number of sinusoidal rings **50** for connecting adjacent hoops to one another. The sinusoidal rings are made from a number of alternating struts **52**, wherein each ring preferably has 54 struts. As will be explained in detail below in connection with the discussion of FIGS. **9-14**, stent **40** includes a distal attachment means **54** and a proximal attachment means **56**.

Stent **40** has a proximal hoop **48** and a distal hoop **46**, also referred to as anchors. The proximal hoop is flared, and is exposed after the graft has been attached thereto. The diamond pattern for the anchors, as well as the other hoops, provide the hoops with radial and longitudinal stiffness. The longitudinal strength provides for better mechanical fixation of stent **40** to a graft (described below). The radial strength provides the distal hoop **46** with better attachment and sealing to stent gasket or precursor stent **10**, and provides the proximal hoop **48** with better fixation and sealing to the arterial

wall. In one preferred embodiment, the proximal and distal hoops have greater radial and longitudinal strength than the hoops therebetween. This creates a stent-graft having stiff ends for anchoring, but a more flexible body for navigation through the vasculature. The stiffer ends can be accomplished by changing the dimensions of the struts for the end hoops, or by varying the heat treatment of the end hoops during manufacture. The rings allow the stent to bend more easily, and generally provide for more flexibility when the stent is being delivered through a tortuous vessel. When a non-compliant graft is attached to stent **40**, the strength of the diamond hoops scaffolds any graft folding into the blood flow lumen, while maintaining a tight kink radius.

As stated above, stent **40** preferably has a graft member attached thereto. The graft member covers at least a portion of the interior or exterior of stent **40**, and most preferably covers substantially all of the exterior of the stent **40**. Shown in FIGS. **5-7** is an embodiment of a tubular graft **60** for use with the present invention. Graft member **60** can be made from any number of materials known to those skilled in the art, including woven polyester, Dacron, Teflon or polyurethane. Graft **60** has a proximal end **64**, a distal end **62**, and a longitudinal axis **66** extending therebetween. As seen from FIG. **5**, graft **60** has a plurality of longitudinal pleats **68** extending along its surface, and being generally parallel to longitudinal axis **66**. As seen from FIG. **7**, when the graft **60** is collapsed around its center, much as it would be when it is delivered into a patient, the pleats in the graft come together as a series of radially oriented regular folds which pack together efficiently, so as to minimize wrinkling and other geometric irregularities. Upon subsequent expansion, graft **60** assumes its natural cylindrical shape, and the pleats or folds uniformly and symmetrically open.

The pleats provide for a more uniform crimping of the graft **60**, which helps the assembled stent graft (stent **40** attached to graft **60**, as will be discussed below) to crimp into a relatively low profile delivery system, and provides for a controlled and consistent deployment therefrom. In addition, pleats **68** help facilitate stent graft manufacture, in that they indicate the direction parallel to the longitudinal axis, allowing stent to graft attachment along these lines, and thereby inhibiting accidental twisting of the graft relative to the stent after attachment. The force required to push the stent-graft out of the delivery system may also be reduced, in that only the pleated edges of the graft make frictional contact with the inner surface of the delivery system. One further advantage of the pleats is that blood tends to coagulate generally uniformly in the troughs of the pleats, discouraging asymmetric or large clot formation on the graft surface, thereby reducing embolus risk.

In one preferred embodiment, the depths of pleats **68** range from 0.06 inch to 0.07 inch for a graft having a crimped inner diameter of 0.08 inch and a crimped outer diameter ranging from 0.131 inch to 0.155 inch. This combination of pleat depth and inner and outer diameters results in pleat frequencies that generally preclude the existence of excessive radial graft flaps across the range of diameters for the device.

As seen best from FIG. **6**, graft **60** preferably includes a plurality of radially oriented pleat interruptions **70**. The pleat interruptions are substantially circular and are oriented perpendicular to longitudinal axis **66**. While the pleats **68** mentioned above provide for a uniform crimping of graft **60**, they may tend to increase kink propensity since they run perpendicular to the graft's natural folding tendencies when bent along its axis. Pleat interruptions **70** allow the graft to better bend at selective points. This design provides for a graft that has good crimpability and improved kink resistance.

FIG. 9 shows an up-close view of distal attachment means 54 of stent 40. Distal hoop 46 of stent 40 has a plurality of attachment tabs 82 extending therefrom which are formed from the joining together of two struts 44(a) and 44(b). Attachment means 54 comprises two apertures 84 (first aperture) and 86 (second aperture) extending therethrough. As seen from FIG. 10, graft 60 also preferably includes two apertures 74 and 76 (which can be initially created during the attachment process) which are coextensive with apertures 84 and 86 when graft 60 is placed over stent 40 for attachment. Finally, attachment means 54 includes a staple 90 having a crown 92 and attachment legs 94 (first leg) and 96 (second leg) extending therefrom. Attachment leg 96 extends through apertures 76 and then aperture 86. Simultaneously, leg 94 bends around notch 85, but it does not penetrate graft 60 like leg 96. Thereafter, attachment leg 94 and 96 are bent back through apertures 84 and 74 and in towards crown 92, so as to attach the distal end of the graft to the distal end of the stent as shown in FIG. 11. Legs 94 and 96 make contact with crown 92 after attachment. Preferably, there are six staples at the distal end.

FIG. 12 shows an up-close view of proximal attachment means 56 of stent 40. Proximal hoop 48 of stent 40 has a plurality of members 110 occurring at the joining of four struts 44(c)–44(f). Attachment means 56 comprises three apertures 112 (first aperture), 114 (middle aperture) and 116 (second aperture) extending therethrough. As seen from FIG. 13, graft 60 also preferably includes three apertures 121, 123 and 125 (which can be initially made during the attachment process by puncturing therethrough with a staple) which are coextensive with apertures 112, 114 and 116 when graft 60 is placed over stent 40 for attachment. Finally, attachment means 56 includes a staple 120 having a crown 122 and legs 124 (first leg) and 126 (second leg) extending therefrom. Legs 124 and 126 extend through apertures 112 and 116 and then through apertures 121 and 125 respectively. Thereafter, legs 124 and 126 are bent back through apertures 124 and 114 and in towards crown 122, so as to attach the proximal end of the graft to the proximal end of the stent as shown in FIG. 14. Legs 124 and 126 make contact with crown 122 after attachment. Preferably, there are three staples at the proximal end.

The above staple aperture design has many advantages for attaching a stent to a graft. Because the legs of the staple are folded around and imbedded within a pocket or the like, any risk of puncturing an inflation balloon is minimized. In addition, the structural integrity of the stent-graft is believed to be increased in that these staples should more securely attach the graft to the stent compared to prior art designs which use suture or adhesives to attach the graft to the stent. Staples 90 and 120, illustrated in FIG. 8, can be made from any number of materials known in the art, including tantalum alloys, platinum alloys or stainless steel, such as 316 LVM stainless steel. The staples may take on other configurations and shapes, and can be coated for lubricity purposes. Having the staples made from a radiopaque material helps the physician in accurately deploying the device.

Another feature of stent-graft 80, illustrated in FIG. 8, can be better understood by referring to its delivery apparatus 130 shown in FIG. 15. Apparatus 130 is very similar to other self-expanding delivery apparatus described in the above incorporated references. Apparatus 130 includes an outer sheath 132 which is essentially an elongated tubular member, similar to ordinary guiding catheters which are well known to those of ordinary skill in the art. An example of a particularly preferred outer sheath is described in commonly assigned U.S. Pat. No. 6,019,778 issued on Feb. 1, 2000, which is hereby incorporated herein by reference. Sheath 132 has a

distal end 134 and a proximal end (not shown). Apparatus 130 also includes an inner shaft 140 located coaxially within the outer sheath 132 prior to deployment. The inner shaft has a distal end 142 and a proximal end (not shown). The distal end 142 of the shaft has at least two grooves 144 disposed thereon. Stent 40 preferably has a number of flanges 41 disposed at its proximal end. The flanges on the stent are set within the grooves of the inner shaft, thereby releasably attaching the stent to the inner shaft. The delivery system for precursor stent 10 is also similar, having an outer sheath and an inner shaft wherein the shaft has grooves to receive flanges 28 of precursor stent 10.

The advantages of flanges 41 on stent 40 and flanges 28 on precursor stent 10 and the grooves on the inner shafts of their delivery system is that they may allow for partial deployment of the stents and recapture within the delivery apparatus if the physician is not pleased with the position of the stent. The present invention allows the physician to partially deploy one of the stents (precursor stent 10 or stent-graft 80) while the flanges remain within the sheath. The flange groove combination allows the physician to “pull” the stent back into the delivery device if the placement is not optimal.

The advantages of flanges 28 on precursor stent 10 and the grooves on the inner shafts of their delivery system can best be described by referring to FIGS. 23–25. FIG. 23 shows an exemplary embodiment of the delivery apparatus 130 for stent gasket or precursor stent 10. Apparatus 130 is very similar to other self-expanding delivery apparatus described in the above incorporated references. Apparatus 130 includes an outer sheath 132 which is essentially an elongated tubular member, similar to ordinary guiding catheters which are well known to those of ordinary skill in the art. An example of a particularly preferred outer sheath is described in commonly assigned U.S. Pat. No. 6,019,778 issued on Feb. 1, 2000, which is hereby incorporated herein by reference. Apparatus 130 also includes an inner shaft 140 located coaxially within the outer sheath 132 prior to deployment. Inner shaft 140 includes a number of grooves 144. As seen from FIG. 24, this arrangement allows for partial deployment of precursor stent 10 and recapture within the delivery apparatus if the physician is not pleased with the initial position of the stent. The present invention allows the physician to partially deploy precursor stent 10 while the flanges remain within the sheath. The flange groove combination allows the physician to “pull” the stent back into the delivery device if the placement is not optimal.

In order to prevent the physician from prematurely completely deploying the precursor stent 10, a releasable stop 150 is preferably placed on the inner shaft. The stop could be a ring having a greater diameter than the sheath, so that as the sheath is pulled proximally along the inner shaft it hits the stop, and prevents full deployment of the entire precursor stent 10. The stop is preferably releasably attached to the inner member so that it can be released from its engagement with the inner shaft to allow the outer member to slide back enough to fully deploy the entire precursor stent 10 within the body.

FIGS. 16–18 generally show how the above described invention is deployed within the body. Prior to what is shown in FIG. 16, the physician would first insert the precursor stent 10, having the gasket member attached thereto, into the body with the aid of guidewire 200, which remains in the body after deployment. The stent gasket or precursor stent 10 is delivered through one of the patient’s femoral arteries and into a first iliac artery 1 and deployed within the infrarenal neck 3. Thereafter, the delivery device for the precursor stent 10 is removed, without removing guidewire 200, and another

11

guidewire **202** is inserted through the other femoral artery and into the other iliac artery **2**. Because the size of opening **36** in occlusive member **32** is relatively large, the physician can only maneuver guidewire **202** therethrough. Thereafter stent-graft delivery apparatus **130a** and **130(b)** are inserted into femoral arteries and into the iliac arteries **1** and **2** by sliding them over guidewires **200** and **202**, and accurately delivering them to the target site. Thereafter, both stent-grafts **80(a)** and **80(b)** are either separately or simultaneously deployed within the body. Ultimately the distal ends of the stent grafts reside level with each other, just below the renal arteries, and some distance above the distal end of the stent gasket. The bodies of the stent grafts pass through the stent gasket and through the aneurysm sac.

After properly delivery, precursor stent **10** and stent-grafts **80(a)** and **80(b)** should appear as they do in FIG. **19**. Precursor stent **10** along with its attached gasket member **30** are firmly secured within the infrarenal neck **3**. The outward force of the stent-grafts **80** on the precursor stent **10** help to secure the device within the body. The proximal ends of the stent-grafts are firmly attached to the iliac arteries **1** and **2**. Thereafter blood will flow from the abdominal aorta **302** down into and through stent-grafts **80(a)** and **80(b)** and into iliac arteries **1** and **2**, thereby bypassing the aneurysmal sack **304**. If all the components are placed accurately, distal end of the device should appear as it does in FIG. **20**.

In order to prevent the physician from prematurely completely deploying the precursor stent **10**, a releasable stop is preferably placed on the inner shaft. The stop could be a ring having a greater diameter than the outer member, so that as the outer member is pulled proximally along the inner shaft it hits the stop, and prevents full deployment of the entire precursor stent **10**. The stop is preferably releasably attached to the inner member, by threads, snap fit or the like, so that it can be released from its engagement with the inner shaft to allow the outer member to slide back enough to fully deploy the entire precursor stent **10** within the body.

Although particular embodiments of the present invention have been shown and described, modification may be made to the device and/or method without departing from the spirit and scope of the present invention. The terms used in describing the invention are used in their descriptive sense and not as terms of limitations.

What is claimed is:

1. A monolithic, hollow substantially cylindrical radially expandable stent having proximal and distal open ends and a

12

longitudinal axis extending therebetween, said stent for deployment within a human body vessel, said stent comprising:

- a. a plurality of hoops comprising a plurality of interconnected struts forming a substantially diamond shape configuration, said stent having a proximal end hoop and a distal end hoop, wherein said distal end hoop and said proximal end hoop are configured to have greater radial and longitudinal strength than the hoops therebetween and said proximal hoop is flared;
- b. a plurality of sinusoidal rings connecting adjacent hoops to one another, said sinusoidal rings being formed from a plurality of alternating struts, the plurality of alternating struts being substantially shorter in length than the plurality of interconnected struts of the plurality of hoops, each of the plurality of sinusoidal rings having more than twice the number of struts forming the plurality of hoops and each of said plurality of sinusoidal rings having a periodic structure of less than one-half of the periodic structure of said plurality of hoops, wherein the union of each of the plurality of sinusoidal rings and each of the plurality of hoops is made at the apex of at least one diamond configuration of the plurality of hoops and the apex of at least one intersection of the plurality of alternating struts of the sinusoidal rings; and
- c. proximal and distal attachment devices for securing a graft member to the substantially cylindrical radially expandable stent, the proximal attachment device being positioned distal of the proximal open end of the stent such that the proximal end hoop of the stent is configured to be exposed to a body vessel, said proximal and distal attachment devices comprising tabs formed from the joining of two struts and having at least two apertures therein, wherein the plurality of hoops, the plurality of sinusoidal rings and the proximal and distal attachment devices form a monolithic structure.

2. The stent according to claim **1** wherein said stent is a self-expanding stent.

3. The stent according to claim **2** wherein said stent is made from a superelastic nickel titanium alloy.

4. The stent according to claim **1**, wherein at least one of said distal and proximal end hoops is formed so as to have a larger diameter than a hoop adjacent thereto.

* * * * *