

US007509758B2

(12) **United States Patent**  
**Nesseth**

(10) **Patent No.:** **US 7,509,758 B2**  
(45) **Date of Patent:** **Mar. 31, 2009**

(54) **REVERSIBLE HITCH STRUCTURE FOR  
LOADER ATTACHMENTS**

(75) Inventor: **Clinton Nesseth**, Cameron, WI (US)

(73) Assignee: **NTH Inc.**, Barron, WI (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 338 days.

3,941,262 A *	3/1976	Moser et al.	414/722
3,984,016 A	10/1976	Kuhn	
3,985,249 A *	10/1976	Aker et al.	414/723
4,013,182 A *	3/1977	Pratt et al.	414/723
4,030,624 A *	6/1977	Matthews	414/723
4,164,821 A	8/1979	Vanchot	
4,749,048 A	6/1988	Kelly	
4,778,011 A	10/1988	Hutchison	
4,837,951 A	6/1989	Verseef	

(21) Appl. No.: **11/194,108**

(22) Filed: **Jul. 28, 2005**

(Continued)

(65) **Prior Publication Data**

US 2006/0070759 A1 Apr. 6, 2006

**Related U.S. Application Data**

(60) Provisional application No. 60/592,800, filed on Jul. 30, 2004.

(51) **Int. Cl.**

*E02H 5/04* (2006.01)

*E02F 3/76* (2006.01)

(52) **U.S. Cl.** ..... **37/231; 37/408; 37/267;**  
172/272; 172/273

(58) **Field of Classification Search** ..... 37/266,  
37/268, 267, 407-410, 449, 231; 414/723;  
172/272, 273

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

539,888 A *	5/1895	Yorgey	172/703
2,622,349 A *	12/1952	Kinnan	172/445.2
2,883,772 A *	4/1959	Dodge	37/409
3,059,357 A *	10/1962	Irish	37/449
3,512,665 A *	5/1970	Westendorf	414/723
3,601,203 A *	8/1971	Holmstrom	172/719
3,672,521 A	6/1972	Bauer et al.	
3,753,508 A	8/1973	Carpenter	
3,851,711 A	12/1974	Steppe	

**OTHER PUBLICATIONS**

ATI Corporation, ATI Products, ATI Skid Steer & Tractor Loader Attachments, 3-Point Hitch Quick Attach, <http://www.abcgroff.com/ic/ati4a.htm>, 2 pages.


*Primary Examiner*—Thomas A Beach

(74) *Attorney, Agent, or Firm*—Merchant & Gould P.C.

(57) **ABSTRACT**

A hitch structure for mounting attachments to a vehicle such as a skid steer loader is disclosed herein. The hitch structure includes a universal, reversible hitch structure. The hitch structure includes a first end positioned opposite a second end, a fixed locking structure located adjacent each of the first end and the second end, the fixed locking structure constructed for receiving a toe end of an attachment carrier of a loader vehicle. The hitch structure also includes a removable locking structure with a slot for receiving a locking wedge positioned adjacent a heel end of the attachment carrier. The removable locking structure is removably engageable with the hitch structure alternatively adjacent either the first end or the second end of the hitch structure to form a clamping structure with the fixed locking structure located at the opposite end from the removable locking structure for mounting the attachment to the vehicle.

**21 Claims, 7 Drawing Sheets**



# US 7,509,758 B2

Page 2

## U.S. PATENT DOCUMENTS

5,098,252	A *	3/1992	Sheesley et al. ....	414/723	6,227,792	B1 *	5/2001	Baker et al. ....	414/723
5,114,299	A *	5/1992	Roche et al. ....	414/722	6,238,130	B1 *	5/2001	Youngers ....	403/322.4
5,224,816	A *	7/1993	Kaczmarczyk et al. ....	414/723	6,256,910	B1	7/2001	Grozde	
5,248,000	A	9/1993	Goto et al.		6,267,818	B1	7/2001	Volpe, Jr.	
5,252,022	A *	10/1993	Culp et al. ....	414/723	6,314,666	B1	11/2001	Klemenhagen et al.	
5,562,398	A *	10/1996	Knutson ....	414/732	6,360,459	B1 *	3/2002	Brookhart et al. ....	37/442
5,590,483	A *	1/1997	Kim ....	37/468	6,386,822	B1 *	5/2002	Burr ....	414/723
5,641,157	A	6/1997	Mays et al.		6,419,030	B1	7/2002	Turner	
5,685,689	A *	11/1997	Schneider et al. ....	414/723	6,470,604	B1	10/2002	Foster et al.	
5,715,613	A	2/1998	Ebert		6,560,904	B2	5/2003	Guggino	
5,724,755	A	3/1998	Weagley		6,604,752	B1	8/2003	Gerres et al.	
5,771,979	A	6/1998	Alanis		6,709,224	B2 *	3/2004	Heiple ....	414/723
5,909,961	A *	6/1999	Pullman ....	37/444	2002/0043009	A1	4/2002	Fulton, III	
5,938,399	A *	8/1999	Knutson ....	414/722	2003/0005605	A1 *	1/2003	Kaczmarski et al. ....	37/444
6,070,343	A	6/2000	Sheldon		2003/0061741	A1	4/2003	Guggino	
6,112,438	A	9/2000	Weagley		2005/0193597	A1 *	9/2005	Sutton et al. ....	37/266
					2007/0107271	A1 *	5/2007	Weagley et al. ....	37/407

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3

FIG. 4




FIG. 6





FIG. 5






FIG. 7






FIG. 8

1

## REVERSIBLE HITCH STRUCTURE FOR LOADER ATTACHMENTS

### CROSS REFERENCE TO RELATED APPLICATIONS

This application claims priority from provisional application Ser. No. 60/592,800, filed Jul. 30, 2004, and which is incorporated herein by reference.

### FIELD OF THE INVENTION

This invention relates generally to loader attachments for vehicles such as skid steer loaders, tractors, or the like and more particularly to a reversible hitch structure for loader attachments.

### BACKGROUND OF THE INVENTION

A wide variety of loader attachments for vehicles such as skid steer loaders, tractors or the like are available and in use. Generally, most attachments include a hitch portion and a workpiece portion. The hitch portion of the attachments is used for mounting the attachments to the loader vehicles. The workpiece portion of the attachments are constructed for a variety of uses and may include augers, backhoes, brooms, buckets, trenchers, cutters, chippers, concrete mixers, crushers, diggers, dozer blades, graders, rakes, pallet forks, snow blowers, tillers, scrapers, clam shells, plows, bale spears, etc. Vehicles such as skid steerers, tractors, or the like typically include a structure at the front end or the back end of the loader for fixedly engaging the loader attachments so that the attachments can be operated and moved, generally by hydraulic power, by the vehicle. Such "hitch" configurations are different from the typical trailer hitch structures used to simply tow or push trailer-type assemblies. Most loader vehicle companies have designed their vehicles to include a universal type structure for engaging a plurality of attachments. One common structure found in the art is what is called a toe-heel attachment carrier that is used to engage the hitch portion of the attachments. Most vehicle companies have also designed their loader attachments with a universal type of a hitch so that they can be used with the toe-heel attachment carriers of vehicles of different manufacturers. In this manner, loader vehicles can use a variety of attachments manufactured by different companies for a variety of purposes, given that the attachment carriers and the hitch structures found on the attachments contain universal counterparts.

Whether it be universal or not, despite the versatile use of front end loader vehicles and the multitude of attachments designed for them, there is no hitch structure in the art that allows reversible coupling of loader attachments to such vehicles. It is conceivable that certain workpieces may be designed to be reversible implements where two sides of the workpiece, e.g., the top and the bottom sides, can be utilized for different purposes. For example, it is conceivable that a plow blade may have a top edge containing rubber material and a bottom edge containing metal material. The rubber edge may serve a different function than the bottom metal edge and reversibility of such a blade allows both edges to be utilized. Reversibility of, for example, a plow blade may also be useful for wear reasons.

However, the art lacks a hitch structure that would allow the reversible use of such an implement. More importantly, the art lacks a reversible hitch structure that can be used with the universal attachment carriers found on most conventional loader vehicles. Thus, only one-sided implements are commonly found in the art.

2

What is needed in the art is a hitch structure that allows multiple sides of an attachment workpiece to be utilized. More importantly, what is needed in the art is a reversible hitch structure that can be made universal so that it can be used with existing vehicle attachment carriers.

### SUMMARY OF THE INVENTION

The invention provides an improved hitch structure used for connecting a loader attachment to a loader vehicle. The loader attachment includes a workpiece portion and a hitch portion. The hitch structure is configured to enable connection of the workpiece to the loader vehicle in either of two orientations, the orientations being 180° from each other, whereby the workpiece can alternatively be used in two or more different orientations.

In certain embodiments, the hitch structure may include a first end positioned opposite a second end, a fixed locking structure located adjacent each of the first end and the second end, the fixed locking structure constructed for receiving a toe end of an attachment carrier of a loader vehicle and a removable locking structure including a slot for receiving a locking wedge positioned adjacent a heel end of the attachment carrier. The removable locking structure is removably engageable to the hitch structure alternatively adjacent either the first end or the second end of the hitch structure and is adapted to form a clamping structure with the fixed locking structure that is located at the opposite end from the removable locking structure.

In certain embodiments, the hitch structure may be universal to accommodate already existing attachment carriers of conventional loader vehicles.

### BRIEF DESCRIPTION OF THE DRAWINGS

Referring now to the Drawings, wherein like numerals represent like parts throughout the several views:

FIG. 1 is a right side elevation view of a skid steer loader vehicle, shown with phantom lines, including a loader attachment, wherein the loader attachment includes a plow blade workpiece, also shown with phantom lines, and a reversible hitch structure incorporating the principles of the invention;

FIG. 2 is a right rear perspective view of the loader attachment of FIG. 1, including the plow blade workpiece of FIG. 1, shown with phantom lines, and the reversible hitch structure of FIG. 1 mounted to the plow blade workpiece;

FIG. 3 is a back view of the loader attachment of FIG. 2, wherein the insertion paths of the removable locking structures of the reversible hitch structure when the loader attachment is to be reversed is shown with phantom lines;

FIG. 4 is a top view of the loader attachment of FIG. 2;

FIG. 5 is a left side elevation view of the loader attachment of FIG. 2, illustrated with a section of the reversible hitch structure cut-out to expose the internal details thereof, shown in combination with an attachment carrier of the skid steer loader of FIG. 1 in an unsecured orientation;

FIG. 6 is another left side elevation view of the loader attachment similar to FIG. 5, shown in combination with the attachment carrier of the skid steer loader of FIG. 1 in a secured orientation;

FIG. 7 is another left side elevation view of the loader attachment similar to FIG. 6, wherein the loader attachment is shown in an orientation that is 180° from that of FIG. 6; and

FIG. 8 is a right rear perspective view of another embodiment of a reversible hitch structure incorporating the principles of the invention.

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to FIGS. 1-7, there is generally illustrated therein a preferred embodiment of a reversible hitch structure **40** that incorporates the principles of this invention. In FIG. 1, the reversible hitch structure **40** is illustrated as part of a loader attachment **30** that has a plow-blade workpiece **60**. The loader attachment **30** is shown attached to and being movable by a skid steer loader vehicle **10**. It will be understood that the invention is not limited to use with a skid steer loader vehicle illustrated in FIG. 1, but that the skid steer loader vehicle **10** is simply representative of one embodiment of a vehicle that can be used to practice the principles of this invention.

Referring to FIG. 1, the skid steer loader vehicle **10** generally includes a chassis **11** containing an engine and power train for moving and operating the vehicle. The vehicle includes a plurality of wheels, generally indicated at **12**, for moving the vehicle over the ground or support surface. The vehicle **10** typically has a cab portion **13** wherein an operator sits to control the vehicle, and a primary pair of pivotally movable lift arms **14** that can be raised and lowered about their rear pivot positions, generally indicated at **15** to raise and lower the forward ends **14a** of the operator arms **14** relative to the ground or support surface. A pair of hydraulic lift cylinders **16** provides the motive force for rotatably moving the operator arms **14**.

The skid steer loader vehicle **10** also has an attachment mounting structure **20** pivotally connected to the forward ends **14a** of the operator arms **14** for engaging the loader attachment **30**. Attachment mounting structure **20** for engaging the loader attachment **30** is depicted as an attachment carrier **21** that is found on most conventional loader type vehicles. It will be understood that other types of engagement structures may be used on the loader type vehicles for engaging the loader attachments.

The attachment carrier **21** provides detachable mounting and connection to various implements such as the plow-blade workpiece **60** of FIG. 1. The attachment carrier **21** is movable and pivotable relative to the forward ends **14a** of the operator arms **14** by one or more hydraulic cylinders **17**. Cylinders **17** are used to pivot and move the attachment carrier **21** and attached implements relative to the forward ends **14a** of the operator arms **14**.

Illustrative key features for the attachment carrier can take a variety of forms, as well known in the art and as, for example, illustrated in U.S. Pat. Nos. 3,753,508; 3,984,016; 3,672,521; and 6,604,752, all of which are incorporated herein by reference in their entirety.

Since attachment carriers can take various forms and configurations in the art, the attachment carrier **21** is illustrated in FIGS. 1, 5-7 in diagrammatic fashion, with only the key features shown. Referring to FIGS. 5-7, a preferred configuration of a typical attachment carrier **21** has a wedge shaped toe-like structure **22** adjacent its upper end **23** and a heel-like structure **24** adjacent its lower end **25**. The attachment carrier **21** is pivotally connected at point **26** near the lower end **25** to the lift arms **14** of the skid steer vehicle **10**. The cylinders **17** are connected to the attachment carrier **21** near its upper end **23** for tilting the attachment carrier **21** about point **27**. The attachment carrier **21** includes a locking wedge **28** which can be operated by a hand lever **29** to raise and lower the locking wedge. In the extended position (shown in FIGS. 6 and 7), the wedge **28** projects through an opening **70** at the bottom end **25** of the attachment carrier **21**. For simplicity's sake, the attachment carrier **21** is conveniently referred to as a toe-heel attachment carrier since it has a toe **22** and a heel **24** that are

fundamental to its structure, whether by way of framing or by the use of solid metal material to create the toe and heel carrier features.

Since configurations and operations of such skid steer loader vehicles and attachment carriers found on these vehicles are well known in the art, further details thereof will not be provided herein, it being understood that those skilled in the art clearly understand the nature of such vehicles and how they operate in numerous versatile situations. Attachment and detachment of the attachment carrier **21** to and from the reversible hitch structure **40** of the invention will be described in greater detail further below.

Referring now to FIG. 2, a loader attachment **30** including a plow-blade workpiece **60** and the reversible hitch structure **40** of the present invention is illustrated in isolation from the skid steer vehicle **10**. The plow-blade workpiece **60** is shown with phantom lines. The plow-blade workpiece includes a main body portion **61**, an upper edge **62** and a lower edge **63**. The upper edge **62** may be constructed of a different material than the lower edge **63**. It shall be understood that the reversible hitch structure **40** of the present invention is not limited to use with the plow-blade workpiece **60** illustrated in the Figures, but that the plow blade **60** is simply representative of one embodiment of a loader attachment workpiece that can be attached to a loader vehicle with the use of the reversible hitch structure **40** of the present invention. Various kinds of other workpiece implements discussed above, such as bucket assemblies, fork lift members, clam shells, and the like, especially loader implements that can be used in a reversible manner, can be secured to a vehicle, such as the skid steer vehicle **10**, with the use of the reversible hitch structure **40** of the present invention. Although depicted as being welded to the plow-blade workpiece **60** in the Figures, it shall be understood that the reversible hitch structure **40** of the present invention can be mounted to workpieces in various ways including by welding, with fasteners, etc.

The reversible hitch structure **40** of the present invention is shown in solid lines in FIG. 2. As shown in FIG. 2, the reversible hitch structure **40** is depicted as a universal hitch structure that is configured to be used in combination with those attachment carriers found in most conventional loader vehicles. It will be understood, however, that the universal type reversible hitch structure is simply one representative embodiment of the reversible hitch structure **40** incorporating the principles of the invention. The universality of the reversible hitch structure **40** will be discussed in further detail below.

As shown in FIG. 2, the reversible hitch structure **40** includes a right hitch structure **41** and a left hitch structure **42** that generally include corresponding structure. In certain embodiments, the reversible hitch structure **40** of the present invention may be configured of one solid piece instead of two separate pieces, as will be discussed further below.

The right hitch structure **41** and the left hitch structure **42** generally have similar structure, therefore the reversible hitch structure **40** of the present invention will be described with respect to only the right hitch structure **41**, it being understood that the discussion applies equally to both the right and the left structures **41**, **42**. Corresponding structure, when identified, will be characterized on the left hitch structure **42** using the same reference number used on the right hitch structure **41**, except that the reference numerals identifying corresponding structure on the left hitch structure **42** will include an apostrophe or prime designation.

The reversible hitch structure **41** includes a first sideplate **43** and a second side plate **44**. The reversible hitch **41** also includes a top plate **45**, a bottom plate **46** (shown in FIG. 3),

5

and a face plate 47 disposed between and separating the side plates 43, 44. Adjacent the top and bottom plates 45, 46 of the reversible hitch structure 41 are top and bottom locking structures 48 and 49. The top and bottom locking structures 48 and 49 are disposed between the sideplates 43, 44 and protrude at an angle from the top and bottom plates 45 and 46, respectively, to form receptor channels for matingly engaging the toe portion of the attachment carrier, as hereinafter described in more detail. The top and bottom locking structures 48 and 49 include similar structure and are constructed to provide reversibility for the hitch structure 41 of the present invention, as will be described further below.

The top and bottom locking structures 48 and 49 are depicted in the Figures as latching ledges that are universal and are configured to engage the toe-like structure 22 of the attachment carrier 21 found in most of the conventional loader vehicles. In certain other embodiments, the top and bottom locking structures may include different configurations.

As illustrated in FIG. 2, the reversible hitch structure 41 includes a removable locking structure 50 at the opposite end from the top locking structure 48. The removable locking structure 50 is depicted as a key with slots, but may include different configurations in other embodiments. The removable locking structure 50 is configured to be slidably received within either the upper or lower triangular key holes 51, 52 defined in the first and second sideplates 43 and 44. Either the upper or the lower key holes, 51, 52 are utilized depending upon the desired orientation of the loader implement. In the preferred embodiment, the removable locking structure 50 is depicted as a key with slots that are adapted to interfit with the locking wedge of a universal attachment carrier. Along with either the top or the bottom latching ledges, the locking structure 50 forms a universal hitch structure for attaching loader attachments to loader vehicles that contain a universal attachment carrier.

The removable locking structure 50, along with the similarly configured top and bottom locking structures 48 and 49, provides a way to make the hitch structure a reversible hitch structure because it can be slid out of the lower key holes 52 and placed in the upper keyholes 51 after the implement has been rotated 180°.

The removable locking structure 50 includes a V-shaped cross-section 53 that prevents the removable locking structure 50 from rotating once received within the triangular key holes 51, 52. As discussed previously, the removable locking structure 50 includes latching slots 54, each of which is adapted to receive a locking wedge 28 of the attachment carrier 21 to lock the attachment carrier to the reversible universal hitch structure 41. The removable locking structure 50 also includes a handle 55 used to insert the removable locking structure 50 into the key holes 51-52.

In FIG. 2, only handle 55' of the left removable locking structure 50' of the left hitch structure 42 can be seen. The handle 55 is configured with a handle slot 56. A pin 57, slidably attached to the second sideplate 44 of the hitch structure 41 by brackets 58, is used to engage the handle slot 56 and prevent the removable locking structure 50 from sliding out when not engaged by the loader attachment carrier. In FIG. 2, the pin 57' and the brackets 58' of only the left hitch structure 42 can be seen. When desired, using the pin handle 59, the pin 57 can be lifted and moved out of the handle slot 56 to allow slidable removal of the locking structure 50 out of the key holes 51-52.

As depicted in the Figures, the removable locking structure 50 includes a larger (wider) latching slot 54a and a smaller (narrower) latching slot 54b. The different sized slots provide

6

universality to the hitch structure since it is known in the art that certain loader vehicles contain wider attachment carriers and contain locking wedges that are spaced further apart than those of certain other manufacturers of loader vehicles.

One way in which the reversible hitch structure of the invention can be used in combination with loader vehicles is illustrated in FIGS. 5-7. In FIGS. 5-7, the left hitch structure 42 is shown in fragmented fashion, with a portion cut-out, along with the attachment carrier 21, and illustrates operation of the invention. In operation, the operator of the loader vehicle manipulates the toe 22 of the attachment carrier of the loader vehicle until it cooperatively matingly engages the top locking structure 48' of the hitch 42. The operator then, using the cylinders 17 and lift arms 14 of the vehicle 10, starts to lift the implement and pivots the bottom of the attachment carrier toward bottom plate 46' of the hitch structure 42 until the attachment carrier 21 abuts the faceplate 47', as depicted by the arrow in FIG. 5. Once the attachment carrier abuts against the faceplate 47' of the hitch structure 42 and the heel 24 of the attachment carrier 21 is resting adjacent the latching slots 54' of the removable locking structure 50', the operator rotates the lever 29 of the attachment carrier 21 lowering and locking the wedges 28 within the latching slots 54' of the removable locking structure 50'. In this manner, the implement is securely locked onto the attachment carrier of the vehicle 10. The triangular shaped lower key holes 52' along with the shape of the removable locking structure 50' prevent any rotation of the removable locking structure 50' within the key holes 52', and the wedges 28 penetrating through the latching slots 54' prevent any lateral movement of the removable locking structure 50' within the key holes 52'.

If use of the reverse side of an implement is desired, the operator detaches the attachment carrier from the hitch 42, removes the pin 57' from the handle 55', slides the removable locking structure 50' out of its retaining slots 52', reverses the implement by rotating it 180°, and then slides the removable locking structure 50' into the keyholes 51 located on the opposite side. The same procedure is mirrored for removal and reinsertion of the removable locking structure 50.

If the loader attachment is small enough in size and weight, the operator can simply manually rotate the implement around 180°. However, if the implement is of substantial size, such as the plow-blade workpiece 60 illustrated in the Figures, a different procedure is recommended. The operator can simply pivot the plow blade 60 down using the cylinders 17 and lay it on the ground face down. The operator can then pull the attachment carrier 21 away from the hitch structure 40 after disengaging the locking wedges 28 from the latching slots 54, 54' and the toe 22 from the top locking structures 48, 48' of the hitch 40. The operator can then slide the removable locking structures 50 and 50' out of the right and left hitch structures 41 and 42 after disengaging the pins 57 and 57'. The right removable locking structure 50 can then be inserted into the upper key holes 51' of the left hitch structure 42 and the left removable locking structure 50' can be inserted into the upper key holes 51 of the right hitch structure 41. The vehicle 10 can then be driven around the implement and after making a U-turn, the vehicle 10 can engage the implement from the opposite edge.

It should be noted that in the embodiment of the right and left hitch structures 41 and 42 depicted in the Figures, the removable locking structure 50 and 50' only have a handle on one side of the removable locking structure and a pin is located on only the second sideplates, as shown in FIGS. 3 and 4. Therefore, the removable locking structure 50 from the right hitch structure 41 must be taken out of the lower key holes 52 of the right hitch structure 41 and be inserted into the

upper keyholes **51'** of the left hitch structure **42** making sure the handle **55** ends up on the same side as the pin **57'** as demonstrated in phantom in FIG. **3**. The same must be done with the removable locking structure **50'** of the left hitch structure **42**. The pin is long enough to be utilized to lock the handle when the removable locking structure is inserted in either the lower keyholes **52** or the upper keyholes **51**. Once the removable locking structures are flipped and inserted into opposite key holes, the same operation can be followed to engage the implement as was discussed previously. In FIG. **7**, the plow-blade workpiece is shown in an orientation that is 180° from that of FIG. **6** after having been reversed.

It should also be understood that, although the hitch structures depicted in the Figures are configured with a pin assembly on only one plate of the hitch structure, other embodiments are contemplated wherein pins are located on both sideplates of the right and left hitch structures, **41**, **42**. In such embodiments, the right removable locking structure can be reinserted into the keyholes of the right hitch structure and the left removable locking structure can be inserted into the keyholes of the left hitch structure, making sure the latching slots are oriented correctly. It is also contemplated that other embodiments may include latching slots or handles defined on both legs of the V-shape of the removable locking structure, dimensioning the sizes and shapes of the slots accordingly. In those embodiments, the removable locking structures may simply be reinserted into the key holes from the same side from which they were removed.

In FIG. **8**, another embodiment of a reversible universal hitch structure **140** incorporating the principles of the invention is shown. This embodiment of the reversible hitch structure includes a generally one-piece construction wherein the right and left hitch structures **141** and **142** are integrally formed with a connection plate **170** interposed therebetween rather than as separate structures that have to be welded onto the workpiece. The connection plate **170** can be used to connect the hitch structure **140** to the workpiece. It will be understood that the hitch structure can take many forms or shapes within the spirit of the invention. For example, in certain embodiments, one long removable locking structure including a single handle instead of two separate removable locking structures with two handles can be used to make the hitch structure reversible and, when desired, universal. In certain other embodiments, one long top or bottom locking structure can be used instead of two separate locking structures wherein the inner sideplates may be eliminated.

Any combination of these variations can be utilized. The shapes and the sizes of the plates of the hitch structure can vary according to the loader attachment workpiece that is used so long as the reversibility of the hitch structure according to the invention is preserved. It will be understood that many variations of the hitch structure of the present invention can be utilized, including, for example, variations which do not require a sliding motion for engaging the reversible locking feature, without departing from the spirit of the invention.

It should also be understood that the top and bottom locking structures **48** and **49** of the hitch structure **41** may be used without the use of a removable locking structure **50** and still provide for full reversibility for the attachment. Since the top and bottom locking structures **48** and **49** include similar structure, they can provide reversibility for the hitch structure **41** of the present invention. The top and bottom locking structures **48** and **49** are disposed between the sideplates **43**, **44** and protrude at an angle from the top and bottom plates **45** and **46**, respectively, to form receptor channels for matingly engaging portions of an attachment carrier. An attachment carrier that is designed to have a first and a second oppositely disposed

coupling members may be coupled to the hitch structure **41** by engaging the receptor channels defined by the top and bottom locking structures **48**, **49**. And if desired, since the top and bottom locking structures **48**, **49** have similar structure, the attachment carrier can be reversed and remounted to the hitch structure. It should be understood that a removable locking structure **50** may be used in combination with the top and bottom locking structures **48**, **49** if a universal toe/heel type of an attachment carrier that is found on most skid steer type loaders is utilized. Otherwise, a removable locking structure **50** may not be needed if a different type of an attachment carrier is utilized.

Although in the foregoing description of the reversible hitch structure **40**, terms such as “top”, “bottom”, “upper”, “lower”, “front”, “back”, “right”, and “left” were used for ease of description and illustration, no restriction is intended by such use of the terms. The reversible hitch structure **40** can be used in any orientation.

It will be appreciated that while a preferred embodiment, description and application of the invention has been disclosed, other modifications of the invention not specifically disclosed or referred to herein will be apparent to those skilled in the art in light of the foregoing description. This invention is intended to provide a specific example of a preferred embodiment structure and application which clearly discloses the apparatus and method of the present invention and its operative principles. Accordingly, the invention is not limited to any particular embodiment or configuration or component parts thereof or to the use of any particular materials for their construction. All alternatives, modifications, and variations of the present invention which fall within the spirit and broad scope of the appended claims are covered.

The above specification, examples and data provide a complete description of the manufacture and use of the composition of the invention. Since many embodiments of the invention can be made without departing from the spirit and scope of the invention, the invention resides in the claims hereinafter appended.

I claim:

**1.** A hitch structure for mounting an attachment to a loader vehicle of the type having a toe/heel type attachment carrier, the hitch structure comprising:

(a) a first end positioned opposite a second end;

(b) a fixed locking structure located adjacent each of the first end and the second end, the fixed locking structure at each of said first and second ends being independently configured to receive the toe end of the attachment carrier of the loader vehicle; and

(c) a removable locking structure including a slot for receiving the heel end of the attachment carrier of the loader vehicle;

(d) wherein the removable locking structure is removably engageable with the hitch structure alternatively adjacent either the first end or the second end of the hitch structure to form a clamping structure with the fixed locking structure located at the opposite end from the removable locking structure for mounting the attachment to the loader.

**2.** A hitch structure according to claim **1**, wherein the removable locking structure includes a key with universal latching slots.

**3.** A hitch structure according to claim **1**, wherein the removable locking structure is slidably disposed with respect to the hitch structure.

**4.** A hitch structure according to claim **3**, further including a locking mechanism for fixedly coupling the removable

locking structure to the hitch structure to prevent the removable locking structure from sliding off from the hitch structure.

**5.** A loader vehicle attachment constructed for mounting to a front side of the loader vehicle, the attachment comprising:

- (a) a workpiece defining a working surface configured to extend in a first direction with respect to the loader vehicle when the workpiece is mounted to the front side of the loader vehicle; and
- (b) a hitch structure connected to the workpiece, the hitch structure being configured to removably connect the workpiece to the front side of the loader vehicle, the hitch structure being configured to enable connection of the workpiece to the loader vehicle in either of two orientations, the orientations being up to 180° from each other, wherein the working surface of the workpiece is configured to extend in the first direction when the workpiece is mounted in either of the two orientations, wherein the hitch structure includes:
  - (i) a first end positioned opposite a second end;
  - (ii) a fixed locking structure located adjacent each of the first end and the second end; and
  - (iii) a removable locking structure constructed to be coupled adjacent either the first end or the second end;
  - (iv) wherein the removable locking structure is removably engageable with the hitch structure alternatively adjacent either the first end or the second end of the hitch structure to cooperatively form a clamping arrangement with the fixed locking structure located at the opposite end from the removable locking structure for connecting the workpiece to the loader vehicle such that the workpiece can be mountable in either of the two orientations up to 180° from each other;

whereby the workpiece can alternatively be used in the two different orientations.

**6.** A loader vehicle attachment according to claim **5**, wherein the workpiece includes a plow blade.

**7.** A loader vehicle attachment according to claim **5**, wherein the removable locking structure includes universal latching slots.

**8.** A loader vehicle attachment according to claim **5**, wherein the removable locking structure is slidably disposed with respect to the hitch structure.

**9.** A loader vehicle attachment according to claim **8**, further including a locking mechanism for fixedly coupling the removable locking structure to the hitch structure to prevent the removable locking structure from sliding off from the hitch structure.

**10.** An attachment assembly for mounting an attachment to a loader type vehicle of the type having an attachment carrier mounted to the front side of the loader vehicle, the attachment carrier having first and second oppositely disposed coupling members, the attachment assembly comprising:

- (a) an attachment constructed for mounting on the attachment carrier, the attachment including:
  - (i) a workpiece; and
  - (ii) a hitch structure connected to the workpiece, the hitch structure configured to removably connect the workpiece to the attachment carrier, the hitch structure being configured to enable connection of the workpiece to the attachment carrier in either of two orientations, the orientations being up to 180° from each other, wherein the hitch structure includes a first end positioned opposite a second end, a first locking structure located adjacent said first end and a second locking structure located adjacent said second end,

said first locking structure configured to cooperatively mate with said first coupling member of the attachment carrier and said second locking structure configured to cooperatively mate with said second coupling member of the attachment carrier;

whereby the workpiece can alternatively be used in two different orientations.

**11.** An attachment assembly according to claim **10**, wherein the workpiece includes a plow blade.

**12.** An attachment assembly according to claim **10**, further including a third locking structure wherein said third locking structure is configured to be detachably mounted to said hitch structure.

**13.** An attachment assembly according to claim **12**, wherein the detachable third locking structure is operatively engageable with the hitch structure alternatively adjacent either said first end or said second end of the hitch structure to cooperatively form with either said first locking structure or said second locking structure a clamping arrangement therebetween, for said first and second coupling members of said attachment carrier.

**14.** An attachment assembly according to claim **12**, wherein the detachable third locking structure includes universal latching slots.

**15.** An attachment assembly according to claim **13**, wherein the detachable third locking structure is slidably disposed with respect to the hitch structure.

**16.** An attachment assembly according to claim **15**, further including a lock to fixedly couple the detachable third locking structure to the hitch structure to prevent the detachable third locking structure from sliding off from the hitch structure.

**17.** A loader vehicle attachment constructed for mounting to a front side of the loader vehicle, the attachment comprising:

- (a) a workpiece; and
- (b) a hitch structure connected to the workpiece, the hitch structure being configured to removably connect the workpiece to the loader vehicle, the hitch structure being configured to enable connection of the workpiece to the loader vehicle in either of two orientations, the orientations being up to 180° from each other; whereby the workpiece can alternatively be used in the two different orientations, the hitch structure further comprising:
  - (i) a first end positioned opposite a second end;
  - (ii) a fixed locking structure located adjacent each of the first end and the second end; and
  - (iii) a removable locking structure constructed to be coupled adjacent either the first end or the second end;
  - (iv) wherein the removable locking structure is removably engageable with the hitch structure alternatively adjacent either the first end or the second end of the hitch structure to cooperatively form a clamping arrangement with the fixed locking structure located at the opposite end from the removable locking structure for connecting the workpiece to the loader vehicle such that the workpiece can be mountable in either of the two orientations up to 180° from each other.

**18.** A loader vehicle attachment according to claim **17**, wherein the removable locking structure includes universal latching slots.

**11**

**19.** A loader vehicle attachment according to claim 17, wherein the removable locking structure is slidably disposed with respect to the hitch structure.

**20.** A loader vehicle attachment according to claim 19, further including a locking mechanism for fixedly coupling the removable locking structure to the hitch structure to pre

**12**

vent the removable locking structure from sliding off from the hitch structure.

**21.** A loader vehicle attachment according to claim 17, wherein the workpiece includes a plow blade.

\* \* \* \* \*