



US007519695B2

(12) **United States Patent**
Farhat et al.

(10) **Patent No.:** **US 7,519,695 B2**
(45) **Date of Patent:** ***Apr. 14, 2009**

(54) **SERVICE QUALITY MONITORING PROCESS**

(75) Inventors: **Jay Farhat**, Foster City, CA (US); **Alla Rozenfeld**, San Carlos, CA (US); **Singam Sunder**, San Jose, CA (US)

(73) Assignee: **iPass Inc.**, Redwood Shores, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **11/810,380**

(22) Filed: **Jun. 4, 2007**

(65) **Prior Publication Data**
US 2007/0239873 A1 Oct. 11, 2007

Related U.S. Application Data

(63) Continuation of application No. 11/126,008, filed on May 9, 2005, now Pat. No. 7,240,112, which is a continuation of application No. 10/318,968, filed on Dec. 13, 2002, now Pat. No. 6,985,945, which is a continuation of application No. 09/732,800, filed on Dec. 7, 2000, now Pat. No. 6,510,463.

(60) Provisional application No. 60/207,670, filed on May 26, 2000.

(51) **Int. Cl.**
G06F 15/173 (2006.01)

(52) **U.S. Cl.** **709/220**

(58) **Field of Classification Search** **709/223,**
709/224, 220

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,811,249 A * 3/1989 Marsh 702/187
5,202,921 A * 4/1993 Herzberg et al. 713/162

5,331,574 A * 7/1994 Temoshenko et al. 702/186
5,412,723 A * 5/1995 Canetti et al. 713/155
5,446,680 A * 8/1995 Sekiya et al. 709/200
5,446,690 A * 8/1995 Tanaka et al. 365/185.25

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0905615 A2 3/1999

(Continued)

OTHER PUBLICATIONS

“About Fiberlink”, Published by Fiberlink Communications Corp., (2001), 1 pg.

(Continued)


Primary Examiner—David Y Eng

(74) *Attorney, Agent, or Firm*—Schwegman, Lundberg & Woessner, P.A.

(57) **ABSTRACT**

A method and system are provided for monitoring service quality of at least one network connection point of a remote network connection service. The method includes establishing a network connection between a client device and the remote network connection service via the network connection point. The network connection point may be one of a plurality of remotely located network connection points. The method includes monitoring access performance of the network connection point to generate access performance data, and processing the access performance data to monitor the service quality of the network connection point.

61 Claims, 6 Drawing Sheets



US 7,519,695 B2

U.S. PATENT DOCUMENTS							
5,497,421	A *	3/1996	Kaufman et al. 713/156	6,640,242	B1 *	10/2003	O'Neal et al. 709/206
5,564,017	A *	10/1996	Corn et al. 709/227	6,687,560	B2 *	2/2004	Kiser et al. 700/108
5,606,663	A	2/1997	Kadooka	6,721,777	B1	4/2004	Sharma
5,611,048	A	3/1997	Jacobs et al.	6,748,439	B1	6/2004	Monachello et al.
5,638,514	A	6/1997	Yoshida et al.	6,753,887	B2	6/2004	Carolan et al.
5,726,883	A	3/1998	Levine et al.	6,779,004	B1	8/2004	Zintel
5,768,521	A	6/1998	Dedrick	6,792,082	B1	9/2004	Levine
5,781,189	A	7/1998	Holleran et al.	6,792,464	B2	9/2004	Hendrick
5,793,952	A	8/1998	Limsico	6,907,032	B2	6/2005	Eastman
5,802,592	A	9/1998	Chess et al.	6,985,901	B1	1/2006	Sachse et al.
5,815,665	A	9/1998	Teper et al.	6,985,945	B2	1/2006	Farhat et al.
5,832,228	A	11/1998	Holden et al.	6,996,093	B2	2/2006	Dalton, Jr. et al.
5,845,267	A	12/1998	Ronen	6,996,628	B2	2/2006	Keane et al.
5,852,812	A	12/1998	Reeder	6,999,420	B1	2/2006	Chiu et al.
5,892,900	A	4/1999	Ginter et al.	7,124,101	B1	10/2006	Mikurak
5,991,292	A	11/1999	Focsaneanu et al.	7,191,239	B2	3/2007	Rozenfeld et al.
6,023,470	A	2/2000	Lee et al.	7,191,244	B2	3/2007	Jennings et al.
6,023,502	A	2/2000	Bouanaka et al.	7,213,077	B2	5/2007	Border
6,026,375	A	2/2000	Hall et al.	7,222,193	B2	5/2007	Stringer
6,028,917	A	2/2000	Creamer et al.	7,240,112	B2	7/2007	Farhat et al.
6,029,143	A	2/2000	Mosher et al.	2001/0056485	A1	12/2001	Barrett et al.
6,032,132	A	2/2000	Nelson	2002/0029275	A1	3/2002	Selgas et al.
6,032,137	A	2/2000	Ballard	2002/0055909	A1	5/2002	Fung et al.
6,035,281	A	3/2000	Crosskey et al.	2002/0069284	A1	6/2002	Slemmer et al.
6,047,051	A	4/2000	Ginzboorg et al.	2002/0114346	A1	8/2002	Lampe
6,049,671	A	4/2000	Slivka et al.	2002/0124078	A1	9/2002	Conrad
6,055,503	A	4/2000	Horstmann	2002/0143494	A1	10/2002	Conrad
6,078,906	A	6/2000	Huberman	2002/0169792	A1	11/2002	Perinet et al.
6,081,508	A	6/2000	West et al.	2003/0120465	A1	6/2003	Mets et al.
6,094,721	A	7/2000	Eldridge et al.	2003/0120627	A1	6/2003	Emery et al.
6,112,239	A	8/2000	Kenner et al.	2003/0120661	A1	6/2003	Mets et al.
6,125,354	A	9/2000	MacFarlane et al.	2004/0128379	A1	7/2004	Mizell et al.
6,128,601	A	10/2000	Van Horne et al.	2005/0021781	A1	1/2005	Sunder et al.
6,157,618	A	12/2000	Boss et al.	2005/0055371	A1	3/2005	Sunder et al.
6,167,126	A	12/2000	Janning	2005/0204036	A1	9/2005	Farhat et al.
6,175,869	B1	1/2001	Ahuja et al.	2006/0020525	A1	1/2006	Borelli et al.
6,178,460	B1 *	1/2001	Maddalozzo, Jr. et al. .. 709/239	FOREIGN PATENT DOCUMENTS			
6,188,994	B1	2/2001	Egendorf	GB	2378021	1/2003	
6,189,096	B1	2/2001	Haverty	JP	02033648	2/1990	
6,198,824	B1	3/2001	Shambroom	JP	02039260	2/1990	
6,208,977	B1	3/2001	Hernandez et al.	JP	02112053	4/1990	
6,212,280	B1	4/2001	Howard, Jr. et al.	JP	03189852	8/1991	
6,212,561	B1	4/2001	Sitaraman et al.	JP	04054661	2/1992	
6,216,117	B1	4/2001	Hall	JP	04067252	3/1992	
6,219,790	B1	4/2001	Lloyd	JP	04084254	3/1992	
6,240,091	B1	5/2001	Ginzboorg et al.	JP	04142655	5/1992	
6,243,367	B1 *	6/2001	Hussain 370/329	JP	05189288	7/1993	
6,247,050	B1 *	6/2001	Tso et al. 709/224	JP	05199327	8/1993	
6,260,142	B1	7/2001	Thakkar et al.	JP	07182064	7/1995	
6,269,401	B1	7/2001	Fletcher et al.	JP	09265455	10/1997	
6,278,460	B1 *	8/2001	Myers et al. 345/424	JP	09330298	12/1997	
6,317,792	B1	11/2001	Mundy et al.	JP	10289209	10/1998	
6,324,579	B1	11/2001	Bleuse et al.	JP	11203247	7/1999	
6,327,707	B1	12/2001	McKeeth et al.	JP	00112892	4/2000	
6,330,443	B1	12/2001	Kirby	JP	00165839	6/2000	
6,339,790	B1	1/2002	Inoue	JP	00194657	7/2000	
6,405,028	B1	6/2002	DePaola et al.	JP	00259276	9/2000	
6,426,955	B1	7/2002	Dalton, Jr. et al.	JP	01053910	2/2001	
6,463,534	B1	10/2002	Geiger et al.	WO	WO-9615616	A3	5/1996
6,505,246	B1 *	1/2003	Land et al. 709/224	WO	WO-9703410	A1	1/1997
6,510,463	B1	1/2003	Farhat et al.	WO	WO-97/15885		5/1997
6,513,060	B1	1/2003	Nixon et al.	WO	WO-9730543	A1	8/1997
6,522,884	B2	2/2003	Tennison et al.	WO	WO-9903243	A1	1/1999
6,538,996	B1	3/2003	West et al.	WO	WO-9956254	A1	11/1999
6,546,492	B1	4/2003	Walker et al.	WO	WO-9966692		12/1999
6,549,770	B1	4/2003	Marran	WO	WO-9966692	A1	12/1999
6,564,214	B1	5/2003	Bhide	WO	WO-0002149	A1	1/2000
6,571,290	B2	5/2003	Selgas et al.	WO	WO-0004434	A2	1/2000
6,577,858	B1	6/2003	Gell	WO	WO-0019297		4/2000
6,578,075	B1	6/2003	Nieminen et al.	WO	WO-0062514		10/2000
6,628,775	B1	9/2003	Van Tol	WO	WO-0135256	A2	5/2001

WO	WO-03 056403	7/2003
WO	WO-03/056403 A1	7/2003
WO	WO-2004072825 A3	8/2004
WO	WO-2004072831 A3	8/2004
WO	WO-2004/079551	9/2004
WO	WO-2004109534 A1	12/2004
WO	WO-2004109535 A1	12/2004

OTHER PUBLICATIONS

“Broadmedia Introduces G-Phone DLX Phone (Product Announcement)”, *Tele-Service News*, 12(6), (Jun. 1, 2000), 2 pgs.

“Companies Mix and Match VPN, Dial Access Support”, *InternetWeek*, No. 749, (Jan. 25, 1999), 3 pgs.

“Dial Up With Bay’s New Remote Access Concentrator”, *IT Times*, (Oct. 21, 1997), p. 6.

“EarthLink Dials Up ClientLogic for Multi-Channel Technical Support”, *Business Wire*, (Jul. 24, 2001), 2 pgs.

“International Search Report for PCT Application No. PCT/US01/05752”, (May 9, 2001).

“International Search Report for PCT Application No. PCT/US01/05724”, (Jun. 8, 2001).

“IP Axxess Adds Fixed-Wireless Service Provider to Participants in Its Expanding Evaluation Program”, *Business Wire*, (Apr. 4, 2001), 2 pgs.

“Lucent Technologies Launches Next-Generation Voice Dialing Service for Wireless Networks. (Brief Article)”, *Cambridge Telcom Report*, (Mar. 27, 2000), 2 pgs.

“Netopia Introduces First ADSL Routers to Offer Integrated Backup Module for “Fast Track” Development and Fully Redundant Internet Connectivity”, *Business Wire*, (May 24, 2000), 5 pgs.

“Trinagy’s New Insight for Dial Access Solution Suite Delivers Proactive Management of Dial-Up Service Offerings”, *Business Wire*, (Apr. 24, 2001), 2 pgs.

“Ubrandit.com Adds Gigitel and Zodiac Cafe to Virtual ISP Client List”, *Business Wire*, (Oct. 16, 2000), 2 pgs.

Aboba, B., et al., “The Network Access Identifier”, *RFC2486*, (Jan. 1999), 6 pgs.

Barron, G., “International Search Report for PCT Application No. PCT/US02/25996”, (Dec. 12, 2002).

Barron, G., “Written Opinion for PCT Application No. PCT/US02/12343”, Found in 2062.010WO1, (Mar. 6, 2003).

Blanche III, F., “Spicing Up the Web”, *Greater Baton Rouge Business Report*, 13(23), (Jul. 18, 2000), 94.

Blass, S., “Dr. Internet”, *Network World*, (Mar. 11, 2002), 55.

Brockmann, P., “Rapport Dialup Switch Redefines Internet Service Opportunities”, *Telesis*, (Dec. 1996), 12-13.

Bruno, L., “Software & Security. (Netegrity’s Siteminder Enterprise Security Software) (Product Information)”, *Data Communications*, (Jan. 1997), p. (d).

Callahan, P., “International Search Report for PCT Application No. PCT/US02/12343”.

Clyde, R., “Try a Step-by-Step Approach. (Data Security Measures)”, *Computing Canada*, (Jan. 4, 1995), p. 42(1).

Derfler, Jr., F. J., et al., “How Network Works”, *Que Corporation, Millenium Edition*, (2000), 8 pgs.

Edwards, Morris, “It’s a VPN thing—Technology Information”, *Communications News*, (Aug. 1, 1999), 4 pgs.

Greene, T., “Upstart VPN Services Staking Out New Group”, *Network World*, (Apr. 16, 2001), 30.

Guy, S., “Untangling Phone Frustration, Bellcore Solution Offers a Simpler Way to do Business”, *Telephony*, (Jun. 2, 1997).

Harrell, R., “International Search Report for PCT Application No. PCT/US01/41540”.

Helmig, J., “Dialup Networking with TCP/IP”, <http://www.windowsnetworking.com>, (Observed Apr. 8, 2005), 1-19.

Johnson, J. T., “Linking Corporate Users to the Internet”, *Data Communications*, (Jan. 1993), 56-58.

Kang, Paul.

Landry, S., “Roaming User Profiles”, http://www.engr.sc.edu/its/handouts/nt_basics/profiles.htm, (Feb. 18, 1999), 3 pgs.

Likier, M., “Using Dial-Up Technology for Internetworking Applications”, *Telecommunications*, (May 1992), 52.

Malinowski, W., “International Search Report for PCT Application PCT/US01/05752”.

Millin, V., “International Search Report for PCT Application No. PCT/US01/05724”.

Newton, Harry, “Newton’s Telecom Dictionary, 18th Edition”, *New York: CMP Books*, (Feb. 2002), p. 65.

Peeso, T., “International Search Report for PCT Application No. PCT/US02/12475”.

Salamone, S., “Simplified Roaming, From POP to POP”, *Internet Week*, (Feb. 15, 1999), 11.

Sanders, B., “Despite Nasty Shake-Out Local ISPs are Thriving”, *New Hampshire Business Review*, 23(4), (Feb. 23, 2001).

Scarcia, C., “Getting On The Net With The Right ISP”, *New Jersey Business*, 45(9), (Sep. 1, 2000), 40.

Schneier, B., *Applied cryptography: protocols, algorithms, and source code in C*, New York: Wiley, 2nd ed., (1996), 37-38.

Schneier, Bruce, *Applied Cryptography: protocols, algorithms, and source code in C*, New York: Wiley, 2nd Edition, (1996), 31-34, 52-56, 60, 75-79, 256, 480-481.

Schneier, B., “Applied Cryptography”, *Protocols, Algorithms, and Source Code in C*, Second Edition, John Wiley and Sons, (1996), 185-187.

Semich, J. W., “56K Server Supports U.S. Robotics and Lucent-Modems Built Into Model 800 From Bay Networks”, *WebWeek*, 3(25), (Aug. 18, 1997), 25.

Shen, J., et al., “8. Research and Implementation of Proxy Server”, *Journal of Nanjing University: Aeronaut. Astronaut. (China)*, 32(6), (Dec. 2000), 620-624.

Silberg, L., “Dialing the Web AT&T’s Internet Cellphone Debuts at Mass; Launches PocketNet Wireless Data Service at Retail in an Attempt to Bring Cellphone With Internet Access to the Masses”, *HFN—The Weekly Newspaper for the Home Furnishing Network*, (Oct. 13, 1997), 93.

Smithers, M., “International Search Report for PCT Application No. PCT/US02/12470”.

Trammell, J., “International Search Report for PCT Application No. PCT/US01/05723”.

Wang, Wei-Lung, et al., “A protocol for billing mobile network access devices operating in foreign networks”, *Seventh IEEE International Workshops on Enabling Technologies: Infrastructure for Collaborative Enterprises*, 1998. (*Wet Ice '98*) Proceedings, (Jun. 17-19, 1998), 262-268.

West, Wray, “Don’t be nervous—remote access VPN’s—Industry Trend or Event”, *Communication News*, 37(5), (May 2000), 28, 30, 32.


About Fiberlink, Published by Fiberlink Communications Corp., (2001), 1 pg.

Helmig, J., “Dialup Networking with TCP/IP”, <http://www.windowsnetworking.com>, (Observed Aug. 8, 2005), pp. 1-19.

Landry, S., “Roaming User Profiles”, http://www.engr.sc.edu/its/handouts/nt_basics/profiles.htm, (Feb. 18, 1999), 3 pgs.

Schneier, B., *Applied cryptography: protocols, algorithms, and source code in C*, New York: Wiley, 2nd ed., (1996), pp. 37-38.

* cited by examiner






FIG. 2




FIG. 3A




FIG. 3B




FIG. 4




FIG. 5




FIG. 6

SERVICE QUALITY MONITORING PROCESS

RELATED APPLICATIONS

This application is a Continuation of U.S. application Ser. No. 11/126,008 filed May 9, 2005 now U.S. Pat. No. 7,240,112 which is a Continuation of U.S. application Ser. No. 10/318,968 filed Dec. 13, 2002 now U.S. Pat. No. 6,985,945, which is a Continuation of U.S. application Ser. No. 09/732,800 filed on Dec. 7, 2000, issued as U.S. Pat. No. 6,510,463, which claims the benefit of U.S. Provisional Application No. 60/207,670, filed May 26, 2000. These applications are incorporated herein by reference.

FIELD OF THE INVENTION

The present invention relates to the field of remote network connections and more particularly to monitoring the quality of network connection points.

BACKGROUND OF THE INVENTION

With the technological developments of the last decade and growing popularity of online commerce, e-mail, online chatting and the Internet in general, the demand to have constant access to these innovative technological ways of communication is rapidly increasing. Some users cannot imagine their lives without the Internet and email; some cannot imagine their lives without being able to buy groceries online. Constant desire to be connected to the informational highway increases demand for reliable, fast, convenient network connection.

Anyone using current technology has dealt with networks at some point. Being connected to a local network where users share files and data on one server is a common scheme in workplaces. However, the advantages of networks are so great that the many of people desire the ability to be connected to networks from multiple physical locations. Remote network connections provide users with opportunities 'to be connected' from many locations throughout the world with the right set of tools, e.g., computer, modem, phone line, etc. However, remote networking uses external wide area network communications links to other physical locations across town or country, and it is not always a simple task to design such a remote network access system with the acceptable performance. Busy phone line signals, unconnected modems, password problems, interrupted network connection sessions reduce the level of performance of the remote network connection and cause frustration in users. In short, the quality of network connections may vary due to a number of factors.

Thus, it would be desirable to provide a system that would reduce the above stated problems and provide high quality remote network connections.

SUMMARY OF THE INVENTION

The present invention discloses a method and system for monitoring service quality of at least one network connection point of a roaming service access system. The method includes establishing a network connection between a client device and the roaming service access system via the network connection point. The network connection point may be one of a plurality of remotely located network connection points via any one of which access to the service access system is obtainable. The method includes monitoring access performance of the network connection point to generate access

performance data, and processing the access performance data thereby to monitor the service quality of the network connection point.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is illustrated by way of example and not limitation in the figures of the accompanying drawings, in which like references indicate similar elements and in which:

FIG. 1 is a diagram of a system architecture according to one embodiment of the present invention;

FIG. 2 is an entity relationship diagram between a client machine and a plurality of point-of-presence gateways (POPs) according to one embodiment of the present invention;

FIGS. 3A and B show a flow diagram illustrating server side processes and client side processes utilized in updating a POP priority list according to one embodiment of the present invention;

FIG. 4 is a data flow diagram according to one embodiment of the present invention;

FIG. 5 a diagram of a traditional client-server system upon which one embodiment of the present invention may be implemented; and

FIG. 6 is a diagram illustrating a process of connection to the Internet utilizing an Internet Service Provider (ISP) according to one embodiment of the present invention. The connection could be dial-up, IDSN, DSL, wireless, etc.

DETAILED DESCRIPTION

Although the present invention is described below by way of various embodiments that include specific structures and methods, embodiments that include alternative structures and methods may be employed without departing from the principles of the invention described herein.

In general, embodiments described below feature a network-based application that collects remote network connection performance data and modifies a priority list of network connection points based on the collected data. A preferred embodiment of the present invention features a network-based application for monitoring quality of remote network connections.

Network-related Technology

Before describing embodiments of the present invention in detail, it may be helpful to discuss some of the concepts on which the present invention is based. A component of one embodiment of the present invention is a computer server. Servers are computer programs that provide some service to other programs, called clients. A client 505 and server 510 of FIG. 5 communicate by means of message passing often over a network 500, and use some protocol, (i.e., a set of formal rules describing how to transmit data), to encode the client's requests and/or responses and the server's responses and/or requests. The server may run continually waiting for client's requests and/or responses to arrive or some higher level continually running server that controls a number of specific servers may invoke it. Client-server communication is analogous to a customer (client) sending an order (request) on an order form to a supplier (server) dispatching the goods and an invoice (response). The order form and invoice are part of the protocol used to communicate in this case.

Another component of one embodiment the present invention is an Internet Service Provider (ISP). An ISP is a service that provides access to the Internet. For a monthly fee, a service provider gives a customer a software package, user-

name, password and Internet access phone number. Equipped with a modem (e.g., a dial-up, DSL, ISDN or wireless), a customer can then log onto the Internet and browse the World Wide Web (WWW) and USENET, send and receive e-mail, and access a particular network. In addition to serving individuals, ISPs also serve large companies, providing a direct connection from the company's networks to the Internet. ISPs themselves are connected to one another through Network Access Points (NAPs). NAP is a public network exchange facility where ISPs can connect with one another in peering arrangements. The NAPs are a key component of the Internet backbone because the connections within them determine how traffic is routed. They are also the points of most Internet congestion. An exemplary diagram of customer to ISP relation is shown in FIG. 6.

ISPs generally provide a plurality of Point of Presence gateways (POP) in order for a customer to gain an Internet access by making a local call. A POP (point-of-presence) is an access point to the Internet that is associated with a phone number. A connection established via such a POP causes a unique IP address to be assigned to a machine that accesses the Internet utilizing the established connection. The number of POPs that an ISP has and the number of subscribers are usually used as a measure of its size or growth rate.

Yet another component one embodiment of the present invention is a servlet. Servlets are Java applications, which run on a Web server or application server and provide server-side processing, typically to access a database. It is a Java-based alternative to Common Gateway Interface (CGI) scripts, interface programs, usually written in C or PERL, which enables an Internet server to run external programs to perform a specific function. The most important difference between servlets and CGI scripts is that a Java servlet is persistent. This means that once it is started, it stays in memory and can fulfill multiple requests. In contrast, a CGI script disappears once it has fulfilled a request.

Architecture

With these concepts in mind, an embodiment of a system architecture of the present invention can be explored. A remote network connection can be established from a client machine **101** of FIG. 1 that runs a dialer **102** to establish a network connection via a POP **103** and network **104** and to collect network connection performance data. The Dialer **102** includes (1) a Service Quality Management (SQM) agent **90** for collecting network connection performance data and for maintaining files storing the collected information, (2) phonebook **92**, which includes a copy of a POP priority list **112** that may be stored at a server machine **105** and (3) a Graphical User Interface **94** that allows a user to identify his/her current location and select an access point in order for the Dialer **102** to apply local dialing rules, enter user name and password, and connect to the Internet and corporate Virtual Private Network (VPN).

In one embodiment of the present invention the server machine **105** includes a Web Server **118** and a Database Server **119**. The Web Server **118** includes such components of the present invention as Load Servlet **107** and Report Servlet **108** database applications. The Database Server **119** includes an SQM Process Application **120** consisting of a Main SQM Thread **109**, Process Thread **110** and Purge Thread **111**. These components are responsible for storing and normalizing data for service quality analysis. It will be appreciated that these components may run on a single server.

In an embodiment of the present invention, database tables for storing collected and analyzed data, (e.g., Raw_SQM Table **115**, SQM Table **114**, POP priority list **112**) are also

stored at the server machine **105**. However, it will be appreciated that databases may be stored at other machines and database data may be uploaded to the server machine **105** when necessary.

Methodology

With these concepts in mind, an exemplary embodiment of the present invention can be further explored. In one embodiment of the present invention a user invokes a Dialer **102** at the client machine **101** of FIG. 2. The Dialer **102** attempts to establish a connection with one of the POPs in a priority order established in the POP priority list **203**. For example, if POP1 is not available then the Dialer **102** selects the next POP (POP2) from the list and attempts to establish a network connection with POP2 and so on.

The next embodiment of the present invention is described with the reference to a simplified flow diagram shown in FIGS. 3A and 3B. At operation **302**, the SQM agent **90** collects network connection performance data of a number of POPs with which the Dialer **102** attempts to establish a connection and stores the data in the files on the client machine **101**. In an embodiment of the present invention, the network connection performance data includes a number of parameters related to a user, software and hardware configurations of a client machine **101**, a user location, a network access location (e.g., a location dialed by modem), the timing of various operations in a connection process, POP related information, client and server IP addresses, baud rates, and error codes reflecting connection errors.

An exemplary listing of parameters that may be collected as part of the network connection performance data is provided below in Table 1:

TABLE 1

35	user identity
	user login string
	authenticating customer identifier
	connection type
	dial start time
40	dial end time
	time taken to connect
	VPN start time
	VPN stop time
	VPN time taken
	time taken for modem negotiations
	baud rate
45	operating system version of a dialing platform
	RAS version
	RAS device type
	RAS device name
	software compression
	PPP LCP extensions
50	tool used to connect
	dialer type
	dialer version
	dialer profile identifier
	source country code, area code, location string the user is dialing from
	destination country code, area code
55	destination phone dial string
	POP identifier
	pop type
	pop City location
	pop state identifier
	pop country code
	pop phone
60	script used when dialing
	remote server IP address
	client IP address
	download start (collected if test file downloaded)
	download stop
	download speed
65	error code of the user received on connection

5

The error codes returned to the user upon a connection attempt may broadly be divided into three categories namely (1) successful dial in connection, (2) user errors and (3) network problems. The user errors typically occur due to a user name and password problems, missing or disconnected modems, incorrect dialing codes, or incorrect or hand-edited phone numbers. Examples of the user errors include:

1. Access denied due to invalid user name or password;
2. The user cancelled operation;
3. Device/configurations error (e.g., port not ready, port already opened, modem not connected, no dial tone detected); and
4. Person answered instead of modem (e.g., incorrect phone number dialed).

Examples of network errors include:

1. Line busy;
2. No answer;
3. PPP time out;
4. Connection dropped;
5. Remote access server not responding; and
6. Port disconnected by remote computer.

When a successful network connection with one of the POPs is established, the SQM agent **90** transmits the collected data to the server machine **105**. In one embodiment of the present invention, the Dialer **102** selects one of the available servers for data transmission based on a data load, thus performing a load balancing function.

In one embodiment of the present invention, the SQM agent **90** collects network connection performance data relating to every POP via which it tries to establish a network connection. Upon establishment of a successful network connection with one of the POPs, the SQM agent **90** composites a message comprising network connection performance data along with software and hardware configuration data and the POP identification numbers to which the network connection performance data relates and transmits the message to the server **105**.

The Web Server **118**, upon receiving the collected data at the server machine **105**, at operation **304** invokes the Load Servlet **107** that stores received data in the RAW SQM table **116**. After the network connection performance data is successfully stored in the RAW SQM table, at operation **307** the Load Servlet **107** sends a message to the Dialer **102** at the client machine **101** with the code number symbolizing successful storage of data on the server machine **105**. At operation **308**, the Dialer **102** deletes data in the files stored at the client machine **101** upon receiving the message with the code number. At operation **309**, the Database Server **119** invokes the SQM Process Application **120**, which invokes the Main SQM Thread **109**. The Main SQM Thread **109** searches RAW SQM table **116** for records, which have not been processed, and at operation **310** appoints the Process Thread **110** to normalize the data from the RAW SQM table. In one embodiment of the present invention the Process Thread **110**, at operation **311**, performs data normalization by parsing the data and adding a customer identification number and POP identification number to the data. The Process Thread **110** then stores normalized data in the SQM table **114** at operation **312**. If the data has errors or customer identification number cannot be identified, the data is stored in an SQM Exception table **113** at operation **313**.

At operation **311**, the process thread may further optionally aggregate and process the normalized data, so as to facilitate convenient analysis thereof. For example, totals may be generated for particular types of errors for each of multiple POPs, averages may be generated for performance measures (e.g., baud rate), and access times may be calculated. Further, totals

6

and averages may also be calculated based on other criteria, such as time, date and geographical criteria. The data in the SQM Exception table **113** is reviewed manually and re-processed or discarded. The Process Thread **110** marks the normalized records in the RAW SQM table **116**. The Purge Thread **111** runs periodically and searches the RAW SQM table **116** for the marked records and deletes them at operation **314**.

At operation **315** the data stored in the SQM table **114**, reflecting POP performance information collected by multiple clients, is ready for human access. In one embodiment a data summarization process is performed on the data in the SQM table **114** to support data analysis and reporting. Multiple tables that contain summarized data are generated as a result of the summarization process that may run on a separate server. The variety of queries and reports can be generated at this point. In one embodiment of the present invention, the types of the reports that are available are: list of single POPs by phone number with the performance information, list of POP groups with the performance information on a group of POPs, end user assistance report including a variety of data on the user, e.g. quantity of dial-ins a day, number of password problems, etc., customer Service Level Agreement (SLA) performance information by month. It will be appreciated that these reports may be generated manually by human operators and automatically by components running on the server machine **105**.

At operation **316** a team of experts monitors the collected network performance data and analyzes it periodically. The team's purpose is to identify the network connection problems experienced by the user and proactively respond before the remote network connection service is noticeably affected. Any suspected problems may be tested using a dialer application. A group of phone numbers, representing POPs with problematic performance, may be loaded into the dialer application for test purposes and the dialer application may dial each one in order to check POPs performance. Based on the test results and on the collected network performance data any POPs that are not performing to the quality standards may be moved to the end of the POP Priority List **112**. The POP Priority List **112** may be sorted by using a number of different criteria such as quality rating, speed, price, provider, etc. These sorting criteria may be applied at an individual city level as well as on the entire phonebook level. In one embodiment manually selected sort order within a city may also be applied. The above process facilitates the identification of the best performing POPs for any given area and the assignment to such best performing POPs of a high priority number. At the same time, low performing POPs may be identified, and assigned a lower priority number. In an embodiment of the present invention if the quality of service of a POP is so poor that it is not worth maintaining in the POP Priority List **112**, the expert team deletes the POP from the list temporarily until the POP's performance is improved. It will be appreciated that the analysis and POP Priority List **112** can be updated automatically without human help by developing an application that updates the POP Priority List **112** based on an advanced-specified criteria. For example, the criteria may be an acceptable average number of failed attempts to establish a network connection a day, or an acceptable number of interrupted network connection sessions, etc.

At operation **317** the phonebook **92** on the client machine **101** is automatically updated after the user establishes a successful Internet connection. The updating of the phonebook **92** may be performed by modifying an existing phonebook **92** stored on the client machine **101**, or may be performed by uploading a complete and new phonebook **92**, as generated on

the server machine **105**, to the client machine **101**. For example, upon the generation of a complete and new phonebook **92**, the new phonebook **92** may be “pushed out” from the server machine **105** to multiple client machines **101**. In one embodiment of the present invention, the user may choose not to receive an automatic update of the phonebook **92**. In this embodiment the user may access a Web site maintained at the server machine **105** where a copy of the latest phonebook may be viewed and downloaded. An exemplary data flow diagram of the above-described process is illustrated in FIG. **4**.

It will be appreciated that the operations **315-317** may be automated, with certain criteria extracted from the collected connection performance data being used automatically to prioritize POPs. Such criteria may include any of the information items identified above, and the automated process may be customizable so as to allow certain criteria to be user-selected to be prominent in the prioritization of POPs. The prioritization of POPs may be even performed according to any number of well-known ranking or prioritization algorithms.

It will be appreciated that the above described database applications do not need to run on the server machine **105**. The above-described process may run on the client machine **101** with an automatic POPs performance analysis.

Moreover, the above described databases and tables do not need to be stored at the server machine **105**. They may be stored at other machines that are accessible by the server machine **105** and uploaded to the server machine **105** when necessary.

In the foregoing specification the present invention has been described with reference to specific exemplary embodiments thereof. It will, however, be evident that various modifications and changes may be made to the specific exemplary embodiments without departing from the broader spirit and scope of the invention as set forth in the appended claims. Accordingly, the specification and drawings are to be regarded in an illustrative rather than a restrictive sense.

What is claimed is:

- 1.** A method comprising:
 - selecting a network connection point from a plurality of network connection points;
 - initiating a network connection between a client device and a remote network connection service via the selected network connection point;
 - monitoring access performance of the selected network connection point to generate access performance data;
 - communicating the access performance data via any one of the plurality of network connection points to a monitoring server for processing; and
 - modifying connection data on the client device in response to the processing of the network performance data, the connection data being used by a connection application to select a network connection point.
- 2.** The method of claim **1**, which includes generating access performance data relating to a plurality of selected network connection points with which the client device initiates a network connection even when no network connection is established.
- 3.** The method of claim **1**, wherein the plurality of network connection points are point-of-presence (POP) gateways and the access performance data includes a POP identifier.
- 4.** The method of claim **1**, which includes communicating the access performance data of a first selected network connection point to the monitoring server via a second selected network connection point of the plurality of network connection points.

5. The method of claim **1**, wherein the connection data includes a plurality of telephone numbers in a connection point list, each telephone number being associated with a network connection point defined by a point-of-presence gateway (POP) providing Internet access, the method including updating the connection point list based on the monitored service quality of the selected network connection point.

6. The method of claim **1**, which includes:

- modifying a priority list of network connection points at a monitoring server wherein a priority level is assigned based on a performance of the network connection point; and

- downloading the priority list to at least one client device for subsequent use in selecting a connection point.

7. The method of claim **6**, which includes storing the priority list of network connection points on a Web site for downloading by any one of a plurality of client devices.

8. The method of claim **1**, which includes selecting a network connection point with a highest priority to establish the network connection.

9. The method of claim **8**, which includes modifying a priority of the network connection point based on the monitoring of the network connection point.

10. The method of claim **8**, which includes selecting a connection via a second network connection point of a priority list of network connection points when the network connection point first selected is unavailable.

11. The method of claim **1**, which includes monitoring at least one client device based connection error resulting from the client device to identify at least one apparent network connection error that is a client device based connection error.

12. The method of claim **11**, wherein the client based connection error includes one of: an access denial due to invalid password entry, a user cancelled access operation, a client device hardware error, and a dialed number error.

13. The method of claim **1**, wherein the access performance data includes at least one network connection error including one of: a line busy error, a no answer error, a PPP time out error, a connection dropped error, a roaming server non-response error, and a port disconnected by the client error.

14. The method of claim **1**, wherein the access performance data includes one of: connection type data, a dial start time, a dial end time, time taken to connect to the network connection point, time taken for network access negotiations, a baud rate of the network connection, a source country code, a location code, a destination country code, a download start time, a download end time, a connection dropped error, a no answer error, and no response from a network connection point.

15. The method of claim **1**, which includes aggregating the access performance data.

16. The method of claim **1**, which includes:

- monitoring access performance at each network connection point of a priority list of network connection points provided for use by a plurality of client devices; and

- modifying network connection point data on the plurality of client devices in response to processing the access performance data, the network connection point data being provided in the priority list of network connection points.

17. The method of claim **16**, wherein the network connection point data includes a list of telephone numbers for use by a connect dialer.

18. The method of claim **1**, further including storing the access performance data at the client device for modifying a priority of the selected network connection point based on the access performance data.

19. A method comprising:
 collecting access performance data of a network connection point from a client device, the access performance data being generated by the client device when a connection application on the client device establishes a network connection between the client device and the network connection point, and the network connection point being selected from a plurality of remotely located network connection points;
 processing the access performance data to monitor a service quality of the selected network connection point; and
 storing the access performance data at the client device for modifying a priority of the selected network connection point based on the access performance data.

20. The method of claim **19**, wherein the access performance data indicates an error at the client device, and the error at the client device includes any one of: a user error, a software error, and a hardware error.

21. The method of claim **19**, wherein the access performance data indicates a network error.

22. The method of claim **21**, wherein the network error comprises a network media error.

23. The method of claim **19**, including establishing a further connection via a second network connection point selected from a priority list of network connection points when connection via a first network connection point fails.

24. The method of claim **23**, wherein the priority list is modified based on the monitored service quality of the selected network connection point.

25. The method of claim **19**, further including generating an updated priority for the selected network connection point for communication to at least one client device, the updated priority being based on the service quality of the selected network connection point.

26. A method comprising:
 establishing a network connection between a client device and a network connection point, the network connection point being selected from a plurality of remotely located network connection points;
 at the client device, monitoring access performance of the selected network connection point to generate access performance data;
 communicating the access performance data from the client device to a monitoring server to modify a priority of the selected network connection point based on the access performance data; and
 generating an updated priority for the selected network connection point for communication to at least one client device, the updated priority being based on the service quality of the selected network connection point.

27. The method of claim **26**, in which the access performance data of the selected connection point is communicated via any one of a plurality of connection points to the monitoring server for processing.

28. The method of claim **26**, which includes generating access performance data relating a plurality of network connection points which the client device has selected to initiate a network connection even if no network connection is established.

29. The method of claim **26**, wherein the network connection points are point-of-presence (POP) gateways and the access performance data includes a POP identifier.

30. The method of claim **26**, which includes modifying connection data on the client device in response to the processing of the network performance data, the connection data being used by a connection application to select a connection with the selected network connection point.

31. The method of claim **30**, wherein the connection data includes a plurality of telephone numbers in a connection point list, each telephone number being associated with a network connection point defined by a point-of-presence gateway (POP) providing Internet access, the method including updating the connection point list based on the monitored service quality of the selected network connection point.

32. The method of claim **26**, which includes downloading a priority list of network connection points on a Web site.

33. The method of claim **26**, in which the client device selects a connection point with a highest priority to establish the network connection.

34. The method of claim **26**, in which the client device modifies the priority of the selected network connection point based on the monitored service quality of the selected network connection point.

35. The method of claim **26**, which includes selecting a second network connection point from a priority list of network connection points when the network connection point selected first is unavailable.

36. The method of claim **26**, which includes monitoring at least one client based connection error resulting from the client device to identify at least one apparent network connection error that is a client based connection error.

37. The method of claim **36**, wherein the client based connection error includes one of an access denial due to invalid password entry, a user cancelled access operation, a client device hardware error, and a dialed number error.

38. The method of claim **26**, wherein the access performance data includes network connection error including one of a line busy error, a no answer error, a PPP time out error, a connection dropped error, a remote server non-response error, and a port disconnected by the client error.

39. The method of claim **26**, wherein the access performance data includes one of a connection type data, a dial start time, a dial end time, time taken to connect to the network connection point, time taken for access negotiations, a baud rate of the network connection, a source country code, a location code, a destination country code, a download start time, a download end time, a connection dropped error, a no answer error, and no response from a network connection point.

40. The method of claim **26**, which includes:
 establishing the connection to the network connection point using a connection application; and
 downloading connection point data which is generated based on the monitored service quality of the connection point, the network connection point data being used by the connection application to select a network connection point.

41. The method of claim **40**, wherein the connection point data includes a list of telephone numbers for use by a connection application in the form of a connect dialer.

42. A method comprising:
 receiving access performance data from a client device at a monitoring server via a network, the access performance data relating to a network connection point and being generated by the client device from a network connection between the client device and the network connection point, the network connection point being selected from a plurality of network connection points; and
 processing the access performance data to monitor a service quality of the selected network connection point; and
 generating an updated priority for the selected network connection point for communication to at least one client device, the updated priority being based on the service quality of the selected network connection point.

11

43. The method of claim 42, which includes receiving access performance data relating to the plurality of network connection points via any one of a plurality of network connection points.

44. The method of claim 42, wherein the network connection points are point-of-presence (POP) gateways and the access performance data includes a POP identifier.

45. The method of claim 42, wherein the connection data includes a plurality of telephone numbers in a connection point list, each telephone number being associated with a network connection point defined by a point-of-presence gateway (POP) providing Internet access, the method including updating the connection point list based on the monitored service quality of the selected network connection point.

46. The method of claim 45, which includes storing a priority list of network connection points on a Web site for downloading by any one of the plurality of client devices.

47. The method of claim 42, which includes:

modifying a priority list of network connection points at the monitoring server wherein a priority level is assigned based on a performance of the network connection point; and

providing the priority list for downloading to at least one client device for subsequent use in selecting a network connection point.

48. The method of claim 42, in which the network access data at least one client based connection error resulting from the client device to identify at least one apparent network connection error that is a client based connection error.

49. The method of claim 48, wherein the client based connection error includes one of an access denial due to invalid password entry, a user cancelled access operation, a client device hardware error, and a dialed number error.

50. The method of claim 42, wherein the access performance data includes at least one network connection error including a line busy error, a no answer error, a PPP time out error, a connection dropped error, a remote server non-response error, and a port disconnected by the client error.

51. The method of claim 42, wherein the access performance data includes one of a connection type data, a dial start time, a dial end time, time taken to connect to the network connection point, time taken for access negotiations, a baud rate of the network connection, a source country code, a location code, a destination country code, a download start time, a download end time, a connection dropped error, a no answer error, and no response from a network connection point.

52. The method of claim 42, which includes aggregating the access performance data.

53. The method of claim 42, wherein the connection point data includes a list of telephone numbers for use by a connect dialer.

54. The method of claim 42, including downloading a priority list of network connection points to the client device, the priority list to be utilized by the client device to identify and prioritize the plurality of network connection points.

55. The method of claim 42, further including modifying a priority list of the selected network connection based on the access performance data, the modifying of the priority list of network connection points including assigning a priority level based on a performance of the network connection point.

56. A machine-readable medium including instructions that, when executed on a machine, cause the machine to:

12

select a network connection point from a plurality of remotely located network connection points;
initiate a network connection between a client device and the selected network connection point;

at the client device, monitor access performance of the selected network connection point to generate access performance data; and

store the access performance data at the client device for modifying a priority of the selected network connection point based on the access performance data.

57. A machine-readable medium including instructions that, when executed on a machine, cause the machine to:

receive access performance data from a client device at a monitoring server via a network, the access performance data relating to a network connection point and being generated from a network connection between the client device and the network connection point, the network connection point being selected from a plurality of network connection points;

processing the access performance data to monitor a service quality of the selected network connection point; and

modifying a priority of the selected network connection point based on the service quality of the selected network connection point.

58. A system comprising:

a client device to select and establish a network connection between the client device and the remote network connection service via a network connection point, the selected network connection point being one of a plurality of remotely located network connection points, and the client device to monitor access performance of the network connection point and to store access performance data;

a server to receive the access performance data related to the selected network connection point, the server to modify a priority of the selected network connection point based on the access performance data; and the server to modify a priority of the selected network connection point based on the service quality of the selected network connection point.

59. The system of claim 58, in which the access performance data is generated at the client device and communicated to the server for processing via any one of a plurality of network connection points.

60. The system of claim 58, in which the client device generates access performance data relating a plurality of network connection points with which the client device initiates a network connection even if no network connection is established.

61. A system comprising:

means for selecting a network connection point from a plurality of network connection points;

means for initiating a network connection between a client device and a remote network connection service via the selected network connection point;

means for monitoring access performance of the selected network connection point to generate access performance data;

means for communicating the access performance data via any one of the plurality of network connection points to a monitoring server for processing; and

means for modifying connection data on the client device in response to the processing of the network performance data, the connection data being used by a connection application to select a network connection point.