



US007520842B2

(12) **United States Patent**
Comair et al.

(10) **Patent No.:** **US 7,520,842 B2**
(45) **Date of Patent:** **Apr. 21, 2009**

(54) **BICYCLE TRAINER**

(75) Inventors: **Claude B. Comair**, Bellevue, WA (US);
Joel N. Smith, Edmonds, WA (US)

(73) Assignee: **DigiPen (USA) Corporation**, Redmond,
WA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/263,544**

(22) Filed: **Oct. 31, 2005**

(65) **Prior Publication Data**

US 2007/0099768 A1 May 3, 2007

(51) **Int. Cl.**
A63B 69/16 (2006.01)

(52) **U.S. Cl.** **482/61; 482/54**

(58) **Field of Classification Search** 482/51,
482/57, 61, 54, 65; 601/23, 27-36; 434/247,
434/255

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,026,546 A * 5/1977 Omori 482/61

4,082,265 A *	4/1978	Berkes	482/61
4,415,152 A *	11/1983	Smith	482/61
4,580,983 A *	4/1986	Cassini et al.	482/61
4,750,737 A *	6/1988	Smith	482/61
4,817,939 A *	4/1989	Augspurger et al.	482/61
5,662,559 A *	9/1997	Vasquez	482/61
6,500,098 B1 *	12/2002	Werner	482/57

FOREIGN PATENT DOCUMENTS

CH 657782 A5 * 9/1986

* cited by examiner

Primary Examiner—Loan H Thanh


Assistant Examiner—Tam Nguyen

(74) *Attorney, Agent, or Firm*—Christensen O'Connor
Johnson Kindness PLLC

(57) **ABSTRACT**

A bicycle trainer (100) for supporting a bicycle (200) while a rider rides the bicycle. The bicycle trainer includes a stationary frame (106) adapted to rest upon a support surface (202) and a rotating frame assembly (108). The rotating frame assembly is coupled to the stationary frame, the rotating frame assembly adapted to be coupled to the bicycle and rotate relative to the stationary frame to permit a frame (204) of the bicycle to turn through a predetermined angular displacement (180) relative to the stationary frame.

18 Claims, 3 Drawing Sheets






Fig. 2.




Fig. 3.

1

BICYCLE TRAINER

FIELD OF THE INVENTION

The illustrated embodiments described herein relate generally to bicycle trainers, and more specifically to bicycle trainers that permit a user to ride a bicycle while the bicycle is supported by the bicycle trainer.

BACKGROUND OF THE INVENTION

Currently available bicycle trainers attempt to simulate riding conditions by providing at least some resistance to a rider's exertions and, thereby, achieve a desired level of exercise. Currently, there are of two general types of trainers. The first general type is known as a roller trainer, and the second general type is commonly referred to as a rear wheel or stand trainer.

In a roller trainer, both wheels of a bicycle engage one or more rollers pinned to a frame. During use, the bicycle wheels rotate on the rollers as a rider pedals. In roller trainers, the frame of the bicycle is neither coupled to nor supported by the roller trainer and the rider is required to maintain the bicycle in an upright position.

The rear wheel or stand trainer includes a bracket for rigidly supporting either the rear or front wheel of a bicycle and, thereby, providing some assistance in maintaining the bicycle in an upright position during use. In such a trainer, only the rear wheel of the bicycle rotates as the rider pedals. Such an arrangement eliminates the need for the rider to balance the bicycle on the trainer.

Although effective, both types of trainers are not without their problems. For example, although rear wheel trainers are easy to use, they do not simulate actual riding conditions because the frame of the bicycle is not permitted to move. Specifically, because the frame is rigidly supported by the trainer itself, movement of the bicycle is unnaturally restrained. Additionally, the rigid coupling of the bicycle in the upright manner results in high stresses upon the bicycle frame during use.

Although roller trainers provide a more realistic simulation of riding a bicycle, most users find them very difficult to ride because the frame is not restrained by the trainer itself. Further, such trainers are not designed for simulating turns.

Thus, there exists a need for a bicycle trainer that is reliable, inexpensive to manufacture, and simulates actual riding conditions of a bicycle.

SUMMARY OF THE INVENTION

A bicycle trainer, constructed in accordance with one non-limiting embodiment of the present invention, includes a stationary frame and an attachment assembly coupled to the stationary frame. The attachment assembly is adapted to be coupled to a bicycle for selectively pivoting the bicycle through an angular displacement relative to the stationary frame in response to user input.

A bicycle trainer constructed in accordance with a second non-limiting embodiment of the present invention includes a stationary frame adapted to rest upon a support surface and first and second roller assemblies. The first roller assembly is coupled to the stationary frame for rotatably engaging a first wheel of a bicycle. The second roller assembly is coupled to the stationary frame and is adapted to permit selective pivoting about a first axis while rotatably engaging a second wheel of the bicycle.

2

A bicycle trainer constructed in accordance with yet another non-limiting embodiment of the present invention includes a stationary frame and a coupling frame rotatably coupled to the stationary frame. The coupling frame includes an attachment assembly adapted to couple to a portion of a bicycle for restraining the bicycle to the bicycle trainer and selectively permitting the bicycle to be angularly displaced relative to the stationary frame.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing aspects and many of the attendant advantages of this invention will become better understood by reference to the following detailed description, when taken in conjunction with the accompanying drawings, wherein:

FIG. 1 is an isometric view of a bicycle trainer formed in accordance with one embodiment of the present invention;

FIG. 2 is an isometric view of the bicycle trainer of FIG. 1; and

FIG. 3 is a top planar view of the bicycle trainer of FIG. 2.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

A bicycle trainer **100** constructed in accordance with one embodiment of the present invention may be best understood by referring to FIGS. 1-3. The bicycle trainer **100** is adapted to permit a bicycle **200** and a rider (not shown) to be supported in an upright, stationary position while the rider pedals. Although the bicycle trainer **100** is illustrated as being used with a recumbent bicycle, it should be apparent that the bicycle trainer is not limited to such a bicycle and that other bicycle types are also within the scope of the present invention.

As may be best seen by referring to FIG. 2, the bicycle trainer **100** includes a frame assembly **102** and a roller assembly **104**. The frame assembly **102** includes a stationary frame **106** portion and a rotating frame (or attachment assembly) **108** portion. The stationary frame **106** is adapted to rest upon a support surface **202**, such as a floor or a ground surface, on a plurality of optional legs **114**. The stationary frame **106** includes a base portion **107** having a pair of side frame rails **110** spaced by a pair of end frame rails **112**.

The rotating frame **108** includes a pair of upright stanchions **132**. The stanchions **132** are coupled to one another at their ends and are selectively spaced to receive the rear wheel of a bicycle therebetween. The upper ends of the stanchions **132** are supported by a support frame **116**. The support frame **116** includes a pair of legs **118** extending downwardly and are attached to the stationary frame **106**.

The rotating frame **108** also includes a bicycle coupling assembly **126**. The bicycle coupling assembly **126** is suitably formed with the stanchions **132** and is positioned on each stanchion **132** in an opposed manner to receive a rear hub (FIG. 1) of the bicycle. The bicycle coupling assembly **126** is adapted to couple the bicycle to the rotating frame **108**. The bicycle coupling assembly **126** includes a clamp assembly **127** for clamping upon the ends of a rear axle **206** of the bicycle **200**. The clamp assembly **127** includes a first receiving member **128**, such a cup shaped member, for receiving one end of the rear axle **206**.

The clamp assembly **127** also includes a second receiving member **130** disposed opposite the first receiving member **128**, which may also be a cup shaped member, for receiving the other end of the rear axle **206**. Preferably, at least the second receiving member **130** is adjustable in position relative to the first receiving member **128** to accommodate

bicycles of differing sizes. The adjustable aspect of the second receiving member **130** also permits the application of a clamping force to the rear axle **206** to securely couple the bicycle **200** to the rotating frame **108**. In certain embodiments, both the first and second receiving members **128** and **130** are adjustable relative to each other. In still yet other embodiments, only the first receiving member **128** is adjustable relative to the second receiving member **130**.

The lower ends of the stanchions **132** are attached to a pivot assembly **134**. The pivot assembly **134** couples the rotating frame **108** to the stationary frame **106**. The pivot assembly **134** allows the rotating frame **108**, and any bicycle attached thereto, to angularly move relative to the stationary frame **106** on bearings (not shown). For instance, the pivot assembly **134** allows the rotating frame **108** to pivot about a rotation axis **136** (FIG. 2). The rotation axis **136** is suitably located substantially perpendicular to the support surface **202**, although those skilled in the art will appreciate that the rotation axis **136** may be inclined relative to the support surface **202** at other angles. As the rotating frame **108** pivots about the rotation axis **136**, the bicycle **200**, also pivots about the rotation axis **136**, thereby simulating the turning of the bicycle.

The pivot assembly **134** includes an upper pivot assembly **138** and a lower pivot assembly **140**. The upper pivot assembly **138** includes a bracket **124** mounted to the top of the support frame **116**. The bracket **124** is a clevis style pivot bracket; however it should be apparent to those skilled in the art that other pivot assemblies are suitable for use with and are within the scope of the present invention. A rotation pin **142**, suitably mounted on bearings (not shown), passes through the bracket **124** and the rotating frame **108**. The rotation pin **142** permits the upper portion of the rotating frame **108** to selectively rotate about the rotation axis **136**.

The lower pivot assembly **140** includes a pivot pin **144** passing through a bushing **146** in the stationary frame **106**. The pivot pin **144** is concentrically aligned with the rotation axis **136** and permits the lower portion of the rotating frame **108** to rotate about the rotation axis **136**.

Still referring to FIG. 2, the roller assembly **104** will now be described in greater detail. The roller assembly **104** includes a front roller assembly **148**, a rear roller assembly **150**, and a power transfer assembly **152**. The rear roller assembly **150** includes a drive roller **154**, an adjustment assembly **156**, a drive belt **158**, and a frame **160**. The drive roller **154** is configured to rotatably engage the rear wheel of a bicycle and rotate about a substantially horizontal rotation axis **162** oriented substantially parallel to the support surface **202** and substantially perpendicular to the rotation axis **136** of the rotating frame **108**. One end of the drive roller **154** also includes a pulley **164** for receiving the drive belt **158** and transferring rotation, as described in greater detail below.

The frame **160** includes a pair of spaced arms **166**, with the distal ends of the arms **166** coupled to the drive roller **154**. The other ends of the arms **166** are rotatably coupled to the rotating frame **108**, such that the rear wheel frame **160** is able to rotate about a rotation axis **168**.

The adjustment assembly **156** permits the spacing of the drive roller **154** to be selectively adjusted relative to a tire of the bicycle. More specifically, the adjustment assembly **156** permits the position of the drive roller **154** to be adjusted closer or farther from the wheel of the bicycle to accommodate different rim and tire sizes and, if desirable, to vary the contact pressure between the tire and the drive roller **154**.

The adjustment assembly **156** includes a turnbuckle **170** that is adjustable in length. A first end of the turnbuckle **170** is coupled to the rotation frame **108** and the other end is coupled to the frame **160**. Shortening the length of the turnbuckle **170**

draws the drive roller **154** closer to the tire of the bicycle and/or increases the contact pressure between the drive roller **154** and the tire of the bicycle. Extending the length of the turnbuckle **170** moves the drive roller **154** farther from the tire of the bicycle and/or decreases the contact pressure between the drive roller **154** and the tire of the bicycle.

Although a specific adjustment assembly is illustrated and described, those skilled in the art will appreciate that the adjustment assembly may take many other forms. As an example, biasing devices, such as springs and elastic materials, can be used to bias the drive roller **154** toward the rear wheel. As a result, such devices are also within the scope of the present disclosure.

The power transfer assembly **152** includes a power transfer roller **172** rotatably coupled to the stationary frame **106**. As configured, the power transfer roller **172** is able to rotate about a rotation axis that is oriented substantially parallel to the support surface **202** and parallel to the rotation axis **162** of the drive roller **154** when the frame **160** is longitudinally aligned. The power transfer roller **172** is sized and configured to be engaged and rotated by the drive belt **158** such that power transferred from the bicycle to the rear wheel drive roller **154** is subsequently transferred to the power transfer roller **172**. In the illustrated embodiment, the drive belt **158** is permitted to move transversely along the length of the power transfer roller **172**, such that when the rotating frame **108** is rotated, the position of engagement of the drive belt **158** to the power transfer roller **172** moves accordingly.

As may be best seen by referring to FIG. 3, the power transfer roller **172** includes a pulley **174** for receiving a drive belt **176**. As configured, one end of the drive belt **176** transfers torque from to the power transfer roller **172** to the front roller assembly **148**.

Returning to FIG. 2, the front roller assembly **148** includes a front wheel roller **178** rotatably coupled to the stationary frame **106**. The front wheel roller **178** is able to rotate about a rotation axis oriented substantially parallel to the support surface **202** and substantially normal to the longitudinal direction of the stationary frame **106**. The front roller **178** is configured to engage and rotate a front wheel **208** (see FIG. 1) of the bicycle utilizing the power generated by the rear wheel of the bicycle and transferred to the front wheel roller **178** by the drive belts **158** and **176**.

The front wheel roller **178** is contoured to have a non-linear outer surface. Preferably, the front wheel roller **178** is contoured such that the front wheel roller **178** is hourglass in shape, wherein it has a greater diameter at the outer ends of the front wheel roller **178** than at its center. The contoured shape of the front wheel roller **178** aids in keeping the front wheel on the front wheel roller **178** during use. Specifically, the sloped end portions tend to direct the front wheel of the bicycle back toward the center of the front wheel roller **178**. Although the front wheel roller **178** is illustrated and described as being contoured, those skilled in the art will appreciate that the front wheel roller **178** may be alternately shaped, such as to have a linear outer surface.

Operation of the bicycle trainer **100** may be best understood by referring to FIGS. 1-3. The bicycle **200** is coupled to the bicycle trainer **100** by the bicycle clamping assembly **127**. More specifically, the bicycle clamping assembly **127** is clamped to the rear axle **206** of the rear wheel **210** of the bicycle. This locks the frame **204** of the bicycle **200** to the rotating frame **108** such that the any rotation of the frame **204** results in rotation of the rotating frame **108**. The position of the rear wheel drive roller **154** relative to the rear wheel **210** is adjusted by the adjustment assembly **156**. The front wheel **208** of the bicycle **200** rests on the front roller **178**.

5

During use, the bicycle **200** is supported in the upright position by the coupling of the bicycle **200** to the rotating frame **108**. The user then pedals the bicycle **200**, which causes the rear wheel **210** to spin. The spinning of the rear wheel **210** in turn causes the wheel roller **154** to rotate. Rotation of the wheel roller **154** causes rotation of the power transfer roller **172**, as the two are connected by the drive belt **158**. Because of the drive belt **176**, rotation of the power transfer roller **172** causes rotation of the front roller **178** and also causes rotation of the front wheel **208** of the bicycle **200** supported thereon.

The user may turn the bicycle **200** by rotating a handle bar **212** of the bicycle **200**. This causes the rotating frame **108** to rotate and the front wheel **208** of the bicycle **200** to travel along at least a portion of the front wheel roller **178**, thereby simulating turning of the bicycle **200**. Thus, the illustrated embodiment of the bicycle trainer **100** permits a user to simulate turns of the bicycle **200** on a bicycle trainer while still providing some upright support to the bicycle **200**.

As may be best seen by referring to FIG. 3, when the user turns the bicycle, the front wheel travels transversely outward from the center of the front roller **178** toward one of the ends of the front roller **178**. As the bicycle turns, the rotating frame **108**, rotates to accommodate turning of the bicycle. The drive belt **158** travels transversely along the length of the power transfer roller **172**, stretching as it moves to accommodate the increased distance between the power transfer roller **172** and the rear wheel drive roller **154**. In the illustrated embodiment, the rotating frame **108** is able to rotate through an angular displacement **180**. Preferably, a limit stop **182** is used to contact and impede the rotating frame **108** from over-rotating to prevent the front wheel of the bicycle from moving transversely off of the front wheel roller **178**.

Although the illustrated and described bicycle trainer is illustrated and described as utilizing a power transfer roller assembly, those skilled in the art will appreciate that the power transfer roller assembly is an optional component, and in alternate embodiments, the front wheel roller is driven by other means, such as directly from the rear wheel drive roller.

Although not illustrated, those skilled in the art will appreciate that the bicycle trainer may include well known resistance devices for providing variable resistance to pedal movement, a few suitable examples being fluid, magnetic, and/or fan resistance devices.

While the preferred embodiment of the invention has been illustrated and described, it will be appreciated that various changes can be made therein without departing from the spirit and scope of the invention.

The embodiments of the invention in which an exclusive property or privilege is claimed are defined as follows:

1. A bicycle trainer, comprising:

- (a) a stationary frame configured to rest on a support surface;
- (b) a support frame extending upwardly from the stationary frame;
- (c) a rotating frame pivotally coupled to the stationary frame at a lower end of the rotating frame and pivotally coupled to the support frame at an upper end of the rotating frame such that the rotating frame is pivotal around a rotation axis that is substantially perpendicular to the support surface when the stationary frame is resting on the support surface; and
- (d) an attachment assembly coupled to the rotating frame and configured to couple a bicycle to the rotating frame such that the bicycle is pivotal with the rotating frame about the rotation axis in response to user input.

6

2. The bicycle trainer of claim 1, wherein the attachment assembly includes a first roller assembly adapted to engage a wheel of the bicycle.

3. The bicycle trainer of claim 2, wherein the first roller is adjustably coupled to the attachment assembly to permit selective positioning of the first roller assembly relative to the attachment assembly.

4. The bicycle trainer of claim 2, further comprising a second roller assembly coupled to the stationary frame and positioned to engage a front wheel of the bicycle during use.

5. The bicycle trainer of claim 4, further comprising a power transfer assembly attached to the stationary frame.

6. The bicycle trainer of claim 5, wherein the power transfer assembly is in communication with the first and second roller assemblies for synchronizing rotational motion between the first and second roller assemblies.

7. The bicycle trainer of claim 5, wherein the second roller assembly includes a roller having a contour adapted to permit a front wheel of the bicycle to freely traverse between ends of the roller.

8. The bicycle trainer of claim 7, wherein the ends of the roller are contoured to assist in maintaining alignment of the front wheel between the ends of the roller.

9. A bicycle trainer, comprising:

- (a) a stationary frame adapted to rest upon a support surface;
- (b) a first roller assembly coupled to the stationary frame, the first roller assembly having a first roller rotatably engageable with a first wheel of a bicycle; and
- (c) a second roller assembly having a second roller rotatably engageable with a second wheel of the bicycle, the second roller assembly pivotally coupled to the stationary frame such that the second roller assembly is pivotal about a rotation axis that is substantially perpendicular to the support surface when the stationary frame is resting on the support surface to permit pivoting of the bicycle about the rotation axis while rotatably engaging the second wheel of the bicycle.

10. The bicycle trainer of claim 9, wherein rotation of the first and second rollers is synchronized by a power transfer assembly.

11. The bicycle trainer of claim 10, wherein the power transfer assembly is coupled to the first roller assembly by a first belt and the power transfer assembly is coupled to the second roller assembly by a second belt.

12. The bicycle trainer of claim 10, wherein the first roller is contoured to permit a front wheel of the bicycle to freely traverse between ends of the first roller during use.

13. The bicycle trainer of claim 9, further comprising an adjustment assembly extending between the second roller assembly and a portion of the bicycle trainer to permit selective adjustment of the second roller assembly relative to the second wheel of the bicycle when the bicycle is coupled to the bike trainer.

14. A bicycle trainer, comprising:

- (a) a stationary frame adapted to rest upon a support surface; and
- (b) a rotating frame pivotally coupled to the stationary frame such that the rotating frame is pivotal about a rotation axis that is substantially perpendicular to the support surface when the stationary frame is resting on the support surface, the rotating frame including a bicycle coupling assembly adapted to restrain a bicycle to the bicycle trainer during use and a roller assembly coupled to the rotating frame such that the entire roller

7

assembly is pivotal about the rotation axis, wherein the rotating frame permits the bicycle to pivot about the rotation axis.

15. The bicycle trainer of claim 14, wherein the roller assembly having a first roller sized and configured to engage a wheel of the bicycle when the bicycle is attached to the bicycle trainer.

16. The bicycle trainer of claim 15, wherein the first roller is adjustably coupled to the bicycle coupling frame by an adjustment assembly to permit selective adjustment of the

8

first roller relative to a rear wheel of the bicycle when the bicycle is attached to the bicycle trainer.

17. The bicycle trainer of claim 16, further comprising a second roller coupled to the stationary frame and configured to rotatably engage a front wheel of the bicycle when the bicycle is attached to the bicycle trainer.

18. The bicycle trainer of claim 17, wherein rotation of the first and second rollers is synchronized by a power transfer assembly.

* * * * *