



US007524207B2

(12) **United States Patent**  
**Honda et al.**

(10) **Patent No.:** **US 7,524,207 B2**  
(45) **Date of Patent:** **Apr. 28, 2009**

(54) **REINFORCING TAB, METHOD OF MANUFACTURING THE SAME AND STRUCTURE OF CONNECTING CONNECTOR USING THE SAME**

5,297,966	A *	3/1994	Brennian et al.	439/64
5,788,515	A *	8/1998	Mitra et al.	439/83
6,475,031	B1 *	11/2002	Wu	439/570
6,478,617	B2 *	11/2002	Fan	439/570
7,001,212	B1 *	2/2006	Juntwait	439/566

(75) Inventors: **Takayoshi Honda**, Kariya (JP); **Tadashi Tsuruzawa**, Chiryu (JP)

(73) Assignee: **DENSO CORPORATION**, Kariya (JP)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/790,114**

(22) Filed: **Apr. 24, 2007**

(65) **Prior Publication Data**

US 2007/0254531 A1 Nov. 1, 2007

(30) **Foreign Application Priority Data**

Apr. 28, 2006 (JP) ..... 2006-125732

(51) **Int. Cl.**  
**H01R 13/73** (2006.01)

(52) **U.S. Cl.** ..... **439/570**

(58) **Field of Classification Search** ..... 439/570, 439/566, 562, 563, 573; 219/76, 73; 248/205.1  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,186,654 A 2/1993 Enomoto et al.

**FOREIGN PATENT DOCUMENTS**

JP	A-6-333620	12/1994
JP	A-11-317265	11/1995
JP	A-2004-319229	11/2004
JP	A-2004-319230	11/2004
JP	A-2006-48970	2/2006
JP	A-2006-48971	2/2006

\* cited by examiner

*Primary Examiner*—Alexander Gilman

(74) *Attorney, Agent, or Firm*—Posz Law Group, PLC

(57) **ABSTRACT**

A reinforcing tab for reinforcing connection between a circuit board and a surface-mounted connector includes a fixing wall to be fixed to a housing of the connector and a connecting wall defining a connecting surface on its end to be connected to the circuit board. The connecting wall extends from the fixing wall and includes a bend at least at a part. Further, the connecting wall has a recess on the connecting surface at a position corresponding to the bend.

**24 Claims, 10 Drawing Sheets**





FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 3A




FIG. 3B







FIG. 3C




**FIG. 4A**




**FIG. 4B**




**FIG. 4C**




**FIG. 5A**




**FIG. 5B**




**FIG. 5C**




**FIG. 5D**




**FIG. 6A**




**FIG. 6D**




**FIG. 6B**



**FIG. 6E**



**FIG. 6C**



**FIG. 6F**




FIG. 7A




FIG. 7B




FIG. 7C






FIG. 8A




FIG. 8B




FIG. 9A







FIG. 9B




**FIG. 10**  
PRIOR ART




**FIG. 11A**  
RELATED ART




**FIG. 11B**  
RELATED ART




**FIG. 11C**  
RELATED ART




**FIG. 12A**  
RELATED ART




**FIG. 12B**  
RELATED ART




**FIG. 12C**  
RELATED ART



**FIG. 13A**  
RELATED ART



**FIG. 13B**  
RELATED ART



1

**REINFORCING TAB, METHOD OF  
MANUFACTURING THE SAME AND  
STRUCTURE OF CONNECTING  
CONNECTOR USING THE SAME**

CROSS REFERENCE TO RELATED  
APPLICATION

This application is based on Japanese Patent Application No. 2006-125732 filed on Apr. 28, 2006, the disclosure of which is incorporated herein by reference.

FIELD OF THE INVENTION

The present invention relates to a reinforcing tab for reinforcing connection between a circuit board and a surface-mounted connector, a method of manufacturing the reinforcing tab, and a connecting structure of the connector using the reinforcing tab.

BACKGROUND OF THE INVENTION

A reinforcing tab for reinforcing connection between a circuit board and a surface-mounted connector is for example disclosed in Japanese Unexamined Patent Publication No. 2004-319229. FIG. 10 shows a reinforcing tab **3** fixed to a connector **1** in the publication. The reinforcing tab **3** includes a fixing portion **5** fixed to the connector **1**, extending portions **6** extending from the fixing portion **5** and connecting portions **4** at the ends of the extending portions **6** to be connected to a circuit board. The connecting portions **4** are bent from the extending portions **6** so as to increase a connecting area with the circuit board and maintain sufficient connecting strength.

The reinforcing tab **3** is fixed to the connector **1** such that the fixing portion **5** is received in a fixing portion **1a** of a housing of the connector **1**. In this condition, the bottom surfaces of the connecting portions **4** are connected with solder mounted on surfaces of lands of the circuit board. Thus, the reinforcing tab **3** reinforces the connected state of the connector **1** and the circuit board.

Such a reinforcing tab **3** is for example formed by punching and bending. FIGS. 11A to 13B show examples of the reinforcing tab **3** formed by punching and bending. In FIGS. 11A to 13B, parts having similar functions as the reinforcing tab **3** shown in FIG. 10 are designated with like reference numerals.

First, a metallic plate is stamped such that a tab base member having the shape shown in FIG. 11A is formed. Then, the connecting portions **4** are bent by applying forces as shown by arrows in FIGS. 11B and 11C. At this time, however, the connecting portions **4** will have protrusions or expansions **4b** on the ends of a bent portion **4a**, as shown in FIGS. 12A to 12C.

As shown in FIGS. 13A and 13B, when this connecting portion **4** is connected to a land **7** of a circuit board, a connecting surface **4c** of the connecting portion is separated from the land **7** due to the protrusion **4b**. As a result, a connecting area between the connecting surface **4c** and the land **7** is reduced, and hence the connection between the reinforcing tab **3** and the circuit board will be degraded.

SUMMARY OF THE INVENTION

The present invention is made in view of the foregoing matter, and it is an object of the present invention to provide a reinforcing tab capable of improving connection between a connector and a circuit board. It is another object of the present invention to provide a method of manufacturing the

2

reinforcing tab capable of improving connection between a connector and a circuit board. It is another object of the present invention to provide a connecting structure of a connector to a circuit board using the reinforcing tab.

According to an aspect of the present invention, a reinforcing tab for reinforcing connection between a circuit board and a surface-mounted connector includes a fixing wall to be fixed to a housing of the connector and a connecting wall that defines a connecting surface to be connected to the circuit board. The connecting wall extends from the fixing wall. The connecting wall includes a bent portion at least at a part such that the connecting wall includes a first connecting portion and a second connecting portion on opposite sides of the bent portion. Namely, the second connecting portion extends from the fixing wall and the first connecting portion extends from the second connecting portion through the bent portion. The first connecting portion defines a first connecting surface as a part of the connecting surface and the second connecting portion defines a second connecting surface as a part of the connecting surface. An end of the bent portion defines a recess that is recessed relative to the second connecting surface.

Accordingly, since the connecting wall does not have a projection or protrusion on its end surface to be connected to the circuit board at a position corresponding to the bent portion, the end surface of the connecting wall is properly connected to the circuit board. Namely, the reinforcing tab sufficiently maintains a connecting area to be connected to the circuit board, the connection between the connector and the circuit board improves.

For example, the reinforcing tab is manufactured as follows. First, a tab base member including the fixing wall and the connecting wall is punched out from a metallic plate. At this time, the recess is formed on the end surface of the connecting wall. Then, the connecting wall is bent at a position corresponding to the first recess by applying force to a portion of the connecting wall in a direction substantially parallel to the end surface. Since the connecting wall is bent at the position corresponding to the recess, the end surface of the connecting wall is not projected at the bent portion.

For example, the reinforcing tab is fixed such that the fixing wall is fixed to the housing of the connector and the connecting wall is connected to a land of the circuit board by a joining material such as solder. In this case, the width of the connecting wall reduces at the bent portion due to the recess. Therefore, this structure restricts heat from of the connecting wall and the joining material from transferring toward the fixing wall, when connecting the connecting wall to the circuit board with the joining material. Because the joining material is easily melted, the connecting wall is properly connected to the circuit board.

According to a second aspect of the present invention, a reinforcing tab for reinforcing connection between a circuit board and a surface-mounted connector includes a fixing wall to be fixed to a housing of the connector and a connecting wall to be connected to the circuit board. The connecting wall extends from the fixing wall and defines a connecting surface at an end. The connecting wall is bent at least at a part, and thus the connecting wall includes a first connecting portion, a second connecting portion and a bent portion between the first and second connecting portion. The second connecting portion extends from the fixing wall and the first connecting portion extends from the second connecting portion through the bent portion. The first connecting portion defines a first connecting surface as a part of the connecting surface, the second connecting portion defines a second connecting surface as a part of the connecting surface. Also, the bent portion

defines a third connecting surface as a part of the connecting surface. The third connecting surface is substantially coplanar at least with the second connecting surface.

Accordingly, since the bent portion provides the third connecting surface, a connecting area with the circuit board is sufficiently maintained. Also, since the third connecting surface is substantially coplanar at least with the second connecting surface, the connecting wall is properly connected to the circuit board. Thus, the connection between the connector and the circuit board improves.

The reinforcing tab is for example manufactured as follows. First, a tab base member including the fixing wall and the connecting wall is punched out from a metallic plate. Then, the connecting wall is bent at least at a part by applying a force in a direction substantially parallel to the end surface of the connecting wall. Thereafter, the end surface is flattened. Accordingly, even if the end surface of the connecting wall is protruded at the end of the bent portion, it can be flattened. Thus, the third connecting wall provided by the end of the bent portion is substantially coplanar with the second connecting surface.

The reinforcing tab is fixed such that the fixing portion is fixed to a housing of the connector and the connecting surface is connected to a land of the circuit board with a joining material. Since the third connecting surface and the second connecting surface are substantially coplanar, the connecting wall is properly connected to the land. Therefore, the connection between the connector and the circuit board improves.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Other objects, features and advantages of the present invention will become more apparent from the following detailed description made with reference to the accompanying drawings, in which like parts are designated by like reference numbers and in which:

FIG. 1A is a top view of a connector that is mounted to a circuit board and reinforced through a reinforcing tab according to an embodiment of the present invention;

FIG. 1B is a side view of the connector shown in FIG. 1A;

FIG. 1C is an enlarged side view of a part of the connector shown in FIG. 1A;

FIG. 2A is a plan view of the reinforcing tab according to the embodiment;

FIG. 2B is a bottom view of the reinforcing tab shown in FIG. 2A;

FIG. 2C is a side view of the reinforcing tab shown in FIG. 2A;

FIG. 2D is an enlarged view of a connecting portion of the reinforcing tab shown in FIG. 2A;

FIG. 3A is a plan view of the reinforcing tab before connecting portions are bent according to the embodiment;

FIG. 3B is a bottom view of the reinforcing tab shown in FIG. 3A;

FIG. 3C is a side view of the reinforcing tab shown in FIG. 3A;

FIGS. 4A and 4B are explanatory side views of a connector and a reinforcing tab connected to a circuit board as comparative examples;

FIG. 4C is an end view of the connector and the reinforcing tab shown in FIGS. 4A and 4B;

FIG. 5A to 5C are explanatory side views of the connector and the reinforcing tab connected to the circuit board for showing various examples of connecting structure according to the embodiment;

FIG. 5D is an end view of the connector and the reinforcing tab shown in FIGS. 5A to 5C;

FIGS. 6A to 6F are plan views for showing various examples of the connecting portion before being bent according to the embodiment;

FIG. 7A is a plan view of a reinforcing tab for showing an example of extending portions according to the embodiment;

FIG. 7B is a plan view of a reinforcing tab without having a groove on a connecting surface as an example according to the embodiment;

FIG. 7C is a side view of a reinforcing tab having a positioning projection on a connecting surface as an example according to the embodiment;

FIG. 8A is a plan view of a reinforcing tab as another example according to the embodiment;

FIG. 8B is a bottom view of the reinforcing tab shown in FIG. 8A;

FIG. 9A is a plan view of a reinforcing tab as further another example according to the embodiment;

FIG. 9B is a bottom view of the reinforcing tab shown in FIG. 9A;

FIG. 10 is a perspective view of a connector and a reinforcing tab fixed to the connector as a prior art;

FIG. 11A is a plan view of a reinforcing tab before connecting portions are bent as a related art;

FIG. 11B is a bottom view of the reinforcing tab shown in FIG. 11A;

FIG. 11C is a side view of the reinforcing tab shown in FIG. 11A;

FIG. 12A is a plan view of the reinforcing tab shown in FIGS. 11A to 11C, after the connecting portions are bent;

FIG. 12B is a bottom view of the reinforcing tab shown in FIG. 12A;

FIG. 12C is a side view of the reinforcing tab shown in FIG. 12A;

FIG. 13A is an enlarged view of the connecting portion of the reinforcing tab shown in FIG. 12A; and

FIG. 13B is a side view of the connecting portion shown in FIG. 13A when connected to a circuit board.

#### DETAILED DESCRIPTION OF EXAMPLE EMBODIMENT

An embodiment of the present invention will be described with reference to FIGS. 1A to 4C. Referring to FIGS. 1A to 1C, first, a connecting structure of a connector **20** and a circuit board **10** using reinforcing tabs **30** will be described.

The circuit board **10** includes a printed circuit board **13** on which wiring patterns and via holes for connecting the wiring patterns are formed. Electronic components such as a micro-computer, power transistors, resistors, capacitors (not shown) and the connector **20** as an input/output part to be connected with external devices are mounted on the printed circuit board **13**. Also, the circuit board **10** includes terminal lands **11** to which terminals **22** of the connector **20** are connected and reinforcing lands **12** to which connecting portions **32** of the reinforcing tabs **30** are connected, on a surface of the printed circuit board **13**. Further, joining materials such as solder (not shown) are formed on surfaces of the terminal lands **11** and the reinforcing lands **12**.

The connector **20** is a surface-mounted type connector, and includes a housing **21** and the terminals **22**. The terminals **22** are made of an electrical conductive material. The housing **21** is made of an electrical insulating material (e.g., synthetic resin). The terminals **22** are arranged in the housing such that first ends thereof are surface-mounted to the circuit board **10** and second ends thereof are disposed to be connectable with the external devices. The housing **21** has housing fixing portions **23** on its end surfaces with respect to a longitudinal

direction, and to which the reinforcing tabs **30** are fixed so as to improve joining strength between the circuit board **10** and the connector **20**.

The terminals **22** are fixed to the housing **21** such as by inserting. The terminals **22** are arranged at equal intervals with respect to the longitudinal direction of the housing **21** without interfering with each other.

The housing fixing portions **23** are configured to receive the reinforcing tabs **30** from top side. For example, the reinforcing tabs **30** can be fixed on the housing fixing portions **23** toward the circuit board **10**, as shown in FIGS. **1B** and **1C**. The reinforcing tabs **30** have tab fixing portions **31** to be engaged with the housing fixing portion **23**. Thus, each reinforcing tab **30** is fixed to the housing **21** such that the tab fixing portions **31** and the housing fixing portion **23** are engaged with a predetermined strength.

The reinforcing tabs **30** are provided to bias the connector **20** toward the circuit board **10** so as to improve reliability of connection between the connector **20** and the circuit board **10**. As shown in FIG. **1B**, each of the reinforcing tabs **30** includes the tab fixing portion (fixing wall) **31** and the connecting portions (connecting walls) **32** extending from the tab fixing portion **31** through extending portions **34**. The connecting portions **32** are connected to the tab fixing portion **31** through the extending portions **34**. For example, the reinforcing tab **30** has a generally U-shape when viewed along the longitudinal direction of the housing **21**.

The extending portions **34** extends substantially perpendicular to the tab fixing portion **31**. The connecting portions **32** extend substantially perpendicular to the extending portions **34**. Further, the connecting portion **32** provides a connecting surface on its end surface that is on a side opposite to the tab fixing portion **31** with respect to the extending portion **34**. The connecting surface extends substantially parallel to the surface of the circuit board **10**. The reinforcing tab **30** is connected to the circuit board **10** through the connecting surface.

As shown in FIG. **1A**, each connecting portion **32** is bent at a bent portion **33** and thus has a substantially L-shape. In other words, the connecting portion **32** includes a first connecting portion **32a** and a second connecting portion **32b** between the first connecting portion **32a** and the extending portion **34**. The connecting surface is provided by end surfaces **32a1**, **32b1** of the first connecting portion **32a** and the second connecting portion **32b**. Hereafter, the end surface of the first connecting portion **32a** is referred to as a first connecting surface **32a1** and the end surface of the second connecting portion **32b** is referred to as a second connecting surface **32b1**.

Further, the connecting portion **32** is formed with a first groove (recess) **33a** and a second groove (recess) **33b** at positions corresponding to ends of the bent portion **33**. Namely, the first groove **33a** is formed on the connecting surface, between the first connecting surface **32a1** and the second connecting surface **32b1**. The second groove **33a** is formed on an end surface of the connecting portion, which is opposite to the connecting surface. Thus, the end surfaces of the connecting portion **32** do not have projections or expansions, which are formed by bending the connecting portion **32** at the bent portion **33**.

The connector **20** is mounted to the circuit board **10** in the following manner. First, the reinforcing tab **30** is fixed to the housing fixing portion **23** of the connector **20**. Specifically, as shown in FIG. **1C**, the tab fixing portion **31** is received by the housing fixing portion **23** such that the extending portions **34** are substantially perpendicular to the circuit board **10** and the

first and second connecting surfaces **32a1**, **32b1** are substantially parallel to the circuit board **10**.

Next, the terminals **22** of the connector **20** are soldered with the terminal lands **11** of the circuit board **10** such as by reflow soldering. Also, the connecting portions **32** of the reinforcing tab **30** are soldered with the reinforcing lands **12** such as by reflow soldering. As such, the connector **20** is mounted to the circuit board **10**.

Since the connector **20** is biased toward the circuit board **10** by the reinforcing tabs **30**, the connecting strength between the connector **20** and the circuit board **10** is improved. In this case, the first grooves **33a** are formed at the ends of the bent portions **33**. In other words, the connecting surface do not have projections at the positions corresponding to the bent portions **33**. Therefore, the first and second connecting surfaces **32a1**, **32b1** are properly soldered with the reinforcing lands **12**. Accordingly, the reinforcing tabs **30** are connected to the circuit board **10** while sufficiently maintaining connecting areas with the circuit board **10**. As a result, the connector **20** is connected to the circuit board **10** with a sufficient strength.

For example, the circuit board **10** on which the connector **20** is mounted is employed to an electronic device such as a control unit for a vehicle. In this case, it is generally subjected to high temperature, and thus the housing **21** and the circuit board **10** will be deformed by thermal expansion. Further, in a case that the housing **21** and the circuit board **10** are made of different materials having different coefficient of thermal expansion, the housing **21** and the circuit board **10** are likely to be displaced relative to each other. For example, the amount of displacement increases with a distance from the center of the housing **21**. That is, the ends of the housing **21** with respect to the longitudinal direction is likely to more displace relative to the circuit board **10**, and receive stress easily.

In this embodiment, the housing fixing portions **23** are formed on the ends of the housing **21** with respect to the longitudinal direction, and the reinforcing tabs **30**, which is connected to the reinforcing lands **12** of the circuit board **10**, are fixed to the housing fixing portions **23**. Therefore, the connecting condition between the connector **20** and the circuit board **10** is sufficiently maintained.

The fixing direction of the reinforcing tabs **30** to the connector **20** may be decided in view of a direction in which the circuit board **10** on which the connector **20** and the reinforcing tabs **30** are mounted is carried and/or a direction in which heat is applied, during the reflow soldering, for soldering the terminals **22** and the connecting portions **32** with the terminal lands **11** and the reinforcing lands **12**, respectively.

For example, during the reflow soldering, reflow heat is applied in the longitudinal direction of the connector **20** from a top of the circuit board **10**, and the circuit board **10** is carried in a left direction in FIG. **1A**. In this case, the first connecting portions **32a** easily receive the solder, and thus the reinforcing tabs **30** and the connector **20** are not easily moved. Namely, since the first connecting portions **32a** extend in a direction perpendicular to the direction in which the circuit board **10** is carried, the first connecting portions **32a** easily catch the solder. Also, the connector **20** can be connected to the circuit board **10** in view of the direction in which the circuit board **10** is carried during the reflow soldering.

Next, structure of the reinforcing tabs **30** will be described more in detail. The reinforcing tabs **30** are formed by shaping a metallic plate into a predetermined shape such as by punching and bending. The metallic plate is for example made of copper such as brass. For example, the metallic plate can be primarily coated with nickel and then coated with tin.

As described in the above, each reinforcing tab **30** includes the tab fixing portion **31**, the extending portions **34** and the connecting portions **32**. When viewed from a bottom, as shown in FIG. 2B, the reinforcing tab **30** has a substantially U-shape. Also, when viewed from a side, as shown in FIG. 2C, the reinforcing tab **30** has a substantially L-shape.

The tab fixing portion **31** is inserted to the housing fixing portion **23** from the top side and fixed to the housing **21** in a condition that the engagement between the housing fixing portion **23** and the tab fixing portion **31** is maintained in the predetermined strength. The extending portions **34** extend from ends of the tab fixing portion **31** substantially perpendicular to the tab fixing portion **31**.

The connecting portions **32** are located at the ends of the extending portions **34** on the side opposite to the tab fixing portion **31**. Thus, the reinforcing tab **30** is connected to the circuit board **10** at two positions. Here, each connecting portion **32** is bent at the bent portion **33** so as to increase the connecting area with the circuit board **10**.

The second connecting portion **32b** extends from the extending portion **34** in a direction substantially parallel to the tab fixing portion **31**. The first connecting portion **32a** connects to the second connecting portion **32b** through the bent portion **33**. For example, the second connecting portion **32b** extends in a direction perpendicular to the longitudinal direction of the housing **21**. The first connecting portion **32a** extends in a direction substantially parallel to the longitudinal direction of the housing **21**.

The first connecting portion **32a** has the first connecting surface **32a1** on its lower end that is opposed to the circuit board **10**, and the second connecting portion **32b** has the second connecting surface **32b1** on its lower end that is opposed to the circuit board **10**. The first connecting surface **32a1** and the second connecting surface **32b1** connect to each other through the bent portion **33**.

The connecting portion **32** has a rectangular shape in a cross-section defined in a direction perpendicular to its axis, e.g., in a cross-section taken along a dashed chain line A1 in FIG. 2D. The first and second connecting surfaces **32a1**, **32b1** and the end surfaces **32a1**, **32b2**, which are on the side opposite to the first and second connecting surfaces **32a1**, **32b1**, extend along the short side of the rectangular shape of the cross-section. Hereafter, the surfaces **32a1**, **32b1**, **32a1**, **32b1** are also referred to as first surfaces S1.

Also, surfaces of the connecting portion **32** that extend along the long side of the rectangular shape of the cross-section are substantially coplanar with surfaces of the extending portion **34** and the fixing portion **31** before the connecting portion **32** is bent at the bent portion **33**. After the connecting portion **32** is bent at the bent portion **33**, the surfaces of the second connecting portion **32b** that extend along the long side of the rectangular shape of the cross-section are substantially coplanar with the surfaces of the extending portion **34** and the fixing portion **31**, and these surfaces are also referred to as second surfaces S2, hereafter.

The first groove **33a** is formed on the lower end of the bent portion **33** and has a length in a direction in which a thickness of the metallic plate forming the reinforcing tab **30** is measured. That is, the first groove **33a** extends in a direction in which the thickness of the metallic plate is measured.

In a condition that the first connecting portion **32a** is bent relative to the second connecting portion **32b**, the inner surfaces of the first groove **33a** are recessed from the first and second connecting surfaces **32a1**, **32b1**. In other words, the first and second connecting surfaces **32a1**, **32b1** are coplanar and do not have projections between them.

In a case that a metallic plate member without having a groove such as the first groove **33a** on its end surface is bent, a portion corresponding to the end of the bent portion is likely to expand or project. If a connecting portion having such a projection on the end surface is connected to the circuit board **10**, a first connecting surface and a second connecting surface are separated from the circuit board **10** due to the projection. As a result, the connecting area between the connecting portion and the circuit board reduces.

In this embodiment, since the first groove **33a** is formed at the position corresponding to the lower end of the bent portion **33**, it is less likely that such a projection will be formed when bending the connecting portion **32**. Therefore, the first and second connecting surfaces **32a1**, **32b1** are sufficiently connected to the circuit board **10**. Accordingly, the connection between the reinforcing tab **30** and the circuit board **10** improves.

Further, the connecting portion **32** has the second groove **33b** on the side opposite to the first groove **33a**. The second groove **33b** extends in the direction in which the thickness of the metallic plate is measured, similar to the first groove. Thus, the connecting portion **32** is easily bent at the bent portion **33**. However, the second groove **33b** is not always necessary.

In the above example, each connecting portion **32** has the substantially L-shape, as shown in FIG. 2B. However, the shape of the connecting portion **32** may not be limited to the L-shape. For example, the connecting portion **32** may be bent such that the bent portion **33** has an arc or curve. Further, it is not always necessary that the first connecting portion **32a** extends substantially perpendicular to the second connecting portion **32b**.

Next, a method of manufacturing the reinforcing tab **30** will be described. First, as shown in FIG. 3A, a base member for the reinforcing tab **30** is formed by punching from the metallic plate. The base member has a predetermined shape including the tab fixing portion **31**, the extending portions **34** and the connecting portions **32**. Also, the base member has the first and second grooves **33a**, **33b** extending in the direction in which the thickness of the metallic plate is measured.

Then, as shown in FIGS. 3B and 3C, force (arrows A2) is applied to portions of the base member, which correspond to the first connecting portions **32a**, in a direction perpendicular to the base member such that the connecting portions **32** are bent at the positions corresponding to the first and second grooves **33a**, **33b**. That is, in this bending step, the force is applied to each first connecting portion **32a** in the direction substantially parallel to the first and second connecting surfaces **32a1**, **32b1** such that the first connecting portion **32a** is moved about a line passing through the first and second grooves **33a**, **33b**. As such, the bent portions **33** are formed.

Accordingly, since the first and second grooves **33a**, **33b** are formed before the bending, it is less likely that the ends of the bent portions will be projected outwardly from the connecting surface. As such, the first and second connecting surfaces **32a1**, **32b1** are properly connected to the circuit board **10** without causing clearances between the first and second connecting surfaces **32a1**, **32b1** and the circuit board **10**. Thus, the reinforcing tabs **30** that provide reliable connections with the circuit board **10** are manufactured.

In the example shown in FIG. 3B, the first groove **33a** extends with a constant width in the direction in which the thickness of the base member is measured. That is, the width of the first groove **33a** on the lower surface in FIG. 3B, which corresponds to an outer side of the bent, is equal to the width of the first groove **33a** on the upper surface in FIG. 3B, which

corresponds to an inner side of the bent. Thus, the first groove **33a** is easily formed only by punching.

On the other hand, the width of the first groove **33a** may be increased in the direction that the force is applied. Namely, the width of the first groove **33a** may be increased from the lower surface, which corresponds to the outer side of the bent, toward the upper surface, which corresponds to the inner side of the bent. Thus, when the reinforcing tab **30** is viewed from the bottom as in FIG. 3B, the first groove **33a** has a trapezoidal shape, for example. In this case, the connecting portions **32** are easily bent.

Also, since the first and second groove **33a**, **33b** are formed on sides of the connecting portion **32**, a width of the connecting portion **32** is reduced at the positions corresponding to the first and second grooves **33a**, **33b**. Therefore, this narrowed portion reduces heat of the solder and the connecting portion **32** from transferring toward the tab fixing portion **31** during the reflow soldering. As such, the solder to be connected with the connecting portions **32** is easily melted during the reflow soldering. Accordingly, the reinforcing tab **30**, which is capable of improving the quality of soldering, is produced.

Further, as shown in FIG. 3A, a width **X2** of the second groove **33b** may be greater than a width **X1** of the first groove **33a**. In this case, when the connecting portion **32** is bent at the bent portion **33**, the first connecting portion **32a** is easily inclined relative to a plane along which the second connecting surface **32b1** extends. That is, the first connecting portion **32a** is easily inclined to separate from the circuit board **10**.

It is preferable that both of the first connecting surface **32a1** and the second connecting surface **32b1** are connected to the circuit board **10**. However, there may be possibility that the first connecting surface **32a1** or the second connecting surface **32b1** is separated from the circuit board **10** for some reason, which may be caused when the reinforcing tab **30** is formed or when the reinforcing tab **30** is fixed to the housing **21**.

For example, as shown in FIG. 4A, the above situation occurs when the first surface **S1** is angled relative to the second surface **S2** equal to or more than  $90^\circ$  ( $\theta_1 \geq 90^\circ$ ) in forming the reinforcing tab **30** (e.g., in the punching or in the bending). When this reinforcing tab **30** is fixed to the connector **20** such that the second surface **S2** is approximately  $90^\circ$  relative to the surface of the circuit board **10** (i.e.,  $\theta_2 = 90^\circ$ ), the second connecting surface **32b1** is separated from the circuit board **10**.

Further, the above situation also occurs even in the reinforcing tab **30** in which the angle  $\theta_1$  between the first surface **S1** and the second surface **S2** is approximately  $90^\circ$ . For example, as shown in FIG. 4B, if the reinforcing tab **30** is fixed to the connector **20** such that the second surface **S2** is inclined relative to a direction perpendicular to the surface of the circuit board **10** (i.e.,  $\theta_2 \geq 90^\circ$ ), the second connecting surface **32b1** is separated from the circuit board **10**.

FIG. 4C shows a front view of the reinforcing tab **30** shown in FIGS. 4A and 4B. In these cases, although the first connecting surfaces **32a1** are connected to the circuit board **10**, the second connecting surfaces **32b1** are separated from the circuit board **10**. Thus, the reinforcing tab **30** is less stable, as compared with a case in which the second connecting surfaces **32b1** are connected to the circuit board **10** but the first connecting surfaces **32a1** are separated from the circuit board **10**. Namely, the second connecting surfaces **32b1** are essential portions for stably connecting the reinforcing tab **30** with the circuit board **10**.

On the other hand, when the connecting portion **32** is formed such that first connecting surface **32a1** is inclined to separate from the circuit board **10** such as by means shown in

FIG. 3A ( $X_2 > X_1$ ), the connection of the second connecting surface **32b1** to the circuit board **10** is enhanced. Thus, the reinforcing tab **30** is more stably connected to the circuit board **10**, as compared with the examples shown in FIGS. 4A to 4C. As such, the connection between the connector **20**, the reinforcing tab **30** and the circuit board **10** improve.

Other examples of the connecting structure of the reinforcing tab **30** to the circuit board **10** will be described with reference to FIGS. 5A to 5D.

In an example shown in FIG. 5A, the angle  $\theta_1$  between the first surface **S1** and the second surface **S2** is approximately  $90^\circ$ . This reinforcing tab **30** can be fixed to the connector **20** such that the angle  $\theta_2$  between the second surface **S2** and the circuit board **10** is equal to or less than  $90^\circ$ .

In an example shown in FIG. 5B, the angle  $\theta_1$  between the first surface **S1** and the second surface **S2** is equal to or greater than  $90^\circ$ . This reinforcing tab **30** can be fixed to the connector **20** such that the angle  $\theta_2$  between the second surface **S2** and the circuit board **10** is equal to or less than  $90^\circ$ .

In an example shown in FIG. 5C, the angle  $\theta_1$  between the first surface **S1** and the second surface **S2** is equal to or less than  $90^\circ$ . This reinforcing tab **30** can be fixed to the connector **20** such that the angle  $\theta_2$  between the second surface **S2** and the circuit board **10** is approximately  $90^\circ$ .

In the examples shown in FIGS. 5A to 5C, at least the second connecting surface **32b1** is connected to the circuit board **10**, even though the first connecting surface **32a1** is separated from the circuit board **10**, as shown in FIG. 5D. Thus, the reinforcing tab **30** is more stably connected to the circuit board **10**, as compared with the case in which the reinforcing tab **30** is connected to the circuit board **10** only through the first connecting surfaces **32a1**. Accordingly, even in the embodiments shown in FIGS. 5A to 5C, the connection between the connector **10**, the reinforcing tab **30** and the circuit board **10** improves.

Further, the connecting portion **32** can be modified. FIGS. 6A to 6F show examples of the connecting portion **32** before the bending.

As shown in FIG. 6A, the first groove **33a** and the second groove **33b** can be formed at different positions with respect to the longitudinal direction of the connecting portion **32**. Namely, the second groove **33b** is closer to the end than the first groove **33a**. Thus, an imaginary line **L1** passing through the first groove **33a** and the second groove **33b** is inclined with respect to a direction perpendicular to the longitudinal direction of the connecting portion **32** before the bending.

In the example shown in FIG. 6B, the second groove **33b** is located closer to the end than the first groove **33a**, similar to the example shown in FIG. 6A. Further, the first and second grooves **33a**, **33b** are inclined along the line **L1** passing through the first and second grooves **33a**, **33b**. That is, side walls of the first and second grooves **33a**, **33b** are inclined along the line **L1**, and bottom walls of the first and second grooves **33a**, **33b** are also inclined.

In the example shown in FIG. 6C, the second groove **33b** is located closer to the end than the first groove **33a**, similar to the example shown in FIG. 6A. Further, a groove **33c** extending from the first groove **33a** to the second groove **33b** is formed on a surface of the connecting portion **32**.

In the example shown in FIG. 6D, the second groove **33b** is located closer to the end than the first groove **33a**, similar to the example shown in FIG. 6A. In this case, however, the width of the first and second grooves **33a**, **33b** is reduced toward its bottom.

In the example shown in FIG. 6E, the first connecting portion **32a** can be tapered such that the first connecting surface **32a1** is inclined relative to an imaginary line **L2**



## 11

extending along the second connecting surface **32b1**. The first connecting surface **32a1** is inclined to separate from the line **L2**.

In the example shown in FIG. 6F, the first connecting surface **32a1** is recessed from the imaginary line **L2** extending along the second connecting surface **32b1**, such that the first connecting surface **32a1** is separated from the circuit board **10**.

When the connecting portions **32** shown in FIGS. 6A to 6F are bent, the first connecting surface **32a1** is inclined relative to or separated from the plane on which the second connecting surfaces **32b1** are included. As such, the reinforcing tabs **30** that can enhance connection between the second connecting surfaces **32b1** and the circuit board **10** are provided.

Also, the extending portions **34** of the reinforcing tab **30** can be modified. For example, as shown in FIG. 7A, the extending portions **34** are formed with narrowed portions (e.g., recesses) **300** at which the extending portions **34** are narrowed, as heat transfer restricting portions. For example, the width of the extending portions **34** at the narrowed portions **300** is smaller than the width of the fixing portion **31** and the connecting portions **32**.

Since the extending portions **34** have the narrowed portion **300**, the heat of the solder and the connecting portion **32** is restricted from being transferred toward the fixing portion **31** during the reflow soldering for soldering the reinforcing tab **30** with the circuit board **10**. Thus, in the reflow soldering, the solder is easily melted and hence the reinforcing tab **30** is properly soldered with the circuit board **10**. Here, the narrowed portions **300** can be formed at the same time as punching the base member.

Further, the shape of the reinforcing tab **30** can be modified. FIGS. 8A and 8B show another example of the reinforcing tab **30**. As shown in FIG. 8A, the second connecting portions **32b1** extend on both sides of each extending portion **34** substantially perpendicular to the extending portion **34**, and the first connecting portions **32a1** extend from the second connecting portions **32b1** through the bent portions **33**. Thus, each connecting portion **32** has a substantially U-shape when viewed from the bottom of the reinforcing tab **30** as shown in FIG. 8B.

In this case, the connecting area between the reinforcing tab **30** and the circuit board **10** increases. As such, the connection between the reinforcing tab **30** and the circuit board **10** improves, and hence the connector **20** is further securely connected to the circuit board **10** through the reinforcing tab **30**.

The reinforcing tab **30** shown in FIGS. 8A and 8B can be further modified as shown in FIGS. 9A and 9B. The first connecting portion **32a** of each connecting portion **32** can be bent in different directions. Namely, the bending directions of the first connecting portions **32a** are changed appropriately in view of a shape of the connector **20**, arrangement of the electronic components mounted on the circuit board **10**, and the like. Therefore, the reinforcing tab **30** is effectively arranged on the circuit board **10**.

Also, even in the case in which each connecting portion **32** has one first connecting portion **32a**, the first connecting portions **32a1** of the reinforcing tab **30** can be bent in different direction. For example, in the example shown in FIGS. 2A and 2B, the first connecting portions **32a1** can be bent in opposite directions.

In the above discussion, each connecting portion **32** has at least one bent portion **33** and the first groove **33a** at the end of the bent portion **33**, the end facing the circuit board **10**. However, the reinforcing tab **30** is not limited to the above.

## 12

For example, as shown in FIG. 7B, the connecting portion **32** has at least one bent portion **33** and the end of the bent portion **33** can be substantially coplanar with the second connecting surface **32a1**, **32b1**, instead of having the first groove **33a**. To make such a reinforcing tab **30**, first, the base member including the tab fixing portion **31**, the extending portions **34** and the connecting portions **32** is formed by punching from a metallic plate made of copper such as brass. Then, each of the connecting portions **32** is bent at least at a part so that the first and second connecting surfaces **32a1**, **32b1** are formed. Then, the end surface of the connecting portion **32**, which is to be connected to the circuit board **10**, is flattened such as by shaving or trimming.

Thus, the end surface **33d** of the bent portion **33** is coplanar with the first and second connecting surfaces **32a1**, **32b1**. As such, the reinforcing tab **30** without having the projection or expansion at the end of the bent portion **33** is produced. Accordingly, the connection between the reinforcing tab **30** and the circuit board **10** improves.

In the above embodiment, solder as the joining material is applied to surfaces of the lands **11**, **12**, and the terminals **22** and the reinforcing tabs **30** are soldered to the lands **11**, **12** of the circuit board **10** in a reflow oven. Therefore, in addition to the above discussed structure, a positioning projection as disclosed in Japanese Unexamined Patent Publication No. 11-317265 may be provided. For example, as shown in FIG. 7C, the connecting portion **32** has a positioning projection that projects from the connecting surface and is received in the reinforcing land **12** and the circuit board **10**. In this structure, the reinforcing tab **30** is effectively positioned relative to the circuit board **10**. Further, this structure provides an effect of reducing separation of the soldered portion between the reinforcing land **12** and the connecting portion **32**. As such, the connecting surface is effectively soldered to the reinforcing land **12**.

The shape of the reinforcing tab **30** is not particularly limited to the illustrated shapes, but may have another shape. For example, the reinforcing tab **30** may have one extending portion **34** and one connecting portion **32** at the end of the extending portion **34**. Further, the above discussed and illustrated examples may be employed with various combinations.

As discussed in the above, the connection between the connector **20** and the circuit board **10** is improved by the reinforcing tab **30**. When the circuit board **10** mounting the connector **20** is employed in the electronic device for a vehicle, it generally receives stress due to heat. Even in such a condition, the connection between the connector **20** and the circuit board **10** is effectively reinforced by the reinforcing tab **30**.

The example embodiments of the present invention are described above. However, the present invention is not limited to the above example embodiment, but may be implemented in other ways without departing from the spirit of the invention.

What is claimed is:

1. A reinforcing tab that reinforces a connection between a circuit board and a connector surface-mounted to the circuit board, the connector including a housing and terminals, the reinforcing tab being made from a metal plate, and comprising:

- a fixing wall to be fixed to the housing; and
- a connecting wall extending from the fixing wall and defining a connecting surface along an edge of the connecting wall connected to the circuit board, wherein the connecting wall includes a first connecting portion, a second connecting portion and a bent portion, the

## 13

second connecting portion extending from the fixing wall and the first connecting portion extending from the second connecting portion through the bent portion such that the first connecting portion is angled relative to the second connecting portion, 5

the first connecting portion and the second connecting portion respectively define a first connecting surface and a second connecting surface as portions of the connecting surface at ends thereof, and

a first recess is formed within the connecting surface at a location corresponding to the bent portion as a projection restricting recess that restricts the connecting wall from forming a projection that extends beyond the connecting surface. 10

2. The reinforcing tab according to claim 1, wherein the first recess is in a form of groove and extends in a direction in which a wall thickness of the connecting wall is measured. 15

3. The reinforcing tab according to claim 1, wherein the first connecting surface of the first connecting portion is spaced from a plane that is defined along the second connecting surface of the second connecting portion. 20

4. The reinforcing tab according to claim 3, wherein the first connecting surface is inclined relative to the plane such that a space increases with a distance from the bent portion. 25

5. The reinforcing tab according to claim 1, wherein the connecting wall defines a second recess on an end surface, which is on a side opposite to the first and second connecting surfaces, at a position corresponding to the bend portion. 30

6. The reinforcing tab according to claim 5, wherein the second recess defines a width that is greater than a width of the first recess.

7. The reinforcing tab according to claim 5, wherein the first recess and the second recess are in the form a first groove and a second groove respectively, and the first groove and the second groove are at different positions with respect to the longitudinal direction on the connecting wall. 40

8. The reinforcing tab according to claim 7, wherein the second groove is located closer to the end of the connecting wall than the first groove.

9. The reinforcing tab according to claim 8, wherein the second groove and the first groove are inclined along an imaginary line, passing through the second groove and the first groove and inclined with respect to a direction perpendicular to the longitudinal direction of the connecting wall, such that sidewalls and bottom walls of both the second groove and the first groove are inclined relative to the imaginary line. 50

10. The reinforcing tab according to claim 8, wherein the width of both the second groove and the first groove is reduced toward the bottom of each groove. 55

11. The reinforcing tab according to claim 1, wherein the connecting wall includes a heat transfer restricting portion at which a width of the connecting wall is reduced for reducing heat transfer from the connecting wall toward the fixing wall. 60

12. A connecting structure comprising:  
the reinforcing tab according to claim 1;  
a connector including a housing and terminals disposed to the housing; and  
a circuit board having first lands for the terminals, a second land for the reinforcing tab, and a joining material disposed on surfaces of the first and second lands, wherein

## 14

the connector is mounted to the circuit board, and the terminals are connected to the first lands by the joining material,  
the fixing wall of the reinforcing tab is fixed to the housing, and the connecting surface of the connecting wall is connected to the second land by the joining material.

13. The structure according to claim 12, wherein the reinforcing tab is fixed in a condition that the first connecting surface is inclined relative to the surface of the second land.

14. An electronic device for a vehicle, comprising:  
a circuit board having first lands and a second land;  
a connector mounted on the circuit board, the connector including a housing and terminals disposed in the housing, the terminals connected to the first lands with a joining material disposed on surfaces of the first lands; and  
the reinforcing tab according to claim 1, wherein the fixing portion of the reinforcing tab is fixed to the housing, and  
the connecting wall is connected to the second land with a joining material disposed on a surface of the second land.

15. The reinforcing tab according to claim 1, wherein the connecting wall further includes a positioning projection that projects from the connecting surface to be positioned relative to the circuit board.

16. The reinforcing tab according to claim 1, wherein the first connecting portion extends from the second connecting portion through the bent portion such the connecting wall is substantially L-shaped when viewed from a plan view.

17. The reinforcing tab according to claim 1, further comprising:  
a second connecting wall extending from the fixing wall, and separated from the connecting wall by the fixing wall, the second connecting wall defining an opposite connecting surface along an edge of the second connecting wall connected to the circuit board, wherein the second connecting wall includes a third connecting portion, a fourth connecting portion and a second bent portion, the fourth connecting portion extending from the fixing wall and the third connecting portion extending from the fourth connecting portion through the second bent portion such that the third connecting portion is angled relative to the fourth connecting portion,  
the third connecting portion and the fourth connecting portion respectively define a third connecting surface and a fourth connecting surface as portions of the opposite connecting surface at ends thereof,  
a third recess is formed within the opposite connecting surface at a location corresponding to the second bent portion as a projection restricting recess that restricts the second connecting wall from forming a projection that extends beyond the opposite connecting surface, and  
the reinforcing tab has a general U-shape when viewed along a longitudinal direction of the housing.

18. The reinforcing tab according to claim 17, wherein the first connecting portion extends from the second connecting portion through the bent portion such that the connecting wall is substantially L-shaped when viewed from a plan view,  
the third connecting portion extends from the fourth connecting portion through the second bent portion such

## 15

that the opposite connecting wall is substantially L-shaped when viewed from a plan view, and the reinforcing tab has a general U-shape when viewed either upwardly, from below the circuit board or from a plan view.

19. The reinforcing tab according to claim 17, wherein the first connecting portion extends from the second connecting portion in a perpendicular direction from the fixing wall,

the third connecting portion extends from the fourth connecting portion in a perpendicular direction from the fixing wall, and

the reinforcing tab is substantially L-shaped when viewed from either side of the reinforcing tab.

20. The reinforcing tab according to claim 1, wherein the first connecting portion extends from the second connecting portion in a perpendicular direction from the fixing wall such that the reinforcing tab is substantially L-shaped when viewed from a side of the reinforcing tab.

21. The reinforcing tab according to claim 1, wherein the first recess is in a form of groove, and the groove has a trapezoidal shape when viewed from the bottom of the reinforcing tab.

22. A reinforcing tab that reinforces a connection between a circuit board and a connector mounted on the circuit board, the connector including a housing and terminals, the reinforcing tab being made from a metal plate, and comprising:

a fixing portion to be fixed to the housing; and

a connecting portion, extending from the fixing portion, having a wall surface as a non-contacting surface to the circuit board and a connecting surface configured as an edge connected to the circuit board, wherein

the connecting portion includes a bent portion at which the connecting portion is bent by bending the wall surface, and

a recess portion is formed as a projection restricting recess at a location, defined by the wall surface and the connecting surface, in the bent portion, at which the connecting surface is notched, that restricts the connecting portion from forming a projection that extends beyond the connecting surface.

23. A reinforcing tab made from a metal plate having an edge surface therearound, the reinforcing tab reinforcing a connection between a circuit board and a housing of a connector surface-mounted to the circuit board, the reinforcing tab bent to form a reinforcing section, the reinforcing tab comprising:

## 16

a fixing wall to be fixed to the housing; and

a connecting wall extending from the fixing wall and having a connecting surface including a portion of the edge surface associated with the reinforcing section, the connecting surface to be connected to the circuit board, wherein

the connecting wall includes a first connecting portion and a second connecting portion extending from the first connecting portion,

the second connecting portion is bent relative to the first connecting portion,

the connecting surface is defined along lower edges of the first and second connecting portions, and

the connecting wall includes a projection restricting recess within the connecting surface and at a location where the second connecting portion is bent relative to the first connecting portion, the projection restricting recess restricting metal that is displaced when the second connecting portion is bent relative to the first connecting portion, from forming a projection that extends beyond the connecting surface.

24. A reinforcing tab made of metal and having a flat shape, the reinforcing tab reinforcing a connection between a circuit board and a connector surface-mounted to the circuit board, the reinforcing tab comprising:

a fixing wall to be fixed to the connector; and

a connecting wall extending from the fixing wall, the connecting wall having a connecting surface along a lower edge portion thereof, at least a portion of the connecting surface to be connected to the circuit board, wherein:

the connecting wall includes a first connecting portion and a second connecting portion extending from the first connecting portion;

the second connecting portion is capable of being bent relative to the first connecting portion;

the connecting surface is defined along lower edges of the first and second connecting portions; and

the connecting wall includes a projection restricting recess at a location on the connecting surface where the second connecting portion is bent relative to the first connecting portion, the projection restricting recess restricting a portion of the reinforcing tab in the vicinity of the location where the second connecting portion is bent relative to the first portion from projecting beyond the connecting surface when the second connecting portion is bent relative to the first connecting portion.

\* \* \* \* \*