

US007560827B2

(12) **United States Patent**
Jacas-Miret et al.

(10) **Patent No.:** **US 7,560,827 B2**
(45) **Date of Patent:** **Jul. 14, 2009**

(54) **REMOVABLE SEAT SENSING SYSTEM**

(75) Inventors: **Josep Jacas-Miret**, Valls (ES); **Alberto Garcia-Briz**, Valls (ES)

(73) Assignee: **Lear Corporation**, Southfield, MI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 304 days.

(21) Appl. No.: **11/554,714**

(22) Filed: **Oct. 31, 2006**

(65) **Prior Publication Data**

US 2008/0100980 A1 May 1, 2008

(51) **Int. Cl.**
B60L 1/00 (2006.01)

(52) **U.S. Cl.** **307/9.1**

(58) **Field of Classification Search** **307/9.1**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,334,428 A	6/1982	Fima et al.
4,578,992 A	4/1986	Galasko et al.
5,515,933 A	5/1996	Meyer et al.
5,610,856 A	3/1997	Yoshizumi et al.
5,618,056 A	4/1997	Schoos et al.
5,696,409 A	12/1997	Handman et al.
5,804,887 A	9/1998	Holzappel et al.
5,838,233 A	11/1998	Hawes et al.
5,851,026 A	12/1998	Schoos et al.
5,887,894 A	3/1999	Castagner et al.
5,890,779 A	4/1999	Blackburn et al.
5,970,587 A	10/1999	Knox
6,008,547 A	12/1999	Dobler et al.

6,278,347 B1	8/2001	Hofelsauer
6,362,732 B1	3/2002	Konchin et al.
6,400,259 B1	6/2002	Bourcart et al.
6,424,055 B1	7/2002	Hambsch et al.
6,485,080 B2	11/2002	Hansen et al.
6,772,056 B2	8/2004	Mattes et al.
6,800,958 B1	10/2004	Baer et al.
6,856,244 B2	2/2005	Jung et al.
6,868,734 B2	3/2005	Jakoby et al.
6,882,162 B2	4/2005	Schirmer et al.
7,170,192 B2	1/2007	Kazmierczak
7,271,501 B2	9/2007	Dukart et al.
2003/0066702 A1	4/2003	Jung et al.
2004/0008036 A1	1/2004	Schirmer et al.
2005/0150705 A1	7/2005	Vincent et al.

(Continued)

FOREIGN PATENT DOCUMENTS

AU 2003217092 A1 9/2003

(Continued)

OTHER PUBLICATIONS


Great Britain Search and Examination Report for corresponding Application No. GB0720774.9, mailed Feb. 25, 2008, 7 pages.

Primary Examiner—Robert L. DeBeradinis
(74) *Attorney, Agent, or Firm*—Brooks Kushman P.C.

(57) **ABSTRACT**

The present invention relates to removable seating systems of the type wherein all or part of a seat may be removed or otherwise disengaged from a secure connection location, such as but not limited to vehicle seats that may be removed or disengage for folding from a vehicle mounted seat frame assembly. The system may include coupling circuits to facilitate assess states of a switch included on the removable seat.

20 Claims, 3 Drawing Sheets



US 7,560,827 B2

Page 2

U.S. PATENT DOCUMENTS

2005/0236899 A1 10/2005 Kazmierczak
2007/0070951 A1 3/2007 Ocket et al.
2007/0090967 A1 4/2007 Zuccotti et al.
2007/0102999 A1* 5/2007 Darraba 307/10.1

FOREIGN PATENT DOCUMENTS

CN 1816464 A 8/2006
DE 40006885 A1 10/1990
DE 19743313 C1 12/1998
DE 19938281 T1 5/2001
DE 10037260 A1 3/2002
DE 10164068 A1 4/2003
DE 10239754 C1 10/2003
DE 10245783 4/2004
EP 1019263 B1 11/2001
EP 1549530 B1 8/2006
EP 0819072 B2 7/2007
EP 1808339 A1 7/2007
EP 1622790 B1 2/2008
FR 2758502 A1 7/1998
FR 2884185 A1 10/2006
FR 2888538 A1 1/2007
FR 2889341 A1 2/2007
FR 2893289 A1 5/2007

FR 2899538 A1 10/2007
GB 1301359 12/1972
GB 2195183 A 3/1988
GB 2299550 A 10/1996
GB 2337335 A 11/1999
GB 2338262 A 12/1999
GB 2383879 A 7/2003
GB 2385630 A 8/2003
GB 2401467 A 11/2004
GB 2410977 A 8/2005
GB 2401467 B 1/2006
JP 2006526529 A 11/2006
KR 20060009919 A 2/2006
WO 9631370 A1 10/1996
WO 9916637 A1 4/1999
WO 9963851 A1 12/1999
WO 03024749 A1 3/2003
WO 03070530 A1 8/2003
WO 2004032088 A1 4/2004
WO 2004098943 A1 11/2004
WO 2006059020 A1 6/2006
WO 2006108954 A2 10/2006
WO 2007007009 A2 1/2007
WO 2007113632 A3 10/2007

* cited by examiner




Fig-1




Fig-2




Fig-3




Fig-4




Fig-5




Fig-6




Fig-7

REMOVABLE SEAT SENSING SYSTEM

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to removable seating systems of the type wherein all or part of a seat may be removed or otherwise disengaged from a secure connection location, such as but not limited to vehicle seats that may be removed or disengage for folding from a vehicle mounted seat frame assembly.

2. Background Art

The present invention relates to removable seating systems of the type wherein all or part of a seat may be removed or otherwise disengaged from a secure connection location, such as but not limited to vehicle seats that may be removed or disengage for folding from a vehicle mounted seat frame assembly. Such systems may include removable, movable or foldable (hide able) seat bottoms and backs.

The need for monitoring some variables in the seat (seat-belt buckle, occupancy sensor, seat anchoring to body platform . . .) may require a logical link (and even a power connection) between seat and vehicle chassis. However, the use of physical connection for an electric circuit is not recommended due to possible quality problems appearing from the limited mating-life of connectors that would lead to malfunction after a few assemblies and disassemblies of the seats.

Furthermore, the need for manual mating of these connectors transfers the responsibility to the end user (driver or passenger), which may not be desired by the OEM. Some self-aligning connectors have been developed to avoid user participation, but these self-matching devices may still have the problem of the limited number of mating—un-mating actions.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is pointed out with particularity in the appended claims. However, other features of the present invention will become more apparent and the present invention will be best understood by referring to the following detailed description in conjunction with the accompanying drawings in which:

FIG. 1 illustrates a seating system in accordance with one non-limiting aspect of the present invention;

FIG. 2 illustrates a seat coupling circuit in accordance with one non-limiting aspect of the present invention;

FIG. 3 illustrates a seat coupling circuit in accordance with one non-limiting aspect of the present invention;

FIG. 4 illustrates coupling between circuits in accordance with one non-limiting aspect of the present invention;

FIG. 5 illustrates a graph of signal variations associated with resonance between coupling circuits;

FIG. 6 illustrates a voltage component of the signal variations in accordance with one non-limiting aspect of the present invention; and

FIG. 7 illustrates a comparator in accordance with one non-limiting aspect of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

FIG. 1 illustrates a seating system **10** in accordance with one non-limiting aspect of the present invention. The system **10** may relate to vehicle or non-vehicle systems wherein a seating system includes a removable seat or seat having a removable portion (not shown) such that the removable por-

tion may be removed or otherwise disengaged from a support element or other element characterized as being a non-removable seat portion, such as but not limited to an element associated with supporting the removable seat.

The system **10** generally relates to facilitating wireless communication between the removable seat and non-removable seat portion. For exemplary purposes only and without intending to limit the scope and contemplation of the present invention, the system is described with respect to a vehicle having a removable seat and vehicle chassis used to support and/or electrically communication with the seat so as to facilitate electrical communications between the removable and non-removable portions. The present invention fully contemplates its use in any number of environments and is not intended to be limited to the foregoing going.

The system **10** illustrated in FIG. 1 includes a number of switches **12-16** associated with one or more removable seats and a fixed controller **18** mounted to a vehicle floor or other element in the vehicle. The controller **18** may be configured to determine an activation state of the switches **12-16** as a function of an electrical coupling between seat coupling circuits **24-28** associated with the switches **12-16** and corresponding vehicle coupling circuits **32-36** associated with the controller **18**.

As described below in more detail, electrical transmission between the coupled circuits **24-36** may be used to sense and/or otherwise assess various seating parameters of the corresponding seat. The electric transmission may be limited to resonance based transmission commonly associated with a transformer, tuned inductance, or other similar arrangement. Optionally, the communication may relate only to resonant based influences without the communication of data or other information.

The switches **12-16** may be associated with any number of sensors or other features included on one or more seats. For example, the switches **12-16** may be associated with belt buckle locks commonly used to lock a seat belt associated with restraining an seat occupant within a vehicle seat. The switches **12-16** may be binary switches having open and closed states such that the open state corresponds with the seat belt being unlocked and the closed state corresponds with the seat being locked.

The controller **18** may assess whether the switches **12-16** are opened or closed as a function of the coupling between the seat and vehicle coupling circuits **24-36**. This information may then be communicated to other vehicle systems. FIG. 1 illustrate an airbag control module **40** being in communication with the controller **18**. The airbag control module **40** may be configured to control airbag deployment as a function of whether the seat belts are buckled or unbuckled, such as but not limited to preventing airbag deployment for seats having unbuckled seat belts.

Of course, the present invention is not limited to controlling airbag deployment as a function switch state. The coupling signals may be used to facilitate any number of operations. For example, the switch state may be used to facilitate controlling displays and other information to the passenger or elsewhere in the vehicle, such as but not limited to generating a seat belt unlock warning or activating an seat belt unlocked indicator.

FIG. 2 illustrates the seat coupling circuit **24** in accordance with one non-limiting aspect of the present invention. The circuit **24** may include an inductor **42** in series with a capacitor **44** and the switch. The circuit **24** provides resonance when the inductor **42** is exposed to a magnetic field and the switch **12** is closed. The circuit **24** fails to provide resonance when the switch **12** is open, regardless of the presence of a magnetic

3

field. In this manner, the circuit **24** may be characterized as providing binary resonance operation in so far as the circuit provides resonance or no resonance at all, i.e., it has as single resonance. In this manner, the circuit **24** may be used to provide resonance when the switch **12** is closed and no resonance with the switch **12** is open.

FIG. **3** illustrates the seat coupling circuit **24** in accordance with one non-limiting aspect of the present invention. The circuit **24** may include the inductor **42** in parallel with the capacitor **44** and in series with the switch **12**. The circuit **24** provides resonance when the inductor **42** is exposed to a magnetic field and the switch **12** is open. The circuit **24** fails to provide resonance when the switch **12** is closed, regardless of the presence of a magnetic field. In this manner, the circuit **24** may be characterized as providing binary resonance operation in so far as the circuit **24** provides resonance or no resonance at all, i.e., it has as single resonance. In this manner, the circuit **24** may be used to provide resonance when the switch **12** is open and no resonance with the switch **12** is closed.

FIG. **4** illustrates one of the vehicle coupling circuits **32** being coupled with one of the seat coupling circuits **24** in accordance with one non-limiting aspect of the present invention. The vehicle coupling circuit **32** may include a signal generator **50** and an inductor **52**. The signal generator **50** may operate in conjunction with the inductor **52** to generate the magnetic field associated with coupling the inductor **52** on the vehicle coupling circuit **32** with the inductor **42** of the seat coupling circuit **24**, which is shown for exemplary purposes to correspond with the seat coupling circuit shown in FIG. **3**.

The controller **18** may be configured to control the signal generated by the signal generator **50** and to perform other operations related thereto. While only one coupling arrangement is shown in FIG. **4**, the controller **18** may be used to separately generate signals and monitor corresponding coupling between any number of pairs of vehicle and seat coupling circuits. This allows the present invention to monitor switch state for different types of switches on any number of seats with the vehicle.

FIG. **5** illustrates a graph **60** of signal variations associated with resonance between the seat **24** and vehicle coupling circuits **34**. The vertical axis corresponds with a voltage at the vehicle inductor **52** and a signal corresponds with the signal associated with the corresponding signal generator and time based variations therein. Condition A corresponds with the absence of resonance and Condition B corresponds with the present of resonance, i.e., coupling. This variation in amplitude may be used to assess switch state as the voltage across the vehicle inductor **52** drops when the circuits are coupled together, i.e., in the present of resonance.

FIG. **6** illustrates a graph **62** associated with the controller **18** converting the AC signal of FIG. **5** to a DC signal in accordance with one non-limiting aspect of the present invention. This conversion may be done with an inverter or other element (not shown) associated with the controller **18**. As shown, distinct voltage based variations occur between condition (no resonance) and condition B (no resonance). Optionally, the controller **18** may include a filter or other similar element to reduce noise and other variance in the signal prior to converting it to the illustrated DC signal.

FIG. **7** illustrates a comparator **64** of the controller **18** in accordance with one non-limiting aspect of the present invention. The comparator **68** may receive the DC signal of associated with the voltage variations at the vehicle inductor **52** (V_{ind}) for comparison to a reference voltage (V_{ref}). The comparison may be used to determine the state of the switch **12**, depending on the configuration of the seat coupling circuit **24**. For example, the seat coupling circuit **24** shown in FIG. **2** is in a closed state when the voltage is less than the reference voltage and in an open state when the voltage is greater than

4

the reference voltage. The seat coupling circuit **24** shown in FIG. **3** is in an open state when the voltage is less than the reference voltage and in a closed state when the voltage is greater than the reference voltage.

An output from the comparator **64** may be communicated to the airbag module **40** for use in controlling airbag deployment, as noted above. Likewise, the controller **18** or other vehicle element may use the output to perform any number of other operations, such as but not limited to generating the seat belt warning, etc. In this manner, the present invention is able to assess switch state and use this information to itself control and/or to facilitate controller other vehicle based systems

One non-limiting aspect of the present invention relates to determining switch state as a function voltage variations resulting from the coupling/resonance between two coupling circuits. In this manner, the analysis of the present invention may be advantageously performed without regard to the actual resonance frequency, without requiring multiple resonance frequencies for each state, and without requiring data to be communicated between the coupling circuits.

One non-limiting aspect of the present invention relates to an only-detection system, without any responsibility in the actuation of safety devices (for example, airbag systems). The related system may produce status signals to an external controller for that safety functions.

One non-limiting aspect of the present invention may be considered as a simplified system that produces a cost-effective system without the need of complex electronics, but at the same time without compromising the required system responses, as the proposed invention includes relatively fast reaction times.

One non-limiting aspect of the present invention relates to the use of active components on the vehicle side and passive units being installed on each seat having only transponders that will react to the external excitation signals. Active components in the vehicle side will generate an alternating signal for each seat, with an optional fixed frequency for all of them. Some other active components will be able to read the response from each separate seat, in order to produce the specific message to the external controller module. Detection may be achieved through a single resonant frequency, and thus it is not needed to differentiate between several frequencies or harmonics from a same frequency.

One non-limiting aspect of the present invention relates to a resonant circuit in the seat including an inductor, a mating capacitor (to create resonance at the desired frequency) and the switches to be detected. As a result, behavior should be expected from the system may include: requiring switches or sensors to be naturally closed in the static position (for example, belt not buckled, or occupancy sensor in low impedance); the active position may be considered as an open circuit (belt buckled, occupancy sensor in high impedance); since any of the switches connected in series will trigger the change of status, only two signals may be produced in the first embodiment, i.e., OK and NOT OK; basic response from the opening of the circuit may be the complete elimination of the resonance in the seat side, so that the coupling will disappear.

One non-limiting aspect of the present invention relates to an inductive coupling system to provide remote diagnostic on the status of one or several signals in one or several movable, removable or foldable (hide-able) seats of a motor vehicle, such as but not limited to within a vehicle having a number of independent seats, two or three (second row only) up to six (second and third rows of seats present) seats in a vehicle.

One non-limiting aspect of the present invention relates to a whole system consisting of main module and slave emitters on the vehicle side, and passive transponders on the seat side, which may optionally uses a single frequency for all seats that does not require the use of harmonic frequencies in its function.

5

One non-limiting aspect of the present invention relates to reporting the switch state to an external module, such as but not limited to detecting status of a seat belt buckle, detecting status of an occupancy sensor, and/or detecting status of a seat locking to the chassis platform, detecting status of a backrest mechanism locking.

One non-limiting aspect of the present invention relates to some parts of the present invention being realized with standard electronic assembly technologies, with metal-fret structures to eliminate the need of circuit boards, and/or with three-dimensional mould-interconnect device (MID) technologies to integrate the electronic components with the required plastic housing.

As required, detailed embodiments of the present invention are disclosed herein; however, it is to be understood that the disclosed embodiments are merely exemplary of the invention that may be embodied in various and alternative forms. The figures are not necessarily to scale, some features may be exaggerated or minimized to show details of particular components. Therefore, specific structural and functional details disclosed herein are not to be interpreted as limiting, but merely as a representative basis for the claims and/or as a representative basis for teaching one skilled in the art to variously employ the present invention.

While embodiments of the invention have been illustrated and described, it is not intended that these embodiments illustrate and describe all possible forms of the invention. Rather, the words used in the specification are words of description rather than limitation, and it is understood that various changes may be made without departing from the spirit and scope of the invention.

What is claimed is:

1. A removable vehicle seating system for wirelessly sensing activation of a switch included on a removable seat, the system comprising:

a first coupling circuit on the removable seat configured for resonating as a function of switch activation;

a second coupling circuit wirelessly coupled with the first coupling circuit; and

a voltage unit in communication with the second coupling circuit for assessing switch activation as a function of a voltage variation of the second coupling circuit resulting from resonance of the first coupling circuit.

2. The system of claim **1** wherein the voltage unit assess switch activation solely as a function of the voltage variation and without assessing a frequency of the first or second coupling circuits.

3. The system of claim **1** wherein the activation of the switch is characterized by the switch being in either one of an inactive state and an active state, and wherein the first coupling circuit resonates for one but not both of the states.

4. The system of claim **1** wherein the voltage variation only occurs if the first coupling circuit is resonating.

5. The system of claim **1** wherein the first coupling circuit includes an inductor connected in series with a capacitor and the seat switch such that the first coupling circuit only resonates when the seat switch is closed.

6. The system of claim **1** wherein the first coupling circuit includes an inductor connected in parallel with a capacitor and in series with the seat switch such that the first coupling circuit only resonates when the seat switch is open.

7. The system of claim **1** wherein the switch is a seat belt lock having a locked state and an unlocked state and the activation of the switch indicates whether the seat belt is in the unlocked or lock state.

6

8. The system of claim **7** further comprising an airbag control module in communication with the voltage sensing unit, wherein the air bag control module controls deployment of an air bag as a function of whether the seat belt is in the locked or unlocked state.

9. The system of claim **1** wherein the second coupling circuit radiates a magnetic field used to couple the first and second coupling circuits, wherein the magnetic field radiates at a fundamental frequency and without any harmonics.

10. A method for wirelessly sensing activation of a switch included on a removable seat, the method comprising:

monitoring a voltage variation of a second coupling circuit wirelessly coupled to a first coupling circuit included on the removable seat, the voltage variation being associated with resonance of the first coupling circuit, wherein the resonance of the first coupling circuit is dependent on an activation state of the switch; and

determining the activation state of the switch to corresponding with the switch being inactive or active based on the voltage variation.

11. The method of claim **10** further comprising determining the activation state of the switch solely as a function of the voltage variation and without determining a frequency of the first or second coupling circuits.

12. The method of claim **10** further comprising determining the activation state as a function of the first coupling circuit resonating for one but not both of the states.

13. The method of claim **10** further comprising determining the activation state of the switch based on the voltage variation only occurring when the first coupling circuit is resonating.

14. The method of claim **10** resonating the second coupling circuit without harmonics of a frequency at which the first coupling circuit resonates.

15. A vehicle seating system comprising:

a first coupling circuit on a removable seat, the seat having a seat switch operable between an active state and an inactive state, the first coupling circuit configured to resonate as a function of one but not both of the states;

a second coupling circuit wirelessly coupled with the first coupling circuit; and

a unit in communication with the second coupling circuit for assessing switch activation as a function of a voltage variation of the second coupling circuit resulting from resonance of the first coupling circuit.

16. The system of claim **15** wherein the unit assess switch activation solely as a function of the voltage variation and without assessing a frequency of the first or second coupling circuits.

17. The system of claim **15** wherein the voltage variation only occurs if the first coupling circuit is resonating.

18. The system of claim **15** wherein the switch is a seat belt lock having a locked state and an unlocked state and the activation of the switch indicates whether the seat belt is the unlocked or locked state.

19. The system of claim **18** further comprising an airbag control module in communication with the voltage sensing unit wherein the air bag control module controls deployment of an air bag as a function of whether the seat belt is in the locked or unlocked state.

20. The system of claim **15** wherein the first coupling resonance at a single frequency to a single resonance frequency of the second coupling circuit.