

US007625046B2

(12) **United States Patent**  
**Sanchez**

(10) **Patent No.:** **US 7,625,046 B2**  
(45) **Date of Patent:** **Dec. 1, 2009**

- (54) **TASK CHAIR**
- (75) Inventor: **Gary L. Sanchez**, Albuquerque, NM (US)
- (73) Assignee: **Garrex LLC**, Albuquerque, NM (US)
- (\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 380 days.

2,060,298 A	11/1936	Gailey
2,182,598 A	12/1939	Owler
2,304,349 A	12/1942	Fox
2,712,346 A	7/1955	Sprinkle
2,859,797 A	11/1958	Mitchelson
2,859,801 A	11/1958	Moore
3,015,148 A	1/1962	Haddad
3,041,109 A	6/1962	Eames et al.
3,059,971 A	10/1962	Becker
3,072,436 A	1/1963	Moore
3,107,991 A	10/1963	Taussig
3,112,987 A	12/1963	Griffiths et al.
3,115,678 A	12/1963	Keen et al.
3,124,092 A	3/1964	Raynes
3,124,328 A	3/1964	Kortsch
3,165,359 A	1/1965	Ashkouti
3,208,085 A	9/1965	Grimshaw
3,214,314 A	10/1965	Rowbottam
3,248,147 A	4/1966	Testa
3,273,877 A	9/1966	Geller et al.
3,298,743 A	1/1967	Albinson et al.
3,301,931 A	1/1967	Morin
3,314,721 A	4/1967	Smith

- (21) Appl. No.: **11/329,776**
- (22) Filed: **Jan. 10, 2006**

- (65) **Prior Publication Data**  
US 2007/0236066 A1 Oct. 11, 2007

**Related U.S. Application Data**

- (63) Continuation-in-part of application No. 11/032,594, filed on Jan. 10, 2005, now Pat. No. 7,396,082, which is a continuation-in-part of application No. 10/888,318, filed on Jul. 9, 2004, now abandoned, which is a continuation-in-part of application No. 10/401,481, filed on Mar. 28, 2003, now Pat. No. 7,040,703.
- (60) Provisional application No. 60/368,157, filed on Mar. 29, 2002, provisional application No. 60/485,775, filed on Jul. 9, 2003, provisional application No. 60/528,427, filed on Dec. 9, 2003.

- (51) **Int. Cl.**  
*A47C 7/46* (2006.01)
  - (52) **U.S. Cl.** ..... **297/353**; 297/217.2; 297/284.4
  - (58) **Field of Classification Search** ..... 297/217, 297/284.1, 284.4, 300.8, 302.5, 302.7, 353, 297/354.1, 354.12, 452.26, 452.29
- See application file for complete search history.

- (56) **References Cited**  
U.S. PATENT DOCUMENTS  
567,096 A 9/1896 Harvey et al.  
1,007,985 A 11/1911 Smith  
1,414,637 A 5/1922 Gell


(Continued)

*Primary Examiner*—Peter R. Brown  
(74) *Attorney, Agent, or Firm*—Luedeka, Neely & Graham, PC

(57) **ABSTRACT**

The present invention relates to task chairs that support the body of the user in healthy positions while the user performs various tasks over extended sitting periods and that provide independent and independently adjustable support to the lower and the upper back.

**18 Claims, 10 Drawing Sheets**



---

U.S. PATENT DOCUMENTS					
			4,595,237 A	6/1986	Nelsen
			4,601,516 A	7/1986	Klein
3,333,811 A	8/1967	Matthews	4,611,851 A	9/1986	Noyes et al.
3,337,267 A	8/1967	Rogers, Jr.	4,629,249 A	12/1986	Yamaguchi
3,399,926 A	9/1968	Hehn	4,629,525 A	12/1986	Rasmussen
3,431,022 A	3/1969	Poppe et al.	4,634,178 A	1/1987	Carney
3,434,181 A	3/1969	Benzies	4,638,679 A	1/1987	Tannenlaufer
3,436,048 A	4/1969	Greer	4,640,547 A	2/1987	Fromme
3,534,129 A	10/1970	Bartel	4,643,481 A	2/1987	Saloff et al.
3,544,163 A	12/1970	Krein	4,653,806 A	3/1987	Willi
3,589,967 A	6/1971	Shirakawa	4,666,121 A	5/1987	Choong et al.
3,601,446 A	8/1971	Persson	4,668,012 A	5/1987	Locher
3,624,814 A	11/1971	Borichevsky	4,670,072 A	6/1987	Pastor et al.
3,640,576 A	2/1972	Morrison et al.	4,691,961 A	9/1987	Rogers, Jr. et al.
3,758,356 A	9/1973	Hardy	4,703,974 A	11/1987	Brauning
3,807,147 A	4/1974	Schoonen	4,709,443 A	12/1987	Bigley
3,817,806 A	6/1974	Anderson et al.	4,709,962 A	12/1987	Steinmann
3,844,612 A	10/1974	Borggren et al.	4,720,142 A	1/1988	Holdredge et al.
3,864,265 A	2/1975	Markley	4,743,323 A	5/1988	Hettinga
3,880,463 A	4/1975	Shephard et al.	4,761,033 A	8/1988	Lanuzzi et al.
3,902,536 A	9/1975	Schmidt	4,763,950 A	8/1988	Tobler
3,915,775 A	10/1975	Davis	4,776,633 A	10/1988	Knoblock et al.
3,932,252 A	1/1976	Woods	4,779,925 A	10/1988	Heinzel
3,947,068 A	3/1976	Buhk	4,793,197 A	12/1988	Petrovsky
3,961,001 A	6/1976	Bethe	4,796,950 A	1/1989	Mrotz, III et al.
3,965,944 A	6/1976	Goff, Jr. et al.	4,796,955 A	1/1989	Williams
3,999,802 A	12/1976	Powers	4,803,118 A	2/1989	Sogi et al.
4,008,029 A	2/1977	Shokite	4,815,499 A	3/1989	Johnson
4,010,980 A	3/1977	Dubinsky	4,815,789 A	3/1989	Marcus
4,013,257 A	3/1977	Paquette	4,819,458 A	4/1989	Kavesh et al.
4,018,479 A	4/1977	Ball	4,826,249 A	5/1989	Bradbury
4,019,776 A	4/1977	Takamatsu	4,829,644 A	5/1989	Kondo et al.
4,036,524 A	7/1977	Takamatsu	4,830,697 A	5/1989	Aizawa
4,046,611 A	9/1977	Sanson	4,831,697 A	5/1989	Urai
4,047,756 A	9/1977	Ney	4,842,257 A	6/1989	Abu-Isa et al.
4,062,590 A	12/1977	Polsky et al.	4,846,230 A	7/1989	Mock et al.
4,067,249 A	1/1978	Deucher	4,852,228 A	8/1989	Zeilinger
4,087,224 A	5/1978	Moser	4,860,415 A	8/1989	Witzke
4,107,371 A	8/1978	Dean	4,861,106 A	8/1989	Sondergeld
4,108,416 A	8/1978	Nagase et al.	4,869,554 A	9/1989	Abu-Isa et al.
4,113,627 A	9/1978	Leason	4,885,827 A	12/1989	Williams
4,116,736 A	9/1978	Sanson et al.	4,889,384 A	12/1989	Sulzer
4,125,490 A	11/1978	Hettinga	4,889,385 A	12/1989	Chadwick et al.
4,149,919 A	4/1979	Lea et al.	4,892,254 A	1/1990	Schneider et al.
4,152,023 A	5/1979	Buhk	4,902,069 A	2/1990	Lehnert
4,161,504 A	7/1979	Baldini	4,904,430 A	2/1990	Yamada
4,174,245 A	11/1979	Martineau	4,906,045 A	3/1990	Hofman
4,189,880 A	2/1980	Ballin	4,927,698 A	5/1990	Jaco et al.
4,190,286 A	2/1980	Bentley	4,939,183 A	7/1990	Abu-Isa et al.
4,299,645 A	11/1981	Newsom	4,942,006 A	7/1990	Loren
4,302,048 A	11/1981	Yount	4,943,115 A	7/1990	Stucki
4,314,728 A	2/1982	Faiks	4,946,224 A	8/1990	Leib
4,336,220 A	6/1982	Takahashi	4,961,610 A	10/1990	Reeder et al.
4,339,488 A	7/1982	Brokmann	4,966,411 A	10/1990	Katagiri et al.
4,364,887 A	12/1982	Becht et al.	4,968,366 A	11/1990	Hukki et al.
4,373,692 A	2/1983	Knoblauch et al.	4,979,778 A	12/1990	Shields
4,375,301 A	3/1983	Pergler et al.	4,981,325 A	1/1991	Zacharkow
4,380,352 A	4/1983	Diffrient	4,981,326 A	1/1991	Heidmann
4,390,206 A	6/1983	Faiks et al.	4,986,948 A	1/1991	Komiya et al.
4,411,469 A	10/1983	Drabert et al.	4,988,145 A	1/1991	Engel
4,429,917 A	2/1984	Diffrient	5,000,515 A	3/1991	Deview
4,438,898 A	3/1984	Knoblauch et al.	5,009,827 A	4/1991	Abu-Isa et al.
4,465,435 A	8/1984	Copas	5,009,955 A	4/1991	Abu-Isa
4,469,738 A	9/1984	Himmelreich, Jr.	5,013,089 A	5/1991	Abu-Isa et al.
4,469,739 A	9/1984	Gretzinger et al.	5,015,034 A	5/1991	Kindig et al.
4,494,795 A	1/1985	Roossien et al.	5,029,940 A	7/1991	Golynsky et al.
4,502,729 A	3/1985	Locher	5,033,791 A	7/1991	Locher
4,522,444 A	6/1985	Pollock	5,070,915 A	12/1991	Kalin
4,529,247 A	7/1985	Stumpf et al.	5,071,189 A	12/1991	Kratz
4,545,614 A	10/1985	Abu-Isa et al.	5,096,652 A	3/1992	Uchiyama et al.
4,548,441 A	10/1985	Ogg	5,100,713 A	3/1992	Homma et al.
4,568,455 A	2/1986	Huber et al.	5,106,678 A	4/1992	Abu-Isa
4,575,150 A	3/1986	Smith	5,107,720 A	4/1992	Hatfield

# US 7,625,046 B2

Page 3

---

5,114,211 A	5/1992	Desanta	6,079,782 A	6/2000	Berg et al.
5,116,556 A	5/1992	Danton	6,089,664 A	7/2000	Yoshida
5,117,865 A	6/1992	Lee	6,095,611 A	8/2000	Bar et al.
5,135,694 A	8/1992	Akahane et al.	6,152,532 A	11/2000	Cosentino
5,143,422 A	9/1992	Althofer et al.	6,189,971 B1	2/2001	Witzig
5,153,049 A	10/1992	Groshens	6,193,313 B1	2/2001	Jonsson
5,228,747 A	7/1993	Greene	6,254,186 B1	7/2001	Falzon
5,240,308 A	8/1993	Goldstein et al.	6,334,650 B1	1/2002	Chien-Chuan
5,288,130 A	2/1994	Foster	6,334,651 B1	1/2002	Duan et al.
5,288,135 A	2/1994	Forcier et al.	6,338,530 B1	1/2002	Gowing
5,346,284 A *	9/1994	Dauphin ..... 297/411.36	6,352,307 B1	3/2002	Engman
5,407,248 A	4/1995	Jay et al.	6,386,634 B1	5/2002	Stumpf et al.
5,501,507 A	3/1996	Hummitzsch	6,431,648 B1	8/2002	Cosentino et al.
5,547,251 A	8/1996	Axelsson	6,447,061 B1	9/2002	Klingler
5,678,891 A	10/1997	O'Neill et al.	6,478,379 B1	11/2002	Ambasz
5,679,891 A	10/1997	Matsuno et al.	6,499,802 B2	12/2002	Drira
5,704,689 A	1/1998	Kim	6,565,155 B1 *	5/2003	Huang ..... 297/353
5,769,497 A *	6/1998	Tsai ..... 297/411.36			

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5






FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

## TASK CHAIR

## CROSS-REFERENCES TO RELATED APPLICATIONS

This application is a continuation-in-part of, and claims priority to, U.S. patent application Ser. No. 11/032,594, entitled "Task Chair", filed Jan. 10, 2005, which is a continuation-in-part application of: U.S. patent application Ser. No. 10/401,481, entitled "The Health Chair A Dynamically Balanced Task Chair", filed Mar. 28, 2003, which in turn claims the benefit of the filing of U.S. Provisional Patent Application Ser. No. 60/368,157; and also a continuation-in-part application of U.S. patent application Ser. No. 10/888,318, entitled "Task Chair", filed Jul. 9, 2004, which in turn claims the benefit of the filing of U.S. Provisional Patent Application Ser. No. 60/485,775, entitled "Task Chair", filed Jul. 9, 2003, and of U.S. Provisional Patent Application Ser. No. 60/528,427, entitled "Task Chair", filed Dec. 9, 2003; and also claims priority to PCT application Ser. No. US/04/21761, filed Jul. 9, 2004. The claims and specifications of said applications are incorporated herein by reference.

## BACKGROUND OF THE INVENTION

## 1. Field of the Invention (Technical Field)

The present invention relates to task chairs that support the body of the user in healthy positions while the user performs various tasks over extended sitting periods and that provide independent and independently adjustable support to the lower and the upper back.

## 2. Description of Related Art

Note that the following discussion refers to a number of publications by author(s) and year of publication, and that due to recent publication dates certain publications are not to be considered as prior art vis-a-vis the present invention. Discussion of such publications herein is given for more complete background and is not to be construed as an admission that such publications are prior art for patentability determination purposes.

Today, the average worker performs less physical activity and workers perform increasingly more of their work while in a seated position. It is known that if any part of person's anatomical function is impinged or static (i.e., remaining in a fixed position) for extended periods of time, posture and health are compromised. It has been determined that both physically active and physically inactive people suffer health problems caused by prolonged sitting. Those problems include lower back pain, muscle tension, numbness, acid reflux, carpal tunnel syndrome, and general fatigue.

Peter Escogue, a recognized expert in anatomical function, suggests these problems are posture related as well as inactivity related. Proper anatomical posture promotes proper anatomical function, i.e. the body functions best when operated from a proper position. Escogue further observes that over a period of time, many persons compromise correct posture causing problems in correct anatomical function.

Static, improper posture (e.g., while sitting in a static improper supporting chair) impairs good health. In the prior art, seats and chairs have been designed for comfort and for performing tasks. Task chairs were designed to incorporate pads, tilts, swivels, etc. Over time, health improvements were added to the combination of such items as family room recliners and workers' rigid elevating stools. Additions such as lumbar supports, adjustable armrests, seat backs with shapes designed for a general vertebrae contour, etc., were incorporated. However, today's combination task chairs offer few

features to accommodate multiple tasks while simultaneously giving adequate consideration to seating health.

Task chairs are typically configured to allow tilting of the seat and backrest as a unit or tilting of the backrest relative to the seat. In chairs having a backrest pivotally attached to a seat in a conventional manner, the movement of the backrest relative to the seat can create shear forces acting on the legs and back of the user. These shear forces tend to cause an uncomfortable pulling of the user's clothing. In an attempt to compensate for these shear forces, some office chairs include a backrest which pivots while the seat tilts, such as those disclosed in U.S. Pat. Nos. 2,859,801 (to Moore) and U.S. Pat. No. 4,429,917 (to Diffrient).

A related disadvantage of conventional task chairs is the configuration of the seat and/or backrest. Such seats typically include single or multi-density foam padding with a covering such as cloth, leather, mesh material or the like, such seating also tends to provide insufficient aeration since it acts as another layer of clothing and does not contain a spinal relief channel in the back support, and/or contain a coccyx relief in the horizontal seat. In addition, the structural requirements of such an attachment limits the shape and size of the frame and the membrane.

Typically, the seats of office task chairs are supported by a single stage telescoping column which provides for vertical adjustment of the seat. These columns include a gas spring mounted in a telescoping tube which is slidable within a base tube. In accordance with guidelines set by the American National Standards Institute (A.N.S.I.) and Business and Institutional Furniture Manufacturer's Association (B.I.F.M.A.), conventional office chairs in the United States are typically adjustable from a seat height of 16.0 inches from a floor to about 20.5 inches from a floor. Nevertheless, it is desirable to exceed this range of height adjustment to account for very small or large users and to accommodate the international population in general.

Typically, it is difficult to exceed this range of height adjustment with seats which tilt about the knees or ankles of the user. To offset the moments acting on single stage support columns, pneumatic manufacturers typically set a minimum overlapping distance of 2.95 inches (75 mm) between the tubes. Because such "ankle tilt" and "knee tilt" chairs have relatively large tilt housings, it is difficult to provide a lower minimum and higher maximum seat height while maintaining the required overlapping distance between the tubes. These types of tilting chairs also impart a greater moment on the tube since the pivot axis is offset from the support column. It is therefore desirable to provide a vertically adjustable support column having a greater overlapping distance to permit a greater stroke which decreases the minimum height and increases the maximum height of a chair seat.

Devices that incorporate a plurality of adjustable means have been disclosed in the prior art such as, for example, U.S. Pat. Nos. 6,478,379 (to Ambasz) and 6,189,971 (to Witzig). However, those devices do not allow for the independent adjustment of multiple, vertical backrest support arms.

Other patents disclose the use of various seat and back units incorporating means for altering the contour of the pads used on such seats such as, for example, U.S. Pat. Nos. 6,499,802 (to Drira) and 6,447,061 (to Klingler). However, these devices do not allow for the independent adjustment of multiple, vertical backrest support arms.

Although offering varying shapes, contours, masses and sizes, as well as a wide range of adjustment means i.e. pivotal, tilt, height, in/out, up/down, soft/firm, etc., all attempts at healthy task chairs in the prior art are burdened with an interdependent posterior design support which ultimately

restricts and compromises adjustability, dynamic support, and active seating. A chair that provides better posterior support and continuous animation, and better supports task functions, is thus needed.

#### BRIEF SUMMARY OF THE INVENTION

The present invention provides a chair with independently adjustable back supports to accommodate a variety of seating positions, user anatomies, and tasks.

Thus, an embodiment of the present invention provides an adjustable chair comprising a base, a seat comprising a seating surface, said seat connected to the base, a back support control assembly connected to the seat, at least two adjustable, generally vertical back support arms pivotally attached to the back support control assembly at a control assembly pivot point and each said back support arm independently adjustable about the respective control assembly pivot points, said back support arms adjustable to form an acute angle relative to the seating surface in a range of from an acute angle to an obtuse angle, and a vertically adjustable back support disposed on each back support arm, a first of the back supports for supporting a lower back of a seated person and a second of the back supports supporting an upper back of the seated person and disposed in a vertical plane generally aft of the first back support, wherein independently adjusting the back support arms about their respective control assembly pivot points moves the back support positions fore and aft.

The chair further comprises adjustment controls for adjusting a position of each back support arm, said adjustment controls accessible to a user while seated. The back supports are preferably pivotally attached to the back support arms so that the back supports may tilt irrespective of a position of the back support arms about the control assembly pivot points. The chair preferably further comprises a first adjuster connected to the first back support and further comprises a second adjuster connected to the second back support, said adjustment controls accessible to a user while seated. The first adjuster and the second adjuster preferably comprise adjustable settings for adjustment of a position of the back supports on each respective back support arm, said adjusters comprising calibrations visible to the user. The back support control assembly preferably comprises pneumatic components attached to the back support arms to move and fix a position of each back support arm. Preferably, the first adjuster faces toward a front of the chair, and the second adjuster faces toward a rear of the chair.

The pneumatic components preferably comprise a first pneumatic cylinder linked to the first back support arm and a second pneumatic cylinder linked to the second back support arm, each of the pneumatic cylinders independently linked to an adjuster control via an actuator cable.

Preferably, each back support comprises a spinal relief channel and the seating surface further comprises a coccyx pressure relief depression.

The chair may further comprise at least two adjustable forearm supports that are preferably tiltably adjustable, preferably adjustable in a direction toward, and away from, a center of the chair, preferably adjustable in height, and preferably rotatably adjustable.

In another embodiment, the chair comprises at least one adjustment alert to remind a user to make positional adjustments of the back support arms, the back supports, the forearm supports, the height of the seating surface, or a combination thereof.

Another embodiment provides a chair comprising a base, a seat comprising a seating surface, said seat connected to the

base, a back support control assembly connected to the seat, at least two independently adjustable, generally vertical back support arms attached to the back support control assembly, a vertically adjustable back support disposed on each back support arm, a first of said back supports for supporting a lower back of a seated person and a second of said back supports supporting an upper back of the seated person, a first adjusting component connected to the first back support for adjusting the first back support, and a second adjusting component connected to the second back support, wherein the adjusting components are accessible to a user while the user is seated. Preferably, the first adjuster faces toward a front of the chair, and the second adjuster faces toward a rear of the chair. In one embodiment, one of the adjusting components comprises an indicator comprising a letter, and/or at least one of the adjusting components comprises an indicator comprising a number. In another embodiment, at least one of the adjusting components comprises an indicator comprising a window showing a number, and another of the adjusting components comprises an indicator comprising a window showing a letter.

Another embodiment provides a chair comprising a base, a seat comprising a seating surface, said seat connected to the base, a back support control assembly connected to the seat, at least two independently adjustable, generally vertical back support arms attached to the back support control assembly, a vertically adjustable back support disposed on each back support arm, a first of said back supports for supporting a lower back of a seated person and a second of said back supports supporting an upper back of the seated person, and a first adjusting component and a second adjusting component for adjusting the first and second back supports, each said adjusting component comprising adjustable settings for adjustment of a position of the back supports on each respective back support arm, said adjusting components comprising calibration indicators visible to a user. In one embodiment, at least one of the calibration indicators comprises a letter and/or one of the calibration indicators comprises a number. In another embodiment, at least one of the calibration indicators comprises a window showing a number, and another of the calibration indicators comprises a window showing a letter.

A primary object of the present invention is to provide a task chair that promotes healthier seating by supporting proper anatomical posture and proper skeletal support and that supports multiple task functions over extended seating periods of time.

A primary advantage of the present invention is that it provides independent upper back support and lower back support that are easily and independently adjustable.

Another advantage of the present invention is that it provides anatomical support to the user while the user performs a wide range of tasks in a seated position.

Other objects, advantages and novel features, and further scope of applicability of the present invention will be set forth in part in the detailed description to follow, taken in conjunction with the accompanying drawings, and in part will become apparent to those skilled in the art upon examination of the following, or may be learned by practice of the invention. The objects and advantages of the invention may be

realized and attained by means of the instrumentalities and combinations particularly pointed out in the appended claims.

#### BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

The accompanying drawings, which are incorporated into, and form a part of, the specification, illustrate one or more embodiments of the present invention and, together with the description, serve to explain the principles of the invention. The drawings are only for the purpose of illustrating one or more preferred embodiments of the invention and are not to be construed as limiting the invention. In the drawings:

FIG. 1 is a side view of an embodiment of the present invention;

FIG. 2 is a side view of the embodiment of FIG. 1 showing back support arms in a slightly reclined position;

FIG. 3 is a side view of the embodiment of FIG. 1 showing one back support arm in a forward inclined position and one back support arm in a slightly reclined position;

FIG. 4 is a side view of the embodiment of FIG. 1 wherein both back support arms are in a forward inclined position;

FIG. 5 is a front view of the embodiment of FIG. 1;

FIG. 6 is a rear view of a back support arm showing an adjustment control and a position setting indicator for an upper back support;

FIG. 7 is a rear view of a lower back support and a position setting indicator;

FIG. 8 is a top perspective view of the back support control assembly of an embodiment of the present invention;

FIG. 9 is a side view of the back support control assembly of FIG. 8;

FIG. 10 is a side view of the back support control assembly of FIG. 8 with a covering removed to expose the lower ends of the back support arms; and

FIG. 11 is a top view of the back support control assembly of FIG. 8 with the back support arms removed.

#### DETAILED DESCRIPTION OF THE INVENTION

The present invention relates to chairs that support the body of the user in healthy positions while the user performs various tasks over extended sitting periods of time and that provide independent, and independently adjustable, support to the lower back and the upper back of the user.

As used in the specification and claims herein, the terms “a”, “an”, and “the” mean one or more.

Turning now to the figures, which describe a non-limiting embodiment of the present invention that is illustrative of the various embodiments within the scope of the present invention, FIG. 1 shows Chair 100 comprising seat 150 preferably attached via seat frame 136 to base 153, and preferably comprises pedestal 151 positioned between base 153 and seat frame 136. Pedestal 151 is preferably adjustable via any means known in the art, such as via telescoping means, and is preferably movably supported by rolling components (such as casters) 152 that are connected to base 153.

Chair 100 also comprises back supports 132, 133. Either, or both, of back supports 132, 133 are preferably adjustable to include adjustability in a vertical direction (i.e. height). Adjusting components or systems 124, 125 are preferably incorporated to make such adjustments. Preferably, adjusting component 124 is positioned to face rearward of chair 100, and adjusting component 125 is positioned to face toward the front of chair 100, although other positions are within the scope of the present invention. Preferably, adjusting compo-

nents 124 and 125 (as well as adjustment controls 126 and 128 described below) are accessible to the user while the user is seated and the user may adjust the settings and thus the configuration of component 124, 125 while being seated. Preferably, chair 100 comprises two back supports, but more may be utilized in other embodiments.

Back supports 132 and 133 are attached to vertical back support arms 134, 135, respectively, at least one of which is preferably adjustable. Back support arms 134 and 135 are preferably attached to seat frame 136 via back support control assembly 137.

The height of either back supports 132, 133 may be adjusted by moving them up and down along back support arms 134 and 135 (as shown in the figures) or, in another embodiment, by adjusting the length of brace support members 134 and 135.

Back support arms 134, 135 are independently and pivotally attached to back support control assembly 137 at pivot points 170, 171 as more fully described herein. Preferably, adjustment controls 126 and 128 (e.g., control buttons) are utilized, as discussed in more detail below, to adjust the angle of each back support arm 134, 135 in relation to seat surface 149 from the rear to the front of chair 100 in such a way that a broad range of angles, from acute to obtuse, is provided. These adjustments are also preferably accomplished while the user is seated by pressing adjustment controls 126, 128 linked to back support arms 134, 135 as described below. Thus, each back support arm 134 and 135 are independently adjustable by pivoting about pivot points 170 and 171, respectively, so that back supports 132 and 133 may be moved fore and aft to accommodate a variety of sitting positions, user anatomies, and user tasks. FIGS. 2-4 show some of the range of adjustability.

Also, back supports 132 and 133 preferably comprise pivoting points 190, 191 (shown in FIG. 6) about which back supports 132 and 133 may tilt to accommodate a user's anatomy as back support arms 134 and 135 are pivoted to movably adjust back supports 132 and 133 fore and aft. Thus, the overall fore and aft movement of back supports 132 and 133 throughout their movable range is in the form of an arc. By adjusting the height of back supports 132 and 133 via adjustment controls 126 and 128, the effect of the arcing movement in changing the height of back supports 132 and 133 can be minimized, buffered, or otherwise controlled.

In the preferred embodiment, back support arm 134, which is longer than back support arm 135, is disposed directly behind back support arm 135. This positioning of back support arms 134, 135 in such an orientation results not only in a more aesthetic appearance for chair 100, but also enables a user to straddle back support arms 134, 135 while sitting in chair 100 facing toward a rear of chair 100. Sitting while facing toward the rear of chair 100 enables the user to gain not only abdominal support from back support 133, but also to gain upper chest support from back support 132. Such support is often needed by users who engage in activities that require a substantial amount of time looking downward. For example dentists, jewelers, dental lab technicians, and computer wafer manufacturers would all benefit from anterior support.

Thus, chair 100 provides flexibility through adaptability. For example, as noted above, when the user requires anterior (forward) support, the seating can be reversed (i.e., the user can sit facing toward the rear of the chair) to accommodate forward tasks. As noted below, should the user require elbow and lower arm support, adjustable forearm support members 140, 141 are adjustable to support vertical and lateral task movements.



In another embodiment of the present invention, the positions of any or all of back supports **132** and **133** and back support arms **134** and **135** are calibrated to a user's desired settings. Thus, calibration indicators, such as window indicators **184**, **185**, for indicating the height of adjustable back support members **132**, **133** are provided. These would enable each user to quickly return the height of adjustable back support members **132** and **133** or the position of back support arms **134** and **135** to the user's desired setting. As an example, one person might prefer an indicator showing settings of "3" and "F" whereas another user might prefer "2" and "B" settings (a window with a setting of "3" is shown in FIG. 6, and a window with a setting of "F" is shown in FIG. 7). Numerous apparatuses known in the art can be utilized to achieve this objective. This allows quickly resetting the chair positions which is particularly useful in offices (e.g., medical or dental offices) where different persons move to different offices throughout the day. Another example may comprise one or more dials with an indicator (not shown) that point to a series of numbers (i.e. an apparatus similar to a volume knob). The apparatus can also be incorporated by disposing an indicator, such as window indicator **183** (shown in FIG. 1) at the side or back of holding component **137**, wherein one or more scales (not shown) may be displayed and affixed to each of brace support members **134**, **135**. Therefore, when brace support members **134**, **135** are moved, the scale would slide, thus showing a different numbered setting. Thus, it is understood that such indicators may comprise any of the means described herein or a combination of such means and may be located anywhere on chair **100**.

FIGS. 1-5 show adjustable forearm support **141** secured to seat **150** via forearm attachment member **143** which is provided with forearm support adjuster **145**. FIG. 5 shows corresponding forearm support **140**, forearm attachment member **142**, and forearm support adjuster **144** on the other side of chair **100**. Any means known in the art may be utilized to accomplish the adjustment of the height of forearm support members **140**, **141** such as, for example, using telescoping means to adjust the length of forearm attachment members **142**, **143**.

In one embodiment, when the user requires elbow and lower arm support, whether anterior or posterior, forearm supports **140**, **141** comprise adjustment flexibility to accommodate adjustments to the "tilt arm rest" from up to down, inwardly and outwardly, and to tilt downwardly from the posterior to anterior allowing an angled support. This capability is useful for such tasks as typing as it has been suggested that a proper, healthy typing position involves a relaxed upper arm and shoulder support at the elbow, while simultaneously allowing lower arm, wrist, and hand to be in straight alignment angled downwardly from the elbow. This typing posture helps prevent carpal tunnel syndrome. Forearm supports **140**, **141** are adjustable along all planes, including tilt, rotation, and in a direction toward and away from the center of chair **100**.

In the preferred embodiment, as shown in FIG. 5, adjustable back supports **132**, **133** comprise vertical indentations **111**, **113** (i.e., spinal relief channels) to relieve pressure that is applied against the spinal column of a user when the user reclines against back supports **132**, **133**. Indentations **111**, **113** may be of any size sufficient to relieve pressure to the spine of a user. In another embodiment, back supports **132**, **133** can each comprise two pads (not shown) connectedly spaced apart so that the space between them accommodates the immediate area of the spine to relieve pressure or remove pressure to the spine.

FIG. 5 also shows seat member **150** comprising indentation **122** to relieve pressure to the coccyx of a user that results when the user sits on seat member **150**. Indentation **122** may be of any size and shape including, but not limited to, rectangles or squares.

FIG. 8 shows a detailed view of an embodiment of back support control assembly **137**. A pair of actuator linkages **172** and **174**, which are linked to adjustment controls **126**, **128**, are used to adjust back support arms **134**, **135**. FIG. 9 shows the front/back orientation of back support arms **134** and **135**. FIG. 10 shows the bottom ends of back support arms **134** and **135** comprising interfaces **167** and **169** that connect to pneumatic gas cylinders **162**, **164** which are in turn connected to linkages **172** and **174**. Thus, in the embodiment shown in FIGS. 8-10, gas cylinders **162**, **164** are connected to different and offset interfaces **167** and **169** which comprise rod-like portions as better shown in FIG. 11. Preferably, as better shown in FIG. 10, cylinders **162**, **164** are connected to the bottom of interfaces **167**, **169** at the lowermost ends of back control arms **134**, **135** so that pivot points **170**, **171** are located above the points of attachment of cylinders **162**, **164** to interfaces **167**, **169**. This enables arms **134**, **135** to move at fore and aft angles as shown in FIGS. 1-4. Linkages **172** and **174** are connected to cylinders **162** and **164** and are in turn linked to adjuster controls **126**, **128** via actuator cables **175** (shown in FIG. 10) or the like. This enables any control mechanism or adjusting component, including actuator buttons **126**, **128** to be easily located in virtually any location, in addition/alternatively to those depicted in the figures.

It should be apparent that the adjustment of back support arms **134** and **135** and back supports **132** and **133** may be accomplished by any means known in the art. For example, adjustments may be made with dials, slide mechanisms, and the like to control the height, angle, and/or other properties of back support members **132**, **133**.

Also, as shown in the figures, adjustment mechanisms such as control mechanisms **175** and **176** may be incorporated to control characteristics of chair **100**, including, but not limited to, height, angle, tilt lock, and tilt tension of seat **150**.

Thus, the present invention provides for a system of variable, and variably timed, seating positions, the system termed herein "active seating" which allows for periodic adjustments to various seat supporting members, and which allows the user's body to remain active, uncompromised, and functioning properly. The antithesis of "active seating" is "static seating". Static seating is undesirable as it is detrimental to the health and posture of the user. Static seating is overcome through the use of the present invention.

To increase the benefits of the present invention and enhance "active seating", another embodiment includes the incorporation of various adjustment alert means into chair **100**, such as adjustment alert **180** as shown in FIG. 1, to alert a user that enough time has elapsed so that making an adjustment is advisable. Thus, a user can, without having to be too consciously engaged in the use of chair **100**, be assured of not remaining in a static position for too long. Adjustment alert **180**, sends an indicator signal such as, but not limited to, an audible alarm, to the user as a reminder to make modifications to the positions of the adjustable components of chair **100**. Thus, a user is reminded to change positions to enhance the posture, biomechanics, etc. of the user.

Thus, the present invention provides a series of independent bracing supports anywhere along the line of vertebrae from the sacrum to the cervix. Depending on the embodiment, two or more independently adjustable back support arms are attached to, and arise from, the seating frame, seat support, seat pedestal, or seat. One or more back supports

attach to these back support arms and each back support arm has flexible adjustments in order to accommodate individual user dimensions. This arrangement allows the user to participate in a wide range of tasks with optimum and healthy musculoskeletal support.

The ability to frequently reposition the support members described herein in order to effect periodic, slight anatomical movement of musculoskeletal, respiratory, nervous, digestive, and circulatory systems ensures that these body systems remain uncompromised and unimpinged. This periodic, slight repositioning of the various support members allows muscles to relax while redistributing anatomical pressure.

All elements described herein are preferably integrated to respond in concert to a myriad of user sizes and shapes and a wide variety of chair-based tasks with a healthy musculoskeletal support system.

#### EXAMPLE

A chair in accordance with the description provided herein was constructed with the following components:

1. A lower back support was attached to a lower back support arm, and an upper back support was attached to an upper back support arm.
2. The lower and upper back support arms were independently attached at respective pivot points to a back support control assembly which was in turn attached to a seat frame.
3. The upper back support arm was located directly behind the lower back support arm.
4. The lower and upper supports were adjustable up and down on the back support arms and could pivot on a plane parallel to the vertical axis of the back support arms.
5. The back support arms could be reclined forward or rearward.
6. The back supports and the back support arms were adjustable using adjusting components that in turn comprised window indicators to show the position settings of the back supports and back support arms.
7. The back support arms were adjustable using buttons linked via actuator linkages connected to pneumatic cylinders that were in turn connected to the lower ends of the back support arms.
8. The chair also comprised adjustable arm rests and an adjustable seat.
9. The back supports incorporated a vertical indentation for the relief of spinal pressure.
16. A base with casters was provided.

The preceding examples can be repeated with similar success by substituting the generically or specifically described components, mechanisms, materials, and/or operating conditions of this invention for those used in the preceding examples.

Although the invention has been described in detail with particular reference to these preferred embodiments, other embodiments can achieve the same results. Variations and modifications of the present invention will be obvious to those skilled in the art and it is intended to cover in the appended claims all such modifications and equivalents. The entire disclosures of all references, applications, patents, and publications cited above are hereby incorporated by reference.

What is claimed is:

1. An adjustable chair comprising:
  - a base;
  - a seat comprising a seating surface, said seat connected to said base;

a back support control assembly connected to said seat for adjusting the fore and aft position of at least two adjustable, generally vertical back support arms, each said back support arm pivotally attached to said back support control assembly at spaced apart control assembly pivot points such that the at least two back support arms pivot about different pivot point axes, and each said back support arm independently adjustable about its said respective control assembly pivot point axis, said back support arms adjustable in the fore and aft position to vary an angle with respect to said seating surface; and a back support disposed on each said back support arm, a first of said back supports for supporting a lower back of a seated person and a second of said back supports supporting an upper back of the seated person.

2. The chair of claim 1 further comprising adjustment controls for adjusting a position of each said back support arm, said adjustment controls accessible to a user while seated.

3. The chair of claim 1 wherein said back supports are attached to said back support arms so that said back supports pivot to accommodate a user's back contours as said back support arms pivot about said control assembly pivot points.

4. The chair of claim 1 further comprising a first adjusting component connected to said first back support for vertically adjusting said first back support and further comprising a second adjusting component connected to said second back support for vertically adjusting said second back support, said adjusting components accessible to a user while the user is seated.

5. The chair of claim 4 wherein said first adjusting component faces toward a front of said chair.

6. The chair of claim 4 wherein said second adjusting component faces toward a rear of said chair.

7. The chair of claim 4 wherein said first adjusting component and said second adjusting component comprise adjustable settings for adjustment of a position of said back supports on each respective back support arm, said adjusting components comprising calibrations visible to a user.

8. The chair of claim 1 wherein said back support control assembly comprises pneumatic components attached to said back support arms to move and fix a position of each back support arm.

9. The chair of claim 8 wherein said pneumatic components comprise a first pneumatic cylinder linked to said first back support arm and a second pneumatic cylinder linked to said second back support arm, each of said pneumatic cylinders independently linked to an adjustor control via an actuator cable.

10. The chair of claim 1 wherein each back support further comprises a spinal relief channel.

11. The chair of claim 1 wherein said seating surface further comprises a coccyx pressure relief depression.

12. The chair of claim 1 further comprising at least two adjustable forearm supports.

13. The chair of claim 1 further comprising at least one adjustment alert integrated into the adjustable chair to remind a user to make positional adjustments of said back support arms, said back supports, or both.

14. An adjustable chair comprising:

- a base;
- a seat comprising a seating surface, said seat connected to said base;
- a back support control assembly connected to said seat for adjusting the fore and aft position of at least two independently adjustable, generally vertical back support arms pivotally attached to said back support control

**11**

assembly at longitudinally spaced apart control assembly pivot axes, wherein the back support arms are longitudinally spaced apart at their points of attachment to the back support control assembly; and  
 a vertically adjustable back support disposed on each said  
 back support arm, a first of said back supports for supporting a lower back of a seated person and a second of said back supports for supporting an upper back of the seated person.  
**15.** The chair of claim **14**, further comprising a first adjusting component and a second adjusting component for adjusting said first and second back supports, each said adjusting component comprising adjustable settings for adjustment of a

**12**

position of said back supports on each respective back support arm, said adjusting components comprising calibration indicators visible to a user.

**16.** The chair of claim **15** wherein at least one of said calibration indicators comprises a letter.

**17.** The chair of claim **15** wherein at least one of said calibration indicators comprises a number.

**18.** The chair of claim **15** wherein at least one of said calibration indicators comprises a window showing a number, and another of said calibration indicators comprises a window showing a letter.

\* \* \* \* \*