



US007628791B2

(12) **United States Patent**  
**Garrison et al.**

(10) **Patent No.:** **US 7,628,791 B2**  
(45) **Date of Patent:** **Dec. 8, 2009**

(54) **SINGLE ACTION TISSUE SEALER**

2,305,156 A	12/1942	Grubel
2,632,661 A	3/1953	Cristofv
2,668,538 A	2/1954	Baker
2,796,065 A	6/1957	Kapp
3,459,187 A	8/1969	Pallotta
3,643,663 A	2/1972	Sutter

(75) Inventors: **David M. Garrison**, Longmont, CO (US); **Paul Hermes**, Guilford, CT (US); **Sean Dycus**, Broomfield, CO (US)

(73) Assignee: **Covidien AG**, Neuhausen am Rheinfall (CH)

(Continued)

**FOREIGN PATENT DOCUMENTS**

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 522 days.

CA 2104423 2/1994

(Continued)

**OTHER PUBLICATIONS**

(21) Appl. No.: **11/207,956**

(22) Filed: **Aug. 19, 2005**

Sigel et al. "The Mechanism of Blood Vessel Closure by High Frequency Electrocoagulation" Surgery Gynecology & Obstetrics, Oct. 1965 pp. 823-831.

(65) **Prior Publication Data**

(Continued)

US 2007/0043352 A1 Feb. 22, 2007

Primary Examiner—Lee S Cohen

(51) **Int. Cl.**

**A61B 18/14** (2006.01)

**A61B 17/32** (2006.01)

(57) **ABSTRACT**

(52) **U.S. Cl.** ..... **606/51**; 606/171

(58) **Field of Classification Search** ..... 606/45,

606/48, 51, 52, 171

See application file for complete search history.


An endoscopic bipolar forceps includes a housing and a shaft, the shaft having an end effector assembly at its distal end. The end effector assembly includes two jaw members for grasping tissue therebetween. The jaw members are adapted to connect to an electrosurgical energy source which enable them to conduct energy through the tissue to create a tissue seal. A drive assembly is disposed within the housing which moves the jaw members. A switch is disposed within the housing which activates the electrosurgical energy. A knife assembly is included which is advanceable to cut tissue held between the jaw members. A movable handle is connected to the housing. Continual actuation of the movable handle engages the drive assembly to move the jaw members, engages the switch to activate the electrosurgical energy source to seal the tissue, and advances the knife assembly the cut the tissue disposed between the jaw members.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

371,664 A	10/1887	Brannan et al.
702,472 A	6/1902	Pignolet
728,883 A	5/1903	Downes
1,586,645 A	6/1926	Bierman
1,813,902 A	7/1931	Bovie
2,002,594 A	5/1935	Wappler et al.
2,011,169 A	8/1935	Wappler
2,031,682 A	2/1936	Wappler et al.
2,176,479 A	10/1939	Willis
2,279,753 A	4/1942	Knopp

**14 Claims, 16 Drawing Sheets**



U.S. PATENT DOCUMENTS					
			5,261,918 A	11/1993	Phillips et al.
3,651,811 A	3/1972	Hildebrandt et al.	5,275,615 A	1/1994	Rose
3,720,896 A	3/1973	Beierlein	5,277,201 A	1/1994	Stern
3,862,630 A	1/1975	Balamuth	5,282,799 A	2/1994	Rydell
3,863,339 A	2/1975	Reaney et al.	5,290,286 A	3/1994	Parins
3,866,610 A	2/1975	Kletschka	5,304,203 A	4/1994	El-Mallawany et al.
3,911,766 A	10/1975	Fridolph et al.	5,308,357 A	5/1994	Lichtman
3,920,021 A	11/1975	Hiltebrandt	5,314,445 A	5/1994	Degwitz et al.
3,921,641 A	11/1975	Hulka	5,318,589 A	6/1994	Lichtman
3,938,527 A	2/1976	Rioux et al.	5,324,289 A	6/1994	Eggers
3,952,749 A	4/1976	Fridolph et al.	5,326,806 A	7/1994	Yokoshima et al.
3,970,088 A	7/1976	Morrison	5,330,471 A	7/1994	Eggers
3,987,795 A	10/1976	Morrison	5,334,183 A	8/1994	Wuchinich
4,005,714 A	2/1977	Hiltebrandt	5,334,215 A	8/1994	Chen
4,041,952 A	8/1977	Morrison, Jr. et al.	5,336,220 A	8/1994	Ryan et al.
4,043,342 A	8/1977	Morrison, Jr.	5,336,221 A	8/1994	Anderson
4,074,718 A	2/1978	Morrison, Jr.	5,342,359 A	8/1994	Rydell
4,088,134 A	5/1978	Mazzariello	5,342,381 A	8/1994	Tidemand
4,112,950 A	9/1978	Pike	5,342,393 A	8/1994	Stack
4,127,222 A	11/1978	Adams	5,344,424 A	9/1994	Roberts et al.
4,128,099 A	12/1978	Bauer	5,352,222 A	10/1994	Rydell
4,165,746 A	8/1979	Burgin	5,354,271 A	10/1994	Voda
4,233,734 A	11/1980	Bies	5,356,408 A	10/1994	Rydell
4,300,564 A	11/1981	Furihata	5,366,477 A	11/1994	LeMarie, III et al.
D263,020 S	2/1982	Rau, III	5,368,600 A	11/1994	Failla et al.
4,370,980 A	2/1983	Lottick	5,376,089 A	12/1994	Smith
4,375,218 A	3/1983	DiGeronimo	5,383,897 A	1/1995	Wholey
4,416,276 A	11/1983	Newton et al.	5,389,098 A	2/1995	Tsuruta et al.
4,418,692 A	12/1983	Guay	5,389,104 A	2/1995	Hahnen et al.
4,452,246 A	6/1984	Bader et al.	5,391,166 A	2/1995	Eggers
4,492,231 A	1/1985	Auth	5,391,183 A	2/1995	Janzen et al.
4,552,143 A	11/1985	Lottick	5,396,900 A	3/1995	Slater et al.
4,574,804 A	3/1986	Kurwa	5,403,312 A	4/1995	Yates et al.
4,597,379 A	7/1986	Kihn et al.	5,411,519 A	5/1995	Tovey et al.
4,600,007 A	7/1986	Lahodny et al.	5,411,520 A	5/1995	Nash et al.
4,655,215 A	4/1987	Pike	5,413,571 A	5/1995	Katsaros et al.
4,655,216 A	4/1987	Tischer	5,415,657 A	5/1995	Taymor-Luria
4,657,016 A	4/1987	Garito et al.	5,422,567 A	6/1995	Matsunaga
4,662,372 A	5/1987	Sharkany et al.	5,423,810 A	6/1995	Goble et al.
4,671,274 A	6/1987	Sorochenko	5,425,690 A	6/1995	Chang
4,685,459 A	8/1987	Xoch et al.	5,425,739 A	6/1995	Jessen
D295,893 S	5/1988	Sharkany et al.	5,429,616 A	7/1995	Schaffer
D295,894 S	5/1988	Sharkany et al.	5,431,672 A	7/1995	Cote et al.
4,754,892 A	7/1988	Retief	5,431,674 A	7/1995	Basile et al.
4,763,669 A	8/1988	Jaeger	5,437,292 A	8/1995	Kipshidze et al.
4,827,929 A	5/1989	Hodge	5,438,302 A	8/1995	Goble
4,846,171 A	7/1989	Kauphusman et al.	5,441,517 A	8/1995	Kensley et al.
4,887,612 A	12/1989	Esser et al.	5,443,463 A	8/1995	Stern et al.
4,938,761 A	7/1990	Ensslin	5,443,464 A	8/1995	Russell et al.
4,985,030 A	1/1991	Melzer et al.	5,443,480 A	8/1995	Jacobs et al.
5,007,908 A	4/1991	Rydell	5,445,638 A	8/1995	Rydell et al.
5,026,370 A	6/1991	Lottick	5,445,658 A	8/1995	Durrfeld et al.
5,035,695 A	7/1991	Weber, Jr. et al.	5,451,224 A	9/1995	Goble et al.
5,084,057 A	1/1992	Green et al.	5,456,684 A	10/1995	Schmidt et al.
5,099,840 A	3/1992	Goble et al.	5,458,598 A	10/1995	Feinberg et al.
5,116,332 A	5/1992	Lottick	5,460,629 A	10/1995	Shlain et al.
5,147,357 A	9/1992	Rose et al.	5,462,546 A	10/1995	Rydell
5,151,102 A	9/1992	Xamiyama et al.	5,472,443 A	12/1995	Cordis et al.
5,176,695 A	1/1993	Dulebohn	5,478,351 A	12/1995	Meade et al.
5,190,541 A	3/1993	Abele et al.	5,480,409 A	1/1996	Riza
5,196,009 A	3/1993	Kirwan, Jr.	5,484,436 A	1/1996	Eggers et al.
5,197,964 A	3/1993	Parins	5,496,312 A	3/1996	Klicek
5,215,101 A	6/1993	Jacobs et al.	5,496,317 A	3/1996	Goble et al.
5,217,457 A	6/1993	Delahuerga et al.	5,496,347 A	3/1996	Hashiguchi et al.
5,217,458 A	6/1993	Parins	5,499,997 A	3/1996	Sharpe et al.
5,217,460 A	6/1993	Knoepfler	5,509,922 A	4/1996	Aranyi et al.
5,219,354 A	6/1993	Choudhury et al.	5,514,134 A	5/1996	Rydell et al.
5,244,462 A	9/1993	Delahuerga et al.	5,527,313 A	6/1996	Scott et al.
5,250,047 A	10/1993	Rydell	5,531,744 A	7/1996	Nardella et al.
5,250,063 A	10/1993	Abidin et al.	5,536,251 A	7/1996	Evard et al.
5,258,001 A	11/1993	Corman	5,540,684 A	7/1996	Hassler, Jr.
5,258,006 A	11/1993	Rydell et al.	5,540,685 A	7/1996	Parins et al.
			5,540,715 A	7/1996	Katsaros et al.

# US 7,628,791 B2

Page 3

5,542,945 A	8/1996	Fritzsch	5,817,093 A	10/1998	Williamson, IV et al.
5,558,671 A	9/1996	Yates	5,820,630 A	10/1998	Lind
5,558,672 A	9/1996	Edwards et al.	5,827,271 A	10/1998	Buysse et al.
5,562,699 A	10/1996	Heimberger et al.	5,827,279 A	10/1998	Hughett et al.
5,569,241 A	10/1996	Edwardds	5,827,281 A	10/1998	Levin
5,569,243 A	10/1996	Kortenbach et al.	5,827,323 A	10/1998	Klieman et al.
5,571,100 A	11/1996	Goble et al.	5,827,548 A	10/1998	Lavallee et al.
5,573,424 A	11/1996	Poppe	5,833,690 A	11/1998	Yates et al.
5,573,534 A	11/1996	Stone	5,843,080 A	12/1998	Fleenor et al.
5,573,535 A	11/1996	Viklund	5,849,022 A	12/1998	Sakashita et al.
5,575,805 A	11/1996	Li	5,853,412 A	12/1998	Mayenberger
5,578,052 A	11/1996	Koros et al.	5,860,976 A	1/1999	Billings et al.
5,582,611 A	12/1996	Tsukagoshi et al.	5,876,401 A	3/1999	Schulze et al.
5,585,896 A	12/1996	Yamazaki et al.	5,882,567 A	3/1999	Cavallaro et al.
5,590,570 A	1/1997	LeMaire, III et al.	5,891,141 A	4/1999	Rydell
5,601,601 A	2/1997	Tal et al.	5,891,142 A	4/1999	Eggers et al.
5,603,711 A	2/1997	Parins et al.	5,893,863 A	4/1999	Yoon
5,603,723 A	2/1997	Aranyi et al.	5,893,875 A	4/1999	O'Connor et al.
5,611,798 A	3/1997	Eggers	5,893,877 A	4/1999	Gampp, Jr. et al.
5,620,453 A	4/1997	Nallakrishnan	5,902,301 A	5/1999	Olig
5,624,452 A	4/1997	Yates	5,906,630 A	5/1999	Anderhub et al.
5,626,578 A	5/1997	Tihon	5,908,420 A	6/1999	Parins et al.
5,626,609 A	5/1997	Zvenyatsky et al.	5,908,432 A	6/1999	Pan
5,630,833 A	5/1997	Katsaros et al.	5,911,719 A	6/1999	Eggers
5,637,110 A	6/1997	Pennybacker et al.	5,913,874 A	6/1999	Berns et al.
5,638,003 A	6/1997	Hall	5,921,984 A	7/1999	Sutcu et al.
5,643,294 A	7/1997	Tovey et al.	5,925,043 A	7/1999	Kumar et al.
5,647,869 A	7/1997	Goble et al.	5,935,126 A	8/1999	Riza
5,647,871 A	7/1997	Levine et al.	5,944,718 A	8/1999	Dafforn et al.
5,649,959 A	7/1997	Hannam et al.	5,951,549 A	9/1999	Richardson et al.
5,658,281 A	8/1997	Heard	5,954,720 A	9/1999	Wilson et al.
5,662,667 A	9/1997	Knodel	5,957,923 A	9/1999	Hahnen et al.
5,665,100 A	9/1997	Yoon	5,960,544 A	10/1999	Beyers
5,667,526 A	9/1997	Levin	5,961,514 A	10/1999	Long et al.
5,674,220 A	10/1997	Fox et al.	5,964,758 A	10/1999	Dresden
5,681,282 A	10/1997	Eggers et al.	5,976,132 A	11/1999	Morris
5,688,270 A	11/1997	Yates et al.	5,984,939 A	11/1999	Yoon
5,693,051 A	12/1997	Schulze et al.	5,989,277 A	11/1999	LeMaire, III et al.
5,695,522 A	12/1997	LeMaire, III et al.	5,997,565 A	12/1999	Inoue
5,700,261 A	12/1997	Brinkerhoff	6,004,335 A	12/1999	Vaitekunas et al.
5,702,390 A	12/1997	Austin et al.	6,010,516 A	1/2000	Hulka
5,707,369 A	1/1998	Vaitekunas et al.	6,024,741 A	2/2000	Williamson et al.
5,709,680 A	1/1998	Yates et al.	6,024,744 A	2/2000	Kese et al.
5,716,366 A	2/1998	Yates	6,030,384 A	2/2000	Nezhat
5,720,744 A	2/1998	Eggleston et al.	6,033,399 A	3/2000	Gines
5,722,421 A	3/1998	Francese et al.	6,039,733 A	3/2000	Buysse et al.
5,725,536 A	3/1998	Oberlin et al.	6,041,679 A	3/2000	Slater et al.
5,727,428 A	3/1998	LeMaire, III et al.	6,050,996 A	4/2000	Schmaltz et al.
5,735,848 A	4/1998	Yates et al.	6,053,914 A	4/2000	Eggers et al.
5,743,906 A	4/1998	Parins et al.	6,053,933 A	4/2000	Balazs et al.
5,755,717 A	5/1998	Yates et al.	D424,694 S	5/2000	Tetzlaff et al.
5,766,130 A	6/1998	Selmonosky	D425,201 S	5/2000	Tetzlaff et al.
5,766,166 A	6/1998	Hooven	6,059,782 A	5/2000	Novak et al.
5,766,170 A	6/1998	Eggers	6,074,386 A	6/2000	Goble et al.
5,769,849 A	6/1998	Eggers	RE36,795 E	7/2000	Rydell
5,772,655 A	6/1998	Bauer et al.	6,083,223 A	7/2000	Baker
5,772,670 A	6/1998	Brosa	6,086,586 A	7/2000	Hooven
5,776,128 A	7/1998	Eggers	6,090,107 A	7/2000	Borgmeier et al.
5,776,130 A	7/1998	Buysse et al.	6,096,037 A	8/2000	Mulier et al.
5,779,701 A	7/1998	McBrayer et al.	6,099,550 A	8/2000	Yoon
H1745 H	8/1998	Paraschac	6,102,909 A	8/2000	Chen et al.
5,792,137 A	8/1998	Carr et al.	6,110,171 A	8/2000	Rydell
5,792,177 A	8/1998	Kaseda	6,113,596 A	9/2000	Hooven et al.
5,797,927 A	8/1998	Yoon	6,113,598 A	9/2000	Baker
5,797,938 A	8/1998	Paraschac et al.	6,117,158 A	9/2000	Measamer et al.
5,797,941 A	8/1998	Schulze et al.	6,123,701 A	9/2000	Nezhat
5,797,958 A	8/1998	Yoon	6,126,658 A	10/2000	Baker
5,800,449 A	9/1998	Wales	6,152,923 A	11/2000	Ryan
5,807,393 A	9/1998	Williamson, IV et al.	6,162,220 A	12/2000	Nezhat
5,810,808 A	9/1998	Eggers	6,174,309 B1	1/2001	Wrublewski et al.
5,810,811 A	9/1998	Yates et al.	6,179,834 B1	1/2001	Buysse et al.
5,810,877 A	9/1998	Roth et al.	6,179,837 B1	1/2001	Hooven
5,814,043 A	9/1998	Shapeton	6,183,467 B1	2/2001	Shapeton et al.

# US 7,628,791 B2

6,187,003 B1	2/2001	Buyse et al.	6,702,810 B2	3/2004	McClurken et al.
6,190,386 B1	2/2001	Rydell	6,726,068 B2	4/2004	Miller
6,193,718 B1	2/2001	Kortenbach et al.	6,726,686 B2	4/2004	Buyse et al.
6,206,876 B1	3/2001	Levine et al.	6,733,498 B2	5/2004	Paton et al.
6,206,877 B1	3/2001	Kese et al.	6,736,813 B2	5/2004	Yamauchi et al.
6,217,602 B1	4/2001	Redmon	6,743,229 B2	6/2004	Buyse et al.
6,221,039 B1	4/2001	Durgin et al.	6,743,230 B2	6/2004	Lutze et al.
6,224,593 B1	5/2001	Ryan et al.	6,757,977 B2	7/2004	Dambal et al.
6,228,080 B1	5/2001	Gines	6,770,072 B1	8/2004	Truckai et al.
6,228,083 B1	5/2001	Lands et al.	6,773,409 B2	8/2004	Truckai et al.
6,267,761 B1	7/2001	Ryan	6,773,434 B2	8/2004	Ciarrocca
6,270,497 B1	8/2001	Sekino et al.	6,775,575 B2	8/2004	Bommannan et al.
6,270,508 B1	8/2001	Klieman et al.	6,776,780 B2	8/2004	Mulier et al.
6,273,887 B1	8/2001	Yamauchi et al.	6,790,217 B2	9/2004	Schulze et al.
6,277,117 B1	8/2001	Tetzlaff et al.	6,796,981 B2	9/2004	Wham et al.
6,280,458 B1	8/2001	Boche et al.	D496,997 S	10/2004	Dycus et al.
6,283,961 B1	9/2001	Underwood et al.	6,802,843 B2	10/2004	Truckai et al.
D449,886 S	10/2001	Tetzlaff et al.	6,808,525 B2	10/2004	Latterell et al.
6,302,424 B1	10/2001	Gisinger et al.	D499,181 S	11/2004	Dycus et al.
6,319,451 B1	11/2001	Brune	6,818,000 B2	11/2004	Muller et al.
6,322,561 B1	11/2001	Eggers et al.	6,887,240 B1	5/2005	Lands et al.
6,334,860 B1	1/2002	Dorn	6,926,716 B2	8/2005	Baker et al.
6,334,861 B1	1/2002	Chandler et al.	6,929,644 B2	8/2005	Truckai et al.
6,345,532 B1	2/2002	Coudray et al.	6,932,810 B2	8/2005	Ryan
6,350,264 B1	2/2002	Hooven	6,932,816 B2	8/2005	Phan
6,352,536 B1	3/2002	Buyse et al.	6,934,134 B2	8/2005	Mori et al.
6,358,249 B1	3/2002	Chen et al.	6,936,061 B2	8/2005	Sasaki
6,358,268 B1	3/2002	Hunt et al.	6,942,662 B2	9/2005	Goble et al.
D457,958 S	5/2002	Dycus et al.	6,953,461 B2	10/2005	McClurken et al.
D457,959 S	5/2002	Tetzlaff et al.	6,958,070 B2	10/2005	Witt et al.
6,387,094 B1 *	5/2002	Eitenmuller ..... 606/48	6,960,210 B2	11/2005	Lands et al.
6,391,035 B1	5/2002	Appleby et al.	6,964,662 B2	11/2005	Kidooka
6,398,779 B1	6/2002	Buyse et al.	6,966,907 B2	11/2005	Goble
6,402,747 B1	6/2002	Lindemann et al.	6,977,495 B2	12/2005	Donofrio
6,409,728 B1	6/2002	Ehr et al.	6,979,786 B2	12/2005	Aukland et al.
6,419,675 B1	7/2002	Gallo, Sr.	6,994,707 B2	2/2006	Ellman et al.
6,425,896 B1	7/2002	Baltschun et al.	6,994,709 B2	2/2006	Iida
6,440,144 B1	8/2002	Bacher	7,011,657 B2	3/2006	Truckai et al.
6,443,952 B1	9/2002	Mulier et al.	7,033,354 B2	4/2006	Keppel
6,443,970 B1	9/2002	Schulze et al.	7,033,356 B2	4/2006	Latterell et al.
6,451,018 B1	9/2002	Lands et al.	7,041,102 B2	5/2006	Truckai et al.
6,458,125 B1	10/2002	Cosmescu	7,044,948 B2	5/2006	Keppel
6,458,128 B1	10/2002	Schulze	7,052,496 B2	5/2006	Yamauchi
6,458,130 B1	10/2002	Frazier et al.	D525,361 S	7/2006	Hushka
6,464,701 B1	10/2002	Hooven et al.	7,070,597 B2	7/2006	Truckai et al.
6,464,702 B2	10/2002	Schulze et al.	7,083,618 B2	8/2006	Couture et al.
6,464,704 B2	10/2002	Schmaltz et al.	7,083,619 B2	8/2006	Truckai et al.
6,500,176 B1	12/2002	Truckai et al.	7,087,054 B2	8/2006	Truckai et al.
6,511,480 B1	1/2003	Tetzlaff et al.	7,090,673 B2	8/2006	Dycus et al.
6,514,252 B2	2/2003	Nezhat et al.	7,090,689 B2	8/2006	Nagase et al.
6,527,771 B1	3/2003	Weadock et al.	7,101,371 B2	9/2006	Dycus et al.
6,558,385 B1	5/2003	McClurken et al.	7,101,372 B2	9/2006	Dycus et al.
6,562,037 B2	5/2003	Paton et al.	7,101,373 B2	9/2006	Dycus et al.
6,585,735 B1	7/2003	Frazier et al.	7,103,947 B2	9/2006	Sartor et al.
6,602,252 B2	8/2003	Mollenauer	7,112,199 B2	9/2006	Cosmescu
6,616,658 B2	9/2003	Ineson	D531,311 S	10/2006	Guerra et al.
6,616,661 B2	9/2003	Wellman et al.	7,115,123 B2	10/2006	Knowlton et al.
6,620,161 B2	9/2003	Schulze et al.	7,118,570 B2	10/2006	Tetzlaff et al.
6,626,901 B1	9/2003	Treat et al.	7,118,587 B2	10/2006	Dycus et al.
6,641,595 B1	11/2003	Moran et al.	7,131,860 B2	11/2006	Sartor et al.
6,652,514 B2	11/2003	Ellman et al.	7,131,970 B2	11/2006	Moses et al.
6,652,521 B2	11/2003	Schulze	7,131,971 B2	11/2006	Dycus et al.
6,656,177 B2	12/2003	Truckai et al.	7,135,020 B2	11/2006	Lawes et al.
6,660,072 B2	12/2003	Chatterjee	D533,942 S	12/2006	Kerr et al.
6,669,696 B2	12/2003	Bacher et al.	7,145,757 B2	12/2006	Shea et al.
6,676,660 B2	1/2004	Wampler et al.	7,147,638 B2	12/2006	Chapman et al.
6,679,882 B1	1/2004	Kornerup	7,150,097 B2	12/2006	Sremcich et al.
6,682,527 B2	1/2004	Strul	7,150,749 B2	12/2006	Dycus et al.
6,682,528 B2	1/2004	Frazier et al.	D535,027 S	1/2007	James et al.
6,685,724 B1	2/2004	Haluck	7,156,842 B2	1/2007	Sartor et al.
6,689,131 B2	2/2004	McClurken	7,156,846 B2	1/2007	Dycus et al.
6,692,445 B2	2/2004	Roberts et al.	7,160,298 B2	1/2007	Lawes et al.
6,695,840 B2	2/2004	Schulze	7,160,299 B2	1/2007	Baily

# US 7,628,791 B2

7,169,146 B2	1/2007	Truckai et al.	2004/0254573 A1	12/2004	Dycus et al.
7,179,258 B2	2/2007	Buysse et al.	2004/0260281 A1	12/2004	Baxter, III et al.
7,195,631 B2	3/2007	Dumbauld	2005/0004564 A1	1/2005	Wham et al.
D541,418 S	4/2007	Schechter et al.	2005/0004568 A1	1/2005	Lawes et al.
7,207,990 B2	4/2007	Lands et al.	2005/0004570 A1	1/2005	Chapman et al.
D541,938 S	5/2007	Kerr et al.	2005/0021025 A1	1/2005	Buysse et al.
7,223,265 B2	5/2007	Keppel	2005/0021026 A1	1/2005	Baily
7,232,440 B2	6/2007	Dumbauld et al.	2005/0021027 A1	1/2005	Shields et al.
7,241,288 B2	7/2007	Braun	2005/0033278 A1	2/2005	McClurken et al.
7,241,296 B2	7/2007	Buysse et al.	2005/0096645 A1	5/2005	Wellman et al.
7,252,667 B2	8/2007	Moses et al.	2005/0101951 A1	5/2005	Wham et al.
7,255,697 B2	8/2007	Dycus et al.	2005/0101952 A1	5/2005	Lands et al.
7,267,677 B2	9/2007	Johnson et al.	2005/0107784 A1	5/2005	Moses et al.
7,270,660 B2	9/2007	Ryan	2005/0107785 A1	5/2005	Dycus et al.
7,270,664 B2	9/2007	Johnson et al.	2005/0113818 A1	5/2005	Sartor et al.
7,276,068 B2	10/2007	Johnson et al.	2005/0113819 A1	5/2005	Wham et al.
7,300,435 B2	11/2007	Wham et al.	2005/0113826 A1	5/2005	Johnson et al.
7,303,557 B2	12/2007	Wham et al.	2005/0113827 A1	5/2005	Dumbauld et al.
7,314,471 B2	1/2008	Holman	2005/0113828 A1	5/2005	Shields et al.
7,329,256 B2	2/2008	Johnson et al.	2005/0119655 A1	6/2005	Moses et al.
7,329,257 B2	2/2008	Kanehira et al.	2005/0149017 A1	7/2005	Dycus
D564,662 S	3/2008	Moses et al.	2005/0149151 A1	7/2005	Orszulak et al.
7,342,754 B2	3/2008	Fitzgerald et al.	2005/0187547 A1	8/2005	Sugi
7,344,268 B2	3/2008	Jigamian	2005/0197659 A1	9/2005	Bahney
7,367,976 B2	5/2008	Lawes et al.	2005/0203504 A1	9/2005	Wham et al.
2002/0013583 A1	1/2002	Camran et al.	2005/0240179 A1	10/2005	Buysse et al.
2002/0049442 A1	4/2002	Roberts et al.	2006/0052778 A1	3/2006	Chapman et al.
2002/0099372 A1	7/2002	Schulze et al.	2006/0064085 A1	3/2006	Schechter et al.
2002/0107517 A1	8/2002	Witt et al.	2006/0074417 A1	4/2006	Cunningham et al.
2002/0111624 A1	8/2002	Witt et al.	2006/0079888 A1	4/2006	Mulier et al.
2002/0188294 A1	12/2002	Couture et al.	2006/0079890 A1	4/2006	Guerra
2003/0014052 A1	1/2003	Buysse et al.	2006/0079891 A1	4/2006	Arts et al.
2003/0014053 A1	1/2003	Nguyen et al.	2006/0116675 A1	6/2006	McClurken et al.
2003/0018331 A1	1/2003	Dycus et al.	2006/0129146 A1	6/2006	Dycus et al.
2003/0018332 A1	1/2003	Schmaltz et al.	2006/0161150 A1	7/2006	Keppel
2003/0032956 A1	2/2003	Lands et al.	2006/0167450 A1	7/2006	Johnson et al.
2003/0055424 A1*	3/2003	Ciarrocca ..... 606/51	2006/0167452 A1	7/2006	Moses et al.
2003/0069571 A1	4/2003	Treat et al.	2006/0173452 A1	8/2006	Buysse et al.
2003/0078578 A1	4/2003	Truckai et al.	2006/0189980 A1	8/2006	Johnson et al.
2003/0109875 A1	6/2003	Tetzlaff et al.	2006/0189981 A1	8/2006	Dycus et al.
2003/0114851 A1	6/2003	Truckai et al.	2006/0190035 A1	8/2006	Hushka et al.
2003/0139741 A1	7/2003	Goble et al.	2006/0217709 A1	9/2006	Couture et al.
2003/0139742 A1	7/2003	Wampler et al.	2006/0224158 A1	10/2006	Odom et al.
2003/0158549 A1	8/2003	Swanson	2006/0259036 A1	11/2006	Tetzlaff et al.
2003/0181910 A1	9/2003	Dycus et al.	2006/0264922 A1	11/2006	Sartor et al.
2003/0199869 A1	10/2003	Johnson et al.	2006/0264931 A1	11/2006	Chapman et al.
2003/0216732 A1	11/2003	Truckai et al.	2006/0271038 A1	11/2006	Johnson et al.
2003/0220637 A1	11/2003	Truckai et al.	2006/0287641 A1	12/2006	Perlin
2003/0229344 A1	12/2003	Dycus et al.	2007/0016182 A1	1/2007	Lipson et al.
2004/0030330 A1	2/2004	Brassell et al.	2007/0016187 A1	1/2007	Weinberg et al.
2004/0030332 A1	2/2004	Knowlton et al.	2007/0043352 A1	2/2007	Garrison et al.
2004/0049185 A1	3/2004	Latterell et al.	2007/0043353 A1	2/2007	Dycus et al.
2004/0064151 A1	4/2004	Mollenauer	2007/0055231 A1	3/2007	Dycus et al.
2004/0078035 A1	4/2004	Kanehira et al.	2007/0060919 A1	3/2007	Isaacson et al.
2004/0082952 A1	4/2004	Dycus et al.	2007/0062017 A1	3/2007	Dycus et al.
2004/0087943 A1	5/2004	Dycus et al.	2007/0074807 A1	4/2007	Guerra
2004/0115296 A1	6/2004	Duffin	2007/0078456 A1	4/2007	Dumbauld et al.
2004/0116924 A1	6/2004	Dycus et al.	2007/0078458 A1	4/2007	Dumbauld et al.
2004/0116979 A1	6/2004	Truckai et al.	2007/0078459 A1	4/2007	Johnson et al.
2004/0122423 A1	6/2004	Dycus et al.	2007/0088356 A1	4/2007	Moses et al.
2004/0143263 A1	7/2004	Schechter et al.	2007/0106295 A1	5/2007	Garrison et al.
2004/0147925 A1	7/2004	Buysse et al.	2007/0106297 A1	5/2007	Dumbauld et al.
2004/0162557 A1	8/2004	Tetzlaff et al.	2007/0118111 A1	5/2007	Weinberg
2004/0176762 A1	9/2004	Lawes et al.	2007/0118115 A1	5/2007	Artale et al.
2004/0193153 A1	9/2004	Sarter et al.	2007/0142833 A1	6/2007	Dycus et al.
2004/0225288 A1	11/2004	Buysse et al.	2007/0142834 A1	6/2007	Dumbauld
2004/0230189 A1	11/2004	Keppel	2007/0156139 A1	7/2007	Schechter et al.
2004/0236325 A1	11/2004	Tetzlaff et al.	2007/0156140 A1	7/2007	Baily
2004/0236326 A1	11/2004	Schulze et al.	2007/0173811 A1	7/2007	Couture et al.
2004/0243125 A1	12/2004	Dycus et al.	2007/0173814 A1	7/2007	Hixson et al.
2004/0249371 A1	12/2004	Dycus et al.	2007/0179499 A1	8/2007	Garrison
2004/0249374 A1	12/2004	Tetzlaff et al.	2007/0203485 A1	8/2007	Keppel
2004/0250419 A1	12/2004	Sremcich et al.	2007/0213706 A1	9/2007	Dumbauld et al.

2007/0213707	A1	9/2007	Dumbauld et al.	GB	2213416	8/1989
2007/0213708	A1	9/2007	Dumbauld et al.	JP	501068	9/1984
2007/0213712	A1	9/2007	Buyse et al.	JP	502328	3/1992
2007/0255279	A1	11/2007	Buyse et al.	JP	5-5106	1/1993
2007/0260235	A1	11/2007	Podhajsky	JP	5-40112	2/1993
2007/0260238	A1	11/2007	Guerra	JP	06343644	A2 12/1994
2007/0260241	A1	11/2007	Dalla Betta et al.	JP	07265328	A2 10/1995
2007/0260242	A1	11/2007	Dycus et al.	JP	08056955	A2 3/1996
2007/0265616	A1	11/2007	Couture et al.	JP	08252263	A2 10/1996
2008/0004616	A1	1/2008	Patrick	JP	09010223	A2 1/1997
2008/0009860	A1	1/2008	Odom	JP	11244298	A2 9/1999
2008/0015575	A1	1/2008	Odom et al.	JP	2000342599	A2 12/2000
2008/0021450	A1	1/2008	Couture	JP	2000350732	A2 12/2000
2008/0033428	A1	2/2008	Artale et al.	JP	2001008944	A2 1/2001
2008/0039835	A1	2/2008	Johnson et al.	JP	2001029356	A2 2/2001
2008/0045947	A1	2/2008	Johnson et al.	JP	2001128990	A2 5/2001
2008/0058802	A1	3/2008	Couture et al.	SU	401367	10/1973
2008/0082100	A1	4/2008	Orton et al.	WO	WO89/00757	1/1989

## FOREIGN PATENT DOCUMENTS

DE	2415263	10/1975	WO	WO 92/04873	4/1992
DE	2627679	1/1977	WO	WO 92/06642	4/1992
DE	8712328	3/1988	WO	WO 94/08524	A 4/1994
DE	4303882	8/1994	WO	WO94/20025	9/1994
DE	29616210	1/1997	WO	WO 95/02369	1/1995
DE	19608716	4/1997	WO	WO 95/07662	3/1995
DE	19751106	5/1998	WO	WO95/15124	6/1995
DE	19751108	5/1999	WO	WO96/05776	2/1996
EP	0364216	A1 4/1990	WO	WO 96/22056	7/1996
EP	518230	A1 12/1992	WO	WO 96/13218	9/1996
EP	0 541 930	B1 5/1993	WO	WO 97/00646	1/1997
EP	0572131	12/1993	WO	WO 97/00647	1/1997
EP	584787	A1 3/1994	WO	WO97/10764	3/1997
EP	0589453	A2 3/1994	WO	WO 97/24073	7/1997
EP	0623316	A1 11/1994	WO	WO 97/24993	7/1997
EP	0624348	A2 11/1994	WO	WO 98/27880	7/1998
EP	0650701	A1 5/1995	WO	WO 99/03407	1/1999
EP	0694290	A3 3/1996	WO	WO 99/03408	1/1999
EP	0717966	A1 6/1996	WO	WO 99/03409	1/1999
EP	0754437	A3 3/1997	WO	WO 99/12488	3/1999
EP	853922	A1 7/1998	WO	WO 99/40857	8/1999
EP	0875209	A1 11/1998	WO	WO 99/40861	8/1999
EP	0878169	A1 11/1998	WO	WO 99/51158	10/1999
EP	0887046	A3 1/1999	WO	WO 99/66850	12/1999
EP	0923907	A1 6/1999	WO	WO 99/66850	A 12/1999
EP	0986990	A1 3/2000	WO	WO 00/24330	5/2000
EP	1034747	A1 9/2000	WO	WO00/24331	5/2000
EP	1034748	A1 9/2000	WO	WO 00/41638	7/2000
EP	1025807	A3 10/2000	WO	WO00/47124	8/2000
EP	1034746	A3 10/2000	WO	WO 00/53112	9/2000
EP	1050278	A1 11/2000	WO	WO 01/17448	A 3/2001
EP	1053719	A1 11/2000	WO	WO 01/54604	8/2001
EP	1053720	A1 11/2000	WO	WO02/07627	1/2002
EP	1055399	A1 11/2000	WO	WO 02/07627	1/2002
EP	1055400	A1 11/2000	WO	WO 02/067798	A1 9/2002
EP	1080694	A1 3/2001	WO	WO02/080783	10/2002
EP	1082944	A1 3/2001	WO	WO 02/080783	10/2002
EP	1159926	A2 12/2001	WO	WO 02/080784	10/2002
EP	1301135	A 4/2003	WO	WO 02/080784	10/2002
EP	1330991	A1 7/2003	WO	WO 02/080785	10/2002
EP	1486177	A2 6/2004	WO	WO 02/080785	10/2002
EP	1472984	A1 11/2004	WO	WO 02/080786	10/2002
EP	1527747	A2 5/2005	WO	WO 02/080786	10/2002
EP	1530952	A1 5/2005	WO	WO 02/080793	10/2002
EP	1532932	A1 5/2005	WO	WO 02/080793	10/2002
EP	1535581	A2 6/2005	WO	WO 02/080794	10/2002
EP	1609430	A1 12/2005	WO	WO 02/080794	10/2002
EP	1632192	A1 3/2006	WO	WO 02/080795	10/2002
EP	1645238	A1 4/2006	WO	WO 02/080796	10/2002
EP	1645240	A2 4/2006	WO	WO 02/080796	A1 10/2002
EP	1707143	A1 10/2006	WO	WO 02/080797	10/2002
GB	2214430	A 6/1989	WO	WO 02/080797	10/2002
			WO	WO 02/080798	A1 10/2002
			WO	WO 02/080799	10/2002
			WO	WO02/081170	10/2002
			WO	WO 02/081170	10/2002

WO	WO/080786	10/2002
WO	WO 03/090630 A3	11/2003
WO	WO 03/101311	12/2003
WO	WO 2004/032776 A1	4/2004
WO	WO 2004/032777	4/2004
WO	WO2004/032777	4/2004
WO	WO 2004/052221 A1	6/2004
WO	WO 2004/073488 A2	9/2004
WO	WO2004/073490	9/2004
WO	WO 2004/073490	9/2004
WO	WO2004/073753	9/2004
WO	WO 2004/082495	9/2004
WO	WO 2004/082495 A1	9/2004
WO	WO 2004/098383 A1	11/2004
WO	WO 2004/103156	12/2004
WO	WO 2005/004734 A1	1/2005
WO	WO2005/004735	1/2005
WO	WO 2005/110264	11/2005

## OTHER PUBLICATIONS

Bergdahl et al. "Studies on Coagulation and the Development of an Automatic Computerized Bipolar Coagulator" *J. Neurosurg*, vol. 75, Jul. 1991, pp. 148-151.

Kennedy et al. "High-burst-strength, feedback-controlled bipolar vessel sealing" *Surgical Endoscopy* (1998) 12: 876-878.

Peterson et al. "Comparison of Healing Process Following Ligation with Sutures and Bipolar Vessel Sealing" *Surgical Technology International* (2001).

Linehan et al. "A Phase I Study of the LigaSure Vessel Sealing System in Hepatic Surgery" Section of HPB Surger, Washington University School of Medicine, St. Louis MO, Presented at AHPBA, Feb. 2001.

Johnson et al. "Evaluation of the LigaSure Vessel Sealing System in Hemorrhoidectomy" American College of Surgeons (ACS) Clinica Congress Poster (2000).

Sayfan et al. "Sutureless Closed Hemorrhoidectomy: A New Technique" *Annals of Surgery* vol. 234 No. 1 Jul. 2001 pp. 21-24.

Heniford et al. "Initial Results with an Electrothermal Bipolar Vessel Sealer" *Surgical Endoscopy* (2000) 15:799-801.

Heniford et al. "Initial Research and Clinical Results with an Electrothermal Bipolar Vessel Sealer" Oct. 1999.

McLellan et al. "Vessel Sealing for Hemostasis During Pelvic Surgery" Int'l Federation of Gynecology and Obstetrics Figo World Congress 2000, Washington, D.C.

Levy et al. "Use of a New Energy-based Vessel Ligation Device During Vaginal Hysterectomy" Int'l Federation of Gynecology and Obstetrics (FIGO) World Congress 1999.

Crawford et al. "Use of the LigaSure Vessel Sealing System in Urologic Cancer Surger" *Grand Rounds in Urology* 1999 vol. 1 Issue 4 pp. 10-17.

Rothenberg et al. "Use of the LigaSure Vessel Sealing System in Minimally Invasive Surgery in Children" Int'l Pediatric Endosurgery Group (IPEG) 2000.

Palazzo et al. "Randomized clinical trial of Ligasure versus open haemorrhoidectomy" *British Journal of Surgery* 2002, 89, 154-157. "Innovations in Electrosurgery" Sales/Product Literature; Dec. 31, 2000.

LigaSure Vessel Sealing System, the Seal of Confidence in General, Gynecologic, Urologic, and Laparoscopic Surgery Sales/Product Literature; Jan. 2004.

Carbonell et al., "Comparison of theGyrus PlasmaKinetic Sealer and the Valleylab LigaSure Device in the Hemostasis of Small, Medium, and Large-Sized Arteries" Carolinas Laparoscopic and Advanced Surgery Program, Carolinas Medical Center, Charlotte, NC 2003.

"Reducing Needlestick Injuries in the Operating Room" Sales/Product Literature 2001.

Chung et al., "Clinical Experience of Sutureless Closed Hemorrhoidectomy with LigaSure" *Diseases of the Colon & Rectum* vol. 46, No. 1 Jan. 2003.

Strasberg et al., "Use of a Bipolar Vessel-Sealing Device for Parenchymal Transection During Liver Surgery" *Journal of Gastrointestinal Surgery*, vol. 6, No. 4, Jul./Aug. 2002 pp. 569-574.

Paul G. Horgan, "A Novel Technique for Parenchymal Division During Hepatectomy" *The American Journal of Surgery*, vol. 181, No. 3, Apr. 2001 pp. 236-237.

W. Scott Helton, "LigaSure Vessel Sealing System: Revolutionary Hemostasis Product for General Surgery" Sales/Product Literature 1999.

Michael Choti, "Abdominoperineal Resection with the LigaSure Vessel Sealing System and LigaSure Atlas 20 cm Open Instrument" *Innovations That Work*, Jun. 2003.

Craig Johnson, "Use of the LigaSure Vessel Sealing System in Bloodless Hemorrhoidectomy" *Innovations That Work*, Mar. 2000.

Muller et al., "Extended Left Hemicolectomy Using the LigaSure Vessel Sealing System" *Innovations That Work*, Sep. 1999.

Herman et al., "Laparoscopic Intestinal Resection With the LigaSure Vessel Sealing System: A Case Report" *Innovations That Work*, Feb. 2002.

Carus et al., "Initial Experience With The LigaSure Vessel Sealing System in Abdominal Surgery" *Innovations That Work*, Jun. 2002.

Levy et al. "Randomized Trial of Suture Versus Electrosurgical Bipolar Vessel Sealing in Vaginal Hysterectomy" *Obstetrics & Gynecology*, vol. 102, No. 1, Jul. 2003.

Levy et al., "Update on Hysterectomy—New Technologies and Techniques" *OBG Management*, Feb. 2003.

Barbara Levy, "Use of a New Vessel Ligation Device During Vaginal Hysterectomy" FIGO 2000, Washington, D.C.

McLellan et al. "Vessel Sealing For Hemostasis During Gynecologic Surgery" Sales/Product Literature 1999.

Sengupta et al., "Use of a Computer-Controlled Bipolar Diathermy System in Radical Prostatectomies and Other Open Urological Surgery" *ANZ Journal of Surgery* (2001) 71.9 pp. 538-540.

Olsson et al. "Radical Cystectomy in Females" *Current Surgical Techniques in Urology*, vol. 14, Issue 3, 2001.

E. David Crawford "Use of a Novel Vessel Sealing Technology in Management of the Dorsal Venous Complex" Sales/Product Literature 2000.

Jarrett et al., "Use of the LigaSure Vessel Sealing System for Perihilar Vessels in Laparoscopic Nephrectomy" Sales/Product Literature 2000.

E. David Crawford "Evaluation of a New Vessel Sealing Device in Urologic Cancer Surgery" Sales/Product Literature 2000.

Joseph Ortenberg "LigaSure Used in Laparoscopic 1st and 2nd Stage Orchiopexy" *Innovations That Work*, Nov. 2002.

Koyle et al., "Laparoscopic Palomo Varicocele Ligation in Children and Adolescents" *Pediatric Endosurgery & Innovative Techniques*, vol. 6, No. 1, 2002.

Dulemba et al. "Use of a Bipolar Electrothermal Vessel Sealer in Laparoscopically Assisted Vaginal Hysterectomy" Sales/Product Literature; Jan. 2004.

Johnson et al. "Evaluation of a Bipolar electrothermal Vessel Sealing Device in Hemorrhoidectomy" Sales/Product Literature; Jan. 2004.

Int'l Search Report PCT/US98/18640.

Int'l Search Report PCT/US98/23950.

Int'l Search Report PCT/US99/24869.

Int'l Search Report PCT/US01/11218.

Int'l Search Report PCT/US01/11340.

Int'l Search Report PCT/US01/11420.

Int'l Search Report PCT/US02/01890.

Int'l Search Report PCT/US02/11100.

Int'l Search Report PCT/US04/03436.

Int'l Search Report PCT/US04/13273.

Int'l Search Report PCT/US04/15311.

Int'l Search Report EP 98944778.

Int'l Search Report EP 98958575.

Int'l Search Report EP 04027314.

Int'l Search Report EP 04027479.

Int'l Search Report EP 04027705.

Int'l Search Report EP 04013772.

Int'l Search Report EP 05016399 dated Jan. 5, 2006.

Int'l Search Report EP 06005185.1 dated Apr. 18, 2006.

Int'l Search Report EP 06008779.8 dated Jun. 13, 2006.

Int'l Search Report EP 1683496 dated Jun. 13, 2006.

Int'l Search Report EP 04013772 dated Apr. 1, 2005.

Int'l Search Report EP 05013895 dated Oct. 14, 2005.

Int'l Search Report EP 05017281 dated Nov. 16, 2005.  
Int'l Search Report EP 06006716 dated Aug. 4, 2006.  
Int'l Search Report PCT/US01/11224 dated Nov. 13, 2001.  
Int'l Search Report EP 06014461.5 dated Oct. 20, 2006.  
Int'l Search Report EP 06020584.6 dated Jan. 12, 2007.  
Int'l Search Report EP 06020583.8 dated Jan. 30, 2007.  
Int'l Search Report EP 06020756.0 dated Feb. 5, 2007.  
Int'l Search Report EP 06024123.9 dated Feb. 26, 2007.  
Int'l Search Report EP 05013463.4 dated Sep. 28, 2005.  
Int'l Search Report EP 05019130.3 dated Oct. 18, 2005.  
Int'l Search Report EP 05020665.5 dated Feb. 16, 2006.  
Int'l Search Report EP 05020666.3 dated Feb. 17, 2006.  
Int'l Search Report EP 05021779.3 dated Jan. 18, 2006.  
Int'l Search Report EP 05021197.8 dated Jan. 31, 2006.  
Int'l Search Report EP 0502137.7 dated Jan. 13, 2006.  
Int'l Search Report—extended- EP 05021937.7 dated Mar. 6, 2006.  
Int'l Search Report EP 05023017.6 dated Feb. 16, 2006.

Int'l Search Report EP 05021780.1 dated Feb. 9, 2006.  
Int'l Search Report EP 06002279.5 dated Mar. 22, 2006.  
Int'l Search Report EP 04 752343.6 dated Jul. 20, 2007.  
Int'l Search Report EP 06 024122.1 dated Mar. 19, 2007.  
Int'l Search Report EP 07 001480.8 dated Apr. 12, 2007.  
Int'l Search Report EP 07 001488.1 dated May 29, 2007.  
Int'l Search Report—Extended EP 07 009029.5 dated Jul. 12, 2007.  
Int'l Search Report EP 07 009321.6 dated Aug. 17, 2007.  
Int'l Search Report EP 06 020574.7 dated Sep. 21, 2007.  
Int'l Search Report EP 07 010672.9 dated Oct. 1, 2007.  
Int'l Search Report EP 07 013779.9 dated Oct. 18, 2007.  
Int'l Search Report EP 07 009026.1 dated Sep. 12, 2007.  
Int'l Search Report EP 07 015601.3 dated Dec. 6, 2007.  
Int'l Search Report EP 07 015191.5 dated Dec. 19, 2007.  
Int'l Search Report EP 07 020283.3 dated Jan. 16, 2008.

\* cited by examiner








FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8






FIG. 12




FIG. 13




FIG. 14






FIG. 15




FIG. 16

FIG. 17




FIG. 18




FIG. 20

FIG. 21

FIG. 19




FIG. 23

FIG. 22






FIG. 26




FIG. 27




FIG. 29






FIG. 28



**FIG. 30**



**FIG. 31**




FIG. 32




FIG. 33



## 1

## SINGLE ACTION TISSUE SEALER

## BACKGROUND

The present disclosure relates to an electrosurgical forceps and more particularly, the present disclosure relates to an endoscopic bipolar electrosurgical forceps for manipulating, clamping, sealing and cutting tissue in a single action.

## TECHNICAL FIELD

Electrosurgical forceps utilize both mechanical clamping action and electrical energy to affect hemostasis by heating the tissue and blood vessels to coagulate, cauterize and/or seal tissue. As an alternative to open forceps for use with open surgical procedures, many modern surgeons use endoscopes and endoscopic instruments for remotely accessing organs through smaller, puncture-like incisions. As a direct result thereof, patients tend to benefit from less scarring and reduced healing time.

Endoscopic instruments are inserted into the patient through a cannula, or port, which has been made with a trocar. Typical sizes for cannulas range from about three millimeters to about 12 millimeters. Smaller cannulas are usually preferred, which, as can be appreciated, ultimately presents a design challenge to instrument manufacturers who look for ways to make endoscopic instruments that fit through the smaller cannulas.

Many endoscopic surgical procedures require cutting or ligating blood vessels or vascular tissue. Due to the inherent spatial considerations of the surgical cavity, surgeons often have difficulty suturing vessels or performing other traditional methods of controlling bleeding, e.g., clamping and/or tying-off transected blood vessels. By utilizing an endoscopic electrosurgical forceps, a surgeon can either cauterize, coagulate/desiccate and/or simply reduce or slow bleeding simply by controlling the intensity, frequency and duration of the electrosurgical energy applied through the jaw members to the tissue. Most small blood vessels, i.e., in the range below two millimeters in diameter, can often be closed using standard electrosurgical instruments and techniques. However, if a larger vessel is ligated, it may be necessary for the surgeon to convert the endoscopic procedure into an open-surgical procedure and thereby abandon the benefits of endoscopic surgery. Alternatively, the surgeon can seal the larger vessel or tissue.

It is thought that the process of coagulating vessels is fundamentally different from electrosurgical vessel sealing. For the purposes herein, "coagulation" is defined as a process of desiccating tissue wherein the tissue cells are ruptured and dried. "Vessel sealing" or "tissue sealing" is defined as the process of liquefying the collagen in the tissue so that it reforms into a fused mass. Coagulation of small vessels is sufficient to permanently close them, while larger vessels need to be sealed to assure permanent closure.

In order to effectively seal larger vessels (or tissue) two predominant mechanical parameters should be accurately controlled—the pressure applied to the vessel (tissue) and the gap distance between the electrodes—both of which are affected by the thickness of the sealed vessel. More particularly, accurate application of pressure is important to oppose the walls of the vessel; to reduce the tissue impedance to a low enough value that allows enough electrosurgical energy through the tissue; to overcome the forces of expansion during tissue heating; and to contribute to the end tissue thickness which is an indication of a good seal. It has been determined that a typical fused vessel wall is optimum between about

## 2

0.001 and about 0.006 inches. Below this range, the seal may shred or tear and above this range the lumens may not be properly or effectively sealed.

With respect to smaller vessels, the pressure applied to the tissue tends to become less relevant whereas the gap distance between the electrically conductive surfaces becomes more significant for effective sealing. In other words, the chances of the two electrically conductive surfaces touching during activation increases as vessels become smaller.

As mentioned above, in order to properly and effectively seal larger vessels or tissue, a greater closure force between opposing jaw members is required. It is known that a large closure force between the jaws typically requires a large moment about the pivot for each jaw. This presents a design challenge because the jaw members are typically affixed with pins which are positioned to have small moment arms with respect to the pivot of each jaw member. A large force, coupled with a small moment arm, is undesirable because the large forces may shear the pins. As a result, designers compensate for these large closure forces by either designing instruments with metal pins and/or by designing instruments which at least partially offload these closure forces to reduce the chances of mechanical failure. As can be appreciated, if metal pivot pins are employed, the metal pins should be insulated to avoid the pin acting as an alternate current path between the jaw members which may prove detrimental to effective sealing.

Increasing the closure forces between electrodes may have other undesirable effects, e.g., it may cause the opposing electrodes to come into close contact with one another which may result in a short circuit and a small closure force may cause pre-mature movement of the tissue during compression and prior to activation. As a result thereof, providing an instrument which consistently provides the appropriate closure force between opposing electrodes within a preferred pressure range will enhance the chances of a successful seal. As can be appreciated, relying on a surgeon to manually provide the appropriate closure force within the appropriate range on a consistent basis would be difficult and the resultant effectiveness and quality of the seal may vary. Moreover, the overall success of creating an effective tissue seal is greatly reliant upon the user's expertise, vision, dexterity, and experience in judging the appropriate closure force to uniformly, consistently and effectively seal the vessel. In other words, the success of the seal would greatly depend upon the ultimate skill of the surgeon rather than the efficiency of the instrument.

It has been found that the pressure range for assuring a consistent and effective seal is between about 3 kg/cm<sup>2</sup> to about 16 kg/cm<sup>2</sup> and, desirably, within a working range of about 7 kg/cm<sup>2</sup> to about 13 kg/cm<sup>2</sup>. Manufacturing an instrument which is capable of providing a closure pressure within this working range has been shown to be effective for sealing arteries, tissues and other vascular bundles.

Various force-actuating assemblies have been developed in the past for providing the appropriate closure forces to affect vessel sealing. For example, one such actuating assembly has been developed by Valleylab, Inc., of Boulder Colo., a division of Tyco Healthcare LP, for use with Valleylab's vessel sealing and dividing instrument commonly sold under the trademark LIGASURE ATLAS®. This assembly includes a four-bar mechanical linkage, a spring and a drive assembly which cooperate to consistently provide and maintain tissue pressures within the above working ranges. The LIGASURE ATLAS® is presently designed to fit through a 10 mm cannula and includes a bi-lateral jaw closure mechanism which is activated by a foot switch. A trigger assembly extends a knife

distally to separate the tissue along the tissue seal. A rotating mechanism is associated with distal end of the handle to allow a surgeon to selectively rotate the jaw members to facilitate grasping tissue. Co-pending U.S. application Ser. Nos. 10/179,863 and 10/116,944 and PCT Application Serial Nos. PCT/US01/01890 and PCT/7201/11340 describe in detail the operating features of the LIGASURE ATLAS® and various methods relating thereto. The contents of all of these applications are hereby incorporated by reference herein.

It would be desirable to develop an instrument that reduces the number of steps it takes to perform the tissue seal and cut. Preferably, the instrument would be able to manipulate, clamp, seal and cut tissue in a single action (e.g., by squeezing a handle).

### SUMMARY

The present disclosure relates to an endoscopic bipolar forceps which includes a housing and a shaft affixed to the distal end of the housing. Preferably, the shaft includes a diameter such that the shaft is freely insertable through a trocar. The shaft also includes a longitudinal axis defined therethrough and a pair of first and second jaw members attached to a distal end thereof. The forceps includes a drive assembly for moving the first jaw member relative to the second member from a first position wherein the jaw members are disposed in spaced relation relative to each other to a second position wherein the jaw members cooperate to grasp tissue therebetween. A movable handle is included which is rotatable about a pivot located above the longitudinal axis of the shaft. Movement of the movable handle mechanically cooperates with internal components to move the jaw members from the open and closed positions, to clamp tissue, to seal tissue and to cut tissue. Advantageously, the pivot is located a fixed distance above the longitudinal axis to provide lever-like mechanical advantage to a drive flange of the drive assembly. The drive flange is located generally along the longitudinal axis. The forceps is connected to a source of electro-surgical energy which carries electrical potentials to each respective jaw member such that the jaw members are capable of conducting bipolar energy through tissue held therebetween to affect a tissue seal.

The forceps includes a switch disposed within the housing which is electromechanically connected to the energy source. Advantageously, the switch allows a user to supply bipolar energy to the jaw members to affect a tissue seal. The switch is activated by contact from a cutter lever or the movable handle itself when a user continues to compress the movable handle after the tissue has been clamped.

The forceps includes an advanceable knife assembly for cutting tissue in a forward direction along the tissue seal. The knife assembly is advanced when a user continues to compress the movable handle after the tissue has been sealed, forcing the cutter lever forward. A rotating assembly may also be included for rotating the jaw members about the longitudinal axis defined through the shaft.

In one embodiment, the movable jaw member includes a first electrical potential and the fixed jaw member includes a second electrical potential. A lead connects the movable jaw member to the first potential and a conductive tube (which is disposed through the shaft) conducts a second electrical potential to the fixed jaw member. Advantageously, the conductive tube is connected to the rotating assembly to permit selective rotation of the jaw members.

In one embodiment, the drive assembly includes a reciprocating sleeve which upon activation of the movable handle, translates atop the rotating conductive tube to move the mov-

able jaw member relative to the fixed jaw member. In one embodiment, the movable jaw member includes a detent which extends beyond the fixed jaw member which is designed for engagement with the reciprocating sleeve such that, upon translation thereof, the movable jaw member moves relative to the fixed jaw member. Advantageously, a spring is included with the drive assembly to facilitate actuation of the movable handle and to ensure the closure force is maintained within the working range of about 3 kg/cm<sup>2</sup> to about 16 kg/cm<sup>2</sup> and, preferably, about 7 kg/cm<sup>2</sup> to about 13 kg/cm<sup>2</sup>.

In one embodiment, at least one of the jaw members includes a series of stop members disposed thereon for regulating the distance between the jaw members (i.e., creating a gap between the two opposing jaw members) during the sealing process. As can be appreciated, regulating the gap distance between opposing jaw members along with maintaining the closing pressure to within the above-described ranges will produce a reliable and consistent tissue seal.

The present disclosure also relates to an endoscopic bipolar forceps which includes a shaft having a movable jaw member and a fixed jaw member at a distal end thereof. The forceps also includes a drive assembly for moving the movable jaw member relative to the fixed jaw member from a first position wherein the movable jaw member is disposed in spaced relation relative to the fixed jaw member to a second position wherein the movable jaw member is closer to the fixed jaw member for manipulating tissue. A movable handle is included which actuates the drive assembly to move the movable jaw member.

The forceps connects to a source of electro-surgical energy which is conducted to each jaw member such that the jaw members are capable of conducting bipolar energy through tissue held therebetween to affect a tissue seal. Advantageously, the forceps also includes a selectively advanceable knife assembly for cutting tissue in a distal direction along the tissue seal and a stop member disposed on at least one of the jaw members for regulating the distance between jaw members during sealing.

### BRIEF DESCRIPTION OF THE DRAWINGS

Various embodiments of the subject instrument are described herein with reference to the drawings wherein:

FIG. 1 is a partial schematic view of one embodiment of an endoscopic bipolar forceps having a movable thumb handle in an unactuated position according to one aspect of the present disclosure;

FIG. 2 is a partial schematic view of the forceps of FIG. 1 illustrated in a partially actuated position;

FIG. 3 is a partial schematic view of another embodiment of an endoscopic bipolar forceps having a movable finger handle illustrated in a partially actuated position;

FIG. 4 is an enlarged, perspective view of an end effector assembly with jaw members shown in an open configuration;

FIG. 5 is an enlarged, side view of the end effector assembly of FIG. 4;

FIG. 6 is an enlarged, perspective view of the tissue contacting side of an upper jaw member of the end effector assembly;

FIG. 7 is an enlarged, broken perspective view showing the end effector assembly and highlighting a cam-like closing mechanism which cooperates with a reciprocating pull sleeve to move the jaw members relative to one another;

FIG. 8 is a full perspective view of the end effector assembly of FIG. 7;

## 5

FIG. 9 is a left, perspective view of a rotating assembly, drive assembly, knife assembly and lower jaw member according to the present disclosure;

FIG. 10 is a rear, perspective view of the rotating assembly, drive assembly and knife assembly;

FIG. 11 is an enlarged, top, perspective view of the end effector assembly with parts separated;

FIG. 12 is an enlarged, perspective view of the knife assembly;

FIG. 13 is an enlarged, perspective view of the rotating assembly;

FIG. 14 is an enlarged, perspective view of the drive assembly;

FIG. 15 is an enlarged, perspective view of the knife assembly with parts separated;

FIG. 16 is an enlarged view of the indicated area of detail of FIG. 15;

FIG. 17 is a greatly-enlarged, perspective view of a distal end of the knife assembly;

FIG. 18 is a greatly-enlarged, perspective view of a knife drive of the knife assembly;

FIG. 19 is an enlarged, perspective view of the rotating assembly and low jaw member with parts separated;

FIG. 20 is a cross section along line 20-20 of FIG. 19;

FIG. 21 is a greatly-enlarged, perspective view of the lower jaw member;

FIG. 22 is an enlarged, perspective view of the drive assembly;

FIG. 23 is an enlarged perspective view of the drive assembly of FIG. 22 with parts separated;

FIG. 24 is a greatly-enlarged, cross section of the shaft taken along line 24-24 of FIG. 25;

FIG. 25 is a side, cross section of the shaft and end effector assembly;

FIG. 26 is a greatly-enlarged, perspective view of a handle assembly and latch mechanism for use with the forceps;

FIG. 27 is a greatly-enlarged view of an end effector;

FIG. 28 is a greatly-enlarged view of the drive assembly;

FIG. 29 is an enlarged, rear, perspective view of the end effector shown grasping tissue;

FIG. 30 is an enlarged view of a tissue seal;

FIG. 31 is a side, cross section of a tissue seal taken along line 31-31 of FIG. 30;

FIG. 32 is an enlarged view of the end effector showing distal translation of the knife; and

FIG. 33 is a side, cross section of a tissue seal after separation by the knife assembly.

## DETAILED DESCRIPTION

Turning now to FIGS. 1-3, one embodiment of an endoscopic bipolar forceps 10 is shown for use with various surgical procedures and generally includes a housing 20, a handle assembly 30, a rotating assembly 80, an end effector assembly 100, a knife assembly 140 (see FIGS. 10, 12, 15-18), a drive assembly 150, a switch 500 and a latch assembly 600 which all mutually cooperate to grasp, seal and divide tubular vessels and vascular tissue 420 (FIG. 29). Although the majority of the figure drawings depict a bipolar forceps 10 for use in connection with endoscopic surgical procedures, the present disclosure may be used for more traditional open surgical procedures. For the purposes herein, the forceps 10 is described in terms of an endoscopic instrument, however, it is contemplated that an open version of the forceps may also include the same or similar operating components and features as described below.

## 6

Forceps 10 includes a shaft 12 which has a distal end 16 dimensioned to mechanically engage the end effector assembly 100 and a proximal end 14 which mechanically engages the housing 20. In the drawings and in the descriptions which follow, the term “proximal,” as is traditional, will refer to the end of the forceps 10 which is closer to the user, while the term “distal” will refer to the end which is farther from the user.

Forceps 10 also includes an electrosurgical cable 310 which connects the forceps 10 to a source of electrosurgical energy, e.g., a generator (not shown). Generators such as those sold by Valleylab—a division of Tyco Healthcare LP, located in Boulder, Colo. are contemplated for use as a source of electrosurgical energy, e.g., FORCE EZ™ Electrosurgical Generator, FORCE FX™ Electrosurgical Generator, FORCE IC™, FORCE 2™ Generator, SurgiStat™ II. One such system is described in commonly-owned U.S. Pat. No. 6,033,399 entitled “ELECTROSURGICAL GENERATOR WITH ADAPTIVE POWER CONTROL,” the entire contents of which are hereby incorporated by reference herein. Other systems have been described in commonly-owned U.S. Pat. No. 6,187,003 entitled “BIPOLAR ELECTROSURGICAL INSTRUMENT FOR SEALING VESSELS,” the entire contents of which are also incorporated by reference herein.

In one embodiment, the generator includes various safety and performance features including isolated output, independent activation of accessories. In one embodiment, the electrosurgical generator includes Valleylab’s Instant Response™ technology features which provide an advanced feedback system to sense changes in tissue 200 times per second and adjust voltage and current to maintain appropriate power. The Instant Response™ technology is believed to provide one or more of the following benefits to surgical procedure:

Consistent clinical effect through all tissue types;

Reduced thermal spread and risk of collateral tissue damage;

Less need to “turn up the generator”; and

Designed for the minimally invasive environment.

Cable 310 is internally divided into cable leads (not shown) which each transmit electrosurgical energy through their respective feed paths through the forceps 10 to the end effector assembly 100. A detailed discussion of the cable leads and their connections through the forceps 10 is described in commonly-assigned, co-pending U.S. application Ser. No. 10/460,926 entitled “VESSEL SEALER AND DIVIDER FOR USE WITH SMALL TROCARS AND CANNULAS” by Dycus et al., which is hereby incorporated by reference in its entirety herein.

Handle assembly 30 includes a fixed handle 50, a movable handle 40, a cutter lever 700 and a handle detent 710. Fixed handle 50 is integrally associated with housing 20 and movable handle 40 is movable relative to fixed handle 50 as explained in more detail below with respect to the operation of the forceps 10.

In one embodiment, rotating assembly 80 is integrally associated with the housing 20 and is rotatable approximately 180 degrees in either direction about a longitudinal axis “A” (FIGS. 1 and 3). Details of the rotating assembly 80 are described in more detail with respect to FIGS. 9 and 10.

Housing 20 may be formed from two housing halves (not shown) which each include a plurality of interfaces which are dimensioned to mechanically align and engage one another to form housing 20 and enclose the internal working components of forceps 10. A detailed discussion of the housing halves and how they mechanically engage with one another is described in commonly-assigned, co-pending U.S. applica-

tion Ser. No. 10/460,926 entitled "VESSEL SEALER AND DIVIDER FOR USE WITH SMALL TROCARS AND CANNULAS" by Dycus et al., which is hereby incorporated by reference in its entirety herein.

It is envisioned that a plurality of additional interfaces (not shown) may be disposed at various points around the periphery of housing halves for ultrasonic welding purposes, e.g., energy direction/deflection points. It is also contemplated that housing halves (as well as the other components described below) may be assembled together in any fashion known in the art. For example, alignment pins, snap-like interfaces, tongue and groove interfaces, locking tabs, adhesive ports, etc. may all be utilized either alone or in combination for assembly purposes.

Rotating assembly 80 includes two halves 82a and 82b (see FIGS. 13 and 19) which, when assembled, form the rotating assembly 80 which, in turn, houses the drive assembly 150 and the knife assembly 140. Half 82b includes a series of detents/flanges 375a, 375b, 375c and 375d which are dimensioned to engage a pair of corresponding sockets or other mechanical interfaces (not shown) disposed within rotating half 82a. In one embodiment, movable handle 40 is of unitary construction and is operatively connected to the housing 20 and the fixed handle 50 during the assembly process.

As mentioned above, end effector assembly 100 is attached at the distal end 14 of shaft 12 and includes a pair of opposing jaw members 110 and 120. Movable handle 40 of handle assembly 30 is in mechanical cooperation with drive assembly 150 which, together, mechanically cooperate to impart movement of the jaw members 110 and 120 from an open position wherein the jaw members 110 and 120 are disposed in spaced relation relative to one another, to a clamping or closed position wherein the jaw members 110 and 120 cooperate to grasp tissue 420 (FIG. 29) therebetween.

It is envisioned that jaw members 110 and 120 of end effector assembly 100 may be curved (as illustrated in FIG. 3) in order to reach specific anatomical structures and promote more consistent seals for certain procedures. For example, it is contemplated that dimensioning the jaw members 110 and 120 at an angle of about 45 degrees to about 70 degrees is preferred for accessing and sealing specific anatomical structures relevant to prostatectomies and cystectomies, e.g., the dorsal vein complex and the lateral pedicles. Other angles may be preferred for different surgical procedures. Such an end effector assembly with curved jaw members is described in commonly-assigned, co-pending U.S. application Ser. No. 10/834,764 entitled "ELECTROSURGICAL INSTRUMENT WHICH REDUCES DAMAGE TO ADJACENT TISSUE," by Dycus et al., which is hereby incorporated by reference in its entirety herein.

It is envisioned that the forceps 10 may be designed such that it is fully or partially disposable depending upon a particular purpose or to achieve a particular result. For example, end effector assembly 100 may be selectively and releasably engageable with the distal end 16 of the shaft 12 and/or the proximal end 14 of shaft 12 may be selectively and releasably engageable with the housing 20 and the handle assembly 30. In either of these two instances, the forceps 10 would be considered "partially disposable" or "reposable," i.e., a new or different end effector assembly 100 (or end effector assembly 100 and shaft 12) selectively replaces the old end effector assembly 100 as needed. As can be appreciated, the presently disclosed electrical connections would have to be altered to modify the instrument to a reposable forceps.

Turning now to the more detailed features of the present disclosure, movable handle 40 includes a finger loop 41 which has an aperture 42 defined therethrough which enables

a user to grasp and move the movable handle 40 relative to the fixed handle 50. FIGS. 1 and 2 illustrate a movable handle 40 with finger loop 41 designed to be grasped and moved by a thumb, while FIG. 3 illustrates a movable handle 40 with finger loop 41 designed to be grasped and moved by one or more fingers. Further, the movable handle 40 of FIGS. 1 and 2 is on the proximal side of fixed handle 50, while the movable handle 40 of FIG. 3 is on the distal side of fixed handle 50. Movable handle 40 may also include one or more ergonomically-enhanced gripping elements (not shown) disposed along the inner peripheral edge of aperture 42 or on fixed handle 50 which is designed to facilitate gripping of the handles 40 and 50 during activation. It is envisioned that the gripping element may include one or more protuberances, scallops and/or ribs to enhance gripping.

As best seen in FIGS. 1 and 2, movable handle 40 is selectively moveable about a pivot point 29 from a first position (FIG. 1) relative to fixed handle 50 to a second position (FIG. 2) in closer proximity to the fixed handle 50 which, as explained below, imparts movement of the jaw members 110 and 120 relative to one another. It is contemplated that there may be intermediate positions between those shown in FIGS. 1 and 2, e.g., discrete closure points which correspond to ratchet positions as discussed in more detail below. Additionally, continued movement of the moveable handle 40 towards the fixed handle 50 first engages switch 500, which causes the tissue to be sealed, and then engages knife assembly 140, which cuts the tissue. Operation of the forceps is discussed further below.

As best seen in FIGS. 1-3 and 26, the lower end of the movable handle 40 includes a flange 90. Flange 90 also includes an end 95 which rides within a predefined channel 52 (see FIG. 26) and mechanically engages with ramps 57 disposed within fixed handle 50. Additional features with respect to the end 95 are explained below in the detailed discussion of the operational features of the forceps 10.

Movable handle 40 is designed to provide a distinct mechanical advantage over conventional handle assemblies due to the position of the pivot point 29 relative to the longitudinal axis "A" of the shaft 12 and the disposition of the drive assembly 150 along longitudinal axis "A." In other words, it is envisioned that by positioning the pivot point 29 above the drive assembly 150, the user gains lever-like mechanical advantage to actuate the jaw members 110 and 120 enabling the user to close the jaw members 110 and 120 with lesser force while still generating the required forces necessary to affect a proper and effective tissue seal and to cut the tissue 420. It is also envisioned that the unilateral design of the end effector assembly 100 will also increase mechanical advantage as explained in more detail below.

As shown best in FIGS. 4-8, the end effector assembly 100 includes opposing jaw members 110 and 120 which cooperate to effectively grasp tissue 420 for sealing purposes. The end effector assembly 100 is designed as a unilateral assembly in this particular embodiment, i.e., jaw member 120 is fixed relative to the shaft 12 and jaw member 110 pivots about a pivot pin 103 to grasp tissue 420. A bilateral jaw assembly is also envisioned wherein both jaw members are movable.

More particularly, the unilateral end effector assembly 100 includes one stationary or fixed jaw member 120 mounted in fixed relation to the shaft 12 and pivoting jaw member 110 mounted about a pivot pin 103 attached to the stationary jaw member 120. A reciprocating sleeve 60 is slidingly disposed within the shaft 12 and is remotely operable by the drive assembly 150. The pivoting jaw member 110 includes a detent or protrusion 117 which extends from jaw member 110 through an aperture 62 disposed within the reciprocating

sleeve 60 (FIG. 8). The pivoting jaw member 110 is actuated by sliding the sleeve 60 axially within the shaft 12 such that a distal end 63 of the aperture 62 abuts against the detent 117 on the pivoting jaw member 110 (see FIGS. 7 and 8). Pulling the sleeve 60 proximally closes the jaw members 110 and 120 about tissue 420 grasped therebetween and pushing the sleeve 60 distally opens the jaw members 110 and 120 for grasping purposes.

As best illustrated in FIGS. 4 and 6, a knife channel 115a and 115b runs through the center of the jaw members 110 and 120, respectively, such that a knife blade 185 from the knife assembly 140 can cut the tissue 420 grasped between the jaw members 110 and 120 when the jaw members 110 and 120 are in a closed position. More particularly, the knife blade 185 can only be advanced through the tissue 420 when the jaw members 110 and 120 are closed thus preventing accidental or premature activation of the knife blade 185 through the tissue 420. Put simply, the knife channel 115 (made up of half channels 115a and 115b) is blocked when the jaws members 110 and 120 are opened and the knife channel 115 is aligned for distal activation when the jaw members 110 and 120 are closed (see FIGS. 25 and 27). It is also envisioned that the unilateral end effector assembly 100 may be structured such that electrical energy can be routed through the sleeve 60 at the protrusion 117 contact point with the sleeve 60 or using a “brush” or lever (not shown) to contact the back of the moving jaw member 110 when the jaw member 110 closes. In this instance, the electrical energy would be routed through the protrusion 117 to the stationary jaw member 120. Alternatively, a cable lead 311 may be routed to energize the stationary jaw member 120 and the other electrical potential may be conducted through the sleeve 60 and transferred to the pivoting jaw member 110 which establishes electrical continuity upon retraction of the sleeve 60. It is envisioned that this particular envisioned embodiment will provide at least two important safety features: 1) the knife blade 185 cannot extend while the jaw members 110 and 120 are opened; and 2) electrical continuity to the jaw members 110 and 120 is made only when the jaw members are closed. The illustrated forceps 10 only includes the knife channel 115.

As best shown in FIG. 4, jaw member 110 also includes a jaw housing 116 which has an insulative substrate or insulator 114 and an electrically conductive surface 112. In one embodiment, insulator 114 is dimensioned to securely engage the electrically conductive sealing surface 112. This may be accomplished by stamping, by overmolding, by overmolding a stamped electrically conductive sealing plate and/or by overmolding a metal injection molded seal plate. For example and as shown in FIG. 11, the electrically conductive sealing plate 112 includes a series of upwardly extending flanges 111a and 111b which are designed to matingly engage the insulator 114. The insulator 114 includes a shoe-like interface 107 disposed at a distal end thereof which is dimensioned to engage the jaw housing 116 in a slip-fit manner. The shoe-like interface 107 may also be overmolded about the outer periphery of the jaw 110 during a manufacturing step. It is envisioned that cable lead 311 terminates within the shoe-like interface 107 at the point where cable lead 311 electrically connects to the seal plate 112 (not shown). The movable jaw member 110 also includes a wire channel 113 which is designed to guide cable lead 311 into electrical continuity with sealing plate 112.

All of these manufacturing techniques produce jaw member 110 having an electrically conductive surface 112 which is substantially surrounded by an insulating substrate 114. In one embodiment, the insulator 114, electrically conductive sealing surface 112 and the outer, non-conductive jaw hous-

ing 116 are dimensioned to limit and/or reduce many of the known undesirable effects related to tissue sealing, e.g., flash-over, thermal spread and stray current dissipation. Alternatively, it is also envisioned that the jaw members 110 and 120 may be manufactured from a ceramic-like material and the electrically conductive surface(s) 112 may be coated onto the ceramic-like jaw members 110 and 120.

Jaw member 110 includes a pivot flange 118 (FIG. 6) which includes a protrusion 117. Protrusion 117 extends from pivot flange 118 and includes an arcuately-shaped inner surface 111 dimensioned to matingly engage the aperture 62 of sleeve 60 upon retraction thereof. Pivot flange 118 also includes a pin slot 119 which is dimensioned to engage pivot pin 103 to allow jaw member 110 to rotate relative to jaw member 120 upon retraction of the reciprocating sleeve 60. As explained in more detail below, pivot pin 103 also mounts to the stationary jaw member 120 through a pair of apertures 101a and 101b disposed within a proximal portion of the jaw member 120.

It is envisioned that the electrically conductive sealing surface 112 may also include an outer peripheral edge which has a pre-defined radius and the insulator 114 meets the electrically conductive sealing surface 112 along an adjoining edge of the sealing surface 112 in a generally tangential position. In one embodiment, at the interface, the electrically conductive surface 112 is raised relative to the insulator 114. These and other envisioned embodiments are discussed in co-pending, commonly assigned Application Serial No. PCT/US01/11412 entitled “ELECTROSURGICAL INSTRUMENT WHICH REDUCES COLLATERAL DAMAGE TO ADJACENT TISSUE” by Johnson et al. and co-pending, commonly assigned Application Serial No. PCT/US01/11411 entitled “ELECTROSURGICAL INSTRUMENT WHICH IS DESIGNED TO REDUCE THE INCIDENCE OF FLASHOVER” by Johnson et al., both of which are hereby incorporated by reference in their entirety herein.

The electrosurgical seal and/or cut can be made utilizing various electrode assemblies on the jaw members, such that energy is applied to the tissue through sealing plates. This and other envisioned electrosurgical sealing and cutting techniques are discussed in co-pending, commonly assigned application Ser. No. 10/932,612 entitled “VESSEL SEALING INSTRUMENT WITH ELECTRICAL CUTTING MECHANISM” by Johnson et al., which is hereby incorporated by reference in its entirety herein.

In one embodiment, the electrically conductive surface 112 and the insulator 114, when assembled, form a longitudinally-oriented slot 115a defined therethrough for reciprocation of the knife blade 185. It is envisioned that the knife channel 115a cooperates with a corresponding knife channel 115b defined in stationary jaw member 120 to facilitate longitudinal extension of the knife blade 185 along a preferred cutting plane to effectively and accurately separate the tissue 420 along the formed tissue seal 450 (see FIGS. 30 and 33).

Jaw member 120 includes similar elements to jaw member 110 such as jaw housing 126 having an insulator 124 and an electrically conductive sealing surface 122 which is dimensioned to securely engage the insulator 124. Likewise, the electrically conductive surface 122 and the insulator 124, when assembled, include a longitudinally-oriented channel 115a defined therethrough for reciprocation of the knife blade 185. As mentioned above, when the jaw members 110 and 120 are closed about tissue 420, knife channels 115a and 115b form a complete knife channel 115 to allow longitudinal extension of the knife blade 185 in a distal fashion to sever tissue 420 along the tissue seal 450. It is also envisioned that the knife channel 115 may be completely disposed in one of

## 11

the two jaw members, e.g., jaw member **120**, depending upon a particular purpose. It is envisioned that the fixed jaw member **120** may be assembled in a similar manner as described above with respect to jaw member **110**.

As best seen in FIG. 4, jaw member **120** includes a series of stop members **750** disposed on the inner facing surfaces of the electrically conductive sealing surface **122** to facilitate gripping and manipulation of tissue and to define a gap "G" (FIG. 29) between opposing jaw members **110** and **120** during sealing and cutting of tissue. It is envisioned that the series of stop members **750** may be employed on one or both jaw members **110** and **120** depending upon a particular purpose or to achieve a desired result. A detailed discussion of these and other envisioned stop members **750** as well as various manufacturing and assembling processes for attaching and/or affixing the stop members **750** to the electrically conductive sealing surfaces **112**, **122** are described in commonly-assigned, co-pending U.S. Application Serial No. PCT/US01/11413 entitled "VESSEL SEALER AND DIVIDER WITH NON-CONDUCTIVE STOP MEMBERS" by Dycus et al. which is hereby incorporated by reference in its entirety herein.

Jaw member **120** is designed to be fixed to the end of a rotating tube **160** which is part of the rotating assembly **80** such that rotation of the tube **160** will impart rotation to the end effector assembly **100** (see FIGS. 13 and 19). Jaw member **120** includes a rear C-shaped cuff **170** having a slot **177** defined therein which is dimensioned to receive a slide pin **171**. More particularly, slide pin **171** includes a slide rail **176** which extends substantially the length thereof which is dimensioned to slide into friction-fit engagement within slot **177**. A pair of chamfered plates **172a** and **172b** extend generally radially from the slide rail **176** and include a radius which is substantially the same radius as the outer periphery of the rotating tube **160** such that the shaft **12** can encompass each of the same upon assembly.

As best shown in FIGS. 19 and 20, the rotating tube **160** includes an elongated guide slot **167** disposed in an upper portion thereof which is dimensioned to carry cable lead **311** therealong. The chamfered plates **172a** and **172b** also form a wire channel **175** which is dimensioned to guide the cable lead **311** from the tube **160** and into the movable jaw member **110** (see FIG. 4). Cable lead **311** carries a first electrical potential to movable jaw **110**.

As shown in FIG. 19, the distal end of the tube **160** is generally C-shaped to include two upwardly extending flanges **162a** and **162b** which define a cavity **165** for receiving the proximal end of the fixed jaw member **120** inclusive of C-shaped cuff **170** and slide pin **171** (see FIG. 21). In one embodiment, the tube cavity **165** retains and secures the jaw member **120** in a friction-fit manner, however, the jaw member **120** may be welded to the tube **160** depending upon a particular purpose. Tube **160** also includes an inner cavity **169** defined therethrough which reciprocates the knife assembly **140** upon distal activation thereof and an elongated guide rail **163** which guides the knife assembly **140** during distal activation (see FIG. 20). The details with respect to the knife assembly are explained in more detail with respect to FIGS. 15-18. The proximal end of tube **160** includes a laterally oriented slot **168** which is designed to interface with the rotating assembly **80** as described below.

FIG. 19 also shows the rotating assembly **80** which includes C-shaped rotating halves **82a** and **82b** which, when assembled about tube **160**, form a generally circular rotating member **82**. More particularly, each rotating half, e.g., **82b**, includes a series of mechanical interfaces **375a**, **375b**, **375c** and **375d** which matingly engage a corresponding series of mechanical interfaces in the other half, e.g., **82a**, to form

## 12

rotating member **82**. Half **82b** also includes a tab **89b** which, together with a corresponding tab **89a** disposed on half **82a** (phantomly illustrated), cooperate to matingly engage slot **168** disposed on tube **160**. As can be appreciated, this permits selective rotation of the tube **160** about axis "A" by manipulating the rotating member **82** in the direction of the arrow "B" (see FIG. 2).

As best shown in the exploded view of FIG. 11, jaw members **110** and **120** are pivotably mounted with respect to one another such that jaw member **110** pivots in a unilateral fashion from a first open position to a second closed position for grasping and manipulating tissue **420**. More particularly, fixed jaw member **120** includes a pair of proximal, upwardly extending flanges **125a** and **125b** which define a cavity **121** dimensioned to receive flange **118** of movable jaw member **110** therein. As explained in detail below with respect to the operation of the jaw members **110** and **120**, proximal movement of the tube **60** engages detent **117** to pivot the jaw member **110** to a closed position.

FIGS. 1-3 show the housing **20** and the component features thereof, namely, the handle assembly **30**, the rotating assembly **80**, the knife assembly **140**, the drive assembly **150**, the switch **500**, the latch assembly **600** and a cutter lever **700**.

The housing includes two halves (constructed similarly to the halves of rotating assembly **80**, as discussed above with reference to FIG. 19) which, when mated, form housing **20**. As can be appreciated, housing **20**, once formed, houses the various assemblies identified above which will enable a user to selectively manipulate, grasp, seal and sever tissue **420** in a single action. In one embodiment, each half of the housing includes a series of mechanical interfacing components (not shown) which align and/or mate with a corresponding series of mechanical interfaces to align the two housing halves about the inner components and assemblies. The housing halves can then be sonic welded to secure the housing halves once assembled.

The movable handle **40** includes clevis **45** which pivots about pivot point **29** to pull the reciprocating sleeve **60** along longitudinal axis "A" and force a drive flange **47** against the drive assembly **150** which, in turn, closes the jaw members **110** and **120**, as explained above. As mentioned above, the lower end of the movable handle **40** includes a flange **90** which has an end **95** which rides within a predefined channel **52** disposed within fixed handle **50** (see FIG. 26). The arrangement of the clevis **45** and the pivot point **29** of the movable handle **40** provides a distinct mechanical advantage over conventional handle assemblies due to the position of the pivot point **29** relative to the longitudinal axis "A" of the drive flange **47**. In other words, by positioning the pivot point **29** above the drive flange **47**, the user gains lever-like mechanical advantage to actuate the jaw members **110** and **120**. This reduces the overall amount of mechanical force necessary to close the jaw members **110** and **120** to affect a tissue seal.

Movable handle **40** also includes a finger loop **41** which defines opening **42** which is dimensioned to facilitate grasping the movable handle **40**. In one embodiment, finger loop **41** includes rubber insert which enhances the overall ergonomic "feel" of the movable handle **40**.

Handle assembly **30** further includes a cutter lever **700** positioned within housing **20**. When movable handle **40** is actuated (squeezed) past a certain threshold, a switch lever **502** is depressed by movable handle **40** to initiate a tissue seal cycle. A flexible detent **602** provides tactile feedback that the movable handle **40** is nearing an exit of the latch sealing zone and an end of the ramps **57**. When the movable handle **40** is pushed past the flexible detent **602**, end **95** of flange **90** drops down from ramps **57** and the user is able to return the movable

13

handle 40 proximally to open the jaw members 110, 120 without cutting the seal. The user may also close the movable handle 40 to cut the sealed tissue 420 via actuation of the lever 700. When closing movable handle 40 farther to cut tissue, end 95 contacts a latch spring 704, which provides resistance on the movable handle 40. This provides an indication to the user that tissue cutting is about to begin.

The movable handle 40 or a handle detent 710 contacts the cutter lever 700, which activates knife assembly 140, which severs the tissue 420. As can be appreciated, this prevents accidental or premature severing of tissue 420 prior to completion of the tissue seal 450. The generator may provide an audible signal or other type of feedback when the seal cycle is complete. The surgeon can then safely cut the seal or return the movable handle 40 without cutting. In an alternative method, an electromechanical, mechanical or electrical feature could prevent cutting without initially sealing or without the surgeon activating a special over-ride feature.

Fixed handle 50 includes a channel 52 (FIG. 26) defined therein which is dimensioned to receive end 95 of flange 90 when movable handle 40 is actuated. The end 95 of flange 90 is dimensioned for facile reception with ramps 57 within channel 52 of fixed handle 50. It is envisioned that flange 90 may be dimensioned to allow a user to selectively, progressively and/or incrementally move jaw members 110 and 120 relative to one another from the open to closed positions. For example, it is contemplated that end 95 and ramps 57 may include a ratchet-like interface (FIGS. 1-3) which lockingly engages the movable handle 40 and, therefore, jaw members 110 and 120 at selective, incremental positions relative to one another depending upon a particular purpose. Such a ratchet-like interface can also prevent the movable handle 40 from becoming unactuated prior to the severing of tissue 420.

It is also contemplated that the ratchet-like interface between the end 95 and ramps 57 are configured such that a catch basin is disposed between each step of the ratchet. A catch basin is described in commonly-assigned, co-pending U.S. application Ser. No. 10/460,926 entitled "VESSEL SEALER AND DIVIDER FOR USE WITH SMALL TROCARS AND CANNULAS" by Dycus et al., which is hereby incorporated by reference in its entirety herein, and can be utilized to be a stopping point between each of the functions that the movable handle 40 can control (i.e., manipulation, clamping, sealing and cutting). Employing such a catch basin will enable the user to selectively advance the movable handle 40, while ensuring the functions are carried out in the proper order.

Other mechanisms may also be employed to control and/or limit the movement of movable handle 40 relative to fixed handle 50 (and jaw members 110 and 120) such as, e.g., hydraulic, semi-hydraulic, linear actuator(s), gas-assisted mechanisms and/or gearing systems.

In one embodiment, forceps 10 includes at least one tactile element which provides tactile feedback to the user to signify when tissue is being grasped, when the tissue has been sealed and/or when the tissue has been cut. Such a tactile element may include the turning on/off of lights (not shown) on housing 20 or mechanical vibrations being created in the fixed handle 50 or movable handle 40. It is further envisioned for a sensor to be disposed on or within forceps 10 to alert to the user when one or more completion stages has occurred, i.e., at the completion of tissue grasping, tissue sealing and/or tissue cutting.

As best illustrated in FIG. 26, housing halves form an internal cavity which predefines the channel 52 within fixed handle 50 such that an entrance pathway 51 and an exit pathway 58 are formed for reciprocation of the end 95 of

14

flange 90 therein. When assembled, two ramps 57 are positioned to define a rail or track 192, such that the flange 90 can fit between the ramps 57 and end 95 moves along the track 192. During movement of end 95 of flange 90 along the entrance and exit pathways 51 and 58, respectively, the end 95 rides along track 192 according to the particular dimensions of the ramps 57, which, as can be appreciated, predetermines part of the overall pivoting motion of movable handle 40 relative to fixed handle 50.

As best illustrated in FIGS. 1 and 2, once actuated, movable handle 40 moves in a generally arcuate fashion towards fixed handle 50 about pivot point 29. End 95 of flange 90 moves along ramps 57 (shown as a single ramp in FIGS. 1-3 for clarity) which forces drive flange 47 against the drive assembly 150 which, in turn, pulls reciprocating sleeve 60 in a generally proximal direction to close jaw member 110 relative to jaw member 120. Continued actuation of movable handle 40 forces end 95 of flange 90 farther along ramps 57 and forces the movable handle 40 or cutter lever 700 into a contact 502 of switch 500, which causes the sealing of tissue 420 to occur. Continued actuation of movable handle 40 then forces movable handle detent 710 into cutter lever 700 to initiate engagement thereof. A detailed discussion of how the sealing occurs, including by electro-mechanical means, is described in commonly-assigned, co-pending U.S. application Ser. No. 10/932,612 entitled "VESSEL SEALING INSTRUMENT WITH ELECTRICAL CUTTING MECHANISM" by Johnson et al., which is hereby incorporated herein.

Continued actuation of movable handle 40 forces end 95 of flange 90 farther along the ramps 57 and into a flexible latch detent 602. The user feels a resistance when the end 95 contacts the flexible latch detent 602, which signifies that the device is about to exit the sealing position and either cut or return to its original position without cutting. To cut the tissue seal 450, the user continues to actuate the movable handle 40, such that the cutter lever 700 activates knife assembly 140, which in turn severs the tissue seal 450. At this cutting stage, the end 95 contacts a detent rib 704 which provides increased resistance to the user indicating that cutting of the tissue is about to begin. The end 95 slides distally along detent rib 704 (in the embodiment shown in FIG. 3, the detent rib 704 is contacted proximally). When the cut is complete, the detent rib 704 may stop the motion of the end 95 and allow flange 90 to follow its return path 58 (FIG. 26), as discussed above. Therefore, a full actuation of movable handle 40 grasps and clamps tissue 420, seals the tissue 420, and cuts the tissue seal 450, before returning the movable handle 40 to its original, unactuated position.

FIG. 3 illustrates the forceps 10 with the movable handle 40 located on the distal side of fixed handle 50. As can be appreciated, the internal dynamics of this embodiment are similar to those of the forceps illustrated in FIGS. 1 and 2, thus causing the forceps 10 to function in a comparable way.

It is envisioned that the flexible latch detent 602 may include one or more electro-mechanical switches, similar to those of switch 500, to seal the tissue 420. In this embodiment, handswitch 500 and contact 502 are not necessary. Details relating to the handswitch are discussed below.

It is also envisioned that latch spring 704 may include one or more mechanical or electro-mechanical switches or activations to drive the knife assembly 140 to cut the tissue seal 450, such that when end 95 contacts the latch spring 704, the tissue seal 450 is automatically severed.

The operating features and relative movements of the internal working components of the forceps 10 are shown as phantom lines in the various figures.

As the movable handle **40** is actuated and flange **90** is incorporated into channel **52** of fixed handle **50**, the drive flange **47**, through the mechanical advantage of the above-the-center pivot points, biases a ring flange **154** of drive ring **159** which, in turn, compresses a drive spring **67** against a rear ring **156** of the drive assembly **150** (FIG. **28**). As a result thereof, the rear ring **156** reciprocates sleeve **60** proximally which, in turn, closes jaw member **110** onto jaw member **120**. It is envisioned that the utilization of an over-the-center pivoting mechanism will enable the user to selectively compress the drive spring **67** a specific distance which, in turn, imparts a specific pulling load on the reciprocating sleeve **60** which is converted to a rotational torque about the jaw pivot pin **103**. As a result, a specific closure force can be transmitted to the opposing jaw members **110** and **120**.

FIG. **26** shows the initial actuation of movable handle **40** towards fixed handle **50** which causes the end **95** of flange **90** to move generally proximally and upwardly along entrance pathway **51** (this illustration is the embodiment of the forceps shown in FIG. **3**; the internal environment of the forceps of FIGS. **1** and **2** is similarly situated). During movement of the flange **90** along the entrance and exit pathways **51** and **58**, respectively, the end **95** rides along track **192** along the ramps **57**. Once the tissue **420** is clamped, sealed and cut, end **95** clears edge **193** and movable handle **40** and flange **90** are redirected to exit pathway **58**, where the movable handle **40** returns to its unactuated position.

As mentioned above, the jaw members **110** and **120** may be opened, closed and rotated to manipulate tissue **420** until sealing is desired. This enables the user to position and reposition the forceps **10** prior to activation and sealing. The end effector assembly **100** is rotatable about longitudinal axis "A" through rotation of the rotating assembly **80**. It is envisioned that the feed path of the cable lead **311** through the rotating assembly **80**, along shaft **12** and, ultimately, to the jaw member **110** enables the user to rotate the end effector assembly **100** approximately 180 degrees in both the clockwise and counterclockwise directions without tangling or causing undue strain on cable lead **311**. As can be appreciated, this facilitates the grasping and manipulation of tissue **420**.

Again as best shown in FIGS. **1** and **2**, cutter lever **700** mounts adjacent movable handle **40** and cooperates with the knife assembly **140** to selectively translate knife blade **185** through a tissue seal **450**.

Distal activation of the movable handle **40** (in the embodiment shown in FIGS. **1** and **2**) forces the cutter lever **700** distally, which, as explained in more detail below, ultimately extends the knife blade **185** through the tissue **420**. A knife spring **350** biases the knife assembly **70** in a retracted position such that after severing tissue **420** the knife blade **185** and the knife assembly **70** are automatically returned to a pre-firing position.

Drive assembly **150** includes reciprocating sleeve **60**, drive housing **158**, drive spring **67**, drive ring **159**, drive stop **155** and guide sleeve **157** which all cooperate to form the drive assembly **150**. More particularly and as best shown in FIGS. **22** and **23**, the reciprocating sleeve **60** includes a distal end **65** which as mentioned above has an aperture **62** formed therein for actuating the detent **117** of jaw member **110**. In one embodiment, the distal end **65** includes a scoop-like support member **69** for supporting a proximal end **61** of the fixed jaw member **120** therein. The proximal end **61** of the reciprocating sleeve **60** includes a slot **68** defined therein which is dimensioned to slidably support the knife assembly **70** for longitudinal reciprocation thereof to sever tissue **420**. The slot

**68** also permits retraction of the reciprocating sleeve **60** over the knife assembly **140** during the closing of jaw member **110** relative to jaw member **120**.

The proximal end **61** of the reciprocating sleeve **60** is positioned within an aperture **151** in drive housing **158** to permit selective reciprocation thereof upon actuation of the movable handle **40**. The drive spring **67** is assembled atop the drive housing **158** between a rear stop **156** of the drive housing **158** and a forward stop **154** of the drive ring **159** such that movement of the forward stop **154** compresses the drive spring **67** against the rear stop **156** which, in turn, reciprocates the drive sleeve **60**. As a result thereof, the jaw members **110** and **120** and the movable handle **40** are biased by drive spring **67** in an open configuration. The drive stop **155** is fixedly positioned atop the drive housing **158** and biases the movable handle **40** when actuated such that the drive flange **47** forces the stop **154** of the drive ring **159** proximally against the force of the drive spring **67**. The drive spring **67**, in turn, forces the rear stop **156** proximally to reciprocate the sleeve **60**. In one embodiment, the rotating assembly **80** is located proximal to the drive flange **47** to facilitate rotation of the end effector assembly **100**. The guide sleeve **157** mates with the proximal end **61** of the reciprocating sleeve **60** and affixes to the drive housing **158**. The assembled drive assembly **150** is shown best in FIG. **14**.

As best shown in FIGS. **12** and **15-18**, the knife assembly **140** includes an elongated rod **182** having a bifurcated distal end comprising prongs **182a** and **182b** which cooperate to receive a knife bar **184** therein. The knife assembly **180** also includes a proximal end **183** which is keyed to facilitate insertion into tube **160** of the rotating assembly **80**. A knife wheel **148** is secured to the knife bar **182** by a pin **143**. More particularly, the elongated knife rod **182** includes apertures **181a** and **181b** which are dimensioned to receive and secure the knife wheel **148** to the knife rod **182** such that longitudinal reciprocation of the knife wheel **148**, in turn, moves the elongated knife rod **182** to sever tissue **420**.

In one embodiment, the knife wheel **148** is donut-like and includes rings **141a** and **141b** which define a drive slot **147** designed to receive a drive bar (not shown) such that actuation of the movable handle **40** forces the drive bar and the knife wheel **148** distally. It is envisioned that apertures **181a** and **181b** may be used for different configurations. As such, pin **143** is designed for attachment through either aperture **181a** or **181b** to mount the knife wheel **148** (see FIG. **18**). Knife wheel **148** also includes a series of radial flanges **142a** and **142b** which are dimensioned to slide along both channel **163** of tube **160** and slot **68** of the reciprocating sleeve **60** (see FIG. **9**).

As mentioned above, the knife rod **182** is dimensioned to mount the knife bar **184** between prongs **182a** and **182b**, which can be in a friction-fit engagement. The knife bar **184** includes a series of steps **186a**, **186b** and **186c** which reduce the profile of the knife bar **184** towards the distal end thereof. The distal end of the knife bar **184** includes a knife support **188** which is dimensioned to retain knife blade **185**. The end of the knife support **188** can include a chamfered edge **188a**. It is envisioned that the knife blade **185** may be welded to the knife support **188** or secured in any manner known in the trade.

As best shown in FIGS. **1** and **2**, as the tissue is securely grasped and the cutter lever **700** advances distally due to actuation of movable handle **40**, switch **500** activates, by virtue of movable handle **40** engaging contact **502**. At this point, electrosurgical energy is transferred through cable leads to jaw members **110** and **120**, as described in commonly-assigned, co-pending U.S. application Ser. No.



10/460,926 entitled "VESSEL SEALER AND DIVIDER FOR USE WITH SMALL TROCARS AND CANNULAS" by Dycus et al., which is hereby incorporated by reference in its entirety herein. As can be appreciated from the mechanics of the forceps **10**, the switch **500** cannot fire unless the jaw members **110** and **120** are closed. A sensor (not shown) may be included in the generator or the housing which prevents activation unless the jaw members **110** and **120** have tissue **420** held therebetween. In addition, other sensor mechanisms may be employed which determine pre-surgical, concurrent surgical (i.e., during surgery) and/or post surgical conditions. The sensor mechanisms may also be utilized with a closed-loop feedback system coupled to the electrosurgical generator to regulate the electrosurgical energy based upon one or more pre-surgical, concurrent surgical or post surgical conditions. Various sensor mechanisms and feedback systems are described in commonly-owned, co-pending U.S. patent application Ser. No. 10/427,832 entitled "METHOD AND SYSTEM FOR CONTROLLING OUTPUT OF RF MEDICAL GENERATOR" filed on May 1, 2003 the entire contents of which are hereby incorporated by reference herein.

In one embodiment, the jaw members **110** and **120** are electrically isolated from one another such that electrosurgical energy can be effectively transferred through the tissue **420** to form seal **450**. For example and as best illustrated in FIGS. **24** and **25**, each jaw member, e.g., **110**, includes a uniquely-designed electrosurgical cable path disposed there-through which transmits electrosurgical energy to the electrically conductive sealing surface **112**. It is envisioned that jaw member **110** may include one or more cable guides or crimp-like electrical connectors to direct cable lead **311** towards electrically conductive sealing surface **112**. In one embodiment, cable lead **311** is held loosely but securely along the cable path to permit rotation of the jaw member **110** about pivot **103**. As can be appreciated, this isolates electrically conductive sealing surface **112** from the remaining operative components of the end effector assembly **100**, jaw member **120** and shaft **12**. The second electrical potential is conducted to jaw member **120** through tube **160**. The two potentials are isolated from one another by virtue of the insulative sheathing surrounding cable lead **311**.

It is contemplated that utilizing a cable feed path for cable lead **311** and by utilizing a conductive tube **160** to carry the first and second electrical potentials not only electrically isolates each jaw member **110** and **120** but also allows the jaw members **110** and **120** to pivot about pivot pin **103** without unduly straining or possibly tangling cable lead **311**. Moreover, it is envisioned that the simplicity of the electrical connections greatly facilitates the manufacturing and assembly process and assures a consistent and tight electrical connection for the transfer of energy through the tissue **420**.

As discussed in commonly-assigned, co-pending U.S. application Ser. No. 10/460,926 entitled "VESSEL SEALER AND DIVIDER FOR USE WITH SMALL TROCARS AND CANNULAS" by Dycus et al., which is hereby incorporated by reference in its entirety herein, it is envisioned that select cable leads are fed through halves **82a** and **82b** of the rotating assembly **80** in such a manner to allow rotation of the shaft **12** (via rotation of the rotating assembly **80**) in the clockwise or counter-clockwise direction without unduly tangling or twisting the cable leads. More particularly, select cable leads are fed through a series of conjoining slots **84a**, **84b**, **84c** and **84d** located in the two halves **82a** and **82b** of the rotating assembly **80**. In one embodiment, each conjoining pair of slots, e.g., **84a**, **84b** and **84c**, **84d**, is large enough to permit rotation of the rotating assembly **80** without unduly straining or tangling the cable leads. The presently disclosed cable lead feed path

is envisioned to allow rotation of the rotation assembly approximately 180 degrees in either direction.

Turning back to FIGS. **1-3** which show a view of the housing **20**, rotating assembly **80**, movable handle **40**, fixed handle **50**, latch assembly **600**, switch **500** and cutter lever **700**, it is envisioned that all of these various component parts along with the shaft **12** and the end effector assembly **100** are assembled during the manufacturing process to form a partially and/or fully disposable forceps **10**. For example and as mentioned above, the shaft **12** and/or end effector assembly **100** may be disposable and, therefore, selectively/releasably engagable with the housing **20** and rotating assembly **80** to form a partially disposable forceps **10** and/or the entire forceps **10** may be disposable after use.

Once assembled, drive spring **67** is poised for compression atop drive housing **158** upon actuation of the movable handle **40**. More particularly, movement of the movable handle **40** about pivot point **29** reciprocates the flange **90** into fixed handle **50** and forces drive flange **47** against flange **154** of drive ring **159** to compress drive spring **67** against the rear stop **156** to reciprocate the sleeve **60** (see FIG. **28**).

The switch **500** is prevented from firing before the tissue **420** is clamped by jaw members **110** and **120**. For the sealing to take place, the movable handle **40** should be actuated far enough to contact (or, alternatively, for the cutter lever **700** to contact) the switch **500**, contact **502** or a sensor (not shown). Before the switch **500** is contacted, the movable handle **40** should travel sufficiently far enough to cause jaw members **110** and **120** to be clamped. It is envisioned that the opposing jaw members **110** and **120** may be rotated and partially opened and closed before activation of switch **500** which, as can be appreciated, allows the user to grip and manipulate the tissue **420** before the tissue **420** is sealed.

It is envisioned that configuring the pivot **29** above or relative to a longitudinal axis defined through the shaft provides an increased mechanical advantage, thus facilitating and easing selective compression of the drive spring **67** a specific distance which, in turn, imparts a specific load on the reciprocating sleeve **60**. As best seen in FIG. **2**, the moveable handle **40** includes a drive cam surface **49'** which is designed in-line with the longitudinal axis "A," which together with the position of the pivot **28** being disposed above axis "A," increase the mechanical advantage of the movable handle **40** and reduce the amount of force necessary to actuate the jaw members **110**, **120** with the preferred closure force. The load of the reciprocating sleeve **60** is converted to a torque about the jaw pivot **103**. As a result, a specific closure force can be transmitted to the opposing jaw members **110** and **120** between the range of about 3 kg/cm<sup>2</sup> to about 16 kg/cm<sup>2</sup>. As mentioned above, the jaw members **110** and **120** may be opened, closed and rotated to manipulate tissue **420** until sealing is desired. This enables the user to position and reposition the forceps **10** prior to activation and sealing.

Once the desired position for the sealing site is determined and the jaw members **110** and **120** are properly positioned, movable handle **40** may be actuated farther such that the switch **500** is engaged to seal the tissue **420** with electrosurgical energy. Continued actuation of movable handle **40** engages knife assembly **140** (as discussed above), which causes the tissue seal **450** to be severed.

It is envisioned that the end effector assembly **100** and/or the jaw members **110** and **120** may be dimensioned to off-load some of the excessive clamping forces to prevent mechanical failure of certain internal operating elements of the end effector **100**.

As can be appreciated, the combination of the increased mechanical advantage provided by the above-the-axis pivot

29 along with the compressive force associated with the drive spring 67 facilitate and assure consistent, uniform and accurate closure pressure about the tissue 420 within the desired working pressure range of about 3 kg/cm<sup>2</sup> to about 16 kg/cm<sup>2</sup> and, preferably, about 7 kg/cm<sup>2</sup> to about 13 kg/cm<sup>2</sup>. By controlling the intensity, frequency and duration of the electro-surgical energy applied to the tissue 420, the user can effectively seal tissue.

In one embodiment, the electrically conductive sealing surfaces 112 and 122 of the jaw members 110 and 120, respectively, are relatively flat to avoid current concentrations at sharp edges and to avoid arcing between high points. In addition and due to the reaction force of the tissue 420 when engaged, jaw members 110 and 120 can be manufactured to resist bending. For example, the jaw members 110 and 120 may be tapered along the width thereof which is advantageous for two reasons: 1) the taper will apply constant pressure for a constant tissue thickness at parallel; 2) the thicker proximal portion of the jaw members 110 and 120 will resist bending due to the reaction force of the tissue 420.

As mentioned above, at least one jaw member, e.g., 120, may include a stop member 750 which limits the movement of the two opposing jaw members 110 and 120 relative to one another. In one embodiment, the stop member 750 extends a predetermined distance from the sealing surface 122 (according to the specific material properties [e.g., compressive strength, thermal expansion, etc.]) to yield a consistent and accurate gap distance "G" during sealing (FIG. 29). The gap distance between opposing sealing surfaces 112 and 122 during sealing ranges from about 0.001 inches to about 0.006 inches and, desirably, between about 0.002 and about 0.003 inches. It is envisioned that the non-conductive stop members 750 may be molded onto the jaw members 110 and 120 (e.g., overmolding, injection molding, etc.), stamped onto the jaw members 110 and 120 or deposited (e.g., deposition) onto the jaw members 110 and 120. For example, one technique involves thermally spraying a ceramic material onto the surface of the jaw member 110 and 120 to form the stop members 750. Several thermal spraying techniques are contemplated which involve depositing a broad range of heat resistant and insulative materials on various surfaces to create stop members 750 for controlling the gap distance between electrically conductive surfaces 112 and 122.

As energy is being selectively transferred to the end effector assembly 100, across the jaw members 110 and 120 and through the tissue 420, a tissue seal 450 forms isolating two tissue halves 420a and 420b. With other known vessel sealing instruments, the user then removes and replaces the forceps 10 with a cutting instrument (not shown) or manually activates another switch to divide the tissue halves 420a and 420b along the tissue seal 450. As can be appreciated, this is both time consuming and tedious and may result in inaccurate tissue division across the tissue seal 450 due to misalignment or misplacement of the cutting instrument along the ideal tissue cutting plane.

As explained in detail above, the present disclosure incorporates a knife assembly 140 which, when activated via the handle assembly 30, progressively and selectively divides the tissue 420 along an ideal tissue plane in precise manner to effectively and reliably divide the tissue 420 into two sealed halves 420a and 420b with a tissue gap 475 therebetween (see FIG. 33). The knife assembly 140 in conjunction with the handle assembly 30 allows the user to quickly separate the tissue 420 immediately after sealing without substituting a cutting instrument through a cannula or trocar port and without having to perform a different action (e.g., manually activating a switch or pulling a trigger). As can be appreciated,

accurate sealing and dividing of tissue 420 is accomplished with a single, continuous motion using the same forceps 10.

It is envisioned that knife blade 185 may also be coupled to the same or an alternative electrosurgical energy source to facilitate separation of the tissue 420 along the tissue seal 450 (not shown). Moreover, it is envisioned that the angle of the tip of the knife blade 185 may be dimensioned to provide more or less aggressive cutting angles depending upon a particular purpose. For example, the knife blade 185 may be positioned at an angle which reduces "tissue wisps" associated with cutting. Moreover, the knife blade 185 may be designed having different blade geometries such as serrated, notched, perforated, hollow, concave, convex etc. depending upon a particular purpose or to achieve a particular result.

From the foregoing and with reference to the various figure drawings, those skilled in the art will appreciate that certain modifications can also be made to the present disclosure without departing from the scope of the same. For example, it may be preferable to add other features to the forceps 10, e.g., an articulating assembly to axially displace the end effector assembly 100 relative to the elongated shaft 12.

It is also contemplated that the forceps 10 (and/or the electrosurgical generator used in connection with the forceps 10) may include a sensor or feedback mechanism (not shown) which automatically selects the appropriate amount of electrosurgical energy to effectively seal the particularly-sized tissue grasped between the jaw members 110 and 120. The sensor or feedback mechanism may also measure the impedance across the tissue during sealing and provide an indicator (visual and/or audible) that an effective seal has been created between the jaw members 110 and 120. Examples of such sensor systems are described in commonly-owned U.S. patent application Ser. No. 10/427,832 entitled "METHOD AND SYSTEM FOR CONTROLLING OUTPUT OF RF MEDICAL GENERATOR," filed on May 1, 2003 the entire contents of which are hereby incorporated by reference herein.

Although the figures depict the forceps 10 manipulating an isolated vessel 420, it is contemplated that the forceps 10 may be used with non-isolated vessels as well. Other cutting mechanisms are also contemplated to cut tissue 420 along the ideal tissue plane.

It is envisioned that the outer surface of the end effector assembly 100 may include a nickel-based material, coating, stamping, metal injection molding which is designed to reduce adhesion between the jaw members 110 and 120 with the surrounding tissue during activation and sealing. Moreover, it is also contemplated that the conductive surfaces 112 and 122 of the jaw members 110 and 120 may be manufactured from one (or a combination of one or more) of the following materials: nickel-chrome, chromium nitride, Med-Coat 2000 manufactured by The Electrolyzing Corporation of OHIO, inconel 600 and tin-nickel. The tissue conductive surfaces 112 and 122 may also be coated with one or more of the above materials to achieve the same result, i.e., a "non-stick surface." As can be appreciated, reducing the amount that the tissue "sticks" during sealing improves the overall efficacy of the instrument.

One particular class of materials disclosed herein has demonstrated superior non-stick properties and, in some instances, superior seal quality. For example, nitride coatings which include, but are not limited to: TiN, ZrN, TiAlN, and CrN are preferred materials used for non-stick purposes. CrN has been found to be particularly useful for non-stick purposes due to its overall surface properties and optimal performance. Other classes of materials have also been found to reducing overall sticking. For example, high nickel/chrome

21

alloys with a Ni/Cr ratio of approximately 5:1 have been found to significantly reduce sticking in bipolar instrumentation. One particularly useful non-stick material in this class is Inconel 600. Bipolar instrumentation having sealing surfaces **112** and **122** made from or coated with Ni200, Ni201 (~100% Ni) also showed improved non-stick performance over typical bipolar stainless steel electrodes.

While several embodiments of the disclosure have been shown in the figures, it is not intended that the disclosure be limited thereto, as it is intended that the disclosure be as broad in scope as the art will allow and that the specification be read likewise. Therefore, the above description should not be construed as limiting, but merely as exemplifications of preferred embodiments. Those skilled in the art will envision other modifications within the scope and spirit of the claims appended hereto.

What is claimed is:

**1.** An endoscopic bipolar forceps, comprising:

a housing;

a shaft affixed to the housing, the shaft having a longitudinal axis defined therethrough and an end effector assembly engaged at a distal end thereof, the end effector assembly including two jaw members moveable from a first position in spaced relation relative to one another to at least a second position closer to one another for grasping tissue therebetween, each of the jaw members adapted to connect to an electrosurgical energy source such that the jaw members are capable of conducting energy through tissue held therebetween to affect a tissue seal;

a drive assembly disposed within the housing for moving the jaw members from the first position to the second position;

a switch disposed within the housing which activates the electrosurgical energy source;

a knife assembly which is advanceable to cut tissue disposed between the jaw members;

a movable handle connected to the housing and selectively rotatable about a pivot, the pivot located a fixed distance above the longitudinal axis, wherein continual actuation of the movable handle initially engages the drive assembly to move the jaw members, subsequently engages the switch to activate the electrosurgical energy source to seal the tissue, and subsequently advances the knife assembly to cut tissue disposed between the jaw members.

**2.** An endoscopic bipolar forceps according to claim **1** further comprising a rotating assembly which rotates the jaw members about the longitudinal axis defined through the shaft.

**3.** An endoscopic bipolar forceps according to claim **1** wherein at least one of the jaw members includes at least one stop member disposed thereon which regulates the distance between the jaw members.

**4.** An endoscopic bipolar forceps according to claim **3** wherein the distance between the jaw members is between 0.001 inches and 0.006 inches.

**5.** An endoscopic bipolar forceps according to claim **1** wherein a pressure range for actuating the movable handle and creating an effective seal is between 3 kg/cm<sup>2</sup> to 16 kg/cm<sup>2</sup>.

**6.** An endoscopic bipolar forceps according to claim **1** further including at least one tactile element which provides tactile feedback to a user relating to at least one of tissue sealing and tissue cutting.

**7.** An endoscopic bipolar forceps according to claim **1** further comprising a ratchet latch assembly associated with

22

the movable handle and the housing such that the movable handle locks into a first ratchet position after it cooperates to manipulate tissue, and the movable handle locks into a second ratchet position after it cooperates to seal tissue.

**8.** A method for using an endoscopic bipolar forceps to grasp, seal and cut tissue, the method comprising the steps of: providing an endoscopic bipolar forceps, the forceps having a housing, a shaft affixed to the housing, the shaft having a longitudinal axis defined therethrough and an end effector assembly engaged at a distal end thereof, the end effector assembly including two jaw members moveable from a first position in spaced relation relative to one another to at least a second position closer to one another for grasping tissue therebetween, each of the jaw members adapted to connect to an electrosurgical energy source such that the jaw members are capable of conducting energy through tissue held therebetween to affect a tissue seal, a drive assembly disposed within the housing for moving the jaw members from the first position to the second position, a switch disposed within the housing which activates the electrosurgical energy source, a knife assembly which is advanceable to cut tissue disposed between the jaw members, and a movable handle connected to the housing and selectively rotatable about a pivot, the pivot located a fixed distance above the longitudinal axis, wherein continual actuation of the movable handle initially engages the drive assembly to move the jaw members, subsequently engages the switch to activate the electrosurgical energy source to seal the tissue, and subsequently advances the knife assembly to cut tissue disposed between the jaw members;

actuating the movable handle, a continued actuation of the movable handle engages the drive assembly and moves the jaw members relative to one another to grasp tissue, engages the switch and activates the electrosurgical energy to seal tissue, and advances the knife assembly to cut the tissue.

**9.** An surgical instrument for surgically joining tissue, the surgical instrument comprising:

a handle assembly;

a shaft extending distally from the handle assembly and defining a longitudinal axis therethrough;

an end effector assembly disposed at a distal end of the shaft, the end effector assembly including two jaw members moveable from a first position in spaced relation relative to one another to at least a second position closer to one another for grasping tissue therebetween;

a drive assembly disposed in mechanical cooperation with the handle assembly for moving the jaw members between the first position and the second position;

a knife assembly configured to cut tissue disposed between the jaw members;

a tactile element configured to provide feedback to the user after tissue has been joined;

a movable handle disposed in mechanical cooperation with the handle assembly, wherein the movable handle is movable from a first, non-actuated position to a second position where the movable handle engages the drive assembly to move at least one of the jaw members, wherein the movable handle is movable between the second position and a third position to cause tissue to be joined, wherein the movable handle engages the tactile element when the movable handle reaches the third position, wherein the movable handle is movable between the third position and a fourth position where the movable handle engages the knife assembly to cut tissue, and

**23**

wherein the movable handle is movable between the third position and the first, non-actuated position without the movable handle moving towards the fourth position.

**10.** The surgical instrument of claim **9**, wherein each of the jaw members is adapted to connect to an electro-  
surgical energy source such that the jaw members are capable of conducting energy through tissue held therebetween to affect a tissue seal.

**11.** The surgical instrument of claim **10**, further comprising a switch disposed within the handle assembly that activates the electro-  
surgical energy source.

**24**

**12.** The surgical instrument of claim **9**, further comprising a second tactile element, the second tactile element being configured to provide feedback to the user while tissue is being cut.

**13.** The surgical instrument of claim **12**, wherein the second tactile element is disposed within the handle assembly.

**14.** The surgical instrument of claim **9**, wherein the tactile element is disposed within the handle assembly.

\* \* \* \* \*