



US007644511B2

(12) **United States Patent**
Ishikawa et al.

(10) **Patent No.:** **US 7,644,511 B2**
(45) **Date of Patent:** **Jan. 12, 2010**

(54) **HEATING AND BLOWING APPARATUS**

(75) Inventors: **Tomoya Ishikawa**, Hikone (JP); **Hideki Tanaka**, Hikone (JP); **Kenji Kamada**, Hikone (JP); **Kazumi Okawa**, Hikone (JP); **Fumio Mihara**, Kyoto (JP)

(73) Assignee: **Matsushita Electric Works, Ltd.**, Osaka (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 99 days.

(21) Appl. No.: **11/819,354**

(22) Filed: **Jun. 27, 2007**

(65) **Prior Publication Data**

US 2008/0000101 A1 Jan. 3, 2008

(30) **Foreign Application Priority Data**

Jun. 30, 2006 (JP) 2006-182466

(51) **Int. Cl.**
F26B 25/00 (2006.01)

(52) **U.S. Cl.** **34/78**; 34/90; 34/96; 392/384; 132/220; 361/213

(58) **Field of Classification Search** 34/78, 34/90, 96; 392/384; 132/220; 361/213; 239/690

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,743,963	A *	1/1930	Edmund	34/98
1,787,251	A *	12/1930	Jancke et al.	34/99
1,993,244	A *	3/1935	Martin	34/535
2,026,942	A *	1/1936	Kelley	34/87
2,281,993	A *	5/1942	Charles	34/553
2,846,777	A *	8/1958	Collins	34/95.1
3,289,679	A *	12/1966	Zellerman	132/208
3,335,503	A *	8/1967	Genger	34/100

3,947,659	A *	3/1976	Ono	392/404
5,805,406	A *	9/1998	Mailand	361/212
6,393,718	B1 *	5/2002	Harris et al.	34/96
6,640,049	B1 *	10/2003	Lee et al.	392/385
6,672,315	B2 *	1/2004	Taylor et al.	132/116
6,701,637	B2 *	3/2004	Lindsay et al.	34/71
6,725,562	B2 *	4/2004	Nakagawa et al.	34/96
6,763,606	B2 *	7/2004	Saida	34/97
6,792,692	B1 *	9/2004	Takizawa et al.	34/96
6,895,686	B1 *	5/2005	Sabbatini	34/96

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1438845 8/2003



(Continued)

Primary Examiner—Stephen M. Gravini
(74) *Attorney, Agent, or Firm*—Bacon & Thomas, PLLC

(57) **ABSTRACT**

A heating and blowing apparatus includes a main body housing having an inlet port and a discharge port. An air flow path extends from the inlet port to the discharge port. A rotatingly driven fan and a heating unit are arranged on the air flow path. A bypass flow path branches off from the air flow path and leads to an ion emission port. An ion generator including a discharge electrode and an opposing electrode is arranged in the bypass flow path. Further, the apparatus includes a cover arranged at the ion emission port and having an opening through which ions pass. One or more protrusions are provided on a rear surface of the cover. The protrusions make contact with the opposing electrode such that the cover is grounded through the opposing electrode.

6 Claims, 5 Drawing Sheets



US 7,644,511 B2

Page 2

U.S. PATENT DOCUMENTS

6,910,281 B2 * 6/2005 Ito 34/96
6,986,212 B2 * 1/2006 Saida et al. 34/98
6,996,916 B2 * 2/2006 Cafaro 34/96
7,047,660 B2 * 5/2006 Leventhal 34/97
7,123,823 B2 * 10/2006 Ceva 392/385
7,165,341 B2 * 1/2007 Saida et al. 34/98
2002/0189128 A1 * 12/2002 Nakagawa et al. 34/96
2003/0033726 A1 * 2/2003 Saida 34/96
2003/0152373 A1 * 8/2003 Wong et al. 392/385
2004/0020070 A1 * 2/2004 Ito 34/96
2004/0172847 A1 * 9/2004 Saida et al. 34/96
2005/0097770 A1 * 5/2005 Sabbatini 34/96
2005/0108889 A1 * 5/2005 Leventhal 34/96
2005/0198853 A1 * 9/2005 Cafaro 34/96
2005/0198855 A1 * 9/2005 Cafaro et al. 34/97
2005/0229425 A1 * 10/2005 Kroll et al. 34/283
2005/0284495 A1 * 12/2005 Yasuda et al. 132/272
2006/0026858 A1 * 2/2006 Saida et al. 34/96

2006/0032077 A1 * 2/2006 Cafaro 34/96
2006/0070255 A1 * 4/2006 Kokuo et al. 34/96
2006/0174507 A1 * 8/2006 Lin 34/96
2006/0196075 A1 * 9/2006 Santhouse et al. 34/96
2006/0201016 A1 * 9/2006 Nakagawa et al. 34/96
2006/0232908 A1 * 10/2006 Izumi et al. 361/220
2007/0006478 A1 * 1/2007 Kotsuji 34/96
2007/0169369 A1 * 7/2007 Lok et al. 34/97
2007/0204477 A1 * 9/2007 Lin 34/96
2007/0220773 A1 * 9/2007 Evanyk et al. 34/96
2008/0216339 A1 * 9/2008 Gray 34/97
2008/0229606 A1 * 9/2008 Hirai et al. 34/97
2008/0235980 A1 * 10/2008 Chasen et al. 34/91

FOREIGN PATENT DOCUMENTS

JP 2005-185864 7/2005
JP 2005-304961 11/2005
WO WO 2005/102101 11/2005

* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4





FIG. 5



1**HEATING AND BLOWING APPARATUS**

FIELD OF THE INVENTION

The present invention relates to a heating and blowing apparatus such as a hair dryer, a hot air blower or the like.

BACKGROUND OF THE INVENTION

A heating and blowing apparatus such as a hair dryer, a hot air blower or the like is design to draw air from an inlet port and force the air toward a discharge port by means of a rotating fan. In such an apparatus, a heating unit is arranged on an internal air flow path and the air heated by the heating unit is discharged through the discharge port.

In case of a heating and blowing apparatus having a negative ion generator, a bypass flow path that allows air to be discharged to the outside without passing through a heating unit is provided on the air flow path leading from an inlet port to a discharge port. The presence of the bypass flow path is to avoid restraining an ion passage amount, which would otherwise be caused by a lattice-shaped member arranged at the discharge port. The ion generator is arranged on the bypass flow path (see, e.g., Japanese Patent Laid-open Application No. 2002-191426).

Since a high voltage portion is present in the ion generator, it is required for safety to block fingers from contacting with the ion generator. Therefore, a cover is normally provided at an ion emission port through which negative ions generated by the negative ion generator are discharged. However, despite the provision of the bypass flow path for passage of the ions, the cover made of an insulating material is electrified by the ions generated in the ion generator, thereby causing the ion passage amount to decrease.

SUMMARY OF THE INVENTION

It is, therefore, an object of the present invention to provide a heating and blowing apparatus that is capable of efficiently discharging ions while assuring safety.

In accordance with the present invention, there is provided a heating and blowing apparatus including a main body housing having an inlet port and a discharge port; a rotatingly driven fan and a heating unit arranged on an air flow path, the air flow path extending from the inlet port to the discharge port; and an ion generator including a discharge electrode and an opposing electrode arranged in a bypass flow path, the bypass flow path branching off from the air flow path and leading to an ion emission port; and a cover, arranged at the ion emission port, having an opening through which ions pass and one or more protrusions provided on a rear surface of the cover, the protrusion making contact with the opposing electrode placed closer to the cover than the discharge electrode is, wherein the cover is grounded through the opposing electrode.

The heating and blowing apparatus may further include a biasing unit for pressing the ion generator toward the protrusion of the cover. This configuration makes it possible to attain a highly stable grounding condition.

In accordance with the present invention, safety is assured by the presence of a cover and there is no likelihood of electrifying the cover and restricting discharge of ions, which helps to discharge the ions in an increased amount. Furthermore, owing to the fact that electric grounding is rendered by use of opposite electrodes of an ion generator, there is no need to employ a separate grounding line.

2**BRIEF DESCRIPTION OF THE DRAWINGS**

The above and other objects and features of the present invention will become apparent from the following description of embodiment given in conjunction with the accompanying drawings, in which:

FIG. 1 is a cross sectional view showing major parts of a hair dryer in accordance with one embodiment of the present invention;

FIG. 2 is a front elevational view illustrating the hair dryer in accordance with the embodiment of the present invention;

FIG. 3 is a side elevational view illustrating the hair dryer in accordance with the embodiment of the present invention;

FIG. 4 is a perspective view depicting a wind tunnel and an ion generator of the hair dryer in accordance with the embodiment of the present invention; and

FIG. 5 is a partial cross section view showing a hair dryer in accordance with another embodiment of the present invention.

DETAILED DESCRIPTION OF THE EMBODIMENT

Hereinafter, the present invention will be described based on embodiment shown in the accompanying drawings.

Referring to FIGS. 1 to 3, a hair dryer which illustrates an example of a heating and blowing apparatus in accordance with an embodiment of the present invention includes a cylindrical main body housing 3 having an inlet port 11 at its rear end and a discharge port 12 at its front end. A grip portion 1 is connected to a rear bottom surface of the main body housing 3.

The main body housing 3 includes a rear wind tunnel 2 in which a motor 20 and a fan 21 are placed and a front wind tunnel 4 in which a heater 65 is arranged. The front wind tunnel 4 is set within the main body housing 3 in a state that an annular air flow path is provided between the front wind tunnel 4 and an inner circumferential surface of the main body housing 3. The front wind tunnel 4 is integrally formed with the rear wind tunnel 2.

Most of the wind from the fan 21 moves through the front wind tunnel 4 toward the discharge port 12, and the rest of the wind flows toward the discharge port 12 through the air flow path formed between the front wind tunnel 4 and the inner circumferential surface of the main body housing 3. This is to ensure that a cold air, which detours the heater 65, can be discharged from the discharge port 12 in such a way as to surround a heated air from the heater 65, thereby preventing the hair of a user from being overheated. In the drawings, the reference numeral "44" designates a grating disposed in a front portion of the front wind tunnel 4 to keep fingers from touching the heater 65.

An ion generator 5 is arranged in an upper part of the main body housing 3. The ion generator 5 illustrated in the drawings has a function of electrostatic atomization and includes a needle-shaped discharge electrode 51, a ring-shaped opposing electrode 52, a cooler 53 for cooling the discharge electrode 51 to condense moisture in the air into water on the discharge electrode 51 formed of a Peltier device, and a radiator 54 for dissipating the heat generated from the cooler 53. The discharge electrode 51 is connected to a high voltage generator (not shown) and the opposing electrode 52 is grounded.

If the high voltage generator applies a negative high voltage to the discharge electrode 51 cooled by the cooler 53, an electric discharge occurs between the discharge electrode 51 and the opposing electrode 52. Then, the water condensed on

3

the discharge electrode **51** is subject to Rayleigh distribution and thus turned to negatively electrified fine water particles which, in turn, are discharged to the outside from an ion emission port **13** formed in an upper front portion of the main body housing **3**. As described, a part of the wind generated by the fan **21** is introduced into the space in which the ion generator **5** lies to cool the radiator **54**, and is partly discharged from the ion emission port **13**, in which process the ions (electrified fine water particles) are air-borne to the outside.

A cover **6** for preventing fingers from entering into the interior space is arranged at the ion emission port **13**. As illustrated in FIG. **2**, the cover **6**, which is made of an insulating material, has an opening through which the ions (electrified water particles) are allowed to pass. The cover **6** is provided with a plurality of integrally formed protrusions **60** projecting rearwardly, i.e., toward the ion generator **5**. The protrusions **60** are in contact with a front surface of the opposing electrode **52** of the ion generator **5**. Thus, the cover **6** is grounded through the opposing electrode **52**.

This prevents the cover **6** from being electrified to impede emission of the ions, when the ions (electrified water particles) generated by the ion generator **5** are discharged from the ion emission port **13** through the opening.

The opposing electrode **52** is of a ring shape and has a circular opening at the center thereof. An electrical discharge occurs between the discharge electrode **51** and an inner circumferential edge of the opposing electrode **52**. The plurality of protrusions **60** of the cover **6** are provided at an equal interval in a circumferential direction to make contact with portions of the opposing electrode **52** close to the inner circumferential edge thereof. Furthermore, the protrusions **60** are formed near an edge of the opening of the cover **6** to further eliminate any electrical influence on the ions passing through the opening of the cover **6**.

In order to assure a stable contact between the protrusions **60** and the opposing electrode **52**, the ion generator **5** is attached by being pressed against the cover **6**. That is, as shown in FIG. **4**, the ion generator **5** is attached to an outer surface of the front wind tunnel **4** through a mounting plate **55**. The mounting plate **55** rests against an end portion of each rib **45** integrally formed on the outer surface of the front wind tunnel **4**, whereby backward movement of the mounting plate **55** is restrained by the ribs **45**. When the cover **6** and the ion generator **5** are assembled, the ribs **45** are adapted to press the mounting plate **55** in a forward direction. Thus, the ribs **45** and the mounting plate **55** are bent to ensure that a forward biasing force is exerted against the protrusions **60** of the cover **6** by the opposing electrode **52**, thereby increasing a contact pressure therebetween.

4

FIG. **5** shows a hair dryer in accordance with another embodiment of the present invention. The hair dryer of this embodiment is provided with an ion generator **5** that includes the discharge electrode **51**, the opposing electrode **52** and the high voltage generator, but has no electrostatic atomization function. This embodiment is the same as the foregoing embodiment in that the cover **6** is grounded through the opposing electrode **52** by bringing the protrusions **60** on the rear surface of the cover **6** into contact with the opposing electrode **52**.

While the invention has been shown and described with respect to the embodiment, it will be understood by those skilled in the art that various changes and modifications may be made without departing from the spirit and scope of the invention as defined in the following claims.

What is claimed is:

1. A heating and blowing apparatus comprising:
 - a main body housing having an inlet port and a discharge port;
 - a rotatably driven fan and a heating unit arranged on an air flow path, the air flow path extending from the inlet port to the discharge port;
 - an ion generator including a discharge electrode and an opposing electrode arranged in a bypass flow path, the bypass flow path branching off from the air flow path and leading to an ion emission port; and
 - a cover arranged at the ion emission port, the cover having an opening through which ions pass and one or more protrusions provided on a rear surface of the cover, the protrusion making contact with the opposing electrode placed closer to the cover than the discharge electrode is, wherein the cover is grounded through the opposing electrode.
2. The heating and blowing apparatus of **1**, further comprising a biasing unit for pressing the ion generator toward the protrusions of the cover.
3. The heating and blowing apparatus of **1**, wherein the opposing electrode is ring-shaped and the protrusions of the cover are provided in a circumferential direction of the opening for contacting portions of the opposing electrode adjacent an inner circumferential edge of the opposing electrode.
4. The heating and blowing apparatus of **1**, wherein the ion generator includes a cooler for cooling the discharge electrode so as to condense moisture in air into water on the discharge electrode.
5. The heating and blowing apparatus of **1**, wherein the cover is made of an insulating material.
6. The heating and blowing apparatus of **4**, wherein the cooler is a Peltier device.

* * * * *