

US007657005B2

(12) **United States Patent**
Chang

(10) **Patent No.:** **US 7,657,005 B2**
(45) **Date of Patent:** **Feb. 2, 2010**

(54) **SYSTEM AND METHOD FOR IDENTIFYING TELEPHONE CALLERS**

5,497,373 A 3/1996 Hulen et al.
5,522,046 A 5/1996 McMillen et al.
5,530,744 A 6/1996 Charalambous et al.
5,555,299 A * 9/1996 Maloney et al. 379/212.01

(75) Inventor: **Hisao M. Chang**, Austin, TX (US)

(73) Assignee: **AT&T Intellectual Property I, L.P.**, Reno, NV (US)

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 18 days.

FOREIGN PATENT DOCUMENTS

EP 0 424 015 A2 4/1991

(21) Appl. No.: **10/979,784**

(22) Filed: **Nov. 2, 2004**

(Continued)

(65) **Prior Publication Data**

US 2006/0093097 A1 May 4, 2006

OTHER PUBLICATIONS

U.S. Appl. No. 10/898,722, filed Jul. 23, 2004.

(51) **Int. Cl.**
H04M 1/64 (2006.01)

(Continued)

(52) **U.S. Cl.** **379/88.02**; 370/352; 370/353; 370/354; 370/355; 370/356; 379/88.01; 379/142.05; 379/142.06; 379/211.01; 379/212.01; 379/213.01; 379/214.01; 379/265.02; 455/415; 455/417; 704/270; 704/270.1; 709/202

Primary Examiner—Hemant Patel
(74) *Attorney, Agent, or Firm*—Toler Law Group

(58) **Field of Classification Search** 370/351–356; 379/88.01–88.02, 142.05–142.06, 211.01, 379/212.01, 213.01, 214.01, 265.02; 455/415, 455/417; 709/202; 704/270–270.1

(57) **ABSTRACT**

See application file for complete search history.


A method of processing calls received at an interactive voice response (IVR) server is provided and includes receiving a telephone call at the IVR. Caller identity data that is associated with the telephone call is received and a customer profile that includes a list of individual names associated with the caller identity data is received. Each of the individual names is mapped to a speech recognition grammar pattern. Further, a caller of the telephone call is prompted to speak their name. A spoken name from the caller is received and recorded. Moreover, the spoken name is converted into a speech recognition grammar pattern. Thereafter, the speech recognition grammar pattern associated with the spoken name is compared to each of the speech recognition grammar patterns associated with the individual names retrieved from the customer profile.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,696,028 A 9/1987 Morganstein et al.
4,788,715 A 11/1988 Lee
4,953,204 A 8/1990 Cuschleg, Jr. et al.
4,964,077 A 10/1990 Eisen et al.
4,967,405 A 10/1990 Upp et al.
5,042,006 A 8/1991 Flohrer
5,235,679 A 8/1993 Yoshizawa et al.
5,335,269 A 8/1994 Steinlicht
5,416,830 A 5/1995 MacMillan, Jr. et al.
5,455,903 A 10/1995 Jolissaint et al.

21 Claims, 3 Drawing Sheets



US 7,657,005 B2

U.S. PATENT DOCUMENTS							
			6,714,631	B1	3/2004	Martin et al.	
			6,714,643	B1	3/2004	Gargeya et al.	
			6,721,416	B1	4/2004	Farrell	
5,590,186	A	12/1996	6,731,722	B2 *	5/2004	Coffey	379/88.01
5,632,002	A	5/1997	6,738,082	B1	5/2004	Dong et al.	
5,652,789	A *	7/1997	6,738,473	B1	5/2004	Burg et al.	
5,754,639	A	5/1998	6,744,861	B1 *	6/2004	Pershan et al.	379/88.03
5,754,978	A *	5/1998	6,744,877	B1	6/2004	Edwards	
5,923,745	A	7/1999	6,751,306	B2	6/2004	Himmel et al.	
5,940,476	A *	8/1999	6,757,306	B1	6/2004	Klish, II et al.	
5,946,388	A	8/1999	6,766,320	B1	7/2004	Wang et al.	
5,953,704	A	9/1999	6,775,359	B1	8/2004	Ron et al.	
5,991,756	A	11/1999	6,778,643	B1	8/2004	Bushey et al.	
5,995,979	A	11/1999	6,792,096	B2	9/2004	Martin et al.	
5,999,965	A	12/1999	6,807,274	B2	10/2004	Joseph et al.	
6,002,689	A	12/1999	6,823,307	B1 *	11/2004	Steinbiss et al.	704/252
6,002,760	A	12/1999	6,831,932	B1	12/2004	Boyle et al.	
6,003,011	A	12/1999	6,832,224	B2	12/2004	Gilmour	
6,038,293	A	3/2000	6,842,504	B2	1/2005	Mills et al.	
6,038,305	A *	3/2000	6,847,711	B2	1/2005	Knott et al.	
6,049,594	A *	4/2000	6,853,722	B2	2/2005	Joseph et al.	
6,064,731	A	5/2000	6,853,966	B2	2/2005	Bushey et al.	
6,118,866	A	9/2000	6,859,529	B2	2/2005	Duncan et al.	
6,119,101	A	9/2000	6,871,212	B2 *	3/2005	Khouri et al.	709/204
RE37,001	E	12/2000	6,879,683	B1	4/2005	Fain et al.	
6,173,266	B1	1/2001	6,885,734	B1	4/2005	Eberle et al.	
6,173,289	B1	1/2001	6,891,932	B2	5/2005	Bhargava et al.	
6,173,399	B1	1/2001	6,895,083	B1	5/2005	Bers et al.	
6,175,621	B1	1/2001	6,901,366	B1	5/2005	Kuhn et al.	
6,259,786	B1	7/2001	6,907,119	B2	6/2005	Case et al.	
6,269,153	B1	7/2001	6,915,246	B2	7/2005	Gusler et al.	
6,317,439	B1	11/2001	6,922,689	B2	7/2005	Shtivelman	
6,333,980	B1	12/2001	6,925,155	B2	8/2005	Reynolds et al.	
6,353,608	B1	3/2002	6,963,983	B2	11/2005	Munson et al.	
6,366,658	B1	4/2002	6,964,023	B2 *	11/2005	Maes et al.	715/811
6,366,668	B1	4/2002	6,970,554	B1	11/2005	Peterson et al.	
6,381,329	B1	4/2002	7,003,079	B1	2/2006	McCarthy et al.	
6,385,584	B1	5/2002	7,006,605	B1 *	2/2006	Morganstein et al.	379/88.02
6,389,400	B1	5/2002	7,013,112	B2	3/2006	Haller et al.	
6,400,804	B1	6/2002	7,027,975	B1	4/2006	Pazandak et al.	
6,400,996	B1	6/2002	7,031,444	B2	4/2006	Shen et al.	
6,405,159	B2	6/2002	7,035,388	B2 *	4/2006	Kurosaki	379/142.06
6,411,687	B1 *	6/2002	7,039,166	B1 *	5/2006	Peterson et al.	379/88.18
6,414,966	B1	7/2002	7,062,505	B2	6/2006	Lane et al.	
6,418,424	B1	7/2002	7,065,201	B2	6/2006	Bushey et al.	
6,434,546	B1	8/2002	7,092,370	B2	8/2006	Jiang et al.	
6,438,520	B1 *	8/2002	7,095,827	B2	8/2006	Guedalia	
6,442,247	B1	8/2002	7,095,842	B2	8/2006	Brown et al.	
6,510,414	B1 *	1/2003	7,106,850	B2	9/2006	Campbell et al.	
6,519,562	B1	2/2003	7,184,534	B2	2/2007	Birch et al.	
6,526,126	B1 *	2/2003	7,200,614	B2	4/2007	Reid et al.	
6,529,871	B1	3/2003	7,245,711	B2	7/2007	Margolis	
6,546,087	B2	4/2003	2001/0011211	A1	8/2001	Bushey et al.	
6,553,113	B1 *	4/2003	2001/0018672	A1	8/2001	Petters et al.	
6,570,967	B2	5/2003	2001/0032229	A1	10/2001	Hulls et al.	
6,574,599	B1 *	6/2003	2001/0034662	A1	10/2001	Morris	
6,584,180	B2 *	6/2003	2002/0046030	A1 *	4/2002	Haritsa et al.	704/256
6,587,556	B1	7/2003	2002/0049874	A1	4/2002	Kimura	
6,598,021	B1	7/2003	2002/0059169	A1	5/2002	Quarterman et al.	
6,598,136	B1	7/2003	2002/0067714	A1	6/2002	Crain et al.	
6,600,736	B1 *	7/2003	2002/0087385	A1	7/2002	Vincent	
6,603,854	B1	8/2003	2002/0133394	A1	9/2002	Bushey et al.	
6,614,781	B1	9/2003	2002/0133413	A1	9/2002	Chang et al.	
6,615,248	B1	9/2003	2002/0135618	A1 *	9/2002	Maes et al.	345/767
6,631,186	B1	10/2003	2002/0156699	A1	10/2002	Gray et al.	
6,662,163	B1 *	12/2003	2002/0165732	A1	11/2002	Ezzeddine et al.	
6,678,360	B1	1/2004	2002/0188438	A1	12/2002	Knight et al.	
6,678,718	B1	1/2004	2002/0196277	A1	12/2002	Bushey et al.	
6,690,788	B1	2/2004	2003/0018659	A1	1/2003	Fuks et al.	
6,694,012	B1	2/2004	2003/0026409	A1	2/2003	Bushey et al.	
6,697,460	B2	2/2004	2003/0035381	A1	2/2003	Chen et al.	
6,700,972	B1	3/2004	2003/0069937	A1	4/2003	Khouri et al.	
6,704,404	B1	3/2004	2003/0097428	A1	5/2003	Afkhami et al.	
6,707,789	B1	3/2004					

2003/0112956 A1* 6/2003 Brown et al. 379/221.01
 2003/0130864 A1 7/2003 Ho et al.
 2003/0143981 A1 7/2003 Kortum et al.
 2003/0144846 A1 7/2003 Denenberg et al.
 2003/0144919 A1 7/2003 Trompette et al.
 2003/0156133 A1 8/2003 Martin et al.
 2003/0165223 A1 9/2003 Timmins et al.
 2003/0187732 A1 10/2003 Seta
 2003/0187773 A1 10/2003 Santos et al.
 2003/0194063 A1 10/2003 Martin et al.
 2003/0195753 A1 10/2003 Homuth
 2003/0202640 A1 10/2003 Knott et al.
 2003/0202643 A1 10/2003 Joseph et al.
 2003/0202649 A1 10/2003 Haug, Jr. et al.
 2003/0204435 A1 10/2003 McQuilkin et al.
 2003/0228007 A1* 12/2003 Kurosaki 379/142.06
 2003/0235282 A1* 12/2003 Sichelman et al. 379/201.03
 2004/0005047 A1 1/2004 Joseph et al.
 2004/0006473 A1 1/2004 Mills et al.
 2004/0032862 A1 2/2004 Schoeneberger et al.
 2004/0032935 A1 2/2004 Mills et al.
 2004/0042592 A1 3/2004 Knott et al.
 2004/0044950 A1 3/2004 Mills et al.
 2004/0066401 A1 4/2004 Bushey et al.
 2004/0066416 A1 4/2004 Knott et al.
 2004/0073569 A1 4/2004 Knott et al.
 2004/0083479 A1 4/2004 Bondarenko et al.
 2004/0088285 A1 5/2004 Martin et al.
 2004/0103017 A1 5/2004 Reed et al.
 2004/0109555 A1 6/2004 Williams
 2004/0125937 A1 7/2004 Turcan et al.
 2004/0125938 A1 7/2004 Turcan et al.
 2004/0125940 A1 7/2004 Turcan et al.
 2004/0161078 A1 8/2004 Knott et al.
 2004/0161094 A1 8/2004 Martin et al.
 2004/0161096 A1 8/2004 Knott et al.
 2004/0174980 A1 9/2004 Knott et al.
 2004/0230438 A1 11/2004 Pasquale et al.
 2004/0240635 A1 12/2004 Bushey et al.
 2004/0243568 A1 12/2004 Wang et al.
 2005/0008141 A1 1/2005 Kortum et al.
 2005/0015197 A1 1/2005 Ohtsuji et al.
 2005/0015744 A1 1/2005 Bushey et al.
 2005/0018825 A1 1/2005 Ho
 2005/0027535 A1 2/2005 Martin et al.
 2005/0041796 A1 2/2005 Joseph et al.
 2005/0047578 A1 3/2005 Knott et al.
 2005/0055216 A1 3/2005 Bushey et al.
 2005/0058264 A1 3/2005 Joseph et al.
 2005/0075894 A1 4/2005 Bushey et al.
 2005/0078805 A1 4/2005 Mills et al.
 2005/0080630 A1 4/2005 Mills et al.
 2005/0080667 A1 4/2005 Knott et al.
 2005/0125232 A1* 6/2005 Gadd 704/270.1
 2005/0131892 A1 6/2005 Knott et al.
 2005/0132262 A1 6/2005 Bushey et al.
 2005/0135595 A1 6/2005 Bushey et al.
 2005/0141692 A1 6/2005 Scherer et al.
 2005/0147218 A1 7/2005 Novack et al.
 2005/0169441 A1* 8/2005 Yacoub et al. 379/88.16
 2005/0169453 A1 8/2005 Knott et al.
 2005/0201547 A1 9/2005 Burg et al.
 2005/0240411 A1* 10/2005 Yacoub 704/270
 2006/0018443 A1 1/2006 Knott et al.
 2006/0023863 A1 2/2006 Joseph et al.
 2006/0026049 A1 2/2006 Joseph et al.
 2006/0036437 A1 2/2006 Bushey et al.
 2006/0039547 A1 2/2006 Klein et al.
 2006/0050865 A1 3/2006 Kortum et al.

2006/0056406 A1 3/2006 Bouchard et al.
 2006/0062375 A1 3/2006 Pasquale et al.
 2006/0072737 A1 4/2006 Paden et al.
 2006/0100998 A1 5/2006 Edwards et al.
 2006/0109974 A1 5/2006 Paden et al.
 2006/0115070 A1 6/2006 Bushey et al.
 2006/0126808 A1 6/2006 Dallessandro et al.
 2006/0126811 A1 6/2006 Bushey et al.
 2006/0133587 A1 6/2006 Bushey et al.
 2006/0153345 A1 7/2006 Bushey et al.
 2006/0159240 A1 7/2006 Bushey et al.
 2006/0161431 A1 7/2006 Bushey et al.
 2006/0165066 A1 7/2006 Campbell et al.
 2006/0177040 A1 8/2006 Mitra
 2006/0188087 A1 8/2006 Kortum et al.
 2006/0195312 A1 8/2006 Knight et al.
 2006/0198505 A1 9/2006 Kortum et al.
 2006/0215831 A1 9/2006 Knott et al.
 2006/0215833 A1 9/2006 Mahoney et al.
 2006/0256932 A1 11/2006 Bushey et al.
 2006/0291642 A1 12/2006 Bushey et al.
 2007/0019800 A1 1/2007 Bushey et al.
 2007/0025528 A1 2/2007 Knott et al.
 2007/0047718 A1 3/2007 Idler et al.

FOREIGN PATENT DOCUMENTS

EP 0 424 015 A3 4/1991
 EP 0 424 015 B1 4/1991
 EP 0 876 652 A4 9/1996
 WO WO 97/26612 7/1997
 WO WO 01/37539 A2 5/2001
 WO WO 01/37539 A3 5/2001
 WO WO 2004/017584 2/2004
 WO WO 2004/049222 A2 6/2004

OTHER PUBLICATIONS

U.S. Appl. No. 10/901,926, filed Jul. 28, 2004.
 U.S. Appl. No. 10/901,925, filed Jul. 28, 2004.
 U.S. Appl. No. 10/917,233, filed Aug. 12, 2004.
 U.S. Appl. No. 10/935,726, filed Sep. 7, 2004.
 U.S. Appl. No. 10/999,199, filed Nov. 29, 2004.
 U.S. Appl. No. 11/005,498, filed Dec. 6, 2004.
 U.S. Appl. No. 11/005,494, filed Dec. 6, 2004.
 U.S. Appl. No. 11/010,633, filed Dec. 13, 2004.
 U.S. Appl. No. 11/032,495, filed Jan. 10, 2005.
 U.S. Appl. No. 11/036,204, filed Jan. 14, 2005.
 U.S. Appl. No. 11/036,201, filed Jan. 14, 2005.
 U.S. Appl. No. 11/062,100, filed Feb. 18, 2005.
 U.S. Appl. No. 11/071,068, filed Mar. 3, 2005.
 U.S. Appl. No. 11/086,796, filed Mar. 23, 2005.
 U.S. Appl. No. 11/129,051, filed May 13, 2005.
 U.S. Appl. No. 11/145,513, filed Jun. 3, 2005.
 U.S. Appl. No. 11/173,227, filed Jul. 1, 2005.
 U.S. Appl. No. 11/176,972, filed Jul. 7, 2005.
 U.S. Appl. No. 11/086,794, filed Mar. 22, 2005.
 U.S. Appl. No. 10/996,127, filed Nov. 23, 2004.
 U.S. Appl. No. 10/920,719, filed Dec. 13, 2004.
 U.S. Appl. No. 10/920,720, filed Aug. 18, 2004.
 U.S. Appl. No. 10/948,089, filed Sep. 23, 2004.
 U.S. Appl. No. 10/975,023, filed Oct. 27, 2004.
 U.S. Appl. No. 11/212,939, filed Aug. 25, 2005.
 Ogino, Tsukasa, et al., "Technologies for Internet Infrastructure: Eliminating the World Wide Wait", iNet Japan, Jul. 18-21, 2000, www.isoc.org/edproceedings/1g/index.
 www.yahoo.com (as in Dec. 12, 1998) as archived in the Internet archive (www.archive.org).

* cited by examiner





FIG. 1






FIG. 3

1

SYSTEM AND METHOD FOR IDENTIFYING TELEPHONE CALLERS

FIELD OF THE DISCLOSURE

The present disclosure relates generally to call center systems.

BACKGROUND

Telephone service providers of the public switched telephone network (PSTN) have been offering caller identification services that utilize the signaling system seven (SS7) protocol for many years. Since the early 1980's, various interactive voice response (IVR) technologies have been developed to use the caller identification function provided by SS7 to determine the originating line from which a telephone call was made. However, caller identification services only provide the telephone number from which the telephone call was initiated and the name(s) associated with the telephone number if the subscriber allows the telephone number to be listed. In order to determine who is calling, an IVR system or human customer service agent, must ask the caller to identify himself or herself.

Accordingly, there is a need for an improved system and method for identifying telephone callers.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is pointed out with particularity in the appended claims. However, other features are described in the following detailed description in conjunction with the accompanying drawings in which:

FIG. 1 is a general diagram of a telephone system;

FIG. 2 is a flow chart to illustrate a method for identifying telephone callers; and

FIG. 3 is a general diagram of a computer.

DETAILED DESCRIPTION OF THE DRAWINGS

A method of processing calls received at an interactive voice response (IVR) server is provided and includes receiving a telephone call at the IVR. Caller identity data that is associated with the telephone call is received and a customer profile that includes a list of individual names associated with the caller identity data is received. Each of the individual names is mapped to a speech recognition grammar pattern. Further, a caller of the telephone call is prompted to speak their name. A spoken name from the caller is received and recorded. Moreover, the spoken name is converted into a speech recognition grammar pattern. Thereafter, the speech recognition grammar pattern associated with the spoken name is compared to each of the speech recognition grammar patterns associated with the individual names retrieved from the customer profile.

In a particular embodiment, the caller identity data includes a telephone number. Also, in a particular embodiment, a caller name is identified based on a result of comparing the speech recognition grammar associated with the spoken name with each of the speech recognition grammar patterns associated with the individual names retrieved from the customer profile. Moreover, a title for the caller is determined based on the spoken name. In a particular embodiment, the title is determined based on a pitch of a voice of the caller and the pitch is derived from a recorded spoken name.

In still another particular embodiment, the method includes determining whether the probability that the title and

2

the caller name are correct is above a predetermined threshold. The telephone call can be forwarded to a service agent terminal via a whisper transfer when the probability is below the predetermined threshold. In a particular embodiment, a name field can be automatically populated at a graphical user interface of an agent terminal with the caller name. Also, a title field can be automatically populated at the graphical user interface with the title of the caller. Additionally, the telephone call can be forwarded to a live customer service agent when the probability is above the predetermined threshold.

In another embodiment, a method of processing calls that are received at an interactive voice response (IVR) server is provided. Initially, a telephone call is received at the IVR and a caller is prompted to speak their name. Further, a spoken name is received from the caller. Based on the spoken name from the caller, a name of the caller is identified. Also, a title associated with the caller is determined.

In yet another embodiment, a system for identifying a telephone caller is provided. The system includes an interactive voice response server that includes a processor. A memory is accessible to the processor and a computer program is embedded within the memory. The computer program includes instructions to identify a name associated with a telephone caller in response to analyzing a recorded spoken name from the telephone caller. Additionally, the computer program includes instructions to determining a title associated with the caller based on the spoken name.

In still another embodiment, a graphical user interface of a customer service agent computer is provided. The graphical user interface includes a title field and the title field is automatically populated with a title of a telephone caller when a call is received at an interactive voice response server that is coupled to the customer service agent computer and forwarded to a customer service agent.

Referring initially to FIG. 1, a telecommunications system is shown and is generally designated 100. As shown, the system 100 includes a telecommunications network 102. In a particular embodiment, the telecommunications network 102 is a public switched telephone network. In another embodiment, the telecommunications network 102 is a voice over Internet protocol (VoIP) network. As illustrated in FIG. 1, a first telephone 104 and a second telephone 106 are coupled to the telecommunications network 102. FIG. 1 also depicts a caller identification system 108 coupled to the telecommunications network 102. The first telephone 104 and the second telephone 106 are for illustrative purposes and many more telephones can be coupled, or otherwise connected, to the telecommunications network 102.

In a particular embodiment, as indicated in FIG. 1, the caller identification system 108 includes an interactive voice response (IVR) server 110. The IVR server 110 includes a memory device 112 and a processor 114 coupled to the memory device 112. In an illustrative embodiment, the IVR server 110 also includes an automatic caller identification module 116 that is embedded within the memory device 112. In a particular embodiment, the automatic caller identification module 116 can retrieve caller identification information related to calls received at the IVR server 110. FIG. 1 further depicts an automatic speech recognition module 118 that is embedded within the memory device 112 in the IVR server 110. The automatic speech recognition module 118 can be used to determine a caller's name and gender after a call is received at the IVR and after the caller is prompted to speak his or her name.

Still referring to FIG. 1, a first-name and gender matching database 120 is coupled to the IVR 110. In a particular embodiment, the first-name and gender matching database

120 includes information that can be used by the automatic speech recognition module **118** for determining the gender of a caller, e.g., based on the first name of the caller or the pitch of the caller's voice. FIG. **1** also shows a customer service database **122** that is coupled to the IVR **110**. Particularly, the customer service database **122** can include customer information such as, account information, customer address information, etc.

As depicted in FIG. **1**, a computer **124** can be coupled to the caller identification system **108**. In a particular embodiment, the computer **124** can be a customer service agent computer or a customer service agent terminal. Further, in a particular embodiment, many more computers **124** can be coupled to the caller identification system **108** than the single computer **124** illustrated in FIG. **1**.

Referring now to FIG. **2**, a flow chart to illustrate a method for identifying telephone callers is shown and commences at block **200**. At block **200**, an incoming telephone call is received. At decision step **202**, a determination is made as to whether caller identification information is delivered with the incoming telephone call. If caller identification information is not delivered with the incoming telephone call, the method moves to block **204** and the caller is prompted to speak an identification number. In a particular embodiment, the identification number can be a telephone number, an account number, a social security number, or any other number linked to a customer's account for identification purposes. From block **204**, the method can move to block **208**.

Returning to decision step **202**, if the caller identification information is delivered, the method continues to decision step **206**. At decision step **206**, a determination is made as to whether the present call is about the telephone number identified in the caller identification information. For example, the present call can be a service call concerning the identified telephone number and the present call can be made from the telephone or location associated with the identified telephone number. If the present call is not about the identified telephone number, the method continues to block **204** and the caller is prompted to speak an identification number. Next, at block **208**, the caller's voice is recorded. The method can then proceed to block **210**.

Returning to decision step **206**, if the call is about the identified telephone number, the method moves to block **210**. At block **210**, a customer record associated with the identified telephone number is retrieved. In a particular embodiment, the customer record can be retrieved from the customer service database **122** (FIG. **1**). Moving to block **212**, a speaker-independent name recognition grammar is dynamically created. In a particular embodiment, the name recognition grammar is a phonetic spelling of the user's name. Next, at block **214**, the caller is prompted to identify himself or herself. Further, at block **216**, the caller's voice is recorded while he or she is identifying himself or herself.

Continuing to block **218**, automatic speech recognition is performed on the recorded voice. In a particular embodiment, the automatic speech recognition is performed in the automatic speech recognition module **118** within the IVR server **110**. Further, in a particular embodiment, the automatic speech recognition module **118** measures the pitch of the speaker's voice in order to determine the gender of the speaker. Additionally, the automatic speech recognition module **118** attempts to recognize the spoken name by comparing the dynamically created name grammar to a table of names. In a particular embodiment, the table of names can be a comprehensive table of names. In another particular embodiment, the table of names corresponds to the names associated with a particular account, e.g., a husband name and a wife name. In

a particular embodiment, the table of names can be a comprehensive table of names. In another particular embodiment, the table of names corresponds to the names associated with a particular account, e.g., a husband name and a wife name.

Moving to decision step **220**, a decision is made in order to determine whether the automatic speech recognition is performed successfully, i.e., whether the automatic speech recognition module recognizes the name spoken. If the automatic speech recognition is not performed successfully, the method moves to block **222** and the name recording is forwarded to a customer service agent via a "whisper transfer" so that the customer service agent can hear the name recording and greet the caller using the recorded name. In a particular embodiment, during the "whisper transfer," the caller is placed in hold and the IVR connects to an available customer service agent. Then, the recorded name is played to the customer service agent before the call is transferred to the customer service agent. The customer service agent can listen to the recorded name and compare it to a name in a name field, if present, to determine the appropriate greeting for the caller. The method then ends at state **224**.

At decision step **220**, if the automatic speech recognition is performed successfully, the method proceeds to block **226** and the caller's name and title is determined. In a particular embodiment, the spelling of the caller's name can be determined. Particularly, the name and title can be determined by comparing the text string corresponding to the recorded name, e.g., the dynamically created recognition grammar, to a list of names. Further, to determine a caller's title, a gender table including common first names is used to determine if a name recognized by the automatic speech recognition module is most likely associated with a male or female caller. If a match is found, the title information obtained from the gender table is assigned to the name. If an initial match is not found, pitch characteristics of the voice recording are used to attempt to determine the gender of the caller.

Moving to decision step **228**, a decision is made in order to determine whether the gender determination is accurate within a predetermine probability. If not, the method continues to block **222** and the telephone call is transferred to a customer service agent using a "whisper transfer." The customer service agent can compare the voice recording to the text of the name that appears in a GUI. The customer service agent can decide the gender of the caller and greet the caller appropriately. If the gender determination is deemed to be accurate above a certain probability, the method proceeds to block **230** and a name field and a title field in a GUI are automatically populated with the caller's name and title. Further, an address field, an account number field, and an account type field can be automatically populated. Moving to block **232**, the telephone call is forwarded to a live agent. Then, the method ends at state **224**.

Referring now to FIG. **3**, a computer configured to support a customer service agent is shown and is generally designated **300**. As illustrated in FIG. **3**, a GUI **302** can be displayed at the computer **300**. In a particular embodiment, the GUI **302** can include a title field **304**, a name field **306**, an address field **308**, an account number field **310**, and an account type field **312**. In a particular embodiment, the title field **304** and the name field **306** can be automatically populated, as described herein, in order to present a caller's name and title to a customer service agent using the computer **300**. The remaining fields **308**, **310**, **312** can be populated with information retrieved from the customer service database **122**.

With the configuration of structure described herein, the system and method provides a way for a customer service agent to appropriately greet a caller who is calling regarding

5

a particular telephone number. The telephone call may concern account information, repair information, and/or the addition of services to an account. Further, the system and method automates the task of asking a caller his or her name, eliminates the need for the customer agent to ask who is calling, and reduces the time that a customer agent service must spend on the phone with callers. Additionally, the system and method can provide improved accuracy for determining a user's name and gender.

For many types of services, e.g., local telephone service, long distance telephone services, Internet-based services, multiple users may initiate a customer service call at different times for the same account. In this type of scenario, the system and method described herein can determine who among the users associated with an account is calling and greet the caller appropriately.

The above-disclosed subject matter is to be considered illustrative, and not restrictive, and the appended claims are intended to cover all such modifications, enhancements, and other embodiments, which fall within the true spirit and scope of the present invention. Thus, to the maximum extent allowed by law, the scope of the present invention is to be determined by the broadest permissible interpretation of the following claims and their equivalents, and shall not be restricted or limited by the foregoing detailed description.

What is claimed is:

1. A method of processing calls received at an interactive voice response (IVR) server, the method comprising:

receiving a telephone call at the IVR server;

receiving caller identity data associated with the telephone call and receiving a text list of names of individuals associated with the caller identity data;

dynamically creating multiple name recognition grammar patterns by generating a phonetic spelling of each name in the text list of names of individuals associated with the caller identity data;

prompting a caller of the telephone call to speak a name associated with the caller;

receiving and recording a spoken name from the caller; converting the spoken name into a speech recognition grammar pattern;

selectively comparing the speech recognition grammar pattern associated with the spoken name to the multiple name recognition grammar patterns;

determining a text string from the text list of names of individuals associated with the caller identity data corresponding to a name recognition grammar pattern that matches the speech recognition grammar pattern;

comparing the text string to entries in a table to determine a gender of the caller, the table including a plurality of first names and an associated indication that a particular first name indicates the caller is one of a male caller and a female caller;

assigning a title to the caller based on the gender of the caller when the text string matches an entry in the table; and

forwarding the telephone call and the title to a service agent terminal.

2. The method of claim 1, wherein the caller identity data includes a telephone number.

3. The method of claim 1, further comprising: identifying a caller name at least partially based on a result of the selective comparison.

4. The method of claim 3, further comprising determining whether a probability that the title and the caller name are correct is above a predetermined threshold.

6

5. The method of claim 4, further comprising populating a name field at a graphical user interface of the service agent terminal with the caller name when the probability that the title and the caller name are correct is above the predetermined threshold.

6. The method of claim 5, further comprising populating a title field at the graphical user interface with the title of the caller.

7. The method of claim 5, further comprising forwarding the telephone call to a live customer service agent.

8. A method of processing calls received at an interactive voice response (IVR) server, the method comprising:

receiving a telephone call at the IVR server;

prompting a caller to speak a name associated with the caller;

receiving and recording a spoken name from the caller;

converting the spoken name into a speech recognition grammar pattern;

identifying a name of the caller based on a comparison between the speech recognition grammar pattern and at least one name recognition grammar pattern that is dynamically created by generating a phonetic spelling of a name in a text list of names of individuals associated with a telephone number from which the telephone call was initiated, the text list obtained from a customer service database;

determining a text string associated with the name of the caller from the text list;

comparing the text string to entries in a table to determine a gender of the caller, the table including a plurality of first names and an associated indication that a particular first name indicates the caller is one of a male caller and a female caller;

assigning a title to the caller based on the gender of the caller when the text string matches an entry in the table and displaying the title and the name of the caller on a service agent terminal; and

forwarding the telephone call, the name, and the title to the service agent terminal via a whisper transfer when a probability that the caller name is correct is determined to be below a predetermined threshold.

9. The method of claim 8, wherein the text string corresponds to a spelling of the name associated with the caller.

10. The method of claim 9, further comprising forwarding the telephone call to a customer service agent computer when the caller name is likely to be correct.

11. The method of claim 10, further comprising populating a name field at a graphical user interface displayed at the customer service agent computer with the identified name of the caller.

12. The method of claim 10, further comprising populating a title field at a graphical user interface displayed at the customer service agent computer with the title.

13. A system for identifying a telephone caller, the system comprising:

an interactive voice response server including a processor; a memory accessible to the processor; and

a computer program embedded within the memory, the computer program comprising:

instructions to identify a name associated with a telephone caller by:

converting a recorded spoken name from the telephone caller into a speech recognition grammar pattern; and

comparing the speech recognition grammar pattern to at least one name recognition grammar pattern that is dynamically created by generating a phonetic

7

- spelling of a name in a text list of names of individuals associated with a telephone number that initiated a received call, the text list obtained from a customer service database;
- instructions to determine a title associated with the telephone caller by:
- determining a text string associated with the name associated with the telephone caller from the text list;
 - comparing the text string to entries in a table to determine a gender of the telephone caller, the table including a plurality of first names and an associated indication that a particular first name indicates the caller is one of a male caller and a female caller; and
 - assigning the title to the telephone caller based on the gender of the telephone caller when the text string matches an entry in the table; and
- instructions to forward the title and a telephone call associated with the telephone caller to a service agent terminal.
- 14.** The system of claim **13**, wherein the text string corresponds to a spelling of the name associated with the telephone caller.
- 15.** The system of claim **14**, further comprising a customer service agent computer coupled to the interactive voice response server.
- 16.** The system of claim **13**, wherein the computer program further comprises instructions to forward the telephone call to a customer service agent computer.

8

- 17.** The system of claim **16**, wherein the computer program further comprises instructions to automatically populate a name field at a graphical user interface displayed at the customer service agent computer with the name associated with the telephone caller, when a probability that the title and the name associated with the telephone caller are correct is above a predetermined threshold.
- 18.** The system of claim **17**, wherein the computer program further comprises instructions to automatically populate a title field of a graphical user interface displayed at the customer service agent computer with the title.
- 19.** The method of claim **1**, further comprising determining a title of the caller at least partially based on a pitch of a voice of the caller when the text string does not match any entry in the table, wherein the pitch is derived from a recording of the spoken name.
- 20.** The method of claim **8**, further comprising determining a title of the caller at least partially based on a pitch of a voice of the caller when the text string does not match any entry in the table, wherein the pitch is derived from a recording of the spoken name.
- 21.** The system of claim **13**, wherein the instructions further comprise instructions to determine the title associated with the telephone caller at least partially based on a pitch of a voice of the telephone caller when the text string does not match any entry in the table, wherein the pitch is derived from the recorded spoken name.

* * * * *