



US007661223B2

(12) **United States Patent**  
**Dudney**

(10) **Patent No.:** **US 7,661,223 B2**  
(45) **Date of Patent:** **Feb. 16, 2010**

(54) **PORTABLE SECURITY DEVICE FOR FISHING RODS AND REELS**

FOREIGN PATENT DOCUMENTS

DE 3103783 A1 \* 9/1982

(76) Inventor: **Morris Dudney**, 5400 Preston Oaks Rd., Apt. 3020, Dallas, TX (US) 75240

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 265 days.

(Continued)

(21) Appl. No.: **11/830,060**

(22) Filed: **Jul. 30, 2007**

(65) **Prior Publication Data**

US 2009/0031610 A1 Feb. 5, 2009

(51) **Int. Cl.**

**A01K 97/18** (2006.01)

**E05B 73/00** (2006.01)

**B65D 33/01** (2006.01)

**B65D 33/16** (2006.01)

(52) **U.S. Cl.** ..... **43/26**; 206/315.11; 224/922; 70/65; 70/64; 70/18; 383/74; 383/72; 383/113; 383/119; 383/121; 383/100; 383/103

(58) **Field of Classification Search** ..... 43/26; 70/57–59, 61, 64, 65, 18, 63; 206/315.11, 206/315, 315.2, 315.3; 224/922; 383/71, 383/72, 74, 75, 109, 113, 117, 119, 121, 383/121.1, 100, 103

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

110,340 A \* 12/1870 Carter ..... 383/103  
314,985 A \* 3/1885 Young ..... 70/65  
403,928 A \* 5/1889 Emeric ..... 383/72  
436,287 A \* 9/1890 Marshall ..... 383/103  
651,256 A \* 6/1900 May ..... 383/71  
656,398 A \* 8/1900 Fairfax ..... 383/71  
672,499 A \* 4/1901 Tully ..... 383/117

OTHER PUBLICATIONS

CorporateTravelSafety.com, PacSafe LidSafe Secure Motorcycle Helmet Gear Bag, Jul. 5, 2007.

(Continued)

*Primary Examiner*—Darren W Ark



(74) *Attorney, Agent, or Firm*—Booth Albanesi Schroeder LLC

(57) **ABSTRACT**

A device is provided for securing against crime-of-opportunity theft at least one fishing rod and reel to be stored or transported in an outdoor, unsecured area or on an open, unsecured portion of a vehicle, such as an open bed of a pick-up truck, trailer, or boat. The device includes: (a) a flexible webbing material, wherein the flexible webbing material has a generally bag-like shape with an open end; (b) a first cable and first lock operatively connected for closing and locking the open end of the flexible webbing material around a forward portion of a fishing rod protruding through the open end when at least the rear portion thereof is positioned inside the flexible webbing material, and (c) a second cable and second lock operatively connected for attaching and locking the flexible webbing material to a fixed structure in the open area or on the vehicle; wherein each of the flexible webbing material, the first cable for closing, and the second cable for attaching is resistant to cutting with a hand-held knife.

(Continued)

**21 Claims, 6 Drawing Sheets**





# US 7,661,223 B2

Page 2

## U.S. PATENT DOCUMENTS

679,422	A *	7/1901	Heritage	43/26	4,306,601	A *	12/1981	Wallis et al.	43/26
764,398	A *	7/1904	Upton	43/26	4,311,262	A *	1/1982	Morin	224/922
849,040	A *	4/1907	Benser et al.	70/65	4,359,161	A *	11/1982	Sinoff	43/26
866,965	A *	9/1907	Redding	70/65	4,369,904	A *	1/1983	Christensen	206/315.11
909,726	A *	1/1909	Williams	383/103	4,381,113	A *	4/1983	Simons	273/286
1,001,996	A *	8/1911	Scott	70/65	4,493,416	A *	1/1985	Steinman	43/26
1,010,901	A *	12/1911	Hamm	383/119	4,503,559	A *	3/1985	Warnke	383/117
1,015,908	A *	1/1912	Sackett	70/64	4,523,704	A *	6/1985	Washington	43/26
1,020,395	A *	3/1912	Beck	70/65	4,530,178	A *	7/1985	Rauscher	43/26
1,055,002	A *	3/1913	Varnum	70/65	4,546,877	A *	10/1985	Evans	224/922
1,148,924	A *	8/1915	Paradise	383/71	4,576,316	A *	3/1986	Foster	383/103
1,418,717	A *	6/1922	Josephson	383/121.1	4,641,454	A *	2/1987	Ray et al.	43/26
1,700,734	A *	2/1929	Brandt	206/315.3	4,643,302	A *	2/1987	Baumgardner	206/315.11
1,814,378	A *	7/1931	Gilbertson et al.	383/117	4,648,121	A *	3/1987	Lowe	383/113
1,903,798	A *	4/1933	Turner	43/26	4,696,122	A *	9/1987	Van Der Zyl	43/21.2
1,915,196	A *	6/1933	McGuire	383/117	4,726,141	A *	2/1988	McBride et al.	43/26
1,980,104	A *	11/1934	Silverspitz	43/26	4,775,082	A *	10/1988	Krache	224/920
1,982,813	A *	12/1934	Jacobi	70/65	4,783,978	A *	11/1988	Vallerga	70/65
2,022,251	A *	11/1935	Mallay et al.	383/71	4,792,073	A *	12/1988	Jacober	70/58
2,040,559	A *	5/1936	Luttrell	383/103	4,811,419	A *	3/1989	Derby	383/121
2,105,853	A *	1/1938	Brodie	206/315.6	4,817,403	A *	4/1989	Dimmick	70/64
2,136,598	A *	11/1938	Strayer	70/65	4,863,019	A *	9/1989	Lewis et al.	70/64
2,166,860	A *	7/1939	Davis	70/65	4,876,819	A *	10/1989	Clifford	43/26
2,253,688	A *	8/1941	Collins	383/117	4,916,852	A *	4/1990	Zebleckis	43/26
2,323,318	A *	7/1943	Farkas	383/117	4,946,478	A *	8/1990	Davis et al.	383/103
2,416,747	A *	3/1947	Geimer	383/117	4,949,842	A *	8/1990	Mokiao, II	383/103
2,447,940	A *	8/1948	Holland	383/113	4,974,537	A *	12/1990	Martin	224/922
2,510,186	A *	6/1950	Marsico et al.	383/72	5,004,100	A *	4/1991	Smith	206/315.2
2,552,443	A *	5/1951	Molinari	383/117	5,012,964	A *	5/1991	Falletta et al.	383/103
2,603,028	A *	7/1952	Roberts	383/103	5,050,999	A *	9/1991	Van Loon, III	383/74
2,618,880	A *	11/1952	Sourek	43/26	5,199,572	A *	4/1993	Abe	383/72
2,682,290	A *	6/1954	Ditlea	383/117	D340,576	S *	10/1993	Delagarza et al.	D3/260
2,713,370	A *	7/1955	Quinn	383/117	5,277,306	A *	1/1994	Sargent	43/26
2,723,482	A *	11/1955	Marten	43/26	5,293,711	A *	3/1994	Robinson	43/26
2,739,409	A *	3/1956	Sokolik	383/103	5,310,103	A *	5/1994	Weber et al.	224/922
2,823,971	A *	2/1958	Hoyt	43/26	5,327,669	A *	7/1994	Lannan et al.	43/26
2,854,775	A *	10/1958	Kleckley	43/26	5,361,611	A *	11/1994	Hisler	224/922
2,867,257	A *	1/1959	Cart	206/315.3	5,366,076	A *	11/1994	Lyles	43/26
2,869,277	A *	1/1959	Breithaupt	43/26	5,417,354	A *	5/1995	Jones	43/26
2,897,863	A *	8/1959	Somers, Jr.	383/103	5,425,194	A *	6/1995	Miller	43/26
2,907,506	A *	10/1959	Sammons	224/922	5,435,473	A *	7/1995	Larkum	224/922
2,913,029	A *	11/1959	Paton	383/113	5,445,267	A *	8/1995	Biafore, Jr.	206/315.3
2,913,030	A *	11/1959	Fisher	206/315.11	5,450,688	A *	9/1995	Hall	43/26
3,033,259	A *	5/1962	Landis, Sr.	206/315.11	5,460,306	A *	10/1995	Rudd	224/922
3,176,427	A *	4/1965	Hershey	383/117	5,490,594	A *	2/1996	Rupe	206/315.4
3,204,362	A *	9/1965	Andrews	43/26	5,505,300	A *	4/1996	Joh	206/315.6
3,406,930	A *	10/1968	Seiler	224/922	5,515,641	A *	5/1996	D'Alessandro	43/26
3,490,169	A *	1/1970	Tweed	206/315.11	5,518,315	A *	5/1996	Nichols	383/119
3,575,327	A *	4/1971	Harrison	43/26	5,560,485	A *	10/1996	O'Hara, Jr.	70/58
3,635,433	A *	1/1972	Anderson	211/70.8	5,582,043	A *	12/1996	McCue et al.	70/18
3,662,933	A *	5/1972	Michel	43/26	5,603,573	A *	2/1997	Mercier et al.	383/117
3,674,188	A *	7/1972	Anderson	383/103	5,625,973	A *	5/1997	Anthony	43/26
3,674,190	A *	7/1972	Wright	43/26	5,632,427	A *	5/1997	Gattuso et al.	224/922
3,701,371	A *	10/1972	Stackhouse	383/103	5,794,747	A *	8/1998	Bryant	383/103
3,744,687	A *	7/1973	Oreck	224/913	5,813,164	A *	9/1998	Liberto	43/21.2
3,762,592	A *	10/1973	Mayes	43/26	5,870,023	A *	2/1999	Jackson	206/315.3
3,811,216	A *	5/1974	Sauey et al.	43/26	5,904,247	A *	5/1999	Voelkner, Jr.	206/315.3
3,876,076	A *	4/1975	Hazelhurst	211/70.8	5,909,833	A *	6/1999	Smith	383/67
3,972,144	A *	8/1976	Geisler	43/26	5,941,195	A *	8/1999	Martz	383/100
4,027,798	A *	6/1977	Swaim	211/70.8	6,026,662	A *	2/2000	Schlipper	70/65
4,063,646	A *	12/1977	Stahl, Jr.	224/922	6,077,587	A *	6/2000	Potok	70/65
4,077,151	A *	3/1978	Johnson	206/315.11	6,085,695	A *	7/2000	Miller et al.	43/26
4,094,351	A *	6/1978	Catenaccio	383/103	6,119,858	A *	9/2000	Davidson	206/315.11
4,134,225	A *	1/1979	Welch	383/119	6,148,998	A *	11/2000	Tan	206/315.3
4,136,478	A *	1/1979	Wycosky	43/26	6,155,001	A *	12/2000	Marin	43/26
4,156,446	A *	5/1979	Nathan	383/103	6,186,087	B1 *	2/2001	Vinas	211/70.8
4,170,801	A *	10/1979	Ward	43/26	6,234,312	B1 *	5/2001	Davis, Sr.	206/315.4
4,175,604	A *	11/1979	Bonner	70/65	6,244,081	B1 *	6/2001	Schlipper	70/65
4,222,193	A *	9/1980	Beck	43/26	6,263,610	B1	7/2001	Doubts, Jr.	
4,251,938	A *	2/1981	Goldman et al.	43/11	6,269,587	B1 *	8/2001	Wallace	206/315.11
4,252,324	A *	2/1981	Simons	206/579	6,343,728	B1 *	2/2002	Carbone	43/26
					6,447,165	B1 *	9/2002	Grewe	383/121.1
					6,471,054	B2 *	10/2002	Nevarez	206/315.11

6,499,248	B2 *	12/2002	Thompson .....	43/21.2
6,530,170	B1 *	3/2003	Sweeney .....	43/21.2
6,564,498	B2 *	5/2003	Sawtell .....	43/26
6,742,789	B1 *	6/2004	Nowak .....	43/54.1
6,760,994	B2 *	7/2004	Henault et al. ....	43/26
6,865,841	B2 *	3/2005	Wieringa .....	43/26
6,932,224	B1 *	8/2005	Sandberg .....	211/70.8
7,021,825	B1 *	4/2006	Schultz .....	383/76
7,069,753	B2 *	7/2006	Schlipper .....	70/65
7,219,464	B1 *	5/2007	Kujawa .....	224/922
7,322,149	B1 *	1/2008	Quintero .....	43/26
7,363,783	B2 *	4/2008	Kolton et al. ....	206/315.11
7,412,857	B2 *	8/2008	Kolton et al. ....	70/63
2002/0032978	A1 *	3/2002	Sawtell .....	43/26
2002/0134119	A1 *	9/2002	Derman .....	70/58
2004/0134117	A1 *	7/2004	Gagnon .....	43/26
2005/0126063	A1 *	6/2005	Bowerman .....	43/21.2
2006/0196102	A1 *	9/2006	Gagnon .....	43/26
2006/0207161	A1 *	9/2006	Lynn .....	43/26
2007/0039231	A1 *	2/2007	Jenkins .....	43/26
2008/0053169	A1 *	3/2008	Ricker et al. ....	70/64
2008/0115542	A1 *	5/2008	Pengelly .....	70/18
2008/0226207	A1 *	9/2008	Frayne .....	383/100
2009/0008007	A1 *	1/2009	Dube .....	70/64

FOREIGN PATENT DOCUMENTS

DE	19630916	C1 *	12/1997
DE	10032751	A1 *	9/2001
FR	2603936	A1 *	3/1988

GB	2224916	A *	5/1990
GB	2280704	A *	2/1995
JP	10117844	A *	5/1998
JP	10227162	A *	8/1998
JP	11075654	A *	3/1999
JP	11152190	A *	6/1999
JP	2000230355	A *	8/2000
JP	2004344124	A *	12/2004
JP	2005237339	A *	9/2005
JP	2006187235	A *	7/2006
JP	2006197844	A *	8/2006
JP	2008161140	A *	7/2008

OTHER PUBLICATIONS


NorthernTool.com, Northern Tool & Equipment, Peerless Cold Shut—1/4in. Size, Apr. 25, 2007.


Cabela’s; Master Fishing Catalog; pp. 247-248, Reel Cases and Covers; Advanced Anglers Adjustable Rod Covers; Pro Rod Bags; Rod Cases; pp. 251-255, Rod Tubes; Rod Racks; Angler’s Tote; Vehicle Rod Carrier; Rod Loft Pro; Pack-A-Pole-Case; Rod Holder; Izorline Rod Sling; Frabill Pack-A-Pole Adjustable Soft Case; 2006, www.cabelas.com, Sidney Nebraska USA.


Bass Pro Shops 2006 Fishing Master Catalog; pp. 158-165, Rod Racks; Fentress Tote’em Rack; Rod Tote: Rod Ready; Lock ‘N’ Hold Rack; Rod Rack ‘N Go; Rod Cases; Bazuka Pro; Frabill Pack-A-Pole Case; Browning Combo Caddy; Neoprene Caddy; Bass Pro Shops Reel Tote; Rod Wrap; Reel Cover; 2006, www.basspro.com, Springfield, Missouri USA.

\* cited by examiner



















FIG. 10






FIG. 11

1

# PORTABLE SECURITY DEVICE FOR FISHING RODS AND REELS

## CROSS-REFERENCE TO RELATED APPLICATIONS

Not applicable.

## STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

Not Applicable.

## REFERENCE TO A MICROFICHE APPENDIX

Not applicable.

## TECHNICAL FIELD

The present invention generally relates to devices for temporarily storing one or more fishing rods in an open area or vehicle and securing the fishing rods against crime-of-opportunity theft.

## SUMMARY OF THE INVENTION

A device is provided for securing against crime-of-opportunity theft at least one fishing rod and reel to be stored or transported in an outdoor, unsecured area or on an open, unsecured portion of a vehicle, such as an open bed of a pick-up truck, trailer, or boat.

According to one aspect, the device includes: (a) a flexible webbing material, wherein the flexible webbing material has a generally bag-like shape with an open end; (b) a first cable and first lock operatively connected to the flexible webbing material for closing and locking the open end of the flexible webbing material around a forward portion of a fishing rod when at least the rear portion thereof is positioned inside the flexible webbing material, and (c) a second cable and second lock operatively connected to the flexible webbing material for attaching and locking the flexible webbing material to a fixed structure in the open area or on the vehicle; wherein each of the flexible webbing material, the first cable for closing, and the second cable for attaching is resistant to cutting with a hand-held knife.

According to another aspect of the invention, the device includes a first flexible webbing material, (i) wherein the first flexible webbing material, when opened, has a generally-tubular shape with at least one open end, and wherein the generally-tubular shape of the first flexible webbing material, when opened, has at least a sufficient internal cross-section and at least a sufficient internal length to receive at least a rear portion of a butt end of at least one fishing rod and reel, wherein the rear portion of the butt end comprises at least a handle, a reel seat, and an attached reel; (ii) wherein the first flexible webbing material is capable of retaining at least the rear portion of the butt end of at least one fishing rod and reel positioned therein from being removed in any direction substantially perpendicular to the internal length of the generally-tubular shape of the first flexible webbing material; whereby the rear portion of the butt end of at least one fishing rod and reel can be inserted or removed through the open end of the first flexible webbing material in a direction generally parallel to the internal length of the first flexible webbing material.

The device also includes a closure means for securing and locking the open end of the first flexible webbing material at

2

least partially around a forward portion of a fishing rod protruding through the upper end when at least the rear portion thereof is positioned inside the flexible webbing material. When in such a closed position, a largest cross-section of the rear portion of the butt end of a fishing rod and reel cannot be removed through the open end of the flexible webbing material.

Further, the device includes an attaching means for securing and locking the flexible webbing material to a fixed structure in the open area or on the vehicle.

Each of the first flexible webbing material, the closure means, and the attaching means is resistant to cutting with a hand-held knife.

According to yet another aspect of the invention, a method is provided for securing against crime-of-opportunity theft of a fishing rod and reel to be stored or transported in an outdoor, unsecured area or on an open, unsecured portion of a vehicle. The method includes the steps of: (a) inserting at least a rear portion of at least one fishing rod and reel into and through an opening of a body of a device having a generally bag-like shape and formed of a flexible webbing material; (b) closing and locking the opening of the flexible webbing material around a forward portion of the fishing rod protruding through the opening when at least the rear portion thereof is positioned inside the body formed of the flexible webbing material and locking the closure for the opening to prevent removal of the rear portion of the fishing rod from inside the device; (c) attaching and locking the body of the device to any available fixed structure in the open area or on the vehicle. Each of the flexible webbing material, the closure for the opening, and the attachment to the fixed structure is resistant to cutting with a hand-held knife.

These and further aspects of the invention are described in more detail below.

## BRIEF DESCRIPTION OF THE DRAWINGS

A more complete understanding of the present disclosure and advantages thereof may be acquired by referring to the following description taken in conjunction with the accompanying drawings, which:

FIG. 1 is a perspective view toward the upper end of a presently most-preferred embodiment of the portable device for securing a plurality of fishing rods, which illustrates the device enclosing the rear portions of a plurality of fishing rods and having forward portions of the fishing rods protruding from the upper end of the device, and further illustrating a cable woven between and about the forward portions of the fishing rods and the upper end of the device to cinch down the opening around the forward ends of the plurality of fishing rods protruding from the upper end of the device and secure the fishing rods from crime-of-opportunity theft;

FIG. 2 is an enlarged view of the upper end of the device and a cable woven through and around a plurality of fishing rods extending through the opening of the device and cinching down the opening of the device around the plurality of fishing rods protruding through the opening;

FIG. 3 is a perspective view toward the bottom end of the presently most-preferred embodiment of the device, wherein a first flexible webbing material forming a generally tubular portion and a second flexible webbing material forming a bottom-wall portion together form a generally bag-shaped body for the device, and wherein the forward portions of a plurality of fishing rods are illustrated protruding from the upper end of the device;



3

FIG. 4 is a detail view of a representative link for connecting a portion of the first flexible webbing material and a portion of the second flexible webbing material of the device to one another;

FIG. 5 is another perspective view toward the upper end of the embodiment of the device shown in FIG. 1, wherein the upper end of the bag-shaped body of the device is shown with the opening thereof in an open position in which it is easy to insert (or remove) the rear portions of one or more fishing rods, and in particular illustrates the position of a plurality of fishing rods having been inserted into the bag-like body of the device with forward portions thereof protruding from the opening of the bag-shaped body;

FIG. 6 is another perspective view toward the upper end of the embodiment of the device shown in FIGS. 1 and 5, wherein the upper end of the bag-shaped body of the device is shown with the opening thereof in the process of being closed (or opened) around the forward portions of a plurality of fishing rods protruding from the bag-shaped body of the device;

FIG. 7 illustrates a presently-preferred construction of the first flexible webbing material, which includes two sheets of a flexible plastic material sandwiching a plurality of reinforcing strands of cable laid out in a crisscrossing pattern and wherein some of the cable can be laid out in a snaking back-and-forth pattern to form lower-end loops and upper-end loops at either end of the material, which lower-end loops can be used for attaching a second flexible webbing material to form a bottom of a bag-shaped device and the upper-end loops at the other end can be used for cinching the opening of the device around a forward portion of a fishing rod;

FIG. 8 illustrates a view toward the upper end of the presently-preferred construction of the first flexible webbing material;

FIG. 9 illustrates a presently-preferred construction of the second flexible webbing material, which includes two sheets of a flexible plastic material sandwiching a plurality of reinforcing strands of cable laid out in a crisscrossing pattern, especially wherein two cables can be laid out in a snaking back-and-forth pattern perpendicular to each other to form bottom loops at all sides of the material, which bottom loops can be used for attaching the second flexible webbing material to the first flexible webbing material to form a bottom of a bag-shaped device;

FIG. 10 illustrates a view of the second flexible webbing material after it has been constructed; and

FIG. 11 illustrates the use of the device for securing a plurality of fishing rods in the back of an open-bed vehicle, such as a pick-up truck.

#### DETAILED DESCRIPTION OF PRESENTLY-PREFERRED EMBODIMENT

The present invention is particularly focused on the problem of protecting fishing rods and attached reels from crime-of-opportunity theft. Fishing rods and reels are often quite valuable. The retail cost of a few good fishing rods and reels can run into the hundreds and even thousands of dollars.

Fishing rods and reels are peculiar, however, because they are extremely long in relation to their other dimensions. This makes fishing rods and reels rather difficult to secure against crime-of-opportunity theft. For example, they are usually much too long to store in a duffle bag or in the trunk of a vehicle. Some fishing rods are collapsible, but that can be time-consuming and make the fishing rod less accessible and convenient to use. Most vehicles and boats do not have special storage devices for fishing rods and reels.

4

Even if a particular fishing rod and reel can be taken apart and collapsed and later re-assembled, these can be relatively time-consuming processes, and it is often preferred to keep fishing rods with their reels maintained in an assembled condition. It is often desired to temporarily secure fishing rods and reels in areas accessible to the public or in the bed of a vehicle such as a pick-up truck, trailer, or boat. These kinds of situations can expose the fishing rods and reels to crime-of-opportunity theft.

It would be desirable to have a device and methods for temporarily storing and locking fishing rods and reels in an open area or in the bed of a vehicle against crime-of-opportunity theft. The device should be simple in design and easy to use. The device should also be relatively quick to use, for example, it should be possible to secure a plurality of fishing rods in a matter of about 10 seconds or so, and similarly, it should be possible to release the fishing rods in a similarly short amount of time. The device should help protect the fishing rods and reels against damage and not itself damage the rods. The present invention is well adapted to accomplish these and other purposes.

#### Definitions

As used herein, the words “comprise,” “has,” and “include” and all grammatical variations thereof are each intended to have an open, non-limiting meaning that does not exclude additional elements or parts of an assembly, subassembly, or structural element.

As used herein, “generally” means of or having such a characteristic, as in “bag-shaped” or at least recognizably or approximately having such a characteristic shape, even if not exactly of or having the characteristic.

As used herein, terms such as “first,” “second,” “third,” etc. are arbitrarily assigned and are merely intended to differentiate between two or more parts that are similar or corresponding in structure and/or function. It is to be understood that the words “first” and “second” serve no other purpose and are not part of the name or description of the following terms. Furthermore, it is to be understood that the mere use of the term “first” does not require that there be any “second” similar or corresponding part, either as part of the same element or as part of another element. Similarly, the mere use of the word “second” does not require that there be any “third” similar or corresponding part, either as part of the same element or as part of another element, etc.

As used herein, the words “upper,” “lower,” and “bottom,” are with respect to the direction of insertion of a fishing rod into a device according to the invention, wherein, as will hereinafter be described in detail, the rear portion of a fishing rod is inserted into an opening in the upper end of the device and through the interior of the device toward a lower end and bottom of the device.

It should also be understood, for example, that the function of a single structure described herein can sometimes be performed by more than one part unless the context requires otherwise, or the functions of two different structures can be performed by a single or integrally formed part. Especially from manufacturing and cost perspectives, it is preferred to design so as to minimize the number of parts. These costs include not only the costs associated with making the parts, but also the costs of assembly. Preferably, the fewest possible number of parts and steps required to manufacture and assemble the apparatus, the better.

If there is any conflict in the usages of a word or term in this specification and one or more patent or other documents that may be incorporated herein by reference, the definitions that



## 5

are consistent with this specification should be adopted for the purposes of understanding this invention.

## Fishing Rod Definitions

It is to be understood, of course, that the purpose of this invention is for the temporary storage and protection against crime-of-opportunity theft of one or more fishing rods.

As used herein, the term “fishing rod” means and includes an attached reel, unless the presence of the reel for the rod is separately specified.

The size and shape of the device according to the invention is appropriately defined in relation to a fishing rod and, more particularly, certain parts of a fishing rod. For this purpose, it should be understood, for example, the length of typical fishing rods range from about 5 feet (1.5 meters) to about 12 feet (3.7 meters) long, depending on the type. It should be further understood that the diameter of a typical reel is in the range of about 2 inches (5 cm) to about 6 inches (15 cm). Typically, a reel is mounted onto the rod blank and stands off from the rod a sufficient distance to allow for operation of the reel, typically in the range of about 0 inches (0 cm) to about 4 inches (10 cm) from the rod blank. Of course, a few fishing rods are outside these ranges, but for reference purposes, these are typical.

A “rod blank” is the central shaft everything else on the fishing rod is built around. Blanks can be made of different materials, but most rods are now constructed of graphite. The rod blank is typically tapered, and the top of the blank is called the “tip,” while the heavy section is known as the “butt.”

To facilitate transportation, longer rods, such as those for most fly rods, are manufactured in sections. The sections have special joints, called “ferrules,” that slip together snugly.

At the butt of the rod blank is the “reel seat.” The foot of a reel is slipped into the reel seat, and locking rings are screwed down to hold the foot firmly in place. Modern reel seats are generally either metal or graphite.

Next to the reel seat is the “rod handle,” which typically extends between the reel seat and the rearward end of the butt. Handles come in a number of different shapes and sizes. Most rods feature cork handles, but some less expensive rods utilize rubber ones.

“Rod guides” are attached to the blank, and the fishing line slides through them. Rod guides come in several different shapes.

As used herein, the “rear portion” of a fishing rod includes at least the reel seat, the reel, and the rod handle of the butt; whereas the “forward portion” of a fishing rod is any portion of a fishing rod from the tip toward the rear portion and that excludes at least the “rear portion.”

As used herein, a largest cross-section of the rear portion of a fishing rod and reel is the largest cross-sectional area through the fishing rod and attached reel that is perpendicular to the length of the rod blank of the fishing rod.

The parts of a fishing rod and reel are extremely common and well known. No more particular description of such well-known items should be necessary for the purposes of describing this invention.

## Other Definitions

As used herein, the term “cut-resistant” means resistant to cutting with a knife, such as a pocket knife that may be commonly carried. It should be understood, of course, that, as the purpose of the invention is to help protect against crime-of-opportunity theft it is not necessary to guard against cutting with wire-cutters or power tools. Examples of materials that would be considered cut-resistant include braided steel wire and flexible sheet material reinforced with braided steel wire. In contrast, examples of materials that would not be

## 6

considered “cut-resistant” include flexible sheet material made entirely of natural fabric such as hemp canvas or plastic film such as polyethylene or polypropylene, and thin rope made entirely of natural hemp fibers.

As used herein, a “lock” means a security fastening, for example, a security fastening operated by a key or a combination. Similarly, “locking” means the act of securing and locking with such a security fastening. The lock should be sufficient to deter crime-of-opportunity theft, but is not required to be strongly resistant to cutting with heavy-duty tools such as bolt, chain, or wire cutters or resistant to cutting with electrically-powered cutting tools.

## Device According to a Presently Most-Preferred Embodiment

FIG. 1 of the drawing is a perspective view of a presently most-preferred embodiment of a device according to the invention, where the device is generally designated in the figures by the reference numeral **100**. The device **100** has a generally bag-shaped body **102**, which includes a generally-tubular portion **104**, which in FIG. 1 is shown in a wrapped and closed condition for securing a plurality of fishing rods **10**. The perspective view of FIG. 1 is toward an upper end **106** of generally-tubular portion **104** of the generally bag-shaped body **102** of the device **100**. FIG. 2 is a detail of the upper end **106** of the device **100**.

An upper-end circumferential edge **108** of the upper end **106** defines an opening **110**. As shown in FIGS. 1-2, the flexible material of the generally-tubular portion **104** at the upper end **106** can be folded and wrapped to have a wrapped portion **111**. The wrapped portion is wrapped around to substantially reduce the size of the opening **110**. Wrapping and gathering the upper end **106** forms a plurality of pleats **112** in the flexible material of the generally tubular portion **104**.

Referring to FIG. 1, the generally-tubular portion **104** of the device **100** also has a lower end **114** and a lower circumferential edge **116**, which can be attached to a bottom-wall portion **118** (not shown in FIG. 1) as hereinafter described in more detail.

The generally-tubular portion **104** of the device **100** is formed of a cut-resistant, flexible webbing material as will hereinafter be described in more detail.

FIG. 3 is a perspective view toward the lower end **114** and a bottom-wall portion **118** of the presently most-preferred embodiment of the device **100**. The bottom-wall portion **118** has a bottom-wall peripheral edge **119**. The generally bag-shaped body **102** includes both the generally-tubular portion **104** and the bottom-wall portion **118**, which together form the generally bag-shaped body **102** for the device **100**.

As will hereinafter be described in more detail, the bottom-wall portion **118** is preferably formed of a cut-resistant material. More preferably, the bottom-wall portion **118** is formed of a cut-resistant, flexible webbing material.

Overall, the generally bag-shaped body **102** and the device **100** as a whole are preferably durable flexible, and relatively lightweight to be easily portable by hand. Preferably, the device weighs between about 2 and 7 pounds (0.9 and 3 Kg), and most preferably about 4-5 pounds (1.8-2.2 Kg).

Continuing to refer to FIG. 3, an interconnecting means **120** is provided for operably connecting the generally-tubular portion of **104** and the bottom-wall portion **118** of the generally bag-shaped body **102**. According to a presently most-preferred embodiment of the invention, the interconnecting means **120** includes a plurality of lower-end loops **122** formed in or connected to a lower circumferential edge **116** of the lower end **114** of the generally-tubular portion **104**. The inter-



connecting means **120** also includes a plurality of bottom-wall loops **124** formed in or connected to a bottom-wall peripheral edge **119** of the bottom-wall portion **118**. Further, the interconnecting means includes a plurality of links **126**, where, as best shown in the detail view of FIG. 4, each of the plurality of links **126** can be used to connect one of the plurality of lower-end loops **122** of the lower circumferential edge **116** of the generally-tubular portion **104** to one of the bottom-wall loops **124** of the bottom-wall peripheral edge **119** of the bottom-wall portion **118**. Accordingly, the lower end **114** of the generally-tubular portion **104** can be interconnected to the bottom-wall portion **118**. This provides a simple method of manufacturing the generally bag-shaped body **102**. Further, this provides a peripheral gap **128** between the lower end **114** generally-tubular portion **104** and the bottom-wall portion **118**. The peripheral gap **128** allows for any water to drain out of the generally bag-shaped body **102** and for air to circulate into and out of the generally bag-shaped body **102**. The peripheral gap **128** can help keep the interior of the device **100** free of mold and mildew.

Referring again primarily to FIG. 1, the structure of preferred cut-resistant, flexible webbing material for making the generally-tubular portion **104** and the bottom-wall portion **118** of the bag-shaped body **102** are each hereinafter described in more detail. It should be understood, of course, that the generally bag-shaped body **102** can be manufactured to be formed of a flexible material that is connected together to form the generally bag-shaped body **102** without having any peripheral gap **128**, however, that would not provide some of the advantages of having a relatively small opening for circulating air, such as the peripheral gap **128**.

The generally bag-shaped body **102** of the device **100** is of a size and adapted for enclosing and securing a plurality of fishing rods, each fishing rod generally designated by the reference numeral **10**. Each fishing rod **10** has a rear portion **11** (one of which is shown in outline in FIG. 1), including an attached reel **13**, positioned inside the bag-shaped body **102** of the device **100**. A forward portion **12** of each fishing rod **10** is illustrated protruding from the upper end **106** of the device **100**, each rod having a plurality of guides **14**.

It is not necessary for the device **100** to enclose the entire length of the fishing rods **10**, provided that rear portion **11** having the reel **13** on each of the fishing rods can be protected. Preferably, the generally-tubular portion **104** of the bag-shaped body **102** has an internal diameter in the range of about 12-18 inches (30-46 cm) and an internal length in the range of 30-48 inches (76-120 cm). According to the presently most-preferred embodiment, the generally-tubular portion **104** of the bag-shaped body **102** has an internal diameter of about 15 inches (38 cm) and an internal length of about 36 inches (91 cm). As the generally-tubular portion **104** is made of a flexible material, the bottom-wall portion **118** can be of any convenient shape, but, according to the presently most-preferred embodiment, the bottom-wall portion **118** is preferably square.

Preferably, at least the interior surface of the generally-tubular portion **104** of the bag-shaped device is smooth, such as the surface of a plastic sheet, whereby the insertion and removal of the rear portion **11** of a fishing rod with an attached reel **13** is reasonably well protected and unlikely to catch or snag on any interior surface features. The interior surface is preferably relatively smooth so that it does not scratch or damage a fishing rod.

As shown in FIGS. 1-2 and as will hereinafter be described in more detail, a wrapped portion **111** of the upper end **106** of the device **100** can be wrapped and cinched down around the forward ends **12** of the plurality of fishing rods **10** protruding

from the upper end **106** of the device **100**. FIG. 1 shows the device **100** in a closed position for securing a plurality of fishing rods **10** having forward portion **12** of the fishing rods **10** protruding through the cinched down opening **110** in the upper end of the device. As best illustrated in FIG. 2, when the flexible material of the upper end **106** of the generally-tubular portion **104** is wrapped around and gathered together or cinched down, it reduces the full-size of the opening **110** to prevent removal of the rear portions **11** of the plurality of fishing rods **10** that can be easily placed therein when the opening **110** is fully opened, as will be hereinafter described in more detail. Further, as best shown in the detailed view of FIG. 2 and as will be hereinafter described in more detail, a first cable **134** of a closure means **130** is used to thread and weave between and around the forward portions **12** of the fishing rods **10** to help secure the rods inside the device **100**.

As shown in FIGS. 1 and 2, a closure means **130** is provided for securing the opening **110** of the upper end **106** of the generally-tubular portion **104** of the body **102** at least partially around a forward portion **12** of a fishing rod **10** when at least the rear portion of the fishing rod is positioned inside the body **102**. Thus, when in such a closed position, a largest cross-section of the rear portion of a fishing rod and reel cannot be removed through the upper end **106** of generally-tubular portion **104**.

According to the presently most-preferred embodiment of the invention, the closure means **130** includes a plurality of upper-end loops **132** formed in or connected to the upper-end circumferential edge **108** of the upper end **106** of the generally tubular portion **104**. The upper end loops **132** are preferably uniformly spaced around the upper-end circumferential edge **108** of the upper end **106**. This provides for the ability to uniformly cinch the opening **110** toward a closed position around the forward portion or portions **12** of one or more fishing rods **10**.

The upper-end loops **132** are preferably formed of cut-resistant cable, which can be made of braided stainless steel. Additionally, each of the plurality of upper-end loops **132** preferably has a plastic coating, such as a vinyl plastic coating. The plastic coating on the loops **132** helps prevent the cable forming the loops from damaging the forward portions **12** of fishing rods **10** protruding from the upper end **106** of the generally-tubular portion **104**. The plastic coating also improves the weather and salt-water resistance of the metal wire used in the upper-end loops **132**.

The closure means **130** also includes a cable, which is arbitrarily referred to as a first cable **134**, that is or can be threaded through some or all of this plurality of upper-end loops **132**. The first cable **134** is preferably a braided metal cable, which resists cutting with a hand-held knife. Additionally, the first cable **134** preferably has a plastic coating, such as a vinyl plastic coating. The plastic coating on the first cable helps prevent the cable from damaging the forward portions **12** of the fishing rods. The plastic coating also improves the weather and salt-water resistance of the metal wire used in the first cable **134**.

At least one end of the first cable **134** has a loop end **136**. As shown in FIGS. 1 and 5, the loop end **136** can be formed by using a clamp **137**, which can be pressed to rigidly hold two portions of the end of the first cable **134** adjacent to one another to form the loop end **136**. The other end of the first cable **134** can be connected securely to the generally-tubular portion **104** of the body **102**. As will be appreciated, it is also contemplated that the first cable **134** could have a loop end at each end of the first cable **134**, which could be used to secure the two ends together in cinching the opening **110** into a closed position. The closure means **130** preferably further



includes a lock, such as a padlock **138**. For example, the padlock **138** can be operated with a key or a combination, or both, as desired or convenient.

As shown in FIGS. **1** and **2**, the first cable **134** can threaded and woven through some of upper end loops **132** of the upper-end circumferential edge **108** to help gather and cinch the wrapped portion **111** of the opening **110** of the upper end **106** of the generally-tubular portion **104** around the forward portion **12** of a fishing rod **10** when at least the rear portion of the fishing rod **10** is positioned inside the bag-shaped body **102** as shown in FIG. **1**. Some of the length of the cable **134** can be preferably threaded around and between the individual forward portions **12** of the fishing rods **10** and/or around the upper end **106** of the body **102**, as can be convenient or desired. As the loops **132** and the cable **134** are preferably plastic coated, they should not damage the delicate material of the rod blank of a fishing rod. The cable **134** threaded and woven around and between the fishing rods **10** makes it impossible to quickly remove the fishing rods with attached reels from the device.

The padlock **138** can be used selectively to secure the first cable **134** in any convenient manner to itself, to any of the upper-end loops **132** to maintain the upper end **106** of the generally-tubular portion **104** securely around the protruding forward portion **12** of a fishing rod **10** or around the forward portions of a plurality of fishing rods, thereby preventing removal of a fishing rod **10**.

As shown in FIGS. **1** and **3**, an attachment means **140** is provided for securing the generally bag-shaped body **102** to a fixed structure in the open area or on the vehicle. Thus, when the attachment means **140** is secured to such a fixture, the body **102** cannot be picked up and stolen. According to the invention, it is preferable to have separate closure means **130** and attachment means **140**. This allows the body **102** to be attached to a fixed structure independently of using the closure means **130** for closing and re-opening the body **102**. A benefit is that the attachment means **140** can be positioned and locked without concern for the arrangement of the closure means **130** for securing and locking one or more fishing rods **10** in position partially inside the body **102** of the device **100**. It is believed that having a separate closure means **130** and attachment means **140** would be faster and easier to use for securing and locking one or more fishing rods, especially when desired to do so repeatedly during a fishing trip.

According to the presently most-preferred embodiment of the invention, the attachment means **140** includes the plurality of lower-end loops **122** formed in or connected to the lower-end peripheral edge **116** of the lower end **114** of the generally-tubular portion **104**. In other words, the lower-end loops **122** can serve two functions, one, as previously described, to interconnect the generally-tubular portion **104** and the bottom-wall portion **118** of the generally bag-shaped body **102**; and two, as part of the attachment means **140**. It should be understood, of course, that separate structures could be used for each of these purposes. Additionally, each of the lower-end loops **122** preferably has a plastic coating, such as a vinyl plastic coating. The plastic coating on the lower-end loops **122** helps prevent the cable of the loops from damaging the butts of the fishing rods **10**. The plastic coating also improves the weather and salt-water resistance of the metal wire used in the lower-end loops **122**.

The attachment means **140** also includes a cable, which is arbitrarily referred to as a second cable **144**. The cable **144** is or can be threaded through some or all of this plurality of lower-end loops **122**. The second cable **144** is preferably a braided metal cable, which resists cutting with a hand-held knife (which is preferably made of the same braided metal

cable as the first cable **134**). Additionally, the second cable **144** preferably has a plastic coating, such as a vinyl plastic coating. The plastic coating on the second cable **144** helps prevent the cable from damaging the forward portions **12** of the fishing rods. The plastic coating also improves the weather and salt-water resistance of the metal wire used in the second cable **144**.

At least one end of the second cable **144** has a loop end **146**. As shown in FIGS. **1** and **3**, the loop end **146** of the second cable **144** can be formed by using a clamp **147**, which can be pressed to rigidly hold two portions of the end of the second cable **144** adjacent to one another to form the loop end **146**. The other end of the second cable **144** can be connected securely to the body **102** of the device **100**. For example, the second cable **144** can be connected securely and permanently to either or both of the generally-tubular portion **104** or the bottom-wall portion **118**. As will be appreciated, it is also contemplated that the second cable **144** could have a loop end at each end of the second cable **144**, which could be used to secure the two ends together in securing the device **100** to a fixed structure. The attachment means **140** preferably further includes a lock, such as a padlock **148**. For example, the padlock **148** can be operable with a key or a combination, or both, as desired or convenient. Most preferably, the key or combination is the same for both the padlock **138** of the closure means **130** and the padlock **148** of the attachment means **140**, which is more convenient in use.

Referring briefly ahead to FIG. **11** of the drawing, the use of the device **100** is illustrated for securing a plurality of fishing rods against crime-of-opportunity theft. The device **100** is shown partially containing a plurality of fishing rods **10** positioned in the open bed **22** of an open-bed vehicle, such as a pick-up truck **20**.

At least the rear portions **11** of the fishing rods **10** are secured in the generally bag-shaped body **102** of the device. At least a forward portion **12** of the fishing rods **10** protrudes through the opening of the device **100**. The opening is shown fully wrapped and cinched down around the forward portions **12** of the fishing rods **10**. As described above and with reference back to FIGS. **1** and **2**, a first cable **134** of the closure means **130** is also used to help secure the rear portions of the fishing rods **10** in the device **100**. The opening **110** and the first cable **134** are closed and threaded through the forward portions of the fishing rods and cinched down sufficiently around the forward ends **12** of the fishing rods **10** to be substantially smaller than a cross-section through the butt portion of a fishing rod having an attached reel. This prevents the rear portion of any fishing rod **10** positioned in the device **100** from being removed. The upper end **106** of the body **102** is closed and secured with the closure means **130**, including the padlock **138**.

Referring again to FIG. **11**, the generally bag-shaped body **102** is attached securely to an available fixture, such as a tie-down attachment point **26** formed on one of the side-walls **24** of the open bed **22**. It should be understood, of course, that the open-bed vehicle **20** is merely representative, and the device **100** can be similarly used, for example, in the open bed of a boat or trailer, or in an open area that is unsecured to public access.

FIGS. **5** and **6**, and then with reference to FIG. **1**, illustrate the process of positioning one or more fishing rods **10** (or at least the rearward portions thereof) into the device **100** and closing the opening **110** of the device. When considered in a reverse sequence, FIG. **1**, to FIG. **6**, and then FIG. **5** illustrate the process of opening the device **100** to be able to remove one or more of the fishing rods **10** positioned therein from the device.



## 11

More particularly, FIG. 5 is another perspective view toward the upper end **106** of the embodiment of the device **100** shown in FIG. 1, wherein the upper end **106** of the bag-shaped body **102** of the device is shown with the opening **110** thereof in an open position. In such an open position, it is easy to insert (or remove) the rear portion **11** (not visible inside the device **100** in this Figure) of each of one or more fishing rods **10**. FIG. 5 illustrates a representative position of the rearward portions of a plurality of fishing rods having been inserted into the bag-like body of the device with forward portions **12** thereof protruding from the opening of the generally bag-shaped body **102**.

FIG. 6 is another perspective view toward the upper end **106** of the embodiment of the device shown in FIGS. 1 and 5, wherein the upper end of the generally bag-shaped body **102** of the device **100** is shown with the opening thereof in the process of being closed (or opened) around the forward portions **12** of a plurality of fishing rods protruding from the bag-shaped body of the device. More particularly, the wrapped portion **111** is available to be folded and wrapped around the forward portions **112** of one or more fishing rods protruding from the opening of the device **100**, or in the process of opening the device, unwrapped from around the forward portions **12** protruding from the opening of the device.

FIGS. 7 and 8 illustrate a presently-preferred construction of a first flexible webbing material **160** for use in forming the generally-tubular portion **104** of the generally bag-shaped body **102** of the device **100** as shown in FIGS. 1 and 3. FIG. 7 illustrates the layered construction for making the first flexible webbing material **160**, and FIG. 8 illustrates forming the layered construction into a generally-tubular portion **104**.

Referring first to FIG. 7, the first flexible webbing material **160** preferably includes an inner sheet **162** of a flexible plastic material and an outer sheet **164** of a flexible plastic material sandwiching a plurality of reinforcing strands **166** of cable. Accordingly, the interior of the first webbing material presents a substantially smooth surface, whereby the rear portion of the butt end of at least one fishing rod can slide against the interior of the first webbing material forming the interior wall without catching thereon. Similarly, the exterior of the first webbing material **160** also presents a substantially smooth surface, which helps avoid scratching the body of a boat or other surfaces exterior of the device **100**. Most preferably, the flexible webbing material **160** with the reinforcing strands **166** is co-extensive and held together as a single sheet of flexible webbing material, whereby the reinforcing material stays with at least an inner sheet **162** of plastic material. This keeps the flexible webbing material and the reinforcing material integrally together to avoid creating any gaps in the pattern of reinforcing strands **166** and to minimize handling difficulties that might arise from using separable layers of plastic material **162** and strands **166** that are not held together into an integrally formed sheet of flexible webbing material **160**.

Preferably, the flexible plastic material is opaque to visible light, opaque to UV radiation, and resistant to UV degradation from sunlight. The opacity of the plastic material to visible light helps protect the value of a rod and reel inside the device **100** from being readily discerned from the outside, and the UV opacity and resistance gives a longer life for the device and also helps protect the rod and reel therein. According to the presently most-preferred embodiment, the plastic material is vinyl coated nylon. A nylon material provides strength, and a vinyl material provides weatherproofing. If desired, advertising or other information can be printed on the outside surface of the plastic material.

## 12

The reinforcing strands **166** are preferably a cut-resistant cable, such as a braided metal cable. According to the presently most-preferred embodiment, the cable is  $\frac{1}{16}$  inch (2 mm) of braided stainless-steel wire with a vinyl plastic coating.

According to the presently most-preferred embodiment of the invention, the inner sheet **162** and the outer sheet **164** are the same size, each being about 48 inches (122 cm) long and about 36 inches (91 cm) wide.

The strands of cable **166** are preferably laid out in a criss-crossing pattern, which gives cut resistance in two directions. Preferably, some of the cable can be laid out as a first length **168** in a snaked back-and-forth pattern as shown, where the loop-back portions of the snaking pattern protrude or extend past each of the edges **116** and **108** of the sheets **162** and **164** (when the sheets are overlaid and glued together). The loop-back portions protruding from the edge **116** (of the overlaid sheets **162** and **164**) can be used to form the lower-end loops **122** at the lower-end circumferential edge **116** (after being formed into a generally-tubular structure). The loop-back portions protruding from the edge **108** can be used to form the upper-end loops **132** at the upper-end circumferential edge **108** (after being formed into a generally-tubular structure). As described above, the lower-end loops **122** formed by the protruding loop-back portions of the first length **168** snaking can be used for attaching a bottom-wall portion **118** of the bag-shaped body **102** for the device **100**, and the upper-end loops **132** formed by the protruding loop-back portions of the first length **168** at the other edge of the first sheet **162** and second sheet **164** can be used for cinching the opening **110** of the device **100** around a forward portion **12** of a fishing rod.

According to the presently-most preferred embodiment, the ends of the first length **168** can be used for or connected to cables **134** and **144**, respectively, as shown, which provides a means for securely connecting the cables to the generally-tubular portion **104**. It is also contemplated that the cables **134** and **144** can be connected, for example, with swage connectors to the reinforcing material **168** or **170**.

It should be understood that the loops **136** and **146**, respectively, can be added or formed at any convenient stage of the manufacturing process. It should be further understood and the padlocks **138** and **148**, respectively, can also be added at any convenient stage of the manufacturing process or to the packaging for the device or can be selected and added by a consumer after purchase of the device.

The strands of cable **166** also preferably include a plurality of straight strands **170**, which are laid out perpendicular to the snaking pattern of the first length **168**. The straight strands **170** are most preferably a length equal to or greater than the full circumference of the first webbing material to be formed into the generally-tubular portion **104**.

The inner sheet **162** is preferably off-set several inches in a lengthwise orientation from the position of the outer sheet **164**. The inner sheet **162** has end portions **172** and **173** at each end thereof. The outer sheet **164** has end portions **174** and **175** at each end thereof. Thus, the end portion **173** of the inner sheet **162** extends beyond the end portion **174** of the outer sheet **164**, and the end portion **175** of the outer sheet **164** extends beyond the end portion **172** of the inner sheet **162**. This allows the off-set extending portions **173** and **175** to be glued or otherwise attached together, thereby connecting the end portions **173** and **175** to form the first webbing material **160** into a generally-tubular portion **104** as shown in FIG. 8 for making a device **100**. FIG. 8 illustrates a view toward the upper end of the presently-preferred construction of the first flexible webbing material **160** after it has been assembled and glued together into a generally-tubular portion **104**.



## 13

FIGS. 9 and 10 illustrate a presently-preferred construction of a second flexible webbing material **180** for use in forming the bottom-wall portion **118** of the generally bag-shaped body **102** of the device **100** as shown in FIG. 3. FIG. 9 illustrates the layered construction for making the second flexible webbing material **180**, and FIG. 10 illustrates forming the layered construction into a bottom-wall portion **184**.

Referring first to FIG. 9, the second flexible webbing material **180** preferably includes an inner sheet **182** of a flexible plastic material and an outer sheet **184** of a flexible plastic material sandwiching a plurality of reinforcing strands **186** of cable. Preferably, the flexible plastic material is opaque to visible light, opaque to UV radiation, and resistant to UV degradation from sunlight. The opacity of the plastic material to visible light helps protect the value of a rod and reel inside the device **100** from being readily discerned from the outside, and the UV opacity and resistance gives a longer life for the device and also helps protect the rod and reel therein. According to the presently most-preferred embodiment, the plastic material is vinyl coated nylon. If desired, advertising or other information can be printed on the outside surface of the plastic material. The reinforcing strands **186** are preferably a cut-resistant cable, such as a braided metal cable. According to the presently most-preferred embodiment, the cable is  $\frac{1}{16}$  inch (2 mm) of braided stainless-steel wire with a vinyl plastic coating.

According to the presently most-preferred embodiment of the invention, the inner sheet **182** and the outer sheet **184** are the same size, each being about 12 inches (30 cm) long and about 12 inches (30 cm) wide.

The strands of cable **186** are preferably laid out in a criss-crossing pattern, which gives cut resistance in two directions. Preferably, some of the cable can be laid out as a first length **188** in a snaked back-and-forth pattern, where the loop-back portions of the snaking pattern protrude or extend past each of the peripheral edge portions **119a** of the sheets **182** and **184** (when the sheets are overlaid and glued together). The loop-back portions protruding from the edge portions **119a** (of the overlaid sheets **182** and **184**) can be used to form some of the plurality of the bottom-wall loops **124** at the peripheral edge **119** (after being formed into the bottom-wall portion **118**). Similarly, some of the cable can be laid out as a second length **190** in a snaking back-and-forth pattern, where the loop-back portions of the snaking pattern protrude or extend past each of the peripheral edge portions **119b** of the sheets **182** and **184** (when the sheets are overlaid and glued together). The loop-back portions protruding from the edge portions **119b** (of the overlaid sheets **182** and **184**) can be used to form some of the plurality of the bottom-wall loops **124** at the peripheral edge **119** (after being formed into the bottom-wall portion **118**). The strands of cable **186** and **188** are preferably laid out in perpendicular snaking patterns.

In the presently most-preferred embodiment, the inner sheet **182** is preferably in aligned overlapping position with of the outer sheet **184**. FIG. 10 illustrates a view of the presently most-preferred construction of the second flexible webbing material **180** after it has been assembled and glued together into a bottom-wall portion **118**.

Preferably, each of the first and second webbing materials is resistant to rain or water spray from penetrating there-through. Preferably, each of the first and second webbing material is resistant to ultraviolet sunlight degradation for at least one year under outdoor conditions. And preferably, the first webbing material is at least substantially opaque to visible light, whereby the particular nature of a fishing rod and reel positioned therein cannot be observed through the webbing material.

## 14

Both the first and second webbing material includes at least one plastic sheet material capable of being repeatedly folded in any direction without rupture. Preferably, the plastic sheet material is a polyvinyl material.

Most preferably, the plastic sheet material of the body **102** is reinforced with a metal, and more preferably with a metal wire. According to the presently most-preferred embodiments the sheet material for of the body **102** includes a stranded or a braided metal wire, which structure is more resistant to cutting than unbraided cable of the same overall dimensions. As described and shown, the metal wire is positioned to reinforce the plastic sheet material of the webbing material in a criss-crossing pattern to the generally-tubular shape. This resists cutting of the flexible webbing material for any length in any direction that would be sufficient to remove a fishing rod and reel from the body **102** of the device made with the flexible webbing material. For example, according to the presently most-preferred embodiment of the invention, the metal wire is crisscrossed at a spacing of about 2 inches (5 cm), although larger spacing is expected to be adequate. Preferably, the metal is rust-resistant steel.

The second flexible webbing material is different than the first flexible webbing material forming the generally-tubular shape.

The second flexible webbing material forming the bottom-wall portion prevents a largest cross-section of the rear portion of a fishing rod and reel from passing therethrough.

The presently most-preferred design for the device offers many advantages. The webbing material is flexible yet reinforced to be resistant to cutting with a hand-held knife. The interconnection between the first and second flexible webbing materials provides a peripheral gap for allowing water to drain out of the bag-like shape and air to circulate into and out of the bag-like shape. Allowing the device and the fishing rod or rods therein to dry out reduces the possibility for mold or mildew on either the inside of the device or on a fishing rod positioned therein. Nevertheless, the flexible webbing material also assists in keeping incidental water spray or rain from getting onto the parts of a fishing rod that may be susceptible to corrosion, especially from salt water spray.

It should be understood that, while it is believed that the presently most-preferred design offers many advantages, various sections or pieces of flexible webbing material could be sewn together or otherwise connected to form a generally bag-like shape as shown in FIGS. 1, 3, 5, and 11.

## Method of Using the Security Device

Referring now primarily to FIGS. 5, 6, 1, and 11 in that order, a method is provided for securing against crime-of-opportunity theft of a fishing rod **10** (including an attached reel) to be stored or transported in an outdoor, unsecured area or on an open, unsecured portion **22** of a vehicle **20** (for example, as illustrated in FIG. 11). The method includes the steps of: (a) inserting at least a rear portion of at least one fishing rod **10** into and through an opening **110** of a body **102** of a device **100** having a generally bag-like shape and formed of a flexible webbing material (for example, as illustrated in FIG. 5); (b) closing and locking the opening **110** of the flexible webbing material around a forward portion of the fishing rod when at least the rear portion thereof is positioned inside the body formed of the flexible webbing material and locking the closure for the opening to prevent removal of the rear portion of the fishing rod from inside the device (for example, as illustrated in the steps of FIGS. 6 and 1); and (c) attaching and locking the body of the device **100** to any available fixed structure in the open area or on the vehicle and locking the attachment to the fixed structure (for example, as illustrated in



## 15

FIG. 11). Each of the flexible webbing material of the generally bag-shaped body 102, the closure means 130 for the opening, and the attachment means 140 to the fixed structure is resistant to cutting with a hand-held knife.

It should be appreciated that the steps of the method can be performed in any practical order. For example, the step of attaching and locking the body of the device 100 to an available fixed structure in the open area or on the bed of the vehicle can be performed first and in practice often would be. After a desired temporary use, the device can be unlocked from the fixed structure until desired to be used again.

It should also be apparent that, with the opening 110 of the device closed and cinched down around the forward portion of a fishing rod 10, removal of the fishing rod is not possible because of the overall cross-section presented by a reel of the fishing rod 10.

It can be appreciated that, to properly remove a fishing rod 10 from the device 100, all that is required is to unlock the closure for the opening of the flexible webbing material, widen the opening, and pull out the rear portion of the fishing rod from inside the body of the device. The device 100 can remain attached and locked to a suitable fixture while the fishing rod is being used, and remains conveniently ready to be used. The device itself is secured against crime-of-opportunity theft by the attachment means 140.

According to a preferred embodiment of the method, the step of closing and locking the opening further includes the step of wrapping a portion of the flexible webbing material of the body of the device around a forward portion of at least one fishing rod and reel protruding through the opening.

According to another preferred embodiment of the method, the step of closing and locking the opening further includes the step of: threading a first cable 134 through a plurality of loops 132 formed on a circumferential edge 108 of the opening 110.

According to another preferred embodiment of the method, the step of inserting further includes the step of inserting the rear portions of a plurality of fishing rods into and through an opening; and the step of closing and locking the opening further includes the step of threading a first cable 134 around and between at least two of the forward portions 12 of the plurality of fishing rods 10. More preferably, the step of closing and locking the opening further includes the step of threading a cable between the plurality of forward portions 12 of the fishing rods protruding through the opening and through a plurality of loops 132 formed on a circumferential edge 108 of the opening 110 of the device 100. And more preferably, the method of the step of closing and locking the opening further includes the step of connecting and locking the first cable 134 to the circumferential edge 108 of the opening 110.

Between uses, the device 100 can be stored in any convenient location, such as a closet in a home or the trunk of a vehicle.

The invention is described with respect to presently preferred embodiments, but is not intended to be limited to the described embodiments. As will be readily apparent to those of ordinary skill in the art, numerous modifications and combinations of the various aspects of the invention and the various features of the preferred embodiment can be made without departing from the scope and spirit of the invention. The invention is to be defined by the appended claims.

What is claimed is:

1. A device for securing against crime-of-opportunity theft of at least one fishing rod and reel to be stored or transported in an outdoor, unsecured area or on an open, unsecured portion of a vehicle, the device comprising:

## 16

- (a) a first flexible webbing material,
  - (i) wherein the first flexible webbing material, when opened, has a generally-tubular shape with an open upper end, the generally-tubular shape having a lower end opposing the open upper end, and a lower circumferential edge of the lower end including lower-end loops extending therefrom, and wherein the generally-tubular shape of the first flexible webbing material, when opened, has at least a sufficient internal cross-section and at least a sufficient internal length to receive at least a rear portion of at least one fishing rod and reel, wherein the rear portion comprises a handle, a reel seat, and an attached reel;
  - (ii) wherein the first flexible webbing material is capable of retaining at least the rear portion of at least one fishing rod and reel positioned therein from being removed in any direction substantially perpendicular to the internal length of the generally-tubular shape of the first flexible webbing material; and
  - (iii) wherein an upper end portion of the first flexible webbing material adjacent the open upper end can be folded and wrapped around a forward portion of a fishing rod;
 whereby the rear portion of at least one fishing rod and reel can be inserted or removed through the open upper end of the first flexible webbing material in a direction generally parallel to the internal length of the first flexible webbing material;
- (b) a second flexible webbing material,
  - (i) wherein the second flexible webbing material forming a bottom-wall portion closing the lower end of the first flexible webbing material that is opposite to the open upper end, and an outer peripheral edge of the bottom wall portion including bottom-wall loops extending therefrom;
- (c) interconnecting means,
  - (i) wherein the interconnecting means extending through the lower-end loops and the bottom-wall loops so as to connect the generally tubular shape and the bottom-wall portion, and a peripheral gap being defined between the lower circumferential edge and the outer peripheral edge which allows water to drain out of the device and for air to circulate into and out of the device;
- (d) a closure means for securing and locking the open upper end of the first flexible webbing material at least partially folded and wrapped around a forward portion of a fishing rod protruding through the open upper end when at least the rear portion thereof is positioned inside the first flexible webbing material, so that, when in such a substantially closed position, a largest cross-section of the rear portion of a fishing rod and reel cannot be removed through the open upper end of the first flexible webbing material, wherein the closure means comprises:
  - (i) a first cable connected to the first flexible webbing material having a first loop end adjacent a first end of the first cable;
  - (ii) a plurality of upper end loops in the first flexible webbing material adjacent to and spaced around the open upper end of the first flexible webbing material; and
  - (iii) a lock;
 so that by threading the first cable through the plurality of upper-end loops, the open upper end of the first flexible webbing material can be cinched to a substantially closed position and the lock can lock the open



17

upper end of the first flexible webbing material in the substantially closed position; and

- (e) an attaching means for securing and locking the first flexible webbing material to a fixed structure in the open area or on the vehicle;

wherein each of the first flexible webbing material, the closure means, and the attaching means is resistant to cutting with a hand-held knife.

2. The device according to claim 1, wherein an interior of the first flexible webbing material presents a substantially smooth surface, whereby the rear portion of at least one fishing rod can slide against the interior of the first webbing material forming an interior wall without catching thereon.

3. The device according to claim 1, wherein the first flexible webbing material comprises a sheet of flexible plastic material that resists rain or water spray from penetrating therethrough.

4. The device according to claim 1 wherein the first flexible webbing material forming the generally-tubular shape is resistant to ultraviolet sunlight degradation for at least one year under outdoor conditions.

5. The device according to claim 1, wherein the first flexible webbing material is at least substantially opaque to visible light, whereby the particular nature of a fishing rod and reel positioned therein cannot be observed through the webbing material.

6. The device according to claim 1, wherein the second flexible webbing material is similar in material and structure to the first flexible webbing material forming the generally tubular shape.

7. The device according to claim 1, wherein the second flexible webbing material forming the bottom-wall portion prevents a largest cross-section of the rear portion of a fishing rod and reel from passing therethrough.

8. The device according to claim 1, wherein the attaching means comprises:

- (a) a second cable connected to the first flexible webbing material having a second loop end adjacent a first end of the second cable; and

- (b) a lock;

so that by threading the loop end of the second cable through at least one of the lower end loops, and by threading the loop end through or around any suitable fixture of the open area or vehicle, the device can be secured to the fixture.

9. The device according to claim 1, wherein the first cable has at least a sufficient length to be threaded and woven between and around the forward portions of a plurality of fishing rods to help secure the rods inside the device.

10. A device for securing against crime-of-opportunity theft of at least one fishing rod and reel to be stored in an outdoor, unsecured area or an open, unsecured portion of a vehicle, the device comprising:

- (a) a flexible webbing material, wherein the flexible webbing material has a generally bag-like shape with an open upper end, and wherein an upper end portion of the flexible webbing material adjacent the open end can be folded and wrapped around a forward portion of a fishing rod, wherein the flexible webbing material further comprises:

- (i) a first flexible webbing material, wherein the first flexible webbing material, when opened, has a generally-tubular shape with the open upper end, the generally-tubular shape having a lower end opposing the open upper end, and a lower circumferential edge of the lower end including lower-end loops extending therefrom;

18

- (ii) a second flexible webbing material forming a bottom-wall portion closing the lower end of the first flexible webbing material that is opposite to the open end, an outer peripheral edge of the bottom wall portion including bottom-wall loops extending therefrom; and

- (iii) interconnecting means extending through the lower-end loops and the bottom-wall loops so as to connect the generally tubular shape and the bottom-wall portion, and a peripheral gap being defined between the lower circumferential edge and the outer peripheral edge which allows water to drain out of the device and for air to circulate into and out of the device;

- (b) a first cable and first lock operatively connected to the flexible webbing material for closing and locking the open end of the flexible webbing material folded and wrapped around a forward portion of a fishing rod when at least a rear portion thereof is positioned inside the flexible webbing material, and

- (c) a second cable and second lock operatively connected to the flexible webbing material for attaching and locking the flexible webbing material to a fixed structure in the open area or on the vehicle;

wherein each of the flexible webbing material, the first cable for closing, and the second cable for attaching is resistant to cutting with a hand-held knife.

11. The device according to claim 10, wherein the first flexible webbing material comprises a plastic sheet material capable of being repeatedly folded in any direction without rupture.

12. The device according to claim 11, wherein the plastic sheet material comprises a vinyl coated nylon material.

13. The device according to claim 11, wherein the plastic sheet material is reinforced with a metal.

14. The device according to claim 13, wherein the plastic sheet material is reinforced with metal in the form of metal wire.

15. The device according to claim 14, wherein the metal wire comprises a stranded or a braided metal wire.

16. The device according to claim 15, wherein the metal wire has a plastic coating.

17. The device according to claim 16, wherein the plastic coating is a vinyl plastic coating.

18. The device according to claim 14, wherein the metal wire is positioned to reinforce the plastic sheet material of the first webbing material in a criss-crossing pattern to the generally-tubular shape.

19. The device according to claim 14, wherein the metal comprises a rust-resistant steel.

20. In combination, the device according to claim 10 and at least one fishing rod having at least a rear portion of at least one fishing rod and reel positioned inside the device.

21. A device for securing against crime-of-opportunity theft of at least one fishing rod and reel to be stored or transported in an outdoor, unsecured area or on an open, unsecured portion of a vehicle, the device comprising:

- (a) a flexible webbing material, wherein the flexible webbing material, when opened, has a generally bag-like shape with an open end and has at least a sufficient internal cross section and at least a sufficient internal length to receive at least a rear portion of at least one fishing rod and reel, and wherein an upper end of the flexible webbing material adjacent the open end can be folded and wrapped around a forward portion of a fishing rod, wherein the flexible webbing material further comprises:



19

- (i) a first flexible webbing material, wherein the first flexible webbing material, when opened, has a generally-tubular shape with the open end, and wherein the generally-tubular shape of the first flexible webbing material, when opened, has at least a sufficient internal cross-section and at least a sufficient internal length to receive at least a rear portion of at least one fishing rod and reel, wherein the rear portion of the butt end comprises at least a handle, a reel seat, and an attached reel, the generally-tubular shape having a lower end opposing the open end, and a lower circumferential edge of the lower end including lower-end loops extending therefrom;
- (ii) a second flexible webbing material forming a bottom-wall portion closing the lower end of the first flexible webbing material that is opposite to the open end, and an outer peripheral edge of the bottom wall portion including bottom-wall loops extending therefrom; and
- (iii) interconnecting means extending through the lower-end loops and the bottom-wall loops so as to connect the generally tubular shape and the bottom-wall por-

20

- tion, and a peripheral gap being defined between the lower circumferential edge and the outer peripheral edge which allows water to drain out of the device and for air to circulate into and out of the device;
- (b) a first cable and first lock operatively connected to the open end of the flexible webbing material for closing and locking the open end of the flexible webbing material folded and wrapped around a forward portion of a fishing rod when at least the rear portion thereof is positioned inside the flexible webbing material, wherein when in such a closed position, a largest-cross section of the rear portion of a fishing rod and reel cannot be removed through the open end of the flexible webbing material; and
- (c) a second cable and second lock operatively connected to the flexible webbing material for attaching and locking the flexible webbing material to a fixed structure in the open area or on the vehicle;
- wherein each of the flexible webbing material, the first cable for closing, and the second cable for attaching is resistant to cutting with a hand-held knife.

\* \* \* \* \*