



US007679513B2

(12) **United States Patent**
King et al.

(10) **Patent No.:** **US 7,679,513 B2**
(45) **Date of Patent:** **Mar. 16, 2010**

(54) **METHOD AND APPARATUS USING RADIO-LOCATION TAGS TO REPORT STATUS FOR A CONTAINER HANDLER**

(75) Inventors: **Henry S. King**, Moraga, CA (US); **Toru Takehara**, Foster City, CA (US)

(73) Assignee: **PACECO Corp.**, Hayward, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 212 days.

(21) Appl. No.: **12/012,369**

(22) Filed: **Feb. 1, 2008**

(65) **Prior Publication Data**
US 2008/0143545 A1 Jun. 19, 2008

Related U.S. Application Data

(60) Division of application No. 11/261,447, filed on Oct. 27, 2005, and a continuation-in-part of application No. 11/130,822, filed on May 16, 2005, now Pat. No. 7,598,863.

(60) Provisional application No. 60/622,980, filed on Oct. 27, 2004, provisional application No. 60/571,009, filed on May 14, 2004.

(51) **Int. Cl.**
G08B 13/14 (2006.01)

(52) **U.S. Cl.** **340/572.1; 340/539.1; 340/539.13; 340/825.49; 340/825.69; 700/214; 700/229; 235/385**

(58) **Field of Classification Search** **340/572.1, 340/539.1, 539.13, 539.16, 686.1, 825.49, 340/825.69, 988; 235/375, 383, 385; 700/213, 700/214, 229**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,780,826 A * 7/1998 Hareyama et al. 235/385
6,577,921 B1 * 6/2003 Carson 700/214
7,013,026 B2 * 3/2006 Takehara et al. 382/104

* cited by examiner


Primary Examiner—Hung T. Nguyen

(74) *Attorney, Agent, or Firm*—GSS Law Group

(57) **ABSTRACT**

The invention includes apparatus and methods using a means for wirelessly communicating, preferably a radio location-tag unit, for reporting a sensed state of a container handler. The status reporting device may include: a micro-controller module, a means for wirelessly communicating, which may include means for wirelessly determining container handler location, and a means for sensing the state of the container handler.

18 Claims, 31 Drawing Sheets






Fig. 1




Fig. 2




Fig. 3A




Fig. 3B




Fig. 4A




Fig. 4B




Fig. 4C




Fig. 4D




Fig. 5A




Fig. 5B




Fig. 6A




Fig. 6B




Fig. 7A




Fig. 7B




Fig. 7C




Fig. 8A




Fig. 8B




Fig. 8C




Fig. 8D




Fig. 9A




Fig. 9B




Fig. 10A




Fig. 10B




Fig. 10C




Fig. 10D




Fig. 10E




Fig. 11A




Fig. 11B




Fig. 11C




Fig. 12A




Fig. 12B




Fig. 12C




Fig. 12D




Fig. 12E




Fig. 13A




Fig. 13B






Fig. 14A






Fig. 15A




Fig. 15B




Fig. 16A




Fig. 16B




Fig. 17







Fig. 18










Fig. 22




Fig. 23




Fig. 24




Fig. 25

METHOD AND APPARATUS USING RADIO-LOCATION TAGS TO REPORT STATUS FOR A CONTAINER HANDLER

CROSS REFERENCES TO PRIORITY DOCUMENTS

This application is a divisional of patent application Ser. No. 11/261,447 filed Oct. 27, 2005, that claimed the benefit of the priority date of provisional patent application No. 60/622,980, filed Oct. 27, 2004. The Ser. No. 11/261,447 application is a continuation-in-part application of patent application Ser. No. 11/130,822, filed May 16, 2005 now U.S. Pat. No. 7,598,863, which claims the benefit of the priority date of provisional application No. 60/571,009, filed May 14, 2004. Each of the aforementioned applications are hereby incorporated by reference in their entirety.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to status reporting devices for container handlers and methods of making these devices. A container handler will refer herein to a device, usually operated by a human operator, which moves a container of at least twenty feet in length.

2. Background Information

Container terminals are transfer points between marine and land-based shipping. These container terminals must maintain inventory control for an ever-increasing number of containers. The basic unit of transfer is a container, which comes in five sizes, a ten foot, a twenty foot, a thirty foot, a forty foot and a forty five foot size. These containers, when filled, may weigh up to 110,000 pounds, or 50,000 kilograms, making them impossible to move, except by machinery.

The last few years have seen increased demand for real-time reporting of container activity throughout the container terminals.

The point of transfer between marine transport and land-based transport is the quay side crane, or quay cranes, as they will be known hereafter. Berthing operations involve transferring containers between a container ship and a land transport by one of these quay cranes. There is often a need for mechanisms to inspect the containers and/or create long lasting records of the visual condition of the containers at the time of transfer. The clerks involved may intentionally or unintentionally mislead the container inventory management system and the terminal management. The container's contents may be damaged when it reaches its destination, leading to the possibility of lawsuits and insurance claims being brought against terminal management. Berthing operations may be seen as loading and unloading containers onto container ships.

The quay cranes deliver the containers onto UTR trucks, which sometimes carry the containers on specialized trailers known as bomb carts. The UTR trucks move containers around a terminal, transferring the containers between one or more stacking yards and the Quay cranes. In the stacking yards, a number of different cranes may be used to place the container in stacks, or possibly load them onto or unload them from trucks used for container movement outside the terminal.

There is an ever growing need to continuously monitor the status of the container handlers around a terminal. Overall terminal efficiency tends to be improved if the terminal management knows the status and/or location of each container handler. Illicit use of container handlers may be minimized by

use of operator identification devices. The container codes may need to be observed and recorded at various points in the terminal transfer operations. Photographs may need to be taken of the container conditions as it is leaving a ship, or being put on a ship.

There is however a problem of scale. While there are millions of containers entering and leaving a country such as the United States annually, there are nowhere near that many container handlers. Even worse, there are many different kinds of container handlers. Some, such as UTR trucks, Front End Loaders (FEL), and bomb carts handle containers differently from the cranes. As used herein, Front End Loaders will refer to Top Handlers (also known as Top Loaders) and Side Handlers (also known as Side Pickers). The crane based container handlers vary in structure greatly. Some have centralized controls, known as Programmable Logic Controllers (PLC), and some do not. As a consequence, these reporting devices, which enable container tracking, represent small production runs. These small production runs involve many variations in circuitry and couplings for these different types of container handlers, with the attendant high setup and manufacturing costs. A modular manufacturing method is needed for these reporting devices, which can readily account for the container handler variations, while minimizing cost and maximizing reliability.

In the last few years, a variety of radio frequency tagging devices have entered the marketplace. These devices can often provide a mechanism for identifying themselves, as well as reporting their location via a wireless communication protocol, often one or more variants IEEE 802.11. Some of these devices rely on a local wireless network to aid them in location determination. While these devices have uses, they do not satisfy all the needs that container handlers have for status reporting. What is needed are mechanisms and methods for using the capabilities of radio frequency tagging devices to provide an integrated solution to the needs of the various container handling devices, to report on the container handler status, and/or provide observations of the container being handled.

BRIEF SUMMARY OF THE INVENTION

The present invention relates to status reporting devices for container handlers and methods of making these devices. A container handler will refer herein to a device, usually operated by a human operator, which moves a container of at least twenty feet in length.

The invention includes apparatus and methods using a means for wirelessly communicating, preferably a radio location-tag unit, for reporting a sensed state of a container handler. The status reporting device may include: a micro-controller module, a means for wirelessly communicating, which may include means for wirelessly determining container handler location, and a means for sensing the state of the container handler. The invention includes an apparatus and a method of making the status reporting devices for container handlers. The manufacturing proceeds in a modular, highly efficient manner, which is able to use a relatively small number of different parts to serve the needs of a wide variety of container handlers.

A container handler will refer herein to a device, usually operated by a human operator, which can move a container of at least twenty feet in length. International commerce primarily uses containers of approximately ten feet, twenty feet, thirty feet, forty feet or forty-five feet in length.

The method making the status reporting devices includes the following steps. A micro-controller module is provided. A

program system is installed into a memory, which a computer can access to direct the micro-controller module.

The micro-controller module is communicatively coupled with a means for wirelessly communicating and a means for sensing a state of the container handler.

The program system includes program steps residing in the memory. These program steps include the following. Using the means for sensing the state of the container handler to create a sensed state. And using the wirelessly communicating means to communicate the sensed state of the container handler.

In many preferred applications of the status reporting device, the means for wirelessly communicating is linked to a container inventory management system, sometimes also known as a terminal operating system. The sensed state may be preferably communicated to another computer, preferably associated with the terminal operating system.

The means for sensing may include, but is not limited to, means for any combination of the following.

Sensing an operator identity.

Sensing a container presence on, or coupled to, the container handler.

Optically sensing a container code on a container.

Radio frequency sensing a radio frequency tag on the container.

Sensing a stack height for the container.

Sensing at least one member of a machine state list of the container handler. The machine state list may include reverse motion, frequent stops count, collisions, fuel level, and compass readings. The machine state list may further include a wind speed, an equipment up-time and a vehicle speed.

Sensing at least one member of a crane state list. The crane state list may include a twistlock sensed state, a spreader sensed state, a sensed landing state, a trolley position, and a hoist height.

Sensing the container size.

Sensing the container weight.

Sensing container damage.

The means for wirelessly communicating may include a means for wirelessly determining the location of the container handler. Alternatively, the micro-controller module may be communicatively coupled to an at least partially separate means for locating the container handler. The means for locating may include an interface to a Global Positioning System (GPS). The means for wirelessly communicating may include a radio location-tag unit.

The container handler is at least one member of a container handler list comprising an UTR truck, a bomb cart, a rubber tire gantry crane, a quay crane, a side picker, a top loader, a top handler, a reach-stacker, a straddle carrier, and a chassis rotator.

The memory may include a non-volatile memory, which may further contain at least part of at least one of the program steps of the invention. Installing the program system may include altering at least part of the non-volatile memory, or installing a memory module containing at least part of at least one of the program steps in the non-volatile memory, creating at least part of the memory, which can be accessed by the computer. As used herein, the computer may be part of a micro-controller.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows three container handlers: a rubber tire gantry (RTG) crane and a UTR truck hauling a bomb cart;

FIG. 2 shows another container handler referred to herein as a quay side crane;

FIG. 3A shows another container handler referred to herein as a side picker;

FIG. 3B shows a stack of containers defining what is referred to herein as a stacking height;

FIG. 4A shows another container handler referred to herein as a reach stacker;

FIG. 4B shows the container handler list;

FIG. 4C shows a top handler;

FIG. 4D shows a straddle carrier;

FIGS. 5A and 5B show housing of the status reporting device and sensors for use on various container handlers;

FIG. 6A shows a system for making a status reporting device for the container handlers of FIGS. 1, 2, 3A, 4A, and 4B;

FIG. 6B shows a flowchart of the program system in the status reporting device of FIG. 6A;

FIG. 7A shows a refinement of the status reporting system of FIG. 6A coupled by a Network Interface Circuit (NIC) to the means for wirelessly communicating;

FIG. 7B shows a detail flowchart of FIG. 6B further using the means for wirelessly communicating;

FIG. 7C shows a further, often preferred embodiment of the manufacturing system of FIGS. 6A and 7A, including a second computer at least partly directing the means for creating the status reporting device;

FIG. 8A shows a flowchart of the program system of FIG. 7C, embodying certain aspects of making the status reporting device of FIGS. 6A and 7A;

FIG. 8B shows a detail of FIG. 8A further providing the micro-controller module to the system of FIG. 6A;

FIG. 8C shows a serial protocol list;

FIG. 8D shows a wireless modulation-demodulation scheme list;

FIG. 9A shows a refinement of part of the wireless modulation-demodulation scheme list of FIG. 8D;

FIG. 9B shows some refinements of the means of FIGS. 6A and 7A for sensing the state of the container handler;

FIG. 10A shows some refinements of the sensed state of FIGS. 6A and 7A;

FIG. 10B shows a container code characteristic list;

FIG. 10C shows some preferred alternative embodiments of the means for optically sensing the container code on the container of FIG. 9B;

FIG. 10D shows a further preferred embodiment of the means for sensing the stacking height, including a stacking height sensor interface to a stacking height sensor on the container handler;

FIG. 10E shows a preferred embodiment of the machine state list;

FIGS. 11A and 11B show example views of FIG. 10B, of the container code optically viewed on the side of container of FIGS. 1, 3A, and 4A;

FIG. 11C shows an example of the container code text of FIG. 10B;

FIG. 12A shows some details of the crane sensor means list related to members of FIG. 9B;

FIG. 12B shows some details of the crane state list related to members of FIGS. 9B and 10A;

FIG. 12C shows some details of a twistlock state list related to members of FIG. 12A;

FIG. 12D shows some details of the spreader state list related to members of FIG. 12A;

FIG. 12E shows some details of the landing state list related to members of FIG. 12A;

5

FIG. 13A shows a refinement of the status reporting device **800** of FIGS. 6A and 7A where the sensing means includes coupling to a crane spreader interface connection;

FIG. 13B shows a refinement of the status reporting device of FIGS. 6A and 7A where the sensing means includes coupling to a Programmable Logic Controller (PLC);

FIG. 14A shows the providing means of FIGS. 6A and 7A further including a means for coupling the micro-controller module with a means for locating the container handler;

FIG. 14B shows a detail flowchart of FIG. 8A further providing the micro-controller module with the coupled means for sensing the state of the container handler of FIGS. 6A and 7A;

FIG. 14C shows a detail of FIG. 8A further providing the micro-controller module with the coupled means for locating the container handler of FIG. 14A;

FIG. 15A shows the means for wirelessly communicating, including the means for wirelessly determining the location of the container handler;

FIG. 15B shows a detail of the program system of FIGS. 6A and 6B for determining and communicating the location of the container handler;

FIG. 16A shows the memory of FIG. 6A including a non-volatile memory;

FIG. 16B shows a detail flowchart of FIG. 8A for installing the program system of FIG. 6A;

FIGS. 17 to 20 show various embodiments of the status reporting device for the rubber tire gantry crane of FIG. 1 and the quay crane of FIG. 2;

FIGS. 21 to 23 show various embodiments of the status reporting device for the side picker of FIG. 3A, the reach stacker of FIG. 4A, the top loader of FIG. 4C, straddle carrier of FIG. 4D; and

FIGS. 24 and 25 shows various embodiments of the status reporting device for the UTR truck and/or bomb cart/chassis of FIG. 1.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

The invention includes apparatus and methods using a means for wirelessly communicating, preferably a radio location-tag unit, for reporting a sensed state of a container handler. The status reporting device may include: a micro-controller module, a means for wirelessly communicating, which may include means for wirelessly determining container handler location, and a means for sensing the state of the container handler. The invention includes an apparatus and a method of making status reporting devices for container handlers. The manufacturing proceeds in a modular, highly efficient manner, which is able to use a relatively small number of different parts to serve the needs of a wide variety of container handlers.

A container handler **78** will refer herein to a device, usually operated by a human operator, which moves a container **2** of at least twenty feet in length. International commerce primarily uses containers of approximately twenty feet to forty five feet in length. Containers when filled with cargo may weigh up to 110,000 pounds, or up to 50,000 kilograms. The width of the container **2** may be at least eight feet wide. The height of the container may be at least eight feet six inches.

As used herein, a container handler **78** will refer to at least one of the members of the container handler list **80** shown in FIG. 4B. The container handler list **80** includes, but is not limited to, the following.

6

The UTR truck **10**, the bomb cart **14**, and the Rubber Tire Gantry crane **20**, often abbreviated RTG crane are shown in FIG. 1.

Note that the bomb cart **14** is also known as a container chassis, when the container **2** is tied down.

Within container terminals, containers are not typically tied down to bomb carts.

The quay crane **30** is shown in FIG. 2.

The side picker **40** is shown in FIG. 3A.

The reach stacker **46** is shown in FIG. 4A.

The top handler **50** is shown in FIG. 4C.

The straddle carrier **54** is shown in FIG. 4D.

The chassis rotator **58**. The chassis rotator is used to rotate the chassis used to haul one or more containers.

Its operations and requirements are similar to other container handlers, except that its rectilinear position is fixed.

More relevant for these container handlers is the use of its location **1900** as an angular measure of its orientation of the container **2**.

The means for determining **1500** the location **1900** consequently may use a shaft encoding, possibly an optical shaft encoder.

The rubber tire gantry crane **20** of FIG. 1 may be called a transfer crane and/or a TRANSTAINER™. The quay crane **30** of FIG. 2 is sometimes referred to as a PORTAINER™. The side picker **40** of FIG. 3A is also referred to as a side handler or a side hauler. The top loader **50** of FIG. 4C is also referred to as a top picker or top handler.

Some of these container handlers have the ability to lift and/or place a container **2**. A container handler **78** able to lift and/or place the container is a member of the stacking handler list of FIG. 4B, which includes, but is not limited to, the following.

The rubber tire gantry **20** of FIG. 1 includes a rubber tire gantry spreader **22**.

The quay crane **30** of FIG. 2 includes a quay crane spreader, which is outside the picture.

The side picker **40** of FIG. 3A includes a side picker spreader **42**.

The reach stacker **46** of FIG. 4A includes a reach stacker spreader **48**.

The top handler **50** of FIG. 4C includes a top handler spreader **52**.

The straddle carrier **54** of FIG. 4D includes a straddle carrier spreader **56**.

FIG. 3B shows a stack of containers including first container **60** to fourth container **66** defining what is referred to herein as a stacking height.

The stacking height of the first container **60** is usually denoted as one.

The stacking height of the second container **62** is two.

The stacking height of the third container **64** is three.

And the stacking height of the fourth container **66** is four.

While this is a standard designation, any other designation may be used within a computer, such as numbering as follows, first container **60** as zero, second container **62** as one, third container **64** as two, and fourth container **66** as three.

In some situations, container stacks may preferably include more than four container stacked on top of each other, for example, up to eight containers high.

FIGS. 5A and 5B show two examples of a housing **3000** of the status reporting device **800** for use on various members of the container handler list **80**.

The housing **3000** of FIG. 5A includes a housing mount **3002**, by which it may be preferably attached to a rubber

tire gantry crane **20** of FIG. **1** and/or quay crane **30** of FIG. **2**. The housing **3000** may preferably contain at least part of the means for optical container code sensing **1230**.

The housing **3000** of FIG. **5B** preferably includes a display **3010**. The housing **3000** may preferably be attached to any member of the container handler list **80**.

FIG. **6A** shows a system for making **100** a status reporting device **800** for a container handler **78** of FIGS. **13A** and **13B**. The container handler **78** is a member of the container handler list **80**. Some preferred embodiments of the status reporting device **800** for specific members of the container handler list **80** are shown in FIGS. **17** to **25**.

In FIG. **6A**, the system for making **100** includes a means for providing **200** a micro-controller module **1000**.

The status reporting device **800** includes a first communicative coupling **1102** of the micro-controller module **1000** with a means for wirelessly communicating **1100**, and

The status reporting device **800** includes a second communicative coupling **1202** of the micro-controller module **1000** with a means for sensing state **1200** of at least one member of the container handler list **80** of FIG. **4B**.

In FIG. **6A**, the system for making **100** also includes means for installing **300** a program system **2000**. The program system **2000** is installed into **302** a memory **1020**.

The micro-controller module **1000** includes an accessible coupling **1022** of a computer **1010** with the memory **1020**.

The computer **1010** directs the activities of the micro-controller module **1000** through a program system **2000**.

The program system **2000** includes program steps residing in the memory **1020** as shown in FIGS. **6A** and **16A**.

The method of operating the status reporting device **800** will be discussed as implemented by the program system **2000**. One skilled in the art will recognize that alternative implementations, which may include, but are not limited to, finite state machines, neural networks, and/or inferential engines are possible, feasible, and in certain circumstances, potentially preferable.

A computer as used herein may include, but is not limited to, an instruction processor and/or a finite state machine, and/or an inferential engine, and/or a neural network. The instruction processor includes at least one instruction processing element and at least one data processing element, each data processing element controlled by at least one instruction processing element.

An embodiment of the computer, as used herein, may include not only what some would consider peripheral circuitry, which may include, but is not limited to, communications circuitry, memory, memory interface circuitry, clocking and timing circuitry, as well as signal protocol interface circuitry.

These circuits may be fabricated in the same package as the computer, sometimes on the same semiconductor substrate as the computer.

While some of these circuits may be discussed separately from the computer, this is done to clarify the operation of the invention and is not meant to limit the scope of the claims to mechanically distinct circuit components.

Certain embodiments of the computer **1010** may include a finite state machine, which may further include a means for using said means for sensing said state of said container handler to create said sensed state and/or a means for using said means for wireless communicating to communicate said sensed state of said container handler.

At least one Field Programmable Gate Array may implement at least part of at least one of the list comprising the instruction processor, the inferential engine, the neural network, and/or the finite state machine.

Embodiments of the status reporting device **800** may include determining the location **1900** of a container handler as shown in FIG. **6A**.

These aspects will be discussed later regarding the means for determining **1500** the location **1900** of the container handler as in FIGS. **14A** to **14C**, **15B**, **17**, **18**, **21**, **22**, and **24**.

Other alternatives may include, but are not limited to, using a means for wirelessly communicating **1100** which includes a means for wirelessly determining **1510** for locating the container handler, as discussed in FIGS. **15A**, **19**, **20**, **23**, and **25**. These aspects of the invention may not require the storage of the location **1900** in the computer **1010** of FIG. **6A**.

Some of the following figures show flowcharts of at least one method of the invention, possessing arrows with reference numbers. These arrows will signify of flow of control and sometimes data supporting implementations including at least one program operation or program thread executing upon a computer, at least one inferential link in an inferential engine, at least one state transitions in a finite state machine, and/or at least one dominant learned response within a neural network.

The operation of starting a flowchart is designated by an oval with the text "Start" in it, and refers to at least one of the following.

Entering a subroutine in a macro instruction sequence in a computer.

Entering into a deeper node of an inferential graph.

Directing a state transition in a finite state machine, possibly while pushing a return state.

And triggering a list of neurons in a neural network.

The operation of termination in a flowchart is designated by an oval with the text "Exit" in it, and refers to the completion of those operations, which may result in at least one of the following.

return from a subroutine return,

traversal of a higher node in an inferential graph,

popping of a previously stored state in a finite state machine, and/or

return to dormancy of the firing neurons of the neural network.

FIG. **6B** shows the program system **2000** of FIG. **6A**, which the means for installing **300** installed into **302** the memory **1020**.

Operation **2012** supports using the means for sensing state **1200** of FIG. **6A** for sensing the state of the container handler **78** of FIGS. **13A** and/or **13B**, to create a sensed state **1800**.

Operation **2022** supports using the means for wirelessly communicating **1100** to communicate the sensed state **1800** of the container handler **78**.

One skilled in the art will recognize that the means for sensing state **1200** may further preferably include specific sensors and interfaces beyond those related with FIGS. **13A** and/or **13B**.

FIGS. **17** to **25** outline some variations of sensors, instrumentation and interfaces which may be preferred for various types of the container handler **78**, which are members of the container handler list **80** of FIG. **4B**.

Because of the complexity of FIGS. 17 to 25, the label 1200 will not be found in the drawings, but will be called out in their discussion.

FIG. 7A shows the computer 1010 coupled 1032 with a Network Interface Circuit (NIC) 1030. The means for providing 200 the micro-controller module 1000 further includes a means 210 for coupling 212 the network interface circuit 1032 to 1104 the means for wirelessly communicating 1100.

FIG. 7A shows a refinement of the status reporting device 800 of FIG. 6A. The micro-controller module 1000 further includes a computer communicative coupling 1032 of the computer 1010 with a Network Interface Circuit 1030, denoted as (NIC).

FIG. 7A also shows a refinement of the means for providing 200 the micro-controller module 1000. The means for providing 200 the micro-controller module 1000 further includes:

A means for coupling 210, which creates the coupling 212 of the network coupling 1104 of the network interface circuit 1030 with the means for wirelessly communicating 1100.

A means for sensor coupling 220, which creates the sensor coupling 222 of the sensor coupling the micro-controller module 1000 to 1202 the means for sensing state 1200 of the container handler. This mechanism and process is similar to the various embodiments of the means for coupling 210 which creates the coupling 212, which will be described in greater detail.

FIG. 7B shows a detail flowchart of operation 2022 of FIG. 6B further using the means for wirelessly communicating 1100. Operation 2052 interacts via the computer communicative coupling 1032 with the network interface circuit 1030 via the network coupling 1104 with the means for wirelessly communicating 1100 to communicate the sensed state 1800 for the container handler.

FIG. 7C shows a further, often preferred, embodiment of the system for making 100 the status reporting device 800 of FIGS. 6A and 7A.

The system for making 100 may include a second computer 500 at least partly directing the creation of the status reporting device 800.

The second computer 500 may at least partly first direct 502 the means for providing 200 the micro-controller module 1000.

The second computer 500 may at least partly second direct 504 the means for installing 300 the program system 2000.

The communications coupling between the second computer 500 with the means for providing 200 and the means for installing 300 may be a shared coupling, and the first direct 502 and the second direct 504 may use an addressing scheme for message or communications addressed to these means.

In FIG. 7C, the system for making 100 further includes the following.

A second accessible coupling 512 of the second computer 500 with a second memory 510.

A second program system 2500 includes program steps residing in the second memory 510.

The second computer 500 is at least partly controlled by the program steps of the second program system 2500, which are provided through the second accessible coupling 512 of the second memory 510.

The second program system 2500 may be considered to embody the method of manufacture, by directing the means for providing 200 and the means for installing 300 to create the status reporting device 800.

The computer 1010 of FIG. 6A may be coupled 1032 with a network interface circuit 1030 as shown in FIG. 7A.

FIG. 8A shows a flowchart of the second program system 2500 of FIG. 7C, embodying certain aspects of the invention's method of making the status reporting device 800 of FIGS. 6A and 7A, which includes the following operations.

Operation 2512 directs the means for providing 200 to provide 202 the micro-controller module 1000 of FIGS. 6A and 7A.

Operation 2522 directs the means for installing 300 to install 302 the program system 2000 of FIGS. 6A, 7A, and 7B, into the memory 1020.

In FIG. 8A, the operation 2512 directing the means for providing 200 to provide 202 the micro-controller module 1000 of FIGS. 6A and 7A may involve the following in certain preferred embodiments.

The act of providing the micro-controller module 1000 may include, but is not limited to, fetching the module into an assembly work station, and/or positioning it for attachment to cables and test instruments.

The micro-controller module 1000 is provided with a first communicative coupling 1102 with the means for wirelessly communicating 1100.

The micro-controller module 1000 is also provided with a second communicative coupling 1202 to the means for sensing state 1200 for the container handler.

In FIG. 8A, the operation 2522 directing the means for installing 300 to install 302 the program system 2000 of FIGS. 6A, 7A, and 7B, into the memory 1020 may involve the following in certain preferred embodiments.

An accessible coupling 1022 of the memory 1020 and the computer 1010 supports the program system 2000 at least partly directing the computer 1010.

In certain preferred embodiments, the program system 2000 is installed 302 from a program system library 2400, as shown in FIG. 7C.

The program system 2000 may be installed 302 using a wireline network interface circuit 1030, and/or using the means for wirelessly communicating 1100.

The memory 1020 may preferably include at least one non-volatile memory component.

The non-volatile memory component may preferably include a flash memory device.

The installation may preferably include programming the flash memory component to install 302 the program system 2000.

The program system library 2400 may include multiple versions of the program system 2000, for use in controlling various embodiments of the status reporting device 800 created by the manufacturing process of the system for making 100.

FIG. 8B shows a detail of operation 2512 of FIG. 8A further providing the micro-controller module 1000. Operation 2552 supports creating the coupling 212 of the network interface circuit 1030 to 1104 the means for wirelessly communicating 1100.

In FIGS. 7A and 8B, the network interface circuit 1030 may preferably support at least one wireline communications protocol via the network coupling 1104 with the means for wirelessly communicating 1100.

The wireline communications protocol may support a version of at least one member of a serial protocol list 2100 shown in FIG. 8C, including the following.

A Synchronous Serial Interface protocol 2101, sometimes abbreviated SSI.

An Ethernet protocol 2102.

11

A Serial Peripheral Interface **2103**, sometimes abbreviated SPI.

An RS-232 protocol **2104**.

An Inter-IC protocol **2105**, sometimes abbreviated I2C.

An Universal Serial Bus protocol **2106**, sometimes abbreviated USB.

A Controller Area Network protocol **2107**, sometimes abbreviated CAN.

A Firewire protocol **2108**, which includes implementations the IEEE 1394 communications standard.

An RS-485 protocol **2109**.

An RS-422 protocol **2111**.

In FIGS. **6A**, **7A** and **7C**, the means for wirelessly communicating **1100** may preferably support communicating using at least one version of at least one member of a wireless modulation-demodulation scheme list **2110** shown in FIG. **8D**. The wireless modulation-demodulation scheme list **2110** includes, but is not limited to, the following.

A Time Division Multiple Access scheme **2112**, sometimes abbreviated TDMA.

A Frequency Division Multiple Access scheme **2114**, sometimes abbreviated FDMA.

And a Spread Spectrum Scheme **2115**, which may include variations on one or more of the following:

A Code Division Multiple Access scheme **2116**, sometimes abbreviated CDMA.

A Frequency Hopping Multiple Access scheme **2118**, sometimes abbreviated FHMA.

A Time Hopping Multiple Access scheme **2120**, sometimes abbreviated THMA.

And an Orthogonal Frequency Division Multiple access scheme **2122**, sometimes abbreviated OFDM.

FIG. **9A** shows a refinement of part of the wireless modulation-demodulation scheme list **2110** of FIG. **8D**.

In FIG. **9A**, at least one version of the Time Division Multiple Access schemes (TDMA) **2112** may preferably include a GSM access scheme **2130**. At least one version of the Frequency Division Multiple Access (FDMA) scheme **2114** may preferably include an AMPs scheme **2132**.

In FIG. **9A**, at least one version of the Code Division Multiple Access (CDMA) scheme **2116** may preferably include at least one member of the CDMA scheme list **2150**. The CDMA scheme list **2150** may preferably include, but is not limited to, an IS-95 access scheme **2152**, and a Wideband CDMA (W-CDMA) access scheme **2154**.

In FIG. **9A**, at least one version of the Orthogonal Frequency Division Multiple (OFDM) access scheme **2122** may preferably include at least one of the IEEE 801.11 access schemes **2134**.

FIG. **9A** shows a refinement of part of the wireless modulation-demodulation scheme list **2110** of FIG. **8D**, which includes the following.

At least one version of the Time Division Multiple Access scheme **2112** (TDMA) may preferably include a GSM access scheme **2130**.

At least one version of the Frequency Division Multiple Access scheme **2114** (FDMA) may preferably include an AMPs scheme **2132**.

At least one version of the Code Division Multiple Access scheme **2116** (CDMA) may preferably include at least one member of the CDMA scheme list **2150**.

At least one version of the Orthogonal Frequency Division Multiple access scheme **2122** (OFDM) may preferably include at least one IEEE 802.11 access scheme **2134**.

At least one version of the IEEE 802.11 access scheme **2134** may include the IEEE 802.11b access scheme **2136**.

12

At least one version of the IEEE 802.11 access scheme **2134** may include the IEEE 802.11g access scheme **2135**.

At least one version of the Spread Spectrum Scheme **2115** uses the ANSI 371.1 scheme **2138** for radio frequency identification and/or location tags.

In FIG. **9A**, the CDMA scheme list **2150** may preferably include, but is not limited to,

An IS-95 access scheme **2152**, which uses at least one spreading code to in modulating and demodulating an access channel.

A Wideband CDMA access scheme **2154**, sometimes abbreviated W-CDMA. W-CDMA schemes use not only a spreading code, but also a scattering code to modulate and demodulate an access channel.

FIG. **9B** shows some refinements of the means **1200** of FIGS. **6A** and **7A** for sensing the state of the container handler.

FIG. **10A** shows some refinements of the sensed state **1800** of FIGS. **6A** and **7A**.

In FIG. **9B**, the means **1200** for sensing the state of the container handler may preferably include a means **1250** for radio frequency sensing a radio frequency tag on a container providing **1252** a container radio frequency tag **1254**. In FIG. **10A**, the sensed state **1800** may preferably include the container radio frequency tag **1254** provided **1252** by the means **1250** of FIG. **9B**.

In FIG. **9B**, the means **1200** for sensing the state of the container handler may preferably include a means **1260** for sensing a stack height for a container providing **1262** a container stack height **1264**. In FIG. **10A**, the sensed state **1800** may preferably include the container stack height **1264** provided **1262** by the means **1260** of FIG. **9B**. The container stack height **1264** may be interpreted as shown in FIG. **3B**.

FIG. **10D** shows a further preferred embodiment of the means **1260** for sensing the stacking height, including a stacking height sensor interface **1266** to a stacking height sensor on the container handler.

In FIG. **9B**, the means **1200** for sensing the container handler state may preferably include a means **1270** for sensing at least one member **1274** of a machine state list **1850**, of the container handler, shown in FIG. **10E**. In FIG. **10A**, the sensed state **1800** may preferably include at least one instance of at least one of the machine state list members **1274** provided **1272** by the means **1270** of FIG. **9B**.

In FIG. **9B**, the means **1200** for sensing the container handler state may preferably include the following. At least one member **1280** of the crane sensor means list shown in FIG. **11A** creating **1282** at least one member **1284** of a crane state list, shown in FIG. **11B**. In FIG. **10A**, the sensed state **1800** may preferably include at least one instance of at least one of the crane state list members **1284** provided **1282** by the crane sensor means list member **1280** of FIG. **9B**.

FIG. **9B** shows some refinements of the means for sensing state **1200** of the container handler of FIGS. **6A** and **7A**. Note that the preferred status reporting device **800** for various of the container handler **78** may include one or more of the means for sensing state **1200** shown in this Figure. The means for sensing state **1200** of the container handler may preferably include at least one of the following

A means for sensing operator identity **1210**, which provides **1212** a sensed operator identity **1214**.

A means for sensing container presence **1220**, which second provides **1222** a sensed container present **1224**.

A means for optical container code sensing **1230**, which third provides **1232** an optical container characteristic **1234**.

13

A means for radio frequency tag sensing **1250** of a radio frequency tag on the container **2** fourth providing **1252** a container radio frequency tag **1254**.

A means for container stack height sensing **1260** of the container **2** fifth providing **1262** a container stack height **1264**. In certain embodiments the means for container stack height sensing **1260** may preferably include a cam switch.

At least one means for sensing a machine state list member **1270** of the container handler, sixth providing **1272** a machine state list member **1274** of the machine state list **1850**, shown in FIG. 10E.

At least one crane sensor means list member **1280** seventh providing **1282** at least one crane state list member **1284** of a crane state list **1400** of FIG. 12B. The crane sensor means list member **1280** is a member of the crane sensor means list **1300** shown in FIG. 12A.

A means for sensing container size **1216** seventeenth providing **1218** a container size **1226**.

The container size **1226** may preferably be denoted similarly to the spreader state list **1420** of FIG. 12D. In certain embodiments, for example for use on a UTR truck **10**, the means for sensing container size **1216** may include an ultrasonic sensor to estimate the container size on the back of a bomb cart **14**.

The ultrasonic sensors measures the delay in an echo from the side of the container **2** to estimate its container size **1226**.

A means for sensing container weight **1228** eighteenth providing **1240** a container weight **1242**.

And a means for sensing container damage **1244** nineteenth providing **1246** a container damage estimate **1248**.

In FIG. 9B, the various combinations of some or all of the providings may be similarly implemented.

Among providings similarly implemented, these providings may share a single communication mechanism with the computer **1010**.

Among providings similarly implemented, these providings may use multiple communication mechanisms with the computer **1010**.

In FIG. 9B, some or all of the providings may be distinctly implemented.

In FIG. 9B, the providings may include at least one instance of the following:

- provides **1212** a sensed operator identity **1214**,
- second provides **1222** a sensed container present **1224**,
- third provides **1232** an optical container characteristic **1234**,
- fourth providing **1252** a container radio frequency tag **1254**,
- fifth providing **1262** a container stack height **1264**,
- sixth providing **1272** a machine state list member **1274**,
- seventh providing **1282** at least one crane state list member **1284** of the crane state list **1400** shown in FIG. 12B,
- seventeenth providing **1218** a container size **1226**,
- eighteenth providing **1240** a container weight **1242**, and
- nineteenth providing **1246** a container damage estimate **1248**.

By way of example, the seventh providing **1282** of FIG. 9B, for a rubber tire gantry crane **20** or a straddle carrier **54**, may preferably use at least one of the Synchronous Serial Interface protocol **2101**, the RS-232 Protocol **2104**, the RS-422 Protocol **2111** and/or the RS-485 Protocol **2109**.

14

The crane sensor means list member **1280** may preferably include the means for sensing trolley position **1360** fourteenth providing **1362** a trolley position **1364** as in FIG. 12A.

The crane sensor means list member **1280** may preferably include the means for sensing hoist height **1370** fifteenth providing **1372** a hoist height **1374**.

The means for sensing trolley position **1360** and/or the means for sensing hoist height **1370** may preferably include a rotary absolute optical encoder with either a hollow shaft or standard shaft.

FIG. 10A shows some refinements of the sensed state **1800** of FIGS. 6A and 7A based upon the means for sensing state **1200** of FIG. 9B. The sensed state **1800** may preferably include at least one of the following,

- The sensed operator identity **1214**.
- The sensed container present **1224**. The sensed container present **1224** may preferably be a boolean value of true or false.
- The optical container characteristic **1234**.
- The container radio frequency tag **1254**.
- The container stack height **1264**. The container stack height **1264** may be interpreted as in the discussion of FIG. 3B.
- At least one instance of at least one machine state list member **1274**.
- At least one of the crane state list members **1284**.
- The container size **1226**.
- The container weight **1242**.
- The container damage estimate **1248**.
- The optical container characteristic **1234** of FIGS. 9B and 10A may preferably include at least one instance of a member of a container code characteristic list **1700**, shown in FIG. 10B, which may preferably include
 - a container code text **1702**,
 - a view **1704** of the container code **4** of the container **2**, and
 - a compression **1706** of the view **1704** of the container code **4** of the container **2**.

FIGS. 11A and 11B show examples of the view **1704** in FIG. 10B, of the container code **4** optically viewed on the side of the container **2** of FIGS. 1, 3A, and 4A. The view **1704** of the container code **4** may preferably and alternatively be viewed on any of the vertical sides of the container **2**.

The compression **1706** of the view **1704** may include, but is not limited to, a still frame compression and/or a motion sequence compression of a succession of frames of views.

The compression **1706** may be at least partly the result of applying a two dimensional (2-D) block transform, such as the 2-D Discrete Cosine Transform (DCT) and/or a 2-D wavelet filter bank.

Alternatively, the compression **1706** may be at least partly the result of a fractal compression method.

FIG. 11C shows an example of the container code text **1702** of FIG. 10B.

The container code text **1702** may be at least partly the result of optical character recognition applied to the view **1704** of FIG. 11B.

The means for optical container code sensing **1230** of FIG. 9B may include optical character recognition capabilities, which may be embodied as a separate optical character recognition hardware module or as a separate optical character recognition program system.

The separate optical character recognition hardware module may reside within the means for optical container code sensing **1230** and/or may be coupled to the means for optical container code sensing **1230**.

The separate optical character recognition program system may reside within the means for optical container code sensing **1230** and/or may be coupled to the means for optical container code sensing **1230**.

As used herein, a video imaging device **1238** may belong to a list including at least a video camera, a digital video camera, and a charged coupled array. A video imaging device **1238** may further include any of the following: a computer, a digital memory, an image processor and a flash lighting system.

The status reporting device **800** of FIG. **6A** may include an optical characteristic system as the means for optical container code sensing **1230** of FIG. **9B**, in housing **3000** of FIGS. **1**, **2**, **5A** and **5B**.

The means for optical container code sensing **1230** may include at least one and preferably two of the video imaging device **1238** of FIG. **10C**, housed in a first housing **3100** and a second housing **3110** as in FIGS. **1** and **2**.

The first housing **3100** and the second housing **3110** may be mechanically coupled to a container handler **20** or **30** as in FIGS. **1** and **2**.

The status reporting device **800** may also include at least one, and preferably more than one, light **3120**. The lights **3120** may be controlled through interaction with the invention.

The mechanical coupling of the means for optical container code sensing **1230** to the rubber tire gantry crane **20** may preferably include a mechanical shock absorber to improve reliability.

FIG. **10C** shows some preferred alternative embodiments of the means for optical container code sensing **1230** of FIG. **9B**. The means for optical container code sensing **1230** of the container code **4** on the container **2** may preferably include any combination of the following.

A video interface **1236** to receive at least one optical container characteristic **1234** of the container code **4**.

At least one video imaging device **1238** to create at least one optical container characteristic **1234** of the container code. The video imaging device **1238** may be in a separate housing and/or location as shown by the first housing **3100** and/or the second housing **3110** in FIGS. **1**, **2**, and **5A**.

At least one image processor **1239** may process and/or create at least one of the optical container characteristic **1234**.

The video imaging device **1238** may belong to a list including at least a video camera, a digital video camera, and a charged coupled array.

The video imaging device **1238** may further include any of the following: a computer, a digital memory, an instance of the image processor **1239** and/or a flash lighting system.

FIG. **10D** shows a further preferred embodiment of the means for container stack height sensing **1260**, including a stacking height sensor interface **1266** to a stacking height sensor on the container handler **78**. One stacking height sensor, which may be preferred, is a draw wire encoder.

The draw wire encoder may be preferred when the container handler is at least one of the following: the rubber tire gantry crane **20**, the side picker **40**, the top loader **50**, the reach stacker **46**, and/or the straddle carrier **54**.

Alternatively, the stacking height sensor may be an absolute/hollow shaft encoder.

FIG. **10E** shows a preferred embodiment of the machine state list **1850**. The machine state list **1850** may include, but is not limited to,

- a reverse motion **1852**,
- a frequent stops count **1854**,
- a collision state **1856**,
- a fuel level **1858**,

a compass reading **1860**,

a wind speed **1862**. In certain embodiments, the wind speed may further indicate a wind direction,

a vehicle speed **1864**, and

a vehicle braking system state **1866**.

In some preferred embodiments, the means for sensing a machine state list member **1270**, the machine state list member **1274** includes the vehicle speed **1864**, may preferably include a drive shaft sensor counting the drive shaft revolutions.

FIG. **10E** shows a preferred embodiment of the machine state list **1850**. The machine state list **1850** may include, but is not limited to, a reverse motion **1852**, a frequent stops count **1854**, a collision state **1856**, a fuel level **1858**, and a compass reading **1860**.

FIG. **12A** shows some details of the crane sensor means list **1300** related to members **1280** of FIG. **9B**. FIG. **12B** shows some details of the crane state list **1400** related to members **1284** of FIGS. **9B** and **10A**. FIG. **12C** shows some details of a twistlock list **1410** related to members **1314** of FIG. **12A**. FIG. **12D** shows some details of the spreader state list **1420** related to members **1324** of FIG. **12A**. FIG. **12E** shows some details of the landing state list **1430** related to members **1334** of FIG. **12A**.

FIG. **12A** shows some details of the crane sensor means list **1300** related to at least one instance of the crane sensor means list member **1280** of FIG. **9B**. The crane sensor means list **1300** preferably includes at least one of the following

A means for twistlock sensing **1310** eighth providing **1312** a twistlock sensed state **1314**.

The means for spreader sensing **1320** to ninth provide **1322** a spreader sensed state **1324**.

The means for sensing container landing **1330** to tenth provide **1332** a sensed landing state **1334**.

The means for sensing trolley position **1360** fourteenth providing **1362** a trolley position **1364**.

The means for sensing hoist height **1370** fifteenth providing **1372** a hoist height **1374**.

The means for sensing trolley position **1360** and/or the means for sensing hoist height **1370** may preferably include a rotary absolute optical encoder with either a hollow shaft or standard shaft.

In FIG. **12A**, the twistlock sensed state **1314**, preferably, is a member of a twistlock state list **1410** shown in FIG. **12C**. FIG. **12C** shows the twistlock state list **1410** including a twistlock-on state **1412** and a twistlock-off state **1414**.

In FIG. **12A**, the spreader sensed state **1324**, preferably is a member of a spreader state list **1420** shown in FIG. **12D**. FIG. **12D** shows the spreader state list **1420** including a ten foot container spread **1421**, a twenty foot container spread **1422**, a thirty foot container spread **1428**, and a forty foot container spread **1424**, and a forty-five foot container spread **1426**.

Various embodiments may support the spreader sensed state **1324** limited to a subset of the spreader state list **1420**.

By way of example, in certain preferred embodiments, the spreader sensed state **1324** may be limited to a subset of the spreader state list **1420** consisting of the twenty foot container spread **1422** and the forty foot container spread **1424**.

In FIG. **12A**, the sensed landing state **1334**, preferably, is a member of a landing state list **1430** shown in FIG. **12E**. FIG. **12E** shows the landing state list **1430** including a landed state **1432** and a not-landed state **1434**.

FIG. 12B shows some details of the crane state list 1400 related to the crane state list member 1284 of FIGS. 9B and 10A. The crane state list 1400 preferably includes at least one of the following

- The twistlock sensed state 1314,
- The spreader sensed state 1324,
- The sensed landing state 1334.

FIG. 13A shows a refinement of the status reporting device 800 of FIGS. 6A and 7A where the sensing means 1200 includes coupling 1202 to a crane spreader interface connection 1340. The crane spreader interface connection 1340 preferably provides at least one of the crane state list 1400 members as shown in FIG. 12B.

FIG. 13B shows a refinement of the status reporting device 800 of FIGS. 6A and 7A where the sensing means 1200 includes coupling 1202 to a Programmable Logic Controller (PLC) 1350. The PLC 1350 preferably provides at least one of the crane state list 1400 members as shown in FIG. 12B.

FIG. 13B also shows the computer 1010 of FIGS. 6A, 7A and 13A, coupled 1352 to the PLC 1350. The coupling 1352 may preferably include a serial communications coupling 1352. The serial communications coupling 1352 preferably supports a version of at least one member of a serial protocol list 2100 of FIG. 8C.

By way of example, the crane spreader interface connection 1340 of FIG. 13A may contain the spreader sensed state 1324 as two signals. The two signals are the “spreader is at least at twenty feet”, and the “spreader is at forty feet”. If the “spreader is at least at twenty feet” is true and the “spreader is at forty feet” is false, then the sensed spreader state 1324 indicates the crane spreader is set for twenty feet. If the “spreader is at least at twenty feet” is true and the “spreader is at forty feet” is true, then the sensed spreader state 1324 indicates the crane spreader set for forty feet.

FIG. 13A shows a refinement of the status reporting device 800 of FIGS. 6A and 7A where the means for sensing state 1200 includes a crane spreader interface connection 1340.

The crane spreader interface connection 1340 preferably provides at least one member of the crane state list 1400 as shown in FIG. 12B.

The crane spreader interface connection 1340 eleventh provides 1344 the twistlock sensed state 1314.

The crane spreader interface connection 1340 twelfth provides 1346 the spreader sensed state 1324.

The crane spreader interface connection 1340 thirteenth provides 1348 the sensed landing state 1334.

FIG. 13A also shows the status reporting device 800 with the means for sensing state 1200 of the container handler 78 including a crane sensor coupling 1342 of the computer 1010 of FIGS. 6A and 7A to the crane spreader interface connection 1340.

The crane sensor coupling 1342 may preferably include conversion circuitry interfaced to parallel input and/or output ports of the computer 1010. The conversion circuitry may interface AC lines through relays.

In certain embodiments, the crane sensor coupling 1342 may be included in the second communicative coupling 1202 of the micro-controller module 1000 with the means for sensing state 1200.

Alternatively, the crane sensor coupling 1342 may not be included in the second communicative coupling 1202 of the micro-controller module 1000 with the means for sensing state 1200.

By way of example, the crane spreader interface connection 1340 of FIG. 13A may contain the spreader sensed state 1324 as two signals.

The two signals are the “spreader is at least twenty foot”, and the “spreader is at forty foot”.

If the “spreader is at least at twenty foot” is true and the “spreader is at forty foot” is false, then the sensed spreader state 1324 indicates the crane spreader is set for twenty foot.

If the “spreader is at least at twenty foot” is true and the “spreader is at forty foot” is true, then the sensed spreader state 1324 indicates the crane spreader set for forty foot.

By way of example, the crane spreader interface connection 1340 of FIG. 13A may contain the spreader sensed state 1324 as three signals.

The two signals are the “spreader is at least at twenty foot”, the “spreader is at forty foot”, and the “spreader is at least forty-five foot”.

If the “spreader is at least at twenty foot” is true, the “spreader is at forty foot” is false, and the “spreader is at least forty-five foot” is false, then the sensed spreader state 1324 indicates the crane spreader is set for twenty foot.

If the “spreader is at least at twenty foot” is true, the “spreader is at forty foot” is true, and the “spreader is at least forty-five foot” is false then the sensed spreader state 1324 indicates the crane spreader set for forty foot.

If the “spreader is at least at twenty foot” is true, the “spreader is at forty foot” is true, and the “spreader is at least forty-five foot” is true then the sensed spreader state 1324 indicates the crane spreader set for forty-five foot.

In FIG. 13A, some or all of the providings may be similarly implemented. Among those providings similarly implemented, they may use the same of different mechanisms to provide. Alternatively, some of the providings may be distinctly implemented. The providings of FIG. 13A include

The eleventh provides 1344 the twistlock sensed state 1314.

The twelfth provides 1346 the spreader sensed state 1324.

The thirteenth provides 1348 the sensed landing state 1334.

FIG. 13B shows a refinement of the status reporting device 800 of FIGS. 6A and 7A, with the means for sensing state 1200 of the container handler 78, including a Programmable Logic Controller 1350, which is sometimes denoted PLC.

The Programmable Logic Controller 1350 preferably provides at least one member of the crane state list 1400 as shown in FIG. 12B.

Preferably, the Programmable Logic Controller 1350 may fourteenth provide 1354 the twistlock sensed state 1314.

Preferably, the Programmable Logic Controller 1350 may fifteenth provide 1356 the spreader sensed state 1324.

Preferably, the Programmable Logic Controller 1350 may sixteenth provide 1358 the sensed landing state 1334.

FIG. 13B also shows the status reporting device 800 including a second crane sensor coupling 1352 of the computer 1010 of FIGS. 6A, 7A and 13A with the Programmable Logic Controller 1350.

The second crane sensor coupling 1352 may preferably include a serial communications coupling 1352.

The serial communications coupling 1352 preferably supports a version of at least one member of a serial protocol list 2100 of FIG. 8C.

In FIG. 13B, some or all of the providings may be similarly implemented. Among those providings similarly implemented, they may use the same of different mechanisms to provide. Alternatively, some of the providings may be distinctly implemented. The providings of FIG. 13B include

19

The fourteenth provide **1354** the twistlock sensed state **1314**.

The fifteenth provide **1356** the spreader sensed state **1324**.

The sixteenth provide **1358** the sensed landing state **1334**.

In FIGS. **13A** and **13B**, the container handler **78** may preferably be a version of a member of the container handler list **80** of FIG. **4B**. The container handler **78** may also be an assembly of two or more members of the container handler list **80**. By way of example, the container handler **78** may include the UTR truck **10** of FIG. **1** attached to the Bomb cart **14**. In certain situations, the UTR truck **10** may be attached to an over the road chassis.

FIG. **14A** shows the means for providing **200** of FIGS. **6A** and **7A** further including a means for location coupling **230**. The means for location coupling **230** assembles **232** the micro-controller module **1000** with a means for determining **1500** location the container handler.

In FIG. **14A**, the means for determining **1500** may include one or more of the following:

An interface to a Global Positioning System (GPS).

An interface to a Differential Global Positioning System (DGPS).

A means for wirelessly determining location, such as by use of a local wireless network providing timed signal bursts from multiple antenna sites within the local wireless network.

A radio location-tag unit.

By way of example, GPS is a satellite communications system which supports determining the location of a receiver. DGPS is a refinement of the GPS using an earth-based reference station to support positional accuracy to within a meter.

FIG. **14B** shows a detail flowchart of operation **2512** of FIG. **8A** further providing the micro-controller module **1000** with the coupled means **1200** for sensing the state of the container handler of FIGS. **6A** and **7A**. Operation **2562** supports providing the micro-controller module **1000** with the second communicative coupling **1202** to the means for sensing state **1200** of the container handler.

FIG. **14C** shows a detail of operation **2512** of FIG. **8A** further providing the micro-controller module **1000** coupled with the means for determining **1500** the location the container handler of FIG. **14A**. Operation **2572** supports providing the micro-controller module **1000** communicatively coupling **1502** to a means for determining **1500** the location of the container handler.

FIG. **15A** shows the means for wirelessly communicating **1100** including the means for wirelessly determining **1510** the location of the container handler. The means for wirelessly determining **1510** may include one or more of the following:

An interface to the Global Positioning System (GPS).

An interface to the Differential Global Positioning System (DGPS).

Alternatively, the means for wirelessly determining **1510** may provide timed signal bursts to multiple antenna sites within the local wireless network to support the wireless network determining the location of itself. This means for wirelessly determining **1510** may not require the use or storage of an estimate of the location **1900** in the memory **1020** accessed **1022** by the computer **1010**, as shown in FIG. **6A**.

FIG. **15B** shows a detail of the program system **2000** of FIGS. **6A** and **6B** for determining and communicating the location of the container handler **78**.

20

Operation **2072** supports using the means **1500** of FIG. **14A** for locating the container handler **78** to, at least partly, determine the location **1900** of the container handler **78**.

Operation **2082** uses the means for wirelessly communicating **1100** to communicate the location **1900**.

In FIG. **15A**, the means for wirelessly communicating **1100** may further include a radio location-tag unit.

In certain preferred embodiments, the radio location-tag unit may act as the means for wirelessly determining **1510** the location **1900** of the container handler **78**.

The radio location-tag unit may further support a national and/or international standard, which may include, but is not limited to, a version of ANSI 371.1 standard for radio location tags.

In such embodiments, the local computer **1010** may not require the location **1900** present in memory **1020**, as shown in FIG. **6A**.

In such embodiments, the need for the program system **2000** to determine location may be non-existent, removing the presence of the operation of FIG. **15B**.

FIG. **16A** shows the memory **1020** of FIG. **6A** including a non-volatile memory **1024**. The computer **1010** may preferably access **1022** the non-volatile memory **1024**, similarly to the discussion of FIG. **6A**. The non-volatile memory **1024** may include at least part of the program system **2000**.

FIG. **16B** shows a detail flowchart of operation **2522** of FIG. **8A** further installing the program system **2000** of FIG. **6A**.

Operation **2592** supports altering at least part of the non-volatile memory **1024** of FIG. **16A** to install at least part of at least one program step of the program system **2000**.

Operation **2602** supports installing a memory module including at least part of at least one of the program steps residing in the non-volatile memory **1024** to create at least part of the memory **1020** accessed **1022** by the computer **1010**.

FIGS. **17** to **20** show various status reporting devices **800** for the rubber tire gantry crane **20** of FIG. **1**. Similar embodiments are useful with the quay crane **30** of FIG. **2**. In FIGS. **17** to **20**, the means for sensing state **1200** is disclosed in terms of the details of its contents and communications.

FIG. **17** shows the status reporting device **800** communicating through couplings with

The means for wirelessly communicating **1100**,

The display **3010**, may preferably be a Liquid Crystal Display, and

The means for sensing state **1200** includes the following:

The means for sensing operator identity **1210**,

The means for container stack height sensing **1260**,

The means for sensing a machine state list member **1270**,

The crane spreader interface connection **1340**,

The means for determining **1500** location, further including a Differential Global Positioning System (DGPS), and

A second means for determining **1500-B** location, which preferably includes a means for sensing laser trolley position Alternatively, this may incorporate a drawwire and/or rotary encoder.

In FIG. **17**, the means for sensing a machine state list member **1270** provides the frequent stops count **1854**, the collision state **1856**, the fuel level **1858**, the wind speed **1862**, and the vehicle speed **1864**.

In FIGS. **17** and **20**, the means for sensing state **1200** also provides, via the crane sensor coupling **1342**, the following to the computer **1010**:

21

The twistlock sensed state **1314**,

The spreader sensed state **1324**, which may further preferably include

the spreader sense state at twenty foot **1324-20**, and
the spread sense state at forty foot **1324-40**, and

the sensed landing state **1334**.

FIG. **18** shows the status reporting device **800** communicates via couplings with

The means for wirelessly communicating **1100**, which preferably includes a wireless modem preferably supporting a version of the IEEE 802.11 access scheme **2134**, preferably the IEEE 802.11b access scheme **2136**. Alternatively, the wireless modem may support an Radio Frequency Identification (RF ID) protocol.

The display **3010**, and

The means for sensing state **1200**, which preferably includes the following

The means for sensing operator identity **1210**,

The means for container stack height sensing **1260**,

The means for sensing a machine state list member **1270**, which provides the frequent stops count **1854**, the collision state **1856**, the fuel level **1858** and the wind speed **1862**.

The Programmable Logic Controller **1350**, and

The means for determining **1500** location, preferably using the Differential Global Positioning System (DGPS) of FIG. **14A**.

In FIG. **18**, the computer **1010** couples through the Programmable Logic Controller **1350** with the following:

at least one means for container stack height sensing **1260**,
and

a second means for determining **1500-B** location, which preferably includes a means for sensing laser trolley position.

FIG. **17** shows the status reporting device **800** coupling with the crane spreader interface connection **1340** of FIG. **13A**, and using a Differential Global Positioning System (DGPS) means **1500** of FIG. **14A**.

FIG. **18** shows the status reporting device **800** coupling with the PLC **1350** of FIG. **13B**, and using the Differential Global Positioning System (DGPS) means **1500** of FIG. **14A**.

FIG. **19** shows the status reporting device **800** communicating via couplings with

The means for wirelessly communicating **1100**, which further includes the means for wirelessly determining **1510** location of FIG. **15A**. The means for wirelessly determining **1510** may preferably include a radio frequency tag device.

The display **3010**.

And the means for sensing state **1200** which includes

The means for container stack height sensing **1260**,

The Programmable Logic Controller **1350**.

The means for sensing a machine state list member **1270**, which preferably provides the frequent stops count **1854**, the collision state **1856**, the fuel level **1858**, and the wind speed **1862**.

The means for sensing operator identity **1210**, similar to **1210** of FIGS. **17** and **18**.

FIG. **20** shows the status reporting device **800** coupling with the crane spreader interface connection **1340** of FIG. **13A**, and using the location and data radio frequency tag device **1510** of FIG. **15A**.

FIG. **20** shows the status reporting device **800** communicating via couplings with

The means for wirelessly communicating **1100** may preferably include the means for wirelessly determining

22

1510 location of FIG. **15A**, which may preferably include a radio frequency tag device.

The display **3010**.

And the means for sensing state **1200** which includes

The means for sensing operator identity **1210**,

The means for container stack height sensing **1260**,

The crane spreader interface connection **1340**,

The second means for determining **1500-B** location, and

The means for sensing a machine state list member **1270**, which provides the frequent stops count **1854**, the collision state **1856**, the fuel level **1858**, the wind speed **1862**, and vehicle speed **1864**.

In FIGS. **17** to **19**, a second means **1500-B** for determining the location of the container handler is used. The second means **1500-B** may preferably be a trolley position sensor, which may be laser based.

In FIGS. **17** to **20**, rubber tire gantry cam shafts and hoist position encoders are shown. These interact with the cam switch for the hoist-stack position to provide the means **1260** to sense the stack height for RTG cranes **20**.

In FIGS. **17** to **20**, the means **1260** for sensing the stack height may involve as many as eight separate sensor states, which may indicate whether their respective stack location is occupied.

FIGS. **17** to **23** show the means for container stack height sensing **1260**.

Preferably, the means for container stack height sensing **1260** may include at least one cam shaft and/or at least one hoist position encoder when used with the rubber tire gantry crane **20** of FIG. **1**.

Preferably, the means for container stack height sensing **1260** may include at least one cam shaft and/or at least one hoist position encoder when used with the quay crane **30** of FIG. **2**.

These interact with one or more sensors of the sensor hoist-stack position to sense the stack height for a rubber tire gantry crane **20** or quay crane **30**.

The means for sensing the stack height **1260** may involve as many as eight separate sensor states, which may indicate whether their respective stack location is occupied. Containers may be preferably stacked as high as seven containers.

FIGS. **21** to **23** show various status reporting devices **800** for use with some or all of the following container handlers **78**, which are members of the container handler list **80** of FIG. **4B**:

The side picker **40** shown in FIG. **3A**.

The reach stacker **46** shown in FIG. **4A**.

The top handler **50** shown in FIG. **4C**.

The straddle carrier **54** shown in FIG. **4D**.

In FIGS. **21** to **23**, the means for sensing state **1200** is disclosed in terms of the details of its contents and communications.

In certain preferred embodiments, the status reporting device **800** of FIGS. **21** to **23**, for use with the side picker **40**, the top handler **50** and/or the straddle carrier **54**, as well as the status reporting device **800** of FIGS. **17** to **20**, for use with the rubber tire gantry crane **20**, may sense the following.

The length of time the vehicle has run since it was started.
The compass reading **1860**.

When the spreader has landed on a container **2** as the sensed landing state **1334**.

When the spreader has locked on the container.

The container size **1226**, which is preferably one of the members of the spreader state list **1420** of FIG. **12D**.
Further, the container size may preferably be one of the

23

twenty foot container spread **1422**, the forty foot container spread **1424** and the forty-five foot container spread **1426**.

The container stack height **1264** may preferably range from one to seven containers in height. This may be preferably be measured in feet.

The reverse motion **1852**.

The fuel level **1858** may be optionally provided.

And the sensed operator identity **1214** may be optionally provided.

In certain embodiments, the status reporting device **800** may use the means for wirelessly communicating **1100** instead of the means for determining **1500** the location **1900**. The means for wirelessly communicating **1100** may sensed by an external radio system to determine the container handler location. This may be preferred in terms of the cost of production of the status reporting device.

In certain preferred embodiments, the status reporting device **800** of FIGS. **21** to **23**, for use with the side picker **40**, the top handler **50** and/or the straddle carrier **54**, as well as the status reporting device **800** of FIGS. **17** to **20**, for use with the rubber tire gantry crane **20**, may implemented to include the following.

The means for spreader sensing **1320** may include a magnetic proximity switch on and/or near the status reporting device **800**.

The reverse sensor may be communicatively coupled with the reverse buzzer on the vehicle.

The sixth providing **1272** of the compass reading **1860** may use the RS-422 protocol **2111**.

The means for sensing container landing **1330** may include a proximity switch on and/or near the status reporting device **800**.

The means for wirelessly communicating **1100** may be used to provide location of the vehicle. It may be further preferred that there are multiple means for wirelessly communicating, which may further preferably embody a radio frequency tag technology, including a version of the ANSI 371.1 scheme **2138**. The radio frequency tag technology may preferably be compatible with the WHERENET™ products.

The first communicative coupling **1102** of the means for wirelessly communicating **1100** and the micro-controller module **1000** may use the RS-485 protocol **2109**.

In certain preferred embodiments, the status reporting device **800** of FIGS. **21** to **23**, for use with the side picker **40** and/or the top handler **50**, may implemented to further include the following.

The means for container stack height sensing **1260** may include a draw wire encoder. The fifth providing **1262** of the container stack height **1264** may preferably use the RS-422 protocol **2111**.

In certain preferred embodiments, the status reporting device **800** of FIGS. **21** to **23**, for use with the straddle, carrier **54**, as well as the status reporting device **800** of FIGS. **17** to **20**, for use with the rubber tire gantry crane **20**, may implemented to include the following.

The means for sensing hoist height **1370** may include a hollow shaft or a shafted optical absolute encoder. The fifteenth providing **1372** of the hoist height **1374** may preferably use the RS-422 protocol **2111** and/or the Synchronous Serial Interface protocol **2101**.

The means for sensing trolley position **1360** may include a hollow shaft or a shafted optical absolute encoder. The fourteenth providing **1362** of the trolley position **1364**

24

may preferably use the RS-422 protocol **2111** and/or the Synchronous Serial Interface protocol **2101**.

In certain preferred embodiments, the status reporting device **800** of FIGS. **21** to **23**, for use with the side picker **40**, the top handler **50** and/or the straddle carrier **54**, as well as of FIGS. **17** to **20** for the rubber tire gantry crane **20**, may be implemented using a programmable logic controller **1350** as in FIG. **13B**. The following may be preferred in such situations.

The sixth providing **1272** of the compass reading **1860** may use the RS-422 protocol **2111**.

The first communicative coupling **1102** of the means for wirelessly communicating **1100** and the micro-controller module **1000** may use the RS-485 protocol **2109**.

In certain preferred embodiments, the status reporting device **800** of FIGS. **21** to **23**, for use with the side picker **40**, the top handler **50**, and/or the straddle carrier **54**, as well as of FIGS. **17** to **20** for the rubber tire gantry crane **20**, may use a second display **3020**.

It may be preferred to send the human operator messages that are displayed on the second display. These messages may include directions to pickup a container **2** from a communicated location in the terminal yard.

Preferably, the means for wirelessly communicating **1100** supports a bi-directional communications protocol. The bi-directional communications protocol may preferably support a version of the IEEE 802.11 access scheme **2134**.

The bi-directional communications protocol may further support the reprogramming of non-volatile memory **1024**.

A location tag associated with the vehicle may be commanded to blink.

FIG. **21** shows the status reporting device **800** communicating via couplings with

The means for wirelessly communicating **1100**.

The display **3010**.

The second display **3020**.

And the means for sensing state **1200**.

In FIG. **21**, the means for sensing state **1200** preferably includes

The means for sensing operator identity **1210**,

The means for sensing container presence **1220**,

The means for optical container code sensing **1230**,

The means for sensing a machine state list member **1270**, which provides the reverse motion **1852**, the frequent stops count **1854**, the collision state **1856**, the fuel level **1858**, the compass reading **1860**, and the vehicle speed **1864**,

The Programmable Logic Controller **1350**, and

The means for determining **1500** location.

In FIGS. **18**, **19**, and **21**, the Programmable Logic Controller **1350** further provides the computer **1010**, via the second crane sensor coupling **1352**, with the following:

The twistlock sensed state **1314**,

By way of example, the spreader sensed state **1324**, b may further preferably include the spreader sense state at twenty foot **1324-20**, and the spread sense state at forty foot **1324-40**, and

the sensed landing state **1334**.

The spreader sensed state **1324** may include other sizes, examples of which are shown in the spreader state list **1420** of FIG. **12D**.

In FIGS. **18**, **19**, and **21**, the Programmable Logic Controller **1350** further provides the computer **1010**, via the second crane sensor coupling **1352**, with the states of the means for container stack height sensing **1260**. The Programmable

25

Logic Controller **1350** may also sometimes preferably provide the spreader sensed state **1324**.

In FIG. **22**, the status reporting device **800** supports the Differential Global Positioning System (DGPS) means **1500** of FIG. **14A**.

FIG. **22** shows the status reporting device **800** communicating via couplings with

The means for wirelessly communicating **1100**.

The display **3010**.

The second display **3020**.

And the means for sensing state **1200**.

In FIG. **22**, the means for sensing state **1200** preferably includes

The means for sensing operator identity **1210**,

The means for sensing container presence **1220**,

The means for optical container code sensing **1230**,

The means for container stack height sensing **1260**,

The means for sensing a machine state list member **1270**,

which provides the reverse motion **1852**, the frequent

stops count **1854**, the collision state **1856**, the fuel level

1858, and the compass reading **1860**, and

The twistlock sensed state **1314**, the spreader sensed state

1324, which may further preferably include the spreader

sense state at twenty foot **1324-20**, and the spread sense

state at forty foot **1324-40**, and the sensed landing state

1334. The spreader sensed state **1324** may include other

sizes, examples of which are shown in the spreader state

list **1420** of FIG. **12D**.

The means for determining **1500** location.

FIG. **23** shows the status reporting device **800** communicating via couplings with

The means for wirelessly communicating **1100**.

The display **3010**.

The second display **3020**.

And the means for sensing state **1200**.

In FIG. **23**, the status reporting device **800** supports the location and data radio frequency tag device **1510** of FIG. **15A**.

In FIG. **23**, the means for sensing state **1200** preferably includes

The means for sensing operator identity **1210**,

The means for sensing container presence **1220**,

The means for optical container code sensing **1230**,

The means for container stack height sensing **1260**,

The means for sensing a machine state list member **1270**,

which provides the reverse motion **1852**, the frequent

stops count **1854**, the collision state **1856**, the fuel level

1858, the compass reading **1860**, and the vehicle speed

1864, and

The twistlock sensed state **1314**, the spreader sensed state

1324, which may further preferably include the spreader

sense state at twenty foot **1324-20**, and the spread sense

state at forty foot **1324-40**, and the sensed landing state

1334.

The spreader sensed state **1324** may include other sizes,

examples of which are shown in the spreader state list

1420 of FIG. **12D**.

FIGS. **24** and **25** show various embodiments of the status reporting device **800** for the UTR truck **10** of FIG. **1**. In these Figures the means for sensing state **1200** is disclosed in the details of its contents and communications. The UTR truck may be attached to the bomb cart **14**, or a chassis **14**, where the container **2** may be tied down.

In FIG. **24**, the status reporting device **800** supports the Differential Global Positioning System (DGPS) means **1500** of FIG. **14A**.

26

FIG. **24**, shows the status reporting device **800** communicating via couplings with

The means for wirelessly communicating **1100**.

The display **3010**.

And the means for sensing state **1200**.

In FIG. **24**, the means for sensing state **1200** preferably includes

The means for sensing operator identity **1210**.

The means for sensing container size **1216**.

The means for sensing container presence **1220**.

The means for optical container code sensing **1230**.

The means for sensing a machine state list member **1270**,

which provides the reverse motion **1852**, the frequent

stops count **1854**, the collision state **1856**, the fuel level

1858, the wind speed **1862**, and the vehicle speed **1864**.

And a fifth wheel engage/disengage proximity sensor.

FIG. **25** shows the status reporting device **800** communicating via couplings with

The means for wirelessly communicating **1100**, preferably

implemented using the means for wirelessly determining

1510.

The display **3010**.

And the means for sensing state **1200**.

In FIG. **25**, the status reporting device **800** supports the location and data radio frequency tag device **1510** of FIG. **15A**.

In FIG. **25**, the means for sensing state **1200** preferably includes

The means for sensing operator identity **1210**.

The means for sensing container presence **1220**.

The means for sensing a machine state list member **1270**,

which provides the reverse motion **1852**, the frequent

stops count **1854**, the collision state **1856**, the fuel level

1858, the wind speed **1862**, and the vehicle speed **1864**.

And a fifth wheel engage/disengage proximity sensor.

The status reporting device **800** used on the bomb cart **14** and/or the chassis **14** may preferably resemble the status reporting device **800** for the UTR truck **10** shown in FIGS. **24** and **25** without those features which sense an engine and/or its fuel, as well as, sense the presence and/or identity of an operator. The status reporting device **800** may also lack the means for optical container code sensing **1230**.

The status reporting device **800** of FIGS. **24** and/or **25**, for the UTR truck **10** may preferably operate as follows.

The micro-controller module **1000** may sense how long the

UTR truck **10** has been running.

The micro-controller module **1000** may sense when the

fifth wheel is engaged.

The micro-controller module **1000** may sense when the

brakes are applied.

The micro-controller module **1000** may sense when the

container **2** is a forty foot container.

The micro-controller module **1000** may sense when the

container **2** is a twenty foot container and positioned in

the front or back of a bomb cart **14**.

The micro-controller module **1000** may sense when the

container **2** is on a chassis.

The micro-controller module **1000** may sense the compass

reading **1860**.

Optionally, the micro-controller module **1000** may sense

the fuel level **1858**.

Optionally, the micro-controller module **1000** may receive

the sensed operator identity **1214**.

The means for wirelessly communicating **1100** may inter-

face with the WHERENET™ radio tag system.

The means for wirelessly communicating **1100** may fur-

ther be a WHERENET tag.

Communication through the means for wirelessly communicating **1100** may preferably occur when a container is engaged, a container is gained or leaves a bomb cart **14**, and/or when the UTR truck **10** starts to move.

In certain embodiments, the status reporting device **800** may use the means for wirelessly communicating **1100** instead of the means for determining **1500** the location **1900**. The means for wirelessly communicating **1100** may be sensed by an external radio system to determine the container handler location. This may be preferred in terms of the cost of production of the status reporting device.

The status reporting device **800** of FIGS. **24** and/or **25**, for the UTR truck **10** may preferably include the following sensor interfaces.

The fifth wheel engage-disengage may be sensed by a magnetic proximity switch.

The vehicle speed **1864** and/or movement may be sensed by the number of revolutions of the driveshaft.

The compass reading **1860** may interface using the RS-422 protocol **2111**.

The container presence may preferably use an ultrasonic sonar with a four to twenty milliAmp (mA) analog output. This is measured by the micro-controller module **1000** to determine the distance.

Alternatively, the container presence may use a laser to determine distance.

The means for wirelessly communicating **1100** may be coupled to the micro-controller module **1000** using the RS-422 protocol **2111**.

The determination of location may be achieved by the means for wirelessly communicating **1100**, particularly implementing the WHERENET™ radio tag.

The radio tag may further be commanded to blink.

The reverse motion sensor may be based upon the reverse motion buzzer of the UTR truck **10**.

In FIGS. **5B**, and **21** to **25**, the status display **3010** is shown.

The display **3010** may communicate directly with the computer **1010**, or communicate through one of the Network Interface Circuits (NICs).

The display **3010** may preferably be a Liquid Crystal display. However, one skilled in the art will recognize that there are many alternative means for presenting a status display.

The display **3010** may preferably be used to display status. In FIGS. **21** to **23**, the second display **3020** is shown.

The second display **3020** may communicate directly with the computer **1010**, or communicating through one of the Network Interface Circuits (NICs).

The second display **3020** may preferably be a Liquid Crystal display. However, one skilled in the art will recognize that there are many alternative means for presenting a status display.

The second display **3020** may preferably be used to display command options, which may be available to an operator of the container handler **78**.

A second display **3020** may also be used in the status reporting device **800** for a UTR truck **10**.

In such situations, when the second display **3020** is present, the status reporting device **800** further includes a network interface circuit supporting a version of the IEEE 802.11 access scheme **2134**.

The operator can receive messages as to where to go in the terminal yard to pickup a container **2**.

The network interface circuit's support of the version of the IEEE 802.11 access scheme **2134**, makes remote reprogramming of the status reporting device **800** possible.

FIGS. **17**, **18**, **21**, **22**, and **24** shows status reporting devices **800** including a second Network Interface Circuit **1034**.

A second network interface coupling **1036** supports the computer **1010** communicating via the second network interface circuit **1034**.

The network interface circuit **1030** and the second network interface circuit **1034** may preferably support distinct serial communications protocols.

By way of example, the network interface circuit **1030** may support RS-232, while the second network interface circuit **1034** may support Ethernet.

Both the network interface circuit **1030** and the second network interface circuit **1034** may preferably be implemented as components within a micro-controller, which also contains the computer **1010**.

The status reporting device **800** and its one or more communications protocols may support use of a TCP/IP stack, HTTP, java, and possibly the use of XML.

The preceding embodiments have been provided by way of example and are not meant to constrain the scope of the following claims.

What is claimed is:

1. An apparatus, comprising:

a micro-controller module for use on a top handler communicatively coupled to a means for optically sensing a container code of a container being handled by said top handler to create an optical container characteristic including at least one member of a container code characteristic collection, and communicatively coupled to at least one of a means for wirelessly communicating said optical container characteristic, and a means for wirelessly determining location;

wherein said micro-controller module includes a computer; said computer further includes at least one member of a list comprising an instruction processor, an inferential engine, a neural network, and a finite state machine;

wherein said instruction processor includes at least one instruction processing element and at least one data processing element; wherein each of said data processing elements is controlled by at least one of said instruction processing elements

and said instruction processor is accessibly coupled to a memory and said instruction processor is directed by a program system including program steps residing in said memory; and

wherein said finite state machine includes at least one of: means for using a means for sensing a state of said top handler to create a sensed state;

means for using said means for wireless communicating to communicate said sensed state of said top handler.

2. The apparatus of claim 1,

wherein said micro-controller module is further communicatively coupled to said means for sensing further comprising a means for sensing a machine state of said top handler, whereby said machine state includes at least one member of the machine state list including a reverse motion, a frequent stops count, a collision state, a fuel level, a compass reading, a wind speed and a vehicle speed.

3. The apparatus of claim 1, wherein said micro-controller module is further communicatively coupled to at least one of: a means for sensing an operator identity to create a sensed operator identity;

29

a means for sensing a container presence to create a sensed container presence;
 a means for sensing a radio tag to create a container radio tag; and
 a means for sensing a container stack height.

4. The apparatus of claim 1, wherein said means for wirelessly communicating supports communicating using at least one version of at least one member of a wireless modulation-demodulation scheme list;

wherein said wireless modulation-demodulation scheme list comprises a time division multiple access scheme, a frequency division multiple access scheme, a code division multiple access scheme, a frequency hopping multiple access scheme, a time hopping multiple access scheme, and an orthogonal frequency division multiple access scheme.

5. The apparatus of claim 4,

wherein at least one of said versions of said time division multiple access scheme includes a GSM access scheme; wherein at least one of said versions of said frequency division multiple access scheme includes an AMPs access scheme;

wherein at least one of said versions of said code division multiple access scheme includes at least one member of the CDMA scheme list; wherein said CDMA list includes an IS-4 access scheme, and a Wideband CDMA access scheme;

wherein at least one of said versions of said orthogonal frequency division multiple access scheme includes an IEEE 801.11 access scheme.

6. The apparatus of claim 1, further comprising:

said means for sensing to create said sensed state, whereby said micro-controller module uses said means for sensing to create said sensed state, and said sensed state includes at least one of a sensed operator identity, a sensed container present, an optical container characteristic, a container radio frequency tag, a container stack height.

7. The apparatus of claim 6, wherein said means for sensing includes at least one member of the crane sensor means list creating at least one member of a crane sensor state list;

wherein said members of said crane sensor means list, include:

means for sensing a twistlock to create a twistlock sensed state belonging to a twistlock state list;

means for sensing a spreader to create a spreader sensed state belonging to a spreader state list; and

means for sensing a landing to create a sensed landing state belonging to a landing state list.

30

8. The apparatus of claim 7,

wherein said members of said crane sensor state list include said twistlock sensed state, said spreader sensed state, and said sensed landing state;

wherein said twistlock state list includes a twistlock-on state and a twistlock-off state;

wherein said spreader state list includes a ten foot container spread, a twenty foot container spread, a thirty foot container spread, a forty foot container spread, and a forty five feet container spread; and

wherein said landing state list includes a landed state and a not-landed state.

9. The apparatus of claim 7, wherein said means for sensing includes coupling to a crane spreader interface connection to at least partly provide at least one of said members of said crane state list.

10. The apparatus of claim 9, wherein said coupling to said crane spreader interface connection includes a computer coupling to said crane spreader interface connection.

11. The apparatus of claim 7, wherein said means for sensing includes coupling to a Programmable Logic Controller (PLC) to at least partly provide at least one of said members of said crane sensor state list.

12. The apparatus of claim 11, wherein coupling to said PLC includes a serial communications coupling to a computer.

13. The apparatus of claim 1, wherein said means for optically sensing said container code includes at least one video camera to create at least one instance of a view of said container code.

14. The apparatus of claim 13, wherein said video camera create at least one instance of a compression of said view of said container code.

15. The apparatus of claim 1, wherein said means for wirelessly determining location includes at least one of an interface to a Global Positioning System (GPS), an interface to a Differential Global Positioning System (DGPS), and a radio location-tag unit.

16. The apparatus of claim 1, wherein said means for wirelessly communicating includes a radio location-tag unit.

17. The apparatus of claim 1, wherein at least one Field Programmable Gate Array implements at least part of at least one of the list comprising said instruction processor, said inferential engine, said neural network, and said finite state machine.

18. The apparatus of claim 1, wherein said container code characteristic collection includes a container code text, a view of said container code, and a compression of said container code.

* * * * *