



US007707806B2

(12) **United States Patent**  
**Weder**

(10) **Patent No.:** **US 7,707,806 B2**  
(45) **Date of Patent:** **\*May 4, 2010**

(54) **FLORAL EASEL**

(75) Inventor: **Donald E. Weder**, Highland, IL (US)

(73) Assignee: **Wanda M. Weder & William F. Straeter**, Highland, IL (US), not individually but solely as Trustees of The Family Trust U/T/A dated 12/8/1995

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **12/150,258**

(22) Filed: **Apr. 25, 2008**

(65) **Prior Publication Data**  
US 2008/0228674 A1 Sep. 18, 2008

**Related U.S. Application Data**

(60) Continuation of application No. 10/973,861, filed on Oct. 26, 2004, now Pat. No. 7,426,813, which is a division of application No. 10/970,979, filed on Oct. 22, 2004.

(60) Provisional application No. 60/572,149, filed on May 18, 2004.

(51) **Int. Cl.**  
**B65B 1/04** (2006.01)

(52) **U.S. Cl.** ..... **53/473; 53/474; 47/39**

(58) **Field of Classification Search** ..... 53/473, 53/474, 472, 393; 248/464, 465, 465.1, 434, 248/168, 170, 440, 175, 27.8; 47/39; 206/423, 206/756, 764  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

1,359,026 A	11/1920	Briggs
1,417,490 A	5/1922	Brandon
1,421,595 A	7/1922	Smith
1,806,454 A	5/1931	Goudeau
2,035,288 A	3/1936	Aughtry
2,289,729 A	7/1942	Robinson
2,733,881 A	2/1956	Threlfall

(Continued)

**OTHER PUBLICATIONS**

Southern Steel and Wire Company, Inc., Floral Supply Syndicate, Sympathy Design Books, Wire Easels, 2004, p. 143. See also photograph of Wire Easel- Exhibits A-B.



(Continued)

*Primary Examiner*—A. Joseph Wujciak, III  
(74) *Attorney, Agent, or Firm*—Dunlap Codding, P.C.

(57) **ABSTRACT**

The present invention relates to an erectable and/or collapsible floral easel for holding a floral object, and more particularly but not by way of limitation, to an erectable or collapsible floral easel for holding a floral object. In one aspect, the present invention relates to a floral easel for holding and/or supporting a floral object. In yet another aspect, the present invention relates to methods of shipping a floral easel, methods of using a floral easel, methods of storing a floral easel, and methods of placing a floral object on a floral easel.

**20 Claims, 52 Drawing Sheets**



U.S. PATENT DOCUMENTS


2,940,705 A 6/1960 Lotz  
3,148,850 A 9/1964 Johnson  
3,481,075 A 12/1969 Dastoli et al.  
D221,970 S 9/1971 Kelly  
D285,754 S 9/1986 Beaty  
4,695,021 A 9/1987 Leinfelder  
4,941,283 A 7/1990 Armstrong  
D392,141 S 3/1998 Cavanaugh  
D435,177 S 12/2000 Buell et al.  
6,322,026 B1 11/2001 Ju

7,426,813 B2\* 9/2008 Weder ..... 53/473


OTHER PUBLICATIONS

H.O. Norman Company, Floral Supply Syndicate, Sympathy Design Books, Wood Easels, 2004, p. 143. See also photographs of H.O. Norman Company Wood Easel- Exhibits C-H.  
Miller Floral Supply, Wholesale Price List 2004, Wood Easel. See also photograph of Miller Floral Supply Wood Easel- Exhibits I-J.  
Source Unknown, Photographs taken at Ohio State Florist Association, Columbus, Ohio, Jul. 2004, Flexible molded plastic member for accepting three bamboo sticks serving as a trellis- Exhibits K-N.


\* cited by examiner



**Fig. 1A**





**Fig. 1B**




**Fig. 1C**








***Fig. 2B***




**Fig. 3A**







***Fig. 3B***




***Fig. 4A***



***Fig. 4B***




**Fig. 5A**




**Fig. 5B**







**Fig. 6**




**Fig. 7**



**Fig. 8A**




**Fig. 8B**




***Fig. 8C***







**Fig. 8D**




**Fig. 9**



**Fig. 10**




**Fig. 11A**




*Fig. 11C*

*Fig. 11B*






***Fig. 11D***



**Fig. 12A**



**Fig. 12B**






Fig. 12C




**Fig. 12D**






**Fig. 12E**



**Fig. 12F**



**Fig. 12G**





Fig. 12H



**Fig. 12I**




Fig. 13A






Fig. 13B



*Fig. 13C*





**Fig. 13D**




Fig. 13E




Fig. 14A




Fig. 14B




Fig. 14C




Fig. 14D




Fig. 14E




Fig. 15A






Fig. 15B




Fig. 15C




Fig. 15D





Fig. 15E



**Fig. 16A**




Fig. 16B




Fig. 16C




Fig. 16D







Fig. 16E



*Fig. 16F*

1

**FLORAL EASEL****CROSS REFERENCE TO RELATED APPLICATIONS**

The present application is a continuation of U.S. Ser. No. 10/973,861, filed Oct. 26, 2004, now U.S. Pat. 7,426,813, issued Sep. 23, 2008; which is a divisional of U.S. Ser. No. 10/970,979, filed Oct. 22, 2004; which claims benefit under 35 U.S.C. 119(e) of U.S. Provisional Application Ser. No. 60/572,149, filed May 18, 2004; each of the above-referenced patents and patent applications is hereby expressly incorporated by reference herein in its entirety.

**STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT**

Not applicable.

**BACKGROUND OF THE INVENTION****1. Field of the Invention**

The present invention relates to a floral easel for holding a floral object, and more particularly but not by way of limitation, to an erectable or collapsible floral easel for holding a floral object. In one aspect, the present invention relates to a floral easel for holding and/or supporting a floral object. In yet another aspect, the present invention relates to methods of shipping a floral easel, methods of using a floral easel, methods of storing a floral easel, and methods of placing a floral object on a floral easel.

**2. Description of the Related Art**

Easels have previously been used in industries such as, for example, art, photography, music, education, framing and the like to support and display designated items. These non-floral easels are expensive to fabricate and unsuitable for use as a floral easel. In the floral industry, floral easels are usually constructed of wood or non-wood materials, such as, for example, steel. Such floral easels are usually cumbersome and difficult to ship, transport, and store in that they do not have the ability to readily fold into a position that is compact and easily manageable. Typically, for example, at least two legs of current floral easels are in an open, fixed (erected) position making it impossible to fold the floral easel into a compact bundle for transportation. Currently, florists attach floral arrangements to wood or non-wood floral easels by affixing the floral arrangement to the two legs that are in the open, fixed (erect) position and transport the easels with only a third leg being collapsed. After a funeral visitation or service in the funeral home or chapel, the only collapsible leg of the current floral easel is collapsed while the other legs remain in the open and erect position. The easel is then transported to the cemetery where the collapsible leg is again erected, usually with the legs pressed several inches into the soil for anchoring purposes. The display is used again during a grave side service or as a decoration at the grave site after the service. These non-wood floral easels are frequently transported to various ceremonies and discarded after the ceremony. The transportability of current non-wood floral easels is therefore not maximized because of the bulky nature of these easels, and recyclability of current non-wood floral easels is poor due to the bulky nature of current non-wood floral easels.

Further, shipping and/or freight costs currently reflect the cumbersome nature of shipping current non-wood floral easels. For example, depending on the freight zone, freight costs may range from 9.26% to 36.14% of the total manufacturing costs.

2

This is because current non-wood floral easels are produced in a factory and shipped to a designated location with two of the three legs fixed in the erected position with only one of the legs being collapsible. Shipping these types of floral easels is costly due to the large amount of space the current floral easel requires because of its inability to fully collapse into a bundle. A floral easel that is fully or partially collapsible would dramatically decrease shipping costs; for example, fully or partially collapsible non-wood floral easels may reduce freight costs by up to 75% when compared to the freight costs of current non-wood floral easels.

Warehousing space must also be maximized to accommodate storage of such floral easels. For example, when arriving at a distributorship or flower shop, current non-wood floral easels require the manufacturer, distributor or florist to provide an excessive and unnecessary amount of storage space for the easel which is attributed to the inability of the floral easel to fully collapse. Also, the reuse of current non-wood floral easels by florists is poor or even non-existent due to the extreme difficulty of packing and transporting the easels.

Current wood floral easels are typically bulkier than non-wood floral easels and require more space even when the current wood floral easel is in a partially collapsed or fully collapsed position. Furthermore, wood is a scarce natural resource and alternative materials are more readily available for the construction of floral easels. Current wood floral easels are subject to warping upon continued use, especially when storing. These easels must be stored in a careful manner, avoiding exposure to certain conditions and must be disposed in a flat plane because of a tendency to conform to a non-linear plane. Current wood floral easels are also subject to insect infestation which requires irradiation when importing (or otherwise be subject to recall), and subject to splintering making the current wood floral easel difficult to transport in commerce as well as difficult to use and re-use. The wood of current wood floral easels must also be treated to provide the desired surface conditions (i.e., for sanding or painting) making the material prohibitively expensive when compared to other non-wood materials from which the floral easel could be constructed. Current wood floral easels also require assembly as well as articulation among the legs.

It is to this end that there is a need in the industry for a fully or partially erectable or collapsible floral easel that overcomes the disadvantages and defects of current floral easels and that is compact, easily transportable, less expensive to ship and store, and is fully reuseable. It is to such a floral easel that the present invention is directed.

**SUMMARY OF THE INVENTION**

The present invention is directed to a fully or partially erectable or collapsible floral easel for holding a floral object having at least two leg members, each of the leg members having a first end and a second end, the first end of each of the leg members being associated at a joining assembly, wherein the leg members are moveable from an open position to a second position wherein the leg members occupy a lesser volume of space in the second position and further wherein the at least two legs are self-erecting from the second position to the open position and a splay assembly capable of holding the leg members in the open position. The floral easel of the present invention may be self-erecting, self-collapsing, self-erecting and self-collapsing, semi-self-erecting, semi-self-collapsing and/or semi-self-erecting and semi-self-collapsing. Additionally, the present invention relates to methods of shipping an erectable or collapsible floral easel, methods of using an erectable or collapsible floral easel, methods of







## 5

FIG. 15E is a perspective view of another embodiment of the floral easel of the present invention.

FIG. 16A is a perspective view of another embodiment of the floral easel of the present invention.

FIG. 16B is a perspective view of another embodiment of the floral easel of the present invention.

FIG. 16C is a perspective view of another embodiment of the floral easel of the present invention.

FIG. 16D is a perspective view of another embodiment of the floral easel of the present invention.

FIG. 16E is a perspective view of another embodiment of the floral easel of the present invention.

FIG. 16F is a perspective view of another embodiment of the floral easel of the present invention.

## DETAILED DESCRIPTION OF THE INVENTION

It is to be understood that the invention is not limited in its application to the details of construction and the arrangements of the components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments or of being practiced or carried out in various ways which would be plain to one of ordinary skill in the art given the present specification, drawings and claims appended hereto. Also, it is to be understood that the phraseology and terminology employed herein is for purpose of description and should not be regarded as limiting and the claimed invention should be given its broadest possible meaning consistent with the terms and phrasing used in the claims.

## Description of FIG. 1

Referring now to FIGS. 1A and 1B, designated generally by the reference numeral 10 is a floral easel. All of the embodiments of the floral easel 10 described herein may be fully erectable and/or collapsible, semi-erectable and/or semi-collapsible, semi-self-erectable and/or semi-self-collapsible, and combinations thereof. Further, all of the embodiments of the floral easel 10 described herein may be erectable without being collapsible and vice-versa. The term "erectable", "erect", or "open" as used herein means that the floral easel 10 is deployed fully for use as intended, i.e., the display of a floral object. The term "collapsible", "collapsed", or "closed" as used herein means that the floral easel 10 is positioned such that at least one of the plurality of leg members are capable of being in or are in a fully or partially collapsed position. The term "fully erectable" as used herein means that at least one of the plurality of leg members are capable of being in or are positioned in the open position. The term "partially erectable" or "semi-erectable" as used herein means that one of the plurality of leg members of the floral easel is in a fully erected position or any number of the plurality of leg members are in a partially erected position. The floral easel 10 may be fully or partially collapsible. The term "fully collapsible" as used herein means that at least one of the plurality of leg members are capable of being positioned in the fully collapsed position. The term "partially collapsible" or "semi-collapsible" as used herein means that one of the plurality of leg members is in a fully collapsed position or any number of the plurality of leg members are in a partially collapsed position. Also, in one embodiment, the floral easel 10 may be reversibly erectable or irreversibly erectable. It should also be understood that the floral easel 10 may only be capable of erecting yet not collapsing, collapsing yet not erecting, and erecting and collapsing.

The floral easel 10 has a plurality of leg members and, in one embodiment shown in FIGS. 1A-1C, the floral easel 10

## 6

has a first leg member 20, a second leg member 30, and a third leg member 40. The floral easel 10 also includes a splay assembly 12 for sustaining the floral easel 10 in an open or erected position as shown in FIG. 1A.

As shown in FIGS. 1A-1C, the first leg member 20 has a first end 60 and a second end 70. The second leg member 30 has a first end 80 and a second end 90. The third leg member 40 has a first end 100 and a second end 110. The first end 60 of the first leg member 20, the first end 80 of the second leg member 30, and the first end 100 of the third leg member 40 are associated at a joining member 120. The second end 70 of the first leg member 20, the second end 90 of the second leg member 30, and the second end 110 of the third leg member 40 are generally in contact with a substrate 45 to thereby support and hold the floral easel 10 in a position suitable for use as a display for a floral object. The substrate 45 may be any surface such as, for example, a floor, dirt, grass, fiber, plastic, tile, carpet, combinations thereof, or any surface capable of supporting floral easel 10 thereon.

All embodiments of the floral easel 10 described herein could be used with or without anchoring materials known in the art to prevent the floral easel 10 from moving or tipping. Examples of anchoring materials include, but are not limited to, adhesive, cohesive, spikes (metal or plastic), rubber feet or pads, combinations thereof, or any other materials capable of anchoring the floral easel 10 to the substrate 45. The anchoring material may be formed integrally or non-integrally with the floral easel 10 and may be constructed of the same or different material as the floral easel 10.

In all of the embodiments of the floral easel 10 described herein, the leg members may be constructed of any material such as, for example, steel rod (tubular, flat, or profile shaped) and/or wire (coated or uncoated), aluminum rod (tubular, flat, or profile shaped) and/or wire (coated, anodized or uncoated), stainless steel rod (flat or profile shaped) and/or wire (coated or uncoated), plastic pieces of material having cylindrical, tubular, triangular, square, rectangular, polygonal, or other profile shapes or cross-sections of profile shapes, hollow, tubular or profile shaped materials made of metals or polymers, solid or hollow wood, synthetic or man-made materials, natural materials, or any other suitable material. In a preferred embodiment, at least a portion of at least one of the leg members and/or the joining member 120 is constructed of a substantially flexible material, i.e. at least a portion of at least one of the leg members is capable of bending. The leg members may have any size diameter, width, or profile dimensions and/or any length that is desired and useful for the particular use the floral easel 10 is put. In general, however, the floral easel 10 will have a height of from about 1/2" to 300", more preferably a height from about 10" to about 60", and most preferably a height from about 18" to about 36".

At least two of the first leg member 20, the second leg member 30, and the third leg member 40 may be formed as a single piece of material that is integrally connected (shown in FIGS. 1A and 1B as one piece of tubular material forming an arch 130 having a center area 140). Alternatively, the first leg member 20 and the second leg member 30 may be formed of two or more pieces of material. If the first leg member 20 and the second leg member 30 are formed of two or more pieces of material, the materials may differ or the materials may be the same. For example, if the first leg member 20 and the second leg member 30 are formed of two or more pieces of material, one of the leg members may be formed of steel and the other may be formed of aluminum. In another embodiment, each of the plurality of leg members may be formed of at least two or more materials. For example, a portion of at least one of the leg members may be steel and another portion



of the leg member may be aluminum. In yet another embodiment, the first leg member **20**, the second leg member **30**, and the third leg member **30** may be integrally connected. The plurality of leg members may be constructed of the same material or a different material. For example, at least one of the plurality of leg members may be constructed of steel and the other leg members may be constructed of aluminum.

The joining member **120** for connecting and/or receiving the first end of the leg members may be formed of the same material as the leg members or the joining member **120** may be formed of a different material than the leg members. Also, the joining member **120** may be integrally connected to the first end **100** of the third leg member **40** or formed separately from the first end **100** of the third leg member **40**. As shown in FIGS. **1A** and **1B**, the joining member **120** is integrally connected to the first end **100** of the third leg member **40** and is crimped around and pivotally connected to the arch **130** formed in the center area **140** thereby integrally joining the first end **60** of the first leg member **20** and the first end **70** of the second leg member **30** to define an apex **150**. In an alternative embodiment, the joining member **120** need not be integrally connected to the first end **100** of the third leg member **40**, and alternatively, the joining member **120** may be welded, clamped, glued, or any other method of connecting the joining member **120** to the first end of each of the leg members. The joining member **120** may also be, for example, a solid block holding device (as shown in FIGS. **11A-11D**), or any other device capable of receiving the first ends of the leg members. Also, the first end **100** of the third leg **40** need not be crimped around the arch **130**. In an alternative embodiment, the joining member **120** and the arch **130** are connected using materials that permit the floral easel **10** to erect and/or collapse. Also, the first end **100** of the third leg **40** need not be pivotally connected to the arch **130**. In an alternative embodiment, the first end **100** may be flexibly connected to the arch **130**.

The splay assembly **12** for sustaining the floral easel **10** in the open or erected position has a bracing assembly **160** and a reinforcing member **170**. It should be understood that the splay assembly **12** may be formed separately from the legs or the splay assembly **12** may be integrally connected to the legs. Alternatively, the bracing assembly **160** may be formed non-integrally from the legs and the reinforcing member **170** may be formed integrally with the legs or vice-versa. The bracing assembly **160** has a first arm **180** and a second arm **190**. The first arm **180** has a first end **200** and a second end **210**. The second arm **190** has a first end **220** and a second end **230**. The first end **200** of the first arm **180** is connected to the first leg member **20**. The first end **220** of the second arm **190** is connected to the second leg member **30**. The second end **210** of the first arm **180** and the second end **230** of the second arm **190** are connected to the third leg member **40**. In the embodiment shown in FIGS. **1A-1C**, the bracing assembly **160** is constructed of one continuous piece of material. The first end **200** of the first arm **180** forms a loop **232** around the first leg member **20** and is slidably connected to the first leg member **20**, the first end **220** of the second arm **190** forms a loop **234** around the second leg member **30** and is slidably connected to the second leg member **30**, the second end **210** of the first arm **180** and second end **230** of the second arm **190** form a contiguous loop **236** around the third leg member **40** and the loop **236** is slidably and pivotally connected to the third leg member **40**. It will be appreciated, however, that the first arm **180** and the second arm **190** may be connected to the leg members in any manner as long as the leg members are able to fully collapse.

The bracing assembly **160** may be a single piece of material, or more than one piece of material. For example, as shown in FIGS. **1A-1C**, the bracing assembly **160** is a single piece of material wherein the second end **210** of the first arm **180** and the second end **230** of the second arm **190** form a continuous loop around the third leg member **40** wherein the looped area is slidably and pivotally connected to the third leg member **40**. If the bracing assembly **160** is fabricated using sufficiently flexible and springy material, it need not be slidably or pivotally connected to any or all of the plurality of leg members.

The bracing assembly **160** may be constructed of the same material as the leg members or the bracing assembly **160** may be constructed of a different material than the leg members as long as the material allows the bracing assembly **160** to sustain the floral easel **10** in the open or erected position.

If the third leg **40** is not pivotally connected to at least one of the first leg **20** and the second leg **30**, or, if the third leg **40** is pivotally connected to at least one of the first leg **20** and the second leg **30** limiting its travel to positions of full erection, full collapse, or intermediate positions; and, if the first leg **20** and the second leg **30** are connected to limit travel to positions from full erection to full collapse, then at least one of the bracing assembly **160** and reinforcing member **170** can be eliminated from this embodiment of the floral easel **10**.

A stop member **235** may be connected adjacent and underneath the second arm **190** of the bracing assembly **160** to prevent the bracing assembly **160** from sliding down the second leg member **30** of the floral easel **10**. The stop member **235** may be constructed of the same material as the leg member or of a different material than the leg member. In the embodiment shown in FIG. **1A**, the stop member **235** is a horizontal cross-piece connected adjacent and below the second arm **190** of the bracing assembly **160**. However, the stop member **235** may be connected to any of the leg members of the floral easel **10**. It should be understood that the stop member **235** is not required; however, for embodiments in which the bracing assembly **160** is slidably or pivotally connected to at least one leg member, the stop member **235** aids in the erection and enhances the stability of the floral easel **10**.

The reinforcing member **170** has a first end **240** and a second end **250**. The first end **240** is connected to the first leg member **20** and the second end **250** is connected to the second leg member **30**. In the embodiment shown in FIG. **1**, the first end **240** forms a loop **252** around the first leg member **20** and is slidably connected to the first leg member **20** and the second end **250** forms a loop **254** around the second leg member **30** and is slidably connected to the second leg member **30**. It will be appreciated, however, that the first end **240** and the second end **250** may be connected in any manner to the first leg member **20** and second leg member **30** of the floral easel **10**.

For example, but not by way of limitation, the reinforcing member **170** may be selected from the group consisting of elastic, a rope, a cord, a chain, a strap, a cable, a wire, springs, tubing, plastic, profiles, wood, polymer/fiber, adhesive, cohesive, velcro, combinations thereof or any other device which allows the floral easel **10** to be sustained in the open or erected position. The reinforcing member **170** may also be constructed of the same material as the leg members or the reinforcing member **170** may be constructed of a different material than the leg members as long as the material allows the reinforcing member **170** to sustain the floral easel **10** in the open or erected position. It will be appreciated, however, that the reinforcing member **170** is not necessary in alternate embodiments where a more flexible floral easel **10** is desirable or acceptable for use.



A stop member **255** may also be connected to the first leg member **20** of the floral easel **10** and placed adjacent and underneath the first end **240** of the reinforcing member **170** for preventing the reinforcing member **170** from sliding down the first leg member **20** of the floral easel **10**. However, it should be understood that the stop member **235** may be placed on either the first leg member **20** or the second leg member **30** of the floral easel **10**. The stop member **255** may be constructed of the same material as the designated leg member or of a different material than the designated leg member. In the embodiment shown in FIG. 1A, the stop member **255** is a horizontal cross-piece connected adjacent and below the first end **240** of the reinforcing member **170**. However, the stop member **255** may be connected to either the first leg member **20**, the second leg member **30**, the third leg member **40** or any of the first leg member **20**, the second leg member **30**, and the third leg member **40** of the floral easel **10**. It should be understood that multiple stop members may be used on the floral easel. It should also be understood that the stop members are not necessary to the erection, collapsibility, or stability of the floral easel **10**; however, the stop members may enhance stability and facilitate erection of the floral easel **10**. The reinforcing member **170** may also provide at least one location on the floral easel **10** to which floral objects and decorations may be fastened using wire clips, glue or any other fastening means capable of securing floral objects and decorations to the floral easel **10**.

In all of the embodiments of the floral easel described herein, the floral easel **10** may be employed to hold and/or support a floral object **260** (FIG. 1C) by placing the floral object **260** about the apex **150** of the floral easel **10**. The term “floral object” as used herein will be understood to include any floral object which can be placed on a floral easel such as, but not limited to, a floral grouping, a floral decoration, a wreath, hanging potted plants, foam shapes (for example, a cross, words (i.e., mom), a flag), non-floral objects such as, for example, a photograph, a piece of artwork, a flag or any other object that is capable of being displayed on a floral easel.

The term “floral grouping” as used herein refers to a single flower, foliage, a botanical item, a propagule, cut flowers, and/or other fresh and/or artificial plants or floral materials, including secondary plants, growing potted plants having a root portion and/or other ornamentation which adds to the aesthetic qualities of the overall floral grouping. The term “floral grouping” as used herein may also refer to a “floral grouping”, as defined above, which is disposed within a pot or a flower pot.

A support member **270** (FIGS. 1A and 1B) may also be employed to hold and/or support the floral object **260** (or non-floral object), however, any portion of the floral easel **10** may hold or support the floral object **260** or non-floral object, such as, for example, the joining member **120**, the bracing assembly **160**, the reinforcing member **170** or any other area of the floral easel **10** capable of supporting the floral object **260** or a non-floral object. The support member **270** may be connected to any area of the floral easel **10** such as, for example, the joining member **120**, the leg members, or to the reinforcing member **170**. The support member **270** may be any kind of device capable of supporting the floral object **260**. For example, but not by way of limitation, the support member **270** may be selected from the group consisting of a hook, a platform, a magnet, wire, adhesive, cohesive, velcro, a slot, a loop, a tab, a groove, a spring, elastic, a band, ribbon, a clip, combinations thereof, or any other device that is capable of

holding and/or supporting the floral object **260**. The support member **270**, as shown in FIG. 1, is a hook connected to the joining member **120**.

The support member **270** may be constructed of the same material as the leg members or the support member **270** may be constructed of a different material than the leg members as long as the material is capable of holding and/or supporting the floral object **260**.

All of the embodiments of the floral easel **10** described herein may also have a retaining member **280** for retaining the leg members in the collapsed position. For example, but not by way of limitation, the retaining member **280** may be selected from the group consisting of elastic, a clip or clips, a spring, a band, shrink material, stretch material, the joining member **120**, a carton, a tube, a bend in the leg members, a groove, a slot, a loop, a hook, a wire, a bow, a rope, a magnet, a cord, a chain, a strap, a cable, adhesive, combinations thereof, or any other device capable of retaining the leg members in the collapsed position. The retaining member **280** may also be constructed of the same material as the leg members or the retaining member **280** may be constructed of a different material than the leg members as long as the material is capable of retaining the leg members in the collapsed position. Alternatively, the retaining member **280** may be eliminated from the floral easel **10** and the plurality of leg members may be retained in the collapsed position by the joining member **120**.

As shown in FIG. 1, the retaining member **280** is connected to the first leg member **20**; however, for example, the retaining member **280** may be attached to any of the leg members, the bracing assembly **160**, the reinforcing member **170**, or to any other area of the floral easel **10** that is suitable for connecting the retaining member **280** or may be a separate device unconnected to the floral easel **10**.

To move the floral easel **10** from the open or erected position (shown in FIG. 1A) to the collapsed position (shown in FIG. 1B), the bracing assembly **160** is rotated about the loop **232** and the loop **234** to cause the loop **236** to slide in an upward direction toward the first end **100** of the third leg member **40** thereby pivoting the third leg member **40** inward toward the area between the first leg member **20** and the second leg member **30**. The reinforcing member **170** is also moved in an upward direction to cause the loop **254** of the second end **250** of the reinforcing member **170** to slide in an upward manner along the first end **100** of the second leg member **30**. The first end **60** of the first leg member **20** and the first end **80** of the second leg member **30** are compressed together thereby decreasing the angle formed at the arch **130** between the center area **140** of the first leg member **20** and the second leg member **30**. The second end **70**, the second end **90**, and the second end **110** may then be inserted into the retaining member **280** forming the leg members into a bundle **290** (shown in FIG. 1B).

While methods of collapsing and methods of erecting the floral easel have been described herein, it is to be understood that other methods of collapsing the easels of the present invention will be evident to a person having ordinary skill in the art and therefore, such additional methods of collapsing and methods of erecting the floral easel are also within the scope of the present invention.

It is also to be understood that the present invention also encompasses any embodiments described herein or modifications thereof with the skill of a person in the art. For example, any of the embodiments of the floral easel described herein may be self-erecting, self-collapsing, self-erecting and self-collapsing, semi-self-erecting, semi-self-collapsing, or semi-self-erecting and semi-self-collapsing. Also, any of the



## 11

embodiments of the present invention described herein may be made so that no more than one assembly must be accomplished to maintain the easel in the erect position, semi-erect position, collapsed position, or semi-collapsed position.

## Description of FIG. 2

Referring now to FIGS. 2A and 2B, designated generally by the reference numeral **10b** is a floral easel.

The floral easel **10b** has a plurality of leg members and, in one embodiment shown in FIG. 2, the floral easel **10b** has a first leg member **20b**, a second leg member **30b** and a third leg member **40b**. The floral easel **10b** also includes a splay assembly **12b** that is capable of sustaining the floral easel **10b** in an open or erected position as shown in FIG. 2A.

As shown in FIGS. 2A and 2B, the first leg member **20b** has a first end **60b** and a second end **70b**, the second leg member **30b** has a first end **80b** and a second end **90b**, and the third leg member **40b** has a first end **100b** and a second end **110b**. The second end **70b** of the first leg member **20b**, the second end **90b** of the second leg member **30b**, and the second end **110b** of the third leg member **40b** are generally in contact with a substrate **45b** to thereby support and hold the floral easel **10b** in a position suitable for use as a display for a floral object. The substrate **45b** may be any surface such as, for example, a floor, dirt, grass, fiber, plastic, or any surface capable of supporting the floral easel **10b** thereon.

At least two of the first leg member **20b**, the second leg member **30b**, and the third leg member **40b** may be formed as a single piece of material that is integrally connected (shown in FIGS. 2A and 2B as one piece of tubular material) thereby forming a loop **112b** around a portion of the third leg member **40b**. Alternatively, the first leg member **20b** and the second leg member **30b** may be formed of two or more pieces of material. If the first leg member **20b** and the second leg member **30b** are formed of two or more pieces of material, the materials may differ or the materials may be the same. For example, if the first leg member **20b** and the second leg member **30b** are formed of two or more pieces of material, one of the leg members may be formed of steel and the other may be formed of aluminum. In another embodiment, each of the plurality of leg members may be formed of at least two or more materials. For example, a portion of at least one of the leg members may be steel and another portion of the leg member may be aluminum. In yet another embodiment, the first leg member **20b**, the second leg member **30b**, and the third leg member **30b** may be integrally connected. The plurality of leg members may be constructed of the same material or a different material. For example, at least one of the plurality of leg members may be constructed of steel and the other leg members may be constructed of aluminum.

The first end **100b** of the third leg member **40b** has an extended portion **114b** extending a distance beyond a juncture **116b** of the first end **60b** of the first leg member **20b** and the first end **80b** of the second leg member **30b**.

The splay assembly **12b** for sustaining the floral easel **10b** in the open or erected position has a bracing assembly **160b** and a reinforcing member **170b**. It should be understood that the splay assembly **12b** may be formed separately from the legs or the splay assembly **12b** may be integrally connected to the legs. Alternatively, the bracing assembly **160b** may be formed non-integrally from the legs and the reinforcing member **170b** may be formed integrally with the legs or vice-versa. The bracing assembly **160b** has a first arm **180b** and a second arm **190b**. The first arm **180b** has a first end **200b** and a second end **210b**. The second arm **190b** has a first end **220b** and a second end **230b**. The first end **200b** of the first arm **180b** is

## 12

connected to the first leg member **20b**. The first end **220b** of the second arm **190b** is connected to the second leg member **30b**. The second end **210b** of the first arm **180b** and the second end **230b** of the second arm **190b** are connected to the third leg member **40b**. In the embodiment shown in FIGS. 2A and 2B, the bracing assembly **160b** is constructed of one continuous piece of material. The first end **200b** of the first arm **180b** forms a loop **232b** around the first leg member **20b** and is slidably connected to the first leg member **20b**, the first end **220b** of the second arm **190b** forms a loop **234b** around the second leg member **30b** and is slidably connected to the second leg member **30b**, the second end **210b** of the first arm **180b** and second end **230b** of the second arm **190b** form a contiguous loop **236b** around the third leg member **40b** and the loop **236b** is slidably and pivotally connected to the third leg member **40b**. It will be appreciated, however, that the first arm **180b** and the second arm **190b** may be connected to the leg members in any manner as long as the leg members are able to collapse.

The bracing assembly **160b** may be a single piece of material or more than one piece of material. For example, as shown in FIGS. 2A and 2B, the bracing assembly **160b** is a single piece of material wherein the second end **210b** of the first arm **180b** and second end **230b** of the second arm **190b** form a continuous loop around the third leg member **40b** wherein the looped area is slidably and pivotally connected to the third leg member **40b**.

The bracing assembly **160b** may be constructed of the same material as the leg members or the bracing assembly **160b** may be constructed of a different material than the leg members as long as the material allows the bracing assembly **160b** to sustain the floral easel **10b** in the open or erected position.

If the third leg **40b** is not pivotally connected to at least one of the first leg **20b** and the second leg **30b**, or, if the third leg **40b** is pivotally connected to at least one of the first leg **20b** and the second leg **30b** limiting its travel to positions of full erection, full collapse, or intermediate positions, and if the first leg **20b** and the second leg **30b** are connected to limit travel to positions from full erection to full collapse; then at least one of the bracing assembly **160b** and reinforcing member **170b** can be eliminated from this embodiment of the floral easel **10b**.

A stop member **235b** is connected adjacent and underneath the second arm **190b** of the bracing assembly **160b** to prevent the bracing assembly **160b** from sliding down the second leg member **30b** of the floral easel **10b**. The stop member **235b** may be constructed of the same material as the leg members or of a different material than the leg members. In the embodiment shown in FIG. 2A, the stop member **235b** is a horizontal cross-piece connected adjacent and below the second arm **190b** of the bracing assembly **160b**. However, the stop member **235b** may be connected to any of the leg members of the floral easel **10b**. It should be understood that the stop member **235b** is not required, however, for embodiments in which the bracing assembly **160b** is slidably or pivotally connected to at least one leg member, the stop member **235b** aids in the erection and enhances the stability of the floral easel **10b**.

The reinforcing member **170b** has a first end **240b** and a second end **250b**. The first end **240b** is connected to the first leg member **20b** and the second end **250b** is connected to the second leg member **30b**. In the embodiment shown in FIG. 2, the first end **240b** forms a loop **252b** around the first leg member **20b** and is slidably connected to the first leg member **20b** and the second end **250b** forms a loop **254b** around the second leg member **30b** and is slidably connected to the second leg member **30b**. It will be appreciated, however, that



the first end **240b** and the second end **250b** may be connected in any manner to the first leg member **20b** and second leg member **30b** of the floral easel **10b**.

For example, but not by way of limitation, the reinforcing member **170b** may be selected from the group consisting of elastic, a rope, a cord, a chain, a strap, a cable, a wire, combinations thereof or any other device which allows the floral easel **10b** to be sustained in the open or erect position. The reinforcing member **170b** may also be constructed of the same material as the leg members or the reinforcing member **170b** may be constructed from a different material than the leg members as long as the material allows the reinforcing member **170b** to sustain the floral easel **10b** in the open or erect position. It will be appreciated, however, that the reinforcing member **170b** is not necessary in alternate embodiments where a more flexible floral easel **10b** is desirable or acceptable for use.

A stop member **255b** may also be connected to the first leg member **20b** of the floral easel **10b** and placed adjacent and underneath the first end **240b** of the reinforcing member **170b** for preventing the reinforcing member **170b** from sliding down the first leg member **20b** of the floral easel **10b**. However, it should be understood that the stop member **255b** may be placed on either the first leg member **20b** or the second leg member **30b** of the floral easel **10b**. The stop member **255b** may be constructed of the same material as the designated leg member or of a different material than the designated leg member. In the embodiment shown in FIG. 2A, the stop member **255b** is a horizontal cross-piece connected adjacent and below the first end **240b** of the reinforcing member **170b**. However, the stop member **255b** may be connected to either the first leg member **20b**, the second leg member **30b**, the third leg member **40b** or any of the first leg member **20b**, the second leg member **30b**, and the third leg member **40b** of the floral easel **10b**. It should be understood that multiple stop members may be used on the floral easel. It should also be understood that the stop members are not necessary to the erection, collapsibility, or stability of the floral easel **10b**; however, the stop members may enhance stability and facilitate erection of the floral easel **10b**. The reinforcing member **170b** may also provide at least one location on the floral easel **10b** to which floral objects and decorations may be fastened using wire clips, glue or any other fastening means capable of securing floral objections and decorations to the floral easel **10b**.

A support member **270b** (FIGS. 2A and 2B) may also be employed to hold and/or support the floral object (not shown) (or non-floral object), however, any portion of the floral easel **10b** may hold or support the floral object **260b** or non-floral object, such as, for example, the bracing assembly **160b**, the reinforcing member **170b** or any other area of the floral easel **10b** capable of supporting the floral object **260b** or a non-floral object. The support member **270b** may be connected to any area of the floral easel **10b** such as, for example, the leg members, or to the reinforcing member **170b**. The support member **270b** may be any kind of device capable of supporting the floral object **260b**. For example, but not by way of limitation, the support member **270b** may be selected from the group consisting of a hook, a platform, a magnet, wire, adhesive, cohesive, velcro, a slot, a loop, a tab, a groove, a spring, elastic, a band, ribbon, a clip, combinations thereof, or any other device that is capable of holding and/or supporting the floral object. The support member **270b**, as shown in FIG. 2, is a hook connected to the first end **100b** of the third leg member **40b**.

The support member **270b** may be constructed of the same material as the leg members or the support member **270b** may

be constructed of a different material than the leg members as long as the material is capable of holding and/or supporting the floral object.

The floral easel **10b** may also have a retaining member **280b** for retaining the leg members in the collapsed position. For example, but not by way of limitation, the retaining member **280b** may be selected from the group consisting of a hook, a loop, a wire, a bow, a rope, a magnet, a cord, a chain, a strap, a cable, adhesive, combinations thereof, or any other device capable of retaining the leg members in the collapsed position. The retaining member **280b** may also be constructed of the same material as the leg members or the retaining member **280b** may be constructed from a different material than the leg members as long as the material is capable of retaining the leg members in the collapsed position. For example, but not by way of limitation, the retaining member **280b** may be selected from the group consisting of elastic, a clip or clips, a spring, a band, shrink material, stretch material, a carton, a tube, a bend in the leg members, a groove, a slot, a loop, a hook, a wire, a bow, a rope, a magnet, a cord, a chain, a strap, a cable, adhesive, combinations thereof, or any other device capable of retaining the leg members in the collapsed position. The retaining member **280b** may also be constructed of the same material as the leg members or the retaining member **280b** may be constructed of a different material than the leg members as long as the material is capable of retaining the leg members in the collapsed position.

As shown in FIG. 2, the retaining member **280b** is connected to the first leg member **20b**, however, for example, the retaining member **280b** may be attached to any of the leg members, the bracing assembly **160b**, the reinforcing member **170b**, or to any other area of the floral easel **10b** that is suitable for connecting the retaining member **280b** or may be a separate device unconnected to the floral easel **10b**.

To move the floral easel **10b** from the open or erect position (shown in FIG. 2A) to the collapsed position (shown in FIG. 2B), the bracing assembly **160b** is rotated about the loop **232b** and the loop **234b** to cause the loop **236b** to slide in an upward direction through the loop **112b** toward the first end **100b** of the third leg member **40b** thereby pivoting the third leg member **40b** inward toward the area between the first leg member **20b** and the second leg member **30b**. The reinforcing member **170b** is also moved in an upward direction to cause the loop **254b** of the second end **250b** of the reinforcing member **170b** to slide in an upward manner along the first end **100b** of the second leg member **30b**. The second end **70b**, the second end **90b**, and the second end **110b** may then be inserted into the retaining member **280b** forming the leg members into a bundle **290b** (shown in FIG. 2B).

#### Description of FIG. 3

Referring now to FIGS. 3A and 3B, designated generally by the reference numeral **10c** is a floral easel. The floral easel **10c** has a plurality of leg members and, in one embodiment shown in FIG. 3, the floral easel **10c** has a first leg member **20c**, a second leg member **30c**, and a third leg member **40c**. The floral easel **10c** also includes a bracing assembly **50c** for sustaining the floral easel **10c** in an open or erected position shown in FIG. 3A.

As shown in FIGS. 3A and 3B, the first leg member **20c** has a first end **60c**, a second end **70c**, a first side **72c** and a second side **74c**. The second leg member **30c** has a first end **80c**, a second end **90c**, a first side **92c** and a second side **94c**. The third leg member **40c** has a first end **100c** and a second end **110c**. The first end **60c** of the first leg member **20c**, the first end **80c** of the second leg member **30c**, and the first end **100c**



of the third leg member **40c** may be integrally connected at a joining member **120c**. The second side **74c** of the first leg member **20c**, the second side **94c** of the second leg member **30c**, and the joining member **120c** are generally in contact with a substrate **45c** to thereby support and hold the floral easel **10c**. The substrate **45c** may be any surface such as, for example, a floor, dirt, grass, fiber, plastic, or any surface capable of supporting the floral easel **10c** thereon. The third leg member **40c** extends a distance **125c** perpendicular to the first leg member **20c** and the second leg member **30c**.

At least two of the first leg member **20c**, the second leg member **30c**, and the third leg member **40c** may be formed as a single piece of material that is integrally connected (shown in FIGS. 3A and 3B as one piece of tubular material forming an arch **130c** having a center area **140c**). Alternatively, the first leg member **20c** and the second leg member **30c** may be formed of two or more pieces of material. If the first leg member **20c** and the second leg member **30c** are formed of two or more pieces of material, the materials may differ or the materials may be the same. For example, if the first leg member **20c** and the second leg member **30c** are formed of two or more pieces of material, one of the leg members may be formed of steel and the other may be formed of aluminum. In another embodiment, each of the plurality of leg members may be formed of at least two or more materials. For example, a portion of at least one of the leg members may be steel and another portion of the leg member may be aluminum. In yet another embodiment, the first leg member **20c** and the second leg member **30c** may be integrally connected. The plurality of leg members may be constructed of the same materials or a different material. For example, at least one of the plurality of leg members may be constructed of steel and the other leg members may be constructed of aluminum.

The joining member **120c** for connecting and/or receiving the first end of the leg members may be formed of the same material as the leg members or the joining member **120c** may be formed of a different material than the leg members. Also, the joining member **120c** may be integrally connected to the first end **100c** of the third leg member **40c** or formed separately from the first end **100c** of the third leg member **40c**. As shown in FIGS. 3A and 3B, the joining member **120c** is integrally connected to the first end **100c** of the third leg member **40c** and is looped around and pivotally connected to the arch **130c** formed in the center area **140c** thereby integrally joining the first end **60c** of the first leg member **20c** and the first end **70c** of the second leg member **30c** to define a juncture **150c**. However, the joining member **120c** may be for example, a solid block holding device, or any other device capable of receiving the first ends of the leg members.

The bracing assembly **50c** has a first arm **180c** and a second arm **190c**. The first arm **180c** has a first end **200c** and a second end **210c**. The second arm **190c** has a first end **220c** and a second end **230c**. The first end **200c** of the first arm **180c** is connected to the first leg member **20c**. The first end **220c** of the second arm **190c** is connected to the second leg member **30c**. The second end **210c** of the first arm **180c** and the second end **230c** of the second arm **190c** are connected to the third leg member **40c**. In the embodiment shown in FIGS. 3A and 3B, the bracing assembly **50c** is constructed of one continuous piece of material. The first end **200c** of the first arm **180c** forms a loop **232c** around the first leg member **20c** and is slidably connected to the first leg member **20c**, the first end **220c** of the second arm **190c** forms a loop **234c** around the second leg member **30c** and is slidably connected to the second leg member **30c**, the second end **210c** of the first arm **180c** and second end **230c** of the second arm **190c** form a contiguous loop **236c** around the third leg member **40c** and

the loop **236c** is slidably and pivotally connected to the third leg member **40c**. It will be appreciated, however, that the first arm **180c** and the second arm **190c** may be connected to the leg members in any manner as long as the leg members are able to fully collapse.

The bracing assembly **50c** may be a single piece of material or more than one piece of material. For example, as shown in FIGS. 3A and 3B, the bracing assembly **50c** is a single piece of material wherein the second end **210c** of the first arm **180c** and the second end **230c** of the second arm **190c** form a continuous loop around the third leg member **40c** wherein the looped area is slidably and pivotally connected to the third leg member **40c**.

The bracing assembly **50c** may be constructed of the same material as the leg members or the bracing assembly **50c** may be constructed of a different material than the leg members as long as the material allows the bracing assembly **50c** to sustain the floral easel **10c** in the open or erected position.

If the third leg member **40c** is not pivotally connected to at least one of the first leg member **20c** and the second leg member **30c** or, if the third leg member **40c** is pivotally connected to at least one of the first leg member **20c** and the second leg member **30c** limiting its travel to positions of full erection, full collapse, or intermediate positions and, if the first leg **20c** and the second leg **20c** are connected to limit travel to positions from full erection to full collapse; then the bracing assembly **50c** can be eliminated from this embodiment of the floral easel **10c**.

A stop member **235c** may be connected adjacent and underneath the second arm **190c** of the bracing assembly **50c** to prevent the bracing assembly **160c** from sliding down the second leg member **30c** of the floral easel **10c**. The stop member **235c** may be constructed of the same material as the leg member or of a different material than the leg member. In the embodiment shown in FIG. 3A, the stop member **235c** is a horizontal cross-piece connected adjacent and below the second arm **190c** of the bracing assembly **50c**. However, the stop member **235c** may be connected to any of the leg members of the floral easel **10c**. It should be understood that the stop member **235c** is not required, however, for embodiments in which the bracing assembly **50c** is slidably or pivotally connected to at least one leg member, the stop member **235c** aids in the erection and enhances the stability of the floral easel **10c**.

The floral easel **10c** may be employed to hold and/or support a floral object (not shown) by placing the floral object about the second end **10c** of the third leg member **40c** of the floral easel **10c**.

A support member **270c** (FIGS. 3A and 3B) may also be employed to hold and/or support the floral object or non-floral object. The support member **270c** may be connected to any area of the floral easel **10c** such as, for example, the bracing assembly **50c**, the first leg member **20c**, the second leg member **30c**, the third leg member **40c**, or any other area capable of having the support member **270c** attached thereto. The support member **270c** may be any kind of device capable of supporting the floral object or non-floral object. For example, but not by way of limitation, the support member **270c** may be selected from the group consisting of a hook, a platform, a magnet, wire, adhesive, cohesive, velcro, a slot, a loop, a tab, a groove, a spring, elastic, a band, ribbon, a clip, combinations thereof, or any other device that is capable of holding and/or supporting the floral object. The support member **270c**, as shown in FIG. 3, is a hook connected to the second end **10c** of the third leg member **40c**.

The support member **270c** may be constructed of the same material as the leg members or the support member **270c** may



be constructed of a different material than the leg members as long as the material is capable of holding and/or supporting the floral object.

The floral easel **10c** may also have a retaining member **280c** for retaining the leg members in the collapsed position. For example, but not by way of limitation, the retaining member **280c** may be selected of the group consisting of elastic, a clip or clips, a spring, a band, shrink material, stretch material, a carton, a tube, a bend in the leg members, a groove, a slot, a hook, a loop, a wire, a bow, a rope, a magnet, a cord, a chain, a strap, a cable, adhesive, combinations thereof, or any other device capable of retaining the leg members in the collapsed position. The retaining member **280c** may also be constructed of the same material as the leg members or the retaining member **280c** may be constructed of a different material than the leg members as long as the material is capable of retaining the leg members in the collapsed position.

As shown in FIG. 3, the retaining member **280c** is connected to the third leg member **30c**, however, for example, the retaining member **280c** may be attached to any of the leg members, the bracing assembly **160c**, or to any other area of the floral easel **10c** that is suitable for connecting the retaining member **280c** or may be a separate device unconnected to the floral easel **10c**.

To move the floral easel **10c** from the open or erected position (shown in FIG. 3A) to the collapsed position (shown in FIG. 3B), the bracing assembly **160c** is rotated about the loop **232c** and the loop **234c** to cause the loop **236c** to slide in an upward direction toward the second end **110c** of the third leg member **40c** thereby pivoting the third leg member **40c** inward toward the area between the first leg member **20c** and the second leg member **30c**. The first end **60c** of the first leg member **20c** and the first end **80c** of the second leg member **30c** are compressed together thereby decreasing the angle formed at the arch **130c** between the center area **140c** of the first leg member **20c** and the second leg member **30c**. The first leg member **20c** and the second leg member **30c** may then be placed within the retaining member **280c** forming the floral easel **10c** into a bundle **290c** (shown in FIG. 3B).

#### Description of FIG. 4

Referring now to FIGS. 4A and 4B, designated generally by the reference numeral **10d** is a floral easel. The floral easel **10d** has a plurality of leg members and, in one embodiment shown in FIG. 4, the floral easel **10d** has a first leg member **20d**, a second leg member **30d**, and a third leg member **40d**.

As shown in FIGS. 4A and 4B, the first leg member **20d** has a first end **60d**, a second end **70d**, a first side **72d** and a second side **74d**. The second leg member **30d** has a first end **80d**, a second end **90d**, a first side **92d** and a second side **94d**. The third leg member **40d** has a first end **100d** and a second end **110d**. The first end **60d** of the first leg member **20d**, the first end **80d** of the second leg member **30d**, and the first end **100d** of the third leg member **40d** may be integrally connected as shown in FIGS. 4A and 4B. The second side **74d** of the first leg member **20d** and the second side **94d** of the second leg member **30d** are generally in contact with a substrate **45d** to thereby support and hold the floral easel **10d**. The substrate **45d** may be any surface such as, for example, a floor, dirt, grass, fiber, plastic, tile, carpet or any surface capable of supporting the floral easel **10d** thereon. The third leg member **40d** extends a distance perpendicular to the first leg member **20d** and the second leg member **30d**.

The anchoring material may be formed integrally or non-integrally with the floral easel **10d**. For example, pins (not

shown) may be added to the first leg member **20d** and the second leg member **30d** so as to penetrate the soil. The pins may be retractable or fixed.

At least two of the first leg member **20d**, the second leg member **30d**, and the third leg member **40d** may be formed as a single piece of material that is integrally connected (shown in FIGS. 4A and 4B as one piece of springy, tubular material) forming a juncture **130d**. Alternatively, the first leg member **20d**, the second leg member **30d**, and the third leg member **40d** may each be formed of different materials. For example, if the first leg member **20d**, the second leg member **30d**, and the third leg member **40d** are formed of different materials, one of the leg members may be formed of steel and the others may be formed of aluminum. In another embodiment, each of the plurality of leg members may be formed of at least two or more materials. For example, at least a portion of at least one of the leg members may be steel and another portion of the leg member may be aluminum. In yet another embodiment, the first leg member **20d**, the second leg member **30d**, and the third leg member **40d** may be integrally connected. The plurality of leg members may be constructed of the same material or a different material. For example, at least one of the plurality of leg members may be constructed of steel and the other leg members may be constructed of aluminum.

A brace **135d** may be placed between the first leg member **20d** and the second leg member **30d** so as to support the leg members in the open position.

The floral easel **10d** may be employed to hold and/or support a floral object (not shown) by placing the floral object about the second end **110d** of the third leg member **40d** of the floral easel **10d**.

A support member **270d** (FIGS. 4A and 4B) may also be employed to hold and/or support the floral object or non-floral object, however, any portion of the floral easel **10d** may hold or support the floral object or non-floral object. The support member **270d** may be connected to any area of the floral easel **10d** such as, for example, the first leg member **20d**, the second leg member **30d**, the third leg member **40d**, or any other area capable of having the support member **270d** attached thereto. The support member **270d** may be any kind of device capable of supporting the floral object. For example, but not by way of limitation, the support member **270d** may be selected from the group consisting of a hook, a platform, a magnet, wire, adhesive, cohesive, velcro, a slot, a loop, a tab, a groove, a spring, elastic, a band, ribbon, a clip, combinations thereof, or any other device that is capable of holding and/or supporting the floral object. The support member **270d**, as shown in FIG. 4, is a hook connected to the second end **110d** of the third leg member **40d**.

The support member **270d** may be constructed of the same material as the leg members or the support member **270d** may be constructed of a different material than the leg members as long as the material is capable of holding and/or supporting the floral object.

The floral easel **10d** may also have a retaining member **280d** for retaining the leg members in the collapsed position. For example, but not by way of limitation, the retaining member **280d** may be selected of the group consisting of elastic, a clip or clips, a spring, a band, shrink material, stretch material, a carton, a tube, a bend in the leg members, a groove, a slot, a hook, a loop, a wire, a bow, a rope, a magnet, a cord, a chain, a strap, a cable, adhesive, combinations thereof, or any other device capable of retaining the leg members in the collapsed position. The retaining member **280d** may also be constructed of the same material as the leg members or the retaining member **280d** may be constructed of a different



material than the leg members as long as the material is capable of retaining the leg members in the collapsed position.

As shown in FIG. 4, the retaining member **280d** is connected to the third leg member **30d**, however, for example, the retaining member **280d** may be attached to any of the leg members or to any other area of the floral easel **10d** that is suitable for connecting the retaining member **280d** or may be a separate device unconnected to the floral easel **10d**.

Further, a display support device (not shown) may be placed on the third leg member **40d** for supporting a floral object. For example, the display support device **290d** may be a bar attached perpendicularly to the third leg member **40d** so as to support a floral object. However, any display support device **290d** may be used so long as it is able to support a floral object.

To move the floral easel **10d** from the open or erected position (shown in FIG. 4A) to the collapsed position (shown in FIG. 4B), the first leg member **20d** and the second leg member **30d** are compressed together thereby decreasing the angle formed at the arch **130d** between the first leg member **20d** and the second leg member **30d**. The first leg member **20d** and the second leg member **30d** are pivoted upwardly toward the third leg member **40d**. The first leg member **20d** and the second leg member **30d** may then be placed within the retaining member **280d** forming the floral easel **10d** into a bundle **290d** (shown in FIG. 4B).

#### Description of FIG. 5

Referring now to FIGS. 5A and 5B, designated generally by the reference numeral **10e** is a floral easel. The floral easel **10e** has a plurality of leg members and, in one embodiment shown in FIG. 5, the floral easel **10e** has a first leg member **20e**, a second leg member **30e** and a third leg member **40e**. The floral easel **10e** also includes a bracing assembly **50e** for sustaining the floral easel **10e** in an open or erected position, shown in FIG. 5A.

As shown in FIGS. 5A and 5B, the first leg member **20e** has a first end **60e** and a second end **70e**, the second leg member **30e** has a first end **80e** and a second end **90e**, and the third leg member **40e** has a first end **100e** and a second end **110e**. The second end **70e** of the first leg member **20e**, the second end **90e** of the second leg member **30e**, and the second end **110e** of the third leg member **40e** are generally in contact with a substrate **45e** to thereby support and hold the floral easel **10e**. The substrate **45e** may be any surface such as, for example, a floor, dirt, grass, fiber, plastic, or any surface capable of supporting the floral easel **10e** thereon. As shown in FIG. 5A, a curve **11e** may be formed in the first leg member **20e** between the first end **60e** and the second end **70e** for allowing the second end **70e** to engage the substrate **45e**. A curve **112e** is formed in the second leg member **30e** between the first end **80e** and the second end **90e** for allowing the second end **90e** to engage the substrate **45e**.

At least two of the first leg member **20e**, the second leg member **30e**, and the third leg member **40e** may be formed as a single piece of material that is integrally connected (shown in FIGS. 5A and 5B as one piece of tubular material) thereby allowing the first end **60e** and the first end **80e** to form a loop **113e** around a portion of the third leg member **40e**. Alternatively, the first leg member **20e** and the second leg member **30e** may be formed of two or more pieces of material. If the first leg member **20e** and the second leg member **30e** are formed of two or more pieces of material, the materials may differ or the materials may be the same. For example, if the first leg member **20e** and the second leg member **30e** are

formed of two or more pieces of material, one of the leg members may be formed of steel and the other may be formed of aluminum. In another embodiment, each of the plurality of leg members may be formed of at least two or more materials.

For example, a portion of at least one of the leg members may be steel and another portion of the leg member may be aluminum. In yet another embodiment, the first leg member **20e**, the second leg member **30e**, and the third leg member **40e** may be integrally connected. The plurality of leg members may be constructed of the same material or a different material. For example, at least one of the plurality of leg members may be constructed of steel and the other leg members may be constructed of aluminum.

The first end **100e** of the third leg member **40e** has an extended portion **114e** extending a distance beyond a juncture **116e** of the plurality of leg members.

The bracing assembly **50e** for sustaining the floral easel **10e** in the open or erected position has a first arm **180e** and a second arm **190e**. The first arm **180e** has a first end **200e** and a second end **210e**. The second arm **190e** has a first end **220e** and a second end **230e**. The first end **200e** of the first arm **180e** is connected to the first leg member **20e**. The first end **220e** of the second arm **190e** is connected to the second leg member **30e**. The second end **210e** of the first arm **180e** and the second end **230e** of the second arm **190e** are connected to the third leg member **40e**. In the embodiment shown in FIGS. 5A and 5B, the bracing assembly **50e** is constructed of one continuous piece of material. The first end **200e** of the first arm **180e** forms a loop **232e** around the first leg member **20e** and is slidably connected to the first leg member **20e**, the first end **220e** of the second arm **190e** forms a loop **234e** around the second leg member **30e** and is slidably connected to the second leg member **30e**, the second end **210e** of the first arm **180e** and second end **230e** of the second arm **190e** form a contiguous loop **236e** around the third leg member **40e** and the loop **236e** is slidably and pivotally connected to the third leg member **40e**. When stated that the loop **232e**, the loop **234e**, and the loop **236e** are “slidably connected”, what is meant is that the loops are able to move a distance up and down each of the respective leg members. It will be appreciated, however, that the first arm **180e** and the second arm **190e** may be connected to the leg members in any manner as long as the leg members are able to collapse. It will also be appreciated that the loops may either be slidably connected or connected in a fixed manner to each respective leg member.

The bracing assembly **50e** may be constructed of the same material as the leg members or the bracing assembly **50e** may be constructed of a different material than the leg members as long as the material allows the bracing assembly **50e** to sustain the floral easel **10e** in the open or erect position.

If the third leg **40e** is not pivotally connected to at least one of the first leg **20e** and the second leg **30e** or, if the third leg **40e** is pivotally connected to at least one of the first leg **20e** and the second leg **30e** limiting its travel to positions of full erection, full collapse, or intermediate positions, and if the first leg **20e** and the second leg **30e** are connected to limit travel to positions from full erection to full collapse, then the bracing assembly **50e** can be eliminated from this embodiment of the floral easel **10e**.

A stop member **235e** is connected adjacent and underneath the second arm **190e** of the bracing assembly **50e** to prevent the bracing assembly **50e** from sliding down the second leg member **30e** of the floral easel **10e**. The stop member **235e** may be constructed of the same material as the leg members or of a different material than the leg members. In the embodiment shown in FIG. 5A, the stop member **235e** is a horizontal cross-piece connected adjacent and below the second arm



## 21

190e of the bracing assembly 50e. However, the stop member 235e may be connected to either the first leg member 20e or the second leg member 30e of the floral easel 10e.

It should be understood that the stop member 235e is not required, however, for embodiments in which the bracing assembly 50e is slidably or pivotally connected to at least one leg member, the stop member 235e aids in the erection and enhances the stability of the floral easel 10e.

A support member 270e (FIGS. 5A and 5B) may also be employed to hold and/or support the floral object or non-floral object, however, any portion of the floral easel 10e may hold or support the floral object or non-floral object, such as, for example, the support member 270e may be connected to any area of the floral easel 10e such as, for example, the first leg member 20e, the second leg member 30e, the third leg member 40e, or any other area capable of having the support member 270e attached thereto. The support member 270e may be any kind of device capable of supporting the floral object, such as, for example the bracing assembly 50e or any other area of the floral easel 10e capable of supporting the floral object or non-floral object. For example, but not by way of limitation, the support member 270e may be selected from the group consisting of a hook, a platform, a magnet, wire, adhesive, cohesive, velcro, a slot, a loop, a tab, a groove, a spring, elastic, a band, ribbon, a clip, combinations thereof, or any other device that is capable of holding and/or supporting the floral object. The support member 270e, as shown in FIG. 5, is a hook connected to the first end 100e of the third leg member 40e.

The support member 270e may be constructed of the same material as the leg members or the support member 270e may be constructed of a different material than the leg members as long as the material is capable of holding and/or supporting the floral object.

The floral easel 10e may also have a retaining member 280e for retaining the leg members in the collapsed position. For example, but not by way of limitation, the retaining member 280e may be selected of the group consisting of elastic, a clip or clips, a spring, a band, shrink material, stretch material, a carton, a tube, a bend in the leg members, a groove, a slot, a loop, a hook, a wire, a bow, a rope, a magnet, a cord, a chain, a strap, a cable, adhesive, combinations thereof, or any other device capable of retaining the leg members in the collapsed position. The retaining member 280e may also be constructed of the same material as the leg members or the retaining member 280e may be constructed from a different material than the leg members as long as the material is capable of retaining the leg members in the collapsed position.

As shown in FIG. 5, the retaining member 280e is connected to the third leg member 40e, however, for example, the retaining member 280e may be attached to any of the leg members, the bracing assembly 160e, or to any other area of the floral easel 10e that is suitable for connecting the retaining member 280e or may be a separate device unconnected to the floral easel 10e.

To move the floral easel 10e from the open or erected position (shown in FIG. 5A) to the collapsed position (shown in FIG. 5B), the bracing assembly 50e is rotated about the loop 232e and the loop 234e to cause the loop 236e to slide in an upward direction toward the first end 100e of the third leg member 40e thereby pivoting the first leg member 20e and the second leg member 30e upward toward the third leg member 40e causing the third leg member 30e to be placed between the first leg member 20e and the second leg member 30e. The first end 60e and the first end 80e may then be inserted into the

## 22

retaining member 280e forming the leg members into a bundle 290e (shown in FIG. 5B).

## Description of FIG. 6

Referring now to FIGS. 6A and 6B, designated generally by the reference numeral 10f is a floral easel. The floral easel 10f has a plurality of leg members and, in one embodiment shown in FIG. 6, the floral easel 10f has a first leg member 20f and a second leg member 30f.

As shown in FIGS. 6A and 6B, the first leg member 20f has a first end 60f, a second end 70f, a first side 100f and a second side 110f. The second leg member 30f has a first end 80f, a second end 90f, a first side 120f and a second side 130f. The first end 60f of the first leg member 20f and the first end 80f of the second leg member 30f are integrally connected forming an arch 140f where the first end 60f and first end 80f are joined. The second side 110f of the first leg member 20f is generally in contact with a substrate 45f to thereby support and hold the floral easel 10f. The substrate 45f may be any surface such as, for example, a floor, dirt, grass, fiber, plastic, or any surface capable of supporting the floral easel 10f thereon.

The first leg member 20f and the second leg member 30f may be formed as a single piece of material that is integrally connected (shown in FIGS. 6A and 6B as one piece of springy material). Alternatively, the first leg member 20f and the second leg member 30f may be formed of two or more pieces of material. If the first leg member 20f and the second leg member 30f are formed of two or more pieces of material, the materials may differ or the materials may be the same. For example, if the first leg member 20f and the second leg member 30f are formed of two or more pieces of material, one of the leg members may be formed of steel and the other may be formed of aluminum. In another embodiment, each of the plurality of leg members may be formed of at least two or more materials. For example, a portion of at least one of the leg members may be steel and another portion of the leg member may be aluminum. In yet another embodiment, the first leg member 20f and the second leg member 30f may be integrally connected. The plurality of leg members may be constructed of the same material or a different material. For example, at least one of the plurality of leg members may be constructed of steel and the other leg member may be constructed of aluminum.

The floral easel 10f may be employed to hold and/or support a floral object (not shown) by placing the floral object about the second end 90h of the second leg member 30f of the floral easel 10f.

A support member 270f (FIGS. 6A and 6B) may also be employed to hold and/or support the floral object or non-floral object, however, any portion of the floral easel 10f may hold or support the floral object or the non-floral object. The support member 270f may be connected to any area of the floral easel 10f such as, for example, the first leg member 20f, the second leg member 30f or any other area capable of having the support member 270f attached thereto. The support member 270f may be any kind of device capable of supporting the floral object. For example, but not by way of limitation, the support member 270f may be selected from the group consisting of a hook, a platform, a magnet, wire, adhesive, cohesive, velcro, a slot, a loop, a tab, a groove, a spring, elastic, a band, ribbon, a clip, combinations thereof, or any other device that is capable of holding and/or supporting the floral object. The support member 270f, as shown in FIG. 6, is a hook connected to the second end 90f of the second leg member 30f.



The support member **270f** may be constructed of the same material as the leg members or the support member **270f** may be constructed of a different material than the leg members as long as the material is capable of holding and/or supporting the floral object.

The floral easel **10f** may also have a retaining member **280f** for retaining the leg members in the collapsed position. For example, but not by way of limitation, the retaining member **280f** may be selected of the group consisting of elastic, a clip or clips, a spring, a band, shrink material, stretch material, a carton, a tube, a bend in the leg members, a groove, a slot, a hook, a loop, a wire, a bow, a rope, a magnet, a cord, a chain, a strap, a cable, adhesive, combinations thereof, or any other device capable of retaining the leg members in the collapsed position. The retaining **280f** may also be constructed of the same material as the leg members or the retaining member **280f** may be constructed of a different material than the leg members as long as the material is capable of retaining the leg members in the collapsed position.

As shown in FIG. 6, the retaining member **280f** is connected to the second leg member **30f**, however, for example, the retaining member **280f** may be attached to either the first leg member **20f** or the second leg member **20f** or to any other area of the floral easel **10f** that is suitable for connecting the retaining member **280f** or may be a separate device unconnected to the floral easel **10f**.

To move the floral easel **10f** from the open or erected position (shown in FIG. 6A) to the collapsed position (shown in FIG. 6B), the second leg member **30f** is rotated counter-clockwise about the arch **140f** formed between the first leg member **20f** and the second leg member **30f**. The second side **110f** of the first leg member **20f** and the second side **130f** of the second leg member **30f** are compressed together thereby inverting the arch **140f** between the first leg member **20f** and the second leg member **30f**. The second end **70f** and the second end **90f** may then be inserted into the retaining member **280f** forming the leg members into a bundle **290f** (shown in FIG. 6B).

#### Description of FIG. 7

Referring now to FIGS. 7A and 7B, designated generally by the reference numeral **10g** is a floral easel. The floral easel **10g** has a plurality of leg members and, in one embodiment shown in FIG. 7, the floral easel **10g** has a first leg member **20g** and a second leg member **30g**.

As shown in FIGS. 7A and 7B, the first leg member **20g** has a first end **60g**, a second end **70g**, a first side **100g** and a second side **110g**. The second leg member **30g** has a first end **80g**, a second end **90g**, a first side **120g** and a second side **130g**. The first end **60g** of the first leg member **20g** and the first end **80g** of the second leg member **30g** are integrally connected forming an arch **140g** where the first end **60g** and first end **80g** are joined. The second side **110g** of the first leg member **20g** is generally in contact with a substrate **45g** to thereby support and hold the floral easel **10g**. The substrate **45g** may be any surface such as, for example, a floor, dirt, grass, fiber, plastic, or any surface capable of supporting the floral easel **10g** thereon.

The first leg member **20g** and the second leg member **30g** may be formed as a single piece of material that is integrally connected (shown in FIGS. 7A and 7B as one piece of elastic or resilient material). Alternatively, the first leg member **20g** and the second leg member **30g** may be formed of two or more pieces of material. If the first leg member **20g** and the second leg member **30g** are formed of two or more pieces of material, the materials may differ or the materials may be the same. For

example, if the first leg member **20g** and the second leg member **30g** are formed of two or more pieces of material, one of the leg members may be formed of steel and the other may be formed of aluminum. In another embodiment, each of the plurality of leg members may be formed of at least two or more materials. For example, at least a portion of at least one of the leg members may be steel and another portion of the leg member may be aluminum. In yet another embodiment, the first leg member **20g** and the second leg member **30g** may be integrally connected. The plurality of leg members may be constructed of the same material or a different material. For example, at least one of the plurality of leg members may be constructed of steel and the other leg members may be constructed of aluminum.

The floral easel **10g** may be employed to hold and/or support a floral object (not shown) by placing the floral object about the second end **90g** of the second leg member **30g** of the floral easel **10g**.

A support member **270g** (FIGS. 7A and 7B) may also be employed to hold and/or support the floral object, however, any portion of the floral easel **10g** may hold or support the floral object or non-floral object. The support member **270g** may be connected to any area of the floral easel **10g** such as, for example, the first leg member **20g**, the second leg member **30g**, or any other area capable of having the support member **270g** attached thereto. The support member **270g** may be any kind of device capable of supporting the floral object. For example, but not by way of limitation, the support member **270g** may be selected from the group consisting of a hook, a platform, a magnet, wire, adhesive, cohesive, velcro, a slot, a loop, a tab, a groove, a spring, elastic, a band, ribbon, a clip, combinations thereof, or any other device that is capable of holding and/or supporting the floral object. The support member **270g**, as shown in FIG. 7, is a hook connected to the second end **90g** of the second leg member **30g**.

The support member **270g** may be constructed of the same material as the leg members or the support member **270g** may be constructed of a different material than the leg members as long as the material is capable of holding and/or supporting the floral object.

The floral easel **10g** may also have a retaining member **280g** for retaining the leg members in the collapsed position. For example, but not by way of limitation, the retaining member **280g** may be selected of the group consisting of elastic, a clip or clips, a spring, a band, shrink material, stretch material, a carton, a tube, a bend in the leg members, a groove, a slot, a hook, a loop, a wire, a bow, a rope, a magnet, a cord, a chain, a strap, a cable, adhesive, combinations thereof, or any other device capable of retaining the leg members in the collapsed position. The retaining member **280g** may also be constructed of the same material as the leg members or the retaining member **280g** may be constructed of a different material than the leg members as long as the material is capable of retaining the leg members in the collapsed position.

As shown in FIG. 7, the retaining member **280g** is connected to the first leg member **20g**, however, for example, the retaining member **280g** may be attached to either the first leg member **20g** or the second leg member **20g** or to any other area of the floral easel **10g** that is suitable for connecting the retaining member **280g** or may be a separate device unconnected to the floral easel **10g**.

To move the floral easel **10g** from the open or erected position (shown in FIG. 7A) to the collapsed position (shown in FIG. 7B), the second leg member **30g** is rotated clockwise about the arch **140g** formed between the first leg member **20g** and the second leg member **30g**. The first side **10g** of the first



25

leg member 20g and the first side 120g of the second leg member 30g are compressed together thereby decreasing the angle formed at the arch 140g between the first leg member 20g and the second leg member 30g. The second end 70g and the second end 90g may then be inserted into the retaining member 280g forming the leg members into a bundle 290g (shown in FIG. 7B).

## Description of FIG. 8

Referring now to FIGS. 8A and 8B, designated generally by the reference numeral 10h, is a floral. The floral easel 10h has a plurality of leg members and, in one embodiment shown in FIG. 8, the floral easel 10h has a first leg member 20h, a second leg member 30h and a third leg member 40h. The floral easel 10h also includes a bracing assembly 50h for sustaining the floral easel 10h in an open or erected position shown in FIG. 8A.

As shown in FIGS. 8A and 8B, the first leg member 20h has a first end 60h and a second end 70h, the second leg member 30h has a first end 80h and a second end 90h, and the third leg member 40h has a first end 100h and a second end 110h. The first end 60h of the first leg member 20h, the first end 80h of the second leg member 30h, and the first end 100h of the third leg member 40h are associated at a joining member 120h. The second end 70h of the first leg member 20h, the second end 90h of the second leg member 30h, and the second end 110h of the third leg member 40h are generally in contact with a substrate 45h to thereby support and hold the floral easel 10h thereon.

At least two of the first leg member 20h, the second leg member 30h, and the third leg member 40h may be formed as a single piece of material that is integrally connected (shown in FIGS. 8A and 8B as one piece of tubular material forming an arch 130h having a center area 140h). Alternatively, at least two of the first leg member 20h, the second leg member 30h, and the third leg member 40h may be formed of two or more pieces of material. If the leg members are formed of two or more pieces of material, the materials may differ or the materials may be the same. For example, if the first leg member 20h and the second leg member 30h are formed of two or more pieces of material, one of the leg members may be formed of steel and the other may be formed of aluminum. In another embodiment, each of the plurality of leg members may be formed of at least two or more materials. For example, a portion of at least one of the leg members may be steel and another portion of the leg member may be aluminum. In yet another embodiment, the first leg member 20h, the second leg member 30h, and the third leg member 40h may be integrally connected. The plurality of leg members may be constructed of the same material or of a different material. For example, at least one of the plurality of leg members may be constructed of steel and the other leg members may be constructed of aluminum.

The joining member 120h for connecting and/or receiving the first end of the leg members may be formed of the same material as the leg members or the joining member 120h may be formed of a different material than the leg members. Also, the joining member 120h may be integrally connected to the first end 100h of the third leg member 40h or formed separately from the first end 100h of the third leg member 40h. As shown in FIGS. 8A and 8B, the joining member 120h is integrally connected to the first end 100h of the third leg member 40h and is crimped around and pivotally connected

26

to the arch 130h formed in the center area 140h thereby integrally joining the first end 60h of the first leg member 20h and the first end 70h of the second leg member 30h to define an apex 150h. However, the joining member 120h may be, for example, a solid block holding device, or any other device capable of receiving the first ends of the leg members. Also, the first end 100h of the third leg 40h need not be crimped around the arch 130h. In an alternative embodiment, the joining member 120h and the arch 130h are connected using materials that permit at least one of erecting and collapsing the floral easel 10h. Also, the first end 100h of the third leg 40h need not be pivotally connected to the arch 130h. In an alternative embodiment, the first end 100h may be flexibly connected to the arch 130h.

The bracing assembly 50h for sustaining the floral easel 10h in the open or erected position has a first arm 160h, a second arm 170h, and a third arm 180h. The first arm 160h has a first end 200h and a second end 210h. The second arm 170h has a first end 220h and a second end 230h. The third arm 180h has a first end 240h and a second end 250h. The first end 200h of the first arm 160h is connected to the first leg member 20h. The first end 220h of the second arm 170h is connected to the second leg member 30h. The first end 240h of the third arm 180h is connected to the third leg member 40h. The second end 210h of the first arm 160h, the second end 230h of the second arm 170h, and the second end 250h of the third arm 180h are connected to an arm support member 255h.

In the embodiment shown in FIGS. 8A and 8B, the bracing assembly 50h is constructed of more than one piece of material, however it is to be understood that the bracing assembly 50h may be constructed of one integrally connected piece of material. Alternatively, the bracing assembly 50h may be formed non-integrally from the leg members. In the embodiment shown in FIGS. 8A and 8B, the first end 200h of the first arm 160h forms a loop 232h around the first leg member 20h and is slidably connected to the first leg member 20h and the second end 210h of the first arm 160h is connected to the arm support member 255h. The first end 220h of the second arm 170h forms a loop 234h around the second leg member 30h and is slidably connected to the second leg member 30h and the second end 230h of the second arm 170h is connected to the arm support member 255h. The first end 240h of the third arm 180h forms a loop 236h around the third leg member 40h and is slidably connected to the third leg member 40h and the second end 250h of the third arm 180h is connected to the arm support member 255h. It will be appreciated, however, that the first arm 160h, the second arm 170h, and the third arm 180h may be connected to the leg members in any manner as long as the leg members are able to collapse. It will also be appreciated that the loops may either be slidably connected or connected in a fixed manner to each respective leg member.

The bracing assembly 50h may be constructed of the same material as the leg members or the bracing assembly 50h may be constructed of a different material than the leg members as long as the material allows the bracing assembly 50h to sustain the floral easel 10h in the open or erected position.

The floral easel 10h may be employed to hold and/or support a floral object (not shown) by placing the floral object about the first end 100h of the third leg member 40h of the floral easel 10h.

A support member 270h (FIGS. 8A and 8B) may also be employed to hold and/or support the floral object or non-floral object, however, any portion of the floral easel 10h may hold or support the floral object or non-floral object, such as, for example, the bracing assembly 50h, the joining member 120h or any other area of the floral easel 10h capable of supporting the floral object or non-floral object. The support member



270*h* may be connected to any area of the floral easel 10*h* such as, for example, the first ends of the plurality of leg members, the bracing assembly 50*h* or to any other area of the floral easel 10*h* to which the support member 270*h* may be attached. The support member 270*h* may be any kind of device capable of supporting the floral object. For example, but not by way of limitation, the support member 270*h* may be selected from the group consisting of a hook, a platform, a magnet, wire, adhesive, cohesive, velcro, a slot, a loop, a tab, a groove, a spring, elastic, a band, ribbon, a clip, combinations thereof, or any other device that is capable of holding and/or supporting the floral object. The support member 270*h*, as shown in FIG. 8, is a hook connected to the first end 100*h* of the third leg member 40*h*.

The support member 270*h* may be constructed of the same material as the leg members or the support member 270*h* may be constructed of a different material than the leg members as long as the material is capable of holding and/or supporting the floral object.

The floral easel 10*h* may also have a retaining member 280*h* for retaining the leg members in the collapsed position. For example, but not by way of limitation, the retaining member 280*h* may be selected of the group consisting of elastic, a clip or clips, a spring, a band, shrink material, stretch material, the joining member 120*h*, a carton, a tube, a bend in the leg members, a groove, a slot, a hook, a loop, a wire, a bow, a rope, a magnet, a cord, a chain, a strap, a cable, adhesive, combinations thereof, or any other device capable of retaining the leg members in the collapsed position. The retaining member 280*h* may also be constructed of the same material as the leg members or the retaining member 280*h* may be constructed from a different material than the leg members as long as the material is capable of retaining the leg members in the collapsed position. Alternatively, the retaining member 280*h* may be eliminated from the floral easel 10*h* and the plurality of leg members may be retained in the collapsed position by the joining member 120*h*.

As shown in FIG. 8, the retaining member 280*h* is connected to the first leg member 20*h*, however, for example, the retaining member 280*h* may be attached to any of the leg members, the bracing assembly 50*h* or to any other area of the floral easel 10*h* that is suitable for connecting the retaining member 280*h* or may be a separate device unconnected to the floral easel 10*h*.

To move the floral easel 10*h* from the open or erect position (shown in FIG. 8A) to the collapsed position (shown in FIG. 8B), the first end 200*h* of the first arm 160*h* (the loop 232*h*), the first end 220*h* of the second arm 170*h* (the loop 234*h*), and the first end 240*h* of the third arm 180*h* (the loop 236*h*) are moved toward the first end of each respective leg member so as to allow the leg members to collapse inward. The second end 70*h*, the second end 90*h*, and the second end 110*h* may then be inserted into the retaining member 280*h* forming the leg members into a bundle 290*h* (shown in FIG. 8B).

In an alternate embodiment, the loop 232*h*, the loop 234*h*, and the loop 236*h* may be fixed to each respective leg member. To move the floral easel 10*h* from the open or erect position to the closed position, the arm support member 255*h* may be moved in an upward direction so as to allow the first leg member 20*h*, the second leg member 30*h*, and the third leg member 40*h* to move from the open or erect position to the collapsed position so that the second end 70*h*, the second end 90*h*, and the second end 110*h* may be inserted into the retaining member 280*h* forming the leg members into the bundle 290*h* (shown in FIG. 8D).

In another embodiment of the present invention shown in FIGS. 8C and 8D, a portion of the first leg member 20*h*, the

second leg member 30*h*, and the third leg member 40*h* may be bent to prevent each of the loops from moving toward the second end of each respective leg member. That is, the first leg member 20*h* has a bend 300*h* to prevent the loop 232*h* from moving toward the second end 70*h* of the first leg member 20*h*. The second leg member 30*h* has a bend 310*h* to prevent the loop 234*h* from moving toward the second end 90*h* of the second leg member 30*h*. The third leg member 40*h* has a bend 320*h* to prevent the loop 236*h* from moving toward the second end 110*h* of the third leg member 40*h*.

To move the floral easel 10*h* from the open or erect position (shown in FIG. 8C) to the collapsed position (shown in FIG. 8D), the loop 232*h*, the loop 234*h*, and the loop 236*h* are moved toward the first end of each respective leg member so as to allow the leg members to collapse inward. The second end 70*h*, the second end 90*h*, and the second end 110*h* may then be inserted into the retaining member 280*h* forming the leg members into a bundle 290*h* (shown in FIG. 8D).

In an alternate embodiment, the loop 232*h*, the loop 234*h*, and the loop 236*h* may be fixed to each respective leg member. To move the floral easel 10*h* from the open or erect position to the closed position, the arm support member 255*h* may be moved in an upward direction so as to allow the first leg member 20*h*, the second leg member 30*h*, and the third leg member 40*h* to move from the open or erect position to the collapsed position so that the second end 70*h*, the second end 90*h*, and the second end 110*h* may be inserted into the retaining member 280*h* forming the leg members into the bundle 290*h* (shown in FIG. 8D).

#### Description of FIG. 9

Referring now to FIGS. 9A and 9B, designated generally by the reference numeral 10*i* is a floral easel. The floral easel 10*i* has a plurality of leg members and, in one embodiment shown in FIG. 9, the floral easel 10*i* has a first leg member 20*i* and a second leg member 30*i*.

As shown in FIGS. 9A and B, the first leg member 20*i* has a first end 60*i*, a second end 70*i*, a first side 100*i* and a second side 110*i*. The second leg member 30*i* has a first end 80*i*, a second end 90*i*, a first side 120*i* and a second side 130*i*. The first end 60*i* of the first leg member 20*i* and the first end 80*i* of the second leg member 30*i* are integrally connected forming an acute angle 140*i* where the first end 60*i* and first end 80*i* are joined. The second side 110*i* of the first leg member 20*i* is generally in contact with a substrate 45*i* to thereby support and hold the floral easel 10*i*. The substrate 45*i* may be any surface such as, for example, a floor, dirt, grass, fiber, plastic, or any surface capable of supporting the floral easel 10*i* thereon.

The first leg member 20*i* and the second leg member 30*i* may be formed as a single piece of material that is integrally connected (shown in FIGS. 9A and 9B as one piece of springy material). Alternatively, the first leg member 20*i* and the second leg member 30*i* may be formed of two or more pieces of material. If the first leg member 20*i* and the second leg member 30*i* are formed of two or more pieces of material, the materials may differ or the materials may be the same. For example, if the first leg member 20*i* and the second leg member 30*i* are formed of two or more pieces of material, one of the leg members may be formed of steel and the other may be formed of aluminum. In another embodiment, each of the plurality of leg members may be formed of at least two or more materials. For example, a portion of at least one of the leg members may be steel and another portion of the leg member may be aluminum. In yet another embodiment, the first leg member 20*i* and the second leg member 30*i* may be



integrally connected. The plurality of leg members may be constructed of the same material or a different material. For example, at least one of the plurality of leg members may be constructed of steel and the other leg member may be constructed of aluminum.

A support member 270*i* (FIGS. 9A and 9B) may also be employed to hold and/or support the floral object or non-floral object, however, any portion of the floral easel 10*i* may hold or support the floral object or the non-floral object. The support member 270*i* may be connected to any area of the floral easel 10*i* such as, for example, the first leg member 20*i*, the second leg member 30*i* or any other area capable of having the support member 270*i* attached thereto. The support member 270*i* may be any kind of device capable of supporting the floral object. For example, but not by way of limitation, the support member 270*i* may be selected from the group consisting of a hook, a platform, a magnet, wire, adhesive, cohesive, velcro, a slot, a loop, a tab, a groove, a spring, elastic, a band, ribbon, a clip, combinations thereof, or any other device that is capable of holding and/or supporting the floral object. The support member 270*i*, as shown in FIG. 9, is a hook connected to the second end 90*i* of the second leg member 30*i*.

The support member 270*i* may be constructed of the same material as the leg members or the support member 270*i* may be constructed of a different material than the leg members as long as the material is capable of holding and/or supporting the floral object.

The floral easel 10*i* may also have a retaining member 280*i* for retaining the leg members in the collapsed position. For example, but not by way of limitation, the retaining member 280*i* may be selected of the group consisting of elastic, a clip or clips, a spring, a band, shrink material, stretch material, a carton, a tube, a bend in the leg members, a groove, a slot, a hook, a loop, a wire, a bow, a rope, a magnet, a cord, a chain, a strap, a cable, adhesive, combinations thereof, or any other device capable of retaining the leg members in the collapsed position. The retaining 280*i* may also be constructed of the same material as the leg members or the retaining member 280*i* may be constructed of a different material than the leg members as long as the material is capable of retaining the leg members in the collapsed position.

As shown in FIG. 9, the retaining member 280*i* is connected to the second leg member 30*i*, however, for example, the retaining member 280*i* may be attached to either the first leg member 20*i* or the second leg member 20*i* or to any other area of the floral easel 10*i* that is suitable for connecting the retaining member 280*i* or may be a separate device unconnected to the floral easel 10*i*.

To move the floral easel 10*i* from the open or erected position (shown in FIG. 9A) to the collapsed position (shown in FIG. 9B), the second leg member 30*i* is rotated either clockwise or counter-clockwise about the acute angle 140*i* formed between the first leg member 20*i* and the second leg member 30*i*. By rotating the floral easel 10*i* clockwise about the acute angle 140*i*, the first side 100*i* of the first leg member 20*i* and the first side 120*i* of the second leg member 30*i* are compressed together thereby decreasing the angle formed at the acute angle 140*i* between the first leg member 20*i* and the second leg member 30*i*. The second end 70*i* and the second end 90*i* may then be inserted into the retaining member 280*i* forming the leg members into a bundle 290*i* (shown in FIG. 9B). By rotating the floral easel 10*i* clockwise about the acute angle 140*i*, the second side 110*i* of the first leg member 20*i* and the second side 130*i* of the second leg member 30*i* are compressed together thereby inverting the acute angle 140*i* between the first leg member 20*i* and the second leg member

30*i*. The second end 70*i* and the second end 90*i* may then be inserted into the retaining member 280*i* forming the leg members into a bundle 290*i* (shown in FIG. 9B or NOT SHOWN—need to decide).

#### Description of FIG. 10

Referring now to FIGS. 10A and 10B, designated generally by the reference numeral 10*j* is a floral easel. The floral easel 10*j* has a plurality of leg members and, in one embodiment shown in FIG. 10, the floral easel 10*j* has a first leg member 20*j* and a second leg member 30*j*.

As shown in FIGS. 10A and 10B, the first leg member 20*j* has a first end 60*j*, a second end 70*j*, a first side 100*j* and a second side 110*j*. The first leg member 20*j* has a plurality of arches 22*j* formed therein. The arches 22*j* may be rigid or they may be collapsible. The second leg member 30*j* has a first end 80*j*, a second end 90*j*, a first side 120*j* and a second side 130*j*. The first end 60*j* of the first leg member 20*j* and the first end 80*j* of the second leg member 30*j* are integrally connected forming an acute angle 140*j* where the first end 60*j* and first end 80*j* are joined. The second side 110*j* of the first leg member 20*j* is generally in contact with a substrate 45*j* to thereby support and hold the floral easel 10*j*. The substrate 45*j* may be any surface such as, for example, a floor, dirt, grass, fiber, plastic, or any surface capable of supporting the floral easel 10*j* thereon.

The first leg member 20*j* and the second leg member 30*j* may be formed as a single piece of material that is integrally connected (shown in FIGS. 10A and 10B as one piece of elastic or resilient material). Alternatively, the first leg member 20*j* and the second leg member 30*j* may be formed of two or more pieces of material. If the first leg member 20*j* and the second leg member 30*j* are formed of two or more pieces of material, the materials may differ or the materials may be the same. For example, if the first leg member 20*j* and the second leg member 30*j* are formed of two or more pieces of material, one of the leg members may be formed of steel and the other may be formed of aluminum. In another embodiment, each of the plurality of leg members may be formed of at least two or more materials. For example, at least a portion of at least one of the leg members may be steel and another portion of the leg member may be aluminum. In yet another embodiment, the first leg member 20*j* and the second leg member 30*j* may be integrally connected. The plurality of leg members may be constructed of the same material or a different material. For example, at least one of the plurality of leg members may be constructed of steel and the other leg members may be constructed of aluminum.

The floral easel 10*j* may be employed to hold and/or support a floral object (not shown) by placing the floral object about the second end 90*j* of the second leg member 30*j* of the floral easel 10*j*.

A support member 270*j* (FIGS. 10A and 10B) may also be employed to hold and/or support the floral object, however any portion of the floral easel 10*j* may hold or support the floral object or non-floral object. The support member 270*j* may be connected to any area of the floral easel 10*j* such as, for example, the first leg member 20*j*, the second leg member 30*j*, or any other area capable of having the support member 270*j* attached thereto. The support member 270*j* may be any kind of device capable of supporting the floral object. For example, but not by way of limitation, the support member 270*j* may be selected from the group consisting of a hook, a platform, a magnet, wire, adhesive, cohesive, velcro, a slot, a loop, a tab, a groove, a spring, elastic, a band, ribbon, a clip, combinations thereof, or any other device that is capable of



holding and/or supporting the floral object. The support member **270j**, as shown in FIG. **10j**, is a hook connected to the second end **90j** of the second leg member **30j**.

The support member **270j** may be constructed of the same material as the leg members or the support member **270j** may be constructed of a different material than the leg members as long as the material is capable of holding and/or supporting the floral object.

The floral easel **10j** may also have a retaining member **280j** for retaining the leg members in the collapsed position. For example, but not by way of limitation, the retaining member **280j** may be selected of the group consisting of elastic, a clip or clips, a spring, a band, shrink material, stretch material, a carton, a tube, a bend in the leg members, a groove, a slot, a hook, a loop, a wire, a bow, a rope, a magnet, a cord, a chain, a strap, a cable, adhesive, combinations thereof, or any other device capable of retaining the leg members in the collapsed position. The retaining member **280j** may also be constructed of the same material as the leg members or the retaining member **280j** may be constructed of a different material than the leg members as long as the material is capable of retaining the leg members in the collapsed position.

As shown in FIG. **10j**, the retaining member **280j** is connected to the first leg member **20j**, however, for example, the retaining member **280j** may be attached to either the first leg member **20j** or the second leg member **20j** or to any other area of the floral easel **10j** that is suitable for connecting the retaining member **280j** or may be a separate device unconnected to the floral easel **10j**.

To move the floral easel **10j** from the open or erected position (shown in FIG. **10A**) to the collapsed position (shown in FIG. **10B**), the second leg member **30j** is rotated clockwise about the acute angle **140j** formed between the first leg member **20j** and the second leg member **30j**. The first side **100j** of the first leg member **20j** and the first side **120j** of the second leg member **30j** are compressed together thereby decreasing the angle formed at the acute angle **140j** between the first leg member **20j** and the second leg member **30j**. The second end **70j** and the second end **90j** may then be inserted into the retaining member **280j** forming the leg members into a bundle **290j** (shown in FIG. **10B**).

#### Description of FIG. 11

Referring now to FIGS. **11A-11D**, designated generally by the reference numeral **10k** is a floral easel. The floral easel **10k** has a plurality of leg members and, in one embodiment shown in FIGS. **11A-11B**, the floral easel **10k** has a first leg member **20k**, a second leg member **30k**, and a third leg member **40k**.

As shown in FIGS. **11A-11B**, the first leg member **20k** has a first end **60k** and a second end **70k**. The second leg member **30k** has a first end **80k** and a second end **90k**. The third leg member **40k** has a first end **100k** and a second end **110k**. The first end **60k** of the first leg member **20k**, the first end **80k** of the second leg member **30k**, and the first end **100k** of the third leg member **40k** are capable of being placed into a joining member **120k** having a plurality of openings therein for positioning the leg members in the open or closed position. In the embodiment shown in FIGS. **11A-11C**, the joining member **120k** has a top portion **121k** and a bottom portion **122k**. The bottom portion has a first exterior opening **123k**, a second exterior opening **124k**, and a third exterior opening **125k** therein for placing the leg members in the open position (FIG. **11C**). The joining member **120k** also has a first interior opening **126k**, a second interior opening **127k**, and a third interior opening **128k** for placing the leg members in the closed position (FIG. **11C**). The joining member **120k** may be any shape

so as to support the leg members such as, for example, a block, an oval, a circle, a triangle, a pentagon, a hexagon, or any other shape capable of receiving and supporting the plurality of leg members. Further, the joining member **120k** may be constructed of any material capable of receiving and supporting the plurality of leg members such as, for example, wood, plastic, rubber, metal, or any other material capable of receiving and supporting the plurality of leg members. The second end **70k** of the first leg member **20k**, the second end **90k** of the second leg member **30k**, and the second end **110k** of the third leg member **40k** are generally in contact with a substrate **45k** (shown in FIG. **11A**) to thereby support and hold the floral easel **10k**. The substrate **45k** may be any surface such as, for example, a floor, dirt, grass, fiber, plastic, tile, carpet, combinations thereof, or any surface capable of supporting the floral easel **10k** thereon.

The first leg member **20k** and the second leg member **30k** may be formed of two or more pieces of material. If the first leg member **20k** and the second leg member **30k** are formed of two or more pieces of material, the materials may differ or the materials may be the same. For example, if the first leg member **20k** and the second leg member **30k** are formed of two or more pieces of material, one of the leg members may be formed of steel and the other may be formed of aluminum. In another embodiment, each of the plurality of leg members may be formed of at least two or more materials. For example, a portion of at least one of the leg members may be steel and another portion of the leg member may be aluminum. In yet another embodiment, the first leg member **20k**, the second leg member **30k**, and the third leg member **30k** may be integrally connected. The plurality of leg members may be constructed of the same material or a different material. For example, at least one of the plurality of leg members may be constructed of steel and the other leg members may be constructed of aluminum.

A support member **270k** (FIGS. **11A-11C**) may also be employed to hold and/or support the floral object **260k** (or non-floral object), however, any portion of the floral easel **10k** may hold or support the floral object **260k** or non-floral object, such as, for example, the joining member **120k** or any other area of the floral easel **10k** capable of supporting the floral object **260k** or a non-floral object. The support member **270k** may be connected to any area of the floral easel **10k** such as, for example, the joining member **120k** or the leg members. Shown in FIGS. **1A-11C**, the support member **270k** is connected to the top portion **121** of the joining member **120k**. However, the support member **270k** may be connected to any portion of the joining member **120k**. The support member **270k** may be any kind of device capable of supporting the floral object **260k**. For example, but not by way of limitation, the support member **270k** may be selected from the group consisting of a hook, a platform, a magnet, wire, adhesive, cohesive, velcro, a slot, a loop, a tab, a groove, a spring, elastic, a band, ribbon, a clip, combinations thereof, or any other device that is capable of holding and/or supporting the floral object **260k**.

The support member **270k** may be constructed of the same material as the leg members or the support member **270k** may be constructed of a different material than the leg members as long as the material is capable of holding and/or supporting the floral object **260k**.

The floral easel **10k** may also have a retaining member (not shown) for retaining the leg members in the collapsed position. For example, but not by way of limitation, the retaining member may be selected from the group consisting of elastic, a clip or clips, a spring, a band, shrink material, stretch material, the joining member **120k**, a carton, a tube, a bend in the



leg members, a groove, a slot, a loop, a hook, a wire, a bow, a rope, a magnet, a cord, a chain, a strap, a cable, adhesive, combinations thereof, or any other device capable of retaining the leg members in the collapsed position. The retaining member may also be constructed of the same material as the leg members or the retaining member may be constructed of a different material than the leg members as long as the material is capable of retaining the leg members in the collapsed position. Alternatively, the retaining member may be eliminated from the floral easel 10 and the plurality of leg members may be retained in the collapsed position by the joining member 120k.

To move the floral easel 10k from the open or erected position (shown in FIG. 11A) to the collapsed position (shown in FIG. 11B), the first ends of the leg members are moved from the exterior openings (123k, 124k and 125k) (FIG. 11C) in the joining member 120k to the interior openings (126k, 127k, and 128k) (FIG. 11C) in the joining member 120k.

Shown in FIG. 11D is another embodiment of the floral easel 10/ wherein the floral easel 10/ has a splay assembly 12/ for sustaining the floral easel 10/ in the open or erected position. The splay assembly 12/ has a bracing assembly 160/ and a reinforcing member 170/. It should be understood that the splay assembly 12/ may be formed separately from the legs or the splay assembly 12/ may be integrally connected to the legs. Alternatively, the bracing assembly 160/ may be formed non-integrally from the legs and the reinforcing member 170/ may be formed integrally with the legs or vice-versa. The bracing assembly 160/ has a first arm 180/ and a second arm 190/. The first arm 180/ has a first end 200/ and a second end 210/. The second arm 190/ has a first end 220/ and a second end 230/. The first end 200/ of the first arm 180/ is connected to the first leg member 20/. The first end 220/ of the second arm 190/ is connected to the second leg member 30/. The second end 210/ of the first arm 180/ and the second end 230/ of the second arm 190/ are connected to the third leg member 40/. In the embodiment shown in FIG. 11D, the bracing assembly 160/ is constructed of one continuous piece of material. The first end 200/ of the first arm 180/ forms a loop 232/ around the first leg member 20/ and is slidably connected to the first leg member 20/, the first end 220/ of the second arm 190/ forms a loop 234/ around the second leg member 30/ and is slidably connected to the second leg member 30/, the second end 210/ of the first arm 180/ and second end 230/ of the second arm 190/ form a contiguous loop 236/ around the third leg member 40/ and the loop 236/ is slidably and pivotally connected to the third leg member 40/. It will be appreciated, however, that the first arm 180/ and the second arm 190/ may be connected to the leg members in any manner as long as the leg members are able to fully collapse.

The bracing assembly 160/ may be a single piece of material, or more than one piece of material. For example, as shown in FIG. 11D, the bracing assembly 160/ is a single piece of material wherein the second end 210/ of the first arm 180 and the second end 230/ of the second arm 190/ form a continuous loop around the third leg member 40/ wherein the looped area is slidably and pivotally connected to the third leg member 40. If the bracing assembly 160/ is fabricated using sufficiently flexible and springy material, it need not be slidably or pivotally connected to any or all of the plurality of leg members.

The bracing assembly 160/ may be constructed of the same material as the leg members or the bracing assembly 160/ may be constructed of a different material than the leg members as long as the material allows the bracing assembly 160/ to sustain the floral easel 10 in the open or erected position.

If the third leg 40/ is not pivotally connected to at least one of the first leg 20/ and the second leg 30/ or, if the third leg 40/ is pivotally connected to at least one of the first leg 20/ and the second leg 30/ limiting its travel to positions of full erection, full collapse, or intermediate positions and, if the first leg 20/ and the second leg 30/ are connected to limit travel to positions from full erection to full collapse, then at least one of the bracing assembly 160/ and reinforcing member 170/ can be eliminated from this embodiment of the floral easel 10/.

A stop member 235/ may be connected adjacent and underneath the second arm 190/ of the bracing assembly 160/ to prevent the bracing assembly 160/ from sliding down the second leg member 30/ of the floral easel 10/. The stop member 235/ may be constructed of the same material as the leg member or of a different material than the leg member. In the embodiment shown in FIG. 11D, the stop member 235/ is a horizontal cross-piece connected adjacent and below the second arm 190/ of the bracing assembly 160/. However, the stop member 235/ may be connected to any of the leg members of the floral easel 10/. It should be understood that the stop member 235/ is not required, however, for embodiments in which the bracing assembly 160/ is slidably or pivotally connected to at least one leg member, the stop member 235/ aids in the erection and enhances the stability of the floral easel 10/.

The reinforcing member 170/ has a first end 240/ and a second end 250/. The first end 240/ is connected to the first leg member 20/ and the second end 250/ is connected to the second leg member 30/. In the embodiment shown in FIG. 11D, the first end 240/ forms a loop 252/ around the first leg member 20/ and is slidably connected to the first leg member 20/ and the second end 250/ forms a loop 254/ around the second leg member 30/ and is slidably connected to the second leg member 30/. It will be appreciated, however, that the first end 240/ and second end 250/ may be connected in any manner to the first leg member 20/ and second leg member 30/ of the floral easel 10/.

For example, but not by way of limitation, the reinforcing member 170/ may be selected from the group consisting of elastic, a rope, a cord, a chain, a strap, a cable, a wire, springs, tubing, plastic, profiles, wood, polymer/fiber, adhesive, cohesive, velcro, combinations thereof or any other device which allows the floral easel 10/ to be sustained in the open or erected position. The reinforcing member 170/ may also be constructed of the same material as the leg members or the reinforcing member 170/ may be constructed of a different material than the leg members as long as the material allows the reinforcing member 170/ to sustain the floral easel 10/ in the open or erected position. It will be appreciated, however, that the reinforcing member 170/ is not necessary in alternate embodiments where a more flexible floral easel 10/ is desirable or acceptable for use.

A stop member 255/ may also be connected to the first leg member 20/ of the floral easel 10/ and placed adjacent and underneath the first end 240/ of the reinforcing member 170/ for preventing the reinforcing member 170/ from sliding down the first leg member 20/ of the floral easel 10/. However, it should be understood that the stop member 235/ may be placed on either the first leg member 20/ or the second leg member 30/ of the floral easel 10/. The stop member 255/ may be constructed of the same material as the designated leg member or of a different material than the designated leg member. In the embodiment shown in FIG. 11D, the stop member 255/ is a horizontal cross-piece connected adjacent and below the first end 240/ of the reinforcing member 170/. However, the stop member 255/ may be connected to either the first leg member 20/, the second leg member 30/, the third



leg member 40/ or any of the first leg member 20/, the second leg member 30/, and the third leg member 40/ of the floral easel 10/. It should be understood that multiple stop members may be used on the floral easel. It should also be understood that the stop members are not necessary to the erection, collapse, or stability of the floral easel 10/; however, the stop members may enhance stability and facilitate erection of the floral easel 10/. The reinforcing member 170/ may also provide at least one location on the floral easel 10/ to which floral objects and decorations may be fastened using wire clips, glue or any other fastening means capable of securing floral objects and decorations to the floral easel 10/.

The floral easel 10/ may also have a retaining member 280/ for retaining the leg members in the collapsed position. For example, but not by way of limitation, the retaining member 280/ may be selected from the group consisting of elastic, a clip or clips, a spring, a band, shrink material, stretch material, the joining member 120/, a carton, a tube, a bend in the leg members, a groove, a slot, a loop, a hook, a wire, a bow, a rope, a magnet, a cord, a chain, a strap, a cable, adhesive, combinations thereof, or any other device capable of retaining the leg members in the collapsed position. The retaining member 280/ may also be constructed of the same material as the leg members or the retaining member 280/ may be constructed of a different material than the leg members as long as the material is capable of retaining the leg members in the collapsed position. Alternatively, the retaining member 280/ may be eliminated from the floral easel 10/ and the plurality of leg members may be retained in the collapsed position by the joining member 120/.

As shown in FIG. 11D, the retaining member 280 is connected to the first leg member 20; however, for example, the retaining member 280 may be attached to any of the leg members, the bracing assembly 160, the reinforcing member 170, or to any other area of the floral easel 10 that is suitable for connecting the retaining member 280 or may be a separate device unconnected to the floral easel 10.

To move the floral easel 10/ from the open or erected position (shown in FIG. 11D) to the collapsed position (not shown), the bracing assembly 160/ is rotated about the loop 232/ and the loop 234/ to cause the loop 236/ to slide in an upward direction toward the first end 100/ of the third leg member 40/ thereby pivoting the third leg member 40/ inward toward the area between the first leg member 20/ and the second leg member 30/. The reinforcing member 170/ is also moved in an upward direction to cause the loop 254/ of the second end 250/ of the reinforcing member 170/ to slide in an upward manner along the first end 100/ of the second leg member 30/. The first end 60/ of the first leg member 20/ and the first end 80/ of the second leg member 30/ are compressed together thereby decreasing the angle formed at the arch 130/ between the center area 140/ of the first leg member 20/ and the second leg member 30/. The second end 70/, the second end 90/, and the second end 110/ may then be inserted into the retaining member 280/ forming the leg members into a bundle (not shown).

The various embodiments of the floral easel described herein in FIGS. 1-11, may be further shipped and/or stored. To ship the various embodiments of the floral easel described herein in FIGS. 1-11, the plurality of legs of the floral easel may be collapsed to the closed position and held in place by the retaining member; the floral easel may then be placed into a shipping container such as, for example, a box or crate, and the floral easel may be shipped to a predetermined location. Further, the various embodiments of the floral easel described herein in FIGS. 1-11, may be placed into a storage area for an indefinite period of time wherein the plurality of legs are

collapsed into the closed position so as to store the floral easel in a storage area for an indefinite period of time.

#### Description of FIG. 12

Referring now to FIGS. 12A-12I, designated generally by the reference numeral 10m-10u, respectively, is a floral easel. The floral easel 10m-10u has a top end 20m-20u, a bottom end 30m-30u and a side wall 40m-40u extending therebetween. The top end 20m-20u, the bottom end 30m-30u and the side-wall 40m-40u are formed so as to have the appearance of a cone as shown in FIGS. 12A-12I. The top end 20m-20u may have an aperture therethrough or may be solid. The bottom end 30m-30u may have an aperture therethrough or may be solid. The floral easel 10m-10u may be a solid structure or may be hollow. The bottom end 30m-30u is generally in contact with a substrate 45m-45u to thereby support and hold the floral easel 10m-10u. The substrate 45m-45u may be any surface such as, for example, a floor, dirt, grass, fiber, plastic, or any surface capable of supporting the floral easel 10m-10u thereon.

In the embodiment shown in FIG. 12A, the floral object (not shown) may be placed adjacent to the top end 20m of the floral easel 10m. In the embodiments shown in FIGS. 12B-12E, a support member 50n-50q may be employed to hold and/or support the floral object, however, any portion of the floral easel 10n-10q may hold or support the floral object or non-floral object. The support member 50n-50q may be any kind of device capable of supporting the floral object. For example, but not by way of limitation, the support member 50n-50q may be selected from the group consisting of a hook, a platform, a magnet, wire, adhesive, cohesive, velcro, a slot, a loop, a tab, a groove, a spring, elastic, a band, ribbon, a clip, combinations thereof, or any other device that is capable of holding and/or supporting the floral object. In the embodiment shown in FIG. 12B, the support member 50n is a tab created by making a cut-out in the floral easel 10n wherein a bottom portion 60n of the support member 50n remains connected to the floral easel 10n. In the embodiment shown in FIGS. 12C and 12D, the support member 50o and 50p, respectively, is adhesive located on the floral easel 10o-10p. The adhesive may be, for example, glue, a tab, tape or any other type of adhesive capable of holding and/or supporting the floral object. The adhesive tab shown in FIGS. 12C and 12D may be any shape such as rectangular as shown in FIG. 12C or circular as shown in FIG. 12D. However, it should be understood that the adhesive may be any shape so long as a floral object may be connected thereto. In the embodiment shown in FIG. 12E, the floral easel 10q includes an aperture 55q through a portion of the sidewall 40q of the floral easel 10q so that a support member (not shown) such as, for example, an s-hook may be placed therethrough. The aperture 55q may be any shape and/or size and may be located on any area of the sidewall 40q for placing the support member therethrough.

In the various embodiments of the floral easel described herein, the support member may be constructed of the same material as the floral easel or the support member may be constructed of a different material than the floral easel so long as the material is capable of holding and/or supporting the floral object. It should be understood however, that the support member is not required. The floral object may alternatively be placed around the top portion of the floral easel. It should also be understood that the floral object may be placed on either or both the top portion and/or the support member of the floral easel.



Shown in FIG. 12F is a floral easel **10r** having a portion of the sidewall **40r** removed so as to create a support member **50r** extending the length of a sidewall **40r** for placing a floral object therethrough.

Shown in FIG. 12G is a floral easel **10s** having a portion of the sidewall **40s** removed wherein a portion of the sidewall **40s** remains connected to the floral easel **10s** thereby creating a support member **50s**, such as a tab, for hanging a floral object thereon. The support member **50s** may be any shape or size. For example, as shown in FIG. 12G, the support member **50s** is substantially triangular.

It should be understood that in the various embodiments of the floral easel described herein, the floral easel may have multiple portions of the sidewall **40t-40u** removed as shown in FIGS. 12H and 12I, respectively. The removed portions of the sidewall **40t-40u** may serve to allow placement of the floral object therethrough for support of the floral object. Further, the floral easel **10t-10u**, as shown in FIGS. 12H and 12I, includes a support member **50t-50u**, such as a triangular tab, for holding and/or supporting a floral object thereon. It should be understood that the support member **50t-50u** may be any shape and/or size such as, for example, triangular, square, or circular, so long as the support member **50t-50u** is capable of holding and/or supporting the floral object.

It should be understood that the various embodiments of the floral easel described herein may be any shape and/or size. For example, as shown in FIGS. 13A-13E, the floral easel **10v-z**, respectively, is a five-sided pyramid. Shown in FIGS. 14A-14E, the floral easel **10aa-10ee**, respectively, is a five-sided pyramid having a plurality of leg members **280aa-280ee**. Shown in FIGS. 15A-15E, the floral easel **10ff-10jj** is a three-sided pyramid. Shown in FIGS. 16A-16F, the floral easel **10kk-10pp** is a three-sided pyramid having a plurality of leg members **280kk-280pp**, respectively.

Changes may be made in the construction and operation of the various components, elements and assemblies described herein or in the steps or sequence of steps of the methods described herein without departing from the spirit and scope of the invention as defined in the following claims.

What is claimed:

**1.** A method of shipping a floral easel for holding a floral object comprising the steps of:

providing a floral easel for holding a floral object comprising:

at least three legs, each of the at least three legs having a first end and a second end, the first end of each of the at least three legs being associated with one another at an apex, whereby the at least three legs are moveable with respect to one another about the apex such that the at least three legs are moveable from a collapsed position to an opened position and from an opened position to a collapsed position and wherein each of the at least three legs are disposed substantially adjacent one another in the collapsed position and wherein each of the at least three legs are spaced a distance away from each other in the opened position whereby the at least three legs form an upright pyramidal configuration when the at least three legs are in the opened position with the second end of each of the at least three legs engaging a substrate;

a splay assembly capable of holding the at least three legs in the opened position;

a support member capable of holding the floral object adjacent the floral easel; and

means for retaining the at least three legs in the collapsed position;

collapsing the at least three legs of the floral easel into the collapsed position;  
placing the floral easel into a shipping container; and  
shipping the container containing the floral easel to a pre-determined location.

**2.** The method of claim **1**, wherein the retaining means is selected from the group consisting of a hook, a loop, a wire, a bow, a rope, a magnet, a cord, a chain, a strap, a cable, adhesive, and combinations thereof.

**3.** The method of claim **1**, wherein the retaining means is attached to at least one of the at least three legs.

**4.** The method of claim **1**, wherein the retaining means is attached to the splay assembly.

**5.** The method of claim **1**, wherein in the step of providing a floral easel, the splay assembly is capable of reversibly holding the at least three legs in the opened position.

**6.** The method of claim **1**, wherein in the step of providing a floral easel, the splay assembly includes an angular member having a first end, a second end and a leg engaging member spaced therebetween, wherein the first end is associated with a first leg of the at least three legs, the second end is associated with a second leg of the at least three legs, and the leg engaging member is moveably associated with a third leg of the at least three legs.

**7.** The method of claim **6**, wherein the splay assembly is positionable about a lower portion of each of the at least three legs, wherein the lower portion is substantially adjacent the second end of each of the at least three legs.

**8.** The method of claim **6**, wherein the splay assembly is positionable about a middle portion of each of the at least three legs.

**9.** The method of claim **6**, wherein the splay assembly is positionable about an upper portion adjacent each of the at least three legs, wherein the upper portion is substantially adjacent the first end of each of the at least three legs.

**10.** The method of claim **1**, wherein in the step of providing a floral easel, the support member is attached to the first end of one of the at least three legs.

**11.** The method of claim **1**, wherein in the step of providing a floral easel, the support member is attached to the reinforcing member.

**12.** The method of claim **1**, wherein in the step of providing a floral easel, the support member is selected from the group consisting of a hook, a platform, a magnet, and a clip.

**13.** A method of shipping a floral easel for holding a floral object comprising the steps of:

providing a floral easel for holding a floral object comprising:

at least three legs, each of the at least three legs having a first end and a second end, the first end of each of the at least three legs being associated with one another at an apex, whereby the at least three legs are moveable with respect to one another about the apex such that the at least three legs are moveable from a collapsed position to an opened position and from an opened position to a collapsed position and wherein each of the at least three legs are disposed substantially adjacent one another in the collapsed position and wherein each of the at least three legs are spaced a distance away from each other in the opened position whereby the at least three legs form an upright pyramidal configuration when the at least three legs are in the opened position with the second end of each of the at least three legs engaging a substrate;

a splay assembly capable of holding the at least three legs in the opened position, the splay assembly comprising an angular member having a v-shaped con-



39

figuration with a first end, a second end and a leg engaging member spaced therebetween, where the first end is associated with a first leg of the at least three legs, the second end is associated with a second leg of the least three legs, and the leg engaging member is located at an apex of the V-shaped configuration, whereby the leg engaging member is movably associated with a third leg of the at least three legs; means for supporting the floral object adjacent the floral easel; and  
 a reinforcing member capable of holding two of the at least three legs in the opened position, wherein the reinforcing member is selected from the group consisting of a wire, elastic, a rope, a cord, a chain, a strap, and a cable;  
 collapsing the at least three legs of the floral easel into the collapsed position;  
 placing the floral easel into a shipping container; and  
 shipping the container containing the floral easel to a predetermined location.

**14.** The method of claim **13**, wherein in the step of providing a floral easel, the splay assembly is capable of reversibly holding the at least three legs in the opened position.

40

**15.** The method of claim **13**, wherein the splay assembly is positionable about a lower portion of each of the at least three legs, wherein the lower portion is substantially adjacent the second end of each of the at least three legs.

**16.** The method of claim **13**, wherein the splay assembly is positionable about a middle portion of each of the at least three legs.

**17.** The method of claim **13**, wherein the splay assembly is positionable about an upper portion of each of the at least three legs, wherein the upper portion is substantially adjacent the first end of each of the at least three legs.

**18.** The method of claim **13**, wherein in the step of providing a floral easel, the means for supporting the floral object is attached to the first end of one of the at least three legs.

**19.** The method of claim **13**, wherein in the step of providing a floral easel, the means for supporting the floral object is attached to the reinforcing member.

**20.** The method of claim **13**, wherein in the step of providing a floral easel, the means for supporting the floral object is selected from the group consisting of a hook, a platform, a magnet, and a clip.

\* \* \* \* \*

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 7,707,806 B2  
APPLICATION NO. : 12/150258  
DATED : May 4, 2010  
INVENTOR(S) : Donald E. Weder

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 16, line 47: After "second end" delete "10c" and replace with -- 110c --.  
Column 16, line 65: After "end" delete "10c" and replace with -- 110c --.  
Column 19, line 50: After "a curve" delete "11e" and replace with -- 111e --.  
Column 24, line 67: Delete "10g" and replace with -- 100g --.  
Column 32, line 45: Delete "1A-11C," and replace with -- 11A-11C, --.

Signed and Sealed this

Twenty-third Day of November, 2010



David J. Kappos  
*Director of the United States Patent and Trademark Office*