

US007764243B2

(12) **United States Patent**
Gierow et al.

(10) **Patent No.:** **US 7,764,243 B2**
(45) **Date of Patent:** **Jul. 27, 2010**

(54) **ANTENNA POSITIONING SYSTEM**

(75) Inventors: **Paul A. Gierow**, Madison, AL (US);
William R. Clayton, Madison, AL (US)

(73) Assignee: **GATR Technologies**, Huntsville, AL
(US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 292 days.

(21) Appl. No.: **11/893,064**

(22) Filed: **Aug. 14, 2007**

(65) **Prior Publication Data**
US 2008/0042921 A1 Feb. 21, 2008

Related U.S. Application Data

(60) Provisional application No. 60/838,085, filed on Aug.
16, 2006.

(51) **Int. Cl.**
H01Q 3/00 (2006.01)

(52) **U.S. Cl.** **343/766; 343/882; 343/915**

(58) **Field of Classification Search** **343/765,**
343/766, 880, 881, 882, 915

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,994,816	A *	2/1991	Kondo	343/762
5,517,204	A *	5/1996	Murakoshi et al.	343/765
6,167,924	B1	1/2001	Buckley et al.	
6,285,338	B1 *	9/2001	Bai et al.	343/882
6,300,893	B1	10/2001	Schaff et al.	
6,650,304	B2	11/2003	Lee et al.	
7,218,289	B2 *	5/2007	Trajkovic et al.	343/882
2004/0222983	A1 *	11/2004	Kakemura	345/204


* cited by examiner


Primary Examiner—Douglas W Owens
Assistant Examiner—Dieu Hien T Duong
(74) *Attorney, Agent, or Firm*—George P. Kobler; Lanier Ford
Shaver & Payne, P.C.

(57) **ABSTRACT**

An apparatus for positioning and controlling a spherical, inflatable antenna includes a driven rotating table disposed in the horizontal plane which supports and drives a horizontal arm member to which is hingedly connected first and second upright support members at either end. The upright support members include journal bearings attachable to the surface of an inflatable antenna.

7 Claims, 5 Drawing Sheets








Fig. 2A

DEPLOYED




Fig. 2B

PARTIALLY STOWED

Fig. 3






Fig. 4








Fig. 6

1

ANTENNA POSITIONING SYSTEM**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application claims priority to U.S. Provisional Application 60/838,085, filed Aug. 16, 2006, and which is incorporated by reference herein.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

The U.S. Government has a paid-up license in this invention and the right in limited circumstances to require the patent owner to license others on reasonable terms as provided for by the terms of Contract No. W9113M-05-0085 awarded by the U.S. Army.

FIELD OF THE INVENTION

This invention relates generally to positioning systems for antennas, and specifically to positioning systems for readily deployable, inflatable antennas.

BACKGROUND

In remote areas, or in emergency situations, it is difficult if not impossible to establish communications with satellite networks or other sorts of networks. Portable, inflatable antennas have been developed to solve this problem. Apparatuses for supporting, positioning, and controlling such antennas are needed however.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is described with reference to the accompanying drawings. In the drawings, like reference numbers indicate identical or functionally similar elements. Additionally, the left-most digit(s) of a reference number identifies the drawing in which the reference number first appears.

FIG. 1 depicts one exemplary embodiment of a an antenna positioning apparatus;

FIG. 2A depicts an embodiment of a collapsible support arm in an extended position;

FIG. 2B depicts the embodiment of FIG. 2A in a partially collapsed position;

FIG. 3 depicts an embodiment for use in tracking geo-stationary satellites;

FIG. 4 depicts a further embodiment for use in tracking geo-stationary satellites;

FIG. 5 depicts a further embodiment for use in tracking geo-stationary satellites; and

FIG. 6 illustrates an elevational view of another embodiment of an exemplary positioning apparatus for an inflatable antenna

DETAILED DESCRIPTION

The various embodiments of the present invention and their advantages are best understood by referring to FIGS. 1 through 6 of the drawings. The elements of the drawings are not necessarily to scale, emphasis instead being placed upon clearly illustrating the principles of the invention. Throughout the drawings, like numerals are used for like and corresponding parts of the various drawings.

2

Furthermore, reference in the specification to “an embodiment,” “one embodiment,” “various embodiments,” or any variant thereof means that a particular feature or aspect of the invention described in conjunction with the particular embodiment is included in at least one embodiment of the present invention. Thus, the appearance of the phrases “in one embodiment,” “in another embodiment,” or variations thereof in various places throughout the specification are not necessarily all referring to its respective embodiment. Moreover, features described with respect to a particular embodiment may also be employed in other disclosed embodiments as those skilled in the relevant arts will appreciate. This invention may be provided in other specific forms and embodiments without departing from the essential characteristics as described herein. The embodiments described below are to be considered in all aspects as illustrative only and not restrictive in any manner

Referring to FIG. 1, a positioning system 10 for a portable, collapsible antenna includes a base assembly, having a platform, or base plate 103, upon which is mounted an azimuth drive assembly 102. A horizontal arm 105 is fastened through its lengthwise midpoint to azimuth drive assembly 102, with the horizontal arm 105 having opposing free ends. At each of the opposing free ends, generally upright support members 107, 109 are pivotally connected to permit the upright support members 107, 109 to be folded for transport. Pivoting connections 104, 106 should be lockable to insure that support members 107, 109 do not collapse during operation but remain in a deployed extended position. In addition, a folding brace (not shown), lockable in its extended position, may be used between the horizontal arm 105 and the upright support members 107, 109 to further insure against collapse during deployment. Lockable pivoting connections also insure that stowed upright support members remain stowed. Each upright support member 107, 109 includes a horizontal journal bearing 112, 114 mounted on the inward sides of the end of the upright support members 107, 109 distal from the pivoting connections 112, 114 to the horizontal arm 105. At least one upright support member 107 includes an elevation drive actuator 108. Journal bearings 112, 114 include antenna structural interface means 115, 117 for attaching the antenna to the journal bearings 112, 114. Depending upon the weight of the antenna 101, a force amplifier 110 may be used to augment azimuth drive assembly.

Antenna structural interface means 115, 117 are generally disc-shaped members having a plurality of apertures through each of which is mounted a quarter-turn screw fastener. Attached to the wall of the antenna dome is a corresponding disc member (not shown) having a plurality of apertures corresponding to the number of quarter-turn fasteners. To attach the antenna to the structural interface means 115, 117, the quarter-turn fasteners of the interface means are inserted into the corresponding apertures in the disc on the antenna wall and turned. It may be preferable to color-code the fasteners and their corresponding apertures to help expedite set and insure proper orientation of the antenna 101.

Base plate 103 may be mounted upon three or more stabilizing struts 113 that extend outwardly from the base plate 103. Stabilizing struts 113 may include “outrigger” type struts that are generally perpendicular to the longitudinal axis of the base plate, with a single strut extending beyond the base plate along its longitudinal axis. In the alternative, stabilizers may extend from base plate at any angle. It should be noted that although base plate 103 is shown as rectangular, base plate may be any suitable shape. A rectangular base plate has an advantage in tending to need less space when the apparatus is being stored or transported. However there may be

instances where a base plate of a non-rectangular shape may be used. For example, an ovoid base plate provides the benefit of a lack of sharp corners. Struts may be fixed, or may be collapsible. They may be hinged so that they may fold underneath the base plate, or may be telescopically collapsible. In either case, they should have locking mechanisms to prevent undesired collapsing of the base assembly. Stabilizer struts may also have feet **119** extending downwardly therefrom which may be adjustable.

It is also preferable to include means for securing pivoting or movable parts in the stowed position. For example, horizontal arm may have a pin and hasp, and the base may have an aperture in its upper surface for receiving the pin located generally so that horizontal arm is locked in a stowed position within the perimeter of the base plate. It will be apparent to those skilled in the relevant arts that other means for securing the stowed position of the horizontal arm, and upright support members, may be used, for example, clamps, clasps, straps, etc.

Components of the positioning system are made from any suitable rigid, lightweight, yet durable materials. Metals, such as aluminum, including alloys, may be used. In addition, those skilled in the arts will recognize that the components made be formed from composite and polymeric materials. Moreover, to achieve even lighter weight, components need not be solid. For example, base plate may be a layered structure having two solid outer layers laminated to a corrugated or honey-combed inner structure. Horizontal arm **105** and upright support arms **107, 109** may be hollow tubing.

It is anticipated that the collapsible antenna positioning apparatus described above may be employed with a variety of antennas, including without limitation, rigid, semi-rigid and inflatable antennas. For an example of such inflatable antennas please see U.S. Pat. No. 6,963,315, to Gierow, et al, which is incorporated herein by reference. An inflatable antenna as contemplated herein is essentially a two-chamber, gas-filled sphere where a partition between the two chambers is maintained the shape of a parabolic dish, or lenticular. The partition reflects energy to or from a feed horn assembly mounted in the surface of the sphere. The parabolic shape of the reflector may be maintained by having higher air pressure in the chamber on the reflecting side of the partition, than in the chamber on the opposing side.

In an embodiment where the positioning apparatus is coupled with such an inflatable antenna, a blower apparatus **111** may be mounted to either or both support arms with piping for communicating gas from the blower apparatus into the inflatable antenna chamber or chambers. In the instance that upright support arms are formed from hollow tubing, piping may be housed within the upright support arms.

Upright supports could also be further articulated to further minimize stowed volume. With reference to FIG. 2A, upright support **201** is shown comprising a plurality of columns **203** connected end-to-end by hinges **204** that are lockable in the extended position. A cross member **205** is hingedly attached to one of the columns **203** at a point generally midway between the outer end and the base **103**. Tension members **211**, which may be a unitary piece or separate pieces, extend from the outer end of the extended columns and is secured to the base **103** to provide compression tension on the columns. Tension members **211** may be comprised of wire, cable, ribbon, or the like. FIG. 2B shows the upright support **201** is a partially stowed position. Column hinges **204** are configured to pivot in opposite directions to each other. This results in an "accordion" fold of the column components **203**. Cross mem-

bers **205** are likewise pivotally connected to column member in order to fold back upon column the column member as shown in the figure.

Further embodiments provide an apparatus for controlling the position of inflatable antennas used in communication with geo-stationary satellites. Referring to FIG. 3, first and second support members **301, 303** are pivotally connected to either pole **302, 304** of an inflatable antenna **101** to allow rotation of the pivot points about the poles **302, 304**, with first support member **301** being longer than second support **303** member so that when the antenna **101** is mounted, its rotational axis **305** is parallel with the earth's rotational axis. A first support member **301**, here shown pivotally connected to an upper pivot **302**, is mounted with a rotational drive actuator **307** for driving rotation of the antenna. The drive actuator rotates a gear **309** which is engaged with a ring gear **311** affixed to the antenna surface concentrically about the pole pivot **302**. Rotation of the gear by the drive actuator therefore results in rotation of the ring gear and, thus, rotation of the antenna globe.

It should be noted that although support members **301, 303** are shown in the figure to be solid triangular members, support members may be any shape or dimension that provides mounting support for the antenna. For example, support members could be tripodal, or tetrapodal. Further, support members could be adjustable in height so that rotational axis of the antenna may be maintained parallel with the earth's rotational axis. Support members may also be collapsible, and may be the type described with reference to FIG. 2A, and 2B above.

Another exemplary embodiment of a positioning system for use with satellite tracking antennas is shown in FIG. 4. Inflatable antenna **101** is shown again oriented such that its rotational axis **305** is parallel with the earth's rotational axis. First and second support members **401, 402**, in this example are implemented with tripods, and are pivotally attached to the poles **302, 304** of the antenna's rotational axis. In this embodiment, drive actuator **307** is mounted in the legs of first support member **401** and rotationally drives a pulley or a gear **405** that is engaged with a drive cable **407**, which could also be a timing chain or the like. The drive cable has opposing ends that are attached to areas of the surface on opposing sides of the inflatable antenna **101**. A plurality of cable guides **411** is attached to the surface of the antenna in configuration to guide the drive cable **407**.

In either of the embodiments described with reference to FIGS. 3 and 4, the inflatable antenna **101** may be mounted with a structure for support of instrumentation such as an inclinometer and a compass. For example, FIG. 4 shows an instrumentation tripod **412** attached to the surface of the antenna **101** in which is suspended such instrumentation.

In a further embodiment shown in FIG. 5, a less rigid and more portable version is disclosed. The inflatable antenna **101** rests directly on the ground, or floor. The rotational axis **305** is kept parallel with the earth's rotational axis with stays **503, 505**, which may be achieved with cables, anchored to the ground. The cables **503, 505** are attached to the respective poles **302, 304** to allow pivoting about the rotational axis **305**. This may be achieved in a variety of ways known in the relevant arts. A drive actuator **307** is disposed to one side of the apparatus and rotates a pulley or gear **509** that engages a looped drive cable **507**, or timing chain or belt. The drive cable **507** extends to loop around a **302** pole of the antenna **101** and is attached to the surface thereof. The drive actuator **307** rotates the pulley or gear **509** engaged with the cable **507** which pulls the cable and, thus, rotates the antenna. Again, drive actuator **307** may include a force amplifier.

FIG. 6 shows yet another embodiment of a positioning system 60 for an inflatable antenna 101. In this case, the antenna is controlled in elevation as well as azimuth, similar to the embodiment described with reference to FIG. 1. Horizontal arm 601 is a generally box-shaped hollow structure at either end of which is attached hinges 603, 605. Hinges 603, 605 are also attached to upright support members 607, 609. Upright support members 607, 609 are shown in this example as curved box structures and may also be hollow. Each upright support member 607, 609 may optionally include a second set of hinges 611, 613 to further articulate the structure. It will be noted that the horizontal arm hinges 603, 605 enable pivoting of the upright support members in the horizontal plane, and the upright support member hinges 611, 613 enable pivoting of the attachment assembly structure in the vertical plane. Each of these hinged connections is also preferably lockable, using a pin and hasp combination, clasps, clamps, or any suitable means to insure that once in the extended deployed position, the structure does not collapse at the hinge points.

Mounted to the inward side of each upright support member 607, 609 is a journal bearing 615, 617 for allowing pivoting in the elevation plane. Each journal bearing 615, 617 supports an attachment mount support 619, 621 in parallel offset from the axis of the journal bearing. In some embodiments, attachment mount support 619, 621 may be a second journal bearing. Each attachment mount support 619, 621 then supports antenna structural interface means 115, 117. The purpose behind providing this offset attachment point is so that the interface structures on the antenna sphere surface do not interfere with the partition, illustrated in the figure in dashed lines at 608, within the sphere. In other words, the partition which acts as the parabolic reflector may be attached within the sphere and the equator thereof. The offset attachment points permit attachment of the sphere to the upright supports while providing a pivot points that define the axis of rotation for the sphere in the elevation plane.

Horizontal arm 601 is pivotally mounted to azimuth drive assembly 102 mounted upon a base 103. Azimuth drive assembly 102 rotates horizontal arm 601 and thus positions the apparatus and the antenna in the azimuth plane. In this example, an elevation drive assembly 612 is mounted within horizontal arm 601 and is connected to a pulley, or gear, which is engaged with a single or a pair of cables, or chains 604, 606. The free ends of the cables 604, 606 are connected to the surface of the sphere, through loops or hooks, or the like. Optionally, cable attachment points may be located roughly opposite each other on the sphere. In operation, cables should be of a length and the attachment points located to result in the least amount of slack possible. This stabilizes the sphere, and thus the parabolic reflector, in the elevation plane. In operation, elevation drive assembly rotates the pulley which pulls the cable in a given direction, or in the case of using two cables, the pulley pulls one cable. This action rotates the sphere about its axis in the elevation plane.

In all of the cases discussed hereinabove, the drive actuators may be achieved with off-the-shelf drive mechanisms such as those used for driving the positioning of telescopes. Those skilled in the relevant arts will appreciate that drive mechanism is reversible, able to provide clockwise and counter-clockwise torque when commanded. This may be accomplished in many ways known in the arts. The motor itself may be commanded to operate with reverse polarity. Alternatively, reversing direction of pull may be achieved mechanically.

Control of the drive mechanisms and other functions of the antenna positioning system may be implemented with a computer system (not shown) configured with program logic to

cause the computer system to execute the functions required. For example, with respect to the drive mechanism, control logic for the computer would direct energizing and de-energizing of the drive mechanism when required to rotate the antenna to the required position.

The detailed description that follows is presented largely in terms of processes and symbolic representations of operations performed by conventional computers, including computer components. A computer may be any microprocessor or processor (hereinafter referred to as processor) controlled device, such as, by way of example, personal computers, workstations, servers, clients, mini-computers, main-frame computers, laptop computers, a network of one or more computers, mobile computers, portable computers, handheld computers, palm top computers, set top boxes for a TV, interactive televisions, interactive kiosks, personal digital assistants, interactive wireless devices, mobile browsers, or any combination thereof. The computer may possess input devices such as, by way of example, a keyboard, a keypad, a mouse, a microphone, or a touch screen, and output devices such as a computer screen, printer, or a speaker.

The computer may be a uniprocessor or multiprocessor machine. Additionally, the computer includes memory such as a memory storage device or an addressable storage medium. The memory storage device and addressable storage medium may be in forms such as, by way of example, a random access memory (RAM), a static random access memory (SRAM), a dynamic random access memory (DRAM), an electronically erasable programmable read-only memory (EEPROM), a programmable read-only memory (PROM), an erasable programmable read-only memory (EPROM), hard disks, floppy disks, laser disk players, digital video disks, compact disks, video tapes, audio tapes, magnetic recording tracks, electronic networks, and other devices or technologies to transmit or store electronic content such as programs and data.

The computer executes an appropriate operating system such as Linux, Unix, Microsoft® Windows® 95, Microsoft® Windows® 98, Microsoft® Windows® NT, Apple® MacOS®, IBM® OS/2®, and later versions thereof. The computer may advantageously be equipped with a network communication device such as a network interface card, a modem, or other network connection device suitable for connecting to one or more networks.

The computer, and the computer memory, may advantageously contain program logic or other substrate configuration representing data and instructions, which cause the computer to operate in a specific and predefined manner as described herein. The program logic may advantageously be implemented as one or more modules. The modules may advantageously be configured to reside on the computer memory and execute on the one or more processors. The modules include, but are not limited to, software or hardware components that perform certain tasks. Thus, a module may include, by way of example, components, such as, software components, processes, functions, subroutines, procedures, attributes, class components, task components, object-oriented software components, segments of program code, drivers, firmware, micro-code, circuitry, data, and the like.

The program logic conventionally includes the manipulation of data bits by the processor and the maintenance of these bits within data structures resident in one or more of the memory storage devices. Such data structures impose a physical organization upon the collection of data bits stored within computer memory and represent specific electrical or magnetic elements. These symbolic representations are the

means used by those skilled in the art to effectively convey teachings and discoveries to others skilled in the art.

The program logic is generally considered to be a sequence of computer-executed steps. These steps generally require manipulations of physical quantities. Usually, although not necessarily, these quantities take the form of electrical, magnetic, or optical signals capable of being stored, transferred, combined, compared, or otherwise manipulated. It is conventional for those skilled in the art to refer to these signals as bits, values, elements, symbols, characters, text, terms, numbers, records, files, or the like. It should be kept in mind, however, that these and some other terms should be associated with appropriate physical quantities for computer operations, and that these terms are merely conventional labels applied to physical quantities that exist within and during operation of the computer.

It should be understood that manipulations within the computer are often referred to in terms of adding, comparing, moving, searching, or the like, which are often associated with manual operations performed by a human operator. It is to be understood that no involvement of the human operator may be necessary, or even desirable. The operations described herein are machine operations performed in conjunction with the human operator or user that interacts with the computer or computers.

It should also be understood that the programs, modules, processes, methods, and the like, described herein are but an exemplary implementation and are not related, or limited, to any particular computer, apparatus, or computer language. Rather, various types of general purpose computing machines or devices may be used with programs constructed in accordance with the teachings described herein. Similarly, it may prove advantageous to construct a specialized apparatus to perform the method steps described herein by way of dedicated computer systems with hard-wired logic or programs stored in nonvolatile memory, such as, by way of example, read-only memory (ROM).

As described above and shown in the associated drawings, the present invention comprises an apparatus for an antenna positioning system. While particular embodiments of the

invention have been described, it will be understood, however, that the invention is not limited thereto, since modifications may be made by those skilled in the art, particularly in light of the foregoing teachings. It is, therefore, contemplated that any claims issuing in an ensuing patent will cover any and all such modifications that incorporate those features or those improvements that embody the spirit and scope of the present invention.

We claim:

1. An apparatus for positioning and controlling a spherical, inflatable antenna comprising:
 - a driven rotating table disposed in the horizontal plane;
 - a horizontal arm member mounted to said table, said arm member having first and second ends;
 - a first and second upright support members hingedly connected to said first and second ends, respectively, said first and second upright support members including journal bearings attachable to the surface of the inflatable antenna.
2. The apparatus of claim 1, further comprising an elevation drive actuator for selectively imparting rotation, mounted to said first upright support member, and coupled to said journal bearing mounted thereto for provided selective rotation of the antenna in the vertical plane.
3. The apparatus of claim 2, further comprising a blower mounted to said second upright support member.
4. The apparatus of claim 1, further comprising:
 - an elevation drive assembly comprising:
 - a motor for providing selective rotation;
 - a line having first and second ends attached to opposing sides of the lower hemisphere of the antenna, said line being rotatably engaged with said motor.
5. The apparatus of claim 4, wherein said upright support members include hinged upper portions.
6. The apparatus of claim 1, wherein said upright support members are articulated.
7. The apparatus of claim 6, further comprising first and second cross members hingedly coupled to said upright support member.

* * * * *