



US007775002B2

(12) **United States Patent**
Puchniak

(10) **Patent No.:** **US 7,775,002 B2**
(45) **Date of Patent:** **Aug. 17, 2010**

(54) **PORTABLE HURRICANE AND SECURITY WINDOW BARRIER**

(76) Inventor: **John Puchniak**, 153 Andover St., Suite 107, Danvers, MA (US) 01923

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 245 days.

(21) Appl. No.: **11/982,539**

(22) Filed: **Nov. 2, 2007**

(65) **Prior Publication Data**

US 2008/0127597 A1 Jun. 5, 2008

Related U.S. Application Data

(60) Provisional application No. 60/857,863, filed on Nov. 10, 2006.

(51) **Int. Cl.**
E06B 3/30 (2006.01)

(52) **U.S. Cl.** **52/202**; 52/584.1; 52/656.7; 52/799.1; 49/57; 49/63; 49/463; 160/135

(58) **Field of Classification Search** 52/202, 52/203, 656.7, 656.8, 588.1, 584.1, 799.1; 49/50, 57, 63, 67, 169, 463, 464; 160/371, 160/135; 206/325

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 173,722 A * 2/1876 Hayes 52/633
- 768,514 A * 8/1904 Christen 52/656.7
- 1,121,756 A 12/1914 Patton
- 1,449,714 A * 3/1923 Williams 206/509
- 1,581,776 A * 4/1926 Altschul 211/4
- 1,661,003 A * 2/1928 Miller 160/229.1
- 1,782,203 A * 11/1930 William 160/379
- 1,791,676 A * 2/1931 Landine 160/229.1
- 1,859,974 A * 5/1932 Kroenke 160/97
- 1,902,949 A 3/1933 Condon

- 1,986,716 A * 1/1935 Downey 206/511
- 2,053,254 A * 9/1936 Fairchild et al. 52/799.1
- 2,145,431 A * 1/1939 Panza 160/229.1
- 2,238,355 A * 4/1941 Whitenack 52/601
- 2,294,966 A * 9/1942 Dreyfus 428/131
- 2,432,047 A * 12/1947 Sterick et al. 160/179
- 2,474,382 A * 6/1949 Smith 449/42
- 2,699,825 A * 1/1955 Stritzler 160/90
- 3,452,477 A * 7/1969 Sassano 49/116
- 3,583,100 A * 6/1971 Catalano 49/50
- 3,596,701 A * 8/1971 Cowan 160/135
- 3,616,838 A 11/1971 Barr
- 3,678,558 A * 7/1972 Fredericks 29/897.15
- 3,948,431 A * 4/1976 Niimi et al. 228/173.6
- 4,325,203 A 4/1982 Wicks
- 4,384,428 A * 5/1983 Cox 49/56
- 4,454,691 A * 6/1984 Mitchell 52/202
- 4,523,415 A * 6/1985 Rosen 52/220.2

(Continued)

FOREIGN PATENT DOCUMENTS

JP 9-13838 * 1/1997

(Continued)



Primary Examiner—Robert J Canfield

(74) *Attorney, Agent, or Firm*—Hamilton, Brook, Smith & Reynolds, P.C.

(57) **ABSTRACT**

An apparatus for covering an opening of a building comprising a plurality of rectangular panels. The panels are sized such that when they are stacked for storage, the panels nest together.

20 Claims, 9 Drawing Sheets



US 7,775,002 B2

Page 2

U.S. PATENT DOCUMENTS

4,790,609	A *	12/1988	Guy	312/117	6,079,475	A *	6/2000	Morgan et al.	160/371
4,993,187	A *	2/1991	Schweiss et al.	49/56	6,109,331	A *	8/2000	Story, Jr.	160/371
5,005,315	A	4/1991	Jackson, Jr.			6,176,050	B1	1/2001	Gower		
5,105,868	A	4/1992	Riise			6,230,455	B1 *	5/2001	Arehart et al.	52/202
5,347,775	A *	9/1994	Santos	52/202	6,263,949	B1	7/2001	Guthrie, Jr.		
5,410,841	A	5/1995	Harris et al.			6,341,455	B1	1/2002	Gunn		
5,431,210	A *	7/1995	Nelson et al.	160/135	6,345,476	B1 *	2/2002	Hill	52/202
5,446,996	A	9/1995	Lamont			6,745,515	B1 *	6/2004	Chen	49/169
5,575,321	A	11/1996	Currier			6,814,127	B2	11/2004	Tagtow et al.		
5,626,926	A *	5/1997	Roberts	428/14	7,134,254	B1 *	11/2006	Van Gelder	52/793.1
5,651,221	A *	7/1997	Golen	52/202	2006/0010792	A1	1/2006	Biggers		
5,787,642	A *	8/1998	Coyle et al.	49/61						
5,832,666	A *	11/1998	Flack et al.	49/67						
5,996,292	A	12/1999	Hill et al.								

FOREIGN PATENT DOCUMENTS

JP 2000110465 4/2000

* cited by examiner






FIG. 1






FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 7




FIG. 8




FIG. 9




FIG. 10A




FIG. 10B




FIG. 11A




FIG. 11B

1

PORTABLE HURRICANE AND SECURITY WINDOW BARRIER

RELATED APPLICATION

This application claims the benefit of U.S. Provisional Application No. 60/857,863, filed on Nov. 10, 2006. The entire teachings of the above application are incorporated herein by reference.

BACKGROUND

Strong winds from hurricanes or tropical storms carry debris, which can cause heavy damage to windows and glass doors. Building owners typically cover windows and doors when a hurricane or tropical storm approaches with a barrier to prevent debris from hitting the glass surfaces. In the past, these barriers have either been disposable (e.g., plywood) or unsightly (e.g., a rollaway or slideaway screen permanently mounted to the door or window).

SUMMARY

Embodiments of the invention feature a portable, quick mounting, easily removable, and convenient-to-store security barrier that can protect an opening to a building, such as a window or sliding glass door, from breakage due to the hazard of flying debris caused by powerful winds generated by hurricanes and tornadoes. In conjunction with these catastrophes, an advantage of the invention is that it also offers a security benefit as a deterrent to home invasion by restricting breaking and entering through windows or sliding glass doors.

An embodiment of the invention comprises multiple panels that can be nested together when stacked for storage. The panels are easily and quickly installed and removed from a building window or other opening. In some embodiments, the panels are installed by inserting one end into slots attached to the building and installing the other end via anchoring bolts to a surface of the building. The panels may install in the slots via pins attached to the panels and the anchoring bolts may pass through the flanges on an opposite side of each panel. In some embodiments, the panels may be connected together via flanges and pins, such as clevis pins.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing will be apparent from the following more particular description of example embodiments of the invention, as illustrated in the accompanying drawings in which like reference characters refer to the same parts throughout the different views. The drawings are not necessarily to scale, emphasis instead being placed upon illustrating embodiments of the present invention.

FIG. 1 illustrates an embodiment in which three panels are installed in front of a sliding door of a building;

FIG. 2A shows two panels of the embodiment of FIG. 1 in a perspective view;

FIG. 2B shows an enlarged view of a panel foot of the embodiment of FIG. 2A;

FIGS. 3A-3B show the top portion of a panel and a side view of a pin of the embodiment of FIG. 1;

FIGS. 4A-4C illustrate a slotted rail according to the embodiment of FIG. 1;

FIG. 5 illustrates the panels of the embodiment of FIG. 1 in an uninstalled and nested configuration for storage;

2

FIG. 6A illustrates an optional variation of the embodiment of FIG. 1 wherein one of the panels incorporates an escape door;

FIG. 6B shows an enlarged view of a panel foot of the embodiment of FIG. 6A;

FIG. 6C shows an enlarged side view of a triangular wedge pin of the embodiment of FIG. 6A;

FIG. 7 illustrates a side view of the optional door shown in FIG. 6;

FIG. 8 illustrates a second embodiment in which three panels of equal width are installed in front of an opening of a building;

FIG. 9 illustrates the panels of the embodiment of FIG. 8 in an uninstalled and nested configuration for storage;

FIGS. 10A-10B illustrate a bracket plate of a third embodiment configured to be mounted to the side of a building; and

FIGS. 11A-11B illustrate a bracket of the embodiment of FIGS. 10A-10B that interfaces with the bracket plate.

DETAILED DESCRIPTION

FIG. 1 illustrates one embodiment of the present invention **100** in an installed configuration. In this embodiment, three panels **102**, **104**, **106** cover a sliding glass door **108** when installed. Each panel **102**, **104**, **106** includes a rectangular frame with a screen **122** covering the open area inside the frame. Each panel has a pair of pins **110** at the ends of a top side and a pair of anchoring flanges **112** at the ends of a bottom side. The pins **110** interface with a rail **118** installed in the wall **120** above the sliding door **108** and the anchoring feet interface with the ground **116** via bolts **114**. Note that the panels **102**, **104**, **106** may alternatively be installed with the pins **110** (and rail **118**) at the bottom and the anchoring flanges **112** and bolts **114** at the top being installed in the wall **120** of the building. While the embodiment shown in FIG. 1 has three panels, other embodiments may have a fewer or greater number of panels.

Each of the panels may be constructed from a number of materials, such as high-impact plastic, aluminum, steel or stainless steel, or a combination of materials. Materials that offer high strength and relatively low weight are preferable, but not required.

FIG. 2A illustrates panels **104**, **106** in accordance with an embodiment of the present invention in perspective view. As can be seen, the pins **110** extend directly above each panel **104**, **106** on frame elements **202** and **210**. The anchoring feet **112**, enlarged in FIG. 2B, extend from each panel **104**, **106** on the opposite frame elements **206** and **214**. The anchoring feet **112**, however, extend out to the side of each panel **104**, **106**. In this embodiment, the anchoring feet **112** extend from each panel **102**, **104**, **106**. Panels **104** and **106** in this embodiment also have optionally included locking flanges **218** on frame elements **204**, **208**, and **216**. The locking flanges **218** are connected via pins, such as clevis pins, or bolts (not shown) after the panel pins **110** and anchoring flanges **112** have been installed. Two locking flanges **218** between each panel are shown in this embodiment, but more or fewer flanges may be used.

FIG. 3A illustrates pins **110** of panel **102** in accordance with an embodiment of the present invention. FIG. 3B shows that each pin **110** of the embodiment has a triangular cross-section with angled faces **302** and **304**. The angled faces **302** and **304** converge at an apex **312**.

FIGS. 4A-4C illustrate the rail **118** with slots **402** in accordance with an embodiment of the present invention. The rail **118** has slots **402**, which have angled faces **404** and **406**, which match the angled faces **304** and **306** of the pins **110**.

The angled faces **302**, **304**, **404**, and **406** firmly hold the pins **110** in the slots **402** when the pins **110** are fully inserted in the slots **402**. However, the angled faces **302**, **304**, **404**, and **406** also allow the panels **102**, **104**, **106** to be pivoted about the apex **312** of each pin **110** when the pins **110** are partially inserted in the slots **402**.

FIGS. **4B** and **4C** illustrate a rail **118** made of solid material, wherein the slots **402** are formed by cutting out portions of the solid material. Alternatively, the rail **118** could be formed of a tubular material, such as a stainless steel or aluminum tube wherein the tube wall has a square cross-section. The slots **402** would be formed by cutting out portions of tube wall. The pins **110**, in this alternative embodiment, would be inserted through the slots **402** and be contained within the hollow space of the tubular rail **118**.

Returning to FIG. **2**, since the anchoring flanges **112** and the locking flanges **218** extend from each panel **104** and **106**, neatly stacking the panels would be difficult if the panels were all the same size because certain features that protrude from each panel **102**, **104**, **106**, such as anchoring flanges **112**, would interfere with each other, preventing the panels **102**, **104**, **106** from resting flat against each other. However, the three panels illustrated in the embodiment in FIG. **1** are each a different width. The top frame element **306** and bottom frame element **312** of the first panel **102** (as shown in FIG. **6**) are longer than the top frame element **202** and bottom frame element **206** of the second panel **104** (as shown in FIG. **2**), which are longer than the top frame element **210** and bottom frame element **214** of the third panel **106** (as shown in FIG. **2**).

FIG. **5** illustrates the three panels **102**, **104**, **106** of the described embodiment stacked together in a nested configuration **500** for storage. Because panel **104** is narrower than panel **102**, the anchoring flanges **112** of panel **104** are completely within the span between the anchoring flanges **112** of panel **102**. Likewise, because panel **106** is narrower than panel **104**, the anchoring flanges **112** of panel **106** are completely within the span between the anchoring flanges **112** of panel **104**. Note that the panels' screens **122** (not shown in FIG. **5**) must be set within each panel so that they do not interfere with the interlocking flanges **218** when the panels are nesting.

FIGS. **6A-C** and **7** illustrate an escape door **602** that may be optionally installed in the above-described embodiment. The escape door **602** is best located in the largest panel **102**, but may be located on any panel **102**, **104**, **106**. The escape door **602** comprises its own frame with hinges **606** on one side and a locking latch **604** on the other side. The panel is illustrated as being located completely on the screen **122**, but may also extend to the frame elements of the panel **102**, **104**, or **106** on which it is mounted. For example, the hinges **606** can be mounted to frame element **308** of panel **102** and the latch may interface with frame element **310**.

FIG. **7** also illustrates the anchoring flanges **112** attached to the bottom frame element of panel **102** in this embodiment. Bolts **114** extend through the portion of the anchoring flanges **112** extending from the panel. Optionally, the bolts may incorporate a security interface that requires a unique tool, such as a keyed wrench or screwdriver, to remove the bolts, thereby increasing the security provided by the screen.

Typically, the anchoring flanges **112** would rest on a floor surface, such as a concrete slab, and the bolts would interface with corresponding holes in the floor surface. FIGS. **10A-B** and **11A-B** illustrate an alternative embodiment in which the anchoring flanges mount to a bracket. FIGS. **10A** and **10B** illustrate a bracket plate **1000** that would be permanently mounted above or below a window or a door. The bracket plate **1000** is mounted to the wall with screws or bolts (not

shown) through holes **1004**. The bracket plate has two flanges **1006**, **1008**. In the illustrated embodiment, flange **1008** is longer than flange **1006**. However, flanges **1006**, **1008** may be equal in size.

FIGS. **11A** and **11B** illustrate a bracket **1100** that interfaces with the bracket **1000** via slider plate **1102** and tabs **1104**, **1106**. Tab **1104** interfaces with flange **1006** and tab **1106** interfaces with flange **1008**. The brackets **1100** slide in bracket plate **1000** to be positioned beneath anchoring flanges **112** of a panel. The flat surface of an anchoring flange **112** is then adjacent to plate **1108** of bracket **1100**. Bolts **114** are passed through the anchoring flange **112** and into holes **1110** of bracket **1100**. Such a bracket system, or an equivalent, allows a panel to be mounted at some height above the ground.

The embodiment described above with respect to FIGS. **10** and **11** illustrates a panel system in which the pins **110** are mounted above the opening to be protected and the anchoring flanges **112** are mounted below the opening. As mentioned earlier, the panels optionally can be mounted upside-down, wherein the pins **110** are mounted beneath the opening to be protected and the anchoring flanges **112** are mounted above the opening. In such an alternative embodiment, rail **118** is mounted below the opening. Pins **110** are located at the bottom of panels **102**, **104**, **106** and are lowered into slots **402**. The panels **102**, **104**, **106** are then pivoted about the pins **110** to bring the anchoring flanges **112** into position for fastening to the building. In conjunction with the embodiment shown in FIGS. **10** and **11**, the bracket plate **1000** and brackets **1100** can be located above the building opening to be protected and anchoring flanges **112** would bolt to the brackets **1100**, which are located above. Alternatively, the anchoring flanges, in this embodiment, can be oriented such that they rest against the side of the building and bolt directly to an interface (not shown) mounted to the side of the building.

FIGS. **8** and **9** illustrate an alternative embodiment **800** of the present invention. Like the first embodiment described above, this embodiment utilizes three separate panels **802**, **804**, and **806**. However, the three panels include identical dimensions of height and width. In this embodiment, the pins **110** are positioned in the ends of top frame elements **804** and the anchoring flanges **810**, **812**, and **814** are located on the opposite bottom frame elements **816**, **818**, and **820**. However, the anchoring flanges **810**, **812**, and **814** are located at different positions on each panel **802**, **804**, and **806**. On panel **802**, the anchoring feet **810** are located at the ends of frame element **816**. On panel **804**, the anchoring feet **812** are located a distance inboard from the ends of frame element **818**. On panel **806**, the anchoring feet **814** are located a further distance inboard from the ends of frame element **820**.

FIGS. **8** and **9** also show optionally-included locking flanges **806** and **808** which differ from the first embodiment in two ways. First, the flanges sit completely outside the perimeter of each panel **802**, **804**, and **806**. Second, the locking flanges **806** and **808** vary in location between each panel. FIG. **8** shows locking flanges **806** between panels **802** and **804** and locking flanges **808** between panels **804** and **806**. There are two locking flange pairs between each pair of panels. The locking flanges **806** between panels **802** and **804** are each higher than the respective locking flanges **808** between panels **804** and **806**.

FIG. **9** shows that when panels **802**, **804**, and **806** are in a stacked configuration **900**, they nest with the anchoring flanges **812** within anchoring flanges **810** and anchoring flanges **814** within anchoring flanges **812**. The locking flanges **806** and **808** rest outside the perimeter of each panel **802**, **804**, **806**. Also, because the locking flanges **806** and **808**

5

are located on panels **802**, **804**, **806** at different heights, they do not interfere with each other when the panels **802**, **804**, and **806** are in the nested configuration **900**.

While this invention has been particularly shown and described with references to example embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the scope of the invention encompassed by the appended claims.

What is claimed is:

1. An apparatus comprising:
a plurality of rectangular panels installable side by side to cover an opening of a building;
the first panel comprising a rectangular frame and a shielding material extending across the rectangular frame;
each subsequent panel comprising a rectangular frame and a shielding material extending across the rectangular frame, wherein each subsequent panel is narrower than a preceding panel such that the first and subsequent panels may be nested together when disassembled; and
wherein each panel has two or more pins fixedly attached at ends of a first frame element and anchoring flanges attached at ends of a second frame element opposite the first frame element.
2. The apparatus of claim 1 wherein the shielding material of the plurality of rectangular panels is arranged as a honeycomb.
3. The system of claim 1 wherein the screening material of the plurality of rectangular panels is arranged as a solid sheet with a series of openings.
4. The apparatus of claim 1 wherein the shielding material of one of the plurality of rectangular panels includes a hinged portion configured to allow access to the opening of the building without removing the panel.
5. The apparatus of claim 1 wherein the shielding material and frame elements of the plurality of rectangular panels are made of at least one of:
aluminum;
stainless steel; and
high-impact molded plastic.
6. The apparatus of claim 1 further comprising anchoring points fixed in relation to the building and configured to interface with the two or more anchoring flanges; and
wherein the anchoring points interface with the two or more anchoring flanges by bolts fed through coaxially aligned holes in the anchoring points and the anchoring flanges.
7. The apparatus of claim 1 further comprising slots configured to interface with the two or more pins.
8. The apparatus of claim 7 wherein the slots are contained within a common rail mounted parallel to one edge of the opening of the building.

6

9. The apparatus of claim 7 wherein the two or more pins are tapered to allow the panels to pivot about the interface of the pins and the slots.

10. A system comprising:

- a plurality of rectangular panels, which are installable adjacent to one another to cover an opening of a building, each panel including:
frame elements at the perimeter of each panel;
a screening material extending across the frame elements;
two or more pins fixedly attached to a first frame element;
two or more anchoring flanges fixedly attached to a second frame element opposite the first frame element; and
the first and second frame elements of any panel having a different length from the remaining panels such that the panels may nest together when not installed.

11. The system of claim 10 wherein the screening material of the plurality of rectangular panels is arranged as a honeycomb.

12. The system of claim 10 wherein the screening material of the plurality of rectangular panels is arranged as a solid sheet with a series of openings.

13. The system of claim 10 wherein the screening material of one of the plurality of rectangular panels includes a hinged section configured to allow access to the building opening without removing the panel.

14. The system of claim 10 wherein the screening material and frame elements are made of at least one of:
aluminum;
stainless steel; and
high-impact molded plastic.

15. The system of claim 10 further comprising anchoring points configured to interface with the two or more anchoring flanges of each panel.

16. The system of claim 15 wherein the anchoring points interface with the two or more anchoring flanges by bolts fed through coaxially aligned holes in the anchoring points and the anchoring flanges.

17. The system of claim 10 further comprising slots configured to interface with the two or more pins of each panel.

18. The system of claim 17 wherein the slots are within a common rail mounted parallel to one edge of the opening of the building.

19. The system of claim 17 wherein the two or more pins are tapered to allow the panels to pivot about the interface of the pins and the slots.

20. The system of claim 10, wherein each panel further includes one or more locking flanges fixedly attached to frame elements adjacent to frame elements of adjacent panels when the panels are installed.

* * * * *