



US007831129B2

(12) **United States Patent**
Abe et al.

(10) **Patent No.:** **US 7,831,129 B2**
(45) **Date of Patent:** **Nov. 9, 2010**

(54) **CAPTURING APPARATUS**

2006/0029364 A1* 2/2006 Kosugi 386/68

(75) Inventors: **Tatsuro Abe**, Ome (JP); **Kuniaki Takahashi**, Fukaya (JP); **Tatsuhiko Ikehata**, Ome (JP); **Shiro Nagaoka**, Ome (JP); **Kei Tashiro**, Ome (JP); **Tsuyoshi Hagiwara**, Ome (JP)

FOREIGN PATENT DOCUMENTS

JP	11-213521	8/1999
JP	2000-115707	4/2000
JP	2002-034001	1/2002
JP	2002-199345	7/2002

(73) Assignee: **Kabushiki Kaisha Toshiba**, Tokyo (JP)

OTHER PUBLICATIONS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1100 days.

Japanese Office Action dated Dec. 22, 2009 for Appln. No. 2005-271084.

Instruction manual "DVD video recorder of product No. DMR-E500H" Matsushita Electric Industrial Co., Ltd., 2004, pp. 46-51.

(21) Appl. No.: **11/514,967**

* cited by examiner

(22) Filed: **Sep. 5, 2006**

Primary Examiner—Robert Chevalier

(65) **Prior Publication Data**

US 2007/0065098 A1 Mar. 22, 2007

(74) Attorney, Agent, or Firm—Pillsbury Winthrop Shaw Pittman, LLP

(30) **Foreign Application Priority Data**

Sep. 16, 2005 (JP) 2005-271084

(57) **ABSTRACT**

(51) **Int. Cl.**
H04N 5/91 (2006.01)

According to one embodiment, a capturing apparatus includes a capturing unit configured to capture a moving image video, a storage unit configured to store the moving image video captured by the capturing unit, an operation unit configured to include a plurality of keys used to instruct playback of the moving image video stored in the storage unit, a skip playback unit configured to play back the moving image video while skipping the moving image video at predetermined time intervals every time a predetermined operation is made on the operation unit, and a playback control unit configured to switch the time intervals skipped by the skip playback unit based on the total playback time period of the moving image video.

(52) **U.S. Cl.** **386/68; 386/67**


(58) **Field of Classification Search** 386/68, 386/67, 46, 124, 125, 107, 117
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,377,051 A * 12/1994 Lane et al. 386/81
5,703,996 A * 12/1997 Omura et al. 386/68

12 Claims, 7 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4

Button / lever \ State	Rest	During playback	During pausing	During fast -forwarding	During fast -rewinding
OK	Switch display				
OK button ▲	Play	Pause	Play		
OK button ▼	Select playback method	Stop			
OK button ◀	Previous image	One-touch replay		-	
OK button ▶	Next image	One-touch skip		-	
Jog dial left	Previous image	Fast -rewinding	Frame-by -frame reverse	Play	Continue fast -rewinding
Jog dial right	Next image	Fast -forwarding	Frame-by -frame advance	Continue fast -forwarding	Play
Zoom lever T side	Chapter display	Tone volume up			
Zoom lever W side	Thumbnail display	Tone volume down			

FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

FIG. 10




FIG. 11

1**CAPTURING APPARATUS****CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is based upon and claims the benefit of priority from Japanese Patent Application No. 2005-271084, filed Sep. 16, 2005, the entire contents of which are incorporated herein by reference.

BACKGROUND**1. Field**

One embodiment of the invention relates to a capturing apparatus for capturing a still image and a moving image.

2. Description of the Related Art

In recent years, multi-functional digital apparatuses such as digital still cameras, digital video cameras, and the like have remarkably prevailed. Various proposals for improvement of the operability of such multi-functional digital apparatuses have been made. For example, Jpn. Pat. Appln. KOKAI Publication No. 2000-115707 proposes a technique associated with playback speed control by means of the rotation angle of a dial.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

A general architecture that implements the various features of the invention will now be described with reference to the drawings. The drawings and the associated descriptions are provided to illustrate embodiments of the invention and not to limit the scope of the invention.

FIG. 1 is a perspective view showing a video capturing apparatus in a state in which a display unit is stored according to an embodiment of the invention;

FIG. 2 is a perspective view showing the video capturing apparatus in a state in which the display unit is extracted according to the embodiment;

FIG. 3 is a view for explaining a jog dial and OK button of the video capturing apparatus according to the embodiment;

FIG. 4 is a schematic block diagram showing the arrangement of the video capturing apparatus according to the embodiment;

FIG. 5 is a table for explaining a plurality of playback operations according to the embodiment;

FIG. 6 is a view showing the data structure of one MPEG moving image file;

FIG. 7 is a flowchart showing playback control according to the embodiment;

FIG. 8 is a flowchart showing $\frac{1}{20}$ skip playback control according to the embodiment;

FIG. 9 is a view for explaining the number of GOPs when the length of a file is divided into $\frac{1}{20}$ according to the embodiment;

FIG. 10 is a view for explaining a skip destination (GOP position) for an operation input by a right key or left key according to the embodiment; and

FIG. 11 is a view for explaining playback control depending on the file length to prevent playback of a moving image file as short as about several ten seconds from instantaneously ending during high-speed playback based on the rotation angle of the jog dial according to the embodiment.

DETAILED DESCRIPTION

Various embodiments according to the invention will be described hereinafter with reference to the accompanying

2

drawings. In general, according to one embodiment of the invention, a capturing apparatus comprises a capturing unit configured to capture a moving image video, a storage unit configured to store the moving image video captured by the capturing unit, an operation unit configured to include a plurality of keys used to instruct playback of the moving image video stored in the storage unit, a skip playback unit configured to play back the moving image video while skipping the moving image video at predetermined time intervals every time a predetermined operation is made on the operation unit, and a playback control unit configured to switch the time intervals skipped by the skip playback unit based on a total playback time period of the moving image video.

FIGS. 1 and 2 show an example of a video capturing apparatus according to the invention. FIG. 1 shows a state in which a display unit is stored in a storage unit provided to a main body which forms the video capturing apparatus. FIG. 2 shows a state in which the display unit is set to allow the user to watch a video displayed on it.

As shown in FIGS. 1 and 2, the video capturing apparatus comprises a main body 1. The main body 1 comprises a lens 2, electronic flash 3, still image record button 4, display unit 5, moving image record button 6, jog dial 7, arrow keys 8, menu button 9, zoom bar 10, mode lever 11, power button 12, and the like.

Furthermore, the main body 1 comprises a storage unit 21, which can store the display unit 5. The display unit 5 is configured to be movable, and can be extracted from the storage unit 21 to adjust its display screen to an arbitrary angle. The display unit 5 comprises an LCD (liquid crystal display) 51 and loudspeaker 52.

FIG. 3 is a view for explaining details of the jog dial and an OK button.

As shown in FIG. 3, the jog dial 7 is formed into an annular shape. This jog dial 7 is configured to be rotatable clockwise and counterclockwise. Note that the shape of the jog dial 7 is not limited to the annular shape but it may be a polygonal annular shape.

Furthermore, the circular arrow keys 8 are arranged inside the jog dial 7. The arrow keys 8 comprise an OK key 81 at the central position, an UP key 82 at the up position, a DOWN key 83 at the down position, a right key (direction key) 84 at the right position, and a left key (direction key) 85 at the left position.

FIG. 4 is a schematic block diagram showing the arrangement of the video capturing apparatus that has been explained with reference to FIGS. 1 to 3.

As shown in FIG. 4, the video capturing apparatus comprises a CCD 101, a signal processing circuit 102, an encoder (JPEG/MPEG) 103, a memory 104, an HDD 105, a memory card 106, a decoder 107, an LCD driver 108, the LCD 51, a LAN controller 110, a USB controller 111, a LAN terminal 112, a USB terminal 113, a CPU 114, and the like. These components are connected via a bus 115.

In response to the operation of the still image record button 4, the CCD 101 converts light (still image) obtained via the lens 2 into an electrical signal. Or in response to the operation of the moving image record button 6, the CCD 101 converts light (moving image) obtained via the lens 2 into an electrical signal. The signal processing circuit 102 converts the electrical signal output from the CCD 101 into a digital signal. The encoder 103 encodes the digital signal of the still image into an image signal compliant to JPEG. Or the encoder 103 encodes the digital signal of the moving image into an image signal compliant to MPEG. The HDD 105 stores an image signal provided via the memory 104. The detachable memory card 106 similarly stores an image signal provided via the

memory **104**. The decoder **107** decodes an image signal provided via the memory. The LCD driver **108** controls to drive the LCD **51** based on the decoded image signal, and outputs the image signal onto the LCD.

Upon playback of a recorded image, the decoder **107** decodes an image signal provided from the HDD **105** or memory card **106** via the memory **104**. The LCD driver **108** controls to drive the LCD **51** based on the decoded image signal, and outputs the image signal onto the LCD **51**.

When an image recorded in the HDD **105** or memory card **106** is to be transferred to an external apparatus (PC or the like) or an image is received from the external apparatus, such image is exchanged from the USB terminal **113** via the USB controller **111**. Also, an encoded image can be directly exchanged with an image recording and playback apparatus (e.g., DVD recorder) without the intervention of the external apparatus (PC or the like).

In general, when an image is to be transferred to a DVD recorder, an encoded moving image is decoded on the transmission side (the video capturing apparatus side), and is output as an analog signal via a video terminal or S terminal. Then, the analog is re-encoded and saved on the reception side (the moving image recording and playback apparatus side). With this method, one hour is required to record an image which was recorded for one hour on a DVD or the like.

However, this video capturing device can transfer an encoded image as streaming data intact to the image recording and playback apparatus via the network, as described above. With this data transfer, a transfer time $\frac{1}{10}$ or less of the real recording time can be achieved although it depends on the compression ratio upon encoding. In addition, high image quality can be maintained since the image is not re-encoded. For example, when only the transfer time about $\frac{1}{10}$ of the real recording time is required, a moving image which was recorded for one hour can be recorded on another recording medium in about six minutes. When a LAN is assumed as the network, image data is exchanged using the LAN terminal **112** via the LAN controller **110**. Note that data to be transferred can be audio data in addition to a moving image and still image.

The playback operation will be described below with reference to FIG. **5**. When a playback mode is selected by the mode lever **11**, a list of playback items (e.g., thumbnails of moving images) is displayed on the display unit. The user selects a playback item using the jog dial **7**, and inputs a playback start instruction using the arrow keys **8** (up key **82**).

Moving image playback includes the following modes, and these playback operations are as shown in FIG. **5**.

1. Normal playback (equal-speed playback)
2. Reverse Playback (equal-speed reverse playback)
3. High-speed playback faster than normal playback (fast-forwarding, one-touch skip, etc.)
4. High-speed reverse playback faster than reverse playback (fast-rewinding, one-touch replay, etc.)
5. Frame-by-frame advance playback
6. Frame-by-frame reverse playback

Note that the reverse playback, high-speed playback, high-speed reverse playback, frame-by-frame advance playback, and frame-by-frame reverse playback will be generically referred to as trick playback. Since the aforementioned video capturing apparatus reads out image data from a randomly accessible medium such as the HDD **105**, memory card **106**, or the like, an image that the user wants to watch can be easily and quickly retrieved.

The jog dial **7** outputs information of a rotation amount (rotation angle) and rotation direction to the CPU **114**, which controls the entire system, in response to its rotation. For

example, the jog dial **7** outputs pulses according to a predetermined rotation angle. For example, when the jog dial **7** is rotated through n° , it outputs one pulse. The CPU **114** counts the number of pulses per unit time, and calculates a rotation angle (rotation velocity) per unit time. In this way, the CPU **114** acquires the rotation information including the rotation amount (rotation angle), rotation direction, rotation velocity, and the like of the jog dial **7** during execution of the playback mode, and controls the playback operation based on this rotation information. The arrow keys **8** inform the CPU **114** of pressing of the OK key **81** at the central position, that of the UP key **82** at the up position, that of the DOWN key **83** at the down position, that of the right key **84** at the right position, and that of the left key **85** at the left position. The CPU **114** controls the playback operation based on pressing of each key of the arrow keys **8**.

As can be seen from FIG. **5**, when the jog dial **7** is rotated upon moving image playback, the playback speed can be finely varied. However, upon playing back an image which was recorded for a long period of time, when a time period from an image that the user is currently watching until an image that the user wants to watch is long, a relatively long period of time is required even by highest-speed playback until the image that the user wants to watch is reached. For example, about two minutes are required even by 15 \times -speed playback until an image 30 minutes ahead of the image that the user is currently watching is reached. In case of high-speed playback, if the next file is a moving image file as short as several ten minutes, playback of that moving image file ends instantaneously, and playback of the next file starts unwantedly.

Hence, the CPU **114** has the following two playback control modes.

Playback control 1: The CPU **114** controls fast-forwarding or fast-rewinding playback after it controls the forwarding or rewinding amount of a video (after it switches the skip interval of a moving image video) based on the rotation angle of the jog dial **7**.

Playback control 2: The CPU **114** controls fast-forwarding or fast-rewinding playback after it controls the forwarding or rewinding amount of a video (after it switches the skip interval of a moving image video) based on pressing of the right key **84** or the left key **85** of the arrow keys **8** and the playback time period of a video to be played back. For example, the CPU **114** controls to forward or rewind a video by steps $\frac{1}{n}$ (n : a natural number) the playback time period of a video for one file.

With the latter playback control, when an image which was captured for a long period of time is to be played back, if a time period from an image that the user is currently watching until an image that the user wants to watch is long, the image that the user wants to watch can be found in a short period of time. Or when an image which was captured for a long period of time is to be played back, if a time period from an image that the user is currently watching until an image that the user wants to watch is short, the image that the user wants to watch can be found without missing.

The CPU **114** may variably control the high-speed playback speed of the jog dial **7** based on the playback time of a moving image file. For example, with the variable control of the high-speed playback speed by the CPU **114**, the high-speed playback speed of a moving image file less than a predetermined time period (e.g., a moving image file as short as several ten seconds) is relatively low, and that of a moving image file equal to or longer than the predetermined time period is relatively high.

5

FIG. 6 shows an example of the data structure of one MPEG moving image file. The MPEG moving image file includes a header **201** and a video object **202**. The header **201** includes information associated with the video object **202**. The video object **202** includes a plurality of VOBUs (Video Object Units) each having data compressed by MPEG. The number of VOBUs is proportional to the capturing time. One VOBUs has compressed captured data for 0.5 sec, i.e., one GOP (Group Of Picture) and many pieces of header information. For example, for capturing for 10 minutes, 10 minutes \times 60 seconds/0.5=1200 GOPs are generated. The header **201** includes VOBU_ENT information, which records the sizes of respective VOBUs. For example, the header **201** of the video object **202** including 1200 GOPs records size information for each of 1200 GOPs.

FIG. 7 is a flowchart showing the playback control by the CPU **114**. Initially, the number (T) of GOPs of the entire file is acquired from the VOBU_ENT information (ST**301**). The number ($s=T/20$) of GOPs is acquired by equally dividing the entire file by 20 ($n=20$) (ST**302**). FIG. 9 shows the number of GOPs when the file length is divided into $1/20$. At this time, when the capturing time is as short as 200 sec or less, $s=10$ is fixed, or s is increased with decreasing capturing time (ST**303**, ST**304**). That is, upon playback of a short file, if this file is skipped at time intervals $1/20$ of this file, the skip interval becomes very short, resulting in an inconvenient function. The high-speed playback by means of the jog dial **7** is faster. Hence, upon playback of a short file (a file whose playback time period is less than a predetermined time period), s is fixed or s is increased with decreasing file length, and that file is played back to the end (ST**305**, ST**306**). In this manner, this function can be conveniently used.

FIG. 8 is a flowchart showing the $1/n$ (n : a natural number, e.g., $n=20$) skip playback control by the CPU **114**. Note that upon playback of a short file (a file whose playback time period is less than the predetermined time period), $1/m$ (m : a natural number, $m<n$) skip playback control is executed since s is fixed or s is increased with decreasing file length, as described above. This playback control is executed in response to an operation input of the right key **84** or the left key **85** of the arrow keys **8**. The number of the GOP which is being played back from the first GOP is calculated. A time is acquired from the decoded time code of MPEG, and the number of the current GOP can be calculated based on 1 GOP=0.5s. Assume that the current GOP is the k -th GOP (ST**401**). If the operation input of the left key **85** is detected, rewinding is executed (ST**402**, left); if that of the right key **84** is detected, forwarding is executed (ST**402**, right). In case of rewinding, the k -th GOP is skipped to the $(k-s)$ -th GOP; in case of forwarding, it is skipped to the $(k+s)$ -th GOP (ST**403**, ST**404**). However, if $k-1$ is 1 or less in case of rewinding, the k -th GOP is skipped to the first GOP; if $k+s$ is larger than the total number T of GOPs in case of forwarding, the k -th GOP is skipped to the last GOP (ST**405**, ST**406**). That is, the $1/20$ skip playback is controlled to have the last or first GOP of the video as a limit. If the number of the GOP to be skipped from the first GOP is determined, its position is acquired from the VOBU_ENT information shown in FIG. 6, and an image is skipped to that position (ST**407**, ST**408**, ST**409**, ST**410**). FIG. 10 shows a skip destination (GOP position) in response to the operation input of the right key **84** or the left key **85**.

Note that this $1/20$ skip is also effective for trick playback such as reverse playback, high-speed playback, high-speed reverse playback, frame-by-frame advance playback, frame-by-frame reverse playback, and the like. Furthermore, when the right key **84** or the left key **85** is kept pressed, forwarding or rewinding is continuously done by $1/20$.

6

Another embodiment will be described below with reference to FIG. 11. FIG. 11 is views for explaining playback control depending on the file length to prevent playback of a moving image file as short as about several ten seconds from instantaneously ending during high-speed playback based on the rotation angle of the jog dial **7**. As shown in FIG. 11, assume that a second file is as short as ten-odd seconds while high-speed playback of first, second, and third files is continuously done. When the playback control according to the file length is not applied, only several frames (two frames in this example) of the second file are played back, as shown in (a) of FIG. 11. By contrast, when the playback control according to the file length is applied, the playback speed of the short file can be decreased. As a result, more frames (four frames in this example) of the second file can be played back, as shown in (b) of FIG. 11. That is, the total captured time is detected from the VOBU_ENT information shown in FIG. 6, and if a short moving image file is detected, the high-speed playback speed is fixed to a low speed without exception or is decreased with increasing file length. That is, the CPU **114** controls fast-forwarding or fast-rewinding playback after it controls the forwarding or rewinding amount of a video based on the rotation angle of the jog dial **7** and the playback time period of a video to be played back.

With the above control, the following operation effects can be obtained.

In case of high-speed fast-forwarding or high-speed fast-rewinding (e.g., 15 \times -speed), a longer time period is required to reach a scene that the user wants to watch with increasing playback time period of a moving image. Likewise, in case of high-speed fast-forwarding or high-speed fast-rewinding (e.g., 15 \times -speed), the user is more likely to miss a scene that he or she wants to watch with decreasing playback time period of a moving image. According to the invention, fast-forwarding or fast-rewinding can be done at $1/n$ steps of the playback time period of the moving image irrespective of the playback time period of the moving image, and a time period required to reach a scene that the user wants to watch can be shortened. Furthermore, as for a short moving image, the high-speed playback speed by means of the jog dial **7** can be decreased. As a result, adequate high-speed playback with high visibility can be provided.

While certain embodiments of the inventions have been described, these embodiments have been presented by way of example only, and are not intended to limit the scope of the inventions. Indeed, the novel methods and systems described herein may be embodied in a variety of other forms; furthermore, various omissions, substitutions and changes in the form of the methods and systems described herein may be made without departing from the spirit of the inventions. The accompanying claims and their equivalents are intended to cover such forms or modification as would fall within the scope and spirit of the inventions.

What is claimed is:

1. A capturing apparatus comprising:

- a capturing unit configured to capture a moving image video;
- a storage unit configured to store the moving image video captured by the capturing unit;
- an operation unit configured to include a plurality of keys used to instruct playback of the moving image video stored in the storage unit;
- a skip playback unit configured to play back the moving image video while skipping the moving image video at predetermined time intervals every time a predetermined operation is made on the operation unit; and

7

a playback control unit configured to switch the time intervals skipped by the skip playback unit based on a total playback time period of the moving image video.

2. The apparatus according to claim 1, wherein the operation unit comprises a dial key and arrow keys used to play back the moving image video while skipping the moving image video at the predetermined time intervals, and the playback control unit switches the time intervals skipped by the skip playback unit based on a rotation angle of the dial key, and switches the time intervals skipped by the skip playback unit based on pressing of one of the arrow keys and the total playback time period of the moving image video.

3. The apparatus according to claim 1, wherein the playback control unit switches the time intervals skipped by the skip playback unit at $1/n$ (n : a natural number) intervals of the total playback time period of the moving image video.

4. The apparatus according to claim 1, wherein the playback control unit switches the time intervals skipped by the skip playback unit at $1/n$ (n : a natural number) intervals of the total playback time period of the moving image video with reference to a current playback position.

5. The apparatus according to claim 3, wherein the playback control unit switches the time intervals skipped by the skip playback unit at $1/m$ (m : a natural number, $m < n$) intervals of the total playback time period of the moving image video based on the fact that the total playback time period of the moving image video is less than a predetermined time period.

6. The apparatus according to claim 3, wherein the playback control unit switches the time intervals skipped by the skip playback unit at $1/m$ (m : a natural number, $m < n$) intervals of the total playback time period of the moving image video with reference to a current playback position based on the fact that the total playback time period of the moving image video is less than a predetermined time period.

7. The apparatus according to claim 1, wherein the operation unit inputs an equal-speed reverse playback instruction, and

the playback control unit controls equal-speed reverse playback of the moving image video based on the equal-speed reverse playback instruction of the operation unit, and switches the time intervals skipped by the skip playback unit at $1/n$ (n : a natural number) intervals of the total playback time period of the moving image video based on a predetermined interval skip playback instruction of the operation unit during the equal-speed reverse playback.

8. The apparatus according to claim 1, wherein the operation unit inputs a pause instruction, and the playback control unit controls pause of playback of the moving image video based on the pause instruction of the operation unit, and switches the time intervals skipped by the skip playback unit

8

at $1/n$ (n : a natural number) intervals of the total playback time period of the moving image video based on a predetermined interval skip playback instruction of the operation unit during pausing.

9. The apparatus according to claim 1, wherein the operation unit inputs a frame-by-frame advance playback instruction, and

the playback control unit controls frame-by-frame advance playback of the moving image video based on the frame-by-frame advance playback instruction of the operation unit, and switches the time intervals skipped by the skip playback unit at $1/n$ (n : a natural number) intervals of the total playback time period of the moving image video based on a predetermined interval skip playback instruction of the operation unit during the frame-by-frame advance playback.

10. The apparatus according to claim 1, wherein the playback control unit switches the time intervals skipped by the skip playback unit at $1/n$ (n : a natural number) intervals of the total playback time period of the moving image video based on a predetermined interval skip playback instruction of the operation unit to have the last or head of the moving image video as a limit.

11. The apparatus according to claim 1, wherein the playback control unit continuously switches the time intervals skipped by the skip playback unit at $1/n$ (n : a natural number) intervals of the total playback time period of the moving image video based on a predetermined interval skip playback continuous instruction of the operation unit.

12. A capturing apparatus comprising:

a capturing unit configured to capture a moving image video;

a storage unit configured to store the moving image video captured by the capturing unit;

an operation unit configured to include a plurality of keys used to instruct playback of the moving image video stored in the storage unit;

a skip playback unit configured to play back the moving image video while skipping the moving image video at predetermined time intervals every time a predetermined operation is made on the operation unit; and

a playback control unit configured to switch the time intervals skipped by the skip playback unit based on a total playback time period of the moving image video,

wherein the operation unit includes a dial key used to play back the moving image video while skipping the moving image video at predetermined time intervals, and

the playback control unit switches the time intervals skipped by the skip playback unit based on a rotation angle of the dial key and the total playback time period of the moving image video.

* * * * *