



US007833071B2

(12) **United States Patent**
Gaither

(10) **Patent No.:** **US 7,833,071 B2**
(45) **Date of Patent:** **Nov. 16, 2010**

(54) **AMPHIBIOUS ALL-TERRAIN VEHICLE**

(75) Inventor: **R. Louis Gaither**, Covington, TN (US)

(73) Assignee: **Hydratrek, LLC**, Covington, TN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/760,197**

(22) Filed: **Jun. 8, 2007**

(65) **Prior Publication Data**

US 2008/0227344 A1 Sep. 18, 2008

Related U.S. Application Data

(60) Provisional application No. 60/812,530, filed on Jun. 9, 2006.

(51) **Int. Cl.**

B60F 3/00 (2006.01)

B63H 19/08 (2006.01)

B63H 21/12 (2006.01)

B63H 21/165 (2006.01)

(52) **U.S. Cl.** **440/12.5; 440/5; 440/12.51; 440/12.57**

(58) **Field of Classification Search** **440/12.5, 440/12.51, 12.57, 5**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,199,486 A 8/1965 Gillois et al.
3,385,255 A 5/1968 Raymond et al.

3,444,837 A 5/1969 Donofrio
3,664,451 A 5/1972 Rogers et al.
4,664,051 A 5/1987 Newkirk
4,671,774 A 6/1987 Owsen
4,744,324 A 5/1988 Martinmaas
5,476,400 A 12/1995 Theophanides
5,546,751 A 8/1996 Last
5,993,273 A * 11/1999 Adams 440/5
6,626,712 B1 * 9/2003 Bellezza Quater
et al. 440/12.56
6,666,735 B2 12/2003 Benoit
6,672,916 B1 1/2004 Lent-Phillips et al.
2006/0237239 A1 10/2006 Bruner et al.

* cited by examiner


Primary Examiner—Daniel V Venne

(74) *Attorney, Agent, or Firm*—Wyatt, Tarrant & Combs, LLP; H. Roy Berkenstock; Matthew A. Williams

(57) **ABSTRACT**

An amphibious, all-terrain vehicle utilizing a pair of hydrostatic pumps to independently provide power to hydraulic drive mechanisms of the left and right side of the vehicle respectively. The hydraulic drive mechanisms on a side of the vehicle comprise a plurality of hydraulic wheel motors and a hydraulic propeller motor. Using a novel hydraulic manifold assembly, the vehicle can operate in three distinct modes: wheels only, wheels and propellers, and propellers only. The hydraulic manifold assembly also allow the vehicle to by put in neutral mode for starting. The wheel motors are mounted in a pair of undercarriage assemblies that are outside of the vehicle's body and fluidly connected to the hydraulic manifold assembly thorough a hose chase that extends well above the vehicle's waterline to eliminate the potential for water to enter the body of the vehicle when operated in the water.

13 Claims, 15 Drawing Sheets








FIG. 1








FIG. 4




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 6A




FIG. 6B

FORWARD




FIG. 6C

GRADUAL RIGHT TURN




FIG. 6D

SHARP RIGHT TURN




FIG. 6E

REVERSE




FIG. 7




FIG. 8




FIG. 9




FIG. 10A

Wheels Only




FIG. 10B

Wheels & Propellers




FIG. 10C

Propeller Only




FIG. 10D

Neutral




FIG. 11




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 12D




FIG. 13




FIG. 14

AMPHIBIOUS ALL-TERRAIN VEHICLECROSS-REFERENCE TO RELATED
APPLICATIONS

This application claims the benefit of U.S. Provisional Application No. 60/812,530, filed Jun. 9, 2006.

STATEMENT REGARDING FEDERALLY
SPONSORED RESEARCH OR DEVELOPMENT

Not applicable

REFERENCE TO MICROFICHE APPENDIX

Not applicable

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention generally relates to amphibious motor vehicles. More specifically, the invention is an amphibious vehicle that utilizes four, six, or eight independent, hydraulically driven wheels when the wheels are in contact with the ground and a pair of propellers when the vehicle is in water. Further, a single pair of levers controls the speed and direction of the vehicle both on land and in water.

2. Description of the Related Art

A variety of amphibious all-terrain vehicles have been devised in an attempt to allow the user to easily traverse from land to water operation and vice versa quickly and easily. The following patents, which are incorporated herein by reference, generally represent the state of the art.

U.S. Pat. No. 3,664,451 describes a vehicle having front and rear body sections rotatably interconnected along the longitudinal axis of the body sections. An engine is located in the front body section and a drive shaft extends through the coupling between the body sections through the compartment of the rear body section and to a gear box on a rear axle located entirely outside of the compartment of the rear body section. Frame members extend from the rear body section to support the rear axle. A propeller may be connected to a drive shaft extending rearwardly from the gear box on the rear axle.

U.S. Pat. No. 4,744,324 describes an all-terrain vehicle that is adapted to amphibious operation by means of a conversion kit that uses rear axle extensions to mount outer rear wheels and radial paddle elements between the inner and outer rear wheels. Flotation is provided by over-size tires.

U.S. Pat. No. 6,672,916 describes an amphibious vehicle having an open seating arrangement and which comprises a drive motor for reciprocally or simultaneously driving an all-wheel drive traveling mechanism and a swimming drive that is configured as a jet drive by means of at least two clutches that operate independently of one another, whereby the drive motor is arranged underneath the seating arrangement in an essentially central manner between the axles of the traveling mechanism.

U.S. Pat. No. 3,444,837 discloses a utility vehicle having structural features directed to a self supporting powered chassis comprising a clutch mechanism that functions by the principal use of planetary gear systems. In addition, the wheels are driven by a series chains and sprockets.

U.S. Pat. No. 3,199,486 describes an amphibious vehicle having a body adapted to be armored and having power driven front and rear axles connected with front and rear wheels for travel on land, propeller means for travel on water; and drive means for said front and rear wheels and for said propeller

means, said wheels being equipped with oversized, shot-proof low pressure tires, the tires for said power driven front wheels projecting ahead of said body, and said drive means including transmission means selectively operative to drive said front and said rear wheels together, said wheels and said propeller means simultaneously, and said propeller means separately, and said transmission means including a propeller driving transmission portion and a land driving transmission portion operative at a land traveling speed not exceeding the speed of water travel, said propeller driving transmission portion including a horizontal drive shaft and said propeller means including a propeller drive shaft extending perpendicularly to said horizontal drive shaft and being connected thereto and pivotally movable about its own axis and about the axis of said horizontal drive shaft.

U.S. Pat. No. 5,993,273 describes an amphibious all-terrain vehicle having a substantially rectangular body or shell constructed of a lightweight durable metallic material. A combustion gas engine is coupled to a dual hydraulic pump system. Six-independent wheel motors are symmetrically disposed in series, three on each side of the shell and are plumbed in series for ground-based mobility respectively. Each of the wheel motors penetrates the shell beneath the waterline of the vehicle. An auxiliary hydraulic pump may be provided to drive a hydraulic propeller motor, said motor also penetrating the shell beneath the waterline. Separate controls are used to control the wheels and the propeller.

U.S. Pat. No. 6,666,735 discloses an amphibious off-road vehicle drive that utilizes an internal combustion engine drive system and a liquid propulsion jet drive system jointly functional in a single engine case of the off-road vehicle for enabling forward motion of the vehicle. The jet drive system provides a means for engaging and disengaging with the internal combustion engine drive system. An outrigger flotation device engages with the off-road vehicle and is adapted for adjustment between a stored attitude and a deployed attitude. When the vehicle enters deep water, the jet drive may be employed to propel the vehicle, and the flotation gear may be employed to maintain buoyancy.

U.S. Pat. No. 4,664,051 discloses a flotation kit to be used to adapt a conventional three wheel all-terrain vehicle for amphibious use.

U.S. Pat. No. 3,385,255 discloses a track type amphibious vehicle with three drive wheels for carrying an endless track mounted on each side of the vehicle. The drive wheels on each side are mounted on axles that protrude from a sealed box beam mounted underneath the vehicle, and below the vehicle's waterline, and are driven by a single hydraulic motor that delivers power to each wheel through a chain and sprocket system. The chain drive is lubricated by a reservoir of lubricating fluid contained in said box beam. Propulsion in the water is provided by a pair of auxiliary motors that are releasably mounted on the rear end wall of the vehicle and that drive a pair of propellers. When the vehicle is in the water, both the propellers and the wheels are driven simultaneously.

The complexity of designing a vehicle that can operate effectively on all terrain and easily traverse from land operation to water operation and back has lead to a variety of problems that plague known devices. One problem in known devices is that the drive mechanism, or mechanisms, for the wheels passes through the shell of the vehicle beneath the waterline. Thus, as the drive mechanism is stressed through torque applied by the power source and through vibration and impact as the vehicle traverses uneven ground, the seal around the mechanism, or mechanisms, tends to fail, allowing water into the passenger compartment.

A second problem is the use of drive systems that utilize a single motor to drive all of the wheels on a single side of the vehicle through complex, failure-prone mechanical systems such as the chain-and-sprocket drive system disclosed in U.S. Pat. No. 3,385,255.

A third problem is the fact that known vehicles that utilize a water propulsion system in addition to their drive wheels either require a separate set of controls for the ground and water propulsion mechanisms or, when a single set of controls is used, drive the wheels simultaneously with the water propulsion mechanism. The first situation is a problem because it makes it difficult for a single operator to drive the vehicle out of water effectively because this feat generally requires the operator to coordinate the drive systems such that water propulsion system provides sufficient forward force to allow the wheels to engage with the ground forming the bottom of the body of water without slipping. The second situation is a problem because it siphons power from the water propulsion system and because the rotation of the tires in the water creates drag.

A fourth problem is that the utilization of a single hydraulic system to drive wheel motors and a propeller motor can result subjecting the propeller motor to high pressure when the vehicle is operated in wheels only mode. This can result in a significant drop in performance of the vehicle because hydraulic motors suitable for providing the high RPM output necessary to drive a propeller are typically of the case drain design such as the PGM-330 from Parker Hannifin Corporation. If such a case drain type motor is subjected to high pressure and not allowed to rotate, a leakage through the case drain can occur resulting in a significant loss in performance.

A fifth problem is the complexity and cost of building a vehicle with independent hydraulic systems to control both land and water propulsion motors on the left and right sides of the vehicle that can be operated in three distinct modes—land drive only, land and water drive, and water drive only—using single set of controls.

SUMMARY OF THE INVENTION

The amphibious all-terrain vehicle of the present invention differs from the vehicles disclosed in the prior art by resolving the long existing problems associated with said prior art vehicles. The present invention utilizes four, six, or eight hydraulic wheel motors, preferably six, mounted in pairs on opposite sides of the vehicle. The wheel motors on a side of the vehicle are connected in series to create an all-wheel drive system that does not require the use of a complex, failure-prone, mechanical drive system. The vehicle also includes a pair of hydraulic water propulsion motors that are located toward the rear of the vehicle with one hydraulic water propulsion motor on each side of the vehicle's longitudinal centerline.

The wheel motors are mounted to an undercarriage such that they are completely outside of the tub that comprises the passenger compartment. The wheel motors are connected to the hydraulic system using hydraulic lines that pass through a pair of hose chases built into the tub that extend above the vehicles waterline so that water cannot enter the tub through the hose chases.

In addition, the present invention utilizes a single pair of levers to control the speed and direction of the vehicle regardless of whether the vehicle is on the land or in the water. When the vehicle is in the water, the hydraulic water propulsion motors can be used by themselves or in combination with the hydraulic wheel motors.

The present invention additionally includes a pair of novel hydraulic manifold assemblies that allows the vehicle to be controlled by a single set of controls while being operated in three distinct modes: land drive only; land and water drives simultaneously; and water drive only. The hydraulic manifold assemblies utilize mechanically actuated ball valves to select the vehicle's operational mode and isolates the propeller motors from high pressure when the vehicle is operated in land drive only mode. Moreover, the operator controls the valves in the manifold assemblies using two levers connected by cables to a pair of yokes that actuate the valves on the manifold assemblies. This eliminates the need to use expensive, electrically actuated valves that tend to create problems in high pressure systems due to increased pressure drops and unexpected changes in state due to a Bernoulli effect.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and, together with a general description of the invention given above and the detailed description of the preferred embodiments given below, serve to explain the principles of the invention. It should however be understood that there is no intent to limit the invention to the particular forms disclosed, and that this patent application incorporates by reference all references and publications disclosed herein. Rather, the intent is that the invention be limited only by the scope of the claims.

FIG. 1—Perspective view of the vehicle.

FIG. 2—Exploded perspective view.

FIG. 3—Perspective view looking down into vehicle with power source and hydraulic components removed.

FIG. 4—Rear view of the vehicle.

FIGS. 5A, 5B, 5C, 5D—Diagram of hydraulic flow paths.

FIGS. 6A, 6B, 6C, 6D, 6E—Diagram showing how vehicle control levers operate the vehicle.

FIG. 7—Perspective view of the hydraulic manifold assembly.

FIG. 8—Perspective view of the valve manifold assembly.

FIG. 9—Diagram of the hydraulic system.

FIGS. 10A, 10B, 10C and 10D—Diagram showing how vehicle propulsion levers select the vehicle's mode of operation.

FIG. 11—Diagram of the vehicle's dashboard.

FIGS. 12A, 12B, 12C and 12D—Perspective views of the right wheel motor housings.

FIG. 13—Stylized perspective of a portion of the right undercarriage assembly.

FIG. 14—Perspective view of an alternative embodiment of the hydraulic manifold assembly.

DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

FIG. 1 illustrates an embodiment of the amphibious all-terrain vehicle 10 according to the present invention. Referring now to FIG. 2, vehicle 10 includes body assembly 100, left undercarriage assembly 200l, right undercarriage assembly 200r, front hood assembly 20, grab bar 30, roll bar 40, and rear hood 60 (shown in FIG. 1).

Body Assembly

Still referring to FIG. 2, body assembly 100 includes body 110, rear bumper assembly 130, front bumper 150, passenger compartment 160, and mechanical compartment 180. Body 110 includes floor 112, left sidewall 114, right sidewall 116,

frontwall 118, left propeller motor mounting flange 120, and right propeller motor mounting flange 122.

Left propeller motor mounting flange 120 extends upward from the left side of the end of floor 112. The left edge of left propeller mounting flange 120 is permanently attached to the inside surface of left side wall 116, preferably by welding. Right propeller motor mounting flange 122 extends upward from the right side of the end of floor 112. The right edge of right propeller mounting flange 122 is permanently attached to the inside surface of right side wall 116, preferably by welding.

Left side wall 114 and right side wall 116 extend upward from the left and right edge of floor 112 respectively. Left side wall 114 terminates in left pontoon 124; right side wall 116 terminates in right pontoon 126. Pontoons 124 and 126 are preferably filled with closed cell expanded bead polystyrene foam. The front end of side walls 114 and 116 taper down from the front ends of pontoons 124 and 126 respectively to the front edge of bottom 112. The rear ends of side walls of 114 and 116 taper down from the rear ends of pontoons 124 and 126 respectively to the rear end of bottom 112. Front wall 118 extends upward and away from floor 112 at an obtuse angle that is preferably between 140 and 160 degrees. Front bumper 150 is conjoined to the upper edge of front wall 118 and to the front ends of pontoons 124 and 126 to form a watertight seal, preferably by welding.

Still referring to FIG. 2, rear bumper assembly 130 is comprised of a rear bumper 132, left bumper assembly mounting flange 134, right bumper assembly mounting flange 136 (not shown), left propeller shroud 138, right propeller shroud 140, propeller screens 141, central mounting flanges 142 and 144, and rear wall 146. Central mounting flange 144 and rear wall 146 are best seen in FIG. 4. (Propeller shrouds 138 and 140 and screens 141 surround the propellers and extend forward to body assembly 100 to protect the propellers from contact with foreign objects).

Again referring to FIG. 2, rear bumper assembly 130 is conjoined to body 110, preferably by welding, to form a watertight seal between rear bumper assembly 130 and body 110. More specifically, left bumper assembly mounting flange 134 is attached to the inside surface of the rear tapered portion of left side wall 114, right bumper assembly mounting flange 136 is attached to the inside surface of the rear tapered portion of right side wall 116, central mounting flanges 142 and 144 are connected to the inside edge of propeller motor mounting flanges 120 and 122 respectively, and the lower edge of rear wall 146 is connected to the edge of bottom 112 between propeller mounting flanges 120 and 122.

Mounted on top of body assembly 100 is front hood assembly 20, grab bar 30, roll bar 40, and rear hood 60. Front hood assembly 20 includes a pair of headlights 22, a fold down windshield 24, and a hinged hood 26. Rear hood 60 is removably attached to body assembly 100, preferably using flange bolts, and covers mechanical compartment 180.

Passenger Compartment

Referring now to FIG. 3, located inside body assembly 100 is passenger compartment 160 and mechanical compartment 180. Passenger compartment 160 is located in the front half of body assembly and includes front seat 162; back seat 164, which includes backrest 166; propulsion selection levers 620 and 622; and dashboard 168. Now referring to FIG. 11, mounted in dashboard 168 are pressure gauges 169 and 170 for monitoring hydraulic systems 500/ and 500r; throttle 630 for controlling the output of power source 182; vehicle control levers 602/ and 602r; ignition switch 606, which is preferably a keyed switch; gauges for monitoring the condition of

power source 182 including temperature gauge 171, oil pressure gauge 172, battery voltage indicator 173, fuel gauge 174, and hour meter 175; and a plurality of electrical switches for controlling various electrical components of vehicle 10, including switch 176 for exterior lights, switch 177 for interior lights, switch 178 for the bilge pump, and switch 179 for auxiliary devices.

Mechanical Compartment

Referring again to FIG. 2, mechanical compartment 180 is located in the rear half of body assembly 100, behind backseat 164. Located within mechanical compartment 180 are power source 182, a battery (not shown), a standard, commercially available bilge pump such as the Tsunami Model T1200 (not shown), hydrostatic pumps 502/ and 502r, hydraulic manifold assemblies 515/ and 515r (best seen in FIG. 7), left propeller motor 506/, right propeller motor 506r, left hose chase 183/, and right hose chase 183r (best seen in FIG. 3). Left propeller motor 506/ is mounted to the inside surface of left propeller mounting flange 120 preferably using two bolts and sealed using a marine grade adhesive such as Vulkem 626. Right propeller motor 506r is mounted to right propeller mounting flange 122 in an identical fashion. To provide for increased maneuverability in the water, left propeller motor 506/ and right propeller motor 506r are counter-rotating motors with appropriate counter-rotating propellers 507/ and 507r mounted to the shafts of each motor. The speed control (not shown) on power source 182 is preferably mechanically connected to throttle 630 and still more preferably connected with a cable and pulleys.

Hydraulic manifold assemblies 515/ and 515r are located toward the front of mechanical compartment 180 and include propeller valve yoke 517 and wheel valve yoke 518, as shown in FIG. 7. Propeller valve yoke 517 is mechanically connected to propulsion selection lever 620, preferably using cables and pulleys, and wheel valve yoke 518 is similarly connected to propulsion selection levers 622. The cables are more preferably $\frac{5}{16}$ inch diameter push-pull cables.

Hydrostatic pumps 502/ and 502r are connected, preferably mechanically, to vehicle control levers 602/ and 602r respectively; said connection being more preferably made with cables and pulleys. Levers 602/ and 602r preferably have a three inch travel both forward and backward from their central positions. In an alternate embodiment, levers 602/ and 602r are self-centering, which can be accomplished using a commercially available self-centering apparatus (not shown) such as model number 1592K13 from Tuthill.

Also located in mechanical compartment 180 are other components necessary to form a functional hydrostatic system that are readily available commercially. These components may include oil reservoir 184; filter head 186, such as model K22 from Parker Hannifin Corporation containing an appropriate filter element; charge pump 190, such as model CL050 from Danfoss; and oil cooler 192, such as model TR3 from Thermal Transfer Products. These items are shown in FIG. 9, which is a diagram of the hydraulic system removed from vehicle 10.

Undercarriage

Referring again to FIG. 2, body assembly 100 is mounted on an undercarriage that is comprised of two separate undercarriage assemblies, 200/ and 200r, that are preferably conjoined to body assembly 100 by welding. Because undercarriage assembly 200/ is a mirror image of undercarriage assembly 200r, only undercarriage assembly 200r will be described in detail with the understanding that undercarriage assembly 200/ is comprised of components that are the mirror image of the components of undercarriage assembly 200r.

Undercarriage assembly **200r** is comprised of channel assembly **210**, access cover **202**, wheel motors **504**, and tires **203**. Channel assembly **210** (see FIG. 12) is further comprised of channel **220**, front end plate **222**, rear end plate **224**, and central partitions **226**. Channel **220** defines aperture **252** that aligns with hose chase **183** to allow hydraulic lines to be routed from mechanical compartment **180** into undercarriage assembly **200r**. Central partitions **226** each define aperture **228** therethrough to allow the hydraulic lines to be routed to wheel motors **504**. Access cover **202** provides a smooth surface that slopes away from the longitudinal centerline of the vehicle to provide improve ground clearance and to eliminate projections that could get hung up on obstructions such as rocks and stumps.

Channel **220** further defines a plurality of wheel motor apertures **232** through which the shaft of each wheel motor **504** passes. One tire **503** is mounted to the shaft of each wheel motor **504**. In alternative embodiments a second tire is connected directly to the shaft of each wheel motor **504** or to each tire **503** to give the vehicle a dual wheel capability that is advantageous in certain conditions or to use with a track.

Once wheel motors **504** are mounted within channel assembly **210** and the hydraulic lines are connected, the remaining space within in channel assembly **210** is preferably filled with closed cell expanded bead polystyrene foam to increase buoyancy and to prevent undercarriage assembly **200** from filling completely with water since access cover **202** preferably does not create a watertight seal.

Hydraulic Propulsion System

Vehicle **10** is powered by a single power source **182** that is preferably a 45 to 55 horsepower gas or diesel engine such as the 50 h.p. turbo diesel model available from Kubota Engine America. Power source **182** includes an alternator (not shown) that provides electrical power to vehicle **10**. Power source **182** also provides power to a pair of identical, closed hydraulic systems to deliver power to the driving mechanisms on the left and right side of the vehicle. To simplify the description of these identical hydraulic systems, the identical components in both systems will be represented by a single number. Where it is necessary to refer to a component in only one of the subsystems, that part will be designated by the number followed by the letter "l" for a component in the hydraulic system powering the left side of the vehicle and by the letter "r" to designate a component in the hydraulic system powering the right side of the vehicle. For example, the hydraulic system powering the left side of the vehicle will be designated **500l** and the hydraulic system powering the right side of the vehicle will be designated **500r** when it is necessary to distinguish between them. When no distinction is required, the hydraulic systems will be referred to generically, i.e. hydraulic system **500**.

Referring now to FIG. 5, hydraulic system **500** is a closed loop, hydrostatic system that includes hydrostatic pump **502** that can deliver a variable flow rate of hydraulic fluid in either direction through the closed system. Hydrostatic pump **502** is rotatably connected to power source **182** and is preferably a Sauer Danfoss M25-2132. Pump **502** is fluidly connected to a plurality (preferably three) of wheel motors **504** that are fluidly connected in series (collectively wheel motor series **505**) and propeller motor **506** using hydraulic manifold assembly **515**, "tee" **514**, and $\frac{5}{8}$ " diameter hydraulic lines to connect said components. Hydraulic manifold assembly **515** is comprised of three-way valve **508**, wheel motor valve **510**, wheel motor bypass valve **512**, propeller motor isolation valve **518**, and manifold **516** (best seen in FIG. 7). Manifold **516** is preferably a welded tube that defines four ports for attaching

said valves, preferably using SAE O-ring connectors, and internal passages fluidly connecting said valves as shown in FIG. 7. Alternatively, manifold **516** could be a machined block defining four ports connected to an internal passage in said block as shown in FIG. 14 and the connection of the valves to the block could be using SAE O-ring connectors, threaded connection, or some other leak proof connection.

Wheel motors **504** preferably have a displacement of 335 cc/rev such as model TG335 from Parker Hannifin Corporation, and propeller motor **506** preferably has a displacement of 22 cc/rev such as model PGM 330 from Parker Hannifin Corporation. Three-way valve **508** is preferably a mechanically actuated three-way ball valve such as model HBV3 from Parker Hannifin Corporation. Wheel motor valve **510**, wheel motor bypass valve **512**, and propeller motor isolation valve **518** are preferably mechanically operated two-way ball valves such as model HBV2 from Parker Hannifin Corporation.

As best seen in FIGS. 5A, 5B, 5C, and 5D, hydrostatic pump **502** is fluidly located between tee **514** and three-way valve **508**. The remaining two ports in three-way valve **508** are fluidly connected to propeller motor **506** and manifold **516**. Propeller motor **506** is then fluidly connected to propeller isolation valve **518**. Propeller isolation valve **518** is further fluidly connected to manifold **516**. Wheel motor valve **510** is fluidly located between manifold **516** and wheel motor series **505**, and wheel motor series **505** is further fluidly connected to tee **514**. The remaining port of manifold **516** is fluidly connected to wheel motor bypass valve **512**, which is further fluidly connected to tee **514**.

Still referring to FIGS. 5A, 5B, 5C, and 5D flow through hydraulic system **500** for the various modes of operation is indicated by arrows. The direction of the arrow indicates the direction of flow when vehicle **10** is being propelled in a forward direction. When the vehicle is operated in reverse, the flow path remains the same for a given mode, but the direction of flow is reversed. Also, a closed valve is indicated by an "X" within the valve.

As can be seen in FIG. 5A, when vehicle **10** is operated in wheels only mode to be driven in a forward direction, output from hydrostatic pump **502** is directed toward three-way valve **508**. Three-way valve **508** then directs said output into manifold **516**. Wheel motor bypass valve **512** is in its closed position causing said output to exit manifold **516** through wheel motor valve **510**, which is in its open position. Said output then flows through wheel motor valve **510**, which is in its open position, and then flows through and drives wheel motors **504**. After said output exits the last wheel motor **504** in wheel motor series **505**, said output returns to hydrostatic pump **502** via tee **514**. Said output must exit tee **514** toward hydrostatic pump **502** because the alternate flow path from tee **514** is blocked by wheel motor bypass valve **512** that is in its closed position. Additionally, propeller isolation valve **518** is in its closed position to prevent propeller motor **506** from being exposed to high pressure while vehicle **10** is operating in wheels only mode.

As can be seen in FIG. 5B, when vehicle **10** is operated in propeller only mode to be driven in a forward direction, output from hydrostatic pump **502** is directed toward three-way valve **508**. Three-way valve **508** then directs said output toward propeller motor **506**. After passing through and driving propeller motor **506**, said output flows through propeller isolation valve **518**, which is in its open position, and into manifold **516**. Said output exits manifold **516** through wheel motor bypass valve **512**, which is in its open position, and returns to hydrostatic pump **502** via tee **514**. Said output

cannot flow through wheel motor series **505** from hydraulic manifold assembly **515** or tee **514** because wheel motor valve **510** is in its closed position.

As can be seen in FIG. 5C, when vehicle **10** is operated in combined wheel and propeller mode to be driven in a forward direction, output from hydrostatic pump **502** is directed toward three-way valve **508**. Three-way valve **508** then directs said output toward propeller motor **506**. After passing through and driving propeller motor **506**, said output flows through propeller isolation valve **518**, which is in its open position, and into manifold **516**. Said output exits manifold **516** and flows through wheel motor valve **510**, which is in its open position, because flow is prevented from exiting hydraulic manifold assembly **515** through wheel motor bypass valve **512** because it is in its closed position. Said output then flows through and drives wheel motors **504**. After said output exits the last wheel motor **504** in wheel motor series **505**, said output returns to hydrostatic pump **502** via tee **514**. Said output must exit tee **514** toward hydrostatic pump **502** because the alternate flow path from tee **514** is blocked by wheel motor bypass valve **512** that is in its closed position.

As can be seen by one of ordinary skill in the art, vehicle **10** can be operated in reverse in any of the modes listed above by reversing the direction of the output from hydrostatic pump **502** and keeping the valves in the same states discussed above.

FIG. 5D represents the flow path taken by the output from hydrostatic pump **502** when a neutral mode of operation is selected. In this neutral mode of operation, output from hydrostatic pump bypasses both propeller motor **506** and wheel motor series **505**.

Operation of Vehicle

1. Selecting Operation Mode of Vehicle **10**

Propulsion selection levers **620** and **622** determine the method of operation, i.e. which propulsion motors are engaged, and the chosen method applies to both the left and right side propulsion systems. Lever **620** is mechanically connected to three-way valves **508l** and **508r** and propeller isolation valves **518l** and **518r** via propeller valve yoke **517**; Lever **622** is mechanically connected to wheel motor valves **510l** and **510r** and wheel motor bypass valves **512l** and **512r** via wheel valve yoke **518**. When both levers **620** and **622** are in their forward positions (FIG. 10A), vehicle **10** operates in wheels only mode as described above and shown in FIG. 5A. When lever **620** is moved to its rearward position and lever **622** remains in its forward position, (FIG. 10B), the positions of three-way valves **508l** and **508r** are changed and propeller isolation valves **518l** and **518r** are opened to direct the output of hydrostatic pump **502** through propeller motor **506** and wheel motors **504** in series, as described above and shown in FIG. 5C, putting vehicle **10** into combined wheel and propeller drive. When lever **622** is moved to its rearward position, putting both levers **620** and **622** in their rearward positions (FIG. 10C), wheel motor valve **510** is closed and wheel motor bypass valve **512** is opened, as described above and shown in FIG. 5C, putting vehicle **10** into propeller only operation. Finally, when lever **620** is in its forward position and lever **622** is in its rearward position (FIG. 10D), vehicle **10** is in its neutral mode of operation, and the output from hydrostatic pump **502** is directed through circuit described above and shown in FIG. 5D in which the output bypasses both wheel motor series **505** and the propeller motor **506**.

2. Starting Vehicle **10**

The first step in operating vehicle **10** is to start power source **182**. This is accomplished by placing vehicle **10** in its

neutral mode of operation by placing propulsion lever **620** in its forward position and propulsion lever **622** in its rearward position. This position is confirmed through the use of a pair of normally open electrical switches (not shown) that are closed by placing levers **620** and **622** in the specified positions, which allows ignition switch **606**, preferably a keyed switch, to start power source **182**. Once power source **182** is started, the mode of propulsion is selected as discussed above.

To move vehicle **10** forward in a straight line, levers **602l** and **602r** are moved forward simultaneously from their central positions, as shown in FIG. 6B, to provide hydraulic power to wheel motors **504** or propeller motors **506** or both. To move vehicle **10** backward in a straight line, levers **602l** and **602r** are moved backward simultaneously from their central positions, as shown in FIG. 6E, to provide hydraulic power to wheel motors **504** or propeller motors **506** or both.

3. Controlling the Speed of Vehicle **10**

The speed of vehicle **10** is controlled by a combination of vehicle control levers **602l** and **602r** and throttle **630**. The further away from their central positions levers **602l** and **602r** are moved, the greater the output from hydrostatic pump **502** and the faster the propulsion motors will rotate. Throttle **630** is mounted in dashboard **168** and is mechanically linked to power source **182** and preferably provides four different throttle settings: idle, low, medium, and high. Throttle **630** controls the range of speed that can be achieved by the operation of levers **602l** and **602r**. The higher the throttle setting, the faster vehicle **10** can travel.

4. Turning Vehicle **10**

Vehicle **10** is turned by creating a differential in the location of levers **602l** and **602r** relative to the levers' central positions—the greater the differential the smaller the radius of the turn. To execute a gradual turn to the right, lever **602l** is moved farther forward from its central position than lever **602r**, as shown in FIG. 6C, resulting in the engaged propulsion motors on the left side of vehicle **10** rotating at a higher rate than the engaged propulsion motors on the right side of vehicle **10** causing vehicle **10** to turn. The larger the differential between the positions of levers **602l** and **602r**, the smaller the radius of the turn. To execute a very sharp turn to the right, lever **602l** is moved forward from its central position, causing the engaged propulsion motors on the left side of vehicle **10** to rotate in a forward direction, while lever **602r** is simultaneously moved backward from its central position, causing the engaged propulsion motors on the right side of vehicle **10** to rotate in a reverse direction, as shown in FIG. 6D. Finally, as would be evident to one of ordinary skill in the art, turns to the left are accomplished by reversing the positions of levers **602l** and **602r** discussed above.

I claim:

1. An amphibious all-terrain vehicle comprising:

- a body assembly, said body assembly further comprising
 - a passenger compartment housing a pair of propulsion selection levers;
 - a mechanical compartment housing a power source, a left hydrostatic pump, a right hydrostatic pump, a left hydraulic propeller motor, a right hydraulic propeller motor, a left hydraulic manifold assembly, and a right hydraulic manifold assembly;
- a left undercarriage assembly; said left undercarriage assembly
 - being conjoined to a bottom of said body assembly along a left edge of said body assembly and
 - housing a left plurality of hydraulic wheel motors connected in series such that said left plurality of wheel motors are external to the body assembly;

11

a right undercarriage assembly; said right undercarriage assembly
 being conjoined to the bottom of said body assembly
 along a right edge of said body assembly and
 housing a right plurality of hydraulic wheel motors con- 5
 nected in series such that said right plurality of wheel
 motors are external to the body assembly, said right
 plurality of wheel motors being identical in number to
 the left plurality of wheel motors;
 said left and right hydrostatic pumps being rotatably 10
 connected to said power source and fluidly connected
 to said left and right hydraulic manifold assemblies
 respectively;
 whereby a variable flow of hydraulic fluid output from
 said left and right hydrostatic pumps is selectively 15
 directed through the left and right pluralities of wheel
 motors only, through the left and right pluralities of
 wheel motors and the left and right hydraulic propel-
 ler motors, through the left and right hydraulic pro- 20
 peller motors only, or through neither the left and right
 pluralities of wheel motors nor the left and right
 hydraulic propeller motors using the propulsion
 selection levers.

2. The vehicle of claim 1 further comprising
 a left hose chase and a right hose chase located in the 25
 mechanical compartment, each of said left and right
 hose chases defining an upper opening in its upper end
 portion and a lower opening in its lower end portion, said
 upper openings being located above the waterline of the
 vehicle;
 an opening defined in the upper surface of each of the left
 and right undercarriage assemblies that aligns with the
 lower opening in the lower end portion of each of the left
 and right hose chases respectively;
 a left set of hydraulic lines routed through the left hose 35
 chase and the opening defined in the upper surface of the
 left undercarriage assembly fluidly connecting the left
 hydrostatic pump and the left hydraulic manifold assem-
 bly to the left plurality of wheel motors; and
 a right set of hydraulic lines routed through the right hose 40
 chase and the opening defined in the upper surface of the
 right undercarriage assembly fluidly connecting the
 right hydrostatic pump and the right hydraulic manifold
 assembly to the right plurality of wheel motors.

3. The vehicle of claim 2 wherein each of the hydraulic 45
 manifold assemblies further comprises:
 a manifold, said manifold defining four ports with the first
 and fourth ports being defined in opposing end portions
 of the manifold and the second and third ports being 50
 defined in the side portion of the manifold and located
 intermediate the first and second end portions of the
 manifold;
 a three-way valve fluidly connected between the hydro-
 static pump, the first port defined in said manifold, and
 the hydraulic propeller motor, whereby said three-way 55
 valve selectively allows fluid flow between the hydro-
 static pump and either the manifold or the hydraulic
 propeller motor;
 a propeller motor isolation valve fluidly connected
 between the hydraulic propeller motor and the manifold, 60
 said propeller motor isolation valve being mechanically
 connected to said three-way valve whereby when said
 three-way valve selectively allows fluid flow between
 the hydrostatic pump and the manifold said propeller
 motor isolation valve is closed to fluid flow and when 65
 said three-way valve selectively allows fluid flow
 between the hydrostatic pump and the hydraulic propel-

12

ler motor said propeller motor isolation valve is open to
 fluid flow, thereby allowing fluid flow between the mani-
 fold and the hydraulic propeller motor;
 a wheel motor valve fluidly connected between the second
 port defined in the manifold and the plurality of wheel
 motors; and
 a wheel motor bypass valve fluidly connected between the
 third port defined in the manifold and the hydrostatic
 pump and mechanically connected to said wheel motor
 valve whereby when said wheel motor valve is open to
 fluid flow between the manifold and the plurality of
 wheel motors said wheel motor bypass valve is closed to
 fluid flow between the manifold and the hydrostatic
 pump and when said wheel motor valve is closed to fluid
 flow between the manifold and the plurality of wheel
 motors said wheel motor bypass valve is open to fluid
 flow between the manifold and the hydrostatic pump.

4. The vehicle of claim 3 wherein the three-way valves on
 the left and right hydraulic manifold assemblies are mechani-
 cally connected to each other, the propeller motor isolation
 valves on the left and right hydraulic manifold assemblies are
 mechanically connected to each other, the wheel motor valves
 on the left and right hydraulic manifold assemblies are
 mechanically connected to each other, and the wheel motor
 bypass valves on the left and right hydraulic manifold assem-
 blies are mechanically connected to each other such that the
 corresponding valves in the first hydraulic manifold assembly
 and the second hydraulic manifold assembly permit fluid flow
 along identical paths.

5. The vehicle of claim 4 further comprising
 a mechanical connection between the first propulsion
 selection lever and the left and right hydraulic manifold
 assemblies whereby the fluid flow through three-way
 valves and the propeller isolation valves can be con-
 trolled and
 a mechanical connection between the second propulsion
 selection lever and the left and right hydraulic manifold
 assemblies whereby the fluid flow through wheel motor
 valves and the wheel motor bypass valves can be con-
 trolled.

6. The vehicle of claim 5 wherein the mechanical connec-
 tion between the first propulsion selection lever and the left
 and right hydraulic manifold assemblies is a push-pull cable
 and the mechanical connection between the second propul-
 sion selection lever and the left and right hydraulic manifold
 assemblies is a push-pull cable.

7. The vehicle of claim 4 wherein said passenger compart-
 ment includes means for controlling said vehicle.

8. An amphibious all-terrain vehicle comprising:
 a body assembly, said body assembly further comprising
 a passenger compartment housing a pair of propulsion
 selection levers;
 a mechanical compartment housing a power source, a
 left hydrostatic pump, a right hydrostatic pump, a left
 hydraulic propeller motor, a right hydraulic propeller
 motor, a left hydraulic manifold assembly, and a right
 hydraulic manifold assembly;
 a left undercarriage assembly; said left undercarriage
 assembly
 being conjoined to a bottom of said body assembly along
 a left edge of said body assembly and
 housing a left plurality of hydraulic wheel motors con-
 nected in series;
 a right undercarriage assembly; said right undercarriage
 assembly
 being conjoined to the bottom of said body assembly
 along a right edge of said body assembly and

13

housing a right plurality of hydraulic wheel motors connected in series;
 said left and right hydrostatic pumps being rotatably connected to said power source and fluidly connected to said left and right hydraulic manifold assemblies respectively;
 5 whereby a variable flow of hydraulic fluid from said left and right hydrostatic pumps is selectively directed through the left and right pluralities of wheel motors only, through the left and right pluralities of wheel motors and the left and right hydraulic propeller motors, through the left and right hydraulic propeller motors only, or through neither the left and right pluralities of wheel motors nor the left and right hydraulic propeller motors using the propulsion selection levers;
 10 a left hose chase and a right hose chase located in the mechanical compartment, each of said left and right hose chases defining a upper opening in its upper end portion and a lower opening in its lower end portion, said upper openings being located above the waterline of the vehicle;
 15 an opening defined in the upper surface of each of the left and right undercarriage assemblies that aligns with the lower opening in the lower end portion of each of the left and right hose chases respectively;
 20 a left set of hydraulic lines routed through the left hose chase and the opening defined in the upper surface of the left undercarriage assembly fluidly connecting the left hydrostatic pump and the left hydraulic manifold assembly to the left plurality of wheel motors; and
 25 a right set of hydraulic lines routed through the right hose chase and the opening defined in the upper surface of the right undercarriage assembly fluidly connecting the right hydrostatic pump and the right hydraulic manifold assembly to the right plurality of wheel motors.
 30
 9. An amphibious all-terrain vehicle comprising:
 a body assembly, said body assembly further comprising
 a floor having an inner surface and an outer surface;
 a passenger compartment;
 35 a mechanical compartment, said mechanical compartment including a first hydrostatic pump that outputs hydraulic fluid at a variable flow rate, a first hydraulic manifold assembly in fluid connection with the first hydrostatic pump capable, a second hydrostatic pump that outputs hydraulic fluid at a variable flow rate, a second hydraulic manifold assembly in fluid connection with the second hydrostatic pump, a left hydraulic propeller motor in fluid connection with the first hydraulic manifold assembly, a right hydraulic propeller motor in fluid connection with the second hydraulic manifold assembly, and a left hose chase and a right hose chase, each of said left and right hose chases defining a upper opening in its upper end portion and a lower opening in its lower end portion, said upper openings being located above a waterline of the vehicle;
 40 a left undercarriage assembly, said left undercarriage assembly
 being affixed to the outer surface of the floor of said body assembly along a left edge of said body assembly and having an opening that aligns with the lower opening of the left hose chase when said left undercarriage assembly is affixed to the outer surface of the floor assembly and
 45 housing a left plurality of hydraulic wheel motors connected in series, said left plurality of wheel motors

14

being fluidly connected to the first hydraulic manifold assembly using a pair of hydraulic lines routed through the left hose chase and said left plurality of motors being external to the body assembly;
 5 a right undercarriage assembly, said right undercarriage assembly
 being affixed to the outer surface of the floor of said body assembly along a right edge of said body assembly and having an opening that aligns with the lower opening of the right hose chase when said right undercarriage assembly is affixed to the outer surface of the floor assembly and
 10 housing a right plurality of hydraulic wheel motors connected in series, said right plurality of wheel motors being fluidly connected to the second hydraulic manifold assembly using a pair of hydraulic lines routed through the right hose chase and said right plurality of motors being external to the body assembly;
 15 whereby the first hydraulic manifold assembly selectively delivers the output provided by the first hydrostatic pump to the left plurality of hydraulic wheel motors or the left hydraulic propeller motor or both the left plurality of hydraulic wheel motors and the left hydraulic propeller motor and the second hydraulic manifold assembly selectively delivers the output provided by the second hydrostatic pump to the right plurality of hydraulic wheel motors or the right hydraulic propeller motor or both the right plurality of hydraulic wheel motors and the right hydraulic propeller motor.
 20
 10. The vehicle of claim 9 wherein each of the hydraulic manifold assemblies further comprises:
 25 a manifold, said manifold defining four ports with the first and fourth ports being defined in opposing end portions of the manifold and the second and third ports being defined in the side portion of the manifold and located intermediate the first and second end portions of the manifold;
 30 a three-way valve fluidly connected between the hydrostatic pump, the first port defined in said manifold, and the hydraulic propeller motor, whereby said three-way valve selectively allows fluid flow between the hydrostatic pump and either the manifold or the hydraulic propeller motor;
 35 a propeller motor isolation valve fluidly connected between the hydraulic propeller motor and the manifold, said propeller motor isolation valve being mechanically connected to said three-way valve whereby when said three-way valve selectively allows fluid flow between the hydrostatic pump and the manifold said propeller motor isolation valve is closed to fluid flow and when said three-way valve selectively allows fluid flow between the hydrostatic pump and the hydraulic propeller motor said propeller motor isolation valve is open to fluid flow, thereby allowing fluid flow between the manifold and the hydraulic propeller motor;
 40 a wheel motor valve fluidly connected between the second port defined in the manifold and the plurality of wheel motors; and
 45 a wheel motor bypass valve fluidly connected between the third port defined in the manifold and the hydrostatic pump and mechanically connected to said wheel motor valve whereby when said wheel motor valve is open to fluid flow between the manifold and the plurality of wheel motors said wheel motor bypass valve is closed to

15

fluid flow between the manifold and the hydrostatic pump and when said wheel motor valve is closed to fluid flow between the manifold and the plurality of wheel motors said wheel motor bypass valve is open to fluid flow between the manifold and the hydrostatic pump. 5

11. The vehicle of claim **10** wherein the three-way valves on the left and right hydraulic manifold assemblies are mechanically connected to each other, the propeller motor isolation valves on the left and right hydraulic manifold assemblies are mechanically connected to each other, the wheel motor valves on the left and right hydraulic manifold assemblies are mechanically connected to each other, and the wheel motor bypass valves on the left and right hydraulic manifold assemblies are mechanically connected to each other such that the corresponding valves in the first hydraulic manifold assembly and the second hydraulic manifold assembly permit fluid flow along identical paths. 10 15

16

12. The vehicle of claim **11** further comprising a mechanical connection between the first propulsion selection lever and the left and right hydraulic manifold assemblies whereby the fluid flow through three-way valves and the propeller isolation valves can be controlled and

a mechanical connection between the second propulsion selection lever and the left and right hydraulic manifold assemblies whereby the fluid flow through wheel motor valves and the wheel motor bypass valves can be controlled.

13. The vehicle of claim **12** wherein the mechanical connection between the first propulsion selection lever and the left and right hydraulic manifold assemblies is a push-pull cable and the mechanical connection between the second propulsion selection lever and the left and right hydraulic manifold assemblies is a push-pull cable. 15

* * * * *