

US007853302B2

(12) **United States Patent**
Rodriguez et al.

(10) **Patent No.:** US 7,853,302 B2
(45) **Date of Patent:** *Dec. 14, 2010

(54) **CATHETER WITH CONTRACTABLE MAPPING ASSEMBLY**

4,882,777 A 11/1989 Narula
4,920,980 A 5/1990 Jackowski

(Continued)

(75) Inventors: **Cynthia D. Rodriguez**, Chino Hills, CA (US); **Isabel B. Solte**, La Puente, CA (US)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Biosense Webster, Inc.**, Diamond Bar, CA (US)

EP 0 499 491 A2 8/1992

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

OTHER PUBLICATIONS

This patent is subject to a terminal disclaimer.

M. Haissaguerre et al., "Spontaneous Initiation of Atrial Fibrillation by Ectopic Beats or gmating in the Pulmonary Veins", The New England Journal of Medicine, 339:659-666 (Sep. 3), 1998.

Primary Examiner—Lee S Cohen
(74) *Attorney, Agent, or Firm*—Christie, Parker & Hale, LLP

(21) Appl. No.: **12/545,703**

(57) **ABSTRACT**

(22) Filed: **Aug. 21, 2009**

(65) **Prior Publication Data**
US 2009/0312623 A1 Dec. 17, 2009

The invention is directed to a mapping catheter useful for mapping tubular regions in and around the heart. The catheter comprises an elongated tubular catheter body. A mapping assembly is provided at the distal end of the catheter body. The mapping assembly comprises a tubular structure comprising a preformed generally circular main region generally transverse and distal to the catheter body and having an outer circumference. The tubular structure comprises a non-conductive cover over at least the main region of the mapping assembly. A plurality of electrodes are carried by the generally circular main region of the mapping assembly. A control handle is mounted at the proximal end of the catheter body. A contraction wire extends through the catheter body and non-conductive cover of the mapping assembly for contracting the generally circular main region of the mapping assembly. The contraction wire has a distal end anchored in the non-conductive cover and a proximal end anchored to a mechanism in the control handle that facilitates longitudinal movement of the contraction wire relative to the catheter body. The portion of the contraction wire extending through the non-conductive cover is positioned on the side of the generally circular main region closer to the center of the generally circular region.

Related U.S. Application Data

(63) Continuation of application No. 11/512,620, filed on Aug. 29, 2006, now Pat. No. 7,593,760, which is a continuation of application No. 10/386,872, filed on Mar. 12, 2003, now Pat. No. 7,142,903.

(51) **Int. Cl.**
A61B 5/04 (2006.01)

(52) **U.S. Cl.** 600/374; 600/381

(58) **Field of Classification Search** 600/374, 600/381; 606/41; 607/122


See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,203,430 A 5/1980 Takahashi
4,207,873 A 6/1980 Kruy
4,777,955 A 10/1988 Brayton et al.

19 Claims, 11 Drawing Sheets



U.S. PATENT DOCUMENTS

4,960,134 A 10/1990 Webster, Jr.
 4,984,581 A 1/1991 Stice
 5,170,787 A 12/1992 Lindegren
 5,255,679 A 10/1993 Imran
 5,263,493 A 11/1993 Avitall
 5,275,162 A 1/1994 Edwards et al.
 5,327,905 A 7/1994 Avitall
 5,354,297 A 10/1994 Avitall
 5,383,923 A 1/1995 Webster, Jr.
 5,445,148 A 8/1995 Jaraczewski et al.
 5,456,664 A 10/1995 Heinzelman et al.
 5,462,544 A 10/1995 Saksena et al.
 5,487,385 A 1/1996 Avitall
 5,545,200 A 8/1996 West et al.
 5,549,581 A 8/1996 Lurie et al.
 5,582,609 A 12/1996 Swanson et al.
 5,617,854 A 4/1997 Munsif
 5,626,136 A 5/1997 Webster, Jr.
 5,642,736 A 7/1997 Avitall
 5,656,030 A 8/1997 Hunjan et al.
 5,673,695 A 10/1997 McGee et al.
 5,680,860 A 10/1997 Imran
 5,730,127 A 3/1998 Avitall
 5,755,760 A 5/1998 Maguire et al.
 5,797,905 A 8/1998 Fleischman et al.
 5,800,428 A 9/1998 Nelson et al.
 5,823,955 A 10/1998 Kuck et al.
 5,827,278 A 10/1998 Webster, Jr.
 5,836,947 A 11/1998 Fleischman et al.
 5,860,920 A 1/1999 McGee et al.
 5,865,800 A 2/1999 Mirarchi et al.
 5,879,295 A 3/1999 Li et al.
 5,882,333 A 3/1999 Schaer et al.
 5,882,346 A 3/1999 Pomeranz et al.
 5,931,811 A 8/1999 Haissaguerre et al.
 5,935,102 A 8/1999 Bowden et al.
 5,938,694 A 8/1999 Jaraczewski et al.

5,951,471 A 9/1999 De la Rama et al.
 5,964,757 A 10/1999 Ponzi
 5,984,909 A 11/1999 Lurie et al.
 5,997,526 A 12/1999 Giba et al.
 6,002,955 A 12/1999 Willems et al.
 6,035,224 A 3/2000 West
 6,064,902 A 5/2000 Haissaguerre et al.
 6,088,614 A 7/2000 Swanson
 6,090,104 A 7/2000 Webster, Jr.
 6,096,036 A 8/2000 Bowe et al.
 6,106,522 A 8/2000 Fleischman et al.
 6,123,699 A 9/2000 Webster, Jr.
 6,129,724 A 10/2000 Fleischman et al.
 6,141,576 A 10/2000 Littmann et al.
 6,146,381 A 11/2000 Bowe et al.
 6,169,916 B1 1/2001 West
 6,171,277 B1 1/2001 Ponzi
 6,183,463 B1 2/2001 Webster, Jr.
 6,219,582 B1 4/2001 Hofstad et al.
 6,308,090 B1 10/2001 Tu et al.
 6,325,797 B1 12/2001 Stewart et al.
 6,371,955 B1 4/2002 Fuimaono et al.
 6,468,260 B1 10/2002 Bumbalough et al.
 6,500,167 B1 12/2002 Webster, Jr.
 6,522,933 B2 2/2003 Nguyen
 6,711,428 B2 3/2004 Fuimaono et al.
 6,866,662 B2 3/2005 Fuimaono et al.
 7,142,903 B2 11/2006 Rodriguez et al.
 7,593,760 B2 * 9/2009 Rodriguez et al. 600/374
 2002/0165532 A1 11/2002 Hill, III et al.
 2003/0125663 A1 7/2003 Coleman et al.

FOREIGN PATENT DOCUMENTS

EP 0 928 601 A1 7/1999
 EP 0 985 423 A2 3/2000
 WO WO 95/10225 4/1995
 WO WO 02/45608 A2 6/2002

* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6




FIG. 7





FIG. 8







FIG. 9

FIG. 10



1

CATHETER WITH CONTRACTABLE MAPPING ASSEMBLY

CROSS-REFERENCE TO RELATED APPLICATION

This application is a continuation of U.S. patent application Ser. No. 11/512,620, filed Aug. 29, 2006 and entitled CATHETER WITH CONTRACTABLE MAPPING ASSEMBLY (now U.S. Pat. No. 7,593,760) which is a continuation of U.S. patent application Ser. No. 10/386,872, filed Mar. 12, 2003 and entitled CATHETER WITH CONTRACTABLE MAPPING ASSEMBLY (now U.S. Pat. No. 7,142,903) the entire contents of which are incorporated herein by reference.

FIELD OF THE INVENTION

The present invention relates to an improved mapping catheter that is particularly useful for mapping electrical activity in a tubular region of or near the heart.

BACKGROUND OF THE INVENTION

Atrial fibrillation is a common sustained cardiac arrhythmia and a major cause of stroke. This condition is perpetuated by reentrant wavelets propagating in an abnormal atrial-tissue substrate. Various approaches have been developed to interrupt wavelets, including surgical or catheter-mediated ablation. Prior to treating the condition, one has to first determine the location of the wavelets. Various techniques have been proposed for making such a determination. None of the proposed techniques, however, provide for measurement of the activity within a pulmonary vein, coronary sinus or other tubular structure about the inner circumference of the structure.

SUMMARY OF THE INVENTION

The present invention is directed to a catheter having a mapping assembly and a method for measuring electrical activity within a tubular region of or near the heart, e.g., a pulmonary vein, the coronary sinus, the superior vena cava, or the pulmonary outflow tract.

In one embodiment, the invention is directed to a mapping catheter useful for mapping tubular regions in and around the heart. The catheter comprises an elongated tubular catheter body. A mapping assembly is provided at the distal end of the catheter body. The mapping assembly comprises a tubular structure comprising a pre-formed generally circular main region generally transverse and distal to the catheter body and having an outer circumference. The tubular structure comprises a non-conductive cover over at least the main region of the mapping assembly. A plurality of electrodes are carried by the generally circular main region of the mapping assembly. A control handle is mounted at the proximal end of the catheter body. A contraction wire extends through the catheter body and non-conductive cover of the mapping assembly for contracting the generally circular main region of the mapping assembly. The contraction wire has a distal end anchored in the non-conductive cover and a proximal end anchored to a mechanism in the control handle that facilitates longitudinal movement of the contraction wire relative to the catheter body. The portion of the contraction wire extending through the non-conductive cover is positioned on the side of the generally circular main region closer to the center of the generally circular region.

2

In another embodiment the invention is directed to a mapping catheter comprising an elongated tubular catheter body having an outer wall and proximal and distal ends. A mapping assembly is provided at the distal end of the catheter body.

5 The mapping assembly comprises a tubular structure comprising a pre-formed generally circular main region generally transverse and distal to the catheter body and having an outer circumference. The tubular structure comprises a non-conductive cover over at least the main region of the mapping assembly and a pre-formed support member extending through a plastic tube that extends through the non-conductive cover. A plurality of electrodes are carried by the generally circular main region of the mapping assembly. A control handle is mounted at the proximal end of the catheter body. A contraction wire extends through the catheter body and through the plastic tube within non-conductive cover of the mapping assembly for contracting the generally circular main region of the mapping assembly. The contraction wire has a distal end anchored in the non-conductive cover and a proximal end anchored to a mechanism in the control handle that facilitates longitudinal movement of the contraction wire relative to the catheter body. The portion of the contraction wire extending through the non-conductive cover is positioned on the side of the generally circular main region closer to the center of the generally circular region. A deflection wire also extends through the catheter body. The deflection wire has a distal end fixedly attached to the catheter body near the catheter body's distal end and a proximal end anchored to a mechanism in the control handle that facilitates longitudinal movement of the deflection wire relative to the catheter body.

In another embodiment, the invention is directed to a method for mapping electrical activity within a tubular region of or near the heart having an inner circumference. The method comprises inserting the distal end of a catheter as described above into the heart. The outer circumference of the generally circular main region is contacted with the inner circumference of the tubular region. The electrical activity within the tubular region is mapped with the electrodes along the generally circular main region.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other features and advantages of the present invention will be better understood by reference to the following detailed description when considered in conjunction with the accompanying drawings wherein:

FIG. 1 is a side view of an embodiment of the catheter of the invention.

FIG. 2 is a schematic side cross-sectional view of the catheter body of FIG. 1, including the junction between the catheter body and distal shaft.

FIG. 3 is a side view of the distal shaft and mapping assembly of the catheter according to FIG. 1.

FIG. 4a is schematic view of the mapping assembly showing one arrangement of the ring electrodes.

FIG. 4b is schematic view of the mapping assembly showing an alternative arrangement of the ring electrodes.

FIG. 5 is a side cross-sectional view of the distal end of the mapping assembly of the catheter of FIG. 1.

FIG. 6 is an end cross-sectional view of the mapping assembly of the catheter of FIG. 3 along line 6-6.

FIG. 7 is an end cross-sectional view of the distal shaft of the catheter of FIG. 3 along line 7-7.

FIG. 8 is a side cross-sectional view of a control handle in accordance with the invention.

FIG. 9 is an exploded perspective view of the interior components of the control handle shown in FIG. 8.

3

FIG. 10 is an enlarged side cross-sectional view of the control handle of FIG. 8 showing the deflection wire adjuster and the contraction wire adjuster.

DETAILED DESCRIPTION OF THE INVENTION

According to the invention, there is provided a catheter having a mapping assembly at its distal end. As shown in FIG. 1, the catheter comprises an elongated catheter body 12 having proximal and distal ends, a control handle 16 at the proximal end of the catheter body, and a mapping assembly 17 mounted at the distal end of the catheter body.

In the depicted embodiment, the catheter body 12 includes an elongated proximal shaft 13 at its proximal end and a shorter distal shaft 14 at its distal end. With reference to FIG. 2, the proximal shaft 13 comprises an elongated tubular construction having a single, axial or central lumen 18. The proximal shaft 13 is flexible, i.e., bendable, but substantially non-compressible along its length. The proximal shaft 13 can be of any suitable construction and made of any suitable material. A presently preferred construction comprises an outer wall 20 made of polyurethane or PEBAX. The outer wall 20 comprises an imbedded braided mesh of stainless steel or the like, as is generally known in the art, to increase torsional stiffness of the proximal shaft 13 so that, when the control handle 16 is rotated, the distal shaft 14 will rotate in a corresponding manner.

The outer diameter of the proximal shaft 13 is not critical, but is preferably no more than about 8 french, more preferably 7 french. Likewise the thickness of the outer wall 20 is not critical, but is thin enough so that the central lumen 18 can accommodate any desired wires, cables and/or tubes. The inner surface of the outer wall 20 is lined with a stiffening tube 21 to provide improved torsional stability. The outer diameter of the stiffening tube 21 is about the same as or slightly smaller than the inner diameter of the outer wall 20. The stiffening tube 21 can be made of any suitable material, such as polyimide, which provides very good stiffness and does not soften at body temperature.

The distal shaft 14 comprises a short section of tubing having four lumens, namely, a lead wire lumen 30, a contraction wire lumen 32, a support member lumen 34, and a deflection wire lumen 36. The tubing of the distal shaft 14 is made of a suitable non-toxic material that is preferably more flexible than the proximal shaft 13. A presently preferred material for the distal shaft tubing is braided polyurethane, i.e., polyurethane with an embedded mesh of braided stainless steel or the like. The size of each lumen is not critical, but is sufficient to house the components extending therethrough, as discussed further below.

The useful length of the catheter, i.e., that portion that can be inserted into the body excluding the mapping assembly 17, can vary as desired. Preferably the useful length ranges from about 110 cm to about 120 cm. The length of the distal shaft 14 is a relatively small portion of the useful length, and preferably ranges from about 3.5 cm to about 11 cm, more preferably from about 5 cm to about 6.5 cm.

A preferred means for attaching the proximal shaft 13 to the distal shaft 14 is illustrated in FIG. 2. The proximal end of the distal shaft 14 comprises an outer circumferential notch 23 that receives the inner surface of the outer wall 20 of the catheter body 12. The distal shaft 14 and catheter body 12 are attached by glue or the like. If desired, a spacer (not shown) can be provided within the proximal shaft 13 between the distal end of the stiffening tube 20 and the proximal end of the distal shaft 14 to provide a transition in flexibility at the junction of the proximal shaft and distal shaft, which allows

4

the junction of the proximal and distal shafts to bend smoothly without folding or kinking. An example of such a spacer is described in more detail in U.S. Pat. No. 5,964,757, the disclosure of which is incorporated herein by reference.

At the distal end of the distal shaft 14 is a mapping assembly 17, as shown in FIGS. 3 to 6. The mapping assembly 17 comprises a generally straight proximal region 38 and a generally circular main region 39. The proximal region 38 is mounted on the distal shaft 14, as described in more detail below, so that its axis is generally parallel to the axis of the distal shaft. The proximal region 38 preferably has an exposed length, e.g., not contained within the distal shaft 14, ranging from about 3 mm to about 12 mm, more preferably about 3 mm to about 8 mm, still more preferably about 5 mm inch, but can vary as desired.

The generally circular main region 39 is generally traverse to the catheter body 12. The generally circular main region 39 is preferably generally perpendicular to the catheter body 12. The generally circular main region 39 can form a flat circle or can be very slightly helical, as shown in FIG. 3. The main region 39 has an outer diameter preferably ranging to about 10 mm to about 25 mm, more preferably about 12 mm to about 20 mm. The generally circular main region 39 can curve in a clockwise direction or a counterclockwise direction.

The mapping assembly 17 is formed of a non-conductive cover 22, which is preferably generally tubular, but can have any cross-sectional shape as desired. The non-conductive cover 22 can be made of any suitable material, and is preferably made of a biocompatible plastic such as polyurethane or PEBAX. The non-conductive cover 22 can be pre-formed into the desired generally circular shape of the generally circular main region. Alternatively, the shape of the generally circular main region can be defined by a wire or other component extending through the non-conductive cover 22.

In the depicted embodiment, a preformed support member 24 extends through the non-conductive cover 22 to define the shape of the generally circular main region 39. The support member 24 is made of a material having shape-memory, i.e., that can be straightened or bent out of its original shape upon exertion of a force and is capable of substantially returning to its original shape upon removal of the force. A particularly preferred material for the support member 24 is a nickel/titanium alloy. Such alloys typically comprise about 55% nickel and 45% titanium, but may comprise from about 54% to about 57% nickel with the balance being titanium. A preferred nickel/titanium alloy is Nitinol, which has excellent shape memory, together with ductility, strength, corrosion resistance, electrical resistivity and temperature stability.

A series of ring electrodes 26 are mounted on the non-conductive cover 22 of the generally circular main region 39 of the mapping assembly 17, as shown in FIGS. 4a and 4b. The ring electrodes 26 can be made of any suitable solid conductive material, such as platinum or gold, preferably a combination of platinum and iridium, and mounted onto the non-conductive cover 22 with glue or the like. Alternatively, the ring electrodes 26 can be formed by coating the non-conductive cover 22 with an electrically conducting material, like platinum, gold and/or iridium. The coating can be applied using sputtering, ion beam deposition or an equivalent technique.

In a preferred embodiment, each ring electrode 26 is mounted by first forming a hole in the non-conductive cover 22. An electrode lead wire 50 is fed through the hole, and the ring electrode 26 is welded in place over the lead wire and non-conductive cover 22. The lead wires 50 extend through the non-conductive cover 22 and into the catheter body 12. The proximal end of each lead wire 50 is electrically con-

5

ected to a suitable connector (not shown), which is connected an appropriate monitor or other device for receiving and displaying the information received from the ring electrodes 26.

The number of ring electrodes 26 on the assembly can vary as desired. Preferably the number of ring electrodes ranges from about six to about twenty, more preferably from about eight to about twelve. In one embodiment, the assembly carries ten ring electrodes. The ring electrodes 26 can be approximately evenly spaced around the generally circular main region 39, as shown in FIG. 4a. In a particularly preferred embodiment, a distance of approximately 5 mm is provided between the centers of the ring electrodes 26.

An alternative electrode arrangement is depicted in FIG. 4b. In this embodiment, the mapping assembly 17 includes a series of ring electrode pairs 25. Each ring electrode pair 25 comprises two closely-spaced ring electrodes 26. As used herein, the term "ring electrode pair" refers to a pair of ring electrodes that are arranged closer to each other than they are to the other adjacent ring electrodes. Preferably the distance between two electrodes 26 of an electrode pair 25 is less than about 3 mm, more preferably less than about 2 mm, still more preferably from about 0.5 mm to about 1.5 mm. The number of electrode pairs 25 can vary as desired, and preferably ranges from 6 to 14 pairs, more preferably 10 pairs.

In a particularly preferred embodiment, the mapping assembly carries 10 pairs of electrodes with a space of approximately 1 mm between the two electrodes 26 of each pair 25. Preferably each ring electrode 26 is relatively short, having a length ranging from about 0.4 mm to about 0.75 mm, with the most distal ring electrode 26c being longer than the other ring electrodes, preferably having a length ranging from about 1 mm to about 1.5 mm. The longer ring electrode provides a signal to the user when the catheter is being viewed under fluoroscopy. Specifically, because the mapping assembly is generally circular, it can be difficult for the user to determine which electrodes are placed at a particular location in the heart. By having one ring electrode, such as the most distal ring electrode, sized differently from the other ring electrodes, the user has a reference point when viewing the catheter under fluoroscopy.

Regardless of the size and number of the ring electrodes 26, the electrode pairs 25 are preferably approximately evenly spaced around the generally circular main region 39. The closely-spaced electrode pairs 25 allow for more accurate detection of near field pulmonary vein potential versus far field atrial signals, which is very important when trying to treat atrial fibrillation. Specifically, the near field pulmonary vein potentials are very small signals whereas the atria, located very close to the pulmonary vein, provides much larger signals. Accordingly, even when the mapping array is placed in the pulmonary vein, it can be difficult for the physician to determine whether the signal is a small, close potential (from the pulmonary vein) or a larger, farther potential (from the atria). Closely-spaced bipoles permit the physician to more accurately determine whether he is looking at a close signal or a far signal. Accordingly, by having closely-spaced electrodes, one is able to target exactly the locations of myocardial tissue that have pulmonary vein potentials and therefore allows the clinician to deliver therapy to the specific tissue. Moreover, the closely-spaced electrodes allow the physician to determine the exact anatomical location of the ostium by the electrical signal.

If desired, additional electrodes (not shown) could be mounted along the distal shaft 14 and/or the generally straight proximal section 39.

6

A contraction wire 40 is provided to contract the generally circular main region 39 to thereby reduce its diameter. The contraction wire 40 has a proximal end anchored in the control handle 16, which is used to manipulate the contraction wire as described further below. The contraction wire 40 extends through the central lumen 18 of the proximal shaft 13, through the contraction wire lumen 32 of the distal shaft 14 and into the non-conductive cover 22. The portion of the contraction wire 40 extending through the non-conductive cover 22 is positioned on the side of the generally circular main region 39 closer to the center of the generally circular main region, as best shown in FIGS. 5 and 6. The center of the generally circular main region refers to the center of the circle formed by the generally circular main region. With this arrangement, contraction of the generally circular main region 39 is dramatically improved over arrangements where the position of the contraction wire 40 is not so controlled.

As shown in FIGS. 5 and 6, within the mapping assembly 17, the contraction wire 40 extends through a plastic tube 42. In one embodiment, the plastic tube 42 comprise three layers, including an inner layer of polyimide over which a braided layer is formed, the braided layer comprising a braided stainless steel mesh or the like, as is generally known in the art. The braided layer enhances the strength of the plastic tube 42, reducing the tendency for the contraction wire 40 to straighten the preformed curve of the mapping assembly. A thin plastic layer of polytetrafluoroethylene is provided over the braided layer to protect the braided layer from getting tangled with the lead wires 50 within the non-conductive cover 22. The plastic tube 42 has a proximal end anchored to the distal end of the distal shaft 14. The support member 24 extends through the plastic tube 42 with the contraction wire 40. The distal ends of the support member 24 and the contraction wire 40 are soldered or otherwise attached to a small stainless steel tube 44. With this arrangement, the relative positions of the contraction wire 40 and the support member 24 can be controlled so that the contraction wire 40 can be positioned on the side of the generally circular region closer to the center of the generally circular region, as described above. The contraction wire 40 on the inside of the curve pulls the support member 24 to the inside of the curve, enhancing contraction of the generally circular region 39. Further, when the plastic tube 42 includes a braided layer, it keeps the contraction wire 40 from tearing through the non-conductive cover 22.

A first compression coil 46 is situated within the proximal shaft 13 and distal shaft 14 in surrounding relation to the contraction wire 40. The first compression coil 46 extends from the proximal end of the proximal shaft 13 and through the contraction wire lumen 32. The first compression coil 46 is made of any suitable metal, preferably stainless steel, and is tightly wound on itself to provide flexibility, i.e., bending, but to resist compression. The inner diameter of the first compression coil 46 is preferably slightly larger than the diameter of the contraction wire 40. The outer surface of the first compression coil 46 is covered by a flexible, non-conductive sheath 68, e.g., made of polyimide tubing. The first compression coil 46 preferably is formed of a wire having a square or rectangular cross-sectional area, which makes it less compressible than a compression coil formed from a wire having a circular cross-sectional area. As a result, the first compression coil 46 keeps the catheter body 12, and particularly the distal shaft 14, from deflecting when the contraction wire 40 is manipulated to contract the mapping assembly 17 as it absorbs more of the compression.

The first compression coil 46 is anchored at its proximal end to the outer wall 20 of the catheter body 12 by proximal

glue joint **70** and to the distal shaft **14** by distal glue joint **72**. Both glue joints **70** and **72** preferably comprise polyurethane glue or the like. The glue may be applied by means of a syringe or the like through a hole made between the outer surface of the catheter body **12** and the central lumen **18**. Such a hole may be formed, for example, by a needle or the like that punctures the outer wall **20** of the catheter body **12** which is heated sufficiently to form a permanent hole. The glue is then introduced through the hole to the outer surface of the first compression coil **46** and wicks around the outer circumference to form a glue joint about the entire circumference of the compression coil.

In the depicted embodiment, the distal end of the mapping assembly **17** is sealed closed with a dome **54** of polyurethane glue or the like. A short ring **56**, made of metal or plastic, and preferably polyamide, is mounted within the distal end of the non-conductive cover **22**. The short ring **56** prevents the distal end of the non-conductive cover **22** from collapsing, there by maintaining the diameter of the non-conductive cover at its distal end.

At the junction of the distal shaft **14** and the mapping assembly **17**, the non-conductive cover **22** is attached to the distal shaft by glue or the like. The plastic tube **42** has its proximal end inserted and glued in the distal end of the distal shaft **14**. The glue from the plastic tube **42** can further serve to anchor the distal end of the first compression coil **46** in place within the contraction wire lumen **32**. The support member **24** extends from the support member lumen **32** into the plastic tube **42** within the non-conductive cover **22**. The proximal end of the support member **24** terminates a short distance within the support member lumen **34**, approximately about 5 mm, so as not to adversely affect the ability of the distal shaft **14** to deflect. However, if desired, the proximal end of the support member **24** can extend further into the catheter body **12**.

The lead wires **50** attached to the ring electrodes **26** extend through the lead wire lumen **30** of the distal shaft **14**, through the central lumen **18** of the catheter body **12**, and the control handle **16**, and terminate at their proximal end in a connector (not shown). The portion of the lead wires **50** extending through the central lumen **18** of the catheter body **12**, control handle **16** and proximal end of the distal shaft **14** are enclosed within a protective sheath **52**, which can be made of any suitable material, preferably polyimide. The protective sheath **52** is anchored at its distal end to the proximal end of the distal shaft **14** by gluing it in the lead wire lumen **30** with polyurethane glue or the like.

A deflection wire **64** is provided for deflection of the distal shaft **14**. The deflection wire **64** extends through the proximal shaft **13**, and is anchored at its proximal end to the control handle **16** and at its distal end to the distal shaft **14**. The deflection wire **64** is made of any suitable metal, such as stainless steel or Nitinol, and is preferably coated with Teflon® or the like. The coating imparts lubricity to the puller wire **64**. The puller wire **64** preferably has a diameter ranging from about 0.006 to about 0.010 inch.

The deflection wire **64** extends into the deflection wire lumen **36** of the distal shaft **14**. Preferably the deflection wire **64** is anchored at its distal end to the sidewall of the distal shaft **14**, as is generally described in U.S. Pat. No. 6,371,955, the disclosure of which is incorporated herein by reference.

A second compression coil **66** is situated within the proximal shaft **13** in surrounding relation to the deflection wire **64**. The second compression coil **66** extends from the proximal end of the proximal shaft **13** to the distal end of the proximal shaft. The second compression coil **66** is made of any suitable metal, preferably stainless steel, and is tightly wound on itself

to provide flexibility, i.e., bending, but to resist compression. The inner diameter of the second compression coil **66** is preferably slightly larger than the diameter of the deflection wire **64**. The Teflon® coating on the deflection wire **64** allows it to slide freely within the second compression coil **66**. Within the proximal shaft **13**, the outer surface of the second compression coil **66** is also covered by a flexible, non-conductive sheath **68**, e.g., made of polyimide tubing. The second compression coil **66** is anchored at its proximal end to the outer wall **20** of the catheter body **12** by the proximal glue joint **70** and to the distal shaft **14** by the distal glue joint **72**. Within the deflection wire lumen **36** of the distal shaft **14**, the deflection wire **64** and second compression coil **66** extends through a plastic, preferably Teflon®, puller wire sheath **71**, which prevents the puller wire **64** from cutting into the wall of the distal shaft when the distal shaft is deflected.

Longitudinal movement of the contraction wire **40** relative to the catheter body **12**, which results in contraction of the generally circular main region **39** of the mapping assembly **17**, is accomplished by suitable manipulation of the control handle **16**. Similarly, longitudinal movement of the deflection wire **64** relative to the catheter body **12**, which results in deflection of the distal shaft **14**, is accomplished by suitable manipulation of the control handle **16**. Suitable control handles for manipulating more than one wire are described, for example, in U.S. Pat. Nos. 6,468,260, 6,500,167, and 6,522,933, the disclosures of which are incorporated herein by reference.

In one embodiment, the catheter includes a control handle **16** as shown in FIGS. **8** to **10**. The control handle **16** includes a handle body **74** in which a core **76** is fixedly mounted. The core has a generally cylindrical distal region **75** and a generally cylindrical proximal region **77** having a larger diameter than the proximal region.

For longitudinal movement of the deflection wire **64**, a piston **82** is slidably mounted over the distal region **77** of the core **76**. The proximal end of the piston **82** is maintained within the handle body **74**, and the distal end of the piston extends outside the handle body. A thumb knob **84** is mounted in surrounding relation to a portion of the distal end of the piston **82** so that the user can more easily move the piston longitudinally relative to the core **76** and handle body **74**. The proximal end of the catheter body **12** is fixedly mounted to the distal end of the piston **82** through a tip portion **78** that is mounted on the distal end of the piston. The proximal end of the catheter body **12** is inserted into an axial passage **80** in the tip portion and optionally glued in place. The piston includes an axial passage **86** in communication with the axial passage **80** of the tip portion **78**, and the core **76** includes an axial passage **88** in communication with the axial passage in the piston. The lead wires **50**, contraction wire **46** and deflection wire **66** that extend through the catheter body **12** extend out the proximal end of the catheter body and through the axial passages in the tip portion **78**, piston **82** and core **76**. The lead wires **50** can extend out the proximal end of the control handle **16** or can be connected to a connector (not shown) that is incorporated into the control handle, as is generally known in the art.

The proximal end of the deflection wire **64** is anchored to the core **76**. As best seen in FIG. **10**, the portion of the axial passage **88** extending through the proximal region **77** of the core **76** has a larger diameter than the portion of the axial passage extending through the distal region **75** of the core **76**. A deflection wire adjuster **90** is adjustably mounted, as described further below, in a portion of the axial passage **88** near the distal end of the proximal region **77** of the core **76**. The deflection wire adjuster **90** has an opening **92** extending

therethrough in a direction generally perpendicular to the axial passage 88 of the core 76. The deflection wire 64 extends through the opening 92 in the deflection wire adjuster 90 such that the deflection wire changes directions.

The proximal end of the deflection wire 64 is then anchored to the core 76. Specifically, the distal region 77 of the core 76 includes a generally rectangular opening 94 that extends generally parallel to the axial passage 88 of the core. A channel 96 connects the proximal end of the generally rectangular opening 94 to the distal end of the portion of the axial passage 88 in the proximal region 75 of the core 76. The proximal end of the deflection wire 64 extends through the channel 96 and into the generally rectangular opening 94. A deflection wire anchor 98, which can comprise a short piece of hypodermic stock, is fixedly attached, for example, by crimping, to a portion of the proximal end of the deflection wire 64 within the generally rectangular opening 94. The deflection wire anchor 98 has a diameter greater than the width of the channel 96 and thus prevents the proximal end of the deflection wire 64 from being pulled through the channel, thereby anchoring the deflection wire to the core 76.

In use, the piston 82 is moved distally relative to the handle body 74 and core 76, thereby pulling the catheter body 12 distally relative to the deflection wire 64, which is anchored to the core. As a result, the deflection wire 64 pulls on the side of the distal shaft 14 to which it is anchored, thereby deflecting the distal shaft in that direction. To straighten the distal shaft 14, the piston 82 is moved proximally back to its original position relative to the handle body 74 and core 76.

Manipulation of the deflection wire adjuster 90 adjusts the amount of free play in the deflection wire 64. As noted above, the deflection wire adjuster 90 is adjustably mounted in a portion of the axial passage 88 near the distal end of the proximal region 77 of the core 76. The portion of the axial passage 88 in which the deflection wire adjuster 90 is mounted includes a series of ridges 100 extending along the surface of the core 76, with the ridges being generally perpendicular to the axis of the core. The deflection wire adjuster 90 carries an outwardly extending tab 102 that fits in the spaces between the ridges 100. The deflection wire adjuster 90 can be moved along the length of the core 76 and snapped into place by placing the tab 102 between two ridges 100. As the deflection wire adjuster 90 is moved proximally (away from catheter body 12) less free play is provided for the deflection wire 64. The precise mechanism for adjusting the amount of free play of the deflection wire 64 is not critical, and alternative mechanisms can be provided. Alternatively, the deflection wire 64 can be anchored directly to the core 76 so that it is not adjustable.

The control handle 16 is also used for longitudinal movement of the contraction wire 40. The contraction wire 40 extends from the catheter body 12, through the axial passage 86 in the piston 82 and through the axial passage 88 within the distal region 75 of the core 76. The proximal end of the contraction wire 40 is anchored to a contraction wire adjuster 104 that is slidably mounted in the core 76.

The contraction wire adjuster 104 is generally rectangular having a bottom region 108 that extends downward through a slot 110 in the proximal region 77 of the core 76, the slot being in communication with the axial passage 88 of the core. The proximal end of the contraction wire 40, which, as noted above, extends through the axial passage 88, is anchored in the contraction wire adjuster 104 in a manner very similar to the manner in which the deflection wire 64 is anchored to the core 76, as described above. Specifically, a contraction wire anchor 108, which can comprise a short piece of hypodermic stock, is fixedly attached, for example, by crimping, to a

portion of the proximal end of the contraction wire 40 within an opening 110 in the contraction wire adjuster 104. A channel 112 connects the opening 110 to the axial passage 88 in the core. The contraction wire anchor 98 has a diameter greater than the width of the channel 112 and thus prevents the proximal end of the contraction wire 40 from being pulled through the channel, thereby anchoring the contraction wire to the contraction wire adjuster 104.

The distal end of the contraction wire adjuster 104 is adjustably attached to a cam receiver 106. The cam receiver 106 is generally tubular, having a short slot 114 extending from its proximal end sized to receive the distal end of the contraction wire adjuster 104. The cam receiver 106 is slidably mounted over the piston 82 and the distal region 75 of the core 76 with the bottom portion of the contraction wire adjuster 104 positioned in the slot 114 in the core and a corresponding slot 115 in the piston.

As shown in FIG. 9, the top of the distal end of the contraction wire adjuster 104 includes a series of outwardly extending teeth 116 that mate with a plurality of notches 118 within the slot 114 of the cam receiver 106 so that the contraction wire adjuster can be snapped into the cam receiver. The position of the contraction wire adjuster 104 relative to the cam receiver 106 can be longitudinally adjusted by repositioning the teeth 116 relative to the notches 118, to thereby adjust the tension on the contraction wire 40.

Longitudinal movement of the cam receiver 106 and contraction wire adjuster 104 relative to the core 76, to which the catheter body 12 is indirectly mounted, results in longitudinal movement of the contraction wire 40 relative to the catheter body. Longitudinal movement of the cam receiver 106 is accomplished through a cam 120 mounted in the control handle 16 in surrounding relation to the piston 82 and distal region 75 of the core 76. A retaining ring 121 maintains the longitudinal position of the cam 120 relative to the handle body 74.

The cam 120 includes a ramped proximal surface 122. The cam receiver 106 includes a ramped distal surface 123 and an outwardly extending tab 124 at the most distal point of the ramped distal surface. The tab 124 contacts the ramped proximal surface 122 of the cam 120. When the cam 120 is rotated counterclockwise, the ramped proximal surface 122 correspondingly rotates and pushes the cam receiver 104 proximally relative to the core 76 and catheter body 12. As the cam receiver 104 and the attached contraction wire adjuster 104 are moved proximally relative to the core 76 and catheter body 12, the contraction wire 40 is pulled proximally to thereby contract the generally circular main region 39 of the mapping assembly 17.

The ramped proximal surface 122 of the cam 120 includes an outwardly extending tab 126 at its most proximal point. As the cam 120 is rotated counterclockwise, the tab 124 on the cam receiver 104 contacts the tab 126 on the ramped proximal surface 122, thereby prohibiting further rotation of the cam relative to the cam receiver. As the cam 120 is rotated clockwise, the tab 126 on the ramped proximal surface 122 pushes the tab 124 on the cam receiver 104 such that the cam receiver moves distally, thereby releasing the tension on the contraction wire 40 so that the generally circular main region 39 of the mapping assembly 17 returns to its original configuration. As would be recognized by one skilled in the art, the direction of the ramped proximal surface 122 can be changed so that clockwise rotation of the cam 120 causes contraction of generally circular main region 39 of the mapping assembly 17 and counterclockwise rotation causes it to return to its origi-

11

nal configuration. A flexible grip **128** is provided over the cam **120** for the user to more easily and comfortably rotate the cam **120**.

In use, a suitable guiding sheath is inserted into the patient with its distal end positioned at a desired mapping location. An example of a suitable guiding sheath for use in connection with the present invention is the Preface™ Braiding Guiding Sheath, commercially available from Biosense Webster, Inc. (Diamond Bar, Calif.). The distal end of the sheath is guided into one of the atria. A catheter in accordance with the present invention is fed through the guiding sheath until its distal end extends out of the distal end of the guiding sheath. As the catheter is fed through the guiding sheath, the mapping assembly **17** is straightened to fit through the sheath. Once the distal end of the catheter is positioned at the desired mapping location, the guiding sheath is pulled proximally, allowing the deflectable distal shaft **14** and mapping assembly **17** to extend outside the sheath, and the mapping assembly **17** returns to its original shape due to the shape-memory of the support member **24**. The mapping assembly **17** is then inserted into a pulmonary vein or other tubular region (such as the coronary sinus, superior vena cava, or inferior vena cava) so that the outer circumference of the generally circular main region **39** of the assembly is in contact with a circumference inside the tubular region. Preferably at least about 50%, more preferably at least about 70%, and still more preferably at least about 80% of the circumference of the generally circular main region is in contact with a circumference inside the tubular region.

The circular arrangement of the electrodes **26** permits measurement of the electrical activity at that circumference of the tubular structure so that ectopic beats between the electrodes can be identified. The size of the generally circular main region **39** permits measurement of electrical activity along a diameter of a pulmonary vein or other tubular structure of or near the heart because the circular main region has a diameter generally corresponding to that of a pulmonary vein or the coronary sinus.

The preceding description has been presented with reference to presently preferred embodiments of the invention. Workers skilled in the art and technology to which this invention pertains will appreciate that alterations and changes in the described structure may be practiced without meaningfully departing from the principal, spirit and scope of this invention.

Accordingly, the foregoing description should not be read as pertaining only to the precise structures described and illustrated in the accompanying drawings, but rather should be read consistent with and as support to the following claims which are to have their fullest and fair scope

What is claimed is:

1. A mapping catheter comprising:

an elongated tubular proximal shaft having an outer wall and proximal and distal ends;

a distal shaft having proximal and distal ends, the proximal end of the distal shaft being attached to the distal end of the proximal shaft;

a mapping assembly at the distal end of the distal shaft, the mapping assembly comprising:

a tubular structure comprising a pre-formed generally circular main region generally transverse and distal to the proximal shaft and having an outer circumference, wherein the tubular structure comprises a non-conductive cover over at least the main region of the mapping assembly, and

a plurality of electrodes carried by the generally circular main region of the mapping assembly;

a control handle mounted at the proximal end of the proximal shaft; and

12

a contraction wire extending through the proximal shaft and non-conductive cover of the mapping assembly for contracting the generally circular main region of the mapping assembly, the contraction wire having a distal end anchored in the non-conductive cover and a proximal end anchored to a mechanism in the control handle that facilitates longitudinal movement of the contraction wire relative to the catheter body, wherein the portion of the contraction wire extending through the non-conductive cover extends through a plastic tube and is positioned on the side of the generally circular main region closer to the center of the generally circular region.

2. A catheter according to claim **1**, wherein the plastic tube comprises polyimide.

3. A catheter according to claim **1**, wherein the plastic tube comprises a polyimide layer and a braided metal layer over the polyimide layer.

4. A catheter according to claim **1**, wherein the mapping assembly further comprises a pre-formed support member having at least a portion extending through the non-conductive cover.

5. A catheter according to claim **4**, wherein the pre-formed support member comprises nitinol.

6. A catheter according to claim **4**, wherein the portion of the contraction wire and the portion of the pre-formed support member extending through the non-conductive cover extend through the plastic tube.

7. A catheter according to claim **6**, wherein the plastic tube comprises polyimide.

8. A catheter according to claim **6**, wherein the plastic tube comprises a polyimide layer and a braided metal layer over the polyimide layer.

9. A catheter according to claim **6**, wherein the contraction wire and the pre-formed support member each have a distal end anchored to a metal tube.

10. A catheter according to claim **6**, wherein the portion of the contraction wire extending through the non-conductive cover is positioned closer than the support member to the center of the generally circular region.

11. A catheter according to claim **4**, wherein the portion of the contraction wire extending through the non-conductive cover is positioned closer than the support member to the center of the generally circular region.

12. A catheter according to claim **1**, wherein the generally circular main region has an outer diameter ranging from about 10 mm to about 25 mm.

13. A catheter according to claim **1**, wherein the generally circular main region has an outer diameter ranging from about 12 mm to about 20 mm.

14. A catheter according to claim **1**, wherein the number of electrodes carried by the generally circular main region ranges from about six to about twenty.

15. A catheter according to claim **1**, further comprising means for deflecting the distal shaft.

16. A catheter according to claim **15**, wherein the deflecting means comprises a deflection wire extending through the proximal shaft, the deflection wire having a distal end fixedly attached to the distal shaft and a proximal end anchored to a mechanism in the control handle that facilitates longitudinal movement of the deflection wire relative to the proximal shaft.

17. A catheter according to claim **1**, wherein the distal shaft is more flexible than the proximal shaft.

18. A catheter according to claim **1**, wherein the plurality of electrodes are arranged in electrode pairs.

19. A catheter according to claim **18**, wherein the number of electrode pairs ranges from about six to about fourteen.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,853,302 B2
APPLICATION NO. : 12/545703
DATED : December 14, 2010
INVENTOR(S) : Cynthia D. Rodriguez et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:


On the Title Page

Item (56) References Cited

OTHER PUBLICATIONS, line 2

Delete "or gmating"
Insert -- originating --

Signed and Sealed this
Thirteenth Day of December, 2011



David J. Kappos
Director of the United States Patent and Trademark Office