

US007874328B2

(12) **United States Patent**  
**Dancyger**

(10) **Patent No.:** **US 7,874,328 B2**  
(45) **Date of Patent:** **Jan. 25, 2011**

(54) **UTILITY BAG**

(75) Inventor: **Michael Dancyger**, Los Angeles, CA  
(US)

(73) Assignee: **Custom Leathercraft Manuf., Inc.**,  
South Gate, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 1051 days.

(21) Appl. No.: **11/347,541**

(22) Filed: **Feb. 3, 2006**

(65) **Prior Publication Data**

US 2007/0181394 A1 Aug. 9, 2007

(51) **Int. Cl.**  
*A45C 1/02* (2006.01)

(52) **U.S. Cl.** ..... **150/112**; 150/106; 150/113;  
190/109; 190/110; 206/234

(58) **Field of Classification Search** ..... 190/109,  
190/111, 112, 113, 117, 110; 150/106, 112,  
150/113; 224/653; 206/234  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

1,367,574 A \* 2/1921 White ..... 190/111

1,495,046 A *	5/1924	Spiegel .....	190/111
2,131,583 A *	9/1938	Crotty et al. ....	211/99
2,604,917 A *	7/1952	Reilly .....	150/111
RE25,826 E *	8/1965	Ward .....	190/108
3,410,376 A *	11/1968	Benzel .....	190/110
4,662,513 A *	5/1987	King et al. ....	206/287.1
4,739,809 A *	4/1988	Adams .....	150/112
5,310,031 A *	5/1994	Plath .....	190/18 A
5,441,134 A *	8/1995	Carson .....	190/111
5,873,504 A *	2/1999	Farmer .....	224/576
5,908,093 A *	6/1999	Miyoshi .....	190/115
5,967,270 A *	10/1999	Shyr .....	190/109
6,102,172 A *	8/2000	Dercole .....	190/18 A
6,105,844 A *	8/2000	Walters et al. ....	224/610



\* cited by examiner

*Primary Examiner*—Tri M Mai

(57) **ABSTRACT**

A utility bag having a compartment recessed in an upper portion of the utility bag to provide additional storage space and utilize unused space in compartments thereof. The recessed compartment may accommodate various items including tools and trays for storing small items.

**13 Claims, 5 Drawing Sheets**






FIG. 1





FIG. 2








FIG. 4




FIG. 5



**1****UTILITY BAG**

## FIELD OF THE INVENTION

The present invention relates generally to utility bags for carrying a plurality of items and more particularly to a utility bag having a compartment recessed in an upper portion of the utility bag to provide additional storage space.

## BACKGROUND OF THE INVENTION

There are currently in use many different types of utility bags used by various tradesmen, construction workers, handymen, plumbers, carpenters, fishermen and the like. These bags conventionally provide for numerous compartments or pockets for containing, storing and carrying items of various sizes and shapes. The compartments and pockets allow a user to aggregate and store articles of similar size and/or function for easy retrieval.

One such utility bag is disclosed in U.S. Pat. No. 5,873,504 entitled "Carrying Bag". The carrying bag is formed of flexible material having an upper compartment and a lower compartment separated by a dividing wall. The carrying bag includes a zippered closure extending around three sides of the bag which allows access to the lower compartment and permits the upper compartment to be pivoted away from the lower compartment. The lower compartment includes a unitary, divided tray for storing articles therein.

A utility bag disclosed in U.S. Pat. No. 6,213,268 and issued to the present inventor has a generally rectangular first compartment which has an opening therein and contains at least one removable tray. A second substantially pocketbook shaped compartment has an opening formed at an upper end to enable access to an inside portion thereof. Pockets sized so as to accommodate elongated objects of varying weight and size, are attached around a perimeter of the bag.

Despite the provision of various compartments and pockets, inefficiencies in the utilization of space within utility bags continues to be a problem. For example, after the upper or pocketbook shaped compartment is filled with tools, implements, containers and the like, unused space remains within the compartment. Attempts to fill this unused space may lead to problems in finding desired items as the items may become lost or buried within the compartment.

There is therefore a need in the art for a utility bag that overcomes the disadvantages of the prior art. There is a need for a utility bag that provides for utilization of unused space in compartments of the utility bag. There is also a need for a utility bag having a compartment recessed in an upper portion of the utility bag to provide additional storage space.

## SUMMARY OF THE INVENTION

The present invention provides a utility bag having a compartment recessed in an upper portion of the utility bag to provide additional storage space and utilize unused space in compartments thereof. The recessed compartment may accommodate various items including tools and trays for storing small items.

In accordance with one aspect of the invention, a utility bag includes a lower portion, an upper portion, and a compartment recessed in the upper portion. The utility bag includes side portions and end portion. The compartment may be recessed in a side portion upper portion and in an end portion upper portion.

In accordance with yet another aspect of the invention, a compartment for accommodating an item in a utility bag

**2**

includes opposed side walls, a top wall, a bottom wall and a rear wall, the opposed side walls, top wall, bottom wall and rear wall being recessed in an upper portion of the utility bag.

In accordance with another aspect of the invention, a utility bag includes a lower portion and an upper portion having opposed side walls, a top wall, a bottom wall and a rear wall defining a recessed compartment extending into an inside portion of the utility bag.

There has been outlined, rather broadly, the more important features of the invention in order that the detailed description thereof that follows may be better understood, and in order that the present contribution to the art may be better appreciated. There are, of course, additional features of the invention that will be described below and which will form the subject matter of the claims appended herein.

In this respect, before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in its application to the details of components and to the arrangements of these components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments and of being practiced and carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein, as well as the abstract, are for the purpose of description and should not be regarded as limiting.

As such, those skilled in the art will appreciate that the conception upon which this disclosure is based may readily be utilized as a basis for the designing of other methods and systems for carrying out the several purposes of the present invention. It is important, therefore, that the claims be regarded as including such equivalent constructions insofar as they do not depart from the spirit and scope of the present invention.

## BRIEF DESCRIPTION OF THE DRAWINGS

The present disclosure may be better understood and its numerous features and advantages made apparent to those skilled in the art by referencing the accompanying drawings.

FIG. 1 is a side elevation view of a side portion of the utility bag in accordance with the invention;

FIG. 2 is a side elevation view of an end portion of the utility bag in accordance with the invention;

FIG. 3 is a partial cross sectional view of the utility bag in accordance with the invention;

FIG. 4 is a top plan view of the utility bag in accordance with the invention; and

FIG. 5 is a top plan view of an alternative embodiment of the utility bag in accordance with the invention.

## DETAILED DESCRIPTION OF THE INVENTION

With reference to FIGS. 1-4, a utility bag generally designated **100** is shown including an upper portion **105** and a lower portion **110**. A compartment **115** is recessed in the upper portion **105** and extends into an inside portion **120** of the utility bag **100**. Compartment **115** may accommodate and carry a removable tray **125** having a plurality of compartments (not shown) so that small and minute items may be carried therein. Tray **125** has a removable lid **127** thereon, which prevents the contents of the tray **125** from shifting, mixing or falling out during transport.

Alternatively, a plurality of smaller trays (not shown) or other tools and items may be carried within the compartment **115**.

Compartment **115** includes opposed side walls **130** and **133**, a top wall **135**, a bottom wall **137** and a rear wall **139**.



Side walls **130** and **133**, the top wall **135**, the bottom wall **137** and the rear wall **139** may form a compartment of generally rectangular cross section. Edges of the walls of the compartment **115** may be attached with re-enforced edging.

Compartment **115** may have a structural element (not shown) enclosed therein to maintain the structural integrity of the compartment **115**. The structural element can be made of any suitable material including wood, metal, plastic and composite materials. In a typical embodiment, the structural element comprises metal wire or a rigid cardboard.

A strap assembly including a strap **140** may retain the tray **125** or other item within the compartment **115**. The strap **140** may be sewn to the upper portion **105** at an end **143** thereof at a location proximate the bottom wall **137** of the compartment **115**. A locking end **145** of the strap **140** includes a male portion **147** of a quick release clip lock **150** having a female portion **151** coupled to a top portion **153** of the upper portion **105**. Clipping the male portion **147** to the female portion **151** secures the strap **140** across the tray **125** so as to secure the tray **125** within the compartment **115**.

With particular reference to FIG. 3, the compartment **115** may be recessed in the upper portion **105** at an upward angle relative to a bottom surface **300** of the utility bag **100**. The upward angle of compartment **115** serves to efficiently utilize space in the inside portion **120** of the utility bag **100**. As shown in FIG. 4, the upward angle provides that the top wall **135** of the compartment **115** is disposed proximate a lateral inside wall **400** of the utility bag **100**.

In a preferred embodiment of the invention, the compartment **115** is recessed in the upper portion **105** of the utility bag **110** along a side portion **160** thereof as shown in FIGS. 1-4. One or more compartments **115** may be recessed in opposite side portions **160**. Alternatively, the compartment **115** may be recessed in the upper portion **105** of the utility bag **100** along an end portion **170** thereof as shown in FIG. 5. An upper wall **500** of compartment **115** may extend into the inside portion **120** of the utility bag **100**.

The utility bag **100** includes handles **171** and **173** to permit the utility bag **100** to be picked up and carried. Handles **171** and **173** may include flexible straps. Handles **171** and **173** are preferably attached to the utility bag **100** by stitching or other suitable means. Handles **171** and **173** may be constructed of heavy duty nylon.

Pockets **180** may be attached around a perimeter of the utility bag **100** to accommodate elongated objects of varying size and weight. Pockets **190** may also be formed in the inside portion **120** of the utility bag **100** for the same purpose.

In a preferred embodiment, the utility bag **100** is made of a heavy duty lightweight material such as Cordura or of a stiff canvas because of its relative rigidity, durability, light weight and ease with which it can be fastened together. However, if more flexible walls are desirable, the utility bag **100** can be made of any thin flexible material, such as cloth, flexible plastic or rubber.

The compartment **115** recessed in the upper portion **105** provides additional storage space and utilizes unused space in the inside portion **120** of the utility bag **100**. The angled configuration of the compartment **115** maximizes the utilization of the unused space.

It should be understood, of course, that the foregoing relates to preferred embodiments of the invention and that modifications may be made without departing from the spirit and scope of the invention as set forth in the following claims.

I claim:

1. A utility bag comprising:

a lower portion coupled to a bottom of the utility bag;  
 an upper portion extending from a top of the lower portion to a top of the utility bag having an interior portion access opening;  
 a compartment extending into the interior portion of the utility bag at an upward angle relative to a bottom surface of the lower portion, wherein the compartment is recessed in a side of the utility bag of the upper portion, wherein the compartment is non-accessible from the interior portion of the utility bag, and the compartment extends from the side of the utility bag towards the top of the utility bag at an acute angle; and  
 a removable tray having a first portion accommodated fully within the compartment and abutted to an end of the compartment, and a second portion extending outside of an exterior of the side of the utility bag,  
 wherein the tray is removable from the side of the utility bag.

2. The utility bag of claim 1, further comprising an end portion upper portion, the compartment being recessed in the end portion upper portion.

3. The utility bag of claim 1, wherein the compartment comprises opposed side walls, a top wall, a bottom wall and a rear wall.

4. The utility bag of claim 1, further comprising a strap assembly for retaining an item in the compartment, the strap assembly comprising a strap attached at one end thereof to the upper portion proximate a bottom wall of the compartment and at another end thereof to a male portion of a quick release clip lock, the male portion being engageable to a female portion attached to a top portion of the upper portion.

5. The utility bag of claim 1, wherein the compartment includes a structural element configured to maintain structural integrity of the compartment.

6. The utility bag of claim 1, further comprising a plurality of pockets attached to the lower portion.

7. The utility bag of claim 1, further comprising a plurality of pockets attached to an inside surface.

8. A utility bag having a compartment for accommodating an item, the compartment comprising:

opposed side walls, a top wall, a bottom wall and a rear wall, the opposed side walls, top wall, bottom wall and rear wall being recessed in an upper portion extending from a top of a lower portion of the utility bag; and  
 a structural element configured to maintain structural integrity of the compartment,

wherein the compartment extends at an upward acute angle from a side of the utility bag towards a top of the utility bag and into an interior portion of the utility bag, and the compartment configured to hold a first portion of a removable tray up to an end of the compartment while a second portion of the removable tray extending outside of an exterior of the side of the utility bag.

9. The utility bag of claim 8, wherein the compartment is recessed in an upper portion of the side portion of the utility bag.

10. The utility bag of claim 8, wherein the compartment is recessed in the upper portion of an end portion of the utility bag.

11. A utility bag comprising:

a lower portion coupled to a bottom of the utility bag;  
 an upper portion extending from a top of the lower portion to a top of the utility bag having an interior portion access opening;



**5**

a compartment extending into the interior portion of the utility bag at an upward angle relative to a bottom surface of the lower portion, wherein the compartment is recessed in a side of the utility bag of the upper portion; a removable tray having a first portion accommodated fully 5 within the compartment and abutted to an end of the compartment, and a second portion extending outside of an exterior of the side of the utility bag; and a strap assembly for retaining an item in the compartment, the strap assembly comprising a strap attached at one 10 end thereof to the upper portion proximate a bottom wall of the compartment and at another end thereof to a male

**6**

portion of a quick release clip lock, the male portion being engageable to a female portion attached to a top portion of the upper portion, wherein the tray is removable from the side of the utility bag.

**12.** The utility bag of claim **11**, wherein the compartment being recessed in the side portion of the upper portion.

**13.** The utility bag of claim **11**, further comprising an end portion of the upper portion, the compartment being recessed 10 in the end portion of the upper portion.

\* \* \* \* \*