

US007896023B2

(12) **United States Patent**  
**Oelerich**

(10) **Patent No.:** **US 7,896,023 B2**  
(45) **Date of Patent:** **Mar. 1, 2011**

(54) **FUEL LEAKAGE VENT FOR FUEL SOURCE  
AND VALVE INTERFACE**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(75) Inventor: **Wolfgang Oelerich**, Mainz-Kastel (DE)

3,563,508 A \* 2/1971 DeLorenzo ..... 251/324

4,022,236 A \* 5/1977 Dumont et al. .... 137/312

(73) Assignee: **GM Global Technology Operations  
LLC**, Detroit, MI (US)

5,074,519 A \* 12/1991 Pettus ..... 251/14

5,316,871 A 5/1994 Swathirajan et al.

6,431,197 B2 \* 8/2002 Hintzman et al. .... 137/613

6,725,876 B2 \* 4/2004 Bowman et al. .... 137/312

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 708 days.

2004/0209150 A1 10/2004 Rock et al.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **11/778,759**

WO WO 2006/082765 A1 8/2006

(22) Filed: **Jul. 17, 2007**

\* cited by examiner

(65) **Prior Publication Data**

US 2009/0020165 A1 Jan. 22, 2009

*Primary Examiner*—Kevin L Lee

(74) *Attorney, Agent, or Firm*—Fraser Clemens Martin &  
Miller LLC; J. Douglas Miller

(51) **Int. Cl.**

**F16K 5/08** (2006.01)

(57) **ABSTRACT**


(52) **U.S. Cl.** ..... **137/312**


A fuel leakage vent is disclosed, wherein the fuel leakage vent  
is formed in a fuel source and valve interface to militate  
against an accumulation of fuel in a tank compartment.



(58) **Field of Classification Search** ..... 137/312,  
137/613

See application file for complete search history.

**15 Claims, 2 Drawing Sheets**









## 1

**FUEL LEAKAGE VENT FOR FUEL SOURCE  
AND VALVE INTERFACE****FIELD OF THE INVENTION**

The present invention relates generally to a vent system and more particularly to a fuel leakage vent for venting an interface between a fuel source and a valve.

**BACKGROUND OF THE INVENTION**

A fuel cell system is increasingly being used as a power source in a wide variety of applications. Fuel cell systems have been proposed for use in power consumers such as vehicles as a replacement for internal combustion engines, for example. Such a system is disclosed in commonly owned U.S. patent application Ser. No. 10/418,536, hereby incorporated herein by reference in its entirety. Fuel cells may also be used as stationary electric power plants in buildings and residences, as portable power in video cameras, computers, and the like. Typically, the fuel cells generate electricity used to charge batteries or to provide power for an electric motor.

The basic process employed by a fuel cell is efficient, substantially pollution-free, quiet, free from moving parts (other than an air compressor, cooling fans, pumps and actuators), and may be constructed to yield only heat and water as by-products. The term "fuel cell" is typically used to refer to either a single cell or a plurality of cells depending upon the context in which it is used. The plurality of cells is typically bundled together and arranged to form a stack with the plurality of cells commonly arranged in electrical series. Since single fuel cells can be assembled into stacks of varying sizes, systems can be designed to produce a desired energy output level providing flexibility of design for different applications.

Fuel cells are electrochemical devices which directly combine a fuel such as hydrogen and an oxidant such as oxygen to produce electricity. The fuel is typically supplied from a fuel source such as a high pressured storage vessel or tank. The oxidant is typically supplied by an air stream.

The fuel source may communicate with a shut-off device such as a shut-off valve, for example. The fuel source and valve interface is typically designed such that a female thread formed on the fuel source mates with a corresponding male counter part formed on the valve for structural integration. A face type seal or a radial type seal such as an O-ring, for example, is typically disposed between the female thread and the male member to create a substantially fluid tight seal therebetween. However, the seals do not completely seal the fuel source/valve interface, as a portion of the fuel may leak past the seal. Accordingly, it is desirable to control leakage of fuel to militate against the accumulation of the fuel in a tank compartment which houses the fuel source and the valve.

It would be desirable to produce a fuel leakage vent for use with a fuel source and valve interface in a fuel cell system, wherein a fuel is directed to a desired location and an accumulation of the fuel in a tank compartment is mitigated.

**SUMMARY OF THE INVENTION**

Harmonious with the present invention, a fuel leakage vent for use with a fuel source and valve interface in a fuel cell system, wherein a fuel is directed to a desired location and an accumulation of the fuel in a tank compartment is mitigated, has surprisingly been discovered.

In one embodiment, a fuel source and valve interface comprises: a fuel source; a valve in fluid communication with the fuel source; and a fuel leakage vent formed in at least one of

## 2

a wall of the fuel source and the valve to provide fluid communication between the fuel source and a desired fuel distribution area.

In another embodiment, a valve comprises: a hollow main body in fluid communication with a fuel source; and a fuel leakage vent formed in the valve, the fuel leakage vent providing fluid communication between the fuel source and a desired fuel distribution area, wherein a pressure within the fuel source is higher than a pressure of the desired fuel distribution area.

In another embodiment, a fuel source and valve interface comprises: a fuel source; a valve in fluid communication with the fuel source; a fuel leakage vent formed in at least one of a wall of the fuel source and the valve, the fuel leakage vent adapted to communicate with a desired fuel distribution area, wherein a pressure within the fuel source is higher than a pressure of the desired fuel distribution area; and a first sealing structure disposed between the fuel source and the valve.

**DESCRIPTION OF THE DRAWINGS**

The above, as well as other advantages of the present invention, will become readily apparent to those skilled in the art from the following detailed description of a preferred embodiment when considered in the light of the accompanying drawings in which:

FIG. 1 is an exploded perspective view of a fuel cell system according to the prior art;

FIG. 2 is a fragmentary sectional view of a fuel source and valve interface in accordance with an embodiment of the invention; and

FIG. 3 is a fragmentary sectional view of a fuel source and valve interface in accordance with another embodiment of the invention.

**DESCRIPTION OF THE PREFERRED  
EMBODIMENT**


The following detailed description and appended drawings describe and illustrate various exemplary embodiments of the invention. The description and drawings serve to enable one skilled in the art to make and use the invention, and are not intended to limit the scope of the invention in any manner.

FIG. 1 shows a fuel cell 10 having a cathode side 9 and an anode side 11. The fuel cell 10 is in fluid communication with a fuel source 37 and an oxidant source 39. Graphite blocks 18, 20 having a plurality of openings 22, 24 respectively formed therein to facilitate fluid distribution are disposed adjacent insulation end plates 14, 16. It is understood that electrically conductive electrode plates (not shown) can be used in the place of the graphite blocks 18, 20 as desired. Gaskets 26, 28 and gas diffusion media (GDM) 30, 32, such as carbon fiber paper, for example, having respective anode and cathode connections 31, 33, are respectively disposed between a membrane electrode assembly (MEA) 12 and the graphite blocks 18, 20. An oxidant and current transport means 36 is made up of the graphite block 18, the gasket 26, and the GDM 30. A fuel and current transport means 38 is made up of the graphite block 20, the gasket 28, and the GDM 32. The anode connection 31 and the cathode connection 33 interconnect the fuel cell 10 with an external circuit 34, and may include other fuel cells (not shown) as desired.

A fuel cell stack (not shown) is constructed of a plurality of fuel cells 10 connected in series. Once a desired number of fuel cells 10 are joined together to form the fuel cell stack, a coolant system (not shown) is provided to cool the fuel cell stack. The illustrative fuel cell stack described herein is com-



In use, a fuel such as hydrogen, for example, is supplied from the fuel source **37** and an oxidant such as oxygen, for example, is supplied from the oxidant source **39**. The fuel and oxidant from respective sources **37**, **39** diffuse through respective fluid and current transport means **36**, **38** to opposing sides of the MEA **12**. Porous electrodes (not shown) form an anode (not shown) at the anode side **11** and a cathode (not shown) at the cathode side **9**, and are separated by a proton exchange membrane (PEM) **35**. The PEM **35** provides for ion transport to facilitate a chemical reaction in the fuel cell **10**. Typically, the PEM **35** is produced from copolymers of suitable monomers. Such proton exchange membranes may be characterized by monomers of the structures:



A valve **50** according to an embodiment of the invention is disposed in an enclosed tank compartment **51** as shown in FIG. 2, wherein similar structure previously described in FIG. 1 includes the same reference numeral followed by a prime (') symbol. The valve **50** includes a main body **52** and an axially extending hollow, threaded male member **54** that is received in a threaded female member **56** formed on a wall **53** of a fuel source **37'**. An interface between the male member **54** and the female member **56** is referred to as a fuel source and valve interface **55**. It is understood that the female member **56** can be formed separately from the wall **53** of the fuel source **37'** as desired without departing from the scope and spirit of the invention, such as wherein the female member **56** is affixed to the wall **53**, for example. It is also understood that the valve **50** may include a female member (not shown) wherein the wall **53** of the fuel source **37'** would include a corresponding male member (not shown) as desired.

A first sealing structure **57**, such as an O-ring, for example, is disposed between the male member **54** and the female member **56** in a first annular channel **58** formed in the male member **54**. Optionally, a first back-up sealing structure **59** is disposed in the first annular channel **58** adjacent the first sealing structure **57**.

The male member **54** of the valve **50** includes an annular groove **60** that is in fluid communication with a first end **62** of a bore **64** that extends axially through the male member **54** and the main body **52** of the valve **50**. It is understood that the annular groove **60** can be formed in the female member **56** as desired. The annular groove **60** and the bore **64** are collectively referred to as a fuel leakage vent **65**. A second end **69** of the bore **64** is in fluid communication with a desired fuel distribution area **71**, such as a vent passageway in communication with the atmosphere or a burner, for example. It is understood that the second end **69** of the bore **64** can be in communication with other structure (not shown) as desired, such as a hollow tube, for example, wherein the fuel flows through the hollow tube to the desired fuel distribution area **71** as desired.

4

formed in the male member **54** on a side of the annular groove **60** opposite the first annular channel **58**. Additionally, a second back-up sealing structure **68** may be disposed in the second annular channel **67** adjacent the second sealing structure **66**.

In use, the valve **50** is opened and closed to selectively permit and militate against a flow of fuel through the valve **50** from the fuel source **37'** to a fuel cell stack (not shown). A controller (not shown), for example, can be used to send an appropriate signal to open and close the valve **50** based on a fuel requirement of the fuel cell stack, for example. As the fuel is supplied from the fuel source **37'** to the fuel cell stack, an amount of fuel may leak through the seal created by the first sealing structure **57** and the first back-up sealing structure **59**. It is understood that an amount of fuel may also leak through the substantially fluid tight seal created by the first sealing structure **57** and the first back-up sealing structure **59** when the valve **50** is in a closed position. A pressure difference between a high pressure within the fuel source **37'** and a low pressure of the desired fluid distribution area **71** causes the fuel to flow into the annular groove **60** formed in the male member **54** of the valve **50** toward the desired fuel distribution area **71**. Thereafter, the fuel flows through the bore **64** formed in the valve **50**, out of the second end **69** thereof, and to the desired fuel distribution area **71**.

The second sealing structure **66** and the second back-up sealing structure **68** militate against the flow of the fuel there-through into the tank compartment **51**. Accordingly, a leakage of fuel into the tank compartment **51** is minimized. Option-  
ally, a sensor (not shown) may be included on a side of the  
second back up ring **68** opposite the first annular channel **58**  
and the annular groove **60**. The sensor could sense an amount  
of fuel flowing into the tank compartment **51**, and could be  
configured to send a signal to an appropriate output device  
(not shown) such as an indicator light, for example, if the  
amount of fuel flowing into the tank compartment **51** were to  
reach a predetermined level.

Use of the fuel leakage vent **65** with the fuel source and valve interface **55** minimizes an amount of fuel permitted to leak into the tank compartment **51**. Accordingly, an accumulation of fuel in the tank compartment **51** is mitigated.

FIG. 3 shows a valve **150** disposed in a tank compartment **51"** in accordance with another embodiment of the invention, wherein similar structure previously described in FIG. 1 or 2 includes the same reference numeral followed by a double prime ("") symbol. The valve **150** includes a main body **152** and an axially extending hollow, threaded male member **154** that is received in a threaded female member **156** formed on a wall **153** of a fuel source **37"**. An interface between the male member **154** and the female member **156** is referred to as a fuel source and valve interface **155**. It is understood that the female member **156** can be formed separately from the wall **153** of the fuel source **37"** as desired without departing from the scope and spirit of the invention, such as wherein the female member **156** is affixed to the wall **153**, for example. It is also understood that the valve **150** may include a female member (not shown) wherein the wall **153** of the fuel source **37"** would include a corresponding male member (not shown) as desired.

A first sealing structure **157**, such as an O-ring, for example, is disposed between the male member **154** and the female member **156** in a first annular channel **158** formed in the male member **154**. Optionally, a first back-up sealing structure **159** is disposed in the first annular channel **158** adjacent the first sealing structure **157**.

The male member **154** of the valve **150** includes an annular groove **160** that is in fluid communication with a first end **162**



## 5

of a bore **164** that extends through the female member **156** and the wall **153** of the fuel source **37"**. It is understood that the annular groove **160** can be formed in the male member **154** as desired. The annular groove **160** and the bore **164** are collectively referred to as a fuel leakage vent **165**. A second end **169** of the bore **164** is in fluid communication with a desired fuel distribution area **171**, such as a vent passageway in communication with the atmosphere or a burner, for example. It is understood that the second end **169** of the bore **164** can be in communication with other structure (not shown) as desired, such as a hollow tube, for example, wherein the fuel flows through the hollow tube to the desired fuel distribution area **171** as desired.

Optionally, a second sealing structure **166** such as an O-ring, for example may be disposed between the male member **154** of the valve **150** and the female member **156**. The second sealing structure **166** is disposed in a second annular channel **167** formed in the male member **154** on a side of the annular groove **160** opposite the first annular channel **158**. Additionally, a second back-up sealing structure **168** may be disposed in the second annular channel **167** adjacent the second sealing structure **166**.

In use, the valve **150** is opened and closed to selectively permit and militate against a flow of fuel through the valve **150** from the fuel source **37"** to a fuel cell stack (not shown). A controller (not shown), for example, can be used to send an appropriate signal to open and close the valve **150** based on a fuel requirement of the fuel cell stack, for example. As the fuel is supplied from the fuel source **37"** to the fuel cell stack, an amount of fuel may leak through the seal created by the first sealing structure **157** and the first back-up sealing structure **159**. It is understood that an amount of fuel may also leak through the substantially fluid tight seal created by the first sealing structure **157** and the first back-up sealing structure **159** when the valve **150** is in a closed position. A pressure difference between a high pressure within the fuel source **37"** and a low pressure of the desired fluid distribution area **171** causes the fuel to flow into the annular groove **160** formed in the male member **154** of the valve **150** toward the desired fuel distribution area **171**. Thereafter, the fuel flows through the bore **164** formed in female member **156** and the wall **153** of the fuel source **37"**, out of the second end **69** of the bore **164**, and to the desired fuel distribution area **171**.

The second sealing structure **166** and the second back-up sealing structure **168** militate against the flow of the fuel therethrough into the tank compartment **51"**. Accordingly, a leakage of fuel into the tank compartment **51"** is minimized. Optionally, a sensor (not shown) may be included on a side of the second back up ring **168** opposite the first annular channel **158** and the annular groove **160**. The sensor could sense an amount of fuel flowing into the tank compartment **51"**, and could be configured to send a signal to an appropriate output device (not shown) such as an indicator light, for example, if the amount of fuel flowing into the tank compartment **51"** were to reach a predetermined level.

Use of the fuel leakage vent **165** with the fuel source and valve interface **155** minimizes an amount of fuel permitted to leak into the tank compartment **51"**. Accordingly, an accumulation of fuel in the tank compartment **51"** is mitigated.

From the foregoing description, one ordinarily skilled in the art can easily ascertain the essential characteristics of this invention and, without departing from the spirit and scope thereof, can make various changes and modifications to the invention to adapt it to various usages and conditions.

## 6

What is claimed is:

1. A fuel source and valve interface comprising:
  - a fuel source;
  - a main body of a valve in fluid communication with the fuel source; and
  - a fuel leakage vent formed in a wall of the fuel source to provide fluid communication between the fuel source and a desired fuel distribution area, wherein at least a portion of the fuel leakage vent is formed in the main body of the valve.
2. The interface according to claim 1, wherein a pressure within the fuel source is higher than a pressure of the desired fuel distribution area.
3. A fuel source and valve interface comprising:
  - a fuel source;
  - a main body of a valve in fluid communication with the fuel source; and
  - a fuel leakage vent formed in a wall of the fuel source to provide fluid communication between the fuel source and a desired fuel distribution area, wherein the fuel source includes a female member that receives a corresponding male member of the main body of the valve.
4. A fuel source and valve interface comprising:
  - a fuel source;
  - a main body of a valve in fluid communication with the fuel source; and
  - a fuel leakage vent formed in a wall of the fuel source to provide fluid communication between the fuel source and a desired fuel distribution area, further comprising a first sealing structure disposed between the fuel source and the main body of the valve.
5. The interface according to claim 4, further comprising a second sealing structure disposed between the fuel source and the main body of the valve.
6. The interface according to claim 5, further comprising a first back-up sealing structure disposed adjacent the first sealing structure.
7. The interface according to claim 6, further comprising a second back-up sealing structure disposed adjacent the second sealing structure.
8. A fuel source and valve interface comprising:
  - a hollow main body of a valve in fluid communication with a fuel source; and
  - a fuel leakage vent formed in the main body of the valve, the fuel leakage vent providing fluid communication between the fuel source and a desired fuel distribution area, wherein a pressure within the fuel source is higher than a pressure of the desired fuel distribution area;
  - a first sealing structure disposed between the fuel source and the main body of the valve; and
  - a first back-up sealing structure disposed adjacent the first sealing structure.
9. The interface according to claim 8, wherein at least a portion of the fuel leakage vent is formed in a wall of the fuel source.
10. The interface according to claim 8, further comprising a second sealing structure disposed between the fuel source and the main body of the valve.
11. The interface according to claim 10, further comprising a second back-up ring disposed adjacent the second sealing structure.
12. A fuel source and valve interface comprising:
  - a high pressure storage vessel;
  - a main body of a valve in fluid communication with the high pressure storage vessel;
  - a fuel leakage vent formed in a wall of the high pressure storage vessel, the fuel leakage vent adapted to commu-

7

nicate with a desired fuel distribution area, wherein a pressure within the high pressure storage vessel is higher than a pressure of the desired fuel distribution area; and a first sealing structure disposed between the high pressure storage vessel and the main body of the valve.

13. The interface according to claim 12, wherein at least a portion of the fuel leakage vent is formed in the main body of the valve.

8

14. The interface according to claim 12, further comprising a second sealing structure disposed between the high pressure storage vessel and the main body of the valve.

5 15. The interface according to claim 12, further comprising a first back-up sealing structure disposed adjacent the first sealing structure and a second back-up sealing structure disposed adjacent the second sealing structure.

\* \* \* \* \*