



US007912966B2

(12) **United States Patent**  
**Witkowski et al.**

(10) **Patent No.:** **US 7,912,966 B2**  
(45) **Date of Patent:** **Mar. 22, 2011**

(54) **ELECTRONIC DEVICE AND REMOTE  
COMPUTER SYSTEM AND METHOD FOR  
CONTROLLING REMOTE  
COMMUNICATIONS**

(75) Inventors: **Carl J Witkowski**, Duryea, PA (US);  
**John H Richardson**, Wilkes-Barre, PA  
(US)

(73) Assignee: **Guard Insurance Group**, Wilkes-Barre,  
PA (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 17 days.

(21) Appl. No.: **12/550,963**

(22) Filed: **Aug. 31, 2009**

(65) **Prior Publication Data**

US 2010/0049853 A1 Feb. 25, 2010

**Related U.S. Application Data**

(63) Continuation of application No. 12/255,319, filed on  
Oct. 21, 2008, now Pat. No. 7,590,744, which is a  
continuation-in-part of application No. 10/905,102,  
filed on Dec. 15, 2004, now abandoned.

(51) **Int. Cl.**  
**G06F 15/16** (2006.01)  
**G06F 12/00** (2006.01)

(52) **U.S. Cl.** ..... **709/227; 709/232**

(58) **Field of Classification Search** ..... **709/217-219,**  
**709/227-229, 232, 250**

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,318,182 A 3/1982 Bachman et al.  
4,320,451 A 3/1982 Bachman et al.  
4,445,171 A 4/1984 Neches  
5,634,038 A 5/1997 Saitoh

5,727,155 A 3/1998 Dawson  
5,754,800 A 5/1998 Lentz et al.  
6,003,069 A 12/1999 Cavill  
6,154,839 A 11/2000 Arrow et al.  
6,249,294 B1 6/2001 Lefebvre et al.  
6,341,272 B1 1/2002 Randle  
6,385,636 B1 5/2002 Suzuki  
6,532,487 B1 3/2003 Perks  
6,625,641 B1 9/2003 Hare et al.  
6,795,851 B1 \* 9/2004 Noy ..... 709/218  
6,920,502 B2 7/2005 Araujo et al.  
7,043,534 B1 5/2006 Donnelly et al.  
7,509,389 B1 \* 3/2009 Duffield et al. .... 709/209  
7,590,744 B2 \* 9/2009 Richardson et al. .... 709/227

(Continued)

**FOREIGN PATENT DOCUMENTS**

JP 9-204383 8/1997

(Continued)


*Primary Examiner* — Zarni Maung

(74) *Attorney, Agent, or Firm* — IP Authority, LLC; Ramraj  
Soundararajan

(57) **ABSTRACT**

A remote communication system and method are disclosed. An environment is identified defining a plurality of parameters communicated between an electronic device (or a computer-based device) and a remote computer as part of a remote session (i.e., the electronic device remotely controlling the remote computer via the remote session), with each parameter defining an action associated with the remote session. A first application (associated with the electronic device), via a unidirectional communication with the environment, modifies at least one parameter associated with the environment (e.g., modifying keyboard scan codes, cursor position, mouse position, clipboard data, screen resolution, or channel administration), wherein the modified parameter is extracted by an interceptor associated with the remote computer and, the interceptor, based on a look-up, executes a pre-defined action affecting the remote session, wherein the pre-defined action being different than the modified parameter's associated action.

**29 Claims, 18 Drawing Sheets**



# US 7,912,966 B2

Page 2

## U.S. PATENT DOCUMENTS

2001/0047406 A1 11/2001 Araujo et al.  
2002/0048054 A1 4/2002 Ohata et al.  
2002/0087729 A1 7/2002 Edgar  
2003/0041147 A1\* 2/2003 van den Oord et al. .... 709/227  
2003/0105813 A1 6/2003 Mizutani  
2005/0091057 A1\* 4/2005 Phillips et al. .... 704/270.1  
2005/0152319 A1\* 7/2005 Kubler et al. .... 370/338  
2006/0146837 A1\* 7/2006 Atsuki et al. .... 370/400

2009/0319671 A1\* 12/2009 Richardson et al. .... 709/227  
2009/0319678 A1\* 12/2009 Richardson et al. .... 709/229  
2010/0049854 A1\* 2/2010 Richardson et al. .... 709/227

## FOREIGN PATENT DOCUMENTS

JP 2001-265880 9/2001  
JP 2003-30383 1/2003  
JP 2003-39767 2/2003

\* cited by examiner




FIG. 1a  
(PRIOR ART)




FIG. 1b  
(PRIOR ART)




FIG. 2




FIG. 3




FIG. 4




FIG. 5






FIG. 6




FIG. 7

**GUARD INSURANCE GROUP** **IIS - Intranet Insurance Software**

Accounting  
Agency  
Background Files  
Billing  
Claims  
Data Reporting  
Development  
Dividends  
General  
GUAROTech  
Loss Control  
Premium Audit  
System  
Underwriting

Recent Items  
→ Adjustor Centre  
MENU Search

Tools Help Help Desk  
Logged in as: JACR8  
11/15/2004 14:35  
HomePage Log Off

Search:

0 unread messages

**Claims**

**15th of the Month**

- Export CLAIMREN to OPRO
- Global Closing

**Beginning of Day (BOD)**

- Checks - MEEAST10\_Credit
- Checks - MEEAST10\_Debit
- Checks - PAAMG10\_Credit
- Checks - PAAMG10\_Debit
- Checks - PANORG10\_Credit
- Checks - PANORG10\_Debit

**End of Day (EOD)**

- Process EDI FROI/SROI Acknowledgements
- Process EDI FROI
- Process EDI SROI
- Recalc Arrays
- Notify Programming of Negative OS Reserves
- AutoClose Claims
- Notify Adjustors of Pending Checks on Hold
- Export CLAIMPRV to OPRO
- CLAIMSOE Check

**End of Month (EOM)**

- Claims Checks - Create Freedom File

**Programming**

- Disability Autodialy
- Export Claimant ISO Index
- Export CLAIMHS to OPRO

**Reports**

- Bills Overdue for Repricing Report
- Automatic Check Voiding
- Check Requirer Detail
- Check Requirer Summary
- Checks Export Totals
- Claimant Information History
- Claims Check Detail
- COR (Claims Operating Report)
- COR (Claims Operating Report) - Drill
- COR (Claims Operating Report) - Export
- Diaries Due

**Tasks**

- Adjustor Caseload Transfer
- Adjustor Review Administration
- Claimant Search
- EDI - First Scripts
- EDI Payment Exceptions - Actuals
- EDI Payment Exceptions - Trials
- EDI Payment Import - Actuals
- EDI Payment Import - Trials
- First Report of Injury (FROI)
- Litigation Review - Administration
- Litigation Review - Claim File/Firm Reviews
- Litigation Review - Law Firm Reviews
- Medical Bill Tracking Utility
- Refresh Correspondence List
- Network Providers Search
- Reserve Worksheet Approval
- Payments After Closing Approval
- Reserve Worksheets Outstanding
- Set FROI Options
- Subsequent Report of Injury (SROI)
- TPA Payment Entry
- Transfer Claims Between Policies
- Void Checks

**Workflow**

- Adjustor Centre
- Mailbox
- Manager Centre

FIG. 8





FIG. 9


**IIS - Intranet**  
**Insurance Software**

Search:

[unread\\_message\(s\)](#)

[Topic Help](#) [Help Desk](#)  
 Logged in as: JACKR  
 11/15/2004 14:40  
[HomePage](#) [Log off](#)

---

[Go to adjustor's centre](#)

**JACKR - Incoming 0**  
 No records to display

---

**Diaries**

	Today Overdue
Disability/Payments	0 All
General	0 All
Litigation	0 All
Other Diary	0 All
Recoveries	0 All
Reserves/Closures	0 All
Plan of Action	0 All
Status	0 All
DocuNotes	0 All
UR Notes	0 All

---

**Workflow**

There are no documents currently assigned to this user and there are no unprocessed documents

You have 0 pending items to address for SROI.

---

**Utilization Review**

There are no utilization reviews outstanding for this user.

---

**Statistics (as of end of prior day)**

Prior Month	0
+ New	0
- Closed	0
+ Re-Open	0
+ Transfers In	0
- Transfers Out	0
Current Pending	0
Conversions	0

---

GUARD Insurance Group (c) 2002

FIG. 10

**IIS - Intranet Insurance Software**

Alison  Go to adjuster's centre  
**ALISOND - Incoming 0**  
 No records to display

Search:    
 0 unread messages(0)

Topic Help Help Desk  
 Logged in as: JACVR  
 11/15/2004 1:41  
 Home Page Log Off

---

**Diaries**

	Today Overdue
Disability/Payments	0 All
General	0 All
Litigation	0 All
Other Diary	0 All
Recoveries	0 All
Reserves/Closures	0 All
Plan of Action	0 All
Status	0 All
Doc Notes	0 All
UR Notes	0 All

**Workflow**

Workflow Activity	Assigned to	Faxes	Overdue
<b>Claims - Initial Document Review</b>			
CORRESPONDENCE	2	0	0
MEDICALBILLSRECORDS	4	0	0
MEDICALREPORTS	1	1	0
STATEFORMS	2	0	0

You have 0 pending items to address for SROI.

**Utilization Review**

There are no utilization reviews outstanding for this user.

**Statistics (as of end of prior day)**

Prior Month	44
+ New	5
- Closed	3
+ Re-Open	2
+ Transfers In	2
- Transfers Out	3
Current Pending	50
Conversions	5

GUARD Insurance Group (c) 2002

FIG. 11




FIG. 12

**GUARD INSURANCE GROUP** **IIS - Intranet Insurance Software**

Return to manage workload for Alison [My Workload Overview](#) [Workflow overview](#)

Search:  [0 unread message\(s\)](#)

[Topic Help](#) [Help Desk](#)  
Logged in as: JACKR  
11/15/2004 14:45  
[HomePage](#) [Log off](#)

[Return](#) [Home](#) [Help](#) [Logout](#)

**Claims - Initial Document Review - CORRESPONDENCE**

Code-Claim	DOL	Claimant	Date Received	Document Name	Pages	Notes
			11/15/2004	MC-QUESTIONNAIRE-15-04-011	1	
			11/15/2004	MED_REC_RELEASE_11-15-04_HFF	1	

GUARD Insurance Group (c) 2002

FIG. 13



**GUARD INSURANCE GROUP** **IIS - Intranet Insurance Software**

Return to manage workload for Alizon [My Workload Overview](#) [Workflow Overview](#)

Claims - Initial Document Review-CORRESPONDENCE

Search:  [0 unread message\(s\)](#)

[Topic](#) [Help](#) [Help Desk](#)  
Logged in as: JACKR  
11/15/2004 14:45  
[HomePage](#) [Log off](#)

Code-Claim	DOL	Claimant	Date Received	Document Name	Pages	Notes
			11/15/2004	MED_REC_RELEASE_11-15-04.TIFF	1	

GUARD Insurance Group (c) 2002

FIG. 14


Remote Desktop

DocuView Terminal Server Document Handling System

Page 1 of 1

Image Size  
 B Best Fit  
 W Width  
 H Height  
 S Scale

Close



Carrier:  
 Claim #:  
 Injured Worker:  
 Policyholder:  
 Date of Loss:  
 Date of Birth:

**Authorization for Release of Medical Records\***

I, the undersigned, authorize any physician, surgeon, dentist, hospital, other health care provider, or insurance company to release my protected health information to GUARD Insurance Group.

I authorize the release of all information pertaining to Inpatient admissions, Emergency Room (ER) visits, outpatient clinics, diagnostic testing, radiology films, doctors' orders, progress notes, nurses' notes, laboratory testing, and social services provided, including reports, correspondence, consultations, memoranda, treatment plans, admission records, discharge summaries, medical summaries, diagnoses, and any other material relevant to my Workers' Compensation claim.

The protected health information shall be disclosed for the purposes of verifying, evaluating, and processing my claim. GUARD Insurance Group shall use my protected health information as necessitated by applicable state and/or other law.

This Authorization shall expire twenty-four (24) months from the date signed by me or upon the conclusion of my claim, whichever occurs later.

I agree that a copy of this Authorization shall be considered as valid as the original.

RIGHT TO REVOKE: I understand that I may revoke this Authorization at any time by sending my written notice to GUARD Insurance Group at P.O. Box 1368, Wilkes-Barre, PA 18703-1368. I also understand that my revocation will not affect any action taken by any healthcare facility or provider, insurance company, or GUARD Insurance Group prior to receipt of my notice of revocation.

Signature: \_\_\_\_\_ Date: \_\_\_\_\_

\*This Authorization is not required by law and is merely intended to expedite the processing of your Workers' Compensation claim.

FIG. 15




FIG.16




FIG.17

**ELECTRONIC DEVICE AND REMOTE  
COMPUTER SYSTEM AND METHOD FOR  
CONTROLLING REMOTE  
COMMUNICATIONS**

RELATED APPLICATIONS

This application is a Continuation of U.S. application Ser. No. 12/255,319, filed Oct. 21, 2008, pending, which is a Continuation-In-Part of U.S. application Ser. No. 10/905,102, filed Dec. 15, 2004, now abandoned.

BACKGROUND OF THE INVENTION

1. Field of Invention

The present invention relates generally to the field of remote processing and remote access solutions. More specifically, the present invention is related to a remote communication system and method between an electronic device and a remote computer.

2. Discussion of Prior Art

There are a myriad of prior art remote access solutions available such as Symantec's PCAnywhere™ and GoTo-MyPC™ wherein users utilize specific remote access software to gain access to remote servers or PC's. FIGS. 1a-1b illustrate two such prior art remote access schemes. In a first scheme, depicted in FIG. 1a, users (such as user 102) interested in gaining remote access to a remote server 110 first install server-specific remote access software (such as a java script 104 or ActiveX component 106) on his/her personal computer (PC) 108. Next, using the installed server-specific remote access software, users access the remotely located server 110 over network 112 (e.g., local area network (LAN), wide area network (WAN), the Internet, etc.).

In a second scenario, depicted in FIG. 1b, users (such as user 114) who wish to remotely access their PC 116 install specific remote access software (such as java script 118 or ActiveX component 120) on the PC 116 that is to be remotely accessed. Next, user 114, or someone who is authorized to access PC 116 (such as a system administrator), is able to remotely access PC 116 over network 128 (e.g., local area network (LAN), wide area network (WAN), the Internet, etc.) after installing specific remote access software (such as a java script 122 or ActiveX component 124) via PC 126.

For example, users who are interested in remotely accessing their office PC 116 from a remote location install software such as Symantec's PCAnywhere™ software on their office PC 116. Next, users have to install a corresponding version of Symantec's PCAnywhere software in computer 126 from a remote location prior to being able to access the remotely located office PC (which should also be running the remote access software at the time access is requested).

A common aspect of prior art remote access solutions, such as the one depicted in FIGS. 1a and 1b, is the necessity to install specific remote access software in a client PC prior to establishing communication with a remote server or remote PC, which also requires the pre-installation of remote access software.

The following patents provide general background regarding client/server interactions, but fail to overcome many of the limitations provided by the present invention.

The patent to Cavil (U.S. Pat. No. 6,003,069) provides for a client/server printer driver system. Cavil discloses a client terminal capable of submitting a job to a server, which processes the request and sends processed data to the client terminal. Additionally disclosed is a subsystem allowing a client terminal to send a portion of data to one or more servers

and/or process a portion of data on the disclosed client itself. The disclosed subsystem is comprised of facilities to combine processed data from each of the different destinations to which the disclosed client terminal sent process requests.

5 The patent to Hare et al. (U.S. Pat. No. 6,625,641) provides for a method and apparatus for providing client support without installation of server software. Hare et al. disclose a client process executing on a local machine, having access to server software physically stored on a remote machine. When a client process has a request, a remote server software entry is located in a mount table entry. Once contact is made between a client and remote host, object services are provided to the disclosed client process. Also disclosed is a method of allowing a client process to locate an active server process at a remote host machine by utilizing the disclosed mount table entry. Processes are located and contacted on a remote host without user intervention.

15 The patent application publication to Mizutani (2003/0105813 A1) discloses a system and method for allowing client application processing requests to be processed on a server. A client-side I/O device is initialized based on information received from a server. The disclosed I/O device receives output information provided by the application-processing unit of the disclosed server in response to processing input information received from a client.

20 The Japanese patent to Asada (JP 9-204383) discloses a method of selecting and connecting to a server terminal with a light load. As a result of the disclosed selection process, applications executed on the server execute faster.

25 The Japanese patent to Wada et al. (JP 2003-30383) discloses a method connecting a client terminal to a data center storing requested rental software. The disclosed data center is also comprised of a form generation database allowing for client input. See abstract.

30 Whatever the precise merits, features, and advantages of the above cited references, none of them achieves or fulfills the purposes of the present invention.

SUMMARY OF THE INVENTION

35 The present invention provides for a method as implemented in a first application running in an electronic device comprising: (a) identifying an environment associated with the electronic device, the electronic device remotely controlling, via a second application, a remote session on a remote computer over a first network, the remote controlling performed via a bidirectional communication, and the environment defining a plurality of parameters communicated between the electronic device and the remote computer as part of the remote session, each parameter in the plurality of parameters defining an action associated with the remote session; and (b) the first application running in the electronic device, via a unidirectional communication with the environment, modifying at least one parameter associated with the environment, the modified parameter extracted by an interceptor associated with the second computer and, based on a look-up, executing a pre-defined action affecting the remote session, the pre-defined action different than said modified parameter's associated action.

40 The present invention also provides for a method as implemented in a first application associated with a computer-based device comprising: (a) identifying an environment associated with the computer-based device, the computer-based device remotely controlling, via a second application, a remote session on a remote computer over a first network, the remote controlling performed via a bidirectional communication, and the environment defining a plurality of parameters

communicated between the computer-based device and the remote computer as part of the remote session, each parameter in the plurality of parameters defining an action associated with the remote session; and (b) the first application running in the computer-based device, via a unidirectional communication with the environment, modifying at least one parameter associated with the environment, the modified parameter extracted by an interceptor associated with the remote computer and, based on a look-up, executing a pre-defined action affecting the remote session, the pre-defined action different than the modified parameter's associated action.

The present invention also provides for a method as implemented in a first application running in an electronic device comprising: (a) identifying an environment associated with the electronic device, the electronic device remotely controlling, via a second application, a remote session on a remote computer over a first network, the remote controlling performed via a bidirectional communication, and the environment defining a plurality of parameters communicated between the electronic device and the remote computer as part of the remote session, each parameter in the plurality of parameters defining an action associated with the remote session; (b) identifying at least one parameter to be modified and temporarily storing contents associated with the identified parameter in computer storage; (c) the first application running in the electronic device, via a unidirectional communication with the environment, modifying the identified parameter, the modified parameter extracted by an interceptor associated with the second computer and, based on a look-up, executing a pre-defined action affecting the remote session, the pre-defined action different than the modified parameter's associated action; and (c) restoring contents associated with the identified parameter from the computer storage.

The present invention also provides for an article of manufacture having computer readable program code implementing each of the above-described methods.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1a and 1b illustrate two prior art remote access schemes.

FIG. 2 illustrates an exemplary embodiment of the communication system of the present invention.

FIG. 3 illustrates an exemplary method of the present invention

FIG. 4 illustrates another embodiment of the present invention's communication method implemented in a session server for remote access to applications implemented in object servers, wherein each object server implements at least one application

FIGS. 5 through 15 illustrate various screenshots of one implementation of the present invention's system and method for remote access to applications implemented in object servers.

FIG. 16 illustrates one embodiment of the present invention's interceptor.

FIG. 17 illustrates another embodiment of the present invention's interceptor.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

While this invention is illustrated and described in a preferred embodiment, the invention may be produced in many different configurations. There is depicted in the drawings, and will herein be described in detail, a preferred embodiment

of the invention, with the understanding that the present disclosure is to be considered as an exemplification of the principles of the invention and the associated functional specifications for its construction and is not intended to limit the invention to the embodiment illustrated. Those skilled in the art will envision many other possible variations within the scope of the present invention.

The present invention provides for a method and system for remote communication. FIG. 2 illustrates an exemplary embodiment of the communication system of the present invention. The present invention's communication system provides access to remotely controllable applications, wherein the system comprises a session server 202 and one or more object servers 204, 206, 208, and 210. Each object server is associated with at least one remotely controllable application, wherein processing associated with the remotely controllable application affected by reflected modifications in one or more client environment(s) (such as client environment(s) associated with client 200). Session server 202 stores one or more software modules, wherein each software module is capable of monitoring modifications to at least one client environment (such as client environment(s) associated with client 200) and communicating with at least one object server (204, 206, 208, or 210) to reflect such modifications. Session server 202 establishes a communication session with one or more clients (such as client 200), identifies at least one remotely controllable application associated with the communication session, loads a software module corresponding to identified remotely controllable application to communicate with corresponding object server (204, 206, 208, or 210), monitors modifications to client environment via the loaded software module, and reflects modifications in said client environment to said corresponding object server.

It should be noted that session server 202 and object server 204, 206, 208, or 210 does not have to be in the same premises, nor, the same segment of a network. They can be on a separate LAN, VAN, or WAN. Hence, the specific locations of the session server and the object servers should not be used to restrict the scope of the present invention.

FIG. 3 illustrates exemplary method 300 of the present invention. In step 302, a communication session is established between a session server and a client. As one example, the communication session is established as a virtual private network (VPN) session. In the preferred embodiment, the client is a web browser (e.g., Internet Explorer™, Netscape™, Mozilla™, etc.) and the session server is a terminal server. Also, in one embodiment, communication between the client and the session server is performed via the remote desktop Protocol™ (RDP). It should be noted that communication between the client and the session server is over any of, or a combination of, the following networks: a local area network (LAN), a wide area network (WAN), or the Internet.

In step 304, the session server loads at least one software application among a plurality of software applications to communicate with at least one object server. Next, in step 306, the loaded software application monitors one or more client environment(s) to detect any changes in the client environment(s). In step 308, the loaded software application reflects modified client environment(s) to the corresponding object server, wherein processing associated with the communication session is effected, in step 310, based on the reflected modified client environment(s) and communication between the session server and corresponding object server.

In the preferred embodiment, the client environment(s) is reflected using one or more semaphore flags. In one embodiment, a plurality of semaphore flags is used, wherein each flag

## 5

is represented via a 16-bit masked constant that triggers a corresponding action. For example, a semaphore flag could be represented by the 16-bit value—00000000:00000001, which corresponds to the action command—OPEN. Similarly, another semaphore flag could be represented by the 16-bit value—00000000:00000010, which corresponds to the action command—CLOSE.

FIG. 4 illustrates another embodiment of the present invention's communication method 400 implemented in a session server for remote access to applications implemented in object servers, wherein each object server implements at least one application. In step 402, the session server establishes a communication session (e.g., a VPN session) with a client (e.g., a web browser such as Internet Explorer™, Netscape™, Mozilla™, etc.). In step 404, the session server identifies at least one application to be remotely loaded and executed in a corresponding object server and, in step 406, the session server loads an appropriate software module to communicate with corresponding object server, wherein the software module corresponds to at least one application to be remotely loaded and executed.

Next, in step 408, the session server monitors modifications to at least one client environment via the loaded software module and, in step 410, the session server reflects modifications in the client environment(s) to the corresponding object server. In step 412, processing associated with the communication session is effected based on reflected modifications in the client environment and communication between the session server and the corresponding object server.

In the preferred embodiment, the client environment(s) is reflected using one or more semaphore flags.

FIGS. 5-15 illustrate various screenshots of one implementation of the present invention's system and method for remote access to applications implemented in object servers. First, an authorized user establishes a virtual private network (VPN) session with a session server. Next, as shown in FIG. 5, an initial login screen is presented to the user via a client (such as a browser). An authorized user then logs into his/her account using the login page. Similarly, an authorized user opens a remote desktop connection via logging into the session server via a login screen shown in FIG. 6. After, logging into the session server, an access portal application is rendered to the user as shown in FIG. 7. The user then clicks on a choice (for example, a user can click on the choice—“Launch Docu\_TS\_Image”) to launch the appropriate application in the session server.

FIG. 8 illustrates a sample screenshot after an authorized user logs into his/her account via the login of FIG. 5. In this example, the user clicks on “Adjustor Centre” (of FIG. 8) to view a particular workflow as shown in FIG. 9. FIG. 10 illustrates the ability to pick and view another user's “Adjustor Centre”. FIG. 11 shows a sample “Adjustor Centre”, wherein a user can click on various workflow items (such as entries for “Correspondence”, “MedicalBillsRecords”, “MedicalReports”, or “StateForms”). Clicking on each of these workflow entries launches appropriate software in the session server to communicate with appropriate object server implementing the workflow entry clicked. For example, when the user clicks on the entry corresponding to item—“Correspondence” and item—“assigned to”, the application shows specific correspondence items (such as the two items shown in FIG. 12-14). When the user further selects and clicks on a specific item of “Correspondence” as in FIG. 14, the client environment is changed and the change is reflected by the session server to the appropriate object server (e.g., the object server implementing the DocuView application), which

## 6

responds by rendering data to the client (e.g., browser), as shown in FIG. 15.

FIG. 16 illustrates an embodiment of the present invention's method as implemented in a first application associated with a first computer 1602 comprising: (a) identifying an environment 1610 associated with the first computer 1602 that is remotely controlling, via a second application 1608, a remote session 1616 on a second computer over a first network 1612 (the environment 1610 defining a plurality of parameters communicated between computers 1602 and 1604 as part of a remote session 1616, with each parameter in the plurality of parameters defining an action associated with the remote session 1616), wherein the remote controlling is performed via a bidirectional communication; and (b) the first application 1606, via a unidirectional communication with the environment 1610, modifying at least one parameter associated with the environment 1610, wherein the modified parameter is extracted by an interceptor 1614 associated with the second computer and, based on a look-up, executes a pre-defined action affecting the remote session 1616, with the pre-defined action being different than the modified parameter's associated action.

As a non-limiting example, the first computer 1602 is a client and the second computer 1604 is a terminal server, wherein the client is remotely controlling a RDP® session running on the terminal server. The environment 1610 associated with the client is defined by a plurality of parameters associated with the RDP® session, wherein the parameters can be any (but should not be limited to) the following: keyboard scan codes, cursor position, mouse position, clipboard data, screen resolution, or channel administration. Each of these parameters associated with the RDP session have an associated action.

For example, in a RDP session, when the cursor position parameters (x, y) change based on a change in the position of an input device (e.g., a mouse) associated with the client, such position changes in the client-side has an associated action of changing the mouse position in the remote session 1615 running on the terminal server. As another example, in a RDP session, when a key is depressed in an input device (e.g., a keyboard) associated with the client, such a depression of a key at a client has an associated action of inputting the value of the depressed key in the remote session 1615 running on the terminal server. As yet another example, when the second application sets the resolution of the remote session to 1024×768, the value of ‘1024×768’ is set in the client environment which causes the remote session running at the terminal server to be rendered at the resolution of 1024×768.

In this non-limiting example, the first application unidirectionally modifies one of the parameters associated with the environment 1610 (it is important to note that the change is propagated in a unidirectional manner as the first application 1606 does not wait for a feedback or acknowledgement). For example, the first application 1606 changes the value of the cursor position to (−4, 20) in environment 1610. Interceptor 1614 is aware of the change in the cursor position. Interceptor 1614 has access to a stored table that can be looked up for determining what pre-defined action needs to be executed that corresponds to the cursor position value of (−4, 20). The stored table has a listing of parameter values and associated actions that need to be executed. A simple non-limiting example of the stored table is provided below:

Parameter	Current Value	Associated Action	Modified Value	Pre-Defined Action
Cursor Position	(5, 20)	Place cursor position at x = 5, y = 20	(-4, 20)	Open desktop editor in remote session
Cursor Position	(5, 20)	Place cursor position at x = 5, y = 20	(-5, 20)	Open email application in remote session
Screen Resolution	1024 × 768	Set current remote session resolution to 1024 × 768	1024 × 766	Print currently open file in remote session
Clipboard Data	Value of clipboard	Post value in clipboard into application requesting a paste operation.	Clipboard modified with pasted value changed of "POST(X)"	Enter value of X in current field of application in remote session and run a script.

Although the above-mentioned example illustrates changing the value of the cursor position to an illegal value of -4, it should be noted that the value does not have to be changed to an illegal value as the table can be updated to execute a pre-defined action for a legal value.

Another non-limiting example involved the modification of the clipboard data. The first application unidirectionally modifies the clipboard data (it is important to note that the change is propagated in a unidirectional manner as the first application **1606** does not wait for a feedback or acknowledgement) such that the clipboard has a value of "POST(X)". This value is reflected at the remote session and the Interceptor **1614** has access to a stored table that can be looked up for determining what pre-defined action needs to be executed that corresponds to the clipboard value of "POST(X)". The pre-defined action, which is different than just a paste operation of the value, could be the input of the value of X into a script that is executed. It should be noted that if there is already a string or value in the clipboard (for example, a value that was copied by the user of first computer **1602**), the present invention can temporarily store the clipboard value, modify the clipboard with the new value, execute the pre-defined action corresponding to the modified value, and then revert the clipboard back to the original state of having the temporarily stored value.

The unidirectional nature of parameter modification, where no feedback or acknowledgement is received by the first application **1606** provides for a robust operation as the first application **1606** need not be programmed to account for any network and/or firewall paths that might have to be accounted for during the proper return of an acknowledgement message.

Network **1612** can be any of, or a combination of, the following: local area network (LAN), wide area network (WAN), a wireless local area network (WLAN), wireless wide area network (WWAN), a cellular network, or the Internet.

The present invention, in another embodiment, provides for a method, as implemented in an interceptor associated with a second computer **1604**, comprising: (a) monitoring an environment **1610** associated with a first computer **1602** (the environment defining a plurality of parameters communicated between the first and second computers as part of a remote session, with each parameter defining an action associated with the remote session), wherein the first computer **1602**, via a bi-directional communication, remotely controls a remote session on the second computer **1604** via a second application **1608**, the remote controlling performed over a first network **1612**, and the environment **1610** being bi-directionally accessible by the second application **1608** and unidirectionally accessible by a first application **1606** associated with the first computer **1602**; and (b) intercepting incoming traffic associated with said environment **1610** from the first

computer **1602**, and upon detecting a parameter modified by the first application **1606**, extracting the modified parameter, wherein the pre-defined action is different than the modified parameter's associated action; (c) looking-up (e.g., based on a looking up a table) at least one pre-defined action associated with the modified parameter; and (d) executing the at least one pre-defined action, wherein the execution affects the remote session.

The present invention, in yet another embodiment, provides for a method as implemented in a first application associated **1606** with a first computer **1602** comprising: identifying an environment **1610** associated with said first computer **1602** (wherein the environment **1610** defines a plurality of parameters communicated between computers **1602** and **1604** as part of a remote session, with each parameter having a value picked from at least one valid range of values), wherein the first computer **1602** remotely controlling, via a second application **1608**, a remote session on a second computer **1604** over a first network, with the remote controlling being performed via a bidirectional communication, and (b) the first application **1606**, via a unidirectional communication with the environment **1610**, modifying at least one parameter associated with the environment **1610**, the modification comprising changing the value of at least one parameter to be outside its range of valid values, wherein the modified parameter is extracted by an interceptor **1614** associated with the second computer **1604**, which, based on a look-up, executes a pre-defined action affecting the remote session.

Although the interceptor has been described in the above-mentioned description as being associated with the second computer **1604**, it should be noted that the specific location and implementation of the interceptor **1614** is a matter of choice. For example, FIG. **17** illustrates that the interceptor **1614** can be implemented independent of the second computer **1604**. In one embodiment, the interceptor **1618** is independently located behind a local area network (LAN) **1620**. In another embodiment, interceptor **1618** is implemented as part of a router or switch (not shown).

Additionally, the present invention provides for an article of manufacture comprising computer readable program code contained within implementing one or more modules to affect a novel communication method. Furthermore, the present invention includes a computer program code-based product, which is a storage medium having program code stored therein which can be used to instruct a computer to perform any of the methods associated with the present invention. The computer storage medium includes any of, but is not limited to, the following: CD-ROM, DVD, magnetic tape, optical disc, hard drive, floppy disk, ferroelectric memory, flash memory, ferromagnetic memory, optical storage, charge coupled devices, magnetic or optical cards, smart cards,



EEPROM, EPROM, RAM, ROM, DRAM, SRAM, SDRAM, or any other appropriate static or dynamic memory or data storage devices.

Implemented in computer program code based products are: (a) a first application module to be deployed on a first computer, wherein the first computer remotely and bidirectionally communicates and controls a remote session implemented on a second computer, wherein the first application unidirectionally modifies at least one parameter associated with an environment associated with the first computer, wherein the environment defines a plurality of parameters communicated between the first and second computer as part of the remote session, where each parameter defines an action associated with said remote session; and (b) a second application module to be deployed in the second computer running the remote session, wherein the second application module intercepts communication data from the first computer, and upon detecting a parameter modified by the first application module, extracts the modified parameter, looks up at least one instruction associated with the modified parameter, and executes the pre-defined action, wherein the execution affects the remote session, with the pre-defined action being different than the modified parameter's associated action

#### CONCLUSION

A system and method has been shown in the above embodiments for the effective implementation of a remote communication system and method between an electronic device and a remote computer. While various preferred embodiments have been shown and described, it will be understood that there is no intent to limit the invention by such disclosure, but rather, it is intended to cover all modifications falling within the spirit and scope of the invention, as defined in the appended claims. For example, the present invention should not be limited by software/program, computing environment, or specific computing hardware.

The above enhancements are implemented in various computing environments. For example, the present invention may be implemented on a conventional IBM PC or equivalent, multi-nodal system (e.g., LAN) or networking system (e.g., Internet, WWW, wireless web). All programming and data related thereto are stored in computer memory, static or dynamic, and may be retrieved by the user in any of: conventional computer storage, display (i.e., CRT) and/or hardcopy (i.e., printed) formats. The programming of the present invention may be implemented by one of skill in the art of remote session programming.

The invention claimed is:

**1.** A method as implemented in a first application running in an electronic device comprising:

identifying an environment associated with said electronic device, said electronic device remotely controlling, via a second application, a remote session on a remote computer over a first network, said remote controlling performed via a bidirectional communication, and said environment defining a plurality of parameters communicated between said electronic device and said remote computer as part of said remote session, each parameter in said plurality of parameters defining an action associated with said remote session; and

said first application running in said electronic device, via a unidirectional communication with said environment, modifying at least one parameter associated with said environment, said modified parameter extracted by an interceptor associated with said remote computer and, based on a look-up, executing a pre-defined action

affecting said remote session, said pre-defined action different than said modified parameter's associated action.

**2.** The method of claim **1**, wherein said modified parameter involves modification of any of the following: keyboard scan codes, cursor position, mouse position, clipboard data, screen resolution, or channel administration.

**3.** The method of claim **1**, wherein said first application is any of the following: web application, office productivity application, or a mail client.

**4.** The method of claim **1**, wherein said modified parameter contains an illegal value with respect to said remote session.

**5.** The method of claim **1**, wherein said interceptor is implemented as computer readable program code in said remote computer.

**6.** The method of claim **1**, wherein said first network is a wide area network (WAN).

**7.** The method of claim **1**, wherein said first network is a cellular network.

**8.** The method of claim **1**, wherein said interceptor is implemented as computer readable program code in a network device communicating over a second network with said remote computer.

**9.** The method of claim **8**, wherein said second network is a local area network (LAN).

**10.** The method of claim **1**, wherein said electronic device is a cellular telephone.

**11.** A method as implemented in a first application associated with a computer-based device comprising:

identifying an environment associated with said computer-based device, said computer-based device remotely controlling, via a second application, a remote session on a remote computer over a first network, said remote controlling performed via a bidirectional communication, and said environment defining a plurality of parameters communicated between said computer-based device and said remote computer as part of said remote session, each parameter in said plurality of parameters defining an action associated with said remote session; and

said first application running in said computer-based device, via a unidirectional communication with said environment, modifying at least one parameter associated with said environment, said modified parameter extracted by an interceptor associated with said remote computer and, based on a look-up, executing a pre-defined action affecting said remote session, said pre-defined action different than said modified parameter's associated action.

**12.** The method of claim **11**, wherein said modified parameter involves modification of any of the following: keyboard scan codes, cursor position, mouse position, clipboard data, screen resolution, or channel administration.

**13.** The method of claim **11**, wherein said first application is any of the following: web application, office productivity application, or a mail client.

**14.** The method of claim **11**, wherein said modified parameter contains an illegal value with respect to said remote session.

**15.** The method of claim **11**, wherein said interceptor is implemented as computer readable program code in said remote computer.

**16.** The method of claim **11**, wherein said first network is a wide area network (WAN).

**17.** The method of claim **11**, wherein said first network is a cellular network.

**11**

**18.** The method of claim **11**, wherein said interceptor is implemented as computer readable program code in a network device communicating over a second network with said remote computer.

**19.** The method of claim **18**, wherein said second network is a local area network (LAN).

**20.** A method as implemented in a first application running in an electronic device comprising:

identifying an environment associated with said electronic device, said electronic device remotely controlling, via a second application, a remote session on a remote computer over a first network, said remote controlling performed via a bidirectional communication, and said environment defining a plurality of parameters communicated between said electronic device and said remote computer as part of said remote session, each parameter in said plurality of parameters defining an action associated with said remote session;

identifying at least one parameter to be modified and temporarily storing contents associated with said identified parameter in computer storage;

said first application running in said electronic device, via a unidirectional communication with said environment, modifying said identified parameter, said modified parameter extracted by an interceptor associated with said remote computer and, based on a look-up, executing a pre-defined action affecting said remote session, said pre-defined action different than said modified parameter's associated action; and

**12**

restoring contents associated with said identified parameter from said computer storage.

**21.** The method of claim **20**, wherein said modified parameter involves modification of any of the following: keyboard scan codes, cursor position, mouse position, clipboard data, screen resolution, or channel administration.

**22.** The method of claim **20**, wherein said first application is any of the following: web application, office productivity application, or a mail client.

**23.** The method of claim **20**, wherein said modified parameter contains an illegal value with respect to said remote session.

**24.** The method of claim **20**, wherein said interceptor is implemented as computer readable program code in said remote computer.

**25.** The method of claim **20**, wherein said electronic device is a cellular telephone.

**26.** The method of claim **20**, wherein said first network is a wide area network (WAN).

**27.** The method of claim **20**, wherein said first network is a cellular network.

**28.** The method of claim **20**, wherein said interceptor is implemented as computer readable program code in a network device communicating over a second network with said remote computer.

**29.** The method of claim **28**, wherein said second network is a local area network (LAN).

\* \* \* \* \*