



US007959002B2

(12) **United States Patent**  
**Liao et al.**

(10) **Patent No.:** **US 7,959,002 B2**  
(45) **Date of Patent:** **\*Jun. 14, 2011**

(54) **AIR ENCLOSURE WITH MULTILAYER DIFFERENT KINDS OF SUBSTRATES**

2003/0094395	A1 *	5/2003	Peper et al.	206/522
2005/0013974	A1 *	1/2005	Koyanagi	428/178
2005/0109411	A1 *	5/2005	Koyanagi	137/846

(75) Inventors: **Chian Hua Liao**, Sindian (TW); **Yao Sin Liao**, Sindian (TW); **Bo Xin Jian**, Sindian (TW); **Yao Chuan Liao**, Sindian (TW)

FOREIGN PATENT DOCUMENTS

JP	H04-128273	U	11/1992
JP	H05-508142	A	11/1993
JP	H06-020041	U	3/1994
JP	H06-022267	U	3/1994
JP	H09-099979	A	4/1997
JP	H11-334762	A	12/1999
JP	2002-019845	A	1/2002
JP	2002-234577	A	8/2002
JP	2003-252376	A	9/2003
JP	2003-292047	A	10/2003

(73) Assignee: **Yao Sin Liao**, Sindian (TW)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 103 days.

\* cited by examiner

This patent is subject to a terminal disclaimer.

*Primary Examiner* — J. Gregory Pickett

*Assistant Examiner* — King M Chu

(21) Appl. No.: **11/743,053**

(74) *Attorney, Agent, or Firm* — Rabin & Berdo, P.C.

(22) Filed: **May 1, 2007**

(57) **ABSTRACT**

(65) **Prior Publication Data**

US 2008/0063315 A1 Mar. 13, 2008

An air enclosure with multilayer different kinds of substrates comprises an air cylinder sheet, at least one air chamber, at least one air entering passageway and a sheet body in which the air cylinder sheet comprises an air filling passageway; the chambers is positioned at one side of the air filling passageway and used for providing an article with the cushioning protection; the air entering passageway is connected to the air filling passageway and the chambers and outside air in the air filling passageway enters the air chamber via the air entering passageway to allow it to be filled with air and expanded; and the sheet body is closely attached onto one side of the air cylinder sheet and used for preventing the air cylinder sheet from being pierced through to damage. The outside air expands the air filling passage while being filled with air and then enters the air chambers via the air entering passageways to allow them to be filled with air and expanded thereby providing the article with the cushioning protection through the air chambers and the sheet body is used to prevent the air chamber from being pierced through to cause air to be leaked out.

(30) **Foreign Application Priority Data**

Sep. 7, 2006 (TW) ..... 95133068 A

(51) **Int. Cl.**  
**B65D 30/10** (2006.01)

(52) **U.S. Cl.** ..... **206/522; 383/3**

(58) **Field of Classification Search** ..... 206/522;  
383/3, 44; 428/35.2


See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,469,966	A *	11/1995	Boyer	206/522
5,755,329	A *	5/1998	Sadow	206/522
5,912,058	A *	6/1999	Takahashi et al.	428/34.3

**20 Claims, 23 Drawing Sheets**






FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2A




FIG. 2B




FIG. 2C






FIG. 2D






FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 4A




FIG. 4B






FIG. 4C




FIG. 4D




FIG. 4E




FIG. 4F




FIG. 4G




FIG. 4H






FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D



1

## AIR ENCLOSURE WITH MULTILAYER DIFFERENT KINDS OF SUBSTRATES

### CROSS-REFERENCES TO RELATED APPLICATIONS

This non-provisional application claims priority under 35 U.S.C. §119(a) on Patent Application No(s). 095133068 filed in Taiwan, R.O.C. on 2006/09/07, the entire contents of which are hereby incorporated by reference.

### FIELD OF INVENTION

The present invention relates to an air enclosure, and more particularly to an air enclosure with multilayer different kinds of substrates.

### BACKGROUND

A conventional way for packing an article with a cushioning agent mostly is wrapping around the article with a plastic sheet on which a plurality of small raised air bags are projected to attain to the shock-absorbed cushioning functions. But the shock absorption capability of the small air bags is limited such that the cushioning and the shock absorption effects to a larger shock or impulse cannot be attained. Therefore, an air packing bag is developed to take as a wrapping cushioning means

However, the air bag made from polyethylene (PE) is easy to be pierced through by a sharp acute angle of a packed article or an adjoining angle of hardware; once a small broken hole appears on the air packing bag, fluid in the air packing bag is then leaked out. If each air cylinder of the air packing bag is disposed with an independent check valve, it is limited to the air cylinder on which the broken hole is yielded leaks air, and is not to cause other unbroken air cylinders to leak air. But, if only one check valve is disposed in the whole air packing bag, the air in the whole air packing bag is then caused to leak out when the broken hole is generated on any air cylinder to cause the whole air packing bag to lose the cushioning protection effect.

Therefore, for not only improving a structure of an air packing bag, but also solving the problem that the air packing bag is pierced through by a packed article and preventing any air cylinder from being damaged to cause the whole air packing bag to lose the suffering protection effect, the present invention is proposed.

### SUMMARY

The present invention proposes an air enclosure with multilayer different kinds of substrates adapted to wrap an article thereby providing a cushioning protection; it comprises an air cylinder sheet, at least one air chamber, at least one air entering passageway and a sheet body; in which the air cylinder sheet comprises an air filling passageway; the air chambers used for providing the cushioning protection for the article are disposed at one side of the air filling passageway; the air entering passageways are connected with the air filling passageway and the air chambers and outside air in the air filling passageway flows into the air chambers through the air entering passageways to fill air and expand them; the sheet body used for preventing the air cylinder sheet from being pierced through to damage is closely attached onto one side of the air cylinder sheet.

the outside air expands the air filling passageway when air is filled and then flows into the air chambers via the air

2

entering passageways to allow them to be filled with air and expanded. A user can use a different shape and size of sheet body or case to wrap the article so as to provide the cushioning protection for the article through the air chambers and preventing the air chambers from being pierced through to allow the air to be leaked.

### BRIEF DESCRIPTION OF THE DRAWINGS

The present invention can be more fully understood by reference to the following description and accompanying drawings, in which:

FIG. 1A is a plane view, showing an air enclosure before air is filled of a first preferred embodiment according to the present invention;

FIG. 1B is a perspective view, showing an air enclosure after air is filled of a first preferred embodiment of the present invention;

FIG. 1C is an air enclosure after air is filled of a first preferred embodiment according to the present invention;

FIGS. 2B to 2D are schematic views, respectively showing a bended air enclosure of a first preferred embodiment according to the present invention;

FIGS. 3A to 3D are schematic views, respectively showing an air enclosure after being filled with air of a second preferred embodiment according to the present invention;

FIGS. 4A to 4G are schematic views, respectively showing a bended air enclosure of a second preferred embodiment according to the present invention;

FIG. 4H is a plane view of an air enclosure shown in FIG. G before being filled with air; and

FIGS. 5A to 5D are schematic view, respectively showing an air enclosure in practical use of a second preferred embodiment according to the present invention.

### DETAILED DESCRIPTION

Please refer to FIGS. 1A to 1C. FIG. 1A is a plane view showing an air enclosure before being filled with air of a first preferred embodiment according to the present invention. FIG. 1B is a perspective view showing an air enclosure after being filled with air of a first preferred embodiment according to the present invention. FIG. 1C is a cross sectional view showing an air enclosure after being filled with air of a first preferred embodiment according to the present invention.

An air enclosure 6 with multilayer different kinds of substrates comprises two outer films 2a and 2b, two inner films 1a and 1b, an air filling passageway 9, air chambers 11, air entering passageways 13 and a sheet body 15.

Both outer films 2a and 2b are folded together vertically.

Both inner films 1a and 1b are attached on one side of the outer film 2a or 2b, and a heat resistant material 1c is spread between the inner films 1a and 1b so as to use the heat resistant material 1c as a passageway capable of allowing air to flow.

Hot sealing is processed along hot sealing lines 3a, 3b, 3e, 3d, 3e and 3f to form an air cylinder sheet 8, in which hot sealing is used to adhere the outer films 2a and 2b and the inner films 1a and 1b together to allow the air filling passageway 9 to be formed between the outer films 2a and 2b. More particularly, the air filling passageway 9 is formed by sticking the two outer films 2a and 2b together by the hot sealing line 3a, and sticking the two outer films 2a and 2b to the two inner films 1a and 1b by the hot sealing line 3f. In the air filling passageway 9 many hot sealing points 3g are positioned between the hot sealing lines 3a and 3f, and stick one of the outer films 2a and 2b to one of the inner films 1a and 1b, The



air filling passageway **9** is passed through the hot sealing lines **3e** and comprises an air inlet **12** through which outside air can be filled in. Furthermore, a plurality of air chambers **11** are formed by adhering the outer films **2a** and **2b** by means of hot sealing. Thereafter, hot sealing is processed on air chambers **11** to generate a plurality of nodes **14a** to enable the air chambers **11** to be bended along the nodes **14a**.

A heat resistant material **1c** is spread separately and sequentially between the inner films **1a** and **1b**, for example, heat resistant resin or ink is printed to allow the inner films **1a** and **1b** not to be adhered to each other even after hot sealing is processed to form the air entering passageways **13**.

The air cylinder sheets **8** can be spread in parallel, stacked in sequence or arranged in vertical disposition on one side of the sheet body **15** and fixed on the sheet body **15** through adhesive or fixed on one side of the sheet body **15** by means of hot sealing. Besides, the sheet body **15** can also be attached levelly on a surface of the air chambers **11**. Moreover, the air chambers **11** can be bended to form multiple layers of air chambers folded to each other along the nodes **14a** thereby providing the multilayer cushioning effect.

The sheet body **15** mentioned above is made from a soft material, for example, Polyvinylchloride (PVC), Polypropylene (PP), EPE, EPP, cloth or foam; it can also be made from corrugated paper, paper or paper-like material.

Air enters the air inlet **12** to expand the air filling passageway **9** to allow the inner films **1a** and **1b** to be pulled apart outward to open the air entering passageways **13** such that air in the air filling passageway **9** can be used to fill the air chambers **11** with air to cause the air chambers **11** to be filled with air and expanded. Because an air pressure at a curved portion of the air entering passageway **13** is larger than the one at two sides thereof, air in the air filling passageway **9** is allowed to enter easily and escape difficulty, and the curved portion of the air entering passageway **13** is pressed tightly when the pressure in the air chamber **11** is increased to attain to the air locking effect. Furthermore, the inner air pressure of the air chamber **11** presses the inner films **1a** and **1b** to allow them to be attached and pressed tightly on the outer film **2a** or **2b** to cause the air entering passageway **13** to seal the air chamber. Whereby, the air is not allowed to leak out so as to attain to the air locking effect.

After the air filling is completed, the sheet body **15** can then be used to wrap an article **20**, thereby providing the article **20** with the cushioning protection through the air cylinder sheet **8** and preventing a sharp angle of the article **20** from piercing through the air cylinder sheet **8** to cause the air in the air chamber **11** to be leaked out.

According to the structure disclosed by the present invention, the inner films **1a** and **1b** and the outer films **2a** and **2b** are made from polyethylene (PE). Moreover, the air enclosure **5** with multilayer different kinds of substrates further comprises an outer box **30** on which an accepting space **32** is disposed; the article **20** can then be placed into the accepting space **32** of the outer box **30** after it is wrapped by the air cylinder sheet **8** and the sheet body **15** to allow a user to transport the article **20**. Furthermore, the sheet body **15** can be bended to form a case **16**; the case **16** comprises a filling space used for accepting the air cylinder sheet **8**.

Please refer to FIGS. **2A**, **2B** and **2C**. FIGS. **2A**, **2B** and **2C** are schematic views respectively showing a bended air enclosure of a first preferred embodiment according to the present invention.

In order to be able to wrap the article **20** more completely, the sheet body **15** can be cut out to a proper shape or size, or bending is processed on the sheet body **15** to enable the sheet body **15** to be more attached to the article **20**, for example,

bend the sheet body **15** to a curved face to allow the sheet body **15** to attach onto a surface of the article completely or bend the sheet body **15** to a circular cylinder to allow the article **20** to be accepted in a space in the circular cylinder and provide the article **20** with the cushioning protection through the air chambers **11**. If the accepted article **20** has a sharp angle, the sharp angle can be prevented from piercing through the air chamber **11** to cause air to be leaked out by means of the sheet body **15**. Besides, the sheet body **15** can also be bended to more than one right angle and two sheets of the sheet body **15** perpendicular to each other can be respectively stuck onto the air chambers **11**, or the air chambers **11** can also be bended along the nodes **14a** and stuck onto the sheet body **15**. Moreover, if the sheet body **15** is made from polypropylene (PP) or EPE, it can further provides the article **20** with secondary cushioning to enforce the shock-absorbed cushioning effect.

The air cylinder sheet **8** can be bended along the nodes **14a** and two sides of the air cylinder sheet **8** are stuck together to form a bag by means of hot sealing and thereby the article **20** can be accepted in the bag to provide the article **20** with the cushioning function, in which the sheet body **15** can be positioned on an inner surface of the bag and can also be positioned on an outer surface of the bag or on both inner and outer sides thereof simultaneously to prevent the air cylinder sheet **8** from being pierced through to cause air to be leaked out.

Please refer to FIGS. **3A**, **3B**, **3C** and **3D**. FIGS. **3A**, **3B**, **3C** and **3D** are schematic views respectively showing an air enclosure after being filled with air of a second preferred embodiment according to the present invention.

An air enclosure **6** with multilayer different kinds of substrates comprises a air cylinder sheet **8** and case **16**.

The air cylinder sheet **8** is constituted by two outer films **2a** and **2b** and two inner films **1a** and **1b** and they are adhered to each other by means of hot sealing to form an air filling passageway **9**, a plurality of air chambers and air entering passageways, in which a plurality of nodes **14a** are also generated on the air chambers **11** by means of hot sealing to allow the air chambers **11** to be bended along the nodes **14a**.

The case **15** is made from a soft material, for example, polyvinylchloride (PVC), polypropylene (PP), EPE, EPP, cloth or foam; it can also be made from corrugated paper, paper or paper-like material. The case **16** has a filling space **160** therein used for accepting a plurality of air chambers **11**; the plurality of air chambers can be spread in parallel, stacked in sequence or arranged in a vertical disposition in the filling space **160**, and fixed on the case **16** by means of adhering or stuck to fix into the filling space **160** by means of hot sealing.

please refer to FIGS. **4A** to **4H**. FIGS. **4A** to **4G** are schematic views respectively showing a bended air enclosure of a second preferred embodiment according to the present invention. FIG. **4H** is a plane view showing a bended air enclosure shown in FIG. **4G** before being filled with air.

For wrapping the article **20** more completely, a different shape or size of case **16**, for example, italic with curved surfaces type case **16**, square arch type case **16** or circular cylinder type case **16**, can be used, and at least one air cylinder sheet **8** is placed in the filling space **160** of the case **16**; this allows the article **20** with a different shape or size to be borne or clipped.

A clipping space **162** used for clipping one corner of the article **20** is also disposed on the case **16** to prevent the article **20** from being struck to scrape or damage during transportation. Moreover, the case **16** can be a square type case and the article is accept therein through a space in the middle of the case **16**, and the case **16** accepting the article **20** can be placed



## 5

into the outer box to form a box-in-box structure to enforce the shock absorbed cushioning protection function.

Furthermore, an air-filling forbidding zone **14b** is disposed on the middle air chambers **11** of the air cylinder sheet **8** to allow the air cylinder sheet to be bended along the nodes **14a** and then bended along the air-filling forbidding zone **14b** so as to allow the air cylinder sheet **8** to cushion and protect two faces perpendicular to each other and one side face thereof of the article **20** or three faces of the article adjacent to one another. Whereby, one single air cylinder sheet **8** is allowed to provide the multidirectional cushioning function to enforce the shock-absorbed cushioning effect of the air cylinder sheet **8**.

Please refer to FIGS. **5A**, **5B**, **5C** and **5D**. FIGS. **5A**, **5B**, **5C** and **5D** are schematic views respectively showing an air enclosure in practice of a second preferred embodiment according to the present invention.

When the article **20** is a curved body, the case **16** can be disposed with a curved clipping face for clipping a curved face of the article **20** to allow the article **20** to be conveniently loaded into the accepting space **32** of the outer box **30** so as to attain to the shock absorbed cushioning protection effects.

Furthermore, when the article **20** is square, two square arch type cases **16** can be used to put around both upper and lower sides or both left and right sides of the article **20**, and the article **20** is then loaded into the outer box **30**. Otherwise, four L type cases **16** can be used to put around four corners of the article **20**, and the article is then loaded into the outer box **30**. Besides, a plurality of different sizes of cases **16** can be arranged to put around the article to enforce the shock-absorbed cushioning protection effect to the article depending on the article **20** or a user's requirement.

Furthermore, the air enclosure **6** with multilayer different kinds of substrates can first be placed into the outer box **30** while being used, and the article **20** is then loaded into the outer box **30**; this can also attain to the shock-absorbed cushioning effect.

According to the structure disclosed by the present invention, the air filling passageway **9** is a space formed by adhering two outer films **2a** and **2b** together by means of hot sealing, a space formed by adhering two inner films **1a** and **1b** together by means of hot sealing or a space formed by adhering an inner film **1a** to an outer film **2a** by means of hot sealing. Moreover, if there is only one inner film **1a**, a heat resistant material **1c** can be spread between an inner film **1a** and an outer film **2a** so as to allow the heat resistant material **1c** to be used as an air flowing passageway. Hot sealing mentioned above can be hot mold pressing.

The air cylinder sheet **8** or the air chambers can provide the good shock-absorbed cushioning effect, but it is easy to be pierced through by a sharp angle of the article to cause air to be leaked out. On the contrary, there is no worry over the sharp angle of the article **20** piercing through the sheet body **15** or the case **16**, but the shock-absorbed cushioning effect to the article **20** cannot be provided. Therefore, the multilayer substrates are used according to the present invention to combine the merits of the both to enforce the air cylinder sheet **8** or the air chambers **11** such that it can prevent the sharp angle of the article **20** from piercing through the air chamber **11** to cause air to be leaked out. Furthermore, according to the present invention, a different shape or size of sheet body **15** or case **16** can be used to wrap the article **20**, partly wrapping or completely wrapping the article **20** can be chosen and the cushioning protection is provided for the article **20** through the air chambers **11**. After the article **20** is wrapped with the air cylinder sheet **8** and the sheet body **15** or the case **16**, it can

## 6

then be placed into the accepting space **32** of the outer box **30** so as to be convenient for a user to transport the article **20**.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the invention in its broader aspects is not limited to the specific details and representative embodiments shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.

What is claimed is:

**1.** A multilayer air enclosure with different kinds of substrates, adapted to cover an article thereby providing a cushioning protection, and including an air cylinder sheet, the air cylinder sheet comprising:

two outer films, stacked together vertically;

two inner films, positioned between the two outer films;

an air filling passageway, being a space formed by sticking the two outer films together by a first hot sealing portion and a second hot sealing portion, wherein the first hot sealing portion sticking the two outer films, the second hot sealing portion sticking the two outer films to the two inner films;

a plurality of hot sealing points, positioned between the first hot sealing portion and the second hot sealing portion so as to lie in the air filling passageway, each hot sealing point lying in between one sheet of the outer films and one sheet of the inner films to stick one sheet of the outer films to one sheet of the inner films;

at least one chamber, disposed at one side of the air filling passageway, being an air storing space formed by sticking the two outer films together by means of hot sealing and providing the article with the cushioning protection; and

at least one air entering passageway, connected to the air filling passageway and the air chamber, formed by spreading a heat resistant material distantly and sequentially on one face of one of the inner films, the face then not stuck to a face of the other one of the inner films by the hot sealing, the outer films being forced apart outwardly when outside air enters and expands the air filling passageway, the two sheets of the unstuck inner films being driven to pull apart outwardly by the hot sealing points to open the air entering passageway, causing the outside air in the air filling passageway entering the air chambers through the air entering passageway to allow the air chambers to be filled with air and expanded, the outside air entering the air cylinder and then compressing the inner film to cover the air entering passageway to shield the air chamber; and

a sheet body, closely attached onto one side of the air cylinder sheet used to prevent air cylinder sheet damage due to piercing.

**2.** The air enclosure according to claim **1**, further comprising an outer box used for accepting the air cylinder sheet, the sheet body and the article thereby being convenient for transportation.

**3.** The air enclosure according to claim **1**, wherein adhering or hot sealing is used for fixing the air cylinder sheet onto one side of the sheet body.

**4.** The air enclosure according to claim **1**, wherein at least one node is formed on the air cylinder sheet by means of hot sealing to allow the air cylinder sheet to be bent along the node.



7

5. The air enclosure according to claim 4, wherein two sides of the air cylinder sheet are adhered to each other to form a bag by means of hot sealing after the air cylinder sheet is bent along the node.

6. The air enclosure according to claim 5, wherein the sheet body is disposed on an inner surface or an outer surface of the bag.

7. The air enclosure according to claim 1, wherein the air cylinder sheets are spread on one side of the sheet body in parallel.

8. The air enclosure according to claim 1, wherein the air cylinder sheets are stacked on one side of the sheet body in sequence.

9. The air enclosure according to claim 1, wherein the air cylinder sheets are arranged in a vertical disposition on one side of the sheet body.

10. The air enclosure according to claim 1, wherein the sheet body is levelly attached on a surface of the air chamber.

11. The air enclosure according to claim 1, wherein the sheet body is bent to form a circular cylinder.

12. The air enclosure according to claim 1, wherein the sheet body is bent to form a curved face.

13. The air enclosure according to claim 1, wherein the sheet body is bent to form at least one right angle to wrap the article.

8

14. The air enclosure according to claim 13, wherein at least one node is formed on the air chamber by means of hot sealing to allow the air chamber to be bent along the node to closely attach on one side of the sheet body.

15. The air enclosure according to claim 13, wherein at least one air filling forbidding zone is formed on the air chamber by means of hot sealing to allow the air chamber to be bent to cushion and protect three adjacent faces of the article along the air filling forbidding zone.

16. The air enclosure according to claim 13, wherein the sheet body is bent to form a case, and the case comprises a filling space used for accepting the air cylinder sheet.

17. The air enclosure according claim 1, wherein the sheet body is made from a soft material.

18. The air enclosure according to claim 17, wherein the soft material is chosen from a group consisting of cloth and foam.

19. The air enclosure according to claim 17, wherein the soft material is chosen from a group consisting of corrugated paper, paper and paper-like material.

20. The air enclosure according to claim 17, wherein the soft material is chosen from a group consisting of polyvinylchloride (PVC), polypropylene (PP), EPE and EPP.

\* \* \* \* \*