

US007967207B1

(12) **United States Patent**
Harris

(10) **Patent No.:** **US 7,967,207 B1**
(45) **Date of Patent:** ***Jun. 28, 2011**

(54) **BAR CODE DATA ENTRY DEVICE**

(75) Inventor: **Scott C. Harris**, Rancho Santa Fe, CA
(US)

(73) Assignee: **Bartex Research, LLC**, Dallas, TX
(US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **10/714,097**

(22) Filed: **Nov. 14, 2003**

Related U.S. Application Data

(62) Division of application No. 09/618,988, filed on Jul.
18, 2000, now Pat. No. 6,666,377.

(51) **Int. Cl.**
G06K 7/10 (2006.01)
G06K 7/14 (2006.01)
G06K 7/00 (2006.01)

(52) **U.S. Cl.** **235/462.01**; 235/454; 235/435

(58) **Field of Classification Search** 235/379-381,
235/462.01, 435, 454, 492, 461, 385, 375
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,476,381 A 10/1984 Rubin
4,570,057 A * 2/1986 Chadima et al. 235/462.45
4,896,029 A 1/1990 Chandler
4,973,830 A * 11/1990 Ouchi et al. 235/462.16
5,012,075 A * 4/1991 Hutchison et al. 235/379

5,176,224 A * 1/1993 Spector 186/52
5,235,172 A * 8/1993 Oehlmann 235/494
5,276,315 A * 1/1994 Surka 235/462.1
5,298,731 A * 3/1994 Ett 235/462.02
5,302,491 A * 4/1994 Akylas et al. 430/311
5,329,105 A * 7/1994 Klancnik et al. 235/462.16
5,352,878 A * 10/1994 Smith et al. 235/462.16
5,361,871 A * 11/1994 Gupta et al. 186/61
5,369,264 A * 11/1994 Rosa et al. 235/462.02
5,477,042 A 12/1995 Wang
5,550,363 A * 8/1996 Obata 235/462.11
5,563,401 A * 10/1996 Lemelson 235/494
5,576,528 A 11/1996 Chew et al.
5,585,616 A * 12/1996 Roxby et al. 235/462.06
5,597,997 A * 1/1997 Obata et al. 235/455
5,602,382 A * 2/1997 Ulvr et al. 235/462.02
5,608,200 A * 3/1997 Le Goff et al. 235/462.02
5,663,552 A * 9/1997 Komizo 235/472.01
5,710,417 A * 1/1998 Joseph et al. 235/462.11
5,767,497 A * 6/1998 Lei 235/462.12

(Continued)

FOREIGN PATENT DOCUMENTS

JP 55102083 8/1980

(Continued)

OTHER PUBLICATIONS

www.iidautomation.com/ccdreaders.*

(Continued)


Primary Examiner — Daniel Walsh

(74) *Attorney, Agent, or Firm* — Law Office of Scott C.
Harris

(57) **ABSTRACT**

Bar codes used for various applications. A bar code can be
used for biometrics, or for computer data entry. A special bar
code is described that has additional information, but can be
read by other readers.

12 Claims, 4 Drawing Sheets



U.S. PATENT DOCUMENTS

5,773,806	A	6/1998	Longacre	
5,805,740	A *	9/1998	Takagi et al.	382/257
5,869,828	A *	2/1999	Braginsky	235/469
5,914,476	A	6/1999	Gerst	
5,914,477	A *	6/1999	Wang	235/462.1
5,920,062	A *	7/1999	Williams	235/494
5,978,773	A *	11/1999	Hudetz et al.	705/23
5,984,177	A *	11/1999	Do et al.	235/379
6,032,861	A *	3/2000	Lemelson et al.	235/456
6,032,863	A *	3/2000	Nethery, III	235/462.07
6,045,048	A *	4/2000	Wilz et al.	235/472.01
6,049,821	A *	4/2000	Theriault et al.	709/203
6,070,805	A *	6/2000	Kaufman et al.	235/494
6,081,842	A *	6/2000	Shachar	709/229
6,082,621	A *	7/2000	Chan et al.	235/462.28
6,095,418	A *	8/2000	Swartz et al.	235/462.01
6,102,289	A *	8/2000	Gabrielson	235/462.01
6,112,991	A *	9/2000	Klug	235/462.04
6,270,724	B1	8/2001	Woodman	
6,321,986	B1	11/2001	Ackley	
6,345,764	B1 *	2/2002	Knowles	235/472.01
6,354,503	B1 *	3/2002	Chiu	235/462.18
6,398,117	B1 *	6/2002	Oakeson et al.	235/494
6,446,871	B1 *	9/2002	Buckley et al.	235/472.03
6,457,651	B2 *	10/2002	Paul et al.	235/494
6,478,223	B1	11/2002	Auckley	
6,479,016	B1	11/2002	Goldsmith et al.	
6,536,670	B1 *	3/2003	Postman et al.	235/487
6,542,933	B1 *	4/2003	Durst et al.	709/229
6,550,672	B1 *	4/2003	Tracy et al.	235/383
6,622,917	B1 *	9/2003	Knowles	235/462.01
6,629,642	B1 *	10/2003	Swartz et al.	235/462.46
6,631,843	B2 *	10/2003	Schuessler	235/462.07
6,655,597	B1 *	12/2003	Swartz et al.	235/462.45
6,666,377	B1 *	12/2003	Harris	235/462.25
6,672,511	B1 *	1/2004	Shellhammer	235/462.08
6,688,523	B1 *	2/2004	Koenck	235/462.06
6,802,450	B2 *	10/2004	Cheung et al.	235/462.25
6,827,273	B2 *	12/2004	Wilz et al.	235/472.01
6,991,164	B2 *	1/2006	Lemelson et al.	235/456
7,185,816	B1 *	3/2007	Shoobridge	235/462.04
7,207,481	B2 *	4/2007	Barenburg et al.	235/381
7,225,260	B2 *	5/2007	Herrod	709/227
7,229,025	B2 *	6/2007	Sussmeier et al.	235/494
7,578,443	B1 *	8/2009	Harris	235/462.01
7,878,400	B2 *	2/2011	Harris	235/462.04
2001/0006191	A1 *	7/2001	Hecht et al.	235/462.16
2001/0030234	A1 *	10/2001	Wiklof	235/383
2001/0045461	A1 *	11/2001	Schuessler	235/462.07
2002/0000468	A1 *	1/2002	Bansal	235/462.15
2002/0017566	A1 *	2/2002	Knowles	235/472.01
2002/0020747	A1 *	2/2002	Wakamiya et al.	235/462.11
2002/0023959	A1 *	2/2002	Miller et al.	235/462.13
2002/0030105	A1 *	3/2002	Miller et al.	235/462.13
2002/0047867	A1 *	4/2002	Mault et al.	345/810
2002/0050526	A1 *	5/2002	Swartz et al.	235/472.02
2002/0065728	A1 *	5/2002	Ogasawara	705/23
2002/0074403	A1 *	6/2002	Krichever et al.	235/454
2002/0082931	A1 *	6/2002	Siegel et al.	705/26
2002/0084330	A1 *	7/2002	Chiu	235/462.11
2002/0088865	A1 *	7/2002	He et al.	235/494
2002/0102966	A1 *	8/2002	Lev et al.	455/412
2002/0185540	A1 *	12/2002	Hashimoto et al.	235/462.25
2002/0186884	A1 *	12/2002	Shaked et al.	382/183
2002/0194075	A1 *	12/2002	O'Hagan et al.	705/21
2003/0034399	A1 *	2/2003	Wilz et al.	235/462.45
2003/0050033	A1 *	3/2003	Kawaguchi	455/277.1
2004/0026511	A1 *	2/2004	Cheung et al.	235/462.1
2004/0069855	A1 *	4/2004	Patel et al.	235/472.01
2004/0177148	A1 *	9/2004	Tsimelzon, Jr.	709/227
2004/0246529	A1 *	12/2004	Pruden et al.	358/3.28
2005/0023354	A1 *	2/2005	Sali et al.	235/462.04
2005/0040230	A1 *	2/2005	Swartz et al.	235/383
2005/0061878	A1 *	3/2005	Barenburg et al.	235/385
2005/0083413	A1 *	4/2005	Reed et al.	348/211.99
2005/0198095	A1 *	9/2005	Du et al.	709/200
2005/0199724	A1 *	9/2005	Lubow	235/462.01

2005/0240478	A1 *	10/2005	Lubow et al.	705/14
2005/0246237	A1 *	11/2005	Hudetz et al.	705/26
2005/0269416	A1 *	12/2005	Sussmeier et al.	235/494
2005/0273186	A1 *	12/2005	Morris et al.	700/59
2006/0006231	A1 *	1/2006	Anson et al.	235/435
2006/0006238	A1 *	1/2006	Singh	235/462.46
2006/0118631	A1 *	6/2006	Lubow et al.	235/462.01
2006/0213969	A1 *	9/2006	Russell et al.	235/375
2006/0231635	A1 *	10/2006	Kim et al.	235/494
2006/0237547	A1 *	10/2006	Barenburg et al.	235/494
2006/0255150	A1 *	11/2006	Longacre, Jr.	235/462.45
2006/0278709	A1 *	12/2006	Longacre et al.	235/462.07
2006/0283952	A1 *	12/2006	Wang	235/462.01
2007/0124414	A1 *	5/2007	Bedingfield et al.	709/217
2008/0191025	A1 *	8/2008	Harris	235/462.41

FOREIGN PATENT DOCUMENTS

JP	61217887	9/1986
JP	3192523	8/1991
JP	07244652 A *	9/1995
JP	10309860 A	11/1998

OTHER PUBLICATIONS

www.hallogram.com/barcodes/others.html.*
 “A white Paper on Two Dimensional Symbols”, CSPI 1996.
 “QED systems in review” Aug. 1999.
 RPS Multicode Bar Code Label Guide, Undated.
 Getting Great Mileage from Automatic Data Collection, Material Handling Engineering (May 1995).
 ANSI MH10.8.3M-1996.
 RPS’s Multicode(SM) Gives Shippers More Information Options; Symbol Technologies LS 4800 Scanners Will Transform RPS into ‘Data Warehouse,’ Business Wire (Oct. 18, 1995).
 “Reading Between the Lines” by Craig Harmon, 1997.
 “UPS Guide to Barcoding”, undated.
 P. Mathans, B. Stamp, and C. Harmon, A White Paper on Two Dimensional Symbols: Because you need information on the fly and on the spot, Vision Systems (1996).
 “Guide to Bar Coding with UPS . . . ” undated.
 “Packaging—Bar code and tw0-dimensional symbols for shipping, transport and receiving labels”, ISO 15394, 2000.
 Automatic Data Capture (ADC) 2D Code applications at Siemens AG, Nov. 1998.
 Symbol Technologies PDF417 Selected by Defense Department as 2D Symbolology for Global ID card, Nov. 1994.
 Warehouse Management Systems: Configurability for Optimization, Oct. 1996.
 AIM—ITS/99-003, Oct. 1999.
 AIM—ITS/99-002, Oct. 1999.
 Codes Don’t Sweat the Small Stuff, Oct. 1998.
 The Portable Database Debate, Nov. 1990.
 Exhibit A, Judgment, Appeal from the United States District Court for the Eastern District of Texas in Case No. 07-CV-0385, Feb. 22, 2011, pp. 1-3.
 Reexam. Control No. 95/000,423, Update on Concurrent Litigation Under 37 CFR 1.985(b), Mar. 1, 2010, pp. 1-3.
 www.iidautomation.com/ccdreaders, dated Nov. 21, 2006.
 www.hallogram.com/barcodes/others.html, dated Nov. 21, 2006.
 Order of Invalidity in parent application 6666377, Feb. 19, 2010.
 Database Disclosure, 1999.
 Markman Construction, Apr. 22, 2009.
 Stages of Developments of International Standards, Jun. 10, 2009.
 How ISO develops standards, Jun. 1, 2009.
 ISO TC 122, Jun. 1, 2009.
 Declaration of Scott Harris, from *Illinois Computer Research, LLC v Fish & Richardson, PC*, 2007.
 File of Reexamination control No. 95/000,423, 2008-present.
 Various Court filings for *Bartex Research, LLC, v. Fedex Corporation, Fedex Express Corporation, Fedex Ground Package System, Inc., and Fedex Kinko’s Office and Print Services, Inc.* Civil Action No. 6:07-cv-00385 LED, Eastern District of Texas, Tyler Division, 2007-2008.

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7A




FIG. 7B




FIG. 7C

BAR CODE DATA ENTRY DEVICE

This is a divisional of U.S. application Ser. No. 09/618,988 filed Jul. 18, 2000 now U.S. Pat. No. 6,666,377.

BACKGROUND

The present application relates to bar codes, and to scanning of bar codes and other scannable type codes to obtain and enter information.

Bar codes are often used in scanning of information. A bar code provides information based on sizes of its different parts.

Typical linear/one-dimensional bar codes provide white and dark bars forming a bar code image. Linear bar codes may include Universal Product Codes (UPCs), Type 39 bar codes and type 128 bar codes. Two-dimensional bar codes, including a "matrix" code and the "Gettysburg Address" type bar code, are also known. Bar codes have been used for many purposes including inventory control.

SUMMARY

The present application teaches using scanned information from a scannable code to enter special kinds of information. One embodiment describes using the scannable code in place of a photo. Another embodiment describes bar codes being sent as part of a message, where the message can be an advertisement, an email, or the like. The information in the bar code relates to some aspect of the message. For example, one embodiment describes using the bar code to represent a meeting time that is described in an email. Another embodiment describes using the bar code to represent a time and place of a function being advertised, e.g. an event. The bar codes can represent the information itself, or can represent an address from a look up database which includes more information about the bar code.

Another embodiment describes special kinds of bar codes which store additional information in a different way than previously carried out. One of these information types is a progressive information type where the bar code can be read by either a linear or a two-dimensional bar code scanner.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other aspects will now be described in detail with respect to the accompanying drawings, wherein:

FIGS. 1A and 1B show an image used in a cellular telephone and/or a portable computer;

FIG. 2 shows a flowchart of operation of the sensor;

FIG. 3 shows a diagram of encoding of a photo;

FIG. 4 shows a message with an associated bar code entry part;

FIG. 5 shows a client-server Internet embodiment;

FIG. 6 shows a bar code meeting system; and

FIGS. 7A-7C show new specialized bar code schemes.

DETAILED DESCRIPTION

The present application teaches using a symbolical code, such as a bar code, to enter information into a computer device. The computer device can be a portable computer which is described herein as being any computer in which the display and user interface are within the same housing, or a personal digital assistant which is a smaller version of the personal computer, which again has data entry parts and display within a single housing, but has outer perimeters which are sized to fit any user's hand, e.g. less than ten inches by ten inches. Another embodiment describes a special kind of PDA which includes a portable telephone such as a cellular telephone, included therein.

The bar codes can be imaged/scanned in a number of different ways. One embodiment discloses using a camera to input and decode these bar codes. The embodiments are shown in FIGS. 1A and 1B. FIG. 1A describes using a personal digital assistant **100** as the input device. One preferred input device of this type is the Palm V™ type hand held computer. A bar code scanner can be used, such as the commercially available Symbol Technology SPT **1700**. Alternatively, a camera add-on unit can be added to the Palm V and used as described herein. The PDA includes a screen **145** and user interface **146** all within the same housing **99**.

FIG. 1B shows the client being a cellular telephone which also may include a screen **145** and user interface **150**. The cellular telephone can be associated with either a dedicated bar code scanner or an image sensor **160** of the type used to obtain photographs for video telephony.

In both devices, the input device obtains either a scan of the bar code, or an image of the bar code on a medium. The medium can be a display screen such as a computer display screen, or can be a sheet of paper. The information in the bar code is entered into the computer.

If a dedicated bar code scanner is used, then the value of the bar code is automatically output from the scanner by the operating system associated with the bar code scanner. FIG. 2 shows the flowchart which is used to obtain scanning information from a camera.

First the scan of the barcode image is acquired at **200**. This image may be a pixel based bitmap.

Each bar code has certain rules constraining how the bar code is recognized. In two-dimensional bar codes, the spacing/pitch/size of and between the black and white bars often represent the information. Certain rules constrain what is a legal bar code. One such rule is the dead space rules, which defines legal characteristics of the edges of the bar code. The following description defines using the dead space rules, however, it should be understood that other constraining rules could alternately be used.

The bitmap is processed at **205** to look for dead space **208** in the bar code. The amount of spacing, which represents sizes of white and black parts, is then determined. The number of pixels which will represent each part can be ascertained. The image is then processed to find the number of white or black spaces **215**, the next number of white or black spaces **220**, and continuing until the ending dead space **222**. Each blank space can be defined as being a certain number of pixels in the image sensor **118**.

Image straightening algorithms can be used to rotate the image and straighten it in order to avoid improper values.

Then, these raw values at **210** that are indicative of the content of the bar code can be decoded by a conventional bar code decoding technique at **215**. This system describes using an alphanumeric bar code such as the type 39 or type 128 bar code. **215** shows decoding these raw values to obtain the output representing the content of the bar code.

In this way, the image sensor which can be used for video output in a portable telephone, or for obtaining for digital pictures in a PDA, can become a bar code scanner. This system also facilitates using the special kinds of bar codes which are described herein with reference to the additional embodiments.

First Embodiment

Personal Identification. Personal cards such as driver license's and credit cards may include a user's personal identifying information. Signatures are conventionally used, but can be imitated by a clever forger. Photographs can also be used. However, a forger may slice out the photograph and replace it with a duplicate in order to spoof the system. The present application defines printing a bar code on the personal

identification card. The bar code can be encrypted, and can include additional personal identifying information.

U.S. Pat. No. 5,420,924 describes putting a bar code on a personal identification card. However, this system recognized that not enough information can be stored. Therefore, this system took a slice of the overall image.

The information which is stored using this technique can include any personal identifying information, including a picture of the user's face, fingerprint information, dynamic information about the user's signature, i.e. the way that the user actually makes the signature. This can include the speed of signing, the technique of holding the pen, and the like. These latter features are more difficult for a forger to copy. This information is stored as data (e.g. dv/dt of the pen, time, angles, etc.) and stored in the bar code. If an image is used, the image should be of reduced resolution e.g. 20 by 20 pixels. Fingerprints can be stored as vectorized images of the fingerprint (e.g. using Adobe Streamline) or the like. The information is also preferably encrypted using a one way code e.g. such as public key cryptography. All of the public, that is every decoding station, is given the decoding key. Only authorized coders, such as the issuers of the cards are given the encoding key. An unauthorized user cannot make an authorized item of information in this way.

Each item of information can be tested using a hash function. Only information from the authorized user will pass the hash function.

The system described herein uses a type 39 bar code. A typical type 39 bar code has an unlimited number of total digits. Each digit can represent any of 0 through 9, A through Z or any of five punctuation characters. According to the present system, it is recognized that this combination provides the possibility of 41 different values for each digit.

FIG. 3 also shows the encoding operation. The bytes representing the code, shown as **320**, are converted into a base N number at **305**, where N is preferably the highest base that can be represented by all of the digits of the bar code or at least 80% of the digits. Here, a base 41 number is used. The digits zero through 9 represent their own value zero through 9, A through Z represent 10_{41} through 37_{41} , and the punctuation characters represent, respectfully, 38_{41} through 41_{41} . This same scheme can be used for any base of numbers.

At **310**, the file representative of the personal information is converted to base 41. This is then encoded as a type 39 bar code at **315**. The value is then encrypted at **320** using a one way function, and stored on the credit card at **325**. Since the type 39 bar code has no limit on length, any amount of information can be stored in this way.

The bar code is read out and reconverted back to the original number at **330** and is used to drive a display device shown as **335** to display the characteristics. In the case of dynamic signature information or other such information, the stored characteristics may be directly compared against the sample instead of being displayed.

Alternatively, the information can represent a pointer to a database, e.g. a publicly available database. This database can later be accessed as part of an information transfer.

In this system, the information can represent an address, e.g. a number that is associated with a special function. The address is used to access a publicly available information network, e.g. by direct connection or by the Internet. As an example, the bar code may store an address command AD, followed by a base 39 alphanumeric value 4DMKDP. The bar code is scanned to obtain the command to obtain the image from address 4DMKDP. The value 4DMKDP may be converted to hex or binary prior to the request.

The database returns the image of the person.

Another embodiment shown in FIG. 4 uses bar codes to enter information into the computer. The FIG. 4 embodiment stores scannable non-alphanumeric information, e.g. bar

code information, as some part of a communication—here an advertisement. The advertisement can be a print advertisement, a television advertisement, or an Internet advertisement for example. The advertisement **400** includes a bar code **405** therein. The bar code **405** is associated with the advertisement, and includes some additional information about the advertisement. For example, the bar code may include the web site address of the company preparing the advertisement, or appointment information about the advertisement, or a "vcf file" or the like which is an importable file with address information about the company or author sponsoring the advertisement.

In operation, the user brings one of the clients, either the cellular telephone **310** or PDA **315**, into range of the bar code **405**. The client reads the bar code and decodes it as noted above. The decoded information can represent ASCII information, a compressed file such as a zip file, G code information, or any other compressed or non-compressed information. The contents are automatically input into the client. The contents can directly represent that information, in which case the information is input into the client. For example, the information can directly represent the ASCII information indicating the website. Alternatively, the information can represent a pointer to a database, e.g. a publicly available database. This database can later be accessed as part of an information transfer.

For example, Palm systems enable a hot sync where the portable computer is synced with another computer that is running hot sync software.

In this system, the information can represent a cue, e.g. a number, that is associated with a special function. The cue is used during a hot sync to access a publicly available information network, e.g. by direct connection or by the Internet. The cue **431** is sent over the Internet **432** to the server **450**, and addresses more detailed information in a memory of the server. The server returns that information as **455**, and the client receives the more detailed information.

As an example, the bar code may store an cue command CX, followed by a base 39 alphanumeric value 4DMKDP. The bar code is scanned to obtain the command to cue to value 4DMKDP during the next hot sync. The value 4DMKDP may be converted to hex or binary prior to the hot sync.

During hot sync, the database returns the full text of the detailed information, e.g., "visit the website at <http://www.p-dascan.com/~more> to get a free gift." Any desired length or size of information can be returned.

As described above, therefore, this system enables the information in the bar code to be used as an address for look up address from a database. The database can be accessible over the Internet. During a later hot sync, this information can be translated into more detailed information which can be returned from the hot sync.

This information can be a hyperlink. The hyperlink can also use the techniques disclosed in co-pending application No. 60/161,700, entitled Internet Browsing From A Television, in which the origin of the hyperlink is included within the hyperlink itself. In this embodiment, a hyperlink may be stored for later visitation. The hyperlink also include a code therein which indicate the source from which the hyperlink originated. For example, the source may indicate the name of the print magazine, or the web page from which the hyperlink originated, or the like. In this way, the advertisement service can keep track of which advertising forms produce the best results. In addition, this facilitates a paradigm whereby the advertiser pays an advertising fee which is based on the number of website visits from the advertisement.

FIG. 5 shows using this system as part of a communication which is an email. A displayable bar code **500**, in image format, e.g. a GIF, JPEG or PDF, is stored as part of the

5

message. This bar code is then displayed in the specified format to a user. The bar code includes the information described above.

FIG. 6 shows an alternative display which is presented to a user. The email is displayed with its usual text part **600**, which describes text of the message. The text indicates information about something to happen in the future e.g. a meeting. If the user wants to go to the meeting, they are invited to scan the bar code **605**. The bar code, once scanned is translated into information for a PDA, e.g. in Palm or Outlook format. The information may say "bar code meeting"; Thursday 4:00-6:00 p.m. This information is then automatically input into the PDA. As above, this text can represent the actual text information, as is shown in FIG. 6. It can represent a compressed form of the actual information, such as compressed using G code. Alternatively, the information can represent a cue address to be used for a look up table during a hot sync or other information transfer, as previously described herein. This information can be printed, and scanned off the printer, or can be scanned directly off the screen. The system shown in FIG. 6 shows scanning the code to input the information.

The communication can also include auxiliary codes **610**. A first code can be scanned to send an automatic acceptance or declining by email. The format for the email acceptance can also be included within the code, or can simply be a pre-stored email saying a user name A (filled in by the scanning software) has accepted your meeting B (filled in from the information from the bar code).

The present system defines using bar codes to enter relatively large amounts of information into the computer. FIGS. 7A through 7C shows special new bar codes which are described according to the present system, which enable this storage of additional information.

Many different kinds of bar codes, that allow storing larger amounts of information, are known. One such bar code is the "Gettysburg Address" type matrix code. This requires, however specialized scanning equipment. This equipment represents a capital investment and has been slow to catch on. The present system teaches, in FIG. 7A, a special bar code which includes increased capacity bar code information, as well as backwards compatibility with previous bar code scanners. The code shown in FIG. 7A includes two parts. A first part **710** is found as legal when scanned for linear codes. A second part **710** registers as invalid/illegal when scanned in this way.

The linear part **700** is a standard and commercially available linear bar code such as a UPC, Type 39 or Type 128 bar code. A conventional linear bar code reader will read and decode this portion. Part of the standard for these bar codes includes certain spacing requirements. For example, dead space at the edges of the bar code may be one of the required characteristics. These are shown as **702**, **704**. When this dead space is detected, and all other aspects of the bar code are detected, the bar codes can be read and decoded, shown as **711**.

The remainder of the bar code may be a code which fails the decoding requirements for the linear bar code **700**. This failure type bar code can represent a matrix code, for example, of any desired type. For example, this can be a Gettysburg Address or Vericode type matrix code. In addition, however, it can be a special kind of matrix code in which each bar shown as **720** is itself made up of another bar code extending in the vertical direction. The spacing between the bars **720**, **722**, **724** may also include information. Within each bar **720**, for example, the pattern also provides additional information. In this way, the bar code is actually formed of two different bar code scans. A scan in the direction **730** obtains first information, and a scan across each line in the direction **732** obtains additional information. After scanning the line **732**, the system scans along the line **734** to obtain the next item of information. If this is obtained from a camera, however, the

6

whole image can be obtained and later processed using processing techniques to obtain the scan information. In addition, scan information can be obtained from the linear bar code part **700**. FIG. 7A shows the linear part taking up approximately twenty-five percent of the area of the entire bar code. However, the two-dimensional scan can take up much less area, e.g. as little as five to ten percent. When scanning with a conventional bar code scanner of the linear type, the bottom portion may be scanned to obtain the two-dimensional bar code information. Enhanced bar code information can be obtained from the additional portion. This enhanced information can be additional information, or it can be the same information as in the first bar code portion, as well as additional information.

In the context of this system, the linear bar code information can represent an address for look up code of the type described above with reference to FIG. 4. The enhanced or non-linear information **710** can represent the total information. A person with a sufficiently advanced bar code scanner can read the entire information. A person with only a linear bar code scanner, however, may scan only the information **700**, and then updates the information via a hot sync.

An additional way of using this information, for example for scanning products, is also contemplated. Scan part **700** may include a Universal Product Code or UPC. Scanning part **710** may include additional information about the product, such as a description, or picture. The picture of the product may be displayed to the sales clerk, so that the sales clerk can verify that the product being purchased is actually the product that the user is presenting. Both parts of the bar code may represent information about the product. The part **700** represents basic information and the part **710** represents advanced information.

A second enhanced bar code shown in FIG. 7B is a standard linear bar code or two-dimensional bar code with additional information stored in the gray scale. FIG. 7B show the system configured as a two-dimensional bar code. A first stripe **700** represents a dark (i.e. non-white) stripe. A second stripe **702** represents a white stripe and a third stripe **704** representing another dark stripe. Similarly, the code **699** alternates between white stripes and dark stripes throughout the entire code. In this embodiment, however, the dark stripes **700** are not actually black, but may be a color that is a shade of gray. For example, 16 or 256 different grayscale levels may be defined. Each time a code is detected, its grayscale value is obtained as a numeric value. Similarly, the white stripes **702**, **706** may actually be a shade of gray. In this system, rather than simply obtaining spacing information, spacing information and grayscale information are both obtained from the scanning of the code. The gray scale information can be obtained when a camera type imager is used, since the color of the stripes can be obtained in addition to the spacing of the stripes. An alternative is that the white areas **702** are not pure white, but are rather some shade of white which can be characterized between zero and sixteen for example.

Information is obtained from both the shade(s) of gray of the dark portion(s), the white portion(s), and the spacing.

In one embodiment, the sequence of the numbers defining the gray scale levels provides the information. For example, hex value is defined by grayscale values of each gray line. This information is used totally separately from the information that is obtained from the linear barcode information.

Yet another alternative does not use black portions and white portions, but rather uses alternating grayscale portions, with each alternating portion representing a grayscale value. Preferably a system is used whereby the gray scale is itself coded as either the gray scale or the compliment of the gray scale to provide maximum contrast between the bars **700**, **702**.

7

An alternative system shown in FIG. 7C uses color bars in the bar code. Not only is the spacing between the bars determined, but also the numerical value representing the bar values themselves. For example, each color can be represented by an eight bit value. That eight bit value is obtained, and used as part of the retrieved information. The eight bit value can represent 2 hex digits. Again, this information can be used as supplemental to the spacing information obtained by the bar code.

In the latter two systems, color is described as being used with a two-dimensional bar code but can also be used with a three-dimensional bar code. In addition, in this system, the color and the spacing can both be used. By taking the available number of digits, and representing the color by that available number of digits, a number in base n, where n can be a very large number, can be obtained. This facilitates storing even more information into a bar code.

These codes preferably follow the paradigm described above, that scanning with a monochrome scanner may return only a part of the information, e.g. an address to be later used for lookup. The color/grey scale information can be used to provide the actual information. For example, the digits represented by the grey scales or colors can be concatenated to form the overall information. Scanning the code gives the bar code information; while looking at the detailed information gives the enhanced information.

Any of these enhanced information codes can be used with the dual information code described above.

Other embodiments are contemplated.

What is claimed is:

1. A method, comprising:

using a portable communication device with a camera and a display unit therein, to obtain an image of a bar code, wherein the bar code is a dual type bar code comprising a first part of a first barcode format and a second part of a second barcode format, wherein the second and first formats are different, and where said first part and said second part are sufficiently close together that they are imaged by a single imaging device at one time;

decoding, by the portable communications device, the first part and second part to obtain corresponding first and second information, wherein said second information comprises more information than the first information;

addressing a remote server, by the portable communications device, using information from said decoding as an address to access said remote server;

receiving information from said remote server, in said portable communication device, based on using said address;

receiving and displaying, on said display unit of said portable communication device, said obtained information, wherein said obtained information comprises additional information from that included in said barcode and wherein said obtained information is based on a meaning that was represented by said barcode;

using said portable communication device to make a telephone call;

and wherein said obtaining of said image comprises capturing a single image of the dual type barcode, said single image comprising both said first and second part, and processing said image via a processor of the portable communication device to obtain the information from said first and second part.

8

2. A method as in claim 1, further comprising:

using said portable communication device to make a telephone call at a different time than said using to obtain an image; and

at a different time than said telephone call or said using to obtain an image, using said camera to obtain a video.

3. A method as in claim 1, wherein said first part is a linear bar code and said second part is a non-linear bar code.

4. A method as in claim 1, wherein said first process is a scan in a first linear direction and said second process is a scan in a second linear direction different than the first linear direction.

5. A method as in claim 1, wherein said second part is one of grayscale or color of the bar code, where said color of the barcode includes colors other than black and white.

6. A method as in claim 1, wherein said barcode is part of an advertisement, and said information obtained from said remote server represents more information about the advertisement.

7. A method as in claim 2, wherein said using comprises using the portable communication device to scan an advertisement, and wherein said information that is received from the remote server represents more information about the advertisement.

8. A method as in claim 2, wherein content of the barcode is a pointer to a remote database, and said content is decoded to determine information indicative of said pointer, and said meaning is received from said remote database based on said pointer.

9. A method as in claim 1, wherein one of said parts is in a grayscale of the bar code.

10. A method, comprising:

using a portable communication device with a camera and a display unit therein, to obtain an image of a bar code, which has two different bar code parts, including a first barcode part in a first format, and a second barcode part in a second format different than the first format, wherein the second and first formats are different, and where said first part and said second part are sufficiently close together that they are imaged by a single imaging device at one time;

decoding, by the portable communications device, the first part and second part to obtain corresponding first and second information, wherein said second information comprises more information than the first information; addressing a remote server, by the portable communications device, using information from said decoding as an address to access said remote server;

receiving information from said remote server, in said portable communication device, based on using said address;

receiving and displaying, on said display unit of said portable communication device, said information from said remote server; and

at a different time, using said portable communication device to make a telephone call.

11. A method as in claim 10, wherein said first part is a linear bar code and said second part is a non-linear bar code.

12. A method as in claim 10, wherein said first format bar code is intended to be scanned in a first linear direction and said second format bar code is intended to be scanned in a second linear direction different than the first linear direction.

* * * * *