



US008028975B2

(12) **United States Patent**
Tertel et al.

(10) **Patent No.:** **US 8,028,975 B2**
(45) **Date of Patent:** **Oct. 4, 2011**

(54) **SEPARATION VESSEL OR PART THEREOF,
AND PROCESS RELATING THERETO**

(75) Inventors: **Jonathan Andrew Tertel**, Mt. Prospect,
IL (US); **July S. Maglente**, Prairie
Grove, IL (US); **David Alden Bahr**,
Chicago, IL (US)

(73) Assignee: **UOP LLC**, Des Plaines, IL (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 519 days.

(21) Appl. No.: **12/270,909**

(22) Filed: **Nov. 14, 2008**

(65) **Prior Publication Data**

US 2010/0122936 A1 May 20, 2010

(51) **Int. Cl.**
C10G 21/10 (2006.01)

(52) **U.S. Cl.** **261/75**; 261/76; 261/78.1; 261/115;
261/116; 261/117; 210/188; 210/322; 210/513;
210/519; 208/226; 208/227; 208/228

(58) **Field of Classification Search** 208/226–228;
261/75–76, 78.1, 115–118; 210/188, 322,
210/513, 519

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,562,300 A 12/1985 LaFoy
4,853,006 A * 8/1989 Mangnall 96/200
5,039,398 A 8/1991 Stine et al.

5,135,616 A * 8/1992 Nicholson et al. 196/46
5,237,823 A 8/1993 Cheung et al.
5,470,441 A 11/1995 Brown
6,565,740 B2 5/2003 Sain et al.
6,749,741 B1 6/2004 Laricchia et al.
6,960,291 B2 11/2005 Greaney et al.
7,014,751 B2 3/2006 Greaney et al.
7,326,333 B2 2/2008 Laricchia et al.
7,381,309 B1 6/2008 Laricchia et al.
2003/0136263 A1 7/2003 Beuke et al.
2004/0175307 A1* 9/2004 Laricchia et al. 422/189

FOREIGN PATENT DOCUMENTS

EP 0 271 823 A1 6/1988
GB 1 240 727 7/1971
WO WO-2005/121279 A1 12/2005

OTHER PUBLICATIONS

Akhmadullina et al., Heterogeneous-Catalytic Demercaptanization
of a Light Petroleum Feedstock, East View Publications, 1993, No. 3,
pp. 6-7.

(Continued)


Primary Examiner — Walter Griffin
Assistant Examiner — Brian McCaig

(74) *Attorney, Agent, or Firm* — James C Paschall

(57) **ABSTRACT**

One exemplary embodiment can be a stack for a separation
vessel adapted to receive a fluid having one or more phases.
The stack may include one or more walls surrounding a void,
a packed bed positioned within the void, and a distributor
positioned above the packed bed. Generally, the stack has a
height greater than its width. Usually, the separation vessel
further includes a base having a length greater than its height,
and the height of the stack is orientated substantially perpen-
dicular to the length of the base.

12 Claims, 2 Drawing Sheets



OTHER PUBLICATIONS

Abstract of Akhmadullina et al., Heterogeneous-Catalytic Demercaptanization of a Light Petroleum Feedstock, East View Publications, 1993, No. 3, pp. 6-7.

Ali et al., Desulphurisation of a Gasoline Fraction from Partially Cracked Naphtha, Fuel Science and Technology International, 1988, vol. 6, No. 4, pp. 397-414.

Basu et al., Merox and Related Metal Phthalocyanine Catalyzed Oxidation Processes, Catalysis Reviews—Science & Engineering, Dec. 1993, vol. 35, No. 4, pp. 571-609.

Mazgarov et al., Combined Scheme for Demercaptization of Light Fractions from Crude Oils and Gas Condensates of the Caspian

Depression, Chemistry and Technology of Fuels and Oils, Nov. 1987, vol. 23, Nos. 11-12, pp. 524-527.

Mazgarov et al., Removing Mercaptans and Hydrogen Sulfide from Oil Products, Chemical and Petroleum Engineering, Nov. 2003, vol. 39, No. 11-12, pp. 719-721.

Zhou et al., Discussion on the Improvement of LPG Sweetening Process for Energy Saving and Pollution Reduction, Petroleum Processing and Petrochemicals, 2008, vol. 39(3), pp. 51-57.

Abstract of Zhou et al., Discussion on the Improvement of LPG Sweetening Process for Energy Saving and Pollution Reduction, Petroleum Processing and Petrochemicals, 2008, vol. 39(3), pp. 51-57.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3

1

SEPARATION VESSEL OR PART THEREOF, AND PROCESS RELATING THERETO

FIELD OF THE INVENTION

This invention generally relates to a separation vessel receiving a fluid.

DESCRIPTION OF THE RELATED ART

Often, hydrocarbon and gas streams are treated to remove sulfur-containing compounds, such as mercaptans. Generally, such compounds are removed because of their malodorous scent.

Mercaptans can be designated R—S—H where R is often a light hydrocarbon radical such as methyl or ethyl. Typically, mercaptans concentrate in hydrocarbon liquid streams separated in a process facility. Many processes can be used to remove mercaptans and other sulfur-containing compounds. Often, such processes can use a caustic stream contacting the hydrocarbon stream in an extractive system.

After use, the caustic stream may be regenerated. As such, air may be used for oxidizing mercaptans to disulfide oils. The unreacted components of the air stream, e.g. nitrogen, oxygen, and other inert gases, are separated from the caustic and disulfide oils. Often, a separation vessel allows the unreacted air components to exit in a vent gas stream. Generally, the vent gas stream contains primarily air and small amounts of water, hydrocarbons, and disulfide oils. Typically, this air stream can contain up to about one mole percent disulfide. However, the presence of disulfide oils can create regulatory concerns. Due to these concerns, it is often desired to treat the vent gas to remove the disulfide oils.

Often units are built under past regulatory codes and do not have equipment readily adapted to facilitate this removal. As a consequence, it would be desired to provide devices that could be incorporated into existing apparatuses to facilitate the removal of the disulfide oils in an economic and efficient manner.

SUMMARY OF THE INVENTION

One exemplary embodiment can be a stack for a separation vessel adapted to receive a fluid having one or more phases. The stack may include one or more walls surrounding a void, a packed bed positioned within the void, and a distributor positioned above the packed bed. Generally, the stack has a height greater than its width. Usually, the separation vessel further includes a base having a length greater than its height, and the height of the stack is orientated substantially perpendicular to the length of the base.

Another exemplary embodiment may be a separation vessel. The separation vessel can have a base defining an interior space at least for separating one liquid phase from another liquid phase. The base can include a coalescer positioned in the interior space. The separation vessel can further have a stack adapted to receive a fluid having one or more phases and coupled to the base. Moreover, the stack defines a void and further comprises one or more walls surrounding the void, a packed bed positioned within the void, and a distributor positioned above the packed bed.

A further exemplary embodiment can be a process for removing one or more sulfur-containing hydrocarbons from a gas. The process may include producing an effluent including a caustic, one or more hydrocarbons, one or more sulfur compounds, and a gas from an oxidation vessel; and sending the effluent to a stack of a disulfide separator. Typically, the

2

stack includes one or more walls surrounding a void and adapted to receive a fluid including one or more phases, a packed bed positioned within the void, and a distributor including one or more risers and one or more compartments coupled to a substantially horizontal member forming a plurality of apertures there-through.

As disclosed herein, the embodiments can provide an efficient and effective modification to an existing vessel to allow the removal of sulfur-containing compounds from a waste gas stream. Alternatively, the features as disclosed herein can be included in a new vessel. As a consequence, the device disclosed herein can facilitate the removal of these compounds and allow an apparatus to meet regulatory requirements. Thus, these embodiments can minimize upgrade costs to an existing apparatus or vessel in an efficient and effective manner.

DEFINITIONS

As used herein, hydrocarbon molecules may be abbreviated C1, C2, C3 . . . Cn where “n” represents the number of carbon atoms in the one or more hydrocarbon molecules.

As used herein, the term “rich” can mean an amount of generally at least about 50%, and preferably about 70%, by mole, of a compound or class of compounds in a stream.

As used herein, the term “substantially” can mean an amount of generally at least about 80%, preferably about 90%, and optimally about 99%, by mole, of a compound or class of compounds in a stream.

As used herein, the term “zone” can refer to an area including one or more equipment items and/or one or more sub-zones. Equipment items can include one or more reactors or reactor vessels, heaters, exchangers, pipes, pumps, compressors, and controllers. Additionally, an equipment item, such as a reactor, an adsorber, or a vessel, can further include one or more zones or sub-zones.

As used herein, the term “coupled” can mean two items, directly or indirectly, joined, fastened, associated, connected, or formed integrally together either by chemical or mechanical means, by processes including stamping, molding, or welding. What is more, two items can be coupled by the use of a third component such as a mechanical fastener, e.g., a screw, a nail, a bolt, a staple, or a rivet; an adhesive; or a solder.

As described herein, the term “coalescer” is a device containing glass fibers or other material to facilitate separation of immiscible liquids of similar density.

As used herein, the term “immiscible” means two or more phases that cannot be uniformly mixed or blended.

As used herein, the term “phase” means a liquid, a gas, or a suspension including a liquid and/or a gas, such as a foam, aerosol, or fog. A phase may include solid particles. Generally, a fluid can include one or more gas, liquid, and/or suspension phases.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic depiction of an exemplary apparatus.

FIG. 2 is a top plan view of an exemplary distributor.

FIG. 3 is an elevational, cross-sectional view of the exemplary distributor along line 3-3 of FIG. 2.

DETAILED DESCRIPTION

Referring to FIG. 1, an exemplary apparatus 100 for removing one or more sulfur-containing compounds, such as mercaptans, from a hydrocarbon stream 20 is depicted in FIG.

1. Typically, the apparatus **100** can include an extractor vessel **120**, an oxidation vessel **160**, and a separation vessel **200**. The vessels, lines and other equipment of the apparatus **100** can be made from any suitable material, such as carbon steel, stainless steel, or titanium. As depicted, process flow lines in the

figures can be referred to as lines, pipes or streams. Particularly, a line or a pipe can contain one or more streams, and one or more streams can be contained by a line or a pipe. The hydrocarbon stream **20** is typically in a liquid phase and can include a liquefied petroleum gas or a naphtha hydrocarbon. Typically, the hydrocarbon stream **20** contains sulfur compounds in the form of one or more mercaptans and/or hydrogen sulfide. Generally, the apparatus **100** can also include a caustic prewash vessel. Exemplary apparatuses having at least a caustic prewash vessel, an extractor vessel, an oxidation vessel, and a separation vessel for removing sulfur-containing compounds from a hydrocarbon stream are disclosed in, for example, U.S. Pat. No. 7,326,333.

A hydrocarbon stream **20** can be an effluent from, for example, a caustic prewash vessel. The hydrocarbon stream **20** can include hydrogen sulfide and C2-C8 hydrocarbons. Usually, the hydrocarbon stream **20** can include up to about 100 ppm, by weight, hydrogen sulfide. Generally, the hydrocarbon stream **20** is combined with a stream **26** including water from a stream **30** and a combined caustic stream **28**, as hereinafter described, for removing, e.g., hydrogen sulfide. The caustic can be any alkaline material, and generally includes caustic soda (NaOH) and caustic alcohol (C₂H₃ONa). The streams **20** and **26** are combined as an extractor feed **50**. The feed **50** can enter the extractor vessel **120**. The extractor vessel **120** can include a lower pre-wash section **130**, and an upper extractor section **150**. The extractor feed **50** can enter the lower prewash section **130**. A predominately hydrocarbon phase can rise while the caustic can fall in the prewash section **130**. The caustic can be withdrawn via a caustic withdrawal **134** with a portion being spent caustic **138** and another portion being a caustic recycle **136**. A transfer conduit **140** can transfer the hydrocarbon phase into the upper extractor section **150**.

The hydrocarbon product **154** mostly free of mercaptans and mercaptides can be withdrawn from the top of the upper extractor section **150** while a spent caustic including mercaptides can be withdrawn via a line **156**. The spent caustic **156** can be combined with an oxidation catalyst **158** and an air stream **162**. The oxidation catalyst **158** can be any suitable oxidation catalyst, such as a sulfonated metal phthalocyanine. However, any suitable oxidation catalyst can be used such as those described in, for example, U.S. Pat. No. 7,326,333. The oxidation catalyst **158**, the air stream **162**, and the spent caustic **156** can be combined in a line **164** before entering the oxidation vessel **160**. The spent aqueous caustic and air mixture is distributed in the oxidation vessel **160**. In the oxidation vessel **160**, the sodium mercaptans catalytically react with oxygen and water to yield caustic and organic disulfides. Optionally, the oxidation vessel **160** can include packing, such as carbon rings, to increase the surface area for improving contact between the spent caustic and catalyst. Afterwards, an effluent **180** from the oxidation vessel **160** can be withdrawn from the top of the vessel **160**. The effluent **180** can include caustic, one or more hydrocarbons, one or more sulfur compounds, and a gas. Typically, the effluent **180** can include a gas phase, a liquid disulfide phase, and a liquid aqueous caustic phase. Generally, the gas phase includes air with at least some oxygen depletion. In the gas phase, the oxygen content can be about 5-about 21%, by mole.

The effluent **180** can be received in the separation vessel **200**. The separation vessel **200** can be any suitable process

equipment, such as a disulfide separator. The separation vessel **200** can include a stack **230** and a base **300**. The separation vessel **200** can be operated at any suitable conditions, such as no more than about 60° C. and about 250-about 500 kPa, preferably about 350-about 450 kPa.

The stack **230** can be any suitable dimension for receiving the three-phase effluent **180**. Typically, the stack **230** can have a height **234** and a width **244**. Generally, the stack **230** is substantially cylindrical in shape having one or more walls **240** forming a void **242**. Generally, the height **234** can be greater than the width **244**.

In addition, the base **300** can have any suitable dimensions. Typically, the base **300** has a length **302** and a height **310** creating an interior space **304**. Generally, the base **300** has a top **306** and a bottom **308**. Usually, the length **302** is greater than the height **310**. Typically, the stack **230** is coupled to the base **300** at any suitable angle. Preferably, the stack **230** is connected at an end **238** at a substantially perpendicular orientation **236** with respect to the length **302** of the base **300**.

The stack **230** can contain a first distributor **250**, a packed bed **254**, a second distributor **260**, a third distributor **280**, and a demister **290**. Generally, the first distributor **250** and the third distributor **280** can be any suitable distributor, such as respectively, a pipe with same or different sized slots for distributing the effluent **180** in the stack **230**. The distributor **260** can be placed above the packed bed **254** and can be any suitable distributor, such as an elongated pipe with one or more slots, or a distributor as disclosed in, for example, U.S. Pat. No. 5,237,823 or U.S. Pat. No. 5,470,441. Generally, the liquid phases fall downward toward the base **300** and the gas phase rises upward in the stack **230**. Usually, the packed bed **254** can include packing elements **258** that increase the surface area of the fluids interacting, as further described herein.

The packing elements **258** can be any suitable packing. One exemplary packing is ring packing, such as RASCHIG packing material sold by Raschig GmbH LLC of Ludwigshafen, Germany. Other types of packing can include structured packing, fiber and/or film contactors, or tray systems, e.g. one or more trays, as long as suitable contact is attained. Typically, the ring packing can be any suitable dimension, but is typically about 1 cm-about 5 cm in diameter. The packing elements **258** can be made from any suitable material, including carbon steel, stainless steel, or carbon.

Referring to FIGS. 1-3, the distributor **260** can include one or more risers **264**, one or more drip guards **266** positioned above the risers **264**, a substantially horizontal member **268**, and one or more compartments **274**. Typically, the substantially horizontal member **268** forms a plurality of apertures **272**, which can have any suitable shape and be the same or different sizes. The one or more risers **264** can be positioned around at least some of the apertures **272** to allow gases to rise upward through the substantially horizontal member **268**. The one or more compartments **274** generally have one or more holes in the side of the compartments to allow built-up fluid on the substantially horizontal member **268** to pass there-through to the packed bed **254** below. Typically, a base **276** of a compartment **274** can be coupled to the substantially horizontal member **268** with any suitable means, such as welding. In some exemplary embodiments, the periphery of one or more risers can at least partially define one or more compartments. Distributors **260** and **280** can also be combined to provide a single wash oil distributor.

The distributor **280** can be any suitable distributor providing a hydrocarbon stream **278** having a boiling point of about 50-about 300° C. Typically, the hydrocarbon stream **278** can be a wash oil that includes hydrotreated heavy naphtha or kerosene with little or no sulfur. The hydrocarbon stream **278**

5

may also be a diesel oil. Generally, it is preferable that the hydrocarbon stream **278** has less than about 10 ppm, preferably less than about 1 ppm, by weight, of sulfur.

The demister **290** can be any suitable demister for removing liquid particles from a rising gas. Generally, the demister **290** can be a mesh or vane demister, preferably a mesh demister. During washing of the gas phase in the separation vessel **200**, the third distributor **280** can provide the wash oil to the stack via a line **278**. Optionally, the hydrocarbon stream **278**, such as a wash oil, can be cooled to a temperature of about 38-about 43° C. to reduce or prevent corrosion in equipment and piping in gas service, e.g., the stack **230** and a line **294**. The wash oil can then fall downward to the second distributor **260**. The wash oil can collect on the substantially horizontal member **268** before passing through the one or more compartments **274** to the packed bed **254** below. The gas passing upward from the first distributor **250** can pass upward through the packed bed **254** with mass transfer occurring between the gas and the wash oil in the packed bed **254**. The organic disulfide compounds can be stripped from the gas and collect in the wash oil which can drop from the stack **230** to the base **300** below. The gas can rise upward and pass through the one or more risers **264**. The one or more drip guards **266** can prevent the wash oil from entering the one or more risers **264**. Subsequently, the gas then passes through the demister **290** where any entrained liquid is removed. Afterwards, the gas can pass upwards through the stack and exit via the line **294**. Generally, the total sulfur in the air exiting the stack **230** can be about 100 ppm, by weight. As such, the gas can be sent or optionally blended with fuel gas for use as a fuel in a heater or furnace.

The wash oil, liquid disulfide, and aqueous caustic phases can enter the base **300**. The base **300** can include a coalescer **312**. Generally, the coalescer **312** can include a support **314** and one or more coalescer elements **318**, which can include at least one of a metal mesh, one or more glass fibers, sand, or an anthracite coal. The various liquid phases can pass through the coalescer **312** and be separated. Generally, the wash oil and the disulfide phase can exit via a line **322** to enter a filter **330**, such as a sand filter. The filter **330** can remove any traces of caustic before passing an effluent **332**.

Generally, the caustic can exit the bottom **308** of the base **300** through a line **326** and be split into separate branches **142** and **152**. The regenerated caustic in the line **142** can be combined with caustic **136** to be combined with hydrocarbon stream **20**. Another branch **152** can be provided to the upper extractor section **150** of the extractor vessel **120**, as described above.

Without further elaboration, it is believed that one skilled in the art can, using the preceding description, utilize the present invention to its fullest extent. The preceding preferred specific embodiments are, therefore, to be construed as merely illustrative, and not limitative of the remainder of the disclosure in any way whatsoever.

In the foregoing, all temperatures are set forth in degrees Celsius and, all parts and percentages are by weight, unless otherwise indicated.

From the foregoing description, one skilled in the art can easily ascertain the essential characteristics of this invention

6

and, without departing from the spirit and scope thereof, can make various changes and modifications of the invention to adapt it to various usages and conditions.

The invention claimed is:

1. A stack for a separation vessel adapted to receive a fluid comprising one or more phases, comprising:

- A) one or more walls surrounding a void;
- B) a packed bed positioned within the void; and
- C) a distributor positioned above the packed bed;

wherein the stack has a height greater than its width and the separation vessel further comprises a base having a length greater than its height, and the height of the stack is orientated substantially perpendicular to the length of the base and the stack is coupled to the separation vessel.

2. The stack according to claim 1, wherein the one or more walls form a substantially cylindrical shape.

3. The stack according to claim 1, wherein the distributor comprises one or more risers coupled to a substantially horizontal member forming a plurality of apertures there-through.

4. The stack according to claim 1, wherein the stack is adapted to receive a fluid for separating at least one phase.

5. The stack according to claim 1, further comprising a demister positioned above the distributor.

6. A separation vessel, comprising:

- A) a base defining an interior space at least for separating one liquid phase from another liquid phase; comprising:
 - 1) a coalescer positioned in the interior space; and
- B) a stack adapted to receive a fluid comprising one or more phases and coupled to the base; wherein the stack defines a void and comprises:

- 1) one or more walls surrounding the void;
- 2) a packed bed positioned within the void; and
- 3) a distributor positioned above the packed bed.

7. The separation vessel according to claim 6, wherein the coalescer further comprises:

a support at least partially surrounding one or more coalescing elements, in turn, comprising at least one of a metal mesh, one or more glass fibers, sand, and anthracite coal.

8. The separation vessel according to claim 6, wherein the packed bed comprises one or more packing elements, in turn, comprising at least one of a ring packing, a fiber contactor, a film contactor, and one or more trays.

9. The separation vessel according to claim 6, further comprising a demister positioned above the distributor in the stack.

10. The separation vessel according to claim 6, wherein the separation vessel is a disulfide separator.

11. The separation vessel according to claim 6, wherein the distributor comprises one or more risers and one or more compartments coupled to a substantially horizontal member forming a plurality of apertures there-through.

12. The separation vessel according to claim 11, wherein the one or more risers allow the upward flow of one or more gases, and one aperture of the plurality of apertures is formed proximate at a base of a corresponding compartment allowing one or more liquids to pass there-through.

* * * * *