

US008045905B2

(12) **United States Patent**
Hara

(10) **Patent No.:** **US 8,045,905 B2**
(45) **Date of Patent:** ***Oct. 25, 2011**

(54) **BELT TRANSFER DEVICE FOR IMAGE FORMING APPARATUS**

(56) **References Cited**

(75) Inventor: **Kazuhiro Hara**, Shizuoka (JP)

(73) Assignees: **Kabushiki Kaisha Toshiba**, Tokyo (JP);
Toshiba Tec Kabushiki Kaisha, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **12/963,591**

(22) Filed: **Dec. 8, 2010**

(65) **Prior Publication Data**

US 2011/0076065 A1 Mar. 31, 2011

Related U.S. Application Data

(63) Continuation of application No. 12/326,524, filed on Dec. 2, 2008, now Pat. No. 7,873,311.

(60) Provisional application No. 60/992,694, filed on Dec. 5, 2007.

(51) **Int. Cl.**
G03G 15/00 (2006.01)
G03G 15/16 (2006.01)

(52) **U.S. Cl.** **399/302; 399/165; 399/303**

(58) **Field of Classification Search** **399/302, 399/303, 308, 313, 162, 165; 198/804, 810.01, 198/810.03**

See application file for complete search history.

U.S. PATENT DOCUMENTS

5,784,676	A	7/1998	Iseki et al.
6,181,900	B1	1/2001	Lee et al.
6,871,038	B2	3/2005	Fujiwara
7,389,068	B2	6/2008	Ito
2002/0085864	A1	7/2002	Abe
2007/0059059	A1	3/2007	Fujino
2007/0147894	A1	6/2007	Yokota
2008/0260424	A1	10/2008	Hara et al.

FOREIGN PATENT DOCUMENTS

CN	1598705	A	3/2005
JP	04-133931		5/1992
JP	2000-130523	A	5/2000
JP	2003-201038		7/2003
JP	2007-041530		2/2007
JP	2007-139997		6/2007
JP	2008-268954		11/2008

OTHER PUBLICATIONS

Official Letter dated Dec. 15, 2010, from China Patent Office for corresponding Chinese Patent Application No. 200810182956.2.

Primary Examiner — Sophia S Chen

(74) *Attorney, Agent, or Firm* — Patterson & Sheridan, LLP

(57) **ABSTRACT**

In a belt transfer device according to an embodiment, rotation of a rear side detection roller or a front side detection roller, which contacts with a rib of a transfer belt and is rotated, is converted into linear driving by using a worm gear. The movement of a linear movement shaft is transmitted to a steering roller through a slider. The steering roller is tilted and meandering of the transfer belt is regulated.

13 Claims, 12 Drawing Sheets




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20





FIG. 21



1

BELT TRANSFER DEVICE FOR IMAGE FORMING APPARATUS**CROSS REFERENCE TO RELATED APPLICATION**

This application is a continuation of U.S. patent application Ser. No. 12/326,524, filed Dec. 2, 2008, which is based upon and claims the benefit of priority from Provisional U.S. Patent Application No. 60/992,694 filed on Dec. 5, 2007, the entire contents of which are incorporated herein by reference.

TECHNICAL FIELD

The present invention relates to an endless belt installed in an image forming apparatus, and particularly to a belt transfer device for an image forming apparatus, which regulates meandering of an endless belt at the time of traveling.

BACKGROUND

In an image forming apparatus such as a tandem type multi function peripheral (MFP) or a printer, toner images of plural colors are sequentially superimposed and transferred on a transfer belt or on a sheet transferred by a transfer belt, and a color toner image is formed. And an image forming apparatus a tandem type MFP or a printer, toner images of plural colors are sequentially superimposed and transferred on a transfer belt, and a color toner image is formed. In this tandem type, when the transfer belt meanders, the image quality of the color toner image is remarkably deteriorated by color shift. Thus, hitherto, there are units for correcting the meandering of the transfer belt. As one of such units, for example, Japanese Patent No. 2868879 discloses a belt drive unit in which a steering roller to change the traveling direction of a transfer belt is tilted by using a balance between the elastic force of a spring and the rotation forces of guide rollers at both sides of the steering roller.

However, in the unit of the related art, since the elastic force of the spring is used for the movement of the steering roller, the high-speed property and reliability are insufficient. Thus, it is not appropriate to install the unit in a high-performance and high-speed MFP or the like in which high image quality is required.

Then, the development of a belt transfer device for an image forming apparatus is desired in which when the transfer belt meanders, the transfer belt is returned to a normal direction at high speed, and by this, a high quality color image without color shift can be obtained.

SUMMARY

According to an aspect of the invention, the traveling direction of the transfer belt is corrected to a normal direction to the distortion and color shift of a toner image on the transfer belt are prevented and a high quality toner image is obtained without fail, by transmit meandering of a transfer belt to a steering roller at high speed and accurately.

According to an embodiment of the invention, a belt transfer device includes a belt member that supports an image and is rotated and traveled, a first detection roller that contacts with a first end of the belt member in a width direction and is rotated, a second detection roller that contacts with a second end of the belt member opposite to the first end and is rotated, a conversion member that converts rotation of the first detection roller or the second detection roller into linear driving, a transmission member driven by the linear driving of the con-

2

version member and a steering member that changes a direction of a rotation traveling of the belt member by an operation of the transmission member.

DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic structural view showing a main part of a printer section according to a first embodiment of the invention;

FIG. 2 is a schematic perspective view showing a transfer belt unit according to the first embodiment of the invention;

FIG. 3 is a schematic perspective view showing a state where a transfer belt of the transfer belt unit is removed according to the first embodiment of the invention;

FIG. 4 is a schematic perspective view showing a self steering mechanism according to the first embodiment of the invention;

FIG. 5 is a schematic side view showing the self steering mechanism according to the first embodiment of the invention;

FIG. 6 is a schematic plan view showing the self steering mechanism according to the first embodiment of the invention;

FIG. 7 is a schematic explanatory view showing the self steering mechanism when the transfer belt deviates to a front side according to the first embodiment of the invention;

FIG. 8 is a schematic explanatory view showing the self steering mechanism when the transfer belt deviates to a rear side according to the first embodiment of the invention;

FIG. 9 is a schematic explanatory view showing a rear side compression spring or a front side compression spring according to the first embodiment of the invention;

FIG. 10 is a schematic perspective view showing a state where a front side belt pressing member presses the transfer belt according to the first embodiment of the invention;

FIG. 11 is a schematic explanatory view showing an attachment state of the front side belt pressing member according to the first embodiment of the invention;

FIG. 12 is a schematic perspective view showing a state where an urethane foam plate is nipped between a support plate and a steering support body according to the first embodiment of the invention;

FIG. 13 is a schematic explanatory view showing an indicator according to the first embodiment of the invention;

FIG. 14 is a graph showing a relation between a tilt angle of a steering roller and a twist angle of the transfer belt according to the first embodiment of the invention;

FIG. 15 is a schematic explanatory view showing a tensioner according to the first embodiment of the invention;

FIG. 16 is a schematic explanatory view showing a movement amount of a rear side detection roller or a front side detection roller when rotation of a support plate is small according to the first embodiment of the invention;

FIG. 17 is a schematic explanatory view showing the movement amount of the rear side detection roller or the front side detection roller when the rotation of the support plate is large according to the first embodiment of the invention;

FIG. 18 is a schematic explanatory view showing rotation of the rear side detection roller by a rear side rib according to the first embodiment of the invention;

FIG. 19 is a schematic explanatory view showing a state where the rear side rib is separated from the rear side detection roller by movement of a linear movement shaft according to the first embodiment of the invention;

FIG. 20 is a schematic explanatory view showing a self steering mechanism when a transfer belt deviates to a rear side according to a second embodiment of the invention; and

FIG. 21 is a schematic explanatory view showing the self steering mechanism when the transfer belt deviates to a front side according to the second embodiment of the invention.

DETAILED DESCRIPTION

Hereinafter, a first embodiment of the invention will be described in detail with reference to the accompanying drawings. FIG. 1 is a schematic structural view showing a main part of a printer section 2 of a four tandem type color image forming apparatus in which a transfer belt unit 1 of the first embodiment of the invention is installed. In the printer section 2, image formation stations 11K, 11Y, 11M and 11C of respective colors of black (K), yellow (Y), magenta (M) and cyan (C) are arranged in tandem along the lower side of a transfer belt 10 as a belt member rotated in an arrow s direction. The printer section 2 includes a laser exposure device 17. The laser exposure device 17 irradiates laser beams corresponding to image information to photoconductive drums 12K, 12Y, 12M and 12C of the image formation stations 11K, 11Y, 11M and 11C of the respective colors.

The image formation station 11K of black (K) of the printer section 2 includes a charger 13K, a developing device 14K, a transfer roller 18K and a cleaner 16K, which are arranged around the photoconductive drum 12K that rotates in a direction indicated by arrow m. Each of the image formation stations 11Y, 11M and 11C of the respective colors of yellow (Y), magenta (M) and cyan (C) has the same structure as the image formation station 11K of black (K). Each of transfer rollers 18Y, 18M and 18C are positioned opposite each of the image formation stations 11Y, 11M and 11C.

A rib 10a is formed on an inner periphery at a rear side end as a first end of the transfer belt 10 of the transfer belt unit 1 in the width direction. A rib 10b is formed on the inner periphery at a front side end as a second end of the transfer belt 10. The ribs 10a and 10b are made of, for example, thin line-shaped rubber. As shown in FIG. 2 and FIG. 3, the transfer belt 10 is stretched by a drive roller 20, a driven roller 21 and first to third tension rollers 22 to 24. Further, the transfer belt 10 is stretched by a steering roller 28a of a self steering mechanism 28. A rear side detection roller 37a and a front side detection roller 37b of a self steering mechanism 28 are pressed to the transfer belt 10 without excessively applying tension to the transfer belt 10.

At a secondary transfer position where the transfer belt 10 is supported by the driven roller 21, a secondary transfer roller 30 is disposed to be opposite thereto. A transfer bias is supplied to the secondary transfer roller 30. At the secondary transfer position, a toner image on the transfer belt 10 is secondarily transferred to a sheet paper P or the like by the secondary transfer roller 30. Incidentally, the structure of the transfer belt unit 1 is not limited to this.

In the printer section 2, by a print operation start, the photoconductive drum 12K is rotated in the arrow m direction in the image formation station 11K of black (K). The photoconductive drum 12K is uniformly charged by the charger 13K as it rotates and is irradiated with an exposure light corresponding to image information by the laser exposure device 17, and an electrostatic latent image is formed. Thereafter, a toner image is formed on the photoconductive drum 12K by the developing device 14K. Further, the toner image on the photoconductive drum 12K is primarily transferred onto the transfer belt 10 rotating in the arrow s direction at the position of the transfer roller 18K. After the end of the primary transfer, residual toner on the photoconductive drum 12K is cleaned by the cleaner 16K, and next printing becomes possible.

Each of the image formation stations 11Y, 11M and 11C of the respective colors of yellow (Y), magenta (M) and cyan (C) performs the image formation operation similarly to the image formation station 11K of black (K). The respective toner images of yellow (Y), magenta (M) and cyan (C) formed by the image formation stations 11Y, 11M and 11C of the respective colors of yellow (Y), magenta (M) and cyan (C) are sequentially primarily transferred to the transfer belt 10. By this, a full color toner image made of multi-transferred toner images of black (K), yellow (Y), magenta (M) and cyan (C) is formed on the transfer belt 10.

The full color toner image superimposed on the transfer belt 10 reaches the secondary transfer position thereafter. The full color toner image is secondarily transferred onto the sheet paper P by the secondary transfer roller 30 at the secondary transfer position at once. The sheet paper P is fed to the secondary transfer position in synchronization with the arrival of the full color toner image on the transfer belt 10 at the secondary transfer position. Thereafter, the full color toner image transferred to the sheet paper P is fixed, the print image is completed, and the paper is ejected to a paper eject section.

Next, the self steering mechanism 28 will be described in detail. As shown in FIG. 4, FIG. 5 and FIG. 6, a support plate 36 as a support member supports a detection section 36a, a steering section 36b and a link section 36c as a transmission member. The detection section 36a includes the rear side detection roller 37a as a first detection roller to detect the meandering of the transfer belt 10, and the front side detection roller 37b as a second detection roller. The steering section 36b includes the steering roller 28a. The link section 36c transmits the rotation of the rear side detection roller 37a or the front side detection roller 37b to the steering roller 28a.

The support plate 36 rotates with respect to the main body of the printer section 2 while a fulcrum 47 is a rotation fulcrum. A spring 47a to push up the support plate is provided at the bottom of the support plate 36. The spring 47a pushes up the support plate 36, so that the steering roller 28a gives tension to the transfer belt 10. In this embodiment, although the support plate 36 is rotated and moved, the support plate 36 may be moved in parallel by a gondola type drive mechanism. The support plate 36 is moved in parallel and is pushed up, and the steering roller 28a, the rear side detection roller 37a and the front side detection roller 37b may be integrally pushed up to the transfer belt 10.

In the detection section 36a, the rear side detection roller 37a or the front side detection roller 37b is supported by a rear side support lever 77a or a front side support lever 77b as a first lever constituting the tensioner 74 as a tension member. One end of the rear side support lever 77a or the front side support lever 77b is fixed to a rear side lever fulcrum 53a or a front side lever fulcrum 53b. The rear side lever fulcrum 53a or the front side lever fulcrum 53b is coaxial to a linear movement shaft 52 as a shaft to coaxially support a worm 51 of a worm gear 50 as a conversion member, and is rotatably provided with respect to the linear movement shaft 52. The rear side lever fulcrum 53a or the front side lever fulcrum 53b is fixed to the support plate 36.

The rear side detection roller 37a or the front side detection roller 37b is rotatably supported by the rear side support lever 77a or the front side support lever 77b. When the transfer belt 10 is held at the normal position, the rear side detection roller 37a and the front side detection roller 37b are separated from the ribs 10a and 10b of the transfer belt 10. As shown in FIG. 7, when the transfer belt 10 meanders to the front, the rear side detection roller 37a contacts with the inside of the rear side rib 10a. By the contact with the rear side rib 10a, the rear side

5

detection roller **37a** is rotated in an arrow **r1** direction. As shown in FIG. 8, when the transfer belt **10** meanders to the rear, the front side detection roller **37b** contacts with the inside of the front side rib **10b**. By the contact with the front side rib **10b**, the front side detection roller **37b** is rotated in an arrow **r5** direction.

As shown in FIG. 9, the rear side detection roller **37a** is urged toward the rib **10a** at the rear side end of the transfer belt **10** by the rear side compression spring **46a** as the first urging member. The rear side compression spring **46a** is supported by a rear side wheel **45a** attached to a rear side shaft **43a**. Similarly, the front side detection roller **37b** is urged toward the rib **10b** at the front side end of the transfer belt **10** by a front side compression spring **46b** as the second urging member. The front side compression spring **46b** is supported by a front side wheel **45b** attached to a front side shaft **43b**. Both the rear side compression spring **46a** and the front side compression spring **46b** have high elastic force. While the transfer belt unit **1** is being driven in the normal range, the rear side compression spring **46a** and the front side compression spring **46b** are not compressed by the deviation of the transfer belt **10**. For example, at the time of abnormality when the color image forming apparatus is tilted, the transfer belt **10** is abruptly deviated, and when a large load is abruptly applied to the rear side detection roller **37a** or the front side detection roller **37b**, the compression spring is compressed. While the rear side compression spring **46a** or the front side compression spring **46b** is compressed at the time of abnormality, the load applied to the transfer belt **10** is reduced. While the compression spring **46b** is compressed, the steering roller **28a** is tilted and the deviation of the transfer belt **10** is corrected. Accordingly, damage of the transfer belt **10** at the time of abnormality can be prevented.

A rear side belt pressing member **57a** or a front side belt pressing member **57b**, as a pressing member, is attached to the rear side shaft **43a** or the front side shaft **43b**. FIG. 10 and FIG. 11 show the front side belt pressing member **57b**. The front side belt pressing member **57b** is rotatably attached to the front side shaft **43b**. The front side belt pressing member **57b** presses the front side of the transfer belt **10** by its own weight toward inner side of the transfer belt **10** to prevent the front side of the transfer belt **10** is waved. By this, the transfer belt **10** more certainly contacts with the front side detection roller **37b**. A free end **59b** of the front side belt pressing member **57b** extends to a portion above the steering roller **28a**. This prevents the free end **59b** from biting into the transfer belt **10** at the time of rotation of the transfer belt **10**. Incidentally, the rear side belt pressing member **57a** is symmetrical to the front side belt pressing member **57b** and has the same structure.

The rear side detection roller **37a** includes a rear side gear unit **39** to transmit the rotation in the arrow **r1** direction to the linear movement shaft **52**. The front side detection roller **37b** includes a front side gear unit **40** to transmit the rotation in the arrow **r5** direction to the linear movement shaft **52**. The rear side gear unit **39** includes a first rear gear **39a**, a second rear gear **39b**, a third rear gear **39c** and a fourth rear gear **39d**. The front side gear unit **40** includes a first front gear **40a**, a second front gear **40b** and a third front gear **40c**. The fourth rear gear **39d** separably contacts with the rear side support lever **77a**. The third front gear **40c** separably contacts with the front side support lever **77b**. The linear movement shaft **52** rotates the worm **51** by the rotation of the fourth rear gear **39d** and the third front gear **40c**.

The worm **51** is engaged with the worm wheel **53** of the worm gear **50**. The worm wheel **53** is not rotated but is fixed to the support plate **36** in a still state. The worm **51** is a

6

left-hand screw, and when being rotated leftward viewed from the front side, the worm advances in an arrow **y** direction of FIG. 6 by the fixed worm wheel **53**. When being rotated rightward viewed from the front side, the worm **51** advances in an arrow **w** direction of FIG. 6 by the fixed worm wheel **53**.

The link member **36c** includes a hanger-like slider **60**. The slider **60** includes a slit **62** through which a fixed pin **61** provided on the support plate **36** is slidably inserted. The linear movement shaft **52** passes through a rear side branch **60a** and a front side branch **60b** of the slider **60**. The linear movement shaft **52** is rotatable with respect to the rear side branch **60a** and the front side branch **60b**, and part of the weight of the slider **60** is loaded to the linear movement shaft **52**.

The rear side branch **60a** or the front side branch **60b** is formed with a rear striking section **63a** or a front striking section **63b**. The rear side support lever **77a** or the front side support lever **77b** contacts with the rear striking section **63a** or the front striking section **63b**, and inward bending is prevented. The slider **60** is urged by the rear side support lever **77a** or the front side support lever **77b**, and is slid in the arrow **w** direction or the arrow **y** direction.

A rack **64** is formed at a center **60c** of the slider **60**. The rack **64** is engaged with a pinion **66** of the steering section **36b**. The steering section **36b** includes a steering support body **67** rotatable with respect to the support plate **36** and the steering roller **28a** supported by the steering support body **67**. The pinion **66** rotates the steering support body **67**. By the rotation of the steering support body **67**, the steering roller **28a** supported by the steering support body **67** is tilted (moved to have an angle with respect to the roller shaft).

As shown in FIG. 12, a urethane foam plate **68** as an elastic member is nipped between the support plate **36** and the steering support body **67**. The urethane foam plate **68** has a braking effect. The urethane foam plate **68** prevents the steering support body **67** from being overdriven to exceed an actually required tilt amount.

As shown in FIG. 13, an indicator **70** as an indicating member is fixed to the support plate **36**. The indicator **70** indicates a tilt angle as a movement amount of the steering roller **28a** with respect to the support plate **36**. The indicator **70** is given a mark **71** of 1° to 3° in \pm directions with respect to 0° . The mark **71** indicates the position of a pointer **72** provided on the steering support body **67**. The tilt angle of the steering roller **28a** is recognized by reading the position of the pointer **72**. For example, when the color image forming apparatus normally operates, the tilt angle of the steering roller **28a** is $\pm 2^\circ$ or less.

When a relation between the tilt angle of the steering roller **28a** indicated by the indicator **70** and the twist angle of the transfer belt **10** is measured, for example, results shown in FIG. 14 are obtained. From FIG. 14, even if the twist angle of the transfer belt **10** increases in the \pm direction, the tilt angle of the steering roller **28a** falls within $\pm 2^\circ$. Accordingly, when the tilt angle of the steering roller **28a** exceeds $\pm 2^\circ$, it is determined that an abnormality occurs in the transfer belt **10** or the color image forming apparatus.

Next, the tensioner **74** as the tension member will be described. The tensioner **74** moves the rear side detection roller **37a** and the front side detection roller **37b** to a contact area with the transfer belt **10** at the rotation of the support plate **36**. The contact area with the transfer belt **10** is an area which the transfer belt **10** contacts the rib **10a** at the rear side detection roller **37a** or the rib **10a** at the front side detection roller **37b** when the transfer belt **10** meanders. As shown in FIG. 15, the tensioner **74** includes the rear side support lever **77a** or the front side support lever **77b**, which is a first lever,

fixed to the rear side lever fulcrum **53a** or the front side lever fulcrum **53b** respectively. The tensioner **74** includes a rear side reference lever **76a** or a front side reference lever **76b**, which is a second lever, fixed to the rear side lever fulcrum **53a** or the front side lever fulcrum **53b** respectively.

The other end of the rear side reference lever **76a** or the front side reference lever **76b** contacts with a bracket **38** fixed to the main body side of the printer section **2**, and the movement is regulated. When the support plate **36** is rotated in an arrow *n* direction, the rear side reference lever **76a** or the front side reference lever **76b** regulated by the bracket **38** rotates the rear side lever fulcrum **53a** or the front side lever fulcrum **53b** in an arrow *q* direction respectively. The rear side support lever **77a** or the front side support lever **77b** fixed to the rear side lever fulcrum **53a** or the front side lever fulcrum **53b** rotates together with the rear side lever fulcrum **53a** or the front side lever fulcrum **53b** respectively.

When the length from the center of the rear side lever fulcrum **53a** or the front side lever fulcrum **53b** to a contact position **38a** between the other end of the rear side reference lever **76a** or the front side reference lever **76b** and the bracket **38** is made 1, the length from the center of the rear side lever fulcrum **53a** or the front side lever fulcrum **53b** to the rear side detection roller **37a** or the front side detection roller **37b** is set to *L*. When the support plate **36** is rotated in the arrow *n* direction and when the movement distance of the rear side lever fulcrum **53a** or the front side lever fulcrum **53b** is δ , the movement distance of the rear side detection roller **37a** or the front side detection roller **37b** becomes δL .

FIG. **16** shows a case where the peripheral length of the transfer belt **10** is short and the rotation amount of the support plate **36** in the arrow *n* direction is small. At this time, the rear side detection roller **37a** or the front side detection roller **37b** arrive in the contact area with the transfer belt **10** by small moving distance. The rear side detection roller **37a** or the front side detection roller **37b** is pressed to the ribs **10a** and **10b** of the transfer belt **10** without excessively applying tension to the transfer belt **10**. By this, the rear side detection roller **37a** or the front side detection roller **37b** can certainly detect the deviation of the transfer belt **10**.

FIG. **17** shows a case where the peripheral length of the transfer belt **10** is long and the rotation distance of the support plate **36** in the arrow *n* direction is large. At this time, the rear side detection roller **37a** or the front side detection roller **37b** is separated from the contact area with the transfer belt **10** unless it is moved much. However, since the movement of the rear side detection roller **37a** or the front side detection roller **37b** is set to be *L* times larger than the movement distance of the rear side lever fulcrum **53a** or the front side lever fulcrum **53b**, the rear side detection roller **37a** or the front side detection roller **37b** can be moved to the contact area with the transfer belt **10**. By this, the rear side detection roller **37a** or the front side detection roller **37b** can certainly detect the deviation of the transfer belt **10**.

Incidentally, when the length to the rear side reference lever **76a** or the front side reference lever **76b** is made 1, the length *L* to the rear side detection roller **37a** or the front side detection roller **37b** is not limited. The length *L* is set within the range where when the support plate **36** is rotated, the rear side detection roller **37a** or the front side detection roller **37b** can detect the deviation of the transfer belt **10**.

Next, the operation of the self steering mechanism **28** will be described. While the print operation is being performed in the printer section **2**, when the transfer belt **10** does not meander but rotates and travels at the normal position, the self steering mechanism **28** is not actuated. On the other hand, while the print operation is being performed, when the trans-

fer belt **10** meanders, the self steering mechanism **28** detects the meandering of the transfer belt **10**. By the detection of the meandering of the transfer belt **10**, the steering roller **28a** is tilted, and the traveling direction of the transfer belt **10** is corrected.

For example, the tilting of the steering roller **28a** when the transfer belt **10** meanders to the front will be described with reference to FIG. **7**. Incidentally, the rotation direction of each gear described here is the rotation direction viewed from the front side. (1) When the transfer belt **10** traveling in the arrow *s* direction deviates to the front side, the inside of the rear side rib **10a** of the transfer belt **10** contacts with the rear side detection roller **37a**. (2) By contacts with the rear side rib **10a**, the rear side detection roller **37a** of the detection section **36a** is rotated with the rear side rib **10a** and rotates left (*r1*).

(3) The rotation of the rear side detection roller **37a** is transmitted to the rear side gear unit **39**, the linear movement shaft **52** and the slider **60**, and tilts the steering roller **28a**. By the rotation of the rear side detection roller **37a**, the coaxial first rear gear **39a** rotates left (*r1*), the second rear gear **39b** rotates right (*r2*), the third rear gear **39c** rotates left (*r3*), and the fourth rear gear **39d** rotates right (*r4*). By right rotation (*r4*) of the second rear gear **39b**, the linear movement shaft **52** connected to the fourth rear gear **39d** rotates right (*r4*). By the right rotation (*r4*) of the linear movement shaft **52**, the worm **51** rotates right. The worm **51** is engaged with the fixed worm wheel **53**, and linearly moves the linear movement shaft **52** in the arrow *w* direction.

(4) By linear movement in the arrow *w* direction of the linear movement shaft **52**, the slider **60** is pushed by the rear side support lever **77a**, and is slid in the arrow *w* direction. (5) When the rack **64** of the slider **60** is slid in the arrow *w* direction, the pinion **66** is rotated in the arrow *t* direction. (6) By the rotation of the pinion **66** in the arrow *t* direction, the steering support body **67** and the steering roller **28a** supported by the steering support body **67** are tilted in an arrow *v* direction. As indicated by a dotted line in FIG. **7**, a force to convey the belt in the direction orthogonal to the axial line *a* of the tilted steering roller **28a** is generated for the transfer belt **10**. By this, the traveling direction is corrected so that the transfer belt **10** deviates to the rear side.

Incidentally, although the angle of the tilting of the steering roller **28a** for correcting the traveling direction of the transfer belt **10** is not limited, in this embodiment, it is assumed that for example, even when the transfer belt **10** is shifted by ± 1 mm from the center in design, the traveling direction can be corrected to the normal direction by tilting the steering roller **28a** by $\pm 3^\circ$ at the maximum.

Besides, when the steering support body **67** and the steering roller **28a** are tilted in the arrow *v* direction, the steering support body **67** is immediately stopped at a desired tilt angle by the braking effect of the urethane foam plate **68**. The steering support body **67** and the steering roller **28a** can correct the direction of the transfer belt **10** at high speed without being overdriven on the support plate **36**.

When the traveling direction of the transfer belt **10** is corrected to the normal direction by the tilting of the steering roller **28a**, the rear side rib **10a** of the transfer belt **10** is separated from the rear side detection roller **37a**, and the rear side detection roller **37a** is stopped. However, after the rotation of the steering roller **28a**, a time lag occurs before the traveling direction of the transfer belt **10** is corrected. During the time lag, when the rear side detection roller **37a** is rotated, the rotation amount of the steering roller **28a** becomes excessive. As a result, the transfer belt **10** deviates to the rear side. Thus, when the rear side detection roller **37a** is rotated, by using the rotation of the rear side detection roller **37a**, the rear

side detection roller 37a is moved to be separated from the transfer belt 10. That is, before the traveling direction of the transfer belt 10 is corrected by the steering roller 28a, the rear side detection roller 37a can be separated from the transfer belt 10. As a result, it is prevented that the rotation amount of the steering roller 28a becomes excessive.

When the rear side detection roller 37a rotates left (r1), as described above, the linear movement shaft 52 is moved in the arrow w direction (shown in FIG. 18). By linear movement in the arrow w direction of the linear movement shaft 52, the rear side detection roller 37a is separated from the rear side rib 10a of the transfer belt 10. As shown in FIG. 19, when the rear side rib 10a of the transfer belt is separated, the rear side detection roller 37a is stopped. However, when the tilting of the steering roller 28a is insufficient, the rear side rib 10a again contacts with the rear side detection roller 37a. By this, the rear side detection roller 37a is again rotated and further tilts the steering roller 28a. Besides, as the rear side detection roller 37a is separated from the rear side rib 10a, the contact force of the rear side rib 10a to the rear side detection roller 37a becomes small. By this, the rotation amount of the rear side detection roller 37a is decreased. The rotation and stop of the rear side detection roller 37a are repeated, so that the traveling direction of the transfer belt 10 is corrected, the meandering is regulated, and the stable rotation and traveling are performed.

Next, the tilting of the steering roller 28a when the transfer belt 10 meanders to the rear will be described with reference to FIG. 8. Incidentally, the rotation direction of each gear described here is the rotation direction viewed from the front side. (1) When the transfer belt 10 traveling in the arrow s direction deviates to the rear side, the inside of the front side rib 10b of the transfer belt 10 contacts with the front side detection roller 37b. (2) By contacts with the front side rib 10b, the front side detection roller 37b of the detection section 36a is rotated with the front side rib 10b and rotates left (r5).

(3) The rotation of the front side detection roller 37b is transmitted to the front side gear unit 40, the linear movement shaft 52 and the slider 60, and tilts the steering roller 28a. By the rotation of the front side detection roller 37b, the coaxial first front gear 40a rotates left (r5), the second front gear 40b rotates right (r6), and the third front gear 40c rotates left (r7). By left rotation (r7) of the third front gear 40c, the linear movement shaft 52 connected to the third front gear 40c rotates left (r7). By the left rotation (r7) of the linear movement shaft 52, the worm 51 rotates left. The worm 51 is engaged with the fixed worm wheel 53, and linearly moves the linear movement shaft 52 in the arrow y direction.

(4) By linear movement in the arrow y direction of the linear movement shaft 52, the slider 60 is pushed by the front side support lever 77b, and is slid in the arrow y direction. (5) When the rack 64 of the slider 60 is slid in the arrow y direction, the pinion 66 is rotated in an arrow u direction. (6) By the rotation of the pinion 66 in the arrow u direction, the steering support body 67 and the steering roller 28a supported by the steering support body 67 are tilted in an arrow x direction. As indicated by a dotted line in FIG. 8, a force to convey the belt in the direction orthogonal to the axial line β of the tilted steering roller 28a is generated for the transfer belt 10. By this, the traveling direction is corrected so that the transfer belt 10 deviates to the front.

Besides, at this time, when the front side detection roller 37b rotates left (r5) by the transfer belt 10, as described above, the linear movement shaft 52 is moved in the arrow y direction. By this, the front side detection roller 37b is separated from the front side rib 10b of the transfer belt 10. Thereafter, similarly to the time of the rotation of the rear side detection

roller 37a, the rotation and stop of the front side detection roller 37b are repeated, and the traveling direction of the transfer belt 10 is corrected.

At the correction of the traveling direction of the transfer belt 10, when the tension of the transfer belt 10 is changed, the support plate 36 is swayed. By this, the steering roller 28a gives suitable tension to the transfer belt 10. At the same time as this, the tensioner 74 moves the rear side detection roller 37a and the front side detection roller 37b, respectively, by required distances. By this, the rear side detection roller 37a and the front side detection roller 37b can contact with the transfer belt 10.

Besides, at the correction of the traveling direction of the transfer belt 10, the transfer belt 10 is pressed by the rear side belt pressing member 57a or the front side belt pressing member 57b. By this, the rear side end and the front side end of the transfer belt 10 are urged to inner side of the transfer belt 10. Accordingly, when the transfer belt 10 deviates, the rear side rib 10a or the front side rib 10b can more certainly contact with the rear side detection roller 37a or the front side detection roller 37b.

While the print operation is performed, the indication of the indicator 70 is confirmed at specified intervals. From the indication of the indicator 70, when the tilt angle of the steering roller 28a falls within $\pm 2^\circ$, it is determined that the normal operation is performed. When the tilt angle of the steering roller 28a exceeds $\pm 2^\circ$, it is determined that an abnormality occurs in the transfer belt 10 or in the inside of the color image forming apparatus, and the operation is interrupted.

While the print operation is being performed, when the transfer belt 10 is abruptly deviated, a large load is abruptly applied between the rear side detection roller 37a and the rear side rib 10a or between the front side detection roller 37b and the front side rib 10b. However, at this time, the rear side compression spring 46a or the front side compression spring 46b is compressed, and the rear side detection roller 37a or the front side detection roller 37b is moved in the direction of separating from the rear side rib 10a or the front side rib 10b. By this, the load applied to the transfer belt 10 by the abrupt deviation is reduced. Further, while the rear side compression spring 46a or the front side compression spring 46b is compressed, the steering roller 28a is tilted, the deviation of the transfer belt 10 is corrected, and the load applied to the transfer belt 10 is reduced. By this, even when there occurs an abnormality that the transfer belt 10 is abruptly deviated, the damage of the transfer belt 10 can be prevented.

According to the first embodiment, the meandering of the transfer belt 10 is detected by the rear side detection roller 37a or the front side detection roller 37b that contacts with the rib 10a or 10b of the transfer belt 10. The rotation of the rear side detection roller 37a or the front side detection roller 37b is converted into the linear driving by using the worm gear 50, and the linear movement shaft 52 is linearly moved. The linear driving of the linear movement shaft 52 is transmitted to the steering roller 28a through the slider 60, and the steering roller 28a is tilted. By the tilting of the steering roller 28a, the direction of the rotation traveling of the transfer belt 10 is corrected.

Further, the rotation of the rear side detection roller 37a or the front side detection roller 37b is converted into the linear movement of the linear movement shaft 52 by the worm gear 50, and the rear side detection roller 37a or the front side detection roller 37b is separated from the rib 10a or 10b of the transfer belt 10. Accordingly, the meandering of the transfer belt can be easily and certainly regulated without requiring expensive and complicated control or mechanism. As a result,

11

the damage of the transfer belt is prevented, the transfer belt can be stably rotated and traveled, and an excellent transfer image can be obtained.

Next, a second embodiment of the invention will be described. The second embodiment is different from the first embodiment in the structure of a transfer belt, and detection of meandering of the transfer belt is reversed between a rear side and a front side. Accordingly, in this second embodiment, a screw of a worm of a worm gear is opposite to that of the first embodiment. In this second embodiment, the same structure as the structure described in the first embodiment is denoted by the same reference numeral and its detail explanation will be omitted.

In a self steering mechanism **81** of the second embodiment, a transfer belt **80** does not have a rib at both ends of an inner periphery. When the transfer belt **80** is held at a normal position, both ends of the transfer belt **80** are separated from a rear side detection roller **82a** and a front side detection roller **82b**. When the transfer belt **80** meanders and contacts with a roller surface of the rear side detection roller **82a** or the front side detection roller **82b**, the rear side detection roller **82a** or the front side detection roller **82b** is rotated. The rotation amount of the rear side detection roller **82a** or the front side detection roller **82b** is adjusted by a contact area between the transfer belt **80** and the roller surface. Accordingly, the width of the roller surface of the rear side detection roller **82a** or the front side detection roller **82b** is formed to be larger than at least the width corresponding to the maximum meandering amount of the transfer belt **80**.

In the second embodiment, it is assumed that a worm **84** engaging with a worm wheel **53** of a worm gear **83** is a right-hand screw. When the worm **84** rotates right viewed from the front side, the worm advances in an arrow y direction of FIG. 20 by the fixed worm wheel **53**.

Next, the operation of the self steering mechanism will be described. Incidentally, the rotation direction of each gear described here is the rotation direction viewed from the front side. When the transfer belt **80** does not meander but is rotated and traveled at the normal position, the self steering mechanism **81** is not operated. When the transfer belt **80** traveling in an arrow s direction meanders to the rear, (1) the inner periphery of the transfer belt **80** at the rear side end contacts with the roller surface of the rear side detection roller **82a**. (2) By this, the rear side detection roller **82a** is rotated with the transfer belt **80** and rotates left (r1). (3) By the rotation of the rear side detection roller **82a**, a coaxial first rear gear **39a** rotates left (r1), a second rear gear **39b** rotates right (r2), a third rear gear **39c** rotates left (r3), and a fourth rear gear **39d** rotates right (r4). By this, a linear movement shaft **52** connected to the fourth rear gear **39d** rotates right (r4). By the right rotation (r4) of the linear movement shaft **52**, the worm **84** rotates right. Since the worm **84** is the right-hand screw, the worm is engaged with the fixed worm wheel **53** and linearly moves the linear movement shaft **52** in the arrow y direction.

(4) By linear movement in the arrow y direction of the linear movement shaft **52**, a slider **60** is pushed by a front side support lever **77b** and is slid in the arrow y direction. (5) When a rack **64** of the slider **60** is slid in the arrow y direction, a pinion **66** is rotated in an arrow u direction. (6) By the rotation of the pinion **66** in the arrow u direction, a steering support body **67** and a steering roller **28a** supported by this are tilted in the arrow x direction. As indicated by a dotted line in FIG. 20, a force to convey the belt in the direction orthogonal to the axial line β of the steering roller **28a** is generated for the transfer belt **80**. By this, the traveling direction is corrected so that the transfer belt **80** deviates to the front.

12

When the rear side detection roller **82a** rotates left (r1), the linear movement shaft **52** is moved in the arrow y direction. By this, the rear side detection roller **82a** is separated from the transfer belt **80**. When the rear side of the transfer belt **80** is separated, the rear side detection roller **82a** is stopped. This prevents the rotation amount of the steering roller **28a** from becoming excessive. However, when the tilting of the steering roller **28a** is insufficient, the transfer belt **80** again contacts with the rear side detection roller **82a**. By this, the rear side detection roller **82a** is again rotated, and further tilts the steering roller **28a**. Besides, as the rear side detection roller **82a** is separated from the transfer belt **80**, the contact force of the transfer belt **80** to the rear side detection roller **82a** becomes small. By this, the rotation amount of the rear side detection roller **82a** is decreased. The rotation and stop of the rear side detection roller **82a** are repeated, so that the traveling direction of the transfer belt **80** is corrected, the meandering is regulated and the stable rotation and traveling are performed.

As shown in FIG. 21, when the transfer belt **80** meanders to the front, (1) the inner periphery of the transfer belt **80** at the front side end contacts with the roller surface of the front side detection roller **82b**. (2) By this, the front side detection roller **82b** is rotated with the transfer belt **80** and rotates left (r5). (3) By the rotation of the front side detection roller **82b**, a coaxial first front gear **40a** rotates left (r5), a second front gear **40b** rotates right (r6), and a third front gear **40c** rotates left (r7). By this, the linear movement shaft **52** connected to the third front gear **40c** rotates left (r7). The worm **84** rotates left by the left rotation (r7) of the linear movement shaft **52**. Since the worm **84** is the right-hand screw, the worm is engaged with the fixed worm wheel **53** and linearly moves the linear movement shaft **52** in an arrow w direction.

(4) By linear movement in the arrow w direction of the linear movement shaft **52**, the slider **60** is pushed by the rear side support lever **77a** and is slid in the arrow w direction. (5) When the rack **64** of the slider **60** is slid in the arrow w direction, the pinion **66** rotates in an arrow t direction. (6) By the rotation of the pinion **66** in the arrow t direction, the steering support body **67** and the steering roller **28a** supported by this are tilted in an arrow v direction. As indicated by a dotted line in FIG. 21, a force to convey the belt in the direction orthogonal to the axial line a of the tilted steering roller **28a** is generated for the transfer belt **80**. By this, the traveling direction is corrected so that the transfer belt **80** deviates to the rear.

When the front side detection roller **82b** rotates left (r5), the linear movement shaft **52** is moved in the arrow w direction. By this, the front side detection roller **82b** is separated from the transfer belt **80**. When the rear side of the transfer belt **80** is separated, the front side detection roller **82b** is stopped. This presents the rotation amount of the steering roller **28a** from becoming excessive. However, when the tilting of the steering roller **28a** is insufficient, the transfer belt **80** again contacts with the front side detection roller **82b**. By this, the front side detection roller **82b** is again rotated and further rotates the steering roller **28a**. Besides, as the front side detection roller **82b** is separated from the transfer belt **80**, the contact force of the transfer belt **80** to the front side detection roller **82b** becomes small. By this, the rotation amount of the front side detection roller **82b** is decreased. The rotation and stop of the front side detection roller **82b** are repeated, so that the traveling direction of the transfer belt **80** is corrected, the meandering is regulated, and the stable rotation and traveling are performed.

According to the second embodiment, similarly to the first embodiment, the meandering of the transfer belt **80** can be easily and certainly regulated. Accordingly, the transfer belt

13

80 is stably rotated and traveled without damaging the transfer belt 80, and an excellent transfer image can be obtained. Further, it is not necessary to form an expensive rib on the transfer belt 80, and the cost of the transfer belt 80 can be reduced.

Incidentally, in this embodiment, although the material of the roller surface of the rear side detection roller or the front side detection roller is not limited, it may be made of a material having a large friction coefficient, such as rubber. By doing so, a sufficient friction force can be ensured between the rear side detection roller or the front side detection roller and the inner periphery of the transfer belt. As a result, the rear side detection roller or the front side detection roller can accurately detect the meandering of the transfer belt, and the traveling direction of the transfer belt can be more certainly corrected.

Incidentally, the invention is not limited to the above embodiments, but can be variously modified within the scope of the invention. For example, with respect to the material of the first detection roller or the second detection roller, as long as the roller can be rotated by the contact with the belt member, its structure, material and the like are not limited. The structure of conversion member is not limited. The screw direction of the worm of the worm gear is not limited. The structure of the printer section is not limited to the tandem type, and a revolver type developing device may be used in which an image on a single image carrier is sequentially transferred to a belt material, a sheet transferred by the belt member or the like.

What is claimed is:

1. An image forming apparatus comprising:

a belt member that travels along a traveling direction;
an image forming member configured to form an image on the belt member;
a first detection roller configured to rotate upon contact with a first end of the belt member in a width direction;
a second detection roller configured to rotate upon contact with a second end of the belt member opposite the first end;
a tension member configured to move the first detection roller and the second detection roller to an area of contact with the belt member;
a conversion member configured to convert rotation of the first detection roller or the second detection roller into linear driving;
a transmission member driven by the linear driving of the conversion member; and
a steering member configured to change the travelling direction of the belt member by an operation of the transmission member.

2. The device of claim 1, wherein the conversion member includes a worm, a shaft that coaxially supports the worm and is linearly moved by rotation of the first detection roller or the second detection roller, and a fixed worm wheel that engages with the worm.

3. The device of claim 1, wherein the belt member includes ribs on an inner periphery at the ends in the width direction, the first detection roller is rotated by contact with the rib at the first end of the belt member, the second detection roller is rotated by contact with the rib at the second end of the belt member, the steering member changes the traveling direction of the belt member by the rotation of the first detection roller to move the belt member to a side of the first end, and the steering member changes the traveling direction of the belt member by the rotation of the second detection roller to move the belt member to a side of the second end.

14

4. The device of claim 1, wherein the first detection roller is rotated by contact with an inner periphery of the belt member at the first end, the second detection roller is rotated by contact with an inner periphery of the belt member at the second end, the steering member changes the traveling direction of the belt member by the rotation of the first detection roller to move the belt member to a side of the second end, and the steering member changes the traveling direction of the belt member by the rotation of the second detection roller to move the belt member to a side of the first end.

5. The device of claim 1, further comprising a first urging member configured to urge the first detection roller toward the first end of the belt member and a second urging member configured to urge the first detection roller toward the first end of the belt member.

6. An image forming apparatus comprising:

a belt member that travels along a traveling direction;
an image forming member configured to form an image on the belt member;
a first detection roller configured to rotate upon contact with a first end of the belt member in a width direction;
a second detection roller configured to rotate upon contact with a second end of the belt member opposite the first end;
a conversion member configured to convert rotation of the first detection roller or the second detection roller into linear driving;
a transmission member driven by the linear driving of the conversion member;
a steering member configured to change the traveling direction of the belt member by an operation of the transmission member; and
an indicating member configured to indicate a movement amount of the steering member.

7. The device of claim 6, wherein an abnormality is detected by the movement amount of the steering member indicated on the indicating member.

8. An image forming apparatus comprising:

a belt member that travels along a traveling direction;
an image forming member configured to form an image on the belt member;
a first detection roller configured to rotate upon contact with a first end of the belt member in a width direction;
a second detection roller configured to rotate upon contact with a second end of the belt member opposite the first end;
a conversion member configured to convert rotation of the first detection roller or the second detection roller into linear driving;
a transmission member driven by the linear driving of the conversion member;
a steering member configured to change the traveling direction of the belt member by an operation of the transmission member; and
an elastic member provided between a support member of the steering member and a fixed member configured to support the support member.

9. An image forming apparatus comprising:

a belt member that travels along a traveling direction;
an image forming member configured to form an image on the belt member;
a first detection roller configured to rotate upon contact with a first end of the belt member in a width direction;
a second detection roller configured to rotate upon contact with a second end of the belt member opposite the first end;

15

a conversion member configured to convert rotation of the first detection roller or the second detection roller into linear driving;

a transmission member driven by the linear driving of the conversion member;

a steering member configured to change the traveling direction of the belt member by an operation of the transmission member; and

a tension member configured to move the first detection roller and the second detection roller to an area of contact with the belt member.

10. The device of claim 9, further comprising a support member that rotates and supports the steering member and causes the steering member configured to give a tensile force to the belt member,

wherein the tension member includes a first lever, one end of which is fixed to a lever fulcrum provided on the support member and the other end of which supports a first roller shaft that supports the first detection roller or a second roller shaft configured to support the second detection roller, and a second lever, one end of which is fixed to the lever fulcrum and the other end of which is stopped, and

lengths of the first lever and the second lever are set to cause the first detection roller and the second detection roller to move to an area of contact with the belt member by rotating the support member.

16

11. The device of claim 10, wherein when a movement amount of the first detection roller or the second detection roller by the rotation of the support member is made L times larger than a movement amount of the lever fulcrum, a length of the first lever is set to be L times larger than a length of the second lever.

12. The device of claim 9, wherein the belt member includes ribs on an inner periphery at the ends in the width direction, the first detection roller is rotated by contact with the rib at the first end of the belt member, the second detection roller is rotated by contact with the rib at the second end of the belt member, the steering member changes the traveling direction of the belt member by the rotation of the first detection roller to move the belt member to a side of the first end, and the steering member changes the traveling direction of the belt member by the rotation of the second detection roller to move the belt member to a side of the second end.

13. The device of claim 9, wherein the first detection roller is rotated by contact with an inner periphery of the belt member at the first end, the second detection roller is rotated by contact with the inner periphery of the belt member at the second end, the steering member changes the traveling direction of the belt member by the rotation of the first detection roller to move the belt member to a side of the second end, and the steering member changes the traveling direction of the belt member by the rotation of the second detection roller to move the belt member to a side of the first end.

* * * * *