

US008067852B2

(12) **United States Patent**
Ortiz et al.

(10) **Patent No.:** **US 8,067,852 B2**
(45) **Date of Patent:** ***Nov. 29, 2011**

(54) **FLUID DRIVEN ELECTRIC POWER GENERATION SYSTEM**

(75) Inventors: **Luis M. Ortiz**, Albuquerque, NM (US);
Anthony Michael Baca, Albuquerque, NM (US); **Donald Wichers**, Albuquerque, NM (US)

(73) Assignee: **MDL Enterprises, LLC**, Albuquerque, NM (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 740 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **12/127,508**

(22) Filed: **May 27, 2008**

(65) **Prior Publication Data**

US 2008/0238105 A1 Oct. 2, 2008

Related U.S. Application Data

(63) Continuation-in-part of application No. 12/058,764, filed on Mar. 31, 2008, now Pat. No. 7,868,476.

(60) Provisional application No. 60/921,331, filed on Mar. 31, 2007, provisional application No. 60/953,106, filed on Jul. 31, 2007.

(51) **Int. Cl.**
F03D 9/00 (2006.01)

(52) **U.S. Cl.** 290/55; 415/4.5

(58) **Field of Classification Search** 290/43, 290/44, 54, 55; 415/4.5, 4.3

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

| | | | | |
|-----------|------|---------|---------------|---------|
| 4,176,283 | A | 11/1979 | McLaren | |
| 5,167,483 | A * | 12/1992 | Gardiner | 415/3.1 |
| 7,663,261 | B2 * | 2/2010 | Miller et al. | 290/54 |
| 7,868,476 | B2 * | 1/2011 | Baca et al. | 290/55 |

* cited by examiner


Primary Examiner — Nicholas Ponomarenko

(74) *Attorney, Agent, or Firm* — Ortiz & Lopez, PLLC

(57) **ABSTRACT**

A tubular housing includes at least one fixed helical vane formed onto the inner surfaces of the tubular housing in a spiral and adapted to direct fluid into a spiraled flow and focus fluid onto a fan blade assembly associated with an alternator system and located within the tubular housing before a system exhaust. A generator cone can be mounted near the center and front of the fan blade assembly facing fluid passing through the tubular housing. As fluid passes over the generator cone it experiences compression between the generator cone and housing resulting in increased pressure and velocity of the fluid, thereby increasing rotational speed of the generator blades and generator as the compressed, spiraled fluid passes through the blades and exits the tubular housing. The system can be used for fixed or mobile applications in water, wind and manually induced air flow.

13 Claims, 15 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4






FIG. 5






FIG. 8




FIG. 9

FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25

1

FLUID DRIVEN ELECTRIC POWER GENERATION SYSTEM

CONTINUATION AND PRIORITY DATA

This application claims priority as a continuation-in-part patent application to non-provisional patent application Ser. No. 12/058,764, filed Mar. 31, 2008 now U.S. Pat. No. 7,868,476, entitled "WIND-DRIVEN ELECTRIC POWER GENERATION SYSTEM", which also claims priority as a continuation to provisional patent application 60/921,331, filed Mar. 31, 2007 and to provisional patent application 60/953,106, filed Jul. 31, 2007, all herein incorporated by reference herein.

TECHNICAL FIELD

The present invention is generally related to renewable energy systems. More particularly, the present invention is related to fluid powered generator systems adapted for fixed and mobile electrical power generation systems and applications.

BACKGROUND OF THE INVENTION

Wind and stream or oceanographic water are forces of nature in the form of fluid that surround us and as a whole is barely being tapped for its energy generating potential. Wind is harnessed to sail ships, pump water, and create electricity, just to name a few. Hydroelectric power has also contributed largely to the production of electricity. Hydroelectric systems have also typically deployed as large industrial system and have not found wide use in the private sector. Yet untapped potential exists with streams and shorelines near residential and commercial developments.

Recent events in the world have highlighted the need for alternative, cleaner methods of power production, whether it is from the wind, the sun, water, or organic matter. Changes in battery storage capacity and life and generator efficiency have made it so that individuals desiring to supplement their energy requirements may do so at a much more affordable cost over 15 years ago. These so-called "Green" technologies continue to be improved as energy shortages and high costs of energy plague society.

In general, electric power generation systems can be classified into hydroelectric power generation, thermal power generation, nuclear power generation, solar power generation, bio-fuel power generation and wind power generation using wind energy. Wind energy is limitless, purely domestic renewable energy that is freely available in the world. The wind power generation system faces some difficulty in its stability due to fluctuation in direction and speed of air. Wind energy has been used as a source of power for sailing ships for several thousands of years, and until recently, we have been using it in water pumping and operating flour mills. Recently, many new ideas and theories for windmill and wind power generation have surfaced, like propeller shaped blades as part of large, scaled power generators that rotate based on aerodynamics of the blade designs.

Wind generated power has been used as a source of electricity that can be used directly by buildings and other fixed infrastructure, or has been fed directly into public utility system grids for distribution and use by public utility customers. Wind generated electrical power will continue to find uses as its need increases at all levels and types of consumption and as an alternative energy to fossil fuels.

2

It is known in the art that the propeller of a wind power generator should ideally be positioned in the path of the flowing air. In most systems currently being deployed internationally, propellers and generators can reach height greater than 100 feet and rotational diameters greater than 50 ft. Propellers currently used with wind power generators are designed in such a way to produce power output as various wind speed conditions press against propeller blades. It is unfortunate that such system must be so large, which is a main point of contention by many communities.

Systems for the generation of electrical power from natural sources are clearly needed that are smaller than is currently available and in wide use. There is also more specifically a need for smaller, less visually intrusive fluid powered electric generation systems for fixed residential, commercial and mobile applications. With the current invention a system is presented that can less expensively generate electrical energy from fluid flow, be it air or water. Power generated by the present invention can be utilized in fixed as well as mobile applications and can generate electrical power from wind, vehicle-induced airflow, flowing water in a stream or river, flowing water through water utility lines, and ocean flow near coastlines.

BRIEF SUMMARY

The following summary is provided to facilitate an understanding of some of the innovative features unique to the embodiments disclosed and is not intended to be a full description. A full appreciation of the various aspects of the embodiments can be gained by taking the entire specification, claims, drawings, and abstract as a whole.

It is therefore an objective of the present invention to provide an improved fluid powered electric power generating system. Fluid flow as used herein includes power harnessed from airflow caused by wind and hydraulic power caused from stream and ocean water movement.

It is another objective of the present invention to provide a fluid driven electric power generator system useful for static and mobile applications. Static application can include residential and commercial building applications whether above ground, associated with public and private water utilities, or within a body of water. Mobile applications include automotive, marine, air, and any commercial/industrial freight or human transportation systems.

A new alternator in one embodiment of the present invention includes a generally radial shape and includes a winding portion integrated on/within a tubular housing adapted to carry fluid there through, and an integrated fan rotor portion rotationally operable within the electromagnetic field of a fixed winding portion associated with a tubular housing. The winding portion can include coil windings formed from flat conductor material and emplaced around a core of magnetic flux conducting material. The integrated fan rotor portion includes permanent magnets attached to a rim formed on the outer circumference of fan blades extending from a center rotor. Rotation of the magnets disposed on the outer perimeter of the fan blades as fluid passes through the tubular housing and the fan blades of the integrated fan rotor portion produces magnetic fields on the winding portion that remains stationary because the winding portion is integrated with the tubular housing.

Another benefit of the alternator of this embodiment is with its potentially low manufacturing cost. The conductor coils can be located on or integrated within the tubular housing peripherally to a magnetic field emitting rotor upon final assembly. The manufacturing reproducibility of the design of

the radial, slotless alternator is therefore less expensive and more practical for enable fluid flow there through in accordance with the present invention. Although the radial, slotless alternator can be incorporated into working embodiments of the present invention, other alternator designs can still operate well within fluid power generating systems described herein without limitation.

In accordance with a feature of the present invention, a system generating electrical power from fluid can include a cowling located at a first end of a tubular housing to capture fluid and can direct it into the tubular housing.

In accordance with yet another feature of the present invention, at least one fixed helical vane can be integrated into the inner surface of the tubular housing in a spiral, adapted to further direct fluid captured in the housing into a spiraled fluid flow and more directly focus the fluid's energy onto fan blades associated with an electrical alternator located at or near the end of the at least one fixed helical vane. A second end of the tubular housing can enable fluid to be exhausted from the tubular housing once it has passed through fan blades associated with the electrical alternator.

In accordance with another feature of the present invention, a conical flange can be formed at the second end of the unit, said conical flange adapted to protect the can blades and also enables fluid to escape from the unit without interruption from exterior wind source moving along the sides of the unit. The conical flange can also assist in the orientation of the first end of the system in the directions of incoming fluid.

In accordance with another feature of the present invention, a cone can be mounted at the center and front of the alternator within the circumference of the fan blades, facing approaching fluid passing through the tubular housing. As fluid passes over the generator cone it can experience compression between the generator cone and housing resulting in increased pressure and velocity of the fluid as it passes through the fan blades, thereby increasing rotational speed of the fan blades and alternator as the compressed air passes through the blades.

In accordance with a feature application of the present invention, the system can be mounted at or integrated within the front of a moving vehicle for mobile applications. Mounting of the unit to the bow of a boat, the front of a cargo container, or integrated it within the front of an automobile, can facilitate the generation of electricity for various uses such as recharging of battery supplies, providing power to mobile refrigeration units, providing power to mobile vehicle electrical components, etc. When the system is integrated near or at the front of a moving vehicle, it can capture airflow as the vehicle moves forward, thereby generating electrical power from airflow for charging a load, such as hybrid vehicle batteries, which can assist in extending the operation range of an electric vehicle.

In accordance with yet another feature application of the present invention, the system can be submersed into flowing water, such as within a stream, river or along a shoreline of an ocean. Fluid in the form of water flowing through the housing can facilitate the generation of electricity for various uses such as recharging of battery supplies, transferring power into an electrical power grid, providing power to electrical components in the field, providing electrical power to mobile and stationary loads such as appliances, etc.

In accordance with yet another feature application of the present invention, the system can be installed along piping associated with municipal and private water distribution systems to facilitate the generation of electricity for various uses such as: recharging of battery supplies for remote power uses,

for transferring power into an electrical power grid, or providing power to electrical components in the field (e.g., street lights), etc.

In accordance with another feature application of the present invention, the system can be rotatably mounted on top of a pole for fixed residential used, remote telecommunications equipment power, power grid distribution, or fixed commercial applications. Mounting of the unit to poles, towers, rooftops, beams and other fixed hardware can be facilitated with bearing and mounts that can withstand extreme fluctuations and high stress.

In accordance with another feature of the present invention, electrical contact discs (plates) can be provided that facilitate electrical connections between the generator and external modules (e.g., batteries, converters, etc.) and prevent wire tangling. Sealed electrical contact discs can be integrated with the bearing and mounting mechanism adapted to rotatably mount the housing to a pole.

In accordance with another feature of the present invention, a fin can be provided in fixed attachment to a second end of the power generating system near the second end of the tubular housing to direct the front of the tubular housing into approaching fluid by rotating the housing on a pole, thereby enabling the system to receive the maximum amount of available wind into the system.

In accordance with another feature of the present invention, power conditioning can be provided to generated power if necessary using conditioning circuits known in the art (e.g., filtering circuits). The size of the present system is scalable to meet delivery requirements.

In accordance with another feature of the present invention, the housing can be made of a tough light weight metal or a composite that will be able to withstand harsh environments while meeting the highest of standards.

In accordance with another feature of the present invention, a cowling can be located at the front of the alternator/fan with its point facing incoming fluid to cause the fluid to flow directly onto fan blades and not encounter a flat surface typically associated with the back of a alternator or center portion of a fan wherefrom blades extend. Pressure caused between the inner surface of the housing tubing and the cone/generator can force fluid directly onto the alternator fan blades and outward past the fan blades where the fluid can be exhausted from the second end of the housing.

In accordance with another feature of the present invention, a cupped fan blade can be included to enhance the effect of fluid pressure on the fan blades and ultimately as rotation of the alternator.

In accordance with another feature of the present invention, a clutching mechanism and/or mechanical breakaway can be provided to accommodate conditions where the wind speed exceeds rotational capabilities of the alternator and/or power output requirements/thresholds. Clutching can be provided in the form of a fan blade assembly designed with materials that can flex above threshold rotational speeds (RPMs) in order to prevent operation of the generator above damage causing thresholds, design parameters and generator capacity limits.

In accordance with another feature of the present invention, an electronic starting circuit can be provided in order to facilitate initial starting of a traditional alternator from periods when the alternator is idle (e.g., no rotation due to lack of fluid). The electronic starting system can provide an initial release of electrical energy to the windings in the generator to thereby reduce the amount of fluid required to spin-up or start rotation of the generator.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying figures, in which like reference numerals refer to identical or functionally-similar elements

5

throughout the separate views and which are incorporated in and form a part of the specification, further illustrate the embodiments and, together with the detailed description, serve to explain the embodiments disclosed herein.

FIG. 1 illustrates a block diagram of a fluid driven electrical power generating system, which can be implemented in accordance with features of the present invention;

FIG. 2 illustrates a block diagram of a fluid driven electrical power generating system including a cowling used with turbulent incoming fluid, which can be implemented in accordance with features of the present invention;

FIG. 3 illustrates a turbulent flow of air flowing through a tubular housing without a cowling;

FIG. 4 a laminar flow of air flowing through a tubular housing of wind driven electrical power generating system using a cowling to capture wind and direct it into the housing, which can be implemented in accordance with a preferred embodiment;

FIG. 5 illustrates three phenomena that can occur with wind directed toward a cowling, a cowling design of a wind driven electrical power generating system, which can be implemented in accordance with a preferred embodiment;

FIG. 6 illustrates a view of the first end of the fluid driven electrical power generating system looking into the cowling or coupling (depending if application is using a cowling with turbulent fluid or a coupling spliced into a water distribution system) through the inside of the tubular housing past helical vanes towards the fan, in accordance with features of the present invention;

FIG. 7 illustrates a view of the first end of the fluid driven electrical power generating system such as that shown in FIG. 6, including a cowling/coupling located at the first end of the system, in accordance with features of the present invention;

FIG. 8 illustrates a side view of fluid driven electrical power generating system including a conical flange located near the second end of the system with fluid directing the cowling located at the first end of the tubular housing into oncoming fluid flow, in accordance with features of the present invention;

FIG. 9 illustrates a side view of an air driven electrical power generating system rotationally mounted on a pole and including a fin to oriented the front end of the power generating system into oncoming wind, in accordance with features of the present invention;

FIG. 10 illustrates a view of the first end of the fluid driven electrical power generating system such as that shown in FIG. 9, similar looking to the generator with a cowling shown in FIG. 7 but including a fin and conical flange located near the second end of the system, in accordance with features of the present invention;

FIG. 11 is an illustration of a water utility line fluid driven electrical power generating system including line couplings for securing the power generator inline within a water distribution system, which can be implemented in accordance with features of the present invention;

FIG. 12 is a schematic representation of applications for a water utility line application for the fluid driven electrical power generating system of the present invention;

FIG. 13 is side view illustration of a fluid driven electrical power generating system including a electric line and land tether, in accordance with features of the present invention;

FIG. 14 is a schematic representation of a hydraulic power generation application for the fluid driven electrical power generating system including a electric line and land tether, in accordance with features of the present invention;

FIG. 15 is side view illustration of a fluid driven electrical power generating system adapted for bi-directional fluid flow

6

and including a cowling at each end of the housing, in accordance with features of the present invention;

FIG. 16 is a side cross sectional perspective view of a bi-directional power generation system, in accordance with features of the present invention;

FIG. 17 is a side cross sectional perspective view of an alternate bi-directional power generation system utilizing a slotless integrated fan alternator wherein the outer circumference of the fan includes magnets that cause electromagnetic energy to be experience by wiring formed in a core form on/outside of the tubular housing, in accordance with features of the present invention;

FIG. 18 is a schematic representation of a hydraulic power generation application for the fluid driven electrical power generating system adapted for bi-directional fluid flow wherein several systems can be tethered for use along a shore-line, in accordance with features of the present invention;

FIG. 19 is a schematic representation of a mobile power generation application for the fluid driven electrical power generating system, in accordance with feat of the present invention;

FIG. 20 is a schematic representation of another mobile power generation application for the fluid driven electrical power generating system, in accordance with features of the present invention;

FIGS. 21-23 is a perspective view of a slotless integrated fan alternator wherein the outer circumference of the fan includes magnets that cause electromagnetic energy to be experience by wiring formed in a core form on/outside of the tubular housing, in accordance with features of the present invention;

FIG. 24 illustrates a high level flow chart of operations depicting a fluid driven electrical power generating method, which can be implemented in accordance with a preferred embodiment; and

FIG. 25 illustrates a high level flow chart of operations depicting a fluid driven electrical power generating method, which can be implemented in accordance with an alternative embodiment.

DETAILED DESCRIPTION

The particular values and configurations discussed in these non-limiting examples can be varied and are cited merely to illustrate at least one embodiment and are not intended to limit the scope thereof.

“Fan” or “fan blade” are commonly used in association with wind or airflow but as referred to herein should also be interpreted to include the meaning associated with “propeller” or “propeller blades” which are terms commonly used when referring to water flow as a fluid medium.

“Alternator” as used herein should also be interpreted to include “generator” as a means for producing electrical energy.

“Fluid” as used herein should be interpreted to include wind, airflow caused by forward motion of a vehicle, water flow caused by a stream or river, water flow as found within water distribution piping for commercial and private entities, and water flow as caused by the ocean.

FIG. 1 illustrates a block diagram of a wind driven electrical power generating system 100, which can be implemented in accordance with a preferred embodiment. The system 100 can include a tubular housing 110 having a first end 101 and a second end 102 including at least one helical vane 120 formed therein which can cause fluid entering the first end 101 and flowing through the tubular housing to spiral as it approaches a integrated fan rotor assembly 130 mechanically

or electromagnetically connected to an electric alternator **140** located near the second end **102**, wherein electrical power can be generated as the fan **130** turns the electric alternator **140**. A cone **150** can also be provided in front of the fan **130** and/or electrical alternator **140**. The cone **150** can be placed in front of the generator **140** if the generator is placed before and is connected to the fan **130**, or the cone **150** can be placed before the flat center portion of the fan **130**, which are the central structural areas that are generally known to generally support fan blades extending there from. It can be appreciated that the alternator **140** and any electrical wiring **160** associated therewith can be protected within the tubular housing **110** when main components the alternator can be placed before the fan. The electrical power from the electrical generator **140** can be routed via electrical connection **160** for immediate use by a load **180** (e.g., storage and later use in/from batteries, transfer to electric power grids, direct use by electric components) or can first pass through a controller **170** for power management.

Fixed helices **120** formed on surfaces of a tubular housing **110** and within the tubular housing **110** as depicted in FIG. **1** can increase fluid flow as well as creating a spiral laminar air flow, thus avoiding turbulent air flow. Enhanced spiraled flow causes efficient spinning of fan blades **130** at an accelerated speed, thereby increasing rotational speed of a generator **140** installed within the system **100** for optimal power output with minimal velocity or fluid speed conditions external to the system. Fixed helical vanes **120** are ideally designed to achieve the direction of incoming fluid into a spiraled air flow. Fixed helices **120** within the enclosure tube can increase fluid flow as well as creating a spiraled air flow. In application where a cowling is used at the intake, the cowling can create a laminar fluid flow prior to a spiraling effect placed on fluid by the helical vanes **120**. Based on enclosure shape and design, the helical vanes **120** can conform to a concave inner surface of the tubular housing **110** enclosure inner surface while insuring the optimal three-dimensional helix angles. The vanes **120** can direct and increase the spiral rotation and velocity of the fluid, thus more efficiently spinning the fan blade **130** thereby increasing rotational efficiency of any generator used therein for optimal power output.

Referring to FIG. **2**, illustrated is a block diagram of a fluid driven electrical power generating system **200** such as that generally shown in FIG. **1**, but including a cowling **105** that can be located at the first end **101** of the tubular housing **110** for some applications wherein fluid (i.e., wind or ocean current must be captured and managed. The cowling **105** enables the receipt of fluid into the tubular housing **110** and the straightening of fluid into laminar flow as it passes the cowling **105** and enters the tubular housing **110**. The cowling **105** is effective in capturing fluid and taming turbulent fluid flow, which is typically encountered with wind and ocean current.

FIG. **3** illustrates a turbulent flow **330** of wind inside a clear passage tube. Air flow occurs only when there is a difference between pressures. Air will generally flow from a region of high pressure to one of low pressure. Typically, the bigger the pressure difference, the faster the flow. When air flows at higher velocities, especially through an airway with irregular walls, flow is generally disorganized, even chaotic, and tends to form eddies. A relatively large driving pressure is typically required to sustain turbulent flow. Driving pressure during turbulent flow is believed proportional to the square of the flow rate such that to double the flow rate one must quadruple the driving pressure, which is touched on by the following equation:

$$\text{Turbulent flow can be described by Poiseuille's Law:}$$

$$\Delta P = KV^2$$

Where ΔP =Driving force,
K=Constant,
V=Air flow.

FIG. **4** illustrates a laminar flow **340** of a wind inside passage tube. When flow is of a relatively low velocity and passes through narrow tubes, it tends to be more orderly and streamlined and can flow in a straighter path. This type of flow is called laminar flow. Unlike turbulent flow, laminar flow is directly proportional to the driving pressure, such that to double the flow rate, one needs only double the driving pressure, as generally shown by the following equation:

$$\text{Laminar flow can be described by Poiseuille's Law}$$

$$\Delta P = V(8\eta l/\pi r^4)$$

Where ΔP =Difference in pressure between two points,
V=Air flow,
R=Radius of passage tube,
 η =Gas Velocity, and
l=length of the tube.

It has become important in the field of fluid dynamics to control turbulent flow and enable the efficient capture of a fluid. FIG. **5** illustrates a cowling design **350**, **360**, **370**, and various airflow phenomena. The design of the conical inlet (a tube with an aerodynamic fairing around it) or conical air intake in the shape of a cowling as illustrated helps to direct air into housing. When used in the present invention, the inlet is ideally design to draw in as much wind coming toward it as possible to cause favorable power generation by the system **100** as depicted in FIG. **2**, especially when used in combination with at least one fixed helical vane **120** as depicted in FIG. **2** and fan blade assembly **130** as depicted in FIG. **2**.

Referring to FIG. **6**, a view from the first end of the fluid driven electrical power generating system **200** looking into the housing shown outlined **110** past a cowling **105** (or coupling, depending if application is using a cowling with turbulent fluid or a coupling spliced into a water distribution system). Inside of the tubular housing **110** are helical vanes **120** fixed on the inner surface of the housing **110** and spiraling towards a fan **130** and cone **150**, in accordance with features of the present invention.

FIG. **7** illustrates another view of a fluid driven electrical power generating system **300** from the first end of the system, in accordance with features of the present invention. The system **300** includes a cowling **105** located at the first end and also an exhaust **310** located at the second end of the system. The exhaust **310** can be provided in the form of a conical flange.

Referring to FIG. **8**, a side view of an exhaust **310** can be designed at a wider, tapered outward diameter than the air passage tubing **110** in order to allow air flowing through the air passage to easily escape the system around cone **150** and generator **140**, thus also aiding in the removal of heat produced in/by the generator during the production of electrical power.

Referring to FIG. **9**, a side views of a wind power electric generation system **400** is illustrated. The wind power electric generation system **400** includes a cowling **105** at the intake, a conical flange shaped exhaust **310**, and a fin **410** used to orient the front of the system **400**, and cowling **105**, into approaching wind. The wind power electric generation system can be rotatable mounted onto a pole **400**, which can be provided at various lengths depending on the systems application and surrounding environmental conditions.

FIG. **10** illustrates a side view of a wind driven electrical power generating system **400** in FIG. **9** from the first end of the system. In accordance with features of the present invention, the system **400** includes a fin **410** for orienting the

system into oncoming wind. Also shown is the exhaust **310** which can be provided in the form of a conical flange.

FIG. **11** illustrates a side view for a schematic diagram of a fluid driven electrical power generating system **600**, which can be installed for use with water distribution lines **210**, in accordance with features of the present invention. The system shown in FIG. **1** can be used herein with the addition of couplings **115** at the first end **101** and second end **102** of the housing **110** to connect the system **600** in line with water distribution lines **210** as part of a water distribution system, such as a public water utilities.

Referring to FIG. **12**, fluid driven electrical power generating systems **100** are shown installed underground level **100** as part of a water distribution system. Couplings **115** located at each end of the system **100** are used to connect them in line with piping **210** for water distribution systems. Piping **210** is typically tapped by smaller water pipes **1220** for delivery through meters (not shown) to residences or business. This same water distribution system is a source of energy that remains largely untapped for electrical power and can easily be tapped for delivery of electricity to electrical distribution system **1210** associated with homes as shown in FIG. **12**, or for distribution of electricity into public electrical utility lines **1230** by municipalities, also shown in FIG. **12**. With such a system, municipalities can generate additional revenue using water distribution systems deployed or planned for deployment underneath and throughout a city.

FIG. **13** illustrates a side view for a schematic diagram of a fluid driven electrical power generating system **800**, which can be placed within a natural stream or river for use to generate electrical power for use remotely (e.g., when camping), in accordance with features of the present invention. The fluid driven electrical power generating system **800** shown in FIG. **13** is meant to be portable for easy deployment within the field. The housing **210** can include a cowling **105** at its fluid intake and an electrical alternator at its exhaust. The alternator shown in FIG. **13** can be a slotless integrated fan alternator described in more detail below in FIGS. **21-23**. Although other alternators/generators can be used, a slotless integrated fan alternator can be more efficient as the outer circumference of the fan includes magnets that cause electromagnetic energy to be experienced by wiring formed around a core that can be fixed to the housing of the system **800** or outside of the tubular housing. The housing can be made of various materials including plastic, stainless steel, and aluminum. It can be appreciated that the housing can also be designed to be collapsible, thereby providing additional portability.

The system shown in FIG. **13** can be used for field application such as camping, military, humanitarian relief, and other remote electrical power generation needs. Referring to FIG. **14**, an example scenario is illustrated wherein a camp **1240** inserts a fluid driven electric power generating system **800** within a stream **850** and tethers a line **860** to the ground near the stream with a tether post **870**. The line **860** serves a dual purpose of securing the system **800** as well as delivering electrical power generated by the system **800** into the camp **1240**. It can be appreciated that the system **800** can be used for fixed residences (e.g., cabins) located near a stream. The system **800** can be scaled in size to accommodate mobile applications (e.g., hiking, camping, military) or residential/commercial needs.

FIG. **15** illustrates a side view for a schematic diagram of a bi-directional fluid driven electrical power generating system **900**, which can be placed within the ocean along a coastline for use to generate electrical power, in accordance with features of the present invention. The bi-directional fluid driven

electrical power generating system **900** shown in FIG. **15** can enable fluid to flow into the housing in either direction from both ends **901/902**. The alternator **945** is shown located in the middle of the tubular housing **910**. Cowlings **905** located at each end enhance capture of fluid from ocean currents located beneath the ocean's surface. At least one helix **920** located within/on the inner housing surface causes fluid to spiral in either direction flow.

As shown in FIG. **16**, the alternator system **940** can include two alternators can be placed at both sides of a fan blade assembly **930**. Each alternator can include a cone **950** installed at the alternator's surface. The alternators and fan blade assembly can be suspended for balanced in line rotation within the housing by brackets **940**.

As shown in FIG. **17**, the alternator system **940** can include a slotless integrated fan alternator described in more detail below in FIGS. **21-23**. A slotless integrated fan alternator when used within the bi-directional fluid driven electric power generation system **900** can simplify the system. Only one fan blade assembly **930** with magnets **930** mounted on its perimeter is required to cause electromagnetic influence on fixed coils **945** integrated with the housing **910**. Two cones **950** can be disposed at each side of the fan blade assembly **930** to direct fluid flow through fan blades and create venture pressure. The fan blade assembly can be mounted for balanced rotation within the housing brackets **980**. Although other alternators/generators can be used, a slotless integrated fan alternator can be more efficient as the outer circumference of the fan includes magnets that cause electromagnetic energy to be experienced by wiring formed around a core that can be fixed to the housing of the bi-directional system **900** or outside of the tubular housing.

The system shown in FIG. **15** can be used for electrical power generation along ocean coastlines. Referring to FIG. **18**, an example scenario is illustrated wherein several bi-directional systems **900** are electrically connected to each other **990** and tethered beneath the ocean's surface within optimum ocean flow in and away from the coast by anchors **595**. Electrical wiring **960** can be carried to end use **1210/1230** via junction boxes **985** located underwater and underground **975** at shore. It can be appreciated that wiring used to electrical connect the bi-directional systems to each other can also serve as support lines.

Some manufacturers are proposing use of a small electric motor that is squeezed between the engine and transmission, replacing the conventional alternator and starter motor. While waiting at a stop light, the truck's internal combustion engine shuts off, then turns on and takes off smoothly with a slight assist from the electric motor when the driver needs to accelerate. An added bonus: the system provides 110-volt outlets on board for power tools or other uses. Some refer to this system as a "start-stop" hybrid, General Motors calls it a "parallel" hybrid, and the auto industry says this, too, is a mild hybrid.

Vehicles that combine two or more sources of power will typically be referred to as a hybrid vehicle (HV). According to the U.S. Department of Energy, hybrid electric vehicles (HEVs) are vehicles that combine an internal combustion engine (ICE) and a battery with an electric motor. Automobile manufacturers such as Toyota®, Honda® and Ford® sell such vehicles. Newer companies are now proposing all electric motor vehicles, such as that proposed by Tesla Motors of San Carlos, Calif.

A parallel system, such as that found in the Ford Escape® Hybrid SUV and Toyota Prius® sedan, can be powered by the gas engine only, the electric motor only, or both at the same time. Honda's two-seat Insight and Honda Civic® sedan

11

incorporate a series-type hybrid, where the electric motor assists the internal combustion engine when needed, such as during acceleration or times of heavy load, but doesn't power the car on its own.

The wind power generator design of the present system lends itself to more efficient power generation for Hybrid or all electric vehicles by incorporating the design of the cowling 105 (a tube with an aerodynamic fairing around it) or conical air intake to help direct air flow encountered at the front of a moving vehicle during the vehicle's forward movement into the electric power generating chamber. The cowling inlet 105 when incorporated into a vehicle is design to draw in as much wind coming toward it as possible to cause favorable power generation by the system as a result of fixed helix 120 and fan blade assembly 130 interaction with air flow through the tubular 110 at the front grill or in the fairing of a hybrid or all electric vehicle. A moving vehicle would therefore be generating electricity while it is in motion; the electricity charging or storing power with the vehicle's batteries.

Referring to FIG. 19, a mobile application 1260 is illustrated. An automobile 1265 includes a fluid driven electrical power generator 200 therein for the mobile application. As shown in FIG. 19, a fluid driven electrical power generator 200 can be installed at the front of an electrical or hybrid vehicle 1265 where air flow is generated when the vehicle 1265 is in forward motion (e.g. along a highway). Air flowing through the system can be exhausted 1262 at various location from the vehicle. Electrical power generated by the system 200 can be used to charge batteries 1263 located in the vehicle.

Other vehicles that can incorporate the electric power generating system of the invention include water vessels, trains, and aircraft. All vehicles encounter some force caused by air at the front of the vehicle, regardless of the vehicle's aerodynamic design. This force is typically viewed as drag on a vehicle's efficiency, and is often used to determine a vehicles drag co-efficient. There is no escaping the phenomena of drag on a moving vehicle, but this drag can now be utilized as a source of energy for the purpose of generating electricity for concurrent or future use by the vehicle.

Referring to FIG. 20, another mobile application 1270 is illustrated wherein a side view of a tractor truck 1275 is shown. In this commercial/industrial application, a fluid driven electrical power generator 200 is installed at the front of the tractor truck wherein air flow can be taken into the system 200 and then exhausted 1272 from the system. Electrical power generated by the system 200 can be used to charge batteries 1265 located on the tractor truck 1275. It can also be appreciated that electrical power can be used real-time to provide power to refrigeration units that might be transported with a trailer being hauled by the tractor truck.

In accordance with a feature of the present invention a slotless integrated fan alternator 560 can be provided as the electrical power generating hardware for the invention described herein. Referring to FIGS. 21-23, partial views of an exemplary slotless integrated fan alternator 560 in accordance with an embodiment of the present invention are illustrated. The cutaway views of the alternator shown in FIGS. 21 and 22 include conductor coils 80 formed from a flat conductor material (e.g., copper) emplaced around a laminated or other eddy current reducing material, such as powdered iron, providing a low loss core 78, the core can be comprised of a magnetic flux conducting material, such as steel or other ferrous material. The use of a flat conductor material can maximize the compactness in spacing of the coils 80, while minimizing eddy currents and other negative effects associ-

12

ated with use of round cross-sectional conductor material, such as typical round profile copper wire.

The laminated or otherwise low loss core 78 and emplaced conductor coils 80 can be surrounded by a watertight molded section 53, such as a sealed plastic casing. The winding portion of the alternator 32, which includes the laminated or otherwise low loss core 78, the coils 80, and the molded section 53, can be integrated in or located within or outside the tubular housing 110 (not shown). In the embodiment shown in FIGS. 21-23, the winding portion of the alternator 32 can be divided into three sections 52a, 52b, 52c, although any suitable number of sections (including one) may be used. Advantages of the use of such sections 52a, 52b, 52c include increased ease of repair by allowing disassembly and replacement of only a portion of the winding portion of the alternator 32. In addition, emplacement of the coils 80 about the laminated or otherwise low loss core 78 is simplified, as the coils 80 may be wound separately from the core portions corresponding to the winding portion sections 52a, 52b, 52c, and then slidably or otherwise emplaced about the winding portion sections 52a, 52b, 52c via the ends of the winding portions sections 52a, 52b, 52c. Further, the sections 52a, 52b, 52c may be more easily produced by comprising smaller angle portions of the overall winding portion of the alternator 32. For example, in one embodiment, the laminations and/or other core material are stamped from flat stock, and a greater number of laminations may be most efficiently produced from the flat stock by using one third sections (or smaller) sections of the winding portion of the alternator 32. Likewise, such produced core sections and produced winding portions may more easily be shipped and stored.

The rotating portion of the alternator 96 can include a rotor portion 84 and a magnet portion 82. The rotor portion 84 includes a rim portion 84a, a hub portion 84b, and one or more fan blade shaped spokes 84c for coupling the rim portion 84a to the hub portion 84b. The fan blades 84c are an important aspect of the generator in order to facilitate its use in line within fluid streams passing through a tubular housing. The fan blades can be provided in a cupped formation in order to enhance the capture of fluid, and thereby enhance rotational movement of the rotor portion 82 as fluid passes through the rotor portion 82 and fan blades 84c. The magnet portion 82 includes a plurality of magnetic elements (e.g., individual magnets or magnetized portions of magnetic material) arranged about and attached to the rim portion 84a. For example, the magnetic elements may include a plurality of individual magnets abuttably attached (e.g., such as by an adhesive) to the rim portion 84a, each of the individual magnets being oriented 180 degrees in its polar direction relative to each pair of adjacent individual magnets, such that alternating pairs of adjacent north and south magnet poles are formed, and fields are produced by such magnets, each field having an orientation 180 degrees opposite the field produced by each adjacent magnet. To increase the magnetic flux transmitted via the magnetic elements, such as relative to air, the core 78 is typically includes a magnetic flux conducting material, such as iron, steel, or other ferrous material, and the rim portion 84a of the rotor portion 84 also includes a magnetic flux conducting material, such as iron, steel, or other ferrous material. A cone 95 can be provided and if provided is oriented facing incoming fluid flow within the tubular housing in order to compress and speed up the flow of fluid as it impacts the fan blades 84C. At the backside of the rotor portion 84, opposite the cone 95, an axle and hub assembly (not shown) can be provided to securely orient and mount the rotor portion within the tubular housing 110 and in alignment with the

winding portion **32** of the alternator. Such an assembly, however, is well known in the mechanical art.

A hub associated with the rotor portion **84** can be attached to an axle. The axle can include one or more features such as bearings or bushings, for minimally frictionally engaging a mounting, such as an opening in an alternator housing. In operation, the magnet portion **82** is thus able to rotatably move via the rotor portion **84** and the driven axle **95** relative to the fixably maintained winding portion as fluid passes over and through the fan blades **84C**. In wet applications, it is preferred that the hub, bearing and bushings section of the rotor be sealed.

The coils **80** of the exemplary embodiment shown in FIGS. **21** and **22** are connected so as to form six sets of windings **81a**, **81b**, **81c**, **81d**, **81e**, **81f**, which abut one another and repeat in sequence about the circumference of the laminated or otherwise low loss core **78**. As shown most clearly in FIG. **117**, each of the sets of windings **81a**, **81b**, **81c**, **81d**, **81e**, **81f** is connected to the next corresponding set of windings along the windings portion of the alternator **32** at one end. In one embodiment, successive pairs of each of the sets of windings are connected at opposite ends, such that the each successive coil portion has opposite polarity to the previous connected coil portion. Among other advantages, this approach allows multiple connections and increased redundancy to be obtained, thereby providing the necessary redundancy for the redundant stall control. Assembly may be eased and performance may be improved by ensuring that each of the sets of windings **81a**, **81b**, **81c**, **81d**, **81e**, **81f** are very similar or essentially identical.

FIG. **23** shows a partial diagram of the alternator **32**, which includes the windings portion **53**, the magnet section **82**, and the rim **84a** of the hub. Upon assembly, each of the three winding portion sections **52a**, **52b**, **52c** of the alternator **32** is connected at its ends to the adjacent two sections. Six wire ends (see, e.g., wiring end groups **105**, **106**, as shown in FIG. **22**), one for each of the six sets of windings **80a**, **80b**, **80c**, **80d**, **80e**, **80f**, as shown in FIGS. **21** and **22**, extend from each end of each of the three winding portion sections **53a**, **53b**, and **53c**. Each of the six wire ends extending from each abutting pair of winding portion sections **53a**, **53b**, **53c** is coupled to the six wire ends extending from the adjacent winding portion section. The coupling may occur, for example, via printed circuit boards or other coupling components **97**, **98**, **99**. Each of the laminated or otherwise low loss cores **78** of each of the winding portion sections **52a**, **52b**, **52c** similarly abut one another.

Six continuous windings can be therefore formed by the coupled corresponding windings in each of the winding portion sections **53a**, **53b**, **53c**, shown in FIGS. **21-23**, with a first end of each of the six continuous windings terminating at one of the coupling components **97**, which includes a lead corresponding to each of the first ends of the six continuous windings.

Each of the second ends of the six continuous windings are coupled together via the coupling component **97** and coupled to a seventh lead, such that seven leads **100** extend from the coupling component **97**, the seventh lead corresponding to the center point of the six continuous windings. Alternators generate electricity by the same principle as DC generators, namely, when the magnetic field around a conductor changes, a current is induced in the conductor. Typically, a rotating magnet called the rotor turns within a stationary set of conductors wound in coils on an iron core, called the stator. The field cuts across the conductors, generating an electrical current, as the mechanical input causes the rotor to turn. The rotor magnetic field can be produced by induction (in a

“brushless” alternator), by permanent magnets (in very small machines), or by a rotor winding energized with direct current through slip rings and brushes. The rotor magnetic field may even be provided by a stationary field winding, with moving poles in the rotor.

FIG. **24** illustrates a high level flow chart **1900** of a fluid driven electrical power generation method, which can be implemented in accordance with a preferred embodiment. External fluid is received into a tubular as shown in Block **1910**. As depicted at Block **1920**, fluid within the housing becomes spiraled by fixed helices, formed on the inner surface of the tubular housing. The spiraled fluid flow is then compressed and speeds up by a cone as shown in Block **1930**. Then as shown in Block **1940**, spiraled fluid impinges on fan blades associated with an alternator rotor. Then as shown in Block **1950**, an alternator converts rotational motion of the rotor by fan blades into electrical energy. Then as shown in block **1960**, electrical energy is routed from the alternator to a load.

FIG. **25** illustrates a high level flow chart **2000** of a fluid driven electrical power generation method, which can be implemented in accordance with a preferred embodiment. As shown in Block **2010**, fluid flow is taken into a tubular housing through a conical intake and then converted into a laminar flow. Then as shown at Block **2020**, laminar fluid flow is converted into spiraled fluid flow with fixed helices formed on the internal surface of the tubular housing. Then as shown in block **2030**, spiraled fluid flow is compressed with a cone disposed before fan blades associated with the alternator rotor. The spiraled fluid impinges on the fan blades associated with alternator rotor and creates mechanical energy as shown in block **2040**. The mechanical energy is then converted from the fan rotor into electrical energy by a coil portion of the alternator, as shown in Block **2050**. Then as shown in Block **2060**, electrical energy is routed for immediate use by a load. Finally, as shown in block **2070**, fluid is exhausted from the system.

The wind driven electric power generator of the present invention can be compact and easy to mount. The present system can be designed for harsh climates, built simply and ruggedly to quietly last. The system design can incorporate a cowling as an air intake and internal helical vanes to help direct the amount of air flow into the chamber to capture more wind and produce more energy, especially in low wind speeds which lends itself to more efficient power generation utilizing renewable energy. Various system configurations can be achieved given the present teaching by incorporating the most advanced technology in the industry and providing highly reliable power systems that can integrate state-of-the-art off the shelf micro-processor regulator for more accurate charging, more power, lower startup speed and quieter operation, and small wind turbine generators. For example, a light weight system can be manufactured using an Aluminum cast body and carbon matrix rotor blades. A system can be designed to start up a low wind speed (e.g., starting at 7 mph), run efficiently (e.g., 100 watts at 18 mph, 200 watts at 22 mph, 400 watts at 28), and be resilient to harsh conditions (e.g., designed to govern in high winds and auto-brake one demand or automatically).

Generated electrical power can be routed via electrical connections from the generator for direct storage in and then for later from batteries. Conditioning can be provided to generated power if necessary using conditioning circuits known in the art (e.g., filtering circuits). The size of the present system is scalable to meet delivery requirements.

Temperature of the system may need to be controlled depending on the climate it operates within. For example,

during winter or in colder climates, an internal thermostatically controlled heating device may be incorporated into the system to prevent freezing of the unit's moving parts.

The enclosure tube (i.e., the general housing) can be designed such that its diameter can be calculated to fit the desired electrical output and must be matched with each integral part both internal as well as external. This calculation can also include allowance for creation of a pressure effect between and/or over the generator and its mounting assembly to maximize the affect of the available wind. The enclosure can be made of a tough light weight metal or a composite that will be able to withstand harsh environments while meeting the highest of standards.

Additional features of the system are that the generator can be placed substantially within the housing, which can protect it from external elements, and the fan can be connected to the generator at the end of the system opposite incoming wind with respect to the generator and tubing. A cone can be located at the front of the generator facing incoming air/wind to cause the wind/air to flow directly onto the blades and not encounter a flat edge typically associated with the back of a generator. Pressure caused between the tubing and the cone/generator can be forced onto the generator fan blade assembly and outward where it exits to the rear of the unit. The back of the generator can be fitted with a cone as well to further direct the air on to the cupped fan blade. The rear funnel also plays a critical part as the blade can be placed in such a way to provide additional thrust to the fan blade by the clearance of the blade and funnel.

An electronic starting circuit can be provided in order to facilitate initial starting of the generator from periods when the generator is idle (e.g., no rotation due to lack of wind). The electronic starting system can provide an initial release of electrical energy to the windings in the generator to thereby reduce the amount of wind required to spin-up or start rotation of the generator. For example, a capacitor circuit has been coupled into electrical systems such as heating and air conditioning units to provide initial startup. Generators are known to have some resistance under a load. With a large initial starting charge drawn from the circuit, the generator can be spun up to a speed where at the wind can take over and continue rotation of the generator at minimum speeds via the fan blades.

It can also be appreciated that a various alternators can be used as the generator for the present invention. Prior art alternators/generators typically contain slots of steel that hold a number of copper windings, which, in connection with the use of permanent magnets, convert the energy of a passing fluid into electrical output. In the prior art designs, the slots often tend to vibrate when in operation. The vibration can produce unacceptable noise and a cogging torque that prevents the fluid turbine from starting up or interferes with startup in lower fluid speeds, which is typically experience by wind turbines. Additionally, prior art alternators typically have low stall torque and high manufacturing costs. A new alternator design is needed that eliminates unnecessary vibrations, increases the stall torque, and decreases manufacturing costs.

It will be appreciated that variations of the above-disclosed and other features and functions, or alternatives thereof, may be desirably combined into many other different systems or applications. Also that various presently unforeseen or unanticipated alternatives, modifications, variations or improvements therein may be subsequently made by those skilled in the art which are also intended to be encompassed by the following claims.

What is claimed is:

1. A fluid driven electrical power generating system, comprising:

a tubular housing having an inner surface, outer surface, a first end and a second end, the first end adapted to receive incoming fluid and directing it through the tubular housing, and the second end providing an exhaust for fluid to exit from the tubular housing;

an electrical alternator mounted within the tubular housing before the exhaust, the electrical alternator further including fan rotor assembling including fan blades adapted to rotate with the passage of fluid through the housing; and

at least one fixed helical vane formed on the inner surfaces of the tubular housing in a spiral and adapted to cause fluid flowing through the housing to become spiraled for optimum effect on the fan blades.

2. The fluid driven electrical power generating system of claim 1, further comprising a cowling located at the first end and adapted to capture fluid and direct it into a tubular housing, the at least one fixed helical vane further direct the captured fluid into a spiraled air flow and focus the fluid directly onto the fan blades located near an exhaust of the system causing the alternator to generate electrical energy.

3. The fluid driven electrical power generating system of claim 1, further comprising a cone mounted at a front surface of at least one of the alternator and fan facing air passing through the tubular housing, wherein as fluid passes over the cone it is compressed between the cone and housing resulting in increased pressure and velocity of the fluid, thereby increasing rotational speed of the fan blades and alternator as compressed air passes through the fan blades and exits the exhaust.

4. The fluid driven electrical power generating system of claim 1, further comprising a fin mounted to the outer surface of the housing near the second end of the housing, the fin adapted for orienting the first end of the housing and the cowling into oncoming fluid.

5. The fluid driven electrical power generating system of claim 1, further comprising a conical flange formed at the second end of the unit, said conical flange adapted to protect the fan blades and enables fluid to escape from the unit without interruption from fluid moving along the outer surface of the housing.

6. The fluid driven electrical power generating system of claim 4, further comprising a pole whereon the housing is rotatably mounted above ground.

7. The fluid driven electrical power generating system of claim 2, wherein the system can be integrated near the front of a moving vehicle to capture air with the cowling as the vehicle moves forward and enable air to pass through the housing and spin the fan blades thereby generating electrical power from air for a load in the moving vehicle.

8. The fluid driven electrical power generating system of claim 1, wherein said alternator further comprises a slotless winding portion, including windings encompassing a core comprising magnetic flux conducting material; a fan rotor portion having a rim formed on the outer diameter of integrated fan blades, and a plurality of magnetic elements attached to the rim, wherein the rim comprises a magnetic flux conducting material and wherein the slotless winding portion is fixed to the tubular housing and the fan rotor portion is rotatably moveable relative to the slotless winding portion as a fluid passes through the tubular housing and said fan rotor.

9. The device of claim 8, wherein said fluid driven electric power generation system is incorporated as part of a system to

generate electrical power for a load in at least one of: in the front of a mobile vehicle, at the front of a marine vessel, in a stream, in a river, under an ocean surface along a coastline, within a water distribution system, mounted above ground on a pole to capture wind, mounted on a building to capture wind.

10. The device of claim 2, wherein said fluid driven electric power generation system is incorporated as part of a system to generate electrical power for a load in at least one of: in the front of a mobile vehicle, at the front of a marine vessel, in a stream, in a river, under an ocean surface along a coastline, mounted above ground on a pole to capture wind, mounted on a building to capture wind.

11. A fluid driven electrical power generating system, comprising:

a tubular housing having an inner surface, outer surface, a first end and a second end, the first end adapted to receive incoming fluid and directing it through the tubular housing, and the second end providing an exhaust for fluid to exit from the tubular housing;

an electrical alternator mounted within the tubular housing before the exhaust, the electrical alternator further including fan rotor assembling including fan blades adapted to rotate with the passage of fluid through the housing, said alternator further comprising a slotless winding portion, including windings encompassing a core comprising magnetic flux conducting material; a fan rotor portion having a rim formed on the outer diameter of integrated fan blades, and a plurality of magnetic elements attached to the rim, wherein the rim comprises a magnetic flux conducting material and wherein the slotless winding portion is fixed to the tubular housing and the fan rotor portion is rotatably moveable relative to the slotless winding portion as a fluid passes through the tubular housing and said fan rotor; and

at least one fixed helical vane formed on the inner surfaces of the tubular housing in a spiral and adapted to cause fluid flowing through the housing to become spiraled for optimum effect on the fan blades.

12. The device of claim 11, wherein said fluid driven electric power generation system is incorporated as part of a

system to generate electrical power for a load in at least one of: in the front of a mobile vehicle, at the front of a marine vessel, in a stream, in a river, under an ocean surface along a coastline, within a water distribution system, mounted above ground on a pole to capture wind, mounted on a building to capture wind.

13. A fluid driven electrical power generating system, comprising:

a tubular housing having an inner surface, outer surface, a first end and a second end, the first end adapted to receive incoming fluid and directing it through the tubular housing, and the second end providing an exhaust for fluid to exit from the tubular housing;

an electrical alternator mounted within the tubular housing before the exhaust, the electrical alternator further including fan rotor assembling including fan blades adapted to rotate with the passage of fluid through the housing, said alternator further comprising a slotless winding portion, including windings encompassing a core comprising magnetic flux conducting material; a fan rotor portion having a rim formed on the outer diameter of integrated fan blades, and a plurality of magnetic elements attached to the rim, wherein the rim comprises a magnetic flux conducting material and wherein the slotless winding portion is fixed to the tubular housing and the fan rotor portion is rotatably moveable relative to the slotless winding portion as a fluid passes through the tubular housing and said fan rotor; and

at least one fixed helical vane formed on the inner surfaces of the tubular housing in a spiral and adapted to cause fluid flowing through the housing to become spiraled for optimum effect on the fan blades;

wherein said fluid driven electric power generation system is incorporated as part of a system to generate electrical power for a load in at least one of: in the front of a mobile vehicle, at the front of a marine vessel, in a stream, in a river, under an ocean surface along a coastline, within a water distribution system, mounted above ground on a pole to capture wind, mounted on a building to capture wind.

* * * * *